

APPENDIX C: SAR SYSTEM VALIDATION

Per FCC KDB Publication 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

Table C-1
SAR System Validation Summary – 1g

System Validation													
SAR System	Freq. (MHz)	Date	Probe SN	Probe Cal Point		Cond. (σ)	Perm. (εr)	CW VALIDATION			MOD. VALIDATION		
								SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
AM11	750	8/1/2023	7682	750	Head	0.894	43.462	PASS	PASS	PASS	N/A	N/A	N/A
AM3	750	10/2/2023	7782	750	Head	0.875	41.917	PASS	PASS	PASS	N/A	N/A	N/A
AM11	835	8/1/2023	7682	835	Head	0.869	42.805	PASS	PASS	PASS	GMSK	PASS	N/A
AM11	1900	8/1/2023	7682	1900	Head	1.379	40.787	PASS	PASS	PASS	GMSK	PASS	N/A
AM3	3500	10/4/2023	7782	3500	Head	2.772	39.763	PASS	PASS	PASS	TDD	PASS	N/A
AM3	3700	10/4/2023	7782	3700	Head	2.967	39.477	PASS	PASS	PASS	TDD	PASS	N/A
AM3	3900	10/4/2023	7782	3900	Head	3.176	39.187	PASS	PASS	PASS	TDD	PASS	N/A

NOTE: Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to FCC KDB Publication 865664 D01v01r04.

FCC ID: BCGA2899	PART 2 RF EXPOSURE EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Tablet Device		APPENDIX C: Page 1 of 1