**MEASUREMENT REPORT****FCC PART 15.407 / ISD RSS-248 UNII 6GHz OFDMA 802.11a/ax****Applicant Name:**

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

10/14/2024 - 12/12/2025

Test Report Issue Date:

9/24/2026

Test Site/Location:

Element Materials Technology, Morgan Hill, CA, USA

Test Report Serial No.:

1C2410280081-10-R2.BCG

FCC ID:

BCGA3218

IC:

579C-A3218

APPLICANT:

Apple Inc.

Application Type:

Certification

Model/HVIN:

A3218

EUT Type:

Smart Speaker with Display

Frequency Range:

5955 – 7095MHz

Modulation Type:

OFDMA

FCC Classification:

15E 6GHz Low Power Dual Client (6CD)

FCC Rule Part(s):

Part 15 Subpart E (15.407)

ISED Specification:

RSS-248 Issue 3

Test Procedure(s):

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to
C63.10a:2024, KDB 789033 D02 v02r01, KDB 662911 D01 v02r01, KDB
987594 D01 v03r01, KDB 987594 D02 v03, KDB 987594 D03 v03r04
KDB 987594 D04 v03

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 and KDB 789033 D02 v02r01. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



RJ Ortanez
Executive Vice President



FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 1 of 362

V 12.0 03/03/2026

Revision Summary

Revision	Date	Comments	Revised By
-	10/11/2025	Initial Release	WKR007077
R1	1/29/2026	Address comments in sections 2.2, 2.5, 7.2, 7.3, 7.6	WKR007077
R2	9/24/2026	Addressed additional comments in section 7.3	WKR0000010305


FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 2 of 362

V 12.0 03/03/2026


TABLE OF CONTENTS

1.0	INTRODUCTION	5
1.1	Scope.....	5
1.2	Element Materials Technology Test Location	5
1.3	Test Facility / Accreditations.....	5
2.0	PRODUCT INFORMATION	6
2.1	Equipment Description	6
2.2	Device Capabilities.....	6
2.3	Antenna Description.....	10
2.4	Test Support Equipment.....	10
2.5	Test Configuration.....	11
2.6	Software and Firmware	11
2.7	EMI Suppression Device(s)/Modifications.....	11
3.0	DESCRIPTION OF TESTS	12
3.1	Evaluation Procedure.....	12
3.2	AC Line Conducted Emissions	12
3.3	Radiated Emissions.....	13
3.4	Environmental Conditions.....	13
4.0	ANTENNA REQUIREMENTS	14
5.0	MEASUREMENT UNCERTAINTY	15
6.0	TEST EQUIPMENT CALIBRATION DATA.....	16
7.0	TEST RESULTS	17
7.1	Summary.....	17
7.2	26dB & 99% Bandwidth Measurement	19
7.3	Conducted Output Power and Max EIRP Measurement	58
7.4	Maximum Power Spectral Density	80
7.5	In-Band Emissions	153
7.6	Contention Based Protocol	226
7.7	Radiated Spurious Emissions – Above 1GHz.....	249
7.8	Radiated Spurious Emissions – Below 1GHz	345
7.9	AC Line-Conducted Emissions Measurement.....	350
7.10	Proper Power Adjustment, Client Devices Connected to a Standard Power Access Point	356
7.11	Dual Client Test, Demonstration of Proper Power Adjustment based on Associated AP	360
8.0	CONCLUSION.....	362

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 3 of 362



MEASUREMENT REPORT



UNII Band	Channel Bandwidth (MHz)	Mode	Tx Frequency (MHz)	SISO				SDM	
				Antenna 0		Antenna 1		Summed	
				Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)
5	20	802.11ax	5955 - 6415	92.470	19.66	1.710	2.33	172.187	22.36
6		802.11ax	6435 - 6515	70.146	18.46	1.067	0.28	138.038	21.40
7		802.11ax	6535 - 6855	42.267	16.26	0.869	-0.61	79.983	19.03
5	40	802.11ax	5965 - 6405	93.541	19.71	1.710	2.33	181.970	22.60
6		802.11ax	6445 - 6525	67.764	18.31	1.067	0.28	139.316	21.44
7		802.11ax	6545 - 6865	41.400	16.17	0.869	-0.61	82.414	19.16
5	80	802.11ax	5985 - 6385	90.573	19.57	1.710	2.33	176.604	22.47
6		802.11ax	6465	66.374	18.22	1.067	0.28	132.739	21.23
7		802.11ax	6585 - 6825	42.267	16.26	0.869	-0.61	83.368	19.21
5	160	802.11ax	6025 - 6345	66.681	18.24	1.710	2.33	129.718	21.13
6		802.11ax	6505	53.703	17.30	1.067	0.28	107.399	20.31
7		802.11ax	6585 - 6755	28.119	14.49	0.869	-0.61	55.081	17.41

EUT Overview Standard Power

UNII Band	Channel Bandwidth (MHz)	Mode	Tx Frequency (MHz)	SISO				SDM	
				Antenna 0		Antenna 1		Summed	
				Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)	Max. e.i.r.p (mW)	Max. e.i.r.p (dBm)
5	20	802.11ax	5955 - 6415	6.546	8.16	1.710	2.33	6.531	8.15
6		802.11ax	6435 - 6515	6.339	8.02	1.067	0.28	6.653	8.23
7		802.11ax	6535 - 6875	6.622	8.21	0.869	-0.61	6.095	7.85
8		802.11ax	6895 - 7095	4.656	6.68	0.916	-0.38	6.887	8.38
5	40	802.11ax	5965 - 6405	11.376	10.56	1.710	2.33	11.429	10.58
6		802.11ax	6445 - 6525	11.169	10.48	1.067	0.28	12.078	10.82
7		802.11ax	6565 - 6845	11.776	10.71	0.869	-0.61	11.272	10.52
8		802.11ax	6885 - 7085	8.356	9.22	0.916	-0.38	12.218	10.87
5	80	802.11ax	5985 - 6385	23.878	13.78	1.710	2.33	22.909	13.60
6		802.11ax	6465	21.086	13.24	1.067	0.28	23.121	13.64
7		802.11ax	6545 - 6865	22.961	13.61	0.869	-0.61	22.080	13.44
8		802.11ax	6945 - 7025	16.069	12.06	0.916	-0.38	23.714	13.75
5	160	802.11ax	6025 - 6345	41.687	16.20	1.710	2.33	40.087	16.03
6		802.11ax	6505	37.670	15.76	1.067	0.28	39.719	15.99
7		802.11ax	6665 - 6825	28.445	14.54	0.869	-0.61	38.282	15.83
8		802.11ax	6985	14.093	11.49	0.916	-0.38	34.995	15.44

EUT Overview Low Power Indoor

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 4 of 362

V 12.0 03/03/2026

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Materials Technology Test Location

These measurement tests were conducted at the Element Materials Technology facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element Materials Technology located in Morgan Hill, CA 95037, U.S.A.

- Element Materials Technology is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Materials Technology facility is a registered test laboratory with the site description on file with ISED (Wireless Test Lab number 22831) and FCC (Designation Number US1163)
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 5 of 362

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Smart Speaker with Display FCC ID: BCGA3218 and IC: 579C-A3218**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter while operating in the 6GHz band.

Test Device Serial No.: XH6Q69KJ3V, K7WW2X44X0, GG30N0WMHW, WLW7K40V4P, F0THAV000LT000033B

2.2 Device Capabilities

This device contains the following capabilities:

802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII (5GHz and 6GHz), 802.15.4, Bluetooth (1x, EDR, LE1M, LE2M)

The device supports channel bandwidth reduction and does not support channel puncturing.

Standard Power (SP) mode is supported in U-NII Bands 5 and 7 for FCC and U-NII Bands 5, 6 and 7 for ISSED. Lower Power Indoor (LPI) mode is supported in U-NII Bands 5 to 8. Throughout report, data of Standard Power mode is denoted as SP while data of Lower Power Indoor mode is denoted as LPI.

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 6 of 362

Band 5

Ch.	Frequency (MHz)
1	5955
:	:
45	6175
:	:
93	6415

Band 6

Ch.	Frequency (MHz)
97	6435
:	:
105	6475
:	:
113	6515

Band 7

Ch.	Frequency (MHz)
117	6535
:	:
149	6695
:	:
185	6875

Band 8

Ch.	Frequency (MHz)
189	6895
:	:
209	6995
:	:
229	7095

Table 2-1. 802.11a / 802.11ax (20MHz) Frequency / Channel Operations

Band 5

Ch.	Frequency (MHz)
3	5965
:	:
43	6165
:	:
91	6405

Band 6

Ch.	Frequency (MHz)
99	6445
:	:
107	6485
:	:
115	6525

Band 7

Ch.	Frequency (MHz)
123	6565
:	:
155	6725
:	:
179	6845

Band 8

Ch.	Frequency (MHz)
187	6885
:	:
211	7005
:	:
227	7085

Table 2-2. 802.11ax (40MHz BW) Frequency / Channel Operations

Band 5

Ch.	Frequency (MHz)
7	5985
:	:
39	6145
:	:
87	6385

Band 6

Ch.	Frequency (MHz)
103	6465

Band 7

Ch.	Frequency (MHz)
119	6545
:	:
151	6705
:	:
183	6865

Band 8

Ch.	Frequency (MHz)
199	6945
:	:
215	7025

Table 2-3. 802.11ax (80MHz BW) Frequency / Channel Operations

Band 5

Ch.	Frequency (MHz)
15	6025
:	:
47	6185
:	:
79	6345

Band 6

Ch.	Frequency (MHz)
111	6505

Band 7

Ch.	Frequency (MHz)
143	6665
:	:
175	6825

Band 8

Ch.	Frequency (MHz)
207	6985

Table 2-4. 802.11ax (160MHz BW) Frequency / Channel Operations

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 7 of 362

V 12.0 03/03/2026

Notes:

- 6GHz NII operation is possible in 20MHz, 40MHz, 80MHz and 160MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) KDB 789033 D02 v02r01 and ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Measured Duty Cycles							
802.11 Mode / Band		Antenna 0		Antenna 1		SDM	
		Duty Cycle [%]	DCCF [dB]	Duty Cycle [%]	DCCF [dB]	Duty Cycle [%]	DCCF [dB]
6GHz	11ax(RU26) (20MHz)	98.63	0.06	98.63	0.06	98.86	0.05
	11ax(RU242) (20MHz)	98.17	0.08	98.17	0.08	97.95	0.09
	11ax(RU26) (40MHz)	98.63	0.06	98.63	0.06	98.40	0.07
	11ax(RU484) (40MHz)	97.05	0.13	96.83	0.14	96.61	0.15
	11ax(RU26) (80MHz)	98.86	0.05	98.63	0.06	98.40	0.07
	11ax(RU996) (80MHz)	94.62	0.24	94.19	0.26	94.62	0.24
	11ax(RU26) (160MHz)	98.4	0.07	98.63	0.06	98.63	0.06
	11ax(RU996x2) (160MHz)	90.57	0.43	90.57	0.43	90.57	0.43

Table 2-5. Measured Duty Cycles

- The device employs MIMO technology. Below are the possible configurations.

WiFi Configurations		SISO		CDD		SDM		STBC	
		Antenna 0	Antenna 1	Antenna 0	Antenna 1	Antenna 0	Antenna 1	Antenna 0	Antenna 1
6GHz	11ax(RU) (20MHz)	✓	✓	✓	✓	✓	✓	✓	✓
	11ax(RU) (40MHz)	✓	✓	✓	✓	✓	✓	✓	✓
	11ax(RU) (80MHz)	✓	✓	✓	✓	✓	✓	✓	✓
	11ax(RU) (160MHz)	✓	✓	✓	✓	✓	✓	✓	✓

Table 2-6. WIFI Configurations

✓ = Support ; ✗ = NOT Support

SISO = Single Input Single Output

SDM = Spatial Diversity Multiplexing – MIMO function

CDD = Cyclic Delay Diversity - 2Tx Function

STBC = Space-Time Block Coding – 2Tx Function

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 8 of 362

V 12.0 03/03/2026

3. The device supports the following data rates (shown in Mbps):

MCS Index	Spatial Stream	MU-OFDMA (802.11ax)																	
		26-tone RU			52-tone RU			106-tone RU			242-tone RU			484-tone RU			996-tone RU		
HE		0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI
0	1	0.9	0.8	0.8	1.8	1.7	1.5	3.8	3.5	3.2	8.6	8.1	7.3	17.2	16.3	14.6	36	34	30.6
1	1	1.8	1.7	1.5	3.5	3.3	3	7.5	7.1	6.4	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3
2	1	2.6	2.5	2.3	5.3	5	4.5	11.3	10.6	9.6	25.8	24.4	21.9	51.6	48.8	43.9	108.1	102.1	91.9
3	1	3.5	3.3	3	7.1	6.7	6	15	14.2	12.8	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5
4	1	5.3	5	4.5	10.6	10	9	22.5	21.3	19.1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8
5	1	7.1	6.7	6	14.1	13.3	12	30	28.3	25.5	68.8	65	58.5	137.6	130	117	288.2	272.2	245
6	1	7.9	7.5	6.8	15.9	15	13.5	33.8	31.9	28.7	77.4	73.1	65.8	154.9	146.3	131.6	324.3	306.3	275.6
7	1	8.8	8.3	7.5	17.6	16.7	15	37.5	35.4	31.9	86	81.3	73.1	172.1	162.5	146.3	360.3	340.3	306.3
8	1	10.6	10	9	21.2	20	18	45	42.5	38.3	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5
9	1	11.8	11.1	10	23.5	22.2	20	50	47.2	42.5	114.7	108.3	97.5	229.4	216.7	195	480.4	453.7	408.3
10	1	13.2	12.5	11.3	26.5	25	22.5	56.3	53.1	47.8	129	121.9	109.7	258.1	243.8	219.4	540.4	510.4	459.4
11	1	14.7	13.9	12.5	29.4	27.8	25	62.5	59	53.1	143.4	135.4	121.9	286.8	270.8	243.8	600.5	567.1	510.4
0	2	1.8	1.7	1.5	3.5	3.3	3	7.5	7.1	6.4	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3
1	2	3.5	3.3	3	7.1	6.7	6	15	14.2	12.8	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5
2	2	5.3	5	4.5	10.6	10	9	22.5	21.3	19.1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8
3	2	7.1	6.7	6	14.1	13.3	12	30	28.3	25.5	68.8	65	58.5	137.6	130	117	288.2	272.2	245
4	2	10.6	10	9	21.2	20	18	45	42.5	38.3	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5
5	2	14.1	13.3	12	28.2	26.7	24	60	56.7	51	137.6	130	117	275.3	260	234	576.5	544.4	490
6	2	15.9	15	13.5	31.8	30	27	67.5	63.8	57.4	154.9	146.3	131.6	309.7	292.5	263.3	648.5	612.5	551.3
7	2	17.6	16.7	15	35.3	33.3	30	75	70.8	63.8	172.1	162.5	146.3	344.1	325	292.5	720.6	680.6	612.5
8	2	21.2	20	18	42.4	40	36	90	85	76.5	206.5	195	175.5	412.9	390	351	864.7	816.7	735
9	2	23.5	22.2	20	47.1	44.4	40	100	94.4	85	229.4	216.7	195	458.8	433.3	390	960.8	907.4	816.7
10	2	26.5	25	22.5	52.9	50	45	112.5	106.3	95.6	258.1	243.8	219.4	516.2	487.5	438.8	1080.9	1020.8	918.8
11	2	29.4	27.8	25	58.8	55.6	50	125	118.1	106.3	286.8	270.8	243.8	573.5	541.7	487.5	1201	1134.3	1020.8

Table 2-7. Supported Data Rates

4. This device supports simultaneous transmission operations, which allows multiple transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.

Antenna	Simultaneous Tx Config	Bluetooth 2.4GHz	Thread	WLAN	WIFI 5GHz	WIFI 6GHz
		BDR, EDR, LE1/2M	802.15.4	802.11 b/g/n/ax	802.11 a/n/ac/ax	802.11 a/ax
Antenna 0	Config 1	✓	✗	✗	✓	✗
Antenna 1		✗	✓	✗	✓	✗
Antenna 0	Config 2	✓	✗	✗	✗	✓
Antenna 1		✗	✓	✗	✗	✓

Table 2-8. Simultaneous Transmission Configurations

✓ = Support; ✗ = Not Support

Note:

All the above simultaneous transmission configurations have been tested and the worst-case configuration was found to be Config 1 and reported in RF Bluetooth, RF 802.15.4, and RF UNII 5GHz OFDM test reports.

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 9 of 362

2.3 Antenna Description

Following antennas gains provided by manufacturer were used for testing. The validity of the calculated results is based on the accuracy of the information provided.

UNII Band	Tx Frequency (MHz)	Highest Antenna Gain (dBi)		Lowest Antenna Gain (dBi)	
		Antenna 0	Antenna 1	Antenna 0	Antenna 1
5	5955-6095	2.54	1.66	2.25	1.26
	6115-6255	2.71	2.33	1.25	1.57
	6275-6415	0.88	0.68	0.88	0.68
6	6435-6525	1.52	0.28	1.52	0.28
7	6535-6875	-0.24	-0.61	-2.50	-2.21
8	6885-7115	-1.74	-0.38	-1.82	-1.06

Table 2-9. Antenna Gain

2.4 Test Support Equipment

1	Apple MacBook Pro	Model:	A2141	S/N:	C02YVA2VLVDD
	w/AC/DC Adapter	Model:	A2166	S/N:	C4H042705ZNPM0WA6
2	Apple USB-C Cable	Model:	Banana Split	S/N:	200605
3	USB-C Cable	Model:	A246C	S/N:	FTLH3N00N3S000002J
	w/ AC Adapter	Model:	A2305	S/N:	C4HHAU000PD0000EWV
4	Smart Speaker with Display	Model:	A3300	S/N:	GM9R4V7RT2
5	Netgear	Model:	RAXE500	S/N:	6JX215GA10A5

Table 2-10. Test Support Equipment List

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 10 of 362

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024, KDB 789033 D02 v02r01 and KDB 987594 D02 v03. ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power and the worst case channel were reported.

The EUT was manipulated through three tilt angles of 0°, 45°, and 60° of the screen. Additionally, the EUT was also manipulated to rest on its side. Only the worst case emissions were reported in this test report.

For AC line conducted and radiated test below 1GHz, the following configuration was investigated and the worst case was reported.

- EUT powered by AC/DC Adapter via USB-C cable

802.11ax HE20/40/80/160 2TX SDM mode test data provided in this report covers 802.11ax HE20/40/80/160 2TX STBC mode.

For 802.11ax-SU test results, see separate UNII 6E OFDM report, 1C2410280081-09.BCG.

2.6 Software and Firmware

The test was conducted with firmware version 22w173 installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 11 of 362

V 12.0 03/03/2026

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024) and the guidance provided in KDB 789033 D02 v02r01 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14kHz - 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.9. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.50.40.

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 12 of 362

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

Per KDB 414788, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was used while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 13 of 362

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 14 of 362

V 12.0 03/03/2026

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	2.07
Line Conducted Disturbance	1.91
Radiated Disturbance (<30MHz)	4.12
Radiated Disturbance (30MHz - 1GHz)	4.85
Radiated Disturbance (1 - 18GHz)	5.08
Radiated Disturbance (>18GHz)	5.22

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 15 of 362

V 12.0 03/03/2026

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance with the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Anritsu	ML2495A	Power Meter	7/8/2024	Annual	7/8/2025	1039008
Anritsu	MA2411B	Pulse Power Sensor	7/1/2024	Annual	7/1/2025	1911105
Anritsu	MA2411B	Pulse Power Sensor	10/21/2024	Annual	10/21/2025	1027293
ATM	180-442A-KF	20dB Nominal Gain Horn Antenna	3/14/2024	Annual	3/14/2025	T058701-01
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	4/9/2024	Annual	4/9/2025	00218555
Fairview Microwave/MCL	FMCA1975-36/BW-K10-2W44+	30MHz-40GHz RF Cable/Attenuator *	6/10/2024	Annual	6/10/2025	-
Keysight Technology	N9040B	UXA Signal Analyzer	5/28/2024	Annual	5/28/2025	MY57212015
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	3/1/2024	Annual	3/1/2025	102145
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	8/14/2024	Annual	8/14/2025	101648
Rohde & Schwarz	FSV40	Signal Analyzer (10Hz-40GHz)	5/29/2024	Annual	5/29/2025	101619
Rohde & Schwarz	ESW44	EMI Test Receiver	5/1/2024	Annual	5/1/2025	101867
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	7/3/2024	Annual	7/3/2025	102356
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	6/10/2024	Annual	6/10/2025	100057
Rohde & Schwarz	ENV216	Two-Line V-Network	4/24/2024	Annual	4/24/2025	101364
Rohde & Schwarz	SMW200A	Vector Signal Generator	4/4/2024	Annual	4/4/2025	109456
Schwarzbeck	VULB 9162	Bilog Antenna (30MHz - 6GHz)	4/29/2024	Annual	4/29/2025	00304

Table 6-1. Test Equipment List (2024 to 2025)

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Anritsu	ML2496A	Power Meter	6/27/2025	Annual	6/27/2026	1840005
Anritsu	MA2411B	Pulse Power Sensor	6/27/2025	Annual	6/27/2026	1911105
Anritsu	MA2411B	Pulse Power Sensor	7/3/2025	Annual	7/3/2026	1726261
ATM	180-442-KF	20dB Nominal Gain Horn Antenna	3/24/2025	Annual	3/24/2026	T058601-02
ETS-Lindgren	3117	Double Ridged Guide Horn (1-18 GHz)	4/16/2025	Annual	4/16/2026	218555
Fairview Microwave/MCL	FMCA1975-36/BW-K10-2W44+	30MHz-40GHz RF Cable/Attenuator *	6/10/2025	Annual	6/10/2026	-
Fairview Microwave	FM2CP1122-10	Directional Coupler *	6/10/2025	Annual	6/10/2026	1946
Keysight Technology	N9040B	UXA Signal Analyzer	9/8/2025	Annual	9/8/2026	MY61320121
Keysight Technology	N9030A	PXA Signal Analyzer	9/15/2025	Annual	9/15/2026	MY49430494
Mini-Circuits	ZN2PD-9G	Power Splitter*	9/16/2025	Annual	9/16/2026	SF456200530
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	8/6/2025	Annual	8/6/2026	101639
Rohde & Schwarz	FSW43	Spectrum Analyzer 2Hz to 43GHz	8/5/2025	Annual	8/5/2026	104093
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	5/13/2025	Annual	5/13/2026	101867
Rohde & Schwarz	SMW200A	Vector Signal Generator	3/10/2025	Annual	3/10/2026	110589
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	10/14/2025	Annual	10/14/2026	102328
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	6/3/2025	Annual	6/3/2026	100052
Rohde & Schwarz	HFH2-Z2	Loop Antenna	5/12/2025	Annual	5/12/2026	100546
Rohde & Schwarz	ENV216	Two-Line V-Network	4/24/2025	Annual	4/24/2026	101364
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	3/4/2025	Annual	3/4/2026	164715
Rohde & Schwarz	CMX500	Wideband Radio Communication Tester	11/11/2024	Annual	11/11/2025	100298
Schwarzbeck	VULB 9162	Bilog Antenna (30MHz - 6GHz)	10/8/2025	Annual	10/8/2026	00358

Table 6-2. Test Equipment List (2025 to 2026)

Note:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- * denotes passive equipment that have been internally verified/calibrated.

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 16 of 362

7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.
 FCC ID: BCGA3218
 IC: 579C-A3218
 FCC Classification: 15E 6GHz Low Power Dual Client (6CD)

FCC Part Section(s) / KDB Reference	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049, 15.407(a)(11)	RSS Gen [5.1], RSS-248 [4.4]	Occupied Bandwidth/ 26dB Bandwidth	99% of the occupied bandwidth of any channel must be contained within each of its respective U-NII sub bands < 320MHz (5.925 - 7.125GHz)	CONDUCTED	PASS	Section 7.2
15.407(a)(8)	RSS-248 [4.5.3]	Maximum Power Spectral Density	< -1dBm/MHz e.i.r.p. for Low Power Indoor		PASS	Section 7.4
15.407(a)(7)	RSS-248 [4.5.5]		< 17dBm/MHz e.i.r.p. for Standard Power		PASS	
15.407(a)(8)	RSS-248 [4.5.3]	Maximum EIRP	< 24dBm over the frequency band of operation		PASS	Section 7.3
15.407(a)(7)	RSS-248 [4.5.5]		< 30dBm over the frequency band of operation		PASS	
15.407(b)(7)	RSS-248 [4.6.2]	In-Band Emissions	EUT must meet the limits detailed in 15.407(b)(7) and RSS-248 [4.6.2] b)		PASS	Section 7.5
15.407(d)(6)	RSS-248 [4.7]	Contention Based Protocol	EUT must detect AWGN signal with 90% (or better) certainty		PASS	Section 7.6
15.407(a)(7)	RSS-248 [4.5.5]	Proper Power Adjustment, Client Devices Connected to a Standard Power Access Point	EUT maintains its power level at least 6 dB lower than that of the standard-power access point		PASS	Section 7.10
987594 D02 v03	987594 D02 v03	Dual Client Test, Demonstration of Proper Power Adjustment based on Associated AP	EUT maximum power level shall not exceed 30dBm EIRP when connected to Standard Power AP, and 24dBm EIRP when connected to Low Power Indoor AP		PASS	Section 7.11
15.407(b)(6)	RSS-248 [4.6.2]	Undesirable Emissions	< -27dBm/MHz e.i.r.p. outside of the 5.925 – 7.125GHz band	RADIATED	PASS	Section 7.7
15.205, 15.209	RSS-248 [4.6.2] RSS-Gen [7.4.3]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [7.4.3])		PASS	Section 7.7, 7.8
15.407(b)(9)	RSS-Gen [7.4.2]	AC Conducted Emissions (150kHz – 30MHz)	< FCC 15.207 (RSS-Gen [7.4.2]) limits	LINE CONDUCTED	PASS	Section 7.9

Table 7-1. Summary of Test Results

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 17 of 362

V 12.0 03/03/2026

Notes:

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Conducted Automation," Version 1.1.1.
- 5) For radiated testing, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 3.1.0.
- 6) All radiated measurements were tested at the highest supported power setting per band.
- 7) 802.11ax OFDMA testing was performed for all signal tone configurations as specified by the 802.11be standard. Worst case results are determined and reported per the guidance provided at the October 2022 TCB Workshop.

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 18 of 362

V 12.0 03/03/2026

7.2 26dB & 99% Bandwidth Measurement

Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 and KDB 789033 D02 v02r01, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

Test Procedure Used

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 – Section 12.5.2
KDB 789033 D02 v02r01 – Section C

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 26$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = in the range of 1% to 5% of the emission bandwidth
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

1. All antenna configurations were investigated and only the worst case is reported.
2. All RU's were investigated and only worst case partially-loaded and fully-loaded RU's were reported.
3. Low, mid, and high channels were tested and tabular data has been reported. Only worst case plots per bandwidth have been reported.

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 19 of 362

7.2.1 Antenna 0 26dB & 99% Bandwidth Measurements – SP

	Frequency [MHz]	Channel	802.11 MODE	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.33	20.05	320	Pass
	5955	1	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.88	18.07	320	Pass
	5955	1	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.38	19.98	320	Pass
	6175	45	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.44	20.04	320	Pass
	6175	45	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.98	17.99	320	Pass
	6175	45	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.40	20.11	320	Pass
	6415	93	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.42	20.15	320	Pass
	6415	93	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.93	18.11	320	Pass
	6415	93	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.40	20.12	320	Pass
	5965	3	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.68	18.87	320	Pass
	5965	3	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.62	21.33	320	Pass
	5965	3	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.72	18.91	320	Pass
	6165	43	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.59	18.84	320	Pass
	6165	43	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.41	21.44	320	Pass
	6165	43	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.62	18.90	320	Pass
	6165	91	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.64	18.90	320	Pass
	6165	91	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.46	21.91	320	Pass
	6165	91	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.65	18.90	320	Pass
	5985	7	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.92	19.16	320	Pass
	5985	7	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.52	38.91	320	Pass
	5985	7	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.88	19.20	320	Pass
	6145	39	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.91	19.32	320	Pass
	6145	39	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.55	38.83	320	Pass
	6145	39	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.72	19.22	320	Pass
	6385	87	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.04	19.40	320	Pass
	6385	87	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.28	38.47	320	Pass
	6385	87	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.76	19.01	320	Pass
	6025	15	ax (160MHz)	26	0	12.5/14.7 (MCS11)	17.90	19.19	320	Pass
	6025	15	ax (160MHz)	26	18	12.5/14.7 (MCS11)	20.20	22.17	320	Pass
	6025	15	ax (160MHz)	26	36	12.5/14.7 (MCS11)	17.53	19.40	320	Pass
	6181	47	ax (160MHz)	26	0	12.5/14.7 (MCS11)	17.95	19.20	320	Pass
	6181	47	ax (160MHz)	26	18	12.5/14.7 (MCS11)	20.93	22.86	320	Pass
	6181	47	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.07	19.45	320	Pass
	6345	79	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.08	19.38	320	Pass
	6345	79	ax (160MHz)	26	18	12.5/14.7 (MCS11)	20.12	21.87	320	Pass
	6345	79	ax (160MHz)	26	36	12.5/14.7 (MCS11)	17.93	19.45	320	Pass
Band 6	6345	97	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.31	19.99	320	Pass
	6345	97	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.87	18.02	320	Pass
	6345	97	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.47	20.09	320	Pass
	6475	105	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.35	19.97	320	Pass
	6475	105	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.84	18.08	320	Pass
	6475	105	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.44	20.22	320	Pass
	6515	113	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.40	19.98	320	Pass
	6515	113	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.91	18.08	320	Pass
	6515	113	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.47	20.32	320	Pass
	6445	99	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.50	18.84	320	Pass
	6445	99	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.65	21.89	320	Pass
	6445	99	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.60	18.84	320	Pass
	6485	107	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.63	18.80	320	Pass
	6485	107	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.44	21.06	320	Pass
	6485	107	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.58	18.96	320	Pass
	6525	115	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.62	18.81	320	Pass
	6525	115	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.76	21.47	320	Pass
	6525	115	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.65	18.86	320	Pass
	6465	103	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.96	19.38	320	Pass
	6465	103	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.62	38.53	320	Pass
Band 7	6465	103	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.90	19.28	320	Pass
	6505	111	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.14	19.47	320	Pass
	6505	111	ax (160MHz)	26	18	12.5/14.7 (MCS11)	36.19	38.53	320	Pass
	6505	111	ax (160MHz)	26	36	12.5/14.7 (MCS11)	20.07	21.94	320	Pass
	6535	117	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.46	19.95	320	Pass
	6535	117	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.61	17.95	320	Pass
	6535	117	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.39	20.31	320	Pass
	6695	149	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.31	19.93	320	Pass
	6695	149	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.95	18.13	320	Pass
	6695	149	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.35	20.28	320	Pass
	6875	181	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.38	20.14	320	Pass
	6875	181	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.91	18.12	320	Pass
	6875	181	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.52	20.49	320	Pass
	6565	123	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.56	18.87	320	Pass
	6565	123	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.53	21.08	320	Pass
	6565	123	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.62	18.88	320	Pass
	6725	155	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.39	18.76	320	Pass
	6725	155	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.60	21.60	320	Pass
	6725	155	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.60	18.86	320	Pass
	6845	179	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.62	18.79	320	Pass
	6845	179	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.56	21.21	320	Pass
	6845	179	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.64	18.90	320	Pass
	6545	135	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.91	19.31	320	Pass
	6545	135	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.37	38.34	320	Pass
	6545	135	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.94	19.16	320	Pass
	6705	151	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.99	19.39	320	Pass
	6705	151	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.56	38.53	320	Pass
	6705	151	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.89	19.13	320	Pass
	6865	167	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.99	19.39	320	Pass
	6865	167	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.09	38.32	320	Pass
	6865	167	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.89	19.11	320	Pass
	6665	143	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.07	19.43	320	Pass
	6665	143	ax (160MHz)	26	18	12.5/14.7 (MCS11)	20.77	22.64	320	Pass
	6665	143	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.21	19.55	320	Pass

Table 7-2. Conducted Bandwidth Measurements Antenna 0 (RU26)


FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 20 of 362

	Frequency [MHz]	Channel	802.11 MODE	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.12	22.54	320	Pass
	6175	45	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.12	22.27	320	Pass
	6415	93	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.13	22.61	320	Pass
	5965	3	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.93	39.91	320	Pass
	6165	43	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.91	39.97	320	Pass
	6165	91	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.91	39.87	320	Pass
	5985	7	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.56	80.80	320	Pass
	6145	39	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.59	80.65	320	Pass
	6385	87	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.54	80.71	320	Pass
	6025	15	ax (160MHz)	996	68	1020.8/1201 (MCS11)	156.93	162.42	320	Pass
Band 6	6181	47	ax (160MHz)	996	68	1020.8/1201 (MCS11)	156.80	162.56	320	Pass
	6345	79	ax (160MHz)	996	68	1020.8/1201 (MCS11)	157.03	163.36	320	Pass
	6345	97	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.12	22.60	320	Pass
	6475	105	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.16	22.32	320	Pass
	6515	113	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.12	22.66	320	Pass
	6445	99	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.93	39.89	320	Pass
	6485	107	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.92	39.99	320	Pass
	6525	115	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.92	39.91	320	Pass
	6465	103	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.64	80.65	320	Pass
	6505	111	ax (160MHz)	996	68	1020.8/1201 (MCS11)	157.05	162.71	320	Pass
Band 7	6535	117	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.13	22.31	320	Pass
	6695	149	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.13	22.55	320	Pass
	6875	181	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.11	22.70	320	Pass
	6565	123	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.92	39.95	320	Pass
	6725	155	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.91	39.94	320	Pass
	6845	179	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.92	39.87	320	Pass
	6545	135	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.48	80.79	320	Pass
	6705	151	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.55	80.81	320	Pass
	6865	167	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.58	80.76	320	Pass
	6665	143	ax (160MHz)	996	68	1020.8/1201 (MCS11)	156.80	162.91	320	Pass


Table 7-2. Conducted Bandwidth Measurements Antenna 0 (Fully – Loaded RU)

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 21 of 362


V 12.0 03/03/2026




Plot 7-1. 26dB & 99% Bandwidth Plot Antenna 0 (20MHz 802.11ax RU26 (UNII Band 5) – Ch. 45)



Plot 7-3. 26dB & 99% Bandwidth Plot Antenna 0 (80MHz 802.11ax RU26 (UNII Band 5) – Ch. 39)






Plot 7-2. 26dB & 99% Bandwidth Plot Antenna 0 (40MHz 802.11ax RU26 (UNII Band 5) – Ch. 3)




Plot 7-4. 26dB & 99% Bandwidth Plot Antenna 0 (160MHz 802.11ax RU26 (UNII Band 5) – Ch. 47)


FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C24102800810-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 22 of 362




FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C24102800810-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 23 of 362




Plot 7-9. 26dB & 99% Bandwidth Plot Antenna 0 (20MHz 802.11ax RU26 (UNII Band 6) – Ch. 97)



Plot 7-11. 26dB & 99% Bandwidth Plot Antenna 0 (80MHz 802.11ax RU26 (UNII Band 6) – Ch. 103)



Plot 7-10. 26dB & 99% Bandwidth Plot Antenna 0 (40MHz 802.11ax RU26 (UNII Band 6) – Ch. 115)






Plot 7-12. 26dB & 99% Bandwidth Plot Antenna 0 (160MHz 802.11ax RU26 (UNII Band 6) – Ch. 111)




FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C24102800810-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 24 of 362

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com




FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C24102800810-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 25 of 362




FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C24102800810-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 26 of 362




Plot 7-21. 26dB & 99% Bandwidth Plot Antenna 0 (20MHz 802.11ax RU242 (UNII Band 7) – Ch. 149)



Plot 7-23. 26dB & 99% Bandwidth Plot Antenna 0 (80MHz 802.11ax RU996 (UNII Band 7) – Ch. 167)



Plot 7-22. 26dB & 99% Bandwidth Plot Antenna 0 (40MHz 802.11ax RU484 (UNII Band 7) – Ch. 179)



Plot 7-24. 26dB & 99% Bandwidth Plot Antenna 0 (160MHz 802.11ax RU996x2 (UNII Band 7) – Ch. 143)

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C24102800810-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 27 of 362

7.2.2 Antenna 0 26dB & 99% Bandwidth Measurements – LPI

	Frequency [MHz]	Channel	802.11 MODE	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.33	20.05	320	Pass
	5955	1	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.88	18.07	320	Pass
	5955	1	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.35	20.25	320	Pass
	6175	45	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.40	20.20	320	Pass
	6175	45	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.87	18.04	320	Pass
	6175	45	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.47	19.98	320	Pass
	6415	93	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.44	20.15	320	Pass
	6415	93	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.87	17.96	320	Pass
	6415	93	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.29	19.99	320	Pass
	5965	3	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.71	18.84	320	Pass
	5965	3	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.76	22.06	320	Pass
	5965	3	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.66	18.93	320	Pass
	6165	43	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.69	18.86	320	Pass
	6165	43	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.80	21.29	320	Pass
	6165	43	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.70	18.99	320	Pass
	6165	91	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.50	18.81	320	Pass
	6165	91	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.68	21.89	320	Pass
	6165	91	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.67	18.90	320	Pass
	5985	7	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.03	19.51	320	Pass
	5985	7	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.41	38.47	320	Pass
	5985	7	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.93	19.07	320	Pass
	6145	39	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.92	19.13	320	Pass
	6145	39	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.61	39.11	320	Pass
	6145	39	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.95	19.20	320	Pass
	6385	87	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.84	19.39	320	Pass
	6385	87	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.32	38.49	320	Pass
	6385	87	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.81	19.10	320	Pass
	6025	15	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.18	19.44	320	Pass
	6025	15	ax (160MHz)	26	18	12.5/14.7 (MCS11)	20.57	22.03	320	Pass
	6025	15	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.00	19.29	320	Pass
	6185	47	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.15	19.54	320	Pass
	6185	47	ax (160MHz)	26	18	12.5/14.7 (MCS11)	21.10	22.83	320	Pass
	6185	47	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.15	19.64	320	Pass
	6345	79	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.16	19.55	320	Pass
	6345	79	ax (160MHz)	26	18	12.5/14.7 (MCS11)	19.44	21.59	320	Pass
	6345	79	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.10	19.45	320	Pass
Band 6	6345	97	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.44	19.97	320	Pass
	6345	97	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.87	18.14	320	Pass
	6345	97	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.36	20.13	320	Pass
	6475	105	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.40	19.95	320	Pass
	6475	105	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.99	18.06	320	Pass
	6475	105	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.37	20.25	320	Pass
	6515	113	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.43	20.03	320	Pass
	6515	113	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.92	18.06	320	Pass
	6515	113	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.44	20.15	320	Pass
	6445	99	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.68	18.88	320	Pass
	6445	99	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.84	21.59	320	Pass
	6445	99	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.61	18.93	320	Pass
	6485	107	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.60	18.84	320	Pass
	6485	107	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.76	21.34	320	Pass
	6485	107	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.53	18.77	320	Pass
	6525	115	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.69	18.88	320	Pass
	6525	115	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.57	21.60	320	Pass
	6525	115	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.60	18.89	320	Pass
	6465	103	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.96	19.23	320	Pass
	6465	103	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.69	38.67	320	Pass
	6465	103	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.86	19.26	320	Pass
	6505	111	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.12	19.31	320	Pass
	6505	111	ax (160MHz)	26	18	12.5/14.7 (MCS11)	29.30	30.61	320	Pass
	6505	111	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.08	19.15	320	Pass

Table 7-3. Conducted Bandwidth Measurements Antenna 0 (RU26)

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 28 of 362

	Frequency [MHz]	Channel	802.11 MODE	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 7	6535	117	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.38	19.87	320	Pass
	6535	117	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.85	18.06	320	Pass
	6535	117	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.42	20.18	320	Pass
	6695	149	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.30	19.89	320	Pass
	6695	149	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.87	18.08	320	Pass
	6695	149	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.47	20.51	320	Pass
	6875	185	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.38	19.80	320	Pass
	6875	185	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.97	18.11	320	Pass
	6875	185	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.46	20.04	320	Pass
	6565	123	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.74	18.78	320	Pass
	6565	123	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.68	22.00	320	Pass
	6565	123	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.67	18.98	320	Pass
	6725	155	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.72	18.89	320	Pass
	6725	155	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.58	22.06	320	Pass
	6725	155	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.58	18.84	320	Pass
	6845	179	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.63	18.94	320	Pass
	6845	179	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.68	21.92	320	Pass
	6845	179	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.60	18.86	320	Pass
	6545	119	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.92	19.34	320	Pass
	6545	119	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.47	38.76	320	Pass
	6545	119	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.86	19.11	320	Pass
	6705	151	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.00	19.35	320	Pass
	6705	151	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.51	38.49	320	Pass
	6705	151	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.84	19.11	320	Pass
	6865	183	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.06	19.41	320	Pass
	6865	183	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.57	38.88	320	Pass
	6865	183	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.92	19.11	320	Pass
	6665	143 (L)	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.05	19.19	320	Pass
	6665	143 (L)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	20.45	22.54	320	Pass
	6665	143 (U)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.17	19.62	320	Pass
	6825	175 (L)	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.21	19.70	320	Pass
	6825	175 (L)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	20.57	22.11	320	Pass
	6825	175 (U)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.12	19.55	320	Pass
Band 8	6895	189	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.38	20.03	320	Pass
	6895	189	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.93	18.16	320	Pass
	6895	189	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.41	20.37	320	Pass
	6995	209	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.40	20.09	320	Pass
	6995	209	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.89	18.04	320	Pass
	6995	209	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.44	20.34	320	Pass
	7095	229	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.50	20.13	320	Pass
	7095	229	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.87	17.99	320	Pass
	7095	229	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.43	19.90	320	Pass
	6885	187	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.68	18.81	320	Pass
	6885	187	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.69	21.95	320	Pass
	6885	187	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.56	18.94	320	Pass
	7005	211	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.69	18.83	320	Pass
	7005	211	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.63	21.82	320	Pass
	7005	211	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.62	18.98	320	Pass
	7085	227	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.63	18.92	320	Pass
	7085	227	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.72	21.89	320	Pass
	7085	227	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.68	19.00	320	Pass
	6945	199	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.86	19.06	320	Pass
	6945	199	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.56	38.74	320	Pass
	6945	199	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.93	19.14	320	Pass
	7025	215	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.08	19.44	320	Pass
	7025	215	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.49	38.46	320	Pass
	7025	215	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.73	18.90	320	Pass
	6985	207 (L)	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.11	19.26	320	Pass
	6985	207 (L)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	20.04	23.55	320	Pass
	6985	207 (U)	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.17	19.50	320	Pass


Table 7-4. Conducted Bandwidth Measurements Antenna 0 (RU26)

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 29 of 362


	Frequency [MHz]	Channel	802.11 MODE	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.09	22.32	320	Pass
	6175	45	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.13	22.68	320	Pass
	6415	93	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.12	22.66	320	Pass
	5965	3	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.91	39.96	320	Pass
	6165	43	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.95	39.99	320	Pass
	6165	91	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.94	39.93	320	Pass
	5985	7	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.51	80.74	320	Pass
	6145	39	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.60	80.77	320	Pass
	6385	87	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.51	80.57	320	Pass
	6025	15	ax (160MHz)	996	68	1020.8/1201 (MCS11)	156.80	162.92	320	Pass
Band 6	6185	47	ax (160MHz)	996	68	1020.8/1201 (MCS11)	156.91	162.42	320	Pass
	6345	79	ax (160MHz)	996	68	1020.8/1201 (MCS11)	157.04	162.99	320	Pass
	6345	97	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.11	22.02	320	Pass
	6475	105	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.14	22.52	320	Pass
	6515	113	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.16	22.55	320	Pass
	6445	99	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.97	39.94	320	Pass
	6485	107	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.88	39.92	320	Pass
	6525	115	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.88	39.92	320	Pass
	6465	103	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.50	80.67	320	Pass
	6505	111	ax (160MHz)	996	68	1020.8/1201 (MCS11)	156.53	162.31	320	Pass
Band 7	6535	117	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.13	22.15	320	Pass
	6695	149	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.12	22.30	320	Pass
	6875	185	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.13	22.08	320	Pass
	6565	123	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.93	39.92	320	Pass
	6725	155	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.95	39.92	320	Pass
	6845	179	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.89	39.85	320	Pass
	6545	119	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.50	80.79	320	Pass
	6705	151	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.48	80.71	320	Pass
	6865	183	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.58	80.71	320	Pass
	6665	143	ax (160MHz)	996	68	1020.8/1201 (MCS11)	156.90	162.85	320	Pass
Band 8	6825	175	ax (160MHz)	996	68	1020.8/1201 (MCS11)	156.80	162.56	320	Pass
	6895	189	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.13	22.29	320	Pass
	6995	209	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.14	22.23	320	Pass
	7115	229	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.12	22.44	320	Pass
	6885	187	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.91	39.92	320	Pass
	7005	211	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.92	39.96	320	Pass
	7085	227	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.91	40.00	320	Pass
	6945	199	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.45	80.72	320	Pass
	7025	215	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.59	80.70	320	Pass
	6985	207	ax (160MHz)	996	68	1020.8/1201 (MCS11)	156.74	162.51	320	Pass

Table 7-5. Conducted Bandwidth Measurements Antenna 0 (Fully – Loaded RU)


FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 30 of 362




Plot 7-25. 26dB & 99% Bandwidth Plot Antenna 0 (20MHz 802.11ax RU26 (UNII Band 5) – Ch. 45)



Plot 7-27. 26dB & 99% Bandwidth Plot Antenna 0 (80MHz 802.11ax RU26 (UNII Band 5) – Ch. 39)



Plot 7-26. 26dB & 99% Bandwidth Plot Antenna 0 (40MHz 802.11ax RU26 (UNII Band 5) – Ch. 43)




Plot 7-28. 26dB & 99% Bandwidth Plot Antenna 0 (160MHz 802.11ax RU26 (UNII Band 5) – Ch. 47)


FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 31 of 362

V 12.0 03/03/2026


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com




Plot 7-29. 26dB & 99% Bandwidth Plot Antenna 0 (20MHz 802.11ax RU242 (UNII Band 5) – Ch. 45)



Plot 7-31. 26dB & 99% Bandwidth Plot Antenna 0 (80MHz 802.11ax RU996 (UNII Band 5) – Ch. 39)



Plot 7-30. 26dB & 99% Bandwidth Plot Antenna 0 (40MHz 802.11ax RU484 (UNII Band 5) – Ch. 43)







Plot 7-32. 26dB & 99% Bandwidth Plot Antenna 0 (160MHz 802.11ax RU996x2 (UNII Band 5) – Ch. 79)


FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 32 of 362

V 12.0 03/03/2026


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com




FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C24102800810-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 33 of 362




Plot 7-37. 26dB & 99% Bandwidth Plot Antenna 0 (20MHz 802.11ax RU242 (UNII Band 6) – Ch. 113)



Plot 7-39. 26dB & 99% Bandwidth Plot Antenna 0 (80MHz 802.11ax RU996 (UNII Band 6) – Ch. 103)



Plot 7-38. 26dB & 99% Bandwidth Plot Antenna 0 (40MHz 802.11ax RU484 (UNII Band 6) – Ch. 99)







Plot 7-40. 26dB & 99% Bandwidth Plot Antenna 0 (160MHz 802.11ax RU996x2 (UNII Band 6) – Ch. 111)


FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 34 of 362

V 12.0 03/03/2026


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com




FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C24102800810-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 35 of 362




Plot 7-45. 26dB & 99% Bandwidth Plot Antenna 0 (20MHz 802.11ax RU242 (UNII Band 7) – Ch. 185)



Plot 7-47. 26dB & 99% Bandwidth Plot Antenna 0 (80MHz 802.11ax RU996 (UNII Band 7) – Ch. 183)




Plot 7-46. 26dB & 99% Bandwidth Plot Antenna 0 (40MHz 802.11ax RU484 (UNII Band 7) – Ch. 155)




Plot 7-48. 26dB & 99% Bandwidth Plot Antenna 0 (160MHz 802.11ax RU996x2 (UNII Band 7) – Ch. 143)

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 36 of 362


V 12.0 03/03/2026




Plot 7-49. 26dB & 99% Bandwidth Plot Antenna 0 (20MHz 802.11ax RU26 (UNII Band 8) – Ch. 229)



Plot 7-51. 26dB & 99% Bandwidth Plot Antenna 0 (80MHz 802.11ax RU26 (UNII Band 8) – Ch. 199)




Plot 7-50. 26dB & 99% Bandwidth Plot Antenna 0 (40MHz 802.11ax RU26 (UNII Band 8) – Ch. 227)




Plot 7-52. 26dB & 99% Bandwidth Plot Antenna 0 (160MHz 802.11ax RU26 (UNII Band 8) – Ch. 207)

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C24102800810-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 37 of 362


V 12.0 03/03/2026




Plot 7-53. 26dB & 99% Bandwidth Plot Antenna 0 (20MHz 802.11ax RU242 (UNII Band 8) – Ch. 209)



Plot 7-55. 26dB & 99% Bandwidth Plot Antenna 0 (80MHz 802.11ax RU996 (UNII Band 8) – Ch. 215)



Plot 7-54. 26dB & 99% Bandwidth Plot Antenna 0 (40MHz 802.11ax RU484 (UNII Band 8) – Ch. 211)



Plot 7-56. 26dB & 99% Bandwidth Plot Antenna 0 (160MHz 802.11ax RU996x2 (UNII Band 8) – Ch. 207)

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 38 of 362

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com

7.2.3 Antenna 1 26dB & 99% Bandwidth Measurements – SP

	Frequency [MHz]	Channel	802.11 MODE	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.41	20.13	320	Pass
	5955	1	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.02	18.09	320	Pass
	5955	1	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.26	20.01	320	Pass
	6175	45	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.37	19.93	320	Pass
	6175	45	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.97	18.05	320	Pass
	6175	45	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.32	20.48	320	Pass
	6415	93	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.42	20.20	320	Pass
	6415	93	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.74	18.05	320	Pass
	6415	93	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.42	20.12	320	Pass
	5965	3	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.60	18.80	320	Pass
	5965	3	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.52	21.52	320	Pass
	5965	3	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.69	18.96	320	Pass
	6165	43	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.54	18.88	320	Pass
	6165	43	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.56	21.46	320	Pass
	6165	43	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.63	18.92	320	Pass
	6165	91	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.69	18.88	320	Pass
	6165	91	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.41	21.78	320	Pass
	6165	91	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.57	18.85	320	Pass
	5985	7	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.96	19.40	320	Pass
	5985	7	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.31	38.58	320	Pass
	5985	7	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.78	19.21	320	Pass
	6145	39	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.92	19.13	320	Pass
	6145	39	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.44	38.93	320	Pass
	6145	39	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.90	19.14	320	Pass
	6385	87	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.98	19.45	320	Pass
	6385	87	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.53	38.64	320	Pass
	6385	87	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.96	19.25	320	Pass
	6025	15	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.13	19.38	320	Pass
	6025	15	ax (160MHz)	26	18	12.5/14.7 (MCS11)	20.09	22.02	320	Pass
	6025	15	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.11	19.50	320	Pass
	6181	47	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.05	19.35	320	Pass
	6181	47	ax (160MHz)	26	18	12.5/14.7 (MCS11)	20.33	22.76	320	Pass
	6181	47	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.09	19.64	320	Pass
	6345	79	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.20	19.51	320	Pass
	6345	79	ax (160MHz)	26	18	12.5/14.7 (MCS11)	20.36	22.33	320	Pass
	6345	79	ax (160MHz)	26	36	12.5/14.7 (MCS11)	18.15	19.46	320	Pass
Band 6	6345	97	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.39	20.02	320	Pass
	6345	97	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.64	18.12	320	Pass
	6345	97	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.37	20.02	320	Pass
	6475	105	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.27	20.24	320	Pass
	6475	105	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.75	17.86	320	Pass
	6475	105	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.21	19.91	320	Pass
	6515	113	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.43	19.93	320	Pass
	6515	113	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.91	18.01	320	Pass
	6515	113	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.36	20.12	320	Pass
	6445	99	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.69	18.87	320	Pass
	6445	99	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.68	22.07	320	Pass
	6445	99	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.61	18.91	320	Pass
	6485	107	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.56	18.86	320	Pass
	6485	107	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.49	21.39	320	Pass
	6485	107	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.74	18.91	320	Pass
	6525	115	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.69	18.84	320	Pass
	6525	115	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.57	21.70	320	Pass
	6525	115	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.64	18.91	320	Pass
	6465	103	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.58	18.87	320	Pass
	6465	103	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.46	38.42	320	Pass
	6465	103	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.96	19.13	320	Pass
Band 7	6505	111	ax (160MHz)	26	0	12.5/14.7 (MCS11)	18.10	19.18	320	Pass
	6505	111	ax (160MHz)	26	18	12.5/14.7 (MCS11)	36.62	38.63	320	Pass
	6505	111	ax (160MHz)	26	36	12.5/14.7 (MCS11)	20.71	22.86	320	Pass
	6535	117	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.32	20.03	320	Pass
	6535	117	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.98	18.08	320	Pass
	6535	117	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.45	20.22	320	Pass
	6695	149	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.44	20.25	320	Pass
	6695	149	ax (20MHz)	26	4	12.5/14.7 (MCS11)	16.96	18.15	320	Pass
	6695	149	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.32	20.28	320	Pass
	6875	181	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.45	20.12	320	Pass
	6875	181	ax (20MHz)	26	4	12.5/14.7 (MCS11)	17.02	18.13	320	Pass
	6875	181	ax (20MHz)	26	8	12.5/14.7 (MCS11)	18.43	20.15	320	Pass
	6565	123	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.74	18.80	320	Pass
	6565	123	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.60	21.89	320	Pass
	6565	123	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.52	18.79	320	Pass
	6725	155	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.72	18.88	320	Pass
	6725	155	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.74	21.73	320	Pass
	6725	155	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.64	18.97	320	Pass
	6845	179	ax (40MHz)	26	0	12.5/14.7 (MCS11)	17.62	18.88	320	Pass
	6845	179	ax (40MHz)	26	8	12.5/14.7 (MCS11)	19.69	22.38	320	Pass
	6845	179	ax (40MHz)	26	17	12.5/14.7 (MCS11)	17.57	18.92	320	Pass
	6545	135	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.99	19.13	320	Pass
	6545	135	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.44	38.40	320	Pass
	6545	135	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.89	19.23	320	Pass
	6705	151	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.98	19.28	320	Pass
	6705	151	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.49	38.68	320	Pass
	6705	151	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.90	19.24	320	Pass
	6865	167	ax (80MHz)	26	0	12.5/14.7 (MCS11)	17.94	19.39	320	Pass
	6865	167	ax (80MHz)	26	18	12.5/14.7 (MCS11)	36.35	38.49	320	Pass
	6865	167	ax (80MHz)	26	36	12.5/14.7 (MCS11)	17.94	19.11	320	Pass
	6665	143	ax (160MHz)	26	0	12.5/14.7 (MCS11)	17.95	19.18	320	Pass
	6665	143	ax (160MHz)	26	18	12.5/14.7 (MCS11)	20.38	22.42	320	Pass
	6665	143	ax (160MHz)	26	36	12.5/14.7 (MCS11)	17.39	18.70	320	Pass

Table 7-6. Conducted Bandwidth Measurements Antenna 1 (RU26)


FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C24102800810-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 39 of 362

	Frequency [MHz]	Channel	802.11 MODE	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.12	22.53	320	Pass
	6175	45	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.11	22.27	320	Pass
	6415	93	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.10	22.74	320	Pass
	5965	3	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.88	39.88	320	Pass
	6165	43	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.92	39.91	320	Pass
	6165	91	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.88	39.96	320	Pass
	5985	7	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.57	80.69	320	Pass
	6145	39	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.56	80.76	320	Pass
	6385	87	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.61	80.79	320	Pass
	6025	15	ax (160MHz)	996	68	1020.8/1201 (MCS11)	156.69	162.44	320	Pass
Band 6	6181	47	ax (160MHz)	996	68	1020.8/1201 (MCS11)	156.79	162.43	320	Pass
	6345	79	ax (160MHz)	996	68	1020.8/1201 (MCS11)	156.86	162.59	320	Pass
	6345	97	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.11	22.65	320	Pass
	6475	105	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.12	22.71	320	Pass
	6515	113	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.13	22.18	320	Pass
	6445	99	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.95	39.88	320	Pass
	6485	107	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.91	39.85	320	Pass
	6525	115	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.93	39.95	320	Pass
	6465	103	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.50	80.76	320	Pass
	6505	111	ax (160MHz)	996	68	1020.8/1201 (MCS11)	157.08	162.72	320	Pass
Band 7	6535	117	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.12	22.64	320	Pass
	6695	149	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.13	22.57	320	Pass
	6875	181	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.10	22.63	320	Pass
	6565	123	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.92	39.89	320	Pass
	6725	155	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.94	39.90	320	Pass
	6845	179	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.91	39.96	320	Pass
	6545	135	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.53	80.73	320	Pass
	6705	151	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.53	80.74	320	Pass
	6865	167	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.58	80.81	320	Pass
	6665	143	ax (160MHz)	996	68	1020.8/1201 (MCS11)	156.70	162.52	320	Pass


Table 7-7. Conducted Bandwidth Measurements Antenna 1 (Fully – Loaded RU)

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2410280081-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 40 of 362


V 12.0 03/03/2026



Plot 7-57. 26dB & 99% Bandwidth Plot Antenna 1 (20MHz 802.11ax RU26 (UNII Band 5) – Ch. 93)



Plot 7-59. 26dB & 99% Bandwidth Plot Antenna 1 (80MHz 802.11ax RU26 (UNII Band 5) – Ch. 87)




Plot 7-58. 26dB & 99% Bandwidth Plot Antenna 1 (40MHz 802.11ax RU26 (UNII Band 5) – Ch. 43)




Plot 7-60. 26dB & 99% Bandwidth Plot Antenna 1 (160MHz 802.11ax RU26 (UNII Band 5) – Ch. 79)


FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C24102800810-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 41 of 362




Plot 7-61. 26dB & 99% Bandwidth Plot Antenna 1 (20MHz 802.11ax RU242 (UNII Band 5) – Ch. 1)



Plot 7-63. 26dB & 99% Bandwidth Plot Antenna 1 (80MHz 802.11ax RU996 (UNII Band 5) – Ch. 87)



Plot 7-62. 26dB & 99% Bandwidth Plot Antenna 1 (40MHz 802.11ax RU484 (UNII Band 5) – Ch. 43)



Plot 7-64. 26dB & 99% Bandwidth Plot Antenna 1 (160MHz 802.11ax RU996x2 (UNII Band 5) – Ch. 79)


FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C24102800810-10-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 42 of 362

V 12.0 03/03/2026


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com




Plot 7-65. 26dB & 99% Bandwidth Plot Antenna 1 (20MHz 802.11ax RU26 (UNII Band 6) – Ch. 113)



Plot 7-67. 26dB & 99% Bandwidth Plot Antenna 1 (80MHz 802.11ax RU26 (UNII Band 6) – Ch. 103)



Plot 7-66. 26dB & 99% Bandwidth Plot Antenna 1 (40MHz 802.11ax RU26 (UNII Band 6) – Ch. 99)



Plot 7-68. 26dB & 99% Bandwidth Plot Antenna 1 (160MHz 802.11ax RU26 (UNII Band 6) – Ch. 111)

FCC ID: BCGA3218 IC: 579C-A3218	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 10/14/2024 - 12/12/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C24102800810-10-R2.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 43 of 362