






Plot 7-211. Channel Power – UNII 7 – 160MHz – Low




Plot 7-212. Channel Power – UNII 7 – 160MHz – Mid




Plot 7-213. Channel Power – UNII 7 – 160MHz – High


FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 91 of 134



Plot 7-214. Channel Power – UNII 8 – 20MHz




Plot 7-215. Channel Power – UNII 8 – 160MHz – Low



Plot 7-216. Channel Power – UNII 8 – 160MHz – Mid

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG	This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 92 of 134



Plot 7-217. Channel Power – UNII 8 – 160MHz – High

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 93 of 134

7.7 Transmit Power Control (TPC)

Test Overview and Limit

Very low power devices operating in the 5.925 - 7.125 GHz bands shall employ a transmit power control (TPC) mechanism. A very low power device is required to have the capability to operate at least 6 dB below the maximum EIRP power spectral density (PSD) value of -5 dBm/MHz.

Test Procedure Used

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 – Section 12.4.2.6
KDB 789033 D02 v02r01 – Section F

Test Settings

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Set span to encompass the entire 99% OBW of the signal.
3. Set sweep trigger to “free run.”
4. Set RBW = 1 MHz
5. Set VBW $\geq$ 3 MHz
6. Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$.
7. Sweep time $\leq (\text{number of points in sweep}) \times T$, where T is defined
8. Detector = power averaging (rms).
9. Trace mode = max hold.
10. Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Test Instrument & Measurement Setup

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 94 of 134

This test demonstrates the ability of the device to increase and decrease power by the required 6dB as the RSSI is decreased and increased.

1. Configure EUT and companion device for peer-to-peer communication as shown in Figure 7-6.
2. Set variable attenuator to 0dB (noise free spectral environment, high RSSI simulation)
3. Establish a link and start communication between EUT and companion device
4. Capture PSD on spectrum analyzer
5. Set attenuator to 20dB (noisy spectral environment, low RSSI simulation)
6. Capture PSD on spectrum analyzer
7. Compare the highest PSD captured in step 4 to the highest PSD on step 6 and determine the delta.

Test Notes

1. The companion device used was model: A3218 (refer to Table 2-10.)
2. Per manufacturer's declaration, after establishing communication between the EUT and the companion device, 6GHz UNII signal was used to maintain communication and traffic.
3. TPC is triggered when a high RSSI is detected. As RSSI detected signal decreases, the transmitters output power will increase back to maximum allowed power.


FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 95 of 134

BW [MHz]	Frequency [MHz]	MIMO		Summed Power Density [dBm/MHz]	Antenna Gain [dBi]	e.i.r.p. Power Density [dBm/MHz]	e.i.r.p. Power Density Limit [dBm/MHz]
		Measured Power Density [dBm/MHz]					
		Antenna 0	Antenna 1				
160	6185	-12.1	-17.39	-10.97	2.01	-8.97	-5.00

Table 7-27. PSD Measurements (No TPC)

BW [MHz]	Frequency [MHz]	MIMO		Summed Power Density [dBm/MHz]	Antenna Gain [dBi]	e.i.r.p. Power Density [dBm/MHz]	e.i.r.p. Power Density Limit [dBm/MHz]
		Measured Power Density [dBm/MHz]					
		Antenna 0	Antenna 1				
160	6185	-17.97	-23.96	-16.99	2.01	-14.99	-11.00

Table 7-28. PSD Measurements (with TPC)



FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 96 of 134

7.8 Radiated Spurious Emissions – Above 1GHz

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 and KDB 789033 D02 v02r01, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11ax(SU) (20MHz BW), 802.11ax(SU) (40MHz BW), 802.11ax(SU) (80MHz), 802.11ax(SU) (160MHz) and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

For transmitters operating in the 5.925-7.125 GHz band: All emissions outside of the 5.925-7.125 GHz band shall not exceed an EIRP of -27 dBm/MHz. Emissions found in a restricted band are subject to the limits of 15.209 as shown in the table below.

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-29. Radiated Limits

Test Procedures Used

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 – Sections 12.7.7.2, 12.7.6, 12.7.5
KDB 789033 D02 v02r01 – Section G

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 97 of 134

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 98 of 134

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Notes

1. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 and Section 7.5 of RSS-Gen are below the limit shown in Table 7-29.
2. All spurious emissions lying in restricted bands specified in §15.205 and Section 7.5 of RSS-Gen are below the limit shown in Table 7-29. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dB μ V/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB μ V/m.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through one orthogonal plane.
4. This unit was tested while powered by an AC/DC Adapter via USB-C Cable.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas.
6. D is the measurement test distance and emissions 1-18GHz were measured at a 3 meters test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. All data rates were investigated and only the worse case is reported
9. The unit was tested with all possible modes and only the highest emission is reported.
10. The “-” shown in the following RSE tables are used to denote a noise floor measurement.
11. All radiated measurements were tested at the highest supported power setting per band.

Sample Calculations

Determining Spurious Emissions Levels


- Field Strength Level [dB μ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB] – Preamplifier Gain [dB]
- Margin [dB] = Field Strength Level [dB μ V/m] – Limit [dB μ V/m]

Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Sections 7.8.2 to 7.8.13 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 99 of 134

7.8.1 SDM Radiated Spurious Emission




Plot 7-220. Radiated Spurious Emissions above 1GHz SDM (802.11ax – Ch. 33)

Mode:	802.11ax
Data Rate:	MCS2
Distance of Measurements:	3 Meters
Operating Frequency:	6115MHz
Channel:	33


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 12230.00	Average	V	-	-	-84.93	20.48	42.55	53.98	-11.58
* 12230.00	Peak	V	-	-	-73.48	20.48	54.00	73.98	-20.95

Table 7-30. Radiated Spurious Emission Measurements SDM

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 100 of 134



Plot 7-221. Radiated Spurious Emissions above 1GHz SDM (802.11ax – Ch. 61, MCS2)




Plot 7-222. Radiated Spurious Emissions 18-40GHz SDM (802.11ax – Ch. 61)

Mode: 802.11ax
Data Rate: MCS2
Distance of Measurements: 3 Meters
Operating Frequency: 6255MHz
Channel: 61

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 12510.00	Average	V	-	-	-84.24	20.11	0.00	42.87	53.98	-11.11
* 12510.00	Peak	V	-	-	-73.24	20.11	0.00	53.87	73.98	-20.11
* 18765.00	Average	V	-	-	-62.39	-5.37	-9.54	29.70	53.98	-24.28
* 18765.00	Peak	V	-	-	-50.71	-5.37	-9.54	41.38	73.98	-32.60
25020.00	Average	V	-	-	-61.79	-6.34	-9.54	29.33	68.23	-38.90
25020.00	Peak	V	-	-	-50.36	-6.34	-9.54	40.76	88.23	-47.47

Table 7-31. Radiated Spurious Emission Measurements SDM

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 101 of 134




Plot 7-223. Radiated Spurious Emissions above 1GHz SDM (802.11ax – Ch. 93)

Mode: 802.11ax
Data Rate: MCS2
Distance of Measurements: 3 Meters
Operating Frequency: 6415MHz
Channel: 93

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
12830.00	Average	H	-	-	-83.35	22.11	45.76	68.23	-23.52
12830.00	Peak	H	-	-	-72.76	21.97	56.21	88.23	-32.44

Table 7-32. Radiated Spurious Emission Measurements SDM

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 102 of 134




Plot 7-224. Radiated Spurious Emissions above 1GHz SDM (802.11ax – Ch. 97)

Mode: 802.11ax
Data Rate: MCS2
Distance of Measurements: 3 Meters
Operating Frequency: 6435MHz
Channel: 97


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
12870.00	Average	V	-	-	-83.95	21.68	44.73	68.23	-23.52
12870.00	Peak	V	-	-	-73.52	21.68	55.16	88.23	-32.44

Table 7-33. Radiated Spurious Emission Measurements SDM

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 103 of 134



Plot 7-225. Radiated Spurious Emissions above 1GHz SDM (802.11ax – Ch. 105, MCS2)




Plot 7-226. Radiated Spurious Emissions 18-40GHz SDM (802.11ax – Ch. 105)

Mode:	802.11ax
Data Rate:	MCS2
Distance of Measurements:	3 Meters
Operating Frequency:	6475MHz
Channel:	105

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
12950.00	Average	V	-	-	-83.00	21.80	0.00	45.80	68.23	-22.43
12950.00	Peak	V	-	-	-72.50	21.80	0.00	56.30	88.23	-31.93
* 19425.00	Average	V	-	-	-62.41	-5.77	-9.54	29.28	53.98	-24.70
* 19425.00	Peak	V	-	-	-50.69	-5.77	-9.54	41.00	73.98	-32.98
25900.00	Average	V	-	-	-62.66	-3.85	-9.54	30.95	68.23	-37.28
25900.00	Peak	V	-	-	-51.02	-3.85	-9.54	42.59	88.23	-45.64

Table 7-34. Radiated Spurious Emission Measurements SDM

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 104 of 134




Plot 7-227. Radiated Spurious Emissions above 1GHz SDM (802.11ax – Ch. 113)

Mode: 802.11ax
Data Rate: MCS2
Distance of Measurements: 3 Meters
Operating Frequency: 6515MHz
Channel: 113

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13030.00	Average	H	-	-	33.14	22.09	43.68	68.23	-24.55
13030.00	Peak	H	-	-	21.65	22.02	55.22	88.23	-33.01

Table 7-35. Radiated Spurious Emission Measurements SDM

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 105 of 134




Plot 7-228. Radiated Spurious Emissions above 1GHz SDM (802.11ax – Ch. 117)

Mode: 802.11ax
Data Rate: MCS2
Distance of Measurements: 3 Meters
Operating Frequency: 6535MHz
Channel: 117


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13070.00	Average	H	-	-	-85.33	22.11	43.78	68.23	-24.61
13070.00	Peak	H	-	-	-74.34	22.11	54.77	88.23	-33.36

Table 7-36. Radiated Spurious Emission Measurements SDM

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 106 of 134



Plot 7-229. Radiated Spurious Emissions above 1GHz SDM (802.11ax – Ch. 149, MCS2)



Plot 7-230. Radiated Spurious Emissions 18-40GHz SDM (802.11ax – Ch. 149)

Mode: 802.11ax

Data Rate: MCS2

Distance of Measurements: 3 Meters


Operating Frequency: 6695MHz

Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 13390.00	Average	V	-	-	-85.21	21.76	0.00	43.55	53.98	-10.43
* 13390.00	Peak	V	-	-	-74.25	21.76	0.00	54.51	73.98	-19.47
* 20085.00	Average	V	-	-	-62.05	-6.36	-9.54	29.05	53.98	-24.93
* 20085.00	Peak	V	-	-	-50.57	-6.36	-9.54	40.53	73.98	-33.45
26780.00	Average	V	-	-	-61.54	-5.86	-9.54	30.06	68.23	-38.17
26780.00	Peak	V	-	-	-49.58	-5.86	-9.54	42.02	88.23	-46.21

Table 7-37. Radiated Spurious Emission Measurements SDM

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 107 of 134




Plot 7-231. Radiated Spurious Emissions above 1GHz SDM (802.11ax – Ch. 185)

Mode: 802.11ax
Data Rate: MCS2
Distance of Measurements: 3 Meters
Operating Frequency: 6875MHz
Channel: 185

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13710.00	Average	H	-	-	-85.96	21.78	42.82	68.23	-25.02
13710.00	Peak	H	-	-	-73.94	21.78	54.84	88.23	-33.86

Table 7-38. Radiated Spurious Emission Measurements SDM

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 108 of 134




Plot 7-232. Radiated Spurious Emissions above 1GHz SDM (802.11ax – Ch. 189)

Mode: 802.11ax
Data Rate: MCS2
Distance of Measurements: 3 Meters
Operating Frequency: 6895MHz
Channel: 189


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13790.00	Average	H	-	-	32.49	21.78	43.13	68.23	-25.10
13790.00	Peak	H	-	-	21.02	22.11	54.27	88.23	-33.96

Table 7-39. Radiated Spurious Emission Measurements SDM

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 109 of 134



Plot 7-233. Radiated Spurious Emissions above 1GHz SDM (802.11ax – Ch. 209, MCS2)



Plot 7-234. Radiated Spurious Emissions 18-40GHz SDM (802.11ax – Ch. 209)

Mode: 802.11ax

Data Rate: MCS2

Distance of Measurements: 3 Meters


Operating Frequency: 6995MHz

Channel: 209

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13990.00	Average	V	-	-	-81.67	18.32	0.00	43.65	68.23	-24.58
13990.00	Peak	V	-	-	-70.23	18.32	0.00	55.09	88.23	-33.14
* 20985.00	Average	V	-	-	-61.63	-5.98	-9.54	29.85	53.98	-24.13
* 20985.00	Peak	V	-	-	-50.22	-5.98	-9.54	41.26	73.98	-32.72
27980.00	Average	V	-	-	-62.05	-4.60	-9.54	30.81	68.23	-37.42
27980.00	Peak	V	-	-	-50.01	-4.44	-9.54	43.01	88.23	-45.22

Table 7-40. Radiated Spurious Emission Measurements SDM

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 110 of 134



Plot 7-235. Radiated Spurious Emissions above 1GHz SDM (802.11ax – Ch. 233)

Mode: 802.11ax
Data Rate: MCS2
Distance of Measurements: 3 Meters
Operating Frequency: 7115MHz
Channel: 233


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
14230.00	Average	H	-	-	32.53	22.48	43.45	68.23	-24.78
14230.00	Peak	H	-	-	20.77	22.69	55.01	88.23	-33.22

Table 7-41. Radiated Spurious Emission Measurements SDM

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 111 of 134

Mode
Data Rate
Distance of Measurement
Operating Frequency
Channel


802.11ax-SU
 MCS11
 3 Meters
 6115MHz
 33



Plot 7-238 Antenna 0 Radiated Upper Band Edge (Peak & Average – UNII Band 5)

Mode
Data Rate
Distance of Measurement
Operating Frequency
Channel

802.11ax-SU
 MCS11
 3 Meters
 6115MHz
 233




Plot 7-239 Antenna 0 Radiated Upper Band Edge (Average – UNII Band 8)

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 113 of 134


7.8.3 Antenna 0 Radiated Band Edge Measurements (40MHz BW)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6125MHz
Channel	35



Plot 7-240 Antenna 0 Radiated Upper Band Edge (Peak & Average – UNII Band 5)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7085MHz
Channel	227




Plot 7-241 Antenna 0 Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 114 of 134


7.8.4 Antenna 0 Radiated Band Edge Measurements (80MHz BW)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6133MHz
Channel	39



Plot 7-242 Antenna 0 Radiated Upper Band Edge (Peak & Average – UNII Band 5)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7025MHz
Channel	215




Plot 7-243 Antenna 0 Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 115 of 134


7.8.5 Antenna 0 Radiated Band Edge Measurements (160MHz BW)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6185MHz
Channel	47



Plot 7-244 Antenna 0 Radiated Upper Band Edge (Peak & Average – UNII Band 5)


Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6985MHz
Channel	207



Plot 7-245 Antenna 0 Radiated Upper Band Edge (Peak & Average – UNII Band 8)


FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 116 of 134

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6115MHz
Channel	33



Plot 7-248 Antenna 1 Radiated Upper Band Edge (Peak & Average – UNII Band 5)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7115MHz
Channel	233




Plot 7-249 Antenna 1 Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG	 This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.			Page 118 of 134


7.8.7 Antenna 1 Radiated Band Edge Measurements (40MHz BW)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6125MHz
Channel	35



Plot 7-250 Antenna 1 Radiated Upper Band Edge (Peak & Average – UNII Band 5)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7085MHz
Channel	227




Plot 7-251 Antenna 1 Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 119 of 134


7.8.8 Antenna 1 Radiated Band Edge Measurements (80MHz BW)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6133MHz
Channel	39



Plot 7-252 Antenna 1 Radiated Upper Band Edge (Peak & Average – UNII Band 5)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7025MHz
Channel	215




Plot 7-253 Antenna 1 Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 120 of 134


7.8.9 Antenna 1 Radiated Band Edge Measurements (160MHz BW)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6185MHz
Channel	47



Plot 7-254 Antenna 1 Radiated Upper Band Edge (Peak & Average – UNII Band 5)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6985MHz
Channel	207




Plot 7-255 Antenna 1 Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 121 of 134


7.8.10 SDM Radiated Band Edge Measurements (20MHz BW)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6115MHz
Channel	33



Plot 7-256 Radiated Upper Band Edge (Peak & Average – UNII Band 5)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7115MHz
Channel	233




Plot 7-257 Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 122 of 134


7.8.11 SDM Radiated Band Edge Measurements (40MHz BW)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6125MHz
Channel	35



Plot 7-258 SDM Radiated Upper Band Edge (Peak & Average – UNII Band 5)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7085MHz
Channel	227




Plot 7-259 SDM Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 123 of 134


7.8.12 SDM Radiated Band Edge Measurements (80MHz BW)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6133MHz
Channel	39



Plot 7-260 SDM Radiated Upper Band Edge (Peak & Average – UNII Band 5)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7025MHz
Channel	215




Plot 7-261 SDM Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 124 of 134


7.8.13 SDM Radiated Band Edge Measurements (160MHz BW)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6185MHz
Channel	47



Plot 7-262 SDM Radiated Upper Band Edge (Peak & Average – UNII Band 5)

Mode	802.11ax-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6985MHz
Channel	207



Plot 7-263 SDM Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 125 of 134

7.9 Radiated Spurious Emissions – Below 1GHz

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (7.5) must not exceed the limits shown in Table 7-42 per Section 15.209 and RSS-Gen (7.4.3).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-42. Radiated Limits

Test Procedures Used

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

7. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
8. RBW = 120kHz (for emissions from 30MHz – 1GHz)
9. VBW = 300kHz
10. Detector = quasi-peak
11. Sweep time = auto couple
12. Trace mode = max hold
13. Trace was allowed to stabilize

Test Setup

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 126 of 134

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-8. Radiated Test Setup < 30MHz




Figure 7-9. Radiated Test Setup < 1GHz

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 127 of 134

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (7.5) are below the limit shown in Table 7-42.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through one orthogonal plane. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested while powered by an AC/DC Adapter via USB-C Cable.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector on emissions that were within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.
10. The below configuration was investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC Adapter via USB-C Cable
11. All antenna configurations were investigated and only the worst case is reported.
12. The unit was tested with all possible modes and only the highest emission is reported.


Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]} - \text{Preamp Gain}_{[dB]}$
- $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 128 of 134

7.9.1 SDM Radiated Spurious Emissions Measurements (Below 1GHz)



Plot 7-264. Radiated Spurious Emissions below 1GHz SDM, 802.11ax, Ch.209 with AC/DC adapter via USB-C cable

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
33.44	Max Peak	V	100	71	-58.84	-18.26	29.90	40.00	-10.10
46.20	Max Peak	V	100	313	-60.12	-14.45	32.43	40.00	-7.57
99.70	Max Peak	V	300	73	-69.12	-16.61	21.27	43.52	-22.25
172.45	Max Peak	H	100	192	-67.06	-18.40	21.54	46.02	-21.98
412.67	Max Peak	H	200	220	-71.12	-10.08	25.80	46.02	-20.22
912.80	Max Peak	H	300	139	-76.32	-1.37	29.31	46.02	-16.72

Table 7-43. Radiated Spurious Emissions Measurement below 1GHz SDM, 802.11ax, Ch.209 with AC/DC adapter via USB-C cable

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 129 of 134

7.10 AC Line-Conducted Emissions Measurement

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (7.4.2).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-44. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024, Section 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 130 of 134

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-10. Test Instrument & Measurement Setup

Test Notes

- All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
- The below configuration was investigated, and the worst case has been reported.
 - EUT powered by AC/DC Adapter via USB-C cable
- The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (7.4.2).
- $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
- $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Correction Factor (dB)}$
- $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
- Traces shown in plots are made using quasi-peak and average detectors.
- Deviations to the Specifications: None.
- The unit was tested with all possible modes and only the highest emission is reported.

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 131 of 134




Plot 7-265. AC Line Conducted Plot with 802.11ax SDM – Ch.209 (L1) with AC/DC adapter via USB-C cable

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.161	FINAL	—	14.53	55.40	-40.87	L1	ON
0.161	FINAL	34.5	—	65.40	-30.95	L1	ON
0.715	FINAL	—	16.97	46.00	-29.03	L1	ON
0.715	FINAL	29.9	—	56.00	-26.13	L1	ON
2.099	FINAL	—	4.83	46.00	-41.17	L1	ON
2.099	FINAL	11.7	—	56.00	-44.33	L1	ON
9.449	FINAL	7.1	—	60.00	-52.90	L1	ON
9.449	FINAL	—	2.11	50.00	-47.89	L1	ON
16.278	FINAL	14.8	—	60.00	-45.25	L1	ON
16.278	FINAL	—	10.84	50.00	-39.16	L1	ON
19.583	FINAL	—	8.36	50.00	-41.64	L1	ON
19.583	FINAL	13.2	—	60.00	-46.76	L1	ON

Table 7-45. AC Line Conducted Data with 802.11ax SDM – Ch. 209 (L1) with AC/DC adapter via USB-C cable

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 132 of 134



Plot 7-266. AC Line Conducted Plot with 802.11ax SDM – Ch. 209 (N) with AC/DC adapter via USB-C cable

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.161	FINAL	—	13.93	55.40	-41.47	N	ON
0.161	FINAL	35.3	—	65.40	-30.10	N	ON
0.713	FINAL	—	14.13	46.00	-31.87	N	ON
0.713	FINAL	30.5	—	56.00	-25.54	N	ON
2.515	FINAL	—	2.84	46.00	-43.16	N	ON
2.515	FINAL	10.0	—	56.00	-45.99	N	ON
7.697	FINAL	5.7	—	60.00	-54.31	N	ON
7.697	FINAL	—	-0.20	50.00	-50.20	N	ON
16.271	FINAL	11.3	—	60.00	-48.70	N	ON
16.271	FINAL	—	6.42	50.00	-43.58	N	ON
19.588	FINAL	—	8.31	50.00	-41.69	N	ON
19.588	FINAL	13.1	—	60.00	-46.88	N	ON

Table 7-46. AC Line Conducted Data with 802.11ax SDM – Ch. 209 (N) with AC/DC adapter via USB-C cable

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 133 of 134

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Smart Speaker with Display FCC ID: BCGA3300** and **IC: 579C-A3300** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-248 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA3300 IC: 579C-A3300	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 03/24/2025 - 06/14/2025	EUT Type: Smart Speaker with Display	Approved by: Technical Manager
Test Report S/N: 1C2503170028-11-R3.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 134 of 134

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.