




ELEMENT MATERIALS TECHNOLOGY

(Formerly PCTEST)
18855 Adams Court, Morgan Hill, CA 95037 USA
Tel. 408.538.5600
<http://www.element.com>



MEASUREMENT REPORT FCC PART 15.247 / ISSED RSS-247 Bluetooth

Applicant Name:

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

05/12/2025 - 07/14/2025

Test Report Issue Date:

8/28/2025

Test Site/Location:

Element Materials Technology, Morgan Hill, CA, USA

Test Report Serial No.:

1C2504170038-09-R1.BCG

FCC ID:

BCGA3357

IC:

579C-A3357

APPLICANT:

Apple Inc.

Application Type:

Certification

Model/HVIN:

A3357

EUT Type:

Tablet Device

Max. RF Output Power

95.280 mW (19.79 dBm) Peak Conducted

Frequency Range:

2402 – 2480MHz

Type of Modulation:

GFSK, $\pi/4$ -DQPSK, 8DPSK

FCC Classification:

FCC Part 15 Spread Spectrum Transmitter (DSS)

FCC Rule Part(s):

Part 15 Subpart C (15.247)

ISED Specification:

RSS-247 Issue 3

Test Procedure(s):

ANSI C63.10-2020

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2020. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1C2504170038-09-R1.BCG) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

R.J. Ortanez
Executive Vice President



FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 1 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

TABLE OF CONTENTS

1.0	INTRODUCTION	3
1.1	Scope	3
1.2	Element Materials Technology Test Location	3
1.3	Test Facility / Accreditations	3
2.0	PRODUCT INFORMATION	4
2.1	Equipment Description	4
2.2	Device Capabilities	4
2.3	Antenna Description	6
2.4	Test Support Equipment	6
2.5	Test Configuration	7
2.6	Software and Firmware	7
2.7	EMI Suppression Device(s)/Modifications	7
3.0	DESCRIPTION OF TESTS	8
3.1	Evaluation Procedure	8
3.2	AC Line Conducted Emissions	8
3.3	Radiated Emissions	9
3.4	Environmental Conditions	9
4.0	ANTENNA REQUIREMENTS	10
5.0	MEASUREMENT UNCERTAINTY	11
6.0	TEST EQUIPMENT CALIBRATION DATA	12
7.0	TEST RESULTS	13
7.1	Summary	13
7.2	Bandwidth Measurement	14
7.3	Output Power Measurement	28
7.4	Conducted Authorized Band Edge	34
7.5	Carrier Frequency Separation	47
7.6	Time of Occupancy	54
7.7	Number of Hopping Channels	59
7.8	Conducted Spurious Emissions	66
7.9	Radiated Spurious Emissions – Above 1GHz	77
7.10	Radiated Spurious Emissions – Below 1GHz	97
7.11	AC Line-Conducted Emissions Measurement	102
8.0	CONCLUSION	108

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 2 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Materials Technology Test Location

These measurement tests were conducted at the Element Materials Technology facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element Materials Technology located in Morgan Hill, CA 95037, U.S.A.

- Element Materials Technology is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- Element Materials Technology facility is a registered (22831) test laboratory with the site description on file with ISSED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISSED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 3 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Tablet Device FCC ID: BCGA3357 and IC: 579C-A3357**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- This Bluetooth module has been tested by manufacturer and the following were confirmed:
 - A. The hopping sequence is pseudorandom
 - B. All channels are used equally on average
 - C. The receiver input bandwidth equals the transmit bandwidth
 - D. The receiver hops in sequence with the transmit signal
- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

Test Device Serial No.: G4574YVFP6, QTV7QG9FTQ, H9HHG5000JS0000SDF, H9HHG5000M80000SDF

2.2 Device Capabilities

This device contains the following capabilities:

802.11b/g/n/ax/be WLAN, 802.11a/n/ac/ax/be UNII (5GHz and 6GHz), 802.15.4, Bluetooth (1x, EDR, LE, HDR, HDT), Narrowband (NB) UNII (5GHz and 6GHz), WPT.

This device supports BT Beamforming.

This device supports channel puncturing and channel bandwidth reduction.

Ch.	Frequency (MHz)
00	2402
:	:
39	2441
:	:
78	2480

Table 2-1. Bluetooth Frequency/ Channel Operations

Note: This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section 6.0 b) of KDB 558074 D01 v05r02 and ANSI C63.10-2020. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 4 of 108

BLE Mode		Antenna WF8		Antenna WF7		Antenna WF9		TxBF Primary		TxBF Diversity	
		Duty Cycle [%]	DCCF [dB]	Duty Cycle [%]	Duty Cycle [%]	DCCF [dB]	DCCF [dB]	DCCF [dB]	DCCF [dB]	Duty Cycle [%]	DCCF [dB]
GFSK	ePA	76.09	1.19	76.09	1.19	76.40	1.17	76.20	1.18	76.09	1.19
	iPA	76.09	1.19	76.09	1.19	76.40	1.17	76.20	1.18	76.09	1.19
8PSK	ePA	76.31	1.17	76.42	1.17	76.39	1.17	76.38	1.17	76.41	1.17
	iPA	76.31	1.17	76.42	1.17	76.39	1.17	76.38	1.17	76.41	1.17
π/4-DQPSK	ePA	76.25	1.18	76.30	1.17	76.30	1.17	76.23	1.18	76.55	1.16
	iPA	76.25	1.18	76.30	1.17	76.30	1.17	76.23	1.18	76.55	1.16

Table 2-2. Measured Duty Cycles

TxBF Primary = Antenna WF8 + Antenna WF7

TxBF Diversity = Antenna WF8 + Antenna WF9

This device supports simultaneous transmission operations, which allows multiple transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.

Antenna	Simultaneous Tx Config	Bluetooth 2.4GHz	Thread	WLAN	NB UNII	WIFI 5GHz	WIFI 6GHz
		BDR, EDR, LE HDR, HDT	802.15.4	802.11 b/g/n/ax/be	BDR, EDR, LE HDR, HDT	802.11 a/n/ac/ax/be	802.11 a/ax/be
Ant WF7	Config 1	✓	✗	✗	✗	✓	✗
Ant WF7	Config 2	✓	✗	✗	✗	✗	✓
Ant WF7	Config 3	✗	✓	✗	✗	✓	✗
Ant WF7	Config 4	✗	✓	✗	✗	✗	✓
Ant WF7	Config 5	✗	✗	✓	✓	✗	✗
Ant WF7	Config 6	✗	✗	✓	✗	✓	✗
Ant WF7	Config 7	✗	✗	✓	✗	✗	✓
Ant WF8	Config 8	✓	✗	✗	✗	✓	✗
Ant WF8	Config 9	✓	✗	✗	✗	✗	✓
Ant WF8	Config 10	✗	✓	✗	✗	✓	✗
Ant WF8	Config 11	✗	✓	✗	✗	✗	✓
Ant WF8	Config 12	✗	✗	✓	✓	✗	✗
Ant WF8	Config 13	✗	✗	✓	✗	✓	✗
Ant WF8	Config 14	✗	✗	✓	✗	✗	✓

Table 2-3. Simultaneous Transmission Configurations

✓ = Support; ✗ = Not Support

FCC ID: BCGA3357 IC: 579C-A3357	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 5 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

2.3 Antenna Description

Following antenna gains provided by manufacturer were used for testing.

Frequency [GHz]	Antenna Gain (dBi)		
	Antenna WF8	Antenna WF7	Antenna WF9
2.4	3.8	2.3	1.1

Table 2-4. Highest Antenna Gain

2.4 Test Support Equipment

1	Apple MacBook Pro	Model:	A2141	S/N:	C02H604EQ05D
	w/AC/DC Adapter	Model:	A2166	S/N:	C4H042705ZNPM0WA6
2	Apple USB-C Cable	Model:	Spartan	S/N:	GXK1336018XKTR024
3	USB-C Cable	Model:	A2795	S/N:	DWH80115BK826GV19
	w/ AC Adapter	Model:	A2305	S/N:	C4H95160004PF4F4V
4	Apple Pencil	Model:	A2538	S/N:	KJ26TCFXJW
5	DC Power Supply	Model:	KPS3010D	S/N:	N/A

Table 2-5. Test Support Equipment List

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 6 of 108

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2020. ANSI C63.10-2020 was also used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, and 7.8 for antenna port conducted emissions test setups.

There are two vendors of the WiFi/Bluetooth radio modules, variant 1 and variant 2. Both radio modules have the same mechanical outline, same on-board antenna matching circuit, identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances. The worst case configuration was found between the two variants. The EUT was also investigated with and without charger.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power and the worst case channel were reported.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

For AC line conducted and radiated test below 1GHz, following configuration were investigated and the worst case was reported.

- EUT powered by AC/DC adaptor via USB-C cable with wire charger
- EUT powered by host PC via USB-C cable with wire charger

$\pi/4$ -DQPSK has been investigated and confirmed as not the worst case.

All possible simultaneous transmission configurations have been investigated and the worst case config has been reported.

Description	Bluetooth	UNII
Antenna	Antenna WF7	Antenna WF7
Channel	78	36
Operating Frequency (MHz)	2480	5180
Mode/Modulation	GFSK ePA	802.11n

Table 2-6. Worst Case Simultaneous Transmission Configuration

2.6 Software and Firmware

The test was conducted with firmware version 23A256 installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added, and no modifications were made during testing.

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 7 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2020) was used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that the cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.12. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.50.40.

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 8 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

Per KDB 414788 D01 v01r01, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was rotated about its vertical axis while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 9 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 10 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	2.07
Line Conducted Disturbance	1.91
Radiated Disturbance (<30MHz)	4.12
Radiated Disturbance (30MHz - 1GHz)	4.85
Radiated Disturbance (1 - 18GHz)	5.08
Radiated Disturbance (>18GHz)	5.22

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 11 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance with the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Anritsu	ML2496A	Power Meter	2/10/2025	Annual	2/10/2026	1306009
Anritsu	MA2411B	Pulse Power Sensor	2/10/2025	Annual	2/10/2026	1315051
Anritsu	MA2411B	Pulse Power Sensor	2/10/2025	Annual	2/10/2026	1339027
ATM	180-442-KF	20dB Nominal Gain Horn Antenna	3/24/2025	Annual	3/24/2026	T058601-02
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	9/25/2024	Annual	9/25/2025	00240109
Fairview Microwave/MCL	FMCA1975-36/BW-K10-2W44+	30MHz-40GHz RF Cable/Attenuator *	6/10/2025	Annual	6/10/2026	-
Keysight Technology	N9040B	UXA Signal Analyzer	9/5/2024	Annual	9/5/2025	MY61320121
Keysight Technology	N9030A	PXA Signal Analyzer	10/16/2024	Annual	10/16/2025	MY49430494
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	8/14/2024	Annual	8/14/2025	101648
Rohde & Schwarz	FSW43	Spectrum Analyzer 2Hz to 43GHz	11/21/2024	Annual	11/21/2025	104093
Rohde & Schwarz	ESW44	EMI Test Receiver	10/17/2024	Annual	10/17/2025	101668
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	9/20/2024	Annual	9/20/2025	102327
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	6/3/2025	Annual	6/3/2026	100052
Rohde & Schwarz	HFH2-Z2	Loop Antenna	5/12/2025	Annual	5/12/2026	100546
Rohde & Schwarz	ENV216	Two-Line V-Network	4/24/2025	Annual	4/24/2026	101364
Schwarzbeck	VULB 9162	Bilog Antenna (30MHz - 6GHz)	9/18/2024	Annual	9/18/2025	00358

Table 6-1. Test Equipment List

Notes:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- * denotes passive equipment that have been internally verified/calibrated.

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 12 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.
 FCC ID: BCGA3357
 IC: 579C-A3357
 Method/System: Frequency Hopping Spread Spectrum (FHSS)
 Number of Channels: 79

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(1)	RSS-247 [5.1(a)]	20dB Bandwidth	N/A	CONDUCTED	N/A	Section 7.2
2.1049	RSS-Gen [6.7]	Occupied Bandwidth	N/A		N/A	Section 7.2
15.247(b)(1)	RSS-247 [5.4(b)]	Peak Transmitter Output Power	< 1 Watt if ≥ 75 non-overlapping channels used		PASS	Section 7.3
15.247(a)(1)	RSS-247 [5.1(b)]	Channel Separation	> 2/3 of 20 dB BW for systems with Output Power < 125mW		PASS	Section 7.5
15.247(a)(1)(iii)	RSS-247 [5.1(d)]	Time of Occupancy	< 0.4 sec in 31.6 sec period		PASS	Section 7.6
15.247(a)(1)(iii)	RSS-247 [5.1(d)]	Number of Channels	> 15 Channels		PASS	Section 7.7
15.247(d)	RSS-247 [5.5]	Band Edge / Out-of-Band Emissions	> 20dBc		PASS	Section 7.4, 7.8
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-247 limits)	RADIATED	PASS	Section 7.9, 7.10
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen [8.8] limits)	LINE CONDUCTED	PASS	Section 7.11

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Conducted Automation," Version 1.4.0.
- 5) For radiated testing, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 3.4.2.

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 13 of 108

7.2 Bandwidth Measurement

§2.1049; §15.247 (a)(1); RSS-247 [5.1(a)]; RSS-Gen [6.7]

Test Overview and Limit

The bandwidth at 20dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

ANSI C63.10-2020 – Subclause 6.9.2
RSS-Gen [6.7]

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 99% occupied bandwidth and the 20dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 20$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. $RBW = 1 - 5\% \text{ OBW}$
3. $VBW \geq 3 \times RBW$
4. Reference level set to keep signal from exceeding maximum input mixer level for linear operation.
5. Detector = Peak
6. Trace mode = max hold
7. Sweep = auto couple
8. The trace was allowed to stabilize
9. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 14 of 108

V 11.0 5/2025

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.

FCC ID: BCGA3357 IC: 579C-A3357	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 15 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.2.1 Antenna WF8


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Measured 99% Occupied Bandwidth [kHz]	Measured 20dB Bandwidth [kHz]
2402	1.0	GFSK	ePA	0	824.41	921.22
2441	1.0	GFSK	ePA	39	824.42	919.30
2480	1.0	GFSK	ePA	78	824.23	920.26
2402	3.0	8DPSK	ePA	0	1181.53	1271.50
2441	3.0	8DPSK	ePA	39	1180.41	1270.20
2480	3.0	8DPSK	ePA	78	1182.02	1272.76

Table 7-2. 20dB BW and 99% OBW Measurements Antenna WF8


FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 16 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-1. 20dB BW and 99% OBW Plot Antenna WF8 (Bluetooth, GFSK, ePA – Ch. 0)




Plot 7-2. 20dB BW and 99% OBW Plot Antenna WF8 (Bluetooth, GFSK, ePA – Ch. 39)


FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 17 of 108

V 11.0 5/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 18 of 108



Plot 7-5. 20dB BW and 99% OBW Plot Antenna WF8 (Bluetooth, 8DPSK, ePA – Ch. 39)



Plot 7-6. 20dB BW and 99% OBW Plot Antenna WF8 (Bluetooth, 8DPSK, ePA – Ch. 78)

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 19 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.2.2 Antenna WF7


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Measured 99% Occupied Bandwidth [kHz]	Measured 20dB Bandwidth [kHz]
2402	1.0	GFSK	ePA	0	824.57	921.36
2441	1.0	GFSK	ePA	39	825.62	919.94
2480	1.0	GFSK	ePA	78	824.73	921.51
2402	3.0	8DPSK	ePA	0	1181.49	1272.37
2441	3.0	8DPSK	ePA	39	1180.89	1270.28
2480	3.0	8DPSK	ePA	78	1181.91	1272.85

Table 7-3. 20dB BW and 99% OBW Bandwidth Measurements Antenna WF7

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 20 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 21 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-9. 20dB BW and 99% OBW Plot Antenna WF7 (Bluetooth, GFSK, ePA – Ch. 78)





Plot 7-10. 20dB BW and 99% OBW Plot Antenna WF7 (Bluetooth, 8DPSK, ePA – Ch. 0)

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 22 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 23 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.2.3 Antenna WF9



Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Measured 99% Occupied Bandwidth [kHz]	Measured 20dB Bandwidth [kHz]
2402	1.0	GFSK	ePA	0	824.01	920.02
2441	1.0	GFSK	ePA	39	823.13	920.42
2480	1.0	GFSK	ePA	78	824.88	921.26
2402	3.0	8DPSK	ePA	0	1181.56	1272.30
2441	3.0	8DPSK	ePA	39	1180.91	1270.50
2480	3.0	8DPSK	ePA	78	1181.79	1272.25

Table 7-4. 20dB BW and 99% OBW Bandwidth Measurements Antenna WF9

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 24 of 108

V 11.0 5/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 25 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-15. 20dB BW and 99% OBW Plot Antenna WF9 (Bluetooth, GFSK, ePA – Ch. 78)





Plot 7-16. 20dB BW and 99% OBW Plot Antenna WF9 (Bluetooth, 8DPSK, ePA – Ch. 0)

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 26 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 27 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.3 Output Power Measurement

§15.247 (b)(1); RSS-247 [5.4(b)]

Test Overview and Limits

Measurement is made while the EUT is operating in non-hopping transmission mode. Peak and Average power measurements are performed using a broadband power meter with a pulse sensor.

The maximum peak conducted output power of frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels is 1 watt

The conducted output power limit on paragraph above is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels. The e.i.r.p. shall not exceed 4 W.

Test Procedure Used

ANSI C63.10-2020 – Subclause 11.9.1.2 PKPM1 Peak Power Method

ANSI C63.10-2020 – Subclause 11.9.2.3.2 Method AVGPM-G

ANSI C63.10-2020 – Subclause 14.4 Measure-and-Sum Technique

Test Settings

Peak Power Measurement

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than the occupied bandwidth.

Method AVGPM-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup for Peak and Average Power Measurement

Note

All supported modulations have been tested and $\pi/4$ -DQPSK was found not to be the worst case modulation so only GFSK and 8DPSK is reported.

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 28 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.3.1 Peak Output Power Measurement

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Peak Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]
					[dBm]	[mW]						
2402	1.0	GFSK	ePA	0	15.96	39.446	30.00	-14.04	3.80	19.76	36.02	-16.26
2441	1.0	GFSK	ePA	39	15.97	39.537	30.00	-14.03	3.80	19.77	36.02	-16.25
2480	1.0	GFSK	ePA	78	16.19	41.591	30.00	-13.81	3.80	19.99	36.02	-16.03
2402	1.0	GFSK	IPA	0	9.44	8.790	30.00	-20.56	3.80	13.24	36.02	-22.78
2441	1.0	GFSK	IPA	39	9.76	9.462	30.00	-20.24	3.80	13.56	36.02	-22.46
2480	1.0	GFSK	IPA	78	9.72	9.376	30.00	-20.28	3.80	13.52	36.02	-22.50
2402	3.0	8DPSK	ePA	0	19.52	89.536	30.00	-10.48	3.80	23.32	36.02	-12.70
2441	3.0	8DPSK	ePA	39	19.44	87.902	30.00	-10.56	3.80	23.24	36.02	-12.78
2480	3.0	8DPSK	ePA	78	19.79	95.280	30.00	-10.21	3.80	23.59	36.02	-12.43
2402	3.0	8DPSK	IPA	0	9.24	8.395	30.00	-20.76	3.80	13.04	36.02	-22.98
2441	3.0	8DPSK	IPA	39	9.24	8.395	30.00	-20.76	3.80	13.04	36.02	-22.98
2480	3.0	8DPSK	IPA	78	9.30	8.511	30.00	-20.70	3.80	13.10	36.02	-22.92

Table 7-5. Peak Conducted Output Power Measurements Antenna WF8

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Peak Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]
					[dBm]	[mW]						
2402	1.0	GFSK	ePA	0	17.99	62.907	30.00	-12.01	2.30	20.29	36.02	-15.73
2441	1.0	GFSK	ePA	39	17.98	62.762	30.00	-12.02	2.30	20.28	36.02	-15.74
2480	1.0	GFSK	ePA	78	17.38	54.739	30.00	-12.62	2.30	19.68	36.02	-16.34
2402	1.0	GFSK	IPA	0	9.48	8.870	30.00	-20.52	2.30	11.78	36.02	-24.24
2441	1.0	GFSK	IPA	39	8.98	7.907	30.00	-21.02	2.30	11.28	36.02	-24.74
2480	1.0	GFSK	IPA	78	8.84	7.649	30.00	-21.16	2.30	11.14	36.02	-24.88
2402	3.0	8DPSK	ePA	0	19.33	85.783	30.00	-10.67	2.30	21.63	36.02	-14.39
2441	3.0	8DPSK	ePA	39	19.31	85.330	30.00	-10.69	2.30	21.61	36.02	-14.41
2480	3.0	8DPSK	ePA	78	19.20	83.176	30.00	-10.80	2.30	21.50	36.02	-14.52
2402	3.0	8DPSK	IPA	0	9.33	8.564	30.00	-20.67	2.30	11.63	36.02	-24.39
2441	3.0	8DPSK	IPA	39	8.83	7.630	30.00	-21.18	2.30	11.13	36.02	-24.90
2480	3.0	8DPSK	IPA	78	8.40	6.921	30.00	-21.60	2.30	10.70	36.02	-25.32

Table 7-6. Peak Conducted Output Power Measurements Antenna WF7

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Peak Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]
					[dBm]	[mW]						
2402	1.0	GFSK	ePA	0	17.34	54.213	30.00	-12.66	1.10	18.44	36.02	-17.58
2441	1.0	GFSK	ePA	39	17.25	53.064	30.00	-12.75	1.10	18.35	36.02	-17.67
2480	1.0	GFSK	ePA	78	17.46	55.693	30.00	-12.54	1.10	18.56	36.02	-17.46
2402	1.0	GFSK	IPA	0	8.80	7.586	30.00	-21.20	1.10	9.90	36.02	-26.12
2441	1.0	GFSK	IPA	39	8.78	7.549	30.00	-21.22	1.10	9.88	36.02	-26.14
2480	1.0	GFSK	IPA	78	8.98	7.907	30.00	-21.02	1.10	10.08	36.02	-25.94
2402	3.0	8DPSK	ePA	0	19.20	83.196	30.00	-10.80	1.10	20.30	36.02	-15.72
2441	3.0	8DPSK	ePA	39	19.48	88.756	30.00	-10.52	1.10	20.58	36.02	-15.44
2480	3.0	8DPSK	ePA	78	19.68	92.918	30.00	-10.32	1.10	20.78	36.02	-15.24
2402	3.0	8DPSK	IPA	0	8.65	7.328	30.00	-21.35	1.10	9.75	36.02	-26.27
2441	3.0	8DPSK	IPA	39	8.72	7.444	30.00	-21.28	1.10	9.82	36.02	-26.20
2480	3.0	8DPSK	IPA	78	8.84	7.647	30.00	-21.17	1.10	9.94	36.02	-26.09

Table 7-7. Peak Conducted Output Power Measurements Antenna WF9

FCC ID: BCGA3357 IC: 579C-A3357	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 29 of 108

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Peak Conducted Power						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	ERP [dBm]	ERP Limit [dBm]
					Antenna WF8		Antenna WF7		Summed						
					[dBm]	[mW]	[dBm]	[mW]	[dBm]	[mW]					
2402	1.0	GFSK	ePA	0	15.98	39.628	17.07	50.933	19.57	90.561	29.91	-10.34	6.09	25.66	36.02
2441	1.0	GFSK	ePA	39	15.95	39.355	17.07	50.933	19.56	90.288	29.91	-10.35	6.09	25.65	36.02
2480	1.0	GFSK	ePA	78	16.11	40.832	17.05	50.699	19.62	91.531	29.91	-10.29	6.09	25.71	36.02
2402	1.0	GFSK	IPA	0	9.63	9.183	8.99	7.925	12.33	17.108	29.91	-17.58	6.09	18.42	36.02
2441	1.0	GFSK	IPA	39	9.69	9.311	9.02	7.980	12.38	17.291	29.91	-17.53	6.09	18.47	36.02
2480	1.0	GFSK	IPA	78	9.24	8.395	9.08	8.091	12.17	16.486	29.91	-17.74	6.09	18.26	36.02
2402	3.0	8DPSK	ePA	0	16.22	41.879	16.22	41.879	19.23	83.759	29.91	-10.68	6.09	25.32	36.02
2441	3.0	8DPSK	ePA	39	16.47	44.361	16.23	41.976	19.36	86.337	29.91	-10.55	6.09	25.45	36.02
2480	3.0	8DPSK	ePA	78	16.44	44.055	16.11	40.832	19.29	84.887	29.91	-10.62	6.09	25.38	36.02
2402	3.0	8DPSK	IPA	0	9.22	8.356	8.75	7.499	12.00	15.855	29.91	-17.91	6.09	18.09	36.02
2441	3.0	8DPSK	IPA	39	9.21	8.337	8.77	7.534	12.01	15.870	29.91	-17.90	6.09	18.10	36.02
2480	3.0	8DPSK	IPA	78	9.24	8.395	8.85	7.674	12.06	16.068	29.91	-17.85	6.09	18.15	36.02

Table 7-8. Peak Conducted Output Power Measurements TxBF Primary

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Peak Conducted Power						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	ERP [dBm]	ERP Limit [dBm]
					Antenna WF8		Antenna WF9		Summed						
					[dBm]	[mW]	[dBm]	[mW]	[dBm]	[mW]					
2402	1.0	GFSK	ePA	0	15.98	39.628	16.89	48.865	19.47	88.493	30.00	-10.53	5.56	25.03	36.02
2441	1.0	GFSK	ePA	39	15.95	39.355	16.96	49.659	19.49	89.014	30.00	-10.51	5.56	25.05	36.02
2480	1.0	GFSK	ePA	78	16.11	40.832	17.02	50.350	19.60	91.182	30.00	-10.40	5.56	25.16	36.02
2402	1.0	GFSK	IPA	0	9.63	9.183	8.88	7.727	12.28	16.910	30.00	-17.72	5.56	17.84	36.02
2441	1.0	GFSK	IPA	39	9.69	9.311	8.53	7.129	12.16	16.440	30.00	-17.84	5.56	17.72	36.02
2480	1.0	GFSK	IPA	78	9.24	8.395	9.09	8.110	12.18	16.504	30.00	-17.82	5.56	17.74	36.02
2402	3.0	8DPSK	ePA	0	16.22	41.879	16.07	40.458	19.16	82.337	30.00	-10.84	5.56	24.72	36.02
2441	3.0	8DPSK	ePA	39	16.47	44.361	16.10	40.738	19.30	85.099	30.00	-10.70	5.56	24.86	36.02
2480	3.0	8DPSK	ePA	78	16.44	44.055	16.05	40.272	19.26	84.327	30.00	-10.74	5.56	24.82	36.02
2402	3.0	8DPSK	IPA	0	9.22	8.356	8.60	7.244	11.93	15.600	30.00	-18.07	5.56	17.49	36.02
2441	3.0	8DPSK	IPA	39	9.21	8.337	8.67	7.362	11.96	15.699	30.00	-18.04	5.56	17.52	36.02
2480	3.0	8DPSK	IPA	78	9.24	8.395	8.78	7.551	12.03	15.946	30.00	-17.97	5.56	17.59	36.02

Table 7-9. Peak Conducted Output Power Measurements TxBF Diversity

FCC ID: BCGA3357 IC: 579C-A3357	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 30 of 108

7.3.2 Average Output Power Measurement

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Avg Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]
					[dBm]	[mW]						
2402	1.0	GFSK	ePA	0	15.86	38.548	30.00	-14.14	3.80	19.66	36.02	-16.36
2441	1.0	GFSK	ePA	39	15.86	38.548	30.00	-14.14	3.80	19.66	36.02	-16.36
2480	1.0	GFSK	ePA	78	15.39	34.594	30.00	-14.61	3.80	19.19	36.02	-16.83
2402	1.0	GFSK	IPA	0	9.40	8.710	30.00	-20.60	3.80	13.20	36.02	-22.82
2441	1.0	GFSK	IPA	39	8.83	7.638	30.00	-21.17	3.80	12.63	36.02	-23.39
2480	1.0	GFSK	IPA	78	9.43	8.770	30.00	-20.57	3.80	13.23	36.02	-22.79
2402	3.0	8DPSK	ePA	0	16.47	44.361	30.00	-13.53	3.80	20.27	36.02	-15.75
2441	3.0	8DPSK	ePA	39	16.38	43.451	30.00	-13.62	3.80	20.18	36.02	-15.84
2480	3.0	8DPSK	ePA	78	16.15	41.210	30.00	-13.85	3.80	19.95	36.02	-16.07
2402	3.0	8DPSK	IPA	0	6.26	4.227	30.00	-23.74	3.80	10.06	36.02	-25.96
2441	3.0	8DPSK	IPA	39	6.36	4.325	30.00	-23.64	3.80	10.16	36.02	-25.86
2480	3.0	8DPSK	IPA	78	6.30	4.266	30.00	-23.70	3.80	10.10	36.02	-25.92

Table 7-10. Average Conducted Output Power Measurements Antenna WF8

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Avg Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]
					[dBm]	[mW]						
2402	1.0	GFSK	ePA	0	17.05	50.699	30.00	-12.95	2.30	19.35	36.02	-16.67
2441	1.0	GFSK	ePA	39	16.98	49.934	30.00	-13.02	2.30	19.28	36.02	-16.74
2480	1.0	GFSK	ePA	78	16.77	47.479	30.00	-13.24	2.30	19.07	36.02	-16.96
2402	1.0	GFSK	IPA	0	8.64	7.313	30.00	-21.36	2.30	10.94	36.02	-25.08
2441	1.0	GFSK	IPA	39	8.83	7.638	30.00	-21.17	2.30	11.13	36.02	-24.89
2480	1.0	GFSK	IPA	78	8.53	7.125	30.00	-21.47	2.30	10.83	36.02	-25.19
2402	3.0	8DPSK	ePA	0	16.33	42.973	30.00	-13.67	2.30	18.63	36.02	-17.39
2441	3.0	8DPSK	ePA	39	16.32	42.855	30.00	-13.68	2.30	18.62	36.02	-17.40
2480	3.0	8DPSK	ePA	78	16.24	42.053	30.00	-13.76	2.30	18.54	36.02	-17.48
2402	3.0	8DPSK	IPA	0	5.82	3.820	30.00	-24.18	2.30	8.12	36.02	-27.90
2441	3.0	8DPSK	IPA	39	5.81	3.812	30.00	-24.19	2.30	8.11	36.02	-27.91
2480	3.0	8DPSK	IPA	78	5.51	3.558	30.00	-24.49	2.30	7.81	36.02	-28.21

Table 7-11. Average Conducted Output Power Measurements Antenna WF7

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Avg Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]
					[dBm]	[mW]						
2402	1.0	GFSK	ePA	0	17.24	52.979	30.00	-12.76	1.10	18.34	36.02	-17.68
2441	1.0	GFSK	ePA	39	17.11	51.404	30.00	-12.89	1.10	18.21	36.02	-17.81
2480	1.0	GFSK	ePA	78	17.31	53.802	30.00	-12.69	1.10	18.41	36.02	-17.61
2402	1.0	GFSK	IPA	0	8.67	7.357	30.00	-21.33	1.10	9.77	36.02	-26.25
2441	1.0	GFSK	IPA	39	8.03	6.347	30.00	-21.97	1.10	9.13	36.02	-26.89
2480	1.0	GFSK	IPA	78	8.85	7.675	30.00	-21.15	1.10	9.95	36.02	-26.07
2402	3.0	8DPSK	ePA	0	16.17	41.400	30.00	-13.83	1.10	17.27	36.02	-18.75
2441	3.0	8DPSK	ePA	39	16.49	44.586	30.00	-13.51	1.10	17.59	36.02	-18.43
2480	3.0	8DPSK	ePA	78	16.28	42.491	30.00	-13.72	1.10	17.38	36.02	-18.64
2402	3.0	8DPSK	IPA	0	5.73	3.744	30.00	-24.27	1.10	6.83	36.02	-29.19
2441	3.0	8DPSK	IPA	39	5.62	3.650	30.00	-24.38	1.10	6.72	36.02	-29.30
2480	3.0	8DPSK	IPA	78	5.93	3.917	30.00	-24.07	1.10	7.03	36.02	-28.99

Table 7-12. Average Conducted Output Power Measurements Antenna WF9

FCC ID: BCGA3357 IC: 579C-A3357	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 31 of 108

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Average Conducted Power						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	ERP [dBm]	ERP Limit [dBm]
					Antenna WF8		Antenna WF7		Summed						
					[dBm]	[mW]	[dBm]	[mW]	[dBm]	[mW]					
2402	1.0	GFSK	ePA	0	15.83	38.282	16.92	49.204	19.42	87.486	29.91	-10.49	6.09	25.51	36.02
2441	1.0	GFSK	ePA	39	15.80	38.019	16.92	49.204	19.41	87.223	29.91	-10.50	6.09	25.50	36.02
2480	1.0	GFSK	ePA	78	15.89	38.815	16.90	48.978	19.43	87.793	29.91	-10.48	6.09	25.52	36.02
2402	1.0	GFSK	IPA	0	9.34	8.590	8.84	7.656	12.11	16.246	29.91	-17.80	6.09	18.20	36.02
2441	1.0	GFSK	IPA	39	8.86	7.691	8.87	7.709	11.88	15.400	29.91	-18.03	6.09	17.97	36.02
2480	1.0	GFSK	IPA	78	8.73	7.464	8.93	7.816	11.84	15.281	29.91	-18.07	6.09	17.93	36.02
2402	3.0	8DPSK	ePA	0	13.10	20.417	13.15	20.654	16.14	41.071	29.91	-13.77	6.09	22.23	36.02
2441	3.0	8DPSK	ePA	39	13.35	21.627	12.89	19.454	16.14	41.081	29.91	-13.77	6.09	22.23	36.02
2480	3.0	8DPSK	ePA	78	13.33	21.528	13.05	20.184	16.20	41.711	29.91	-13.71	6.09	22.29	36.02
2402	3.0	8DPSK	IPA	0	6.31	4.276	5.85	3.846	9.10	8.122	29.91	-20.81	6.09	15.19	36.02
2441	3.0	8DPSK	IPA	39	6.30	4.266	5.30	3.388	8.84	7.654	29.91	-21.07	6.09	14.93	36.02
2480	3.0	8DPSK	IPA	78	6.18	4.150	5.98	3.963	9.09	8.112	29.91	-20.82	6.09	15.18	36.02

Table 7-13. Average Conducted Output Power Measurements TxBF Primary

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Average Conducted Power						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	ERP [dBm]	ERP Limit [dBm]
					Antenna WF8		Antenna WF9		Summed						
					[dBm]	[mW]	[dBm]	[mW]	[dBm]	[mW]					
2402	1.0	GFSK	ePA	0	15.83	38.282	16.74	47.206	19.32	85.489	30.00	-10.68	5.56	24.88	36.02
2441	1.0	GFSK	ePA	39	15.80	38.019	16.81	47.973	19.34	85.962	30.00	-10.66	5.56	24.90	36.02
2480	1.0	GFSK	ePA	78	15.89	38.815	16.87	48.641	19.42	87.456	30.00	-10.58	5.56	24.98	36.02
2402	1.0	GFSK	IPA	0	9.34	8.590	8.73	7.464	12.06	16.055	30.00	-17.94	5.56	17.62	36.02
2441	1.0	GFSK	IPA	39	8.86	7.691	8.38	6.887	11.64	14.578	30.00	-18.36	5.56	17.20	36.02
2480	1.0	GFSK	IPA	78	8.73	7.464	8.94	7.834	11.85	15.299	30.00	-18.15	5.56	17.41	36.02
2402	3.0	8DPSK	ePA	0	13.10	20.417	13.02	20.045	16.07	40.462	30.00	-13.93	5.56	21.63	36.02
2441	3.0	8DPSK	ePA	39	13.35	21.627	12.56	18.030	15.98	39.657	30.00	-14.02	5.56	21.54	36.02
2480	3.0	8DPSK	ePA	78	13.33	21.528	13.01	19.999	16.18	41.526	30.00	-13.82	5.56	21.74	36.02
2402	3.0	8DPSK	IPA	0	6.31	4.276	5.56	3.597	8.96	7.873	30.00	-21.04	5.56	14.52	36.02
2441	3.0	8DPSK	IPA	39	6.30	4.266	5.74	3.750	9.04	8.016	30.00	-20.96	5.56	14.60	36.02
2480	3.0	8DPSK	IPA	78	6.18	4.150	5.06	3.206	8.67	7.356	30.00	-21.33	5.56	14.23	36.02

Table 7-14. Average Conducted Output Power Measurements TxBF Diversity

FCC ID: BCGA3357 IC: 579C-A3357	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 32 of 108

Note:

Per ANSI C63.10-2020 and KDB 662911 D01 v02r01 Section E)1), the conducted powers at Antenna WF8 and Antenna WF7 were first measured separately during TxBF transmission as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Per ANSI C63.10-2020 Subclause 14.6.3, the directional gain is calculated using the following formula, where G_N is the gain of the nth antenna and N_{ANT} , the total number of antennas used.

$$\text{Directional gain} = 10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}] \text{ dBi}$$

Sample TxBF Calculation:

At 2404MHz the average conducted output power was measured to be 15.83 dBm for Antenna WF8 and 17.42 dBm for Antenna WF7.

$$\text{Antenna WF8} + \text{Antenna WF7} = \text{TxBF}$$

$$(15.83 \text{ dBm} + 16.92 \text{ dBm}) = (38.282 \text{ mW} + 49.204 \text{ mW}) = 87.486 \text{ mW} = 19.42 \text{ dBm}$$

Sample e.i.r.p. Calculation:

At 2402MHz, the average conducted output power was calculated to be 19.54 dBm with antenna gain of 6.09 dBi.

$$\text{e.i.r.p. (dBm)} = \text{Conducted Power (dBm)} + \text{Ant gain (dBi)}$$

$$19.42 \text{ dBm} + 6.09 \text{ dBi} = 25.51 \text{ dBm}$$

FCC ID: BCGA3357 IC: 579C-A3357	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 33 of 108

7.4 Conducted Authorized Band Edge

§15.247 (d); RSS-247 [5.5]

Test Overview and Limits

EUT operates in hopping and non-hopping transmission mode. Measurement is taken at the highest point located outside of the emission bandwidth. **The maximum permissible out-of-band emission level is 20 dBc.**

Test Procedure Used

ANSI C63.10-2020 – Section 6.10.4

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup


Test Notes

1. Out of band conducted spurious emissions at the band edge were investigated for all data rates in hopping and non-hopping modes. The worst case emissions were found with the EUT transmitting at 3 Mbps. Band edge emissions were also investigated with the EUT transmitting in all data rates. Plots of the worst case emissions are shown below.
2. All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.


FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 34 of 108

V 11.0 5/2025

7.4.1 Antenna WF8



Plot 7-19. Band Edge Plot Antenna WF8 (Bluetooth with Hopping Disabled, GFSK, ePA – Ch. 0)




Plot 7-20. Band Edge Plot Antenna WF8 (Bluetooth with Hopping Disabled, GFSK, ePA – Ch. 78)


FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 35 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-21. Band Edge Plot Antenna WF8 (Bluetooth with Hopping Enabled, GFSK, ePA)




Plot 7-22. Band Edge Plot Antenna WF8 (Bluetooth with Hopping Enabled, GFSK, ePA)

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 36 of 108



Plot 7-23. Band Edge Plot Antenna WF8 (Bluetooth with Hopping Disabled, 8DPSK, ePA – Ch. 0)




Plot 7-24. Band Edge Plot Antenna WF8 (Bluetooth with Hopping Disabled, 8DPSK, ePA – Ch. 78)


FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 37 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-25. Band Edge Plot Antenna WF8 (Bluetooth with Hopping Enabled, 8DPSK, ePA)




Plot 7-26. Band Edge Plot Antenna WF8 (Bluetooth with Hopping Enabled, 8DPSK, ePA)

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 38 of 108


V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.4.2 Antenna WF7



Plot 7-27. Band Edge Plot Antenna WF7 (Bluetooth with Hopping Disabled, GFSK, ePA – Ch. 0)




Plot 7-28. Band Edge Plot Antenna WF7 (Bluetooth with Hopping Disabled, GFSK, ePA – Ch. 78)


FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 39 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-29. Band Edge Plot Antenna WF7 (Bluetooth with Hopping Enabled, GFSK, ePA)




Plot 7-30. Band Edge Plot Antenna WF7 (Bluetooth with Hopping Enabled, GFSK, ePA)


FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 40 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-31. Band Edge Plot Antenna WF7 (Bluetooth with Hopping Disabled, 8DPSK, ePA – Ch. 0)




Plot 7-32. Band Edge Plot Antenna WF7 (Bluetooth with Hopping Disabled, 8DPSK, ePA – Ch. 78)

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 41 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-33. Band Edge Plot Antenna WF7 (Bluetooth with Hopping Enabled, 8DPSK, ePA)




Plot 7-34. Band Edge Plot Antenna WF7 (Bluetooth with Hopping Enabled, 8DPSK, ePA)

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 42 of 108


V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.4.3 Antenna WF9



Plot 7-35. Band Edge Plot Antenna WF9 (Bluetooth with Hopping Disabled, GFSK, ePA – Ch. 0)




Plot 7-36. Band Edge Plot Antenna WF9 (Bluetooth with Hopping Disabled, GFSK, ePA – Ch. 78)


FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 43 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-37. Band Edge Plot Antenna WF9 (Bluetooth with Hopping Enabled, GFSK, ePA)




Plot 7-38. Band Edge Plot Antenna WF9 (Bluetooth with Hopping Enabled, GFSK, ePA)


FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 44 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-39. Band Edge Plot Antenna WF9 (Bluetooth with Hopping Disabled, 8DPSK, ePA – Ch. 0)




Plot 7-40. Band Edge Plot Antenna WF9 (Bluetooth with Hopping Disabled, 8DPSK, ePA – Ch. 78)


FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 45 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-41. Band Edge Plot Antenna WF9 (Bluetooth with Hopping Enabled, 8DPSK, ePA)



Plot 7-42. Band Edge Plot Antenna WF9 (Bluetooth with Hopping Enabled, 8DPSK, ePA)

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 46 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.5 Carrier Frequency Separation

§15.247 (a)(1); RSS-247 [5.1(b)]

Test Overview and Limit

Measurement is made with EUT operating in hopping mode. ***The minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.***

Test Procedure Used

ANSI C63.10-2020 – Section 7.8.2

Test Settings

1. Span = Wide enough to capture peaks of two adjacent channels
2. RBW = 30% of channel spacing. Adjust as necessary to best identify center of each individual channel
3. VBW $\geq$ RBW
4. Sweep = Auto
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize.
8. Marker-delta function used to determine separation between peaks of the adjacent channels

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup

Test Notes

1. The EUT complies with the minimum channel separation requirement when it is operating in 1x/EDR mode using 79 channels.
2. All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 47 of 108

7.5.1 Antenna WF8


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Measured Channel Separation [MHz]	Min. Channel Separation [MHz]	Pass/Fail
2441	1.0	GFSK	ePA	39	1.00	0.61	Pass
2441	3.0	8DPSK	ePA	39	1.00	0.85	Pass

Table 7-15. Minimum Channel Separation Antenna WF8


FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 48 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-43. Channel Spacing Plot Antenna WF8 (Bluetooth, GFSK, ePA)



Plot 7-44. Channel Spacing Plot Antenna WF8 (Bluetooth, 8DPSK, ePA)

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 49 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.5.2 Antenna WF7



Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Measured Channel Separation [MHz]	Min. Channel Separation [MHz]	Pass/Fail
2441	1.0	GFSK	ePA	39	1.00	0.61	Pass
2441	3.0	8DPSK	ePA	39	1.00	0.85	Pass

Table 7-16. Minimum Channel Separation Antenna WF7

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 50 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 51 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.5.3 Antenna WF9


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Measured Channel Separation [MHz]	Min. Channel Separation [MHz]	Pass/Fail
2441	1.0	GFSK	ePA	39	1.00	0.61	Pass
2441	3.0	8DPSK	ePA	39	1.00	0.85	Pass

Table 7-17. Minimum Channel Separation Antenna WF9


FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 52 of 108

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-47. Channel Spacing Plot Antenna WF9 (Bluetooth, GFSK, ePA)



Plot 7-48. Channel Spacing Plot Antenna WF9 (Bluetooth, 8DPSK, ePA)

FCC ID: BCGA3357 IC: 579C-A3357		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 53 of 108

7.6 Time of Occupancy

§15.247 (a)(1)(iii); RSS-247 [5.1(d)]

Test Overview and Limit

Measurement is made while EUT is operating in hopping mode with the spectrum analyzer set to zero span. ***The maximum permissible time of occupancy is 400 ms within a period of 400ms multiplied by the number of hopping channels employed.***

Test Procedure Used

ANSI C63.10-2020 – Section 7.8.4

Test Settings

1. Span = zero span, centered on a hopping channel
2. RBW $\leq$ channel spacing and $\gg 1/T$, where T is expected dwell time per channel
3. Sweep = as necessary to capture entire dwell time. Second plot may be required to demonstrate two successive hops on a channel
4. Trigger is set with appropriate trigger delay to place pulse near the center of the plot
5. Detector = peak
6. Trace mode = max hold
7. Marker-delta function used to determine transmit time per hop

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-5. Test Instrument & Measurement Setup

Test Notes

All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.

FCC ID: BCGA3357 IC: 579C-A3357	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170038-09-R1.BCG	Test Dates: 05/12/2025 - 07/14/2025	EUT Type: Tablet Device	Page 54 of 108