



7.8.14 Antenna 2a Radiated Band Edge Measurements (160MHz BW)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6185MHz
Channel	47



Plot 7-383 Antenna 2a Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6985MHz
Channel	207




Plot 7-384 Antenna 2a Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 162 of 188

V 11.0 05/2025


7.8.15 CDD/SDM Primary Radiated Band Edge Measurements (20MHz BW)

Mode	802.11a
Data Rate	MCS54
Distance of Measurement	3 Meters
Operating Frequency	6115MHz
Channel	33



Plot 7-385 CDD Primary Radiated Lower Band Edge (Peak & Average – UNII Band 8)

Mode	802.11a
Data Rate	MCS54
Distance of Measurement	3 Meters
Operating Frequency	7095MHz
Channel	229




Plot 7-386 CDD Primary Radiated Upper Band Edge (Peak & Average – UNII Band 8)


FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 163 of 188

V 11.0 05/2025

Mode	802.11a
Data Rate	MCS54
Distance of Measurement	3 Meters
Operating Frequency	7115MHz
Channel	233



Plot 7-387 CDD Primary Radiated Upper Band Edge (Peak – UNII Band 8)




Plot 7-388 CDD Primary Radiated Upper Band Edge (Average – UNII Band 8)

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 164 of 188

V 11.0 05/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6115MHz
Channel	33



Plot 7-389 SDM Primary Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7095MHz
Channel	229




Plot 7-390 SDM Primary Radiated Upper Band Edge (Peak & Average – UNII Band 8)


FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 165 of 188

V 11.0 05/2025

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7115MHz
Channel	233



Plot 7-391 SDM Primary Radiated Upper Band Edge (Peak – UNII Band 8)




Plot 7-392 SDM Primary Radiated Upper Band Edge (Average – UNII Band 8)

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 166 of 188

V 11.0 05/2025


7.8.16 SDM Primary Radiated Band Edge Measurements (40MHz BW)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6125MHz
Channel	35



Plot 7-393 SDM Primary Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7085MHz
Channel	227




Plot 7-394 SDM Primary Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 167 of 188

V 11.0 05/2025


7.8.17 SDM Primary Radiated Band Edge Measurements (80MHz BW)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6145MHz
Channel	39



Plot 7-395 SDM Primary Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7025MHz
Channel	215




Plot 7-396 SDM Primary Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 168 of 188

V 11.0 05/2025


7.8.18 SDM Primary Radiated Band Edge Measurements (160MHz BW)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6185MHz
Channel	47



Plot 7-397 SDM Primary Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6985MHz
Channel	207




Plot 7-398 SDM Primary Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 169 of 188

V 11.0 05/2025


7.8.19 CDD/SDM Diversity Radiated Band Edge Measurements (20MHz BW)

Mode	802.11a
Data Rate	MCS54
Distance of Measurement	3 Meters
Operating Frequency	6115MHz
Channel	33



Plot 7-399 CDD Diversity Radiated Lower Band Edge (Peak & Average – UNII Band 8)

Mode	802.11a
Data Rate	MCS54
Distance of Measurement	3 Meters
Operating Frequency	7095MHz
Channel	229




Plot 7-400 CDD Diversity Radiated Upper Band Edge (Peak & Average – UNII Band 8)


FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 170 of 188

V 11.0 05/2025

Mode	802.11a
Data Rate	MCS54
Distance of Measurement	3 Meters
Operating Frequency	7115MHz
Channel	233



Plot 7-401 CDD Diversity Radiated Upper Band Edge (Peak – UNII Band 8)




Plot 7-402 CDD Diversity Radiated Upper Band Edge (Average – UNII Band 8)

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 171 of 188

V 11.0 05/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6115MHz
Channel	33



Plot 7-403 SDM Diversity Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7095MHz
Channel	229




Plot 7-404 SDM Diversity Radiated Upper Band Edge (Peak & Average – UNII Band 8)


FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 172 of 188

V 11.0 05/2025

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7115MHz
Channel	233



Plot 7-405 SDM Diversity Radiated Upper Band Edge (Peak – UNII Band 8)




Plot 7-406 SDM Diversity Radiated Upper Band Edge (Average – UNII Band 8)

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 173 of 188

V 11.0 05/2025


7.8.20 SDM Diversity Radiated Band Edge Measurements (40MHz BW)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6125MHz
Channel	35



Plot 7-407 SDM Diversity Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7085MHz
Channel	227




Plot 7-408 SDM Diversity Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 174 of 188

V 11.0 05/2025


7.8.21 SDM Diversity Radiated Band Edge Measurements (80MHz BW)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6145MHz
Channel	39



Plot 7-409 SDM Diversity Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7025MHz
Channel	215




Plot 7-410 SDM Diversity Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 175 of 188

V 11.0 05/2025


7.8.22 SDM Diversity Radiated Band Edge Measurements (160MHz BW)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6185MHz
Channel	47



Plot 7-411 SDM Diversity Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6985MHz
Channel	207



Plot 7-412 SDM Diversity Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 176 of 188

V 11.0 05/2025

7.9 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 7-70 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-70. Radiated Limits

Test Procedures Used

ANSI C63.10-2020

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = quasi-peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 177 of 188

V 11.0 05/2025

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-8. Radiated Test Setup < 30MHz




Figure 7-9. Radiated Test Setup < 1GHz

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 178 of 188

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-70.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector on emissions that were within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
10. All antenna configurations were investigated and only the worst case is reported.
11. The unit was tested with all possible modes and only the highest emission is reported.

Sample Calculations


Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]} - \text{Preamp Gain}_{[dB]}$
- $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$

FCC ID: BCGA3358 IC: 579C-A3358	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 179 of 188

V 11.0 05/2025

7.9.1 SDM Primary Radiated Spurious Emissions Measurements (Below 1GHz)



Plot 7-413. Radiated Spurious Emissions below 1GHz SDM Primary, 802.11be, Ch.61 with AC/DC Adaptor


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
37.91	Max-Peak	V	100	358	-61.89	-17.23	27.88	40.00	-12.12
79.81	Max-Peak	V	100	242	-56.94	-22.87	27.19	40.00	-12.81
142.62	Max-Peak	H	100	178	-59.85	-21.55	25.60	43.52	-17.92
171.67	Max-Peak	H	100	206	-60.37	-20.26	26.37	43.52	-17.15
243.35	Max-Peak	H	100	278	-68.00	-16.57	22.43	46.02	-23.59
462.09	Max-Peak	V	100	41	-72.67	-12.08	22.25	46.02	-23.77

Table 7-71. Radiated Spurious Emissions Measurement below 1GHz SDM Primary, 802.11be, Ch.61 with AC/DC Adaptor

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 180 of 188

V 11.0 05/2025

7.9.2 SDM Diversity Radiated Spurious Emissions Measurements (Below 1GHz)



Plot 7-414. Radiated Spurious Emissions below 1GHz SDM Diversity, 802.11be, Ch.61 with AC/DC Adaptor

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
39.60	Max-Peak	V	100	205	-64.74	-15.93	26.33	40.00	-13.67
44.31	Max-Peak	V	100	37	-59.73	-14.68	32.59	40.00	-7.41
129.72	Max-Peak	H	300	350	-63.46	-19.55	23.99	43.52	-19.53
184.86	Max-Peak	H	100	85	-62.81	-17.38	26.81	43.52	-16.71
271.58	Max-Peak	H	100	15	-71.75	-14.02	21.23	46.02	-24.79
836.56	Max-Peak	H	100	15	-76.76	-2.30	27.94	46.02	-18.08

Table 7-72. Radiated Spurious Emissions Measurement below 1GHz SDM Diversity, 802.11be, Ch.61 with AC/DC Adaptor

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 181 of 188

V 11.0 05/2025

7.10 AC Line-Conducted Emissions Measurement

§15.407; RSS-Gen[8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-73. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2020, Section 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 182 of 188

V 11.0 05/2025

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-10. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated, and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
2. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
3. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
4. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
5. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Correction Factor (dB)}$
6. $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
7. Traces shown in plots are made using quasi-peak and average detectors.
8. Deviations to the Specifications: None.
9. The unit was tested with all possible modes and only the highest emission is reported.

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 183 of 188

V 11.0 05/2025




Plot 7-415. AC Line Conducted Plot with 802.11be SDM Primary – Ch.61 (L1), with AC/DC Adaptor

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.161	FINAL	—	42.40	55.40	-13.00	L1	GND
0.164	FINAL	54.2	—	65.28	-11.09	L1	GND
0.242	FINAL	—	34.99	52.02	-17.03	L1	GND
0.245	FINAL	48.4	—	61.94	-13.51	L1	GND
0.647	FINAL	—	20.96	46.00	-25.04	L1	GND
0.654	FINAL	34.3	—	56.00	-21.71	L1	GND
4.484	FINAL	—	15.64	46.00	-30.36	L1	GND
4.490	FINAL	31.2	—	56.00	-24.78	L1	GND
8.480	FINAL	13.4	—	60.00	-46.56	L1	GND
8.482	FINAL	—	6.42	50.00	-43.58	L1	GND
16.190	FINAL	—	10.96	50.00	-39.04	L1	GND
16.193	FINAL	15.9	—	60.00	-44.14	L1	GND

Table 7-74. AC Line Conducted Data with 802.11be SDM Primary – Ch. 61 (L1) with AC/DC Adaptor

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 184 of 188

V 11.0 05/2025




Plot 7-416. AC Line Conducted Plot with 802.11be SDM Primary – Ch. 61 (N), with AC/DC Adaptor

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.161	FINAL	—	41.16	55.40	-14.23	N	GND
0.164	FINAL	52.8	—	65.28	-12.52	N	GND
0.242	FINAL	—	33.61	52.02	-18.41	N	GND
0.245	FINAL	46.9	—	61.94	-15.05	N	GND
0.647	FINAL	35.0	—	56.00	-20.96	N	GND
0.650	FINAL	—	20.91	46.00	-25.09	N	GND
4.506	FINAL	32.5	—	56.00	-23.51	N	GND
4.603	FINAL	—	19.50	46.00	-26.50	N	GND
8.374	FINAL	22.1	—	60.00	-37.90	N	GND
8.471	FINAL	—	15.92	50.00	-34.08	N	GND
16.197	FINAL	—	11.56	50.00	-38.44	N	GND
16.197	FINAL	17.2	—	60.00	-42.82	N	GND

Table 7-75. AC Line Conducted Data with 802.11be SDM Primary – Ch. 61 (N), with AC/DC Adaptor

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 185 of 188

V 11.0 05/2025




Plot 7-417. AC Line Conducted Plot with 802.11be SDM Diversity – Ch.61 (L1), with AC/DC Adaptor

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.161	FINAL	—	37.97	55.40	-17.43	L1	GND
0.161	FINAL	51.2	—	65.40	-14.24	L1	GND
0.395	FINAL	—	20.95	47.95	-27.00	L1	GND
0.395	FINAL	37.5	—	57.95	-20.43	L1	GND
0.881	FINAL	—	17.06	46.00	-28.94	L1	GND
0.881	FINAL	30.2	—	56.00	-25.83	L1	GND
2.416	FINAL	17.9	—	56.00	-38.11	L1	GND
2.416	FINAL	—	9.81	46.00	-36.19	L1	GND
4.468	FINAL	31.2	—	56.00	-24.79	L1	GND
4.468	FINAL	—	16.63	46.00	-29.37	L1	GND
16.424	FINAL	—	10.15	50.00	-39.85	L1	GND
16.424	FINAL	15.9	—	60.00	-44.13	L1	GND

Table 7-76. AC Line Conducted Data with 802.11be SDM Diversity – Ch. 61 (L1) with AC/DC Adaptor

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 186 of 188

V 11.0 05/2025



Plot 7-418. AC Line Conducted Plot with 802.11be SDM Diversity – Ch. 61 (N), with AC/DC Adaptor

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.164	FINAL	—	39.16	55.28	-16.12	N	GND
0.164	FINAL	54.0	—	65.28	-11.28	N	GND
0.393	FINAL	—	22.84	48.00	-25.16	N	GND
0.393	FINAL	39.9	—	58.00	-18.06	N	GND
0.886	FINAL	—	18.54	46.00	-27.46	N	GND
0.886	FINAL	32.0	—	56.00	-24.03	N	GND
2.409	FINAL	22.4	—	56.00	-33.59	N	GND
2.409	FINAL	—	12.70	46.00	-33.30	N	GND
4.497	FINAL	32.1	—	56.00	-23.86	N	GND
4.497	FINAL	—	18.83	46.00	-27.17	N	GND
16.431	FINAL	—	10.60	50.00	-39.40	N	GND
16.431	FINAL	16.9	—	60.00	-43.14	N	GND

Table 7-77. AC Line Conducted Data with 802.11be SDM Diversity – Ch. 61 (N), with AC/DC Adaptor

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 187 of 188

V 11.0 05/2025

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device FCC ID: BCGA3358** and **IC: 579C-A3358** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-248 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-26-R1.BCG	Test Dates: 5/12/2025 - 8/13/2025	EUT Type: Tablet Device	Page 188 of 188

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.