



7.6.22 CDD Diversity Radiated Band Edge Measurements (160MHz BW)


RU52




Plot 7-1106. CDD Diversity (Peak & Average, RU52, Index 37, Ch.50, MCS11)




Plot 7-1109. CDD Diversity (Peak & Average, RU52, Index 52 (H), Ch.50, MCS11)




Plot 7-1107. CDD Diversity (Peak & Average, RU52, Index 52 (H), Ch.50, MCS11)



Plot 7-1110. CDD Diversity (Peak & Average, RU52, Index 37, Ch.114 (FCC ONLY), MCS11)




Plot 7-1108. CDD Diversity (Peak & Average, RU52, Index 37, Ch.50, MCS11)




Plot 7-1111. CDD Diversity (Peak & Average, RU52, Index 52 (H), Ch.114 (FCC ONLY), MCS11)

FCC ID: BCGA3358 IC: 579C-A3358			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device		Page 341 of 374

V 11.0 5/2025



Plot 7-1112. CDD Diversity (Peak, RU52, Index 37, Ch.114 (FCC ONLY), MCS11)




Plot 7-1113. CDD Diversity (Peak, RU52, Index 52 (H), Ch.114 (FCC ONLY), MCS11)


FCC ID: BCGA3358 IC: 579C-A3358			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device		Page 342 of 374

V 11.0 5/2025


MRU




Plot 7-1114. CDD Diversity (Peak & Average, RU996+484, Index 94, Ch.50, MCS11)




Plot 7-1117. CDD Diversity (Peak & Average, RU996+484, Index 95, Ch.50, MCS11)




Plot 7-1115. CDD Diversity (Peak & Average, RU996+484, Index 95, Ch.50, MCS11)



Plot 7-1118. CDD Diversity (Peak & Average, RU996+484, Index 94 (L), Ch.114 (FCC ONLY), MCS11)




Plot 7-1116. CDD Diversity (Peak & Average, RU996+484, Index 94, Ch.50, MCS11)




Plot 7-1119. CDD Diversity (Peak & Average, RU996+484, Index 94 (H), Ch.114 (FCC ONLY), MCS11)

FCC ID: BCGA3358 IC: 579C-A3358			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device		Page 343 of 374


V 11.0 5/2025




Plot 7-1120. CDD Diversity (Peak & Average, RU996+484, Index 95 (L), Ch.114 (FCC ONLY), MCS11)




Plot 7-1123. CDD Diversity (Peak, RU996+484, Index 94 (H), Ch.114 (FCC ONLY), MCS11)




Plot 7-1121. CDD Diversity (Peak & Average, RU996+484, Index 95 (H), Ch.114 (FCC ONLY), MCS11)



Plot 7-1124. CDD Diversity (Peak, RU996+484, Index 95 (H), Ch.114 (FCC ONLY), MCS11)




Plot 7-1122. CDD Diversity (Peak, RU996+484, Index 94 (L), Ch.114 (FCC ONLY), MCS11)




Plot 7-1125. CDD Diversity (Peak, RU996+484, Index 95 (L), Ch.114 (FCC ONLY), MCS11)


FCC ID: BCGA3358 IC: 579C-A3358			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 344 of 374	




Plot 7-1126. CDD Diversity (Peak & Average, RU996+484+242, Index 94, Ch.50, MCS11)




Plot 7-1129. CDD Diversity (Peak & Average, RU996+484+242, Index 97, Ch.50, MCS11)




Plot 7-1127. CDD Diversity (Peak & Average, RU996+484+242, Index 95, Ch.50, MCS11)



Plot 7-1130. CDD Diversity (Peak & Average, RU996+484+242, Index 98, Ch.50, MCS11)




Plot 7-1128. CDD Diversity (Peak & Average, RU996+484+242, Index 96, Ch.50, MCS11)




Plot 7-1131. CDD Diversity (Peak & Average, RU996+484+242, Index 99, Ch.50, MCS11)


FCC ID: BCGA3358 IC: 579C-A3358			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 345 of 374	




Plot 7-1132. CDD Diversity (Peak & Average, RU996+484+242, Index 94, Ch.50, MCS11)




Plot 7-1135. CDD Diversity (Peak & Average, RU996+484+242, Index 97, Ch.50, MCS11)




Plot 7-1133. CDD Diversity (Peak & Average, RU996+484+242, Index 95, Ch.50, MCS11)



Plot 7-1136. CDD Diversity (Peak & Average, RU996+484+242, Index 98, Ch.50, MCS11)




Plot 7-1134. CDD Diversity (Peak & Average, RU996+484+242, Index 96, Ch.50, MCS11)




Plot 7-1137. CDD Diversity (Peak & Average, RU996+484+242, Index 99, Ch.50, MCS11)


FCC ID: BCGA3358 IC: 579C-A3358			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 346 of 374	




Plot 7-1138. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (L), Ch.114 (FCC ONLY), MCS11)




Plot 7-1141. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (H), Ch.114 (FCC ONLY), MCS11)




Plot 7-1139. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (H), Ch.114 (FCC ONLY), MCS11)



Plot 7-1142. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (H), Ch.114 (FCC ONLY), MCS11)




Plot 7-1140. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (L), Ch.114 (FCC ONLY), MCS11)




Plot 7-1143. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (L), Ch.114 (FCC ONLY), MCS11)


FCC ID: BCGA3358 IC: 579C-A3358			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device		Page 347 of 374




Plot 7-1144. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (L), Ch.114 (FCC ONLY), MCS11)




Plot 7-1147. CDD Diversity (Peak, RU996+484+242, Index 96 (L), Ch.114 (FCC ONLY), MCS11)




Plot 7-1145. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (H), Ch.114 (FCC ONLY), MCS11)



Plot 7-1148. CDD Diversity (Peak, RU996+484+242, Index 97 (H), Ch.114 (FCC ONLY), MCS11)




Plot 7-1146. CDD Diversity (Peak, RU996+484+242, Index 96 (H), Ch.114 (FCC ONLY), MCS11)




Plot 7-1149. CDD Diversity (Peak, RU996+484+242, Index 97 (L), Ch.114 (FCC ONLY), MCS11)


FCC ID: BCGA3358 IC: 579C-A3358			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 348 of 374	




Plot 7-1150. CDD Diversity (Peak, RU996+484+242, Index 98 (L), Ch.114 (FCC ONLY), MCS11)



Plot 7-1153. CDD Diversity (Peak, RU996+484+242, Index 99 (H), Ch.114 (FCC ONLY), MCS11)




Plot 7-1151. CDD Diversity (Peak, RU996+484+242, Index 98 (H), Ch.114 (FCC ONLY), MCS11)




Plot 7-1152. CDD Diversity (Peak, RU996+484+242, Index 99 (L), Ch.114 (FCC ONLY), MCS11)

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device		Page 349 of 374


RU996X2




Plot 7-1154. CDD Diversity (Peak & Average, RU996X2, Index 68, Ch.50, MCS11)



Plot 7-1156. CDD Diversity (Peak & Average, RU996X2, Index 68, Ch.114 FCC ONLY, MCS11)



Plot 7-1155. CDD Diversity (Peak & Average, RU996X2, Index 68, Ch.50, MCS11)



Plot 7-1157. CDD Diversity (Peak, RU996X2, Index 68, Ch.114 FCC ONLY, MCS11)

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 350 of 374

V 11.0 5/2025

7.7 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-234 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-234. Radiated Limits

Test Procedures Used

ANSI C63.10-2020

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 351 of 374

V 11.0 5/2025

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-6. Radiated Test Setup < 30MHz




Figure 7-7. Radiated Test Setup < 1GHz

FCC ID: BCGA3358 IC: 579C-A3358	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 352 of 374

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-234.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector for emissions within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.
10. All antenna configurations and data rates were investigated and only the worst case are reported.
11. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger

Sample Calculations


Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]} - \text{Preamplifier Gain }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 353 of 374

V 11.0 5/2025

7.7.1 CDD Primary Radiated Spurious Emissions (Below 1GHz)




Plot 7-1158. RSE below 1GHz CDD Primary (RU26 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
37.81	Max Peak	V	100	347	-62.61	-16.53	27.86	40.00	-12.14
45.57	Max Peak	V	100	15	-62.81	-14.50	29.69	40.00	-10.31
94.17	Max Peak	V	100	97	-64.72	-17.54	24.74	43.52	-18.78
192.33	Max Peak	H	100	237	-59.62	-16.24	31.14	43.52	-12.38
227.78	Max Peak	H	100	81	-67.89	-15.22	23.89	46.02	-22.13
300.58	Max Peak	H	100	62	-71.76	-13.34	21.90	46.02	-24.12

Table 7-235. RSE below 1GHz CDD Primary (RU26 – Ch.40), with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 354 of 374




Plot 7-1159. RSE below 1GHz CDD Primary (RU78 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
47.51	Max Peak	V	200	331	-63.41	-14.36	29.23	40.00	-10.77
60.46	Max Peak	V	100	157	-67.24	-15.91	23.85	40.00	-16.15
94.12	Max Peak	H	200	16	-65.62	-17.55	23.83	43.52	-19.69
192.28	Max Peak	H	200	250	-62.27	-16.25	28.48	43.52	-15.04
228.71	Max Peak	H	100	99	-66.75	-15.21	25.04	46.02	-20.98
300.29	Max Peak	H	100	54	-72.95	-13.34	20.71	46.02	-25.31

Table 7-236. RSE below 1GHz CDD Primary (RU78 – Ch.40), with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 355 of 374



Plot 7-1160. RSE below 1GHz CDD Primary (RU242 – Ch.40), with AC/DC Adapter


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
30.49	Max Peak	V	100	20	-54.65	-18.45	33.90	40.00	-6.10
43.44	Max Peak	V	200	118	-62.39	-14.85	29.76	40.00	-10.24
116.62	Max Peak	H	300	196	-65.06	-17.85	24.09	43.52	-19.43
192.38	Max Peak	H	200	258	-61.26	-16.23	29.51	43.52	-14.01
222.89	Max Peak	H	100	92	-67.32	-15.56	24.12	46.02	-21.90
276.67	Max Peak	H	100	169	-73.33	-14.00	19.67	46.02	-26.35

Table 7-237. RSE below 1GHz CDD Primary (RU242– Ch.40), with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 356 of 374

V 11.0 5/2025

7.7.2 CDD Diversity Radiated Spurious Emissions (Below 1GHz)




Plot 7-1161. RSE below 1GHz CDD Diversity (RU26 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
36.40	Max Peak	V	100	284	-60.13	-17.70	29.17	40.00	-10.83
79.28	Max Peak	V	100	303	-56.22	-22.92	27.86	40.00	-12.14
150.91	Max Peak	H	100	46	-61.42	-21.26	24.32	43.52	-19.20
190.44	Max Peak	H	100	218	-62.08	-18.49	26.43	43.52	-17.09
267.41	Max Peak	H	100	159	-67.90	-16.33	22.77	46.02	-23.25
436.96	Max Peak	V	100	133	-71.93	-12.15	22.92	46.02	-23.10

Table 7-238. RSE below 1GHz CDD Diversity (RU26 – Ch.40), with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 357 of 374


V 11.0 5/2025



Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
51.58	Max Peak	V	100	9	-62.40	-15.45	29.15	40.00	-10.85
80.78	Max Peak	V	100	0	-55.62	-22.70	28.68	40.00	-11.32
105.42	Max Peak	V	300	103	-67.49	-18.16	21.35	43.52	-22.17
171.62	Max Peak	H	100	202	-60.17	-20.27	26.56	43.52	-16.96
264.64	Max Peak	H	100	166	-68.17	-16.29	22.54	46.02	-23.48
614.47	Max Peak	V	300	19	-72.90	-8.90	25.20	46.02	-20.82

Table 7-239. RSE below 1GHz CDD Diversity (RU78 – Ch.40), with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 358 of 374



Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
50.23	Max Peak	V	100	41	-62.16	-15.40	29.44	40.00	-10.56
80.20	Max Peak	V	100	257	-56.16	-22.82	28.02	40.00	-11.98
142.28	Max Peak	H	100	208	-60.07	-21.57	25.36	43.52	-18.16
172.74	Max Peak	H	100	212	-60.28	-20.17	26.55	43.52	-16.97
264.30	Max Peak	H	100	148	-68.74	-16.31	21.95	46.02	-24.07
485.51	Max Peak	V	300	103	-73.49	-11.26	22.25	46.02	-23.77

Table 7-240. RSE below 1GHz CDD Diversity (RU242– Ch.40), with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 359 of 374

V 11.0 5/2025

7.8 AC Line Conducted Emissions Measurement

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. All data rates and modes were investigated for AC Line conducted spurious emissions.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-241. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2020, Subclause 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 360 of 374

V 11.0 5/2025

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-8. Test Instrument & Measurement Setup

Test Notes


- All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
- Both configurations below were investigated, and the worst case has been reported.
 - EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - EUT powered by host PC via USB-C cable with wire charger
- The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
- $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
- $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Correction Factor (dB)}$
- $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
- Traces shown in plots are made using quasi-peak and average detectors.
- Deviations to the Specifications: None.

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 361 of 374

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.8.1 CDD Primary AC Line Conducted Emissions Measurement




Plot 7-1164. AC Line Conducted Plot with 11be UNII Band 1 – RU26 – Ch.40 (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.16	FINAL	---	42.26	55.40	-13.14	L1	GND
0.16	FINAL	53.94	---	65.28	-11.34	L1	GND
0.33	FINAL	---	28.88	49.57	-20.69	L1	GND
0.33	FINAL	42.47	---	59.51	-17.04	L1	GND
1.06	FINAL	---	15.90	46.00	-30.10	L1	GND
1.07	FINAL	30.08	---	56.00	-25.92	L1	GND
2.54	FINAL	---	7.92	46.00	-38.08	L1	GND
2.55	FINAL	18.35	---	56.00	-37.65	L1	GND
4.60	FINAL	30.85	---	56.00	-25.15	L1	GND
4.60	FINAL	---	15.86	46.00	-30.14	L1	GND
24.28	FINAL	---	4.16	50.00	-45.84	L1	GND
24.28	FINAL	10.35	---	60.00	-49.65	L1	GND

Table 7-242. AC Line Conducted with 11be UNII Band 1 – RU26 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 362 of 374

V 11.0 5/2025




Plot 7-1165. AC Line Conducted Plot with 11be UNII Band 1 – RU26 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.16	FINAL	---	40.52	55.40	-14.88	N	GND
0.16	FINAL	52.02	---	65.40	-13.38	N	GND
0.33	FINAL	---	27.06	49.57	-22.51	N	GND
0.33	FINAL	40.53	---	59.57	-19.04	N	GND
0.65	FINAL	34.76	---	56.00	-21.24	N	GND
0.65	FINAL	---	20.32	46.00	-25.68	N	GND
1.52	FINAL	28.93	---	56.00	-27.07	N	GND
1.52	FINAL	---	14.53	46.00	-31.47	N	GND
4.60	FINAL	32.95	---	56.00	-23.05	N	GND
4.60	FINAL	---	20.20	46.00	-25.80	N	GND
16.21	FINAL	---	12.54	50.00	-37.46	N	GND
16.21	FINAL	18.21	---	60.00	-41.79	N	GND

Table 7-243. AC Line Conducted with 11be UNII Band 1 – RU26 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 363 of 374




Plot 7-1166. AC Line Conducted Plot with 11be UNII Band 1 – RU78 – Ch.40 (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.16	FINAL	---	41.99	55.40	-13.41	L1	GND
0.16	FINAL	53.62	---	65.28	-11.66	L1	GND
0.33	FINAL	---	28.76	49.57	-20.81	L1	GND
0.33	FINAL	42.25	---	59.51	-17.26	L1	GND
0.72	FINAL	32.57	---	56.00	-23.43	L1	GND
0.73	FINAL	---	16.86	46.00	-29.14	L1	GND
1.87	FINAL	---	9.88	46.00	-36.12	L1	GND
1.89	FINAL	19.64	---	56.00	-36.36	L1	GND
4.47	FINAL	31.30	---	56.00	-24.70	L1	GND
4.47	FINAL	---	15.79	46.00	-30.21	L1	GND
16.19	FINAL	---	11.48	50.00	-38.52	L1	GND
16.19	FINAL	15.94	---	60.00	-44.06	L1	GND

Table 7-244. AC Line Conducted with 11be UNII Band 1 – RU78 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 364 of 374

V 11.0 5/2025




Plot 7-1167. AC Line Conducted Plot with 11be UNII Band 1 – RU78 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.16	FINAL	---	40.48	55.40	-14.92	N	GND
0.16	FINAL	52.01	---	65.28	-13.27	N	GND
0.41	FINAL	---	25.01	47.72	-22.71	N	GND
0.41	FINAL	38.60	---	57.67	-19.08	N	GND
0.80	FINAL	---	17.48	46.00	-28.52	N	GND
0.80	FINAL	32.50	---	56.00	-23.50	N	GND
1.52	FINAL	29.05	---	56.00	-26.95	N	GND
1.52	FINAL	---	14.72	46.00	-31.28	N	GND
4.71	FINAL	32.97	---	56.00	-23.03	N	GND
4.71	FINAL	---	20.00	46.00	-26.00	N	GND
16.19	FINAL	---	12.50	50.00	-37.50	N	GND
16.20	FINAL	18.04	---	60.00	-41.96	N	GND

Table 7-245. AC Line Conducted with 11be UNII Band 1 – RU78 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 365 of 374




Plot 7-1168. AC Line Conducted Plot with 11be UNII Band 1 – RU242 – Ch.40 (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.16	FINAL	---	39.74	55.40	-15.66	L1	GND
0.16	FINAL	51.34	---	65.28	-13.94	L1	GND
0.49	FINAL	---	22.74	46.13	-23.39	L1	GND
0.49	FINAL	37.09	---	56.13	-19.04	L1	GND
0.90	FINAL	---	14.97	46.00	-31.03	L1	GND
0.90	FINAL	30.48	---	56.00	-25.52	L1	GND
1.72	FINAL	---	10.85	46.00	-35.15	L1	GND
1.73	FINAL	21.39	---	56.00	-34.61	L1	GND
4.50	FINAL	31.68	---	56.00	-24.32	L1	GND
4.50	FINAL	---	16.26	46.00	-29.74	L1	GND
16.19	FINAL	---	11.48	50.00	-38.52	L1	GND
16.19	FINAL	16.13	---	60.00	-43.87	L1	GND

Table 7-246. AC Line Conducted with 11be UNII Band 1 – RU242 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 366 of 374



Plot 7-1169. AC Line Conducted Plot with 11be UNII Band 1 – RU242 – Ch.40 (N) with AC/DC Adapter


Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.16	FINAL	---	42.13	55.40	-13.27	N	GND
0.16	FINAL	53.90	---	65.28	-11.38	N	GND
0.41	FINAL	---	25.93	47.67	-21.74	N	GND
0.41	FINAL	40.05	---	57.67	-17.62	N	GND
0.90	FINAL	---	15.99	46.00	-30.01	N	GND
0.91	FINAL	32.52	---	56.00	-23.48	N	GND
1.96	FINAL	---	13.09	46.00	-32.91	N	GND
1.98	FINAL	24.14	---	56.00	-31.86	N	GND
4.48	FINAL	32.70	---	56.00	-23.30	N	GND
4.49	FINAL	---	19.32	46.00	-26.68	N	GND
16.20	FINAL	---	12.06	50.00	-37.94	N	GND
16.20	FINAL	17.73	---	60.00	-42.27	N	GND

Table 7-247. AC Line Conducted with 11be UNII Band 1 – RU242 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 367 of 374

V 11.0 5/2025

7.8.2 CDD Diversity AC Line Conducted Emissions Measurement




Plot 7-1170. AC Line Conducted Plot with 11be UNII Band 1 – RU26 – Ch.40 (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.16	FINAL	---	43.77	55.28	-11.51	L1	GND
0.16	FINAL	55.02	---	65.28	-10.26	L1	GND
0.57	FINAL	---	23.77	46.00	-22.23	L1	GND
0.57	FINAL	39.05	---	56.00	-16.95	L1	GND
1.32	FINAL	---	18.86	46.00	-27.14	L1	GND
1.32	FINAL	33.18	---	56.00	-22.82	L1	GND
4.82	FINAL	34.18	---	56.00	-21.82	L1	GND
4.82	FINAL	---	19.05	46.00	-26.95	L1	GND
16.04	FINAL	14.90	---	60.00	-45.10	L1	GND
16.04	FINAL	---	10.56	50.00	-39.44	L1	GND
24.05	FINAL	---	2.80	50.00	-47.20	L1	GND
24.05	FINAL	9.31	---	60.00	-50.69	L1	GND

Table 7-248. AC Line Conducted with 11be UNII Band 1 – RU26 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 368 of 374

V 11.0 5/2025




Plot 7-1171. AC Line Conducted Plot with 11be UNII Band 1 – RU26 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.16	FINAL	---	40.13	55.40	-15.27	N	GND
0.16	FINAL	52.52	---	65.40	-12.88	N	GND
0.65	FINAL	---	24.15	46.00	-21.85	N	GND
0.65	FINAL	39.31	---	56.00	-16.69	N	GND
1.94	FINAL	---	14.83	46.00	-31.17	N	GND
1.94	FINAL	26.60	---	56.00	-29.40	N	GND
4.83	FINAL	36.07	---	56.00	-19.93	N	GND
4.83	FINAL	---	23.28	46.00	-22.72	N	GND
16.04	FINAL	18.51	---	60.00	-41.49	N	GND
16.04	FINAL	---	12.81	50.00	-37.19	N	GND
24.06	FINAL	---	1.65	50.00	-48.35	N	GND
24.06	FINAL	7.57	---	60.00	-52.43	N	GND

Table 7-249. AC Line Conducted with 11be UNII Band 1 – RU26 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 369 of 374

V 11.0 5/2025



Plot 7-1172. AC Line Conducted Plot with 11be UNII Band 1 – RU78 – Ch.40 (L1) with AC/DC Adapter


Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.16	FINAL	---	40.69	55.40	-14.71	L1	GND
0.16	FINAL	52.14	---	65.40	-13.26	L1	GND
0.58	FINAL	---	22.89	46.00	-23.11	L1	GND
0.58	FINAL	38.61	---	56.00	-17.39	L1	GND
1.32	FINAL	---	18.37	46.00	-27.63	L1	GND
1.32	FINAL	32.55	---	56.00	-23.45	L1	GND
4.84	FINAL	34.89	---	56.00	-21.11	L1	GND
4.84	FINAL	---	20.07	46.00	-25.93	L1	GND
16.02	FINAL	15.04	---	60.00	-44.96	L1	GND
16.02	FINAL	---	10.41	50.00	-39.59	L1	GND
24.04	FINAL	---	3.46	50.00	-46.54	L1	GND
24.04	FINAL	10.08	---	60.00	-49.92	L1	GND

Table 7-250. AC Line Conducted with 11be UNII Band 1 – RU78 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 370 of 374

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-1173. AC Line Conducted Plot with 11be UNII Band 1 – RU78 – Ch.40 (N) with AC/DC Adapter


Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.16	FINAL	---	39.63	55.40	-15.77	N	GND
0.16	FINAL	51.29	---	65.40	-14.11	N	GND
0.65	FINAL	---	23.49	46.00	-22.51	N	GND
0.65	FINAL	39.16	---	56.00	-16.84	N	GND
1.99	FINAL	---	13.27	46.00	-32.73	N	GND
2.00	FINAL	26.88	---	56.00	-29.12	N	GND
4.85	FINAL	36.25	---	56.00	-19.75	N	GND
4.85	FINAL	---	23.20	46.00	-22.80	N	GND
16.03	FINAL	18.67	---	60.00	-41.33	N	GND
16.03	FINAL	---	13.04	50.00	-36.96	N	GND
24.05	FINAL	---	1.32	50.00	-48.68	N	GND
24.05	FINAL	7.17	---	60.00	-52.83	N	GND

Table 7-251. AC Line Conducted with 11be UNII Band 1 – RU78 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 371 of 374

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-1174. AC Line Conducted Plot with 11be UNII Band 1 – RU242 – Ch.40 (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.16	FINAL	---	40.70	55.40	-14.70	L1	GND
0.16	FINAL	52.19	---	65.40	-13.21	L1	GND
0.65	FINAL	---	22.74	46.00	-23.26	L1	GND
0.65	FINAL	37.78	---	56.00	-18.22	L1	GND
1.99	FINAL	---	9.92	46.00	-36.08	L1	GND
1.99	FINAL	21.28	---	56.00	-34.72	L1	GND
4.83	FINAL	34.62	---	56.00	-21.38	L1	GND
4.83	FINAL	---	19.78	46.00	-26.22	L1	GND
16.01	FINAL	15.10	---	60.00	-44.90	L1	GND
16.01	FINAL	---	10.66	50.00	-39.34	L1	GND
24.02	FINAL	---	3.39	50.00	-46.61	L1	GND
24.02	FINAL	9.74	---	60.00	-50.26	L1	GND

Table 7-252. AC Line Conducted with 11be UNII Band 1 – RU242 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 372 of 374

V 11.0 5/2025



Plot 7-1175. AC Line Conducted Plot with 11be UNII Band 1 – RU242 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.16	FINAL	---	43.57	55.28	-11.71	N	GND
0.16	FINAL	54.84	---	65.28	-10.44	N	GND
0.66	FINAL	---	23.89	46.00	-22.11	N	GND
0.66	FINAL	39.30	---	56.00	-16.70	N	GND
1.99	FINAL	---	13.28	46.00	-32.72	N	GND
1.99	FINAL	26.68	---	56.00	-29.32	N	GND
4.83	FINAL	36.12	---	56.00	-19.88	N	GND
4.83	FINAL	---	22.50	46.00	-23.50	N	GND
16.02	FINAL	18.39	---	60.00	-41.61	N	GND
16.02	FINAL	---	12.69	50.00	-37.31	N	GND
24.03	FINAL	---	0.92	50.00	-49.08	N	GND
24.03	FINAL	6.83	---	60.00	-53.17	N	GND

Table 7-253. AC Line Conducted with 11be UNII Band 1 – RU242 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 373 of 374

V 11.0 5/2025

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device FCC ID: BCGA3358** and **IC: 579C-A3358** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA3358 IC: 579C-A3358		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170039-23-R1.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 374 of 374

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.