



7.9.4 Antenna WF8 Radiated Restricted Band Edge Measurements

Bluetooth Mode: GFSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 0



Plot 7-97. Radiated Restricted Lower Band Edge Measurement Antenna WF8

Bluetooth Mode: 8DPSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 0




Plot 7-98. Radiated Restricted Lower Band Edge Measurement Antenna WF8

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 88 of 109


V 11.0 5/2025

Bluetooth Mode: GFSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 78



Plot 7-99. Radiated Restricted Upper Band Edge Measurement Antenna WF8

Bluetooth Mode: 8DPSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 78




Plot 7-100. Radiated Restricted Upper Band Edge Measurement Antenna WF8

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 89 of 109

V 11.0 5/2025


7.9.5 Antenna WF7 Radiated Restricted Band Edge Measurements

Bluetooth Mode: GFSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 0



Plot 7-101. Radiated Restricted Lower Band Edge Measurement Antenna WF7

Bluetooth Mode: 8DPSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 0




Plot 7-102. Radiated Restricted Lower Band Edge Measurement Antenna WF7

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 90 of 109

V 11.0 5/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Bluetooth Mode: GFSK
Power Scheme: ePA
Measurement Distance: 3 Meters
Operating Frequency: 2480MHz
Channel: 78



Plot 7-103. Radiated Restricted Upper Band Edge Measurement Antenna WF7

Bluetooth Mode: 8DPSK
Power Scheme: ePA
Measurement Distance: 3 Meters
Operating Frequency: 2480MHz
Channel: 78



Plot 7-104. Radiated Restricted Upper Band Edge Measurement Antenna WF7


FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 91 of 109

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


7.9.6 Antenna WF9 Radiated Restricted Band Edge Measurements

Bluetooth Mode: GFSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 0



Plot 7-105. Radiated Restricted Lower Band Edge Measurement Antenna WF9

Bluetooth Mode: 8DPSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 0




Plot 7-106. Radiated Restricted Lower Band Edge Measurement Antenna WF9

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 92 of 109

V 11.0 5/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Bluetooth Mode: GFSK
Power Scheme: ePA
Measurement Distance: 3 Meters
Operating Frequency: 2480MHz
Channel: 78



Plot 7-107. Radiated Restricted Upper Band Edge Measurement Antenna WF9

Bluetooth Mode: 8DPSK
Power Scheme: ePA
Measurement Distance: 3 Meters
Operating Frequency: 2480MHz
Channel: 78




Plot 7-108. Radiated Restricted Upper Band Edge Measurement Antenna WF9

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 93 of 109

V 11.0 5/2025


7.9.7 TxBF Primary Radiated Restricted Band Edge Measurements

Bluetooth Mode: GFSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 0



Plot 7-109. Radiated Restricted Lower Band Edge Measurement TxBF Primary

Bluetooth Mode: 8DPSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 0




Plot 7-110. Radiated Restricted Lower Band Edge Measurement TxBF Primary

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 94 of 109

V 11.0 5/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Bluetooth Mode: GFSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 78



Plot 7-111. Radiated Restricted Upper Band Edge Measurement TxBF Primary

Bluetooth Mode: 8DPSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 78




Plot 7-112. Radiated Restricted Upper Band Edge Measurement TxBF Primary

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 95 of 109

V 11.0 5/2025


7.9.8 TxBF Diversity Radiated Restricted Band Edge Measurements

Bluetooth Mode: GFSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 0



Plot 7-113. Radiated Restricted Lower Band Edge Measurement TxBF Diversity

Bluetooth Mode: 8DPSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 0




Plot 7-114. Radiated Restricted Lower Band Edge Measurement TxBF Diversity

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 96 of 109

V 11.0 5/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Bluetooth Mode: GFSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 78



Plot 7-115. Radiated Restricted Upper Band Edge Measurement TxBF Diversity

Bluetooth Mode: 8DPSK
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 78



Plot 7-116. Radiated Restricted Upper Band Edge Measurement TxBF Diversity

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 97 of 109

V 11.0 5/2025

7.10 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-29 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-29. Radiated Limits

Test Procedures Used

ANSI C63.10-2020

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 98 of 109

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-9. Radiated Test Setup < 30MHz




Figure 7-10. Radiated Test Setup < 1GHz

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device		Page 99 of 109

V 11.0 5/2025

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-29.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector on emissions that were within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.
10. All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.
11. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger


Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]} - \text{Preamplifier Gain }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 100 of 109

7.10.1 TxBF Radiated Spurious Emissions Measurements (Below 1GHz)



Plot 7-117. Radiated Spurious Emissions Below 1GHz TxBF Primary (GFSK ePA – Ch.39, with AC/DC Adapter)

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
46.30	Max Peak	V	100	11	-62.15	-15.39	29.46	40.00	-10.54
79.37	Max Peak	V	100	7	-58.41	-22.91	25.68	40.00	-14.32
142.08	Max Peak	H	300	64	-60.03	-21.58	25.39	43.52	-18.13
193.35	Max Peak	H	100	226	-61.40	-18.03	27.57	43.52	-15.95
267.65	Max Peak	H	100	197	-69.87	-16.32	20.81	46.02	-25.21
417.18	Max Peak	V	100	356	-72.71	-12.37	21.92	46.02	-24.10


Table 7-30. Radiated Measurements Below 1GHz TxBF Primary (GFSK ePA – Ch.39, with AC/DC Adapter)

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 101 of 109

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.10.2 TxBF Diversity Radiated Spurious Emissions Measurements (Below 1GHz)



Plot 7-118. Radiated Spurious Emissions Below 1GHz TxBF Diversity (GFSK ePA – Ch.39, with AC/DC Adapter)

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
34.22	Max Peak	V	100	0	-59.73	-18.77	28.50	40.00	-11.50
53.28	Max Peak	V	100	79	-62.73	-15.63	28.64	40.00	-11.36
105.56	Max Peak	H	300	145	-67.02	-18.17	21.81	43.52	-21.71
173.95	Max Peak	H	100	222	-59.59	-20.11	27.30	43.52	-16.22
277.88	Max Peak	H	100	90	-70.29	-16.05	20.66	46.02	-25.36
509.18	Max Peak	V	300	210	-73.01	-10.96	23.03	46.02	-22.99

Table 7-31. Radiated Measurements Below 1GHz TxBF Diversity (GFSK ePA – Ch.39, with AC/DC Adapter)

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 102 of 109

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.11 AC Line-Conducted Emissions Measurement

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-32. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2020, Section 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 103 of 109

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-11. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
2. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
3. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen (8.8).
4. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
5. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Correction Factor (dB)}$
6. $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
7. Traces shown in plot are made using a quasi peak and average detectors.
8. Deviations to the Specifications: None.

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 104 of 109

V 11.0 5/2025



Plot 7-119. AC Line-Conducted Test Plot TxBF Primary (L1, GFSK ePA – Ch.39, with AC/DC Adapter)


Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.164	FINAL	—	40.91	55.28	-14.37	L1	GND
0.164	FINAL	51.5	—	65.28	-13.78	L1	GND
0.886	FINAL	—	21.27	46.00	-24.73	L1	GND
0.886	FINAL	35.6	—	56.00	-20.37	L1	GND
1.986	FINAL	—	10.63	46.00	-35.37	L1	GND
1.986	FINAL	21.2	—	56.00	-34.76	L1	GND
4.756	FINAL	34.8	—	56.00	-21.25	L1	GND
4.756	FINAL	—	19.46	46.00	-26.54	L1	GND
16.006	FINAL	15.2	—	60.00	-44.84	L1	GND
16.006	FINAL	—	10.65	50.00	-39.35	L1	GND
24.005	FINAL	—	3.65	50.00	-46.35	L1	GND
24.005	FINAL	10.0	—	60.00	-50.02	L1	GND

Table 7-33. AC Line-Conducted Test Data TxBF Primary (L1, GFSK ePA – Ch.39, with AC/DC Adapter)

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 105 of 109

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-120. AC Line-Conducted Test Plot TxBF Primary (N, GFSK ePA – Ch.39, with AC/DC Adapter)


Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.164	FINAL	—	43.74	55.28	-11.55	N	GND
0.164	FINAL	55.0	—	65.28	-10.27	N	GND
0.654	FINAL	—	24.58	46.00	-21.42	N	GND
0.654	FINAL	39.5	—	56.00	-16.48	N	GND
1.988	FINAL	—	13.20	46.00	-32.80	N	GND
1.988	FINAL	27.3	—	56.00	-28.67	N	GND
4.848	FINAL	36.5	—	56.00	-19.53	N	GND
4.848	FINAL	—	22.86	46.00	-23.14	N	GND
16.008	FINAL	18.7	—	60.00	-41.30	N	GND
16.008	FINAL	—	13.00	50.00	-37.00	N	GND
24.014	FINAL	—	1.09	50.00	-48.91	N	GND
24.014	FINAL	7.1	—	60.00	-52.92	N	GND

Table 7-34. AC Line-Conducted Test Data TxBF Primary (N, GFSK ePA – Ch.39, with AC/DC Adapter)

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 106 of 109

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-121. AC Line-Conducted Test Plot TxBF Diversity (L1, GFSK ePA – Ch.39, with AC/DC Adapter)


Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.161	FINAL	—	40.72	55.40	-14.68	L1	GND
0.161	FINAL	52.1	—	65.40	-13.31	L1	GND
0.650	FINAL	—	23.89	46.00	-22.11	L1	GND
0.650	FINAL	39.4	—	56.00	-16.65	L1	GND
1.991	FINAL	—	13.08	46.00	-32.92	L1	GND
1.991	FINAL	27.4	—	56.00	-28.59	L1	GND
4.859	FINAL	35.3	—	56.00	-20.66	L1	GND
4.859	FINAL	—	22.65	46.00	-23.35	L1	GND
16.008	FINAL	19.3	—	60.00	-40.72	L1	GND
16.008	FINAL	—	13.80	50.00	-36.20	L1	GND
24.011	FINAL	—	1.62	50.00	-48.38	L1	GND
24.011	FINAL	8.0	—	60.00	-52.05	L1	GND

Table 7-35. AC Line-Conducted Test Data TxBF Diversity (L1, GFSK ePA – Ch.39, with AC/DC Adapter)

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 107 of 109

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-122. AC Line-Conducted Test Plot TxBF Diversity (N, GFSK ePA – Ch.39, with AC/DC Adapter)

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.161	FINAL	—	39.39	55.40	-16.01	N	GND
0.161	FINAL	50.7	—	65.40	-14.66	N	GND
0.654	FINAL	—	22.99	46.00	-23.01	N	GND
0.654	FINAL	37.8	—	56.00	-18.17	N	GND
1.977	FINAL	—	11.10	46.00	-34.90	N	GND
1.977	FINAL	20.9	—	56.00	-35.12	N	GND
4.785	FINAL	32.9	—	56.00	-23.12	N	GND
4.785	FINAL	—	18.75	46.00	-27.25	N	GND
16.015	FINAL	14.0	—	60.00	-45.97	N	GND
16.015	FINAL	—	8.70	50.00	-41.30	N	GND
24.023	FINAL	—	3.35	50.00	-46.65	N	GND
24.023	FINAL	9.7	—	60.00	-50.26	N	GND

Table 7-36. AC Line-Conducted Test Data TxBF Diversity (N, GFSK ePA – Ch.39, with AC/DC Adapter)

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 108 of 109

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Apple Tablet Device**
FCC ID: BCGA3360 and IC: 579C-A3360 is in compliance with Part 15 Subpart C (15.247) of the FCC Rules and
RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-09.BCG	Test Dates: 05/12/2025 - 09/02/2025	EUT Type: Tablet Device	Page 109 of 109

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.