


7.8.5 Antenna WF7 Radiated Band Edge Measurements


\$15.407(b.1)(b.2) \$15.205 \$15.209

Mode	BDR
Power Scheme	ePA
Distance of Measurement	3 Meters
Operating Frequency	6106MHz



Plot 7-457 Radiated Lower Band Edge Measurement Antenna WF7


Mode	LE1M
Power Scheme	ePA
Distance of Measurement	3 Meters
Operating Frequency	6106MHz



Plot 7-458 Radiated Lower Band Edge Measurement Antenna WF7


FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 288 of 329

Mode LE2M
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6106MHz



Plot 7-459 Radiated Lower Band Edge Measurement Antenna WF7


Mode HDR4
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6106MHz



Plot 7-460 Radiated Lower Band Edge Measurement Antenna WF7


FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 289 of 329

Mode HDR8
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6107MHz



Plot 7-461 Radiated Lower Band Edge Measurement Antenna WF7


Mode XHDRPS2
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6106MHz



Plot 7-462 Radiated Lower Band Edge Measurement Antenna WF7


FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 290 of 329

Mode XHDRPM8
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6107MHz



Plot 7-463 Radiated Lower Band Edge Measurement Antenna WF7


Mode XHDRPM16
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6107MHz



Plot 7-464 Radiated Lower Band Edge Measurement Antenna WF7


FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 291 of 329

Mode XHDRPL16
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6109MHz



Plot 7-465 Radiated Lower Band Edge Measurement Antenna WF7


Mode XHDRPL32
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6109MHz



Plot 7-466 Radiated Lower Band Edge Measurement Antenna WF7

FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 292 of 329

Mode	HDT8
Power Scheme	ePA
Distance of Measurement	3 Meters
Operating Frequency	6106MHz



Plot 7-467 Radiated Lower Band Edge Measurement Antenna WF7

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 293 of 329


© Apple Inc. Apple Inc.

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Material Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.8.6 TxBF Primary Radiated Band Edge Measurements


§15.407(b.1)(b.2) §15.205 §15.209

Mode	BDR
Power Scheme	ePA
Distance of Measurement	3 Meters
Operating Frequency	6106MHz



Plot 7-468 Radiated Lower Band Edge Measurement TxBF Primary


Mode	LE1M
Power Scheme	ePA
Distance of Measurement	3 Meters
Operating Frequency	6106MHz



Plot 7-469 Radiated Lower Band Edge Measurement TxBF Primary


FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 294 of 329

Mode LE2M
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6106MHz



Plot 7-470 Radiated Lower Band Edge Measurement TxBF Primary


Mode HDR4
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6106MHz



Plot 7-471 Radiated Lower Band Edge Measurement TxBF Primary


FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 295 of 329

Mode HDR8
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6107MHz



Plot 7-472 Radiated Lower Band Edge Measurement TxBF Primary


Mode XHDRPS2
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6106MHz



Plot 7-473 Radiated Lower Band Edge Measurement TxBF Primary


FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 296 of 329

Mode XHDRPM8
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6107MHz



Plot 7-474 Radiated Lower Band Edge Measurement TxBF Primary


Mode XHDRPM16
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6107MHz



Plot 7-475 Radiated Lower Band Edge Measurement TxBF Primary


FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 297 of 329

Mode XHDRPL16
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6109MHz



Plot 7-476 Radiated Lower Band Edge Measurement TxBF Primary


Mode XHDRPL32
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6109MHz



Plot 7-477 Radiated Lower Band Edge Measurement TxBF Primary

FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 298 of 329

Mode	HDT8
Power Scheme	ePA
Distance of Measurement	3 Meters
Operating Frequency	6106MHz



Plot 7-478 Radiated Lower Band Edge Measurement TxBF Primary

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 299 of 329


© Apple Inc. Apple Inc.

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Material Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.8.7 TxBF Diversity Radiated Band Edge Measurements


§15.407(b.1)(b.2) §15.205 §15.209

Mode	BDR
Power Scheme	ePA
Distance of Measurement	3 Meters
Operating Frequency	6106MHz



Plot 7-479 Radiated Lower Band Edge Measurement TxBF Diversity


Mode	LE1M
Power Scheme	ePA
Distance of Measurement	3 Meters
Operating Frequency	6106MHz



Plot 7-480 Radiated Lower Band Edge Measurement TxBF Diversity


FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 300 of 329

Mode LE2M
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6106MHz



Plot 7-481 Radiated Lower Band Edge Measurement TxBF Diversity


Mode HDR4
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6106MHz



Plot 7-482 Radiated Lower Band Edge Measurement TxBF Diversity


FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 301 of 329

Mode HDR8
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6107MHz



Plot 7-483 Radiated Lower Band Edge Measurement TxBF Diversity


Mode XHDRPS2
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6106MHz



Plot 7-484 Radiated Lower Band Edge Measurement TxBF Diversity


FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 302 of 329

Mode XHDRPM8
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6107MHz



Plot 7-485 Radiated Lower Band Edge Measurement TxBF Diversity


Mode XHDRPM16
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6107MHz



Plot 7-486 Radiated Lower Band Edge Measurement TxBF Diversity


FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 303 of 329

Mode XHDRPL16
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6109MHz



Plot 7-487 Radiated Lower Band Edge Measurement TxBF Diversity


Mode XHDRPL32
Power Scheme ePA
Distance of Measurement 3 Meters
Operating Frequency 6109MHz



Plot 7-488 Radiated Lower Band Edge Measurement TxBF Diversity

FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 304 of 329

Mode	HDT8
Power Scheme	ePA
Distance of Measurement	3 Meters
Operating Frequency	6106MHz



Plot 7-489 Radiated Lower Band Edge Measurement TxBF Diversity

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 305 of 329

© Apple Inc. Apple Inc.

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Material Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.9 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 must not exceed the limits shown in Table 7-44 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-44. Radiated Limits

Test Procedures Used

ANSI C63.10-2020

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 306 of 329

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-9. Radiated Test Setup < 30MHz




Figure 7-10. Radiated Test Setup < 1GHz

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 307 of 329

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-44.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector for emissions within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. All supported modulation and power schemes have been tested on the unit and only worst case configuration is reported.
10. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC Adapter to USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
11. The unit was tested with all possible modes and only the highest emission is reported.

Sample Calculations


Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]} - \text{Preamplifier Gain}_{[dB]}$
- $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$

FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 308 of 329

7.9.1 TxBF Primary Radiated Spurious Emissions (Below 1GHz)

\$15.209




Plot 7-490. Radiated Spurious Emissions Below 1GHz TxBF Primary (NB UNII BDR ePA – 6263MHz), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
37.32	Max-Peak	V	100	353	-61.38	-17.39	28.23	40.00	-11.77
79.33	Max-Peak	V	100	280	-56.33	-22.92	27.75	40.00	-12.25
107.02	Max-Peak	H	200	268	-66.71	-18.19	22.10	43.52	-21.42
190.15	Max-Peak	H	100	243	-62.48	-18.55	25.97	43.52	-17.55
241.70	Max-Peak	H	100	309	-66.14	-16.63	24.23	46.02	-21.79
423.09	Max-Peak	H	200	176	-72.84	-12.37	21.79	46.02	-24.23

Table 7-45. Radiated Spurious Emissions Below 1GHz TxBF Primary (NB UNII BDR ePA – 6263MHz), with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 309 of 329




Plot 7-491. Radiated Spurious Emissions Below 1GHz TxBF Primary (NB UNII HDR4 ePA – 6263MHz), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
37.37	Max-Peak	V	100	339	-61.74	-17.37	27.89	40.00	-12.11
78.65	Max-Peak	V	100	272	-56.81	-22.90	27.29	40.00	-12.71
142.81	Max-Peak	H	200	199	-59.92	-21.54	25.54	43.52	-17.98
190.00	Max-Peak	H	100	256	-62.15	-18.58	26.27	43.52	-17.25
242.19	Max-Peak	H	100	296	-66.74	-16.62	23.64	46.02	-22.38
347.24	Max-Peak	H	200	322	-72.64	-13.71	20.65	46.02	-25.37

Table 7-46. Radiated Spurious Emissions Below 1GHz TxBF Primary (NB UNII HDR4 ePA – 6263MHz), with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 310 of 329




Plot 7-492. Radiated Spurious Emissions Below 1GHz TxBF Primary (NB UNII LE1M ePA – 6263MHz), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
36.74	Max-Peak	V	100	352	-61.07	-17.57	28.36	40.00	-11.64
77.92	Max-Peak	V	100	258	-56.68	-22.80	27.52	40.00	-12.48
142.04	Max-Peak	H	200	197	-56.65	-21.58	28.77	43.52	-14.75
190.00	Max-Peak	H	100	234	-61.72	-18.58	26.70	43.52	-16.82
242.33	Max-Peak	H	100	293	-66.18	-16.61	24.21	46.02	-21.81
599.63	Max-Peak	V	200	20	-73.87	-8.68	24.45	46.02	-21.57

Table 7-47. Radiated Spurious Emissions Below 1GHz TxBF Primary (NB UNII LE1M ePA – 6263MHz), with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 311 of 329

7.9.2 TxBF Diversity Radiated Spurious Emissions (Below 1GHz)




Plot 7-493. Radiated Spurious Emissions Below 1GHz TxBF Diversity (NB UNII BDR ePA – 6263MHz), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
37.13	Max-Peak	V	100	357	-61.02	-17.44	28.54	40.00	-11.46
79.71	Max-Peak	V	100	279	-57.19	-22.88	26.93	40.00	-13.07
142.47	Max-Peak	H	200	237	-59.95	-21.56	25.49	43.52	-18.03
185.10	Max-Peak	H	200	207	-62.85	-19.17	24.98	43.52	-18.54
240.10	Max-Peak	H	100	292	-67.55	-16.63	22.82	46.02	-23.20
337.98	Max-Peak	H	100	331	-73.00	-14.06	19.94	46.02	-26.08

Table 7-48. Radiated Spurious Emissions Below 1GHz TxBF Diversity (NB UNII BDR ePA – 6263MHz), with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 312 of 329




Plot 7-494. Radiated Spurious Emissions Below 1GHz TxBF Diversity (NB UNII HDR4 ePA – 6263MHz), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
36.45	Max-Peak	V	100	313	-60.57	-17.69	28.74	40.00	-11.26
77.53	Max-Peak	V	100	273	-56.13	-22.74	28.13	40.00	-11.87
137.14	Max-Peak	H	300	211	-59.16	-21.37	26.47	43.52	-17.05
197.52	Max-Peak	H	100	273	-63.57	-17.59	25.84	43.52	-17.68
244.90	Max-Peak	H	100	153	-66.94	-16.61	23.45	46.02	-22.57
306.79	Max-Peak	H	100	137	-69.88	-15.44	21.68	46.02	-24.34

Table 7-49. Radiated Spurious Emissions Below 1GHz TxBF Diversity (NB UNII HDR4 ePA – 6263MHz), with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 313 of 329



Plot 7-495. Radiated Spurious Emissions Below 1GHz TxBF Diversity (NB UNII LE1M ePA – 6263MHz), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
51.05	Max-Peak	V	100	2	-62.74	-15.40	28.86	40.00	-11.14
79.08	Max-Peak	V	100	247	-56.75	-22.93	27.32	40.00	-12.68
105.42	Max-Peak	V	100	158	-66.96	-18.16	21.88	43.52	-21.64
152.12	Max-Peak	H	200	188	-60.59	-21.10	25.31	43.52	-18.21
266.05	Max-Peak	H	100	167	-67.61	-16.37	23.02	46.02	-23.00
421.01	Max-Peak	H	200	6	-73.18	-12.36	21.46	46.02	-24.56

Table 7-50. Radiated Spurious Emissions Below 1GHz TxBF Diversity (NB UNII LE1M ePA – 6263MHz), with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 314 of 329

7.10 AC Line Conducted Emissions Measurement

§15.207; RSS-Gen[8.8]

Test Overview and Limit

All AC line conducted emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted emissions. All data rates and modes were investigated for AC Line conducted emissions.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-51. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2020, Subclause 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 315 of 329

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-11. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated, and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
2. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC Adapter to USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
3. The limit for an intentional radiator from 150kHz to 30MHz is specified in 15.207 and RSS-Gen (8.8).
4. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
5. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Correction Factor (dB)}$
6. $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
7. Traces shown in plots are made using quasi-peak and average detectors.
8. Deviations to the Specifications: None.
9. The unit was tested with all possible modes and only the highest emission is reported.

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 316 of 329

7.10.1 TxBF Primary AC Line Conducted Emissions Measurement




Plot 7-496. AC Line Conducted Plot TxBF Primary (NB UNII BDR ePA – 6263MHz) (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.164	FINAL	—	35.97	55.28	-19.31	L1	GND
0.164	FINAL	50.5	—	65.28	-14.79	L1	GND
0.904	FINAL	—	20.84	46.00	-25.16	L1	GND
0.904	FINAL	34.7	—	56.00	-21.31	L1	GND
2.945	FINAL	—	11.30	46.00	-34.70	L1	GND
2.945	FINAL	21.6	—	56.00	-34.42	L1	GND
4.918	FINAL	34.5	—	56.00	-21.54	L1	GND
4.918	FINAL	—	20.95	46.00	-25.05	L1	GND
15.970	FINAL	16.4	—	60.00	-43.57	L1	GND
15.970	FINAL	—	11.49	50.00	-38.51	L1	GND
23.960	FINAL	—	0.90	50.00	-49.10	L1	GND
23.960	FINAL	6.9	—	60.00	-53.09	L1	GND

Table 7-52. AC Line Conducted Data TxBF Primary (NB UNII BDR ePA – 6263MHz) (L1) with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 317 of 329	




Plot 7-497. AC Line Conducted Plot TxBF Primary (NB UNII BDR ePA – 6263MHz) (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.168	FINAL	—	35.42	55.06	-19.64	N	GND
0.168	FINAL	49.3	—	65.06	-15.81	N	GND
0.670	FINAL	—	22.61	46.00	-23.39	N	GND
0.670	FINAL	36.3	—	56.00	-19.69	N	GND
2.011	FINAL	—	10.46	46.00	-35.54	N	GND
2.011	FINAL	20.3	—	56.00	-35.66	N	GND
4.974	FINAL	32.7	—	56.00	-23.33	N	GND
4.974	FINAL	—	18.29	46.00	-27.71	N	GND
15.977	FINAL	15.2	—	60.00	-44.77	N	GND
15.977	FINAL	—	9.56	50.00	-40.44	N	GND
23.964	FINAL	—	3.90	50.00	-46.10	N	GND
23.964	FINAL	10.2	—	60.00	-49.82	N	GND

Table 7-53. AC Line Conducted TxBF Primary (NB UNII BDR ePA – 6263MHz) (N) with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 318 of 329




Plot 7-498. AC Line Conducted Plot TxBF Primary (NB UNII HDR4 ePA – 6263MHz) (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.166	FINAL	---	38.51	55.17	-16.66	L1	GND
0.166	FINAL	51.4	---	65.17	-13.77	L1	GND
0.573	FINAL	---	21.93	46.00	-24.07	L1	GND
0.573	FINAL	37.5	---	56.00	-18.47	L1	GND
2.378	FINAL	---	12.33	46.00	-33.67	L1	GND
2.378	FINAL	22.8	---	56.00	-33.22	L1	GND
4.940	FINAL	34.7	---	56.00	-21.28	L1	GND
4.940	FINAL	---	21.03	46.00	-24.97	L1	GND
15.972	FINAL	16.5	---	60.00	-43.55	L1	GND
15.972	FINAL	---	11.35	50.00	-38.65	L1	GND
23.957	FINAL	---	0.88	50.00	-49.12	L1	GND
23.957	FINAL	6.7	---	60.00	-53.35	L1	GND

Table 7-54. AC Line Conducted Data TxBF Primary (NB UNII HDR4 ePA – 6263MHz) (L1) with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 319 of 329	




Plot 7-499. AC Line Conducted Plot TxBF Primary (NB UNII HDR4 ePA – 6263MHz) (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.166	FINAL	---	36.62	55.17	-18.55	N	GND
0.166	FINAL	49.6	---	65.17	-15.56	N	GND
0.584	FINAL	---	21.41	46.00	-24.59	N	GND
0.584	FINAL	36.9	---	56.00	-19.11	N	GND
2.373	FINAL	---	10.51	46.00	-35.49	N	GND
2.373	FINAL	19.9	---	56.00	-36.13	N	GND
4.956	FINAL	32.9	---	56.00	-23.06	N	GND
4.956	FINAL	---	18.74	46.00	-27.26	N	GND
15.974	FINAL	15.1	---	60.00	-44.93	N	GND
15.974	FINAL	---	9.52	50.00	-40.48	N	GND
23.960	FINAL	---	3.65	50.00	-46.35	N	GND
23.960	FINAL	10.1	---	60.00	-49.92	N	GND

Table 7-55. AC Line Conducted TxBF Primary (NB UNII HDR4 ePA – 6263MHz) (N) with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 320 of 329	




Plot 7-500. AC Line Conducted Plot TxBF Primary (NB UNII LE1M ePA – 6263MHz) (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.166	FINAL	---	35.42	55.17	-19.75	L1	GND
0.166	FINAL	49.4	---	65.17	-15.73	L1	GND
0.656	FINAL	---	21.52	46.00	-24.48	L1	GND
0.656	FINAL	36.5	---	56.00	-19.48	L1	GND
2.378	FINAL	---	11.59	46.00	-34.41	L1	GND
2.378	FINAL	22.0	---	56.00	-33.96	L1	GND
4.945	FINAL	34.1	---	56.00	-21.91	L1	GND
4.945	FINAL	---	20.56	46.00	-25.44	L1	GND
15.954	FINAL	16.2	---	60.00	-43.84	L1	GND
15.954	FINAL	---	10.47	50.00	-39.53	L1	GND
23.935	FINAL	---	0.82	50.00	-49.18	L1	GND
23.935	FINAL	6.9	---	60.00	-53.06	L1	GND

Table 7-56. AC Line Conducted Data TxBF Primary (NB UNII LE1M ePA – 6263MHz) (L1) with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 321 of 329




Plot 7-501. AC Line Conducted Plot TxBF Primary (NB UNII LE1M ePA – 6263MHz) (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.164	FINAL	---	37.62	55.28	-17.67	N	GND
0.164	FINAL	52.0	---	65.28	-13.31	N	GND
0.654	FINAL	---	20.72	46.00	-25.28	N	GND
0.654	FINAL	36.5	---	56.00	-19.46	N	GND
2.378	FINAL	---	11.10	46.00	-34.90	N	GND
2.378	FINAL	20.7	---	56.00	-35.27	N	GND
5.026	FINAL	32.5	---	60.00	-27.55	N	GND
5.026	FINAL	---	18.38	50.00	-31.62	N	GND
15.961	FINAL	14.7	---	60.00	-45.32	N	GND
15.961	FINAL	---	9.14	50.00	-40.86	N	GND
23.944	FINAL	---	3.56	50.00	-46.44	N	GND
23.944	FINAL	9.9	---	60.00	-50.14	N	GND

Table 7-57. AC Line Conducted TxBF Primary (NB UNII LE1M ePA – 6263MHz) (N) with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 322 of 329

7.10.2 TxBF Diversity AC Line Conducted Emissions Measurement




Plot 7-502. AC Line Conducted Plot TxBF Diversity (NB UNII BDR ePA – 6263MHz) (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.166	FINAL	—	41.33	55.17	-13.84	L1	GND
0.166	FINAL	53.5	—	65.17	-11.64	L1	GND
0.659	FINAL	—	22.55	46.00	-23.45	L1	GND
0.659	FINAL	37.4	—	56.00	-18.64	L1	GND
2.378	FINAL	—	12.62	46.00	-33.38	L1	GND
2.378	FINAL	23.4	—	56.00	-32.65	L1	GND
4.911	FINAL	34.2	—	56.00	-21.78	L1	GND
4.911	FINAL	—	20.49	46.00	-25.51	L1	GND
15.970	FINAL	16.3	—	60.00	-43.74	L1	GND
15.970	FINAL	—	11.57	50.00	-38.43	L1	GND
23.955	FINAL	—	1.51	50.00	-48.49	L1	GND
23.955	FINAL	7.4	—	60.00	-52.56	L1	GND

Table 7-58. AC Line Conducted Data TxBF Diversity (NB UNII BDR ePA – 6263MHz) (L1) with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 323 of 329




Plot 7-503. AC Line Conducted Plot TxBF Diversity (NB UNII BDR ePA – 6263MHz) (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.166	FINAL	—	38.20	55.17	-16.97	N	GND
0.166	FINAL	50.8	—	65.17	-14.42	N	GND
0.659	FINAL	—	21.49	46.00	-24.51	N	GND
0.659	FINAL	36.6	—	56.00	-19.39	N	GND
2.380	FINAL	—	10.64	46.00	-35.36	N	GND
2.380	FINAL	20.5	—	56.00	-35.52	N	GND
4.954	FINAL	33.1	—	56.00	-22.95	N	GND
4.954	FINAL	—	18.77	46.00	-27.23	N	GND
15.977	FINAL	14.7	—	60.00	-45.28	N	GND
15.977	FINAL	—	9.23	50.00	-40.77	N	GND
23.962	FINAL	—	3.74	50.00	-46.26	N	GND
23.962	FINAL	10.2	—	60.00	-49.84	N	GND

Table 7-59. AC Line Conducted TxBF Diversity (NB UNII BDR ePA – 6263MHz) (N) with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 324 of 329	




Plot 7-504. AC Line Conducted Plot TxBF Diversity (NB UNII HDR4 ePA – 6263MHz) (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.166	FINAL	---	38.28	55.17	-16.89	L1	GND
0.166	FINAL	50.4	---	65.17	-14.74	L1	GND
0.668	FINAL	---	22.55	46.00	-23.45	L1	GND
0.668	FINAL	36.9	---	56.00	-19.07	L1	GND
2.384	FINAL	---	12.10	46.00	-33.90	L1	GND
2.384	FINAL	23.1	---	56.00	-32.90	L1	GND
5.055	FINAL	34.4	---	60.00	-25.61	L1	GND
5.055	FINAL	---	20.77	50.00	-29.23	L1	GND
15.970	FINAL	16.7	---	60.00	-43.31	L1	GND
15.970	FINAL	---	11.74	50.00	-38.26	L1	GND
23.953	FINAL	---	1.37	50.00	-48.63	L1	GND
23.953	FINAL	7.4	---	60.00	-52.60	L1	GND

Table 7-60. AC Line Conducted Data TxBF Diversity (NB UNII HDR4 ePA – 6263MHz) (L1) with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 325 of 329




Plot 7-505. AC Line Conducted Plot TxBF Diversity (NB UNII HDR4 ePA – 6263MHz) (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.166	FINAL	---	36.75	55.17	-18.42	N	GND
0.166	FINAL	49.2	---	65.17	-15.93	N	GND
0.746	FINAL	---	19.21	46.00	-26.79	N	GND
0.746	FINAL	35.1	---	56.00	-20.94	N	GND
2.384	FINAL	---	10.19	46.00	-35.81	N	GND
2.384	FINAL	20.2	---	56.00	-35.79	N	GND
5.062	FINAL	32.6	---	60.00	-27.37	N	GND
5.062	FINAL	---	18.32	50.00	-31.68	N	GND
15.974	FINAL	15.0	---	60.00	-45.05	N	GND
15.974	FINAL	---	9.47	50.00	-40.53	N	GND
23.960	FINAL	---	4.08	50.00	-45.92	N	GND
23.960	FINAL	10.5	---	60.00	-49.48	N	GND

Table 7-61. AC Line Conducted TxBF Diversity (NB UNII HDR4 ePA – 6263MHz) (N) with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 326 of 329




Plot 7-506. AC Line Conducted Plot TxBF Diversity (NB UNII LE1M ePA – 6263MHz) (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.166	FINAL	---	34.45	55.17	-20.72	L1	GND
0.166	FINAL	48.2	---	65.17	-16.97	L1	GND
0.661	FINAL	---	22.37	46.00	-23.63	L1	GND
0.661	FINAL	36.8	---	56.00	-19.20	L1	GND
2.130	FINAL	---	8.68	46.00	-37.32	L1	GND
2.130	FINAL	21.5	---	56.00	-34.53	L1	GND
4.963	FINAL	33.3	---	56.00	-22.67	L1	GND
4.963	FINAL	---	19.87	46.00	-26.13	L1	GND
15.956	FINAL	16.3	---	60.00	-43.67	L1	GND
15.956	FINAL	---	11.57	50.00	-38.43	L1	GND
23.933	FINAL	---	0.79	50.00	-49.21	L1	GND
23.933	FINAL	7.2	---	60.00	-52.83	L1	GND

Table 7-62. AC Line Conducted Data TxBF Diversity (NB UNII LE1M ePA – 6263MHz) (L1) with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 327 of 329	



Plot 7-507. AC Line Conducted Plot TxBF Diversity (NB UNII LE1M ePA – 6263MHz) (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.164	FINAL	---	38.49	55.28	-16.80	N	GND
0.164	FINAL	52.1	---	65.28	-13.18	N	GND
0.582	FINAL	---	22.56	46.00	-23.44	N	GND
0.582	FINAL	37.5	---	56.00	-18.51	N	GND
2.378	FINAL	---	11.11	46.00	-34.89	N	GND
2.378	FINAL	21.1	---	56.00	-34.86	N	GND
5.035	FINAL	32.8	---	60.00	-27.18	N	GND
5.035	FINAL	---	18.35	50.00	-31.65	N	GND
15.961	FINAL	14.4	---	60.00	-45.59	N	GND
15.961	FINAL	---	8.92	50.00	-41.08	N	GND
23.944	FINAL	---	3.58	50.00	-46.42	N	GND
23.944	FINAL	9.8	---	60.00	-50.16	N	GND

Table 7-63. AC Line Conducted TxBF Diversity (NB UNII LE1M ePA – 6263MHz) (N) with AC/DC Adapter

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 328 of 329

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device FCC ID: BCGA3360** and **IC: 579C-A3360** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-248 of the Innovation, Science and Economic Development Canada Rules..

FCC ID: BCGA3360 IC: 579C-A3360		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2504170040-11-R3.BCG	Test Dates: 05/12/2025 - 08/13/2025	EUT Type: Tablet Device	Page 329 of 329