



| Test Configuration       |                                                                 |                 |                |
|--------------------------|-----------------------------------------------------------------|-----------------|----------------|
| Frequency Range:         | 2400-2483.5 MHz                                                 | Band:           | 2.4 GHz        |
| Limit Clause(s):         | 15.247 (e)<br>RSS-247 6.3.1                                     | Test Method(s): | C63.10 11.10.5 |
| Additional Reference(s): | 662911 D01 v02r01 E)2)b)                                        |                 |                |
| Note(s):                 | DCCF was added to the spectrum analyser reference level offset. |                 |                |

| DUT Configuration         |                                        |                          |      |
|---------------------------|----------------------------------------|--------------------------|------|
| Mode:                     | 802.11be EHT20 RU Size 52 + RU Size 26 | Duty Cycle (%):          | 97.8 |
| Modulation Coding Scheme: | MCS2x1                                 | DCCF (dB):               | 0.10 |
| Antenna Configuration:    | MIMO CDD                               | Peak Antenna Gain (dBi): | 7.22 |
| Active Port(s):           | A+B (Core 0 + Core 1)                  | Active Chain(s):         | 0+1  |

| Test Frequency (MHz)              | RBW (kHz) | PSD (dBm/RBW) |        |   |   |          | Limit (dBm/3 kHz) | Margin (dB) |
|-----------------------------------|-----------|---------------|--------|---|---|----------|-------------------|-------------|
|                                   |           | A             | B      | C | D | $\Sigma$ |                   |             |
| 2412 (RU Size 52 + RU Size 26.70) | 100.0     | 1.43          | 0.77   | - | - | 4.12     | 6.78              | -2.66       |
| 2442 (RU Size 52 + RU Size 26.70) | 100.0     | 0.31          | -0.15  | - | - | 3.10     | 6.78              | -3.68       |
| 2472 (RU Size 52 + RU Size 26.70) | 100.0     | -19.37        | -19.40 | - | - | -16.37   | 6.78              | -23.15      |

**Table 175 - FCC Maximum Power Spectral Density Results**

| Test Frequency (MHz)              | RBW (kHz) | PSD (dBm/3 kHz) |        |   |   |          | Limit (dBm) | Margin (dB) |
|-----------------------------------|-----------|-----------------|--------|---|---|----------|-------------|-------------|
|                                   |           | A               | B      | C | D | $\Sigma$ |             |             |
| 2412 (RU Size 52 + RU Size 26.70) | 100.0     | 1.43            | 0.77   | - | - | 4.12     | 8.00        | -3.88       |
| 2442 (RU Size 52 + RU Size 26.70) | 100.0     | 0.31            | -0.15  | - | - | 3.10     | 8.00        | -4.90       |
| 2472 (RU Size 52 + RU Size 26.70) | 100.0     | -19.37          | -19.40 | - | - | -16.37   | 8.00        | -24.37      |

**Table 176 - ISED Maximum Power Spectral Density Results**



| Test Configuration       |                                                                 |                 |                |
|--------------------------|-----------------------------------------------------------------|-----------------|----------------|
| Frequency Range:         | 2400-2483.5 MHz                                                 | Band:           | 2.4 GHz        |
| Limit Clause(s):         | 15.247 (e)<br>RSS-247 6.3.1                                     | Test Method(s): | C63.10 11.10.5 |
| Additional Reference(s): | 662911 D01 v02r01 E)2)b)                                        |                 |                |
| Note(s):                 | DCCF was added to the spectrum analyser reference level offset. |                 |                |

| DUT Configuration         |                       |                          |      |
|---------------------------|-----------------------|--------------------------|------|
| Mode:                     | 802.11n HT20          | Duty Cycle (%):          | 99.1 |
| Modulation Coding Scheme: | MCS10                 | DCCF (dB):               | 0.04 |
| Antenna Configuration:    | MIMO SDM              | Peak Antenna Gain (dBi): | 4.22 |
| Active Port(s):           | A+B (Core 0 + Core 1) | Active Chain(s):         | 0+1  |

| Test Frequency (MHz) | RBW (kHz) | PSD (dBm/RBW) |        |   |   |          | Limit (dBm/3 kHz) | Margin (dB) |
|----------------------|-----------|---------------|--------|---|---|----------|-------------------|-------------|
|                      |           | A             | B      | C | D | $\Sigma$ |                   |             |
| 2412                 | 100.0     | -4.03         | -4.27  | - | - | -1.14    | 8.00              | -9.14       |
| 2432                 | 51.0      | -0.20         | -0.35  | - | - | 2.74     | 8.00              | -5.26       |
| 2442                 | 100.0     | 0.67          | 0.44   | - | - | 3.57     | 8.00              | -4.43       |
| 2472                 | 100.0     | -14.54        | -14.74 | - | - | -11.63   | 8.00              | -19.63      |

**Table 177 - Maximum Power Spectral Density Results**



| Test Configuration       |                                                                 |                 |                |
|--------------------------|-----------------------------------------------------------------|-----------------|----------------|
| Frequency Range:         | 2400-2483.5 MHz                                                 | Band:           | 2.4 GHz        |
| Limit Clause(s):         | 15.247 (e)<br>RSS-247 6.3.1                                     | Test Method(s): | C63.10 11.10.5 |
| Additional Reference(s): | 662911 D01 v02r01 E)2)b)                                        |                 |                |
| Note(s):                 | DCCF was added to the spectrum analyser reference level offset. |                 |                |

| DUT Configuration         |                       |                          |      |
|---------------------------|-----------------------|--------------------------|------|
| Mode:                     | 802.11ax HE20 SU      | Duty Cycle (%):          | 99.1 |
| Modulation Coding Scheme: | MCS2x2                | DCCF (dB):               | 0.04 |
| Antenna Configuration:    | MIMO SDM              | Peak Antenna Gain (dBi): | 4.22 |
| Active Port(s):           | A+B (Core 0 + Core 1) | Active Chain(s):         | 0+1  |

| Test Frequency (MHz) | RBW (kHz) | PSD (dBm/RBW) |        |   |   |          | Limit (dBm/3 kHz) | Margin (dB) |
|----------------------|-----------|---------------|--------|---|---|----------|-------------------|-------------|
|                      |           | A             | B      | C | D | $\Sigma$ |                   |             |
| 2412                 | 100.0     | -6.39         | -6.61  | - | - | -3.49    | 8.00              | -11.49      |
| 2432                 | 100.0     | 1.03          | 0.69   | - | - | 3.87     | 8.00              | -4.13       |
| 2442                 | 100.0     | -0.18         | -0.20  | - | - | 2.82     | 8.00              | -5.18       |
| 2472                 | 100.0     | -16.31        | -16.54 | - | - | -13.41   | 8.00              | -21.41      |

**Table 178 - Maximum Power Spectral Density Results**



| Test Configuration       |                                                                 |                 |                |
|--------------------------|-----------------------------------------------------------------|-----------------|----------------|
| Frequency Range:         | 2400-2483.5 MHz                                                 | Band:           | 2.4 GHz        |
| Limit Clause(s):         | 15.247 (e)<br>RSS-247 6.3.1                                     | Test Method(s): | C63.10 11.10.5 |
| Additional Reference(s): | 662911 D01 v02r01 E)2)b)                                        |                 |                |
| Note(s):                 | DCCF was added to the spectrum analyser reference level offset. |                 |                |

| DUT Configuration         |                       |                          |      |
|---------------------------|-----------------------|--------------------------|------|
| Mode:                     | 802.11ax HE20 RU26    | Duty Cycle (%):          | 98.8 |
| Modulation Coding Scheme: | MCS2x2                | DCCF (dB):               | 0.05 |
| Antenna Configuration:    | MIMO SDM              | Peak Antenna Gain (dBi): | 4.22 |
| Active Port(s):           | A+B (Core 0 + Core 1) | Active Chain(s):         | 0+1  |

| Test Frequency (MHz) | RBW (kHz) | PSD (dBm/RBW) |        |   |   |          | Limit (dBm/3 kHz) | Margin (dB) |
|----------------------|-----------|---------------|--------|---|---|----------|-------------------|-------------|
|                      |           | A             | B      | C | D | $\Sigma$ |                   |             |
| 2412 (RU26.0)        | 100.0     | 0.88          | 0.21   | - | - | 3.57     | 8.00              | -4.43       |
| 2442 (RU26.0)        | 100.0     | 0.74          | 0.22   | - | - | 3.50     | 8.00              | -4.50       |
| 2472 (RU26.8)        | 100.0     | -17.40        | -17.44 | - | - | -14.41   | 8.00              | -22.41      |

**Table 179 - Maximum Power Spectral Density Results**



| Test Configuration       |                                                                 |                 |                |
|--------------------------|-----------------------------------------------------------------|-----------------|----------------|
| Frequency Range:         | 2400-2483.5 MHz                                                 | Band:           | 2.4 GHz        |
| Limit Clause(s):         | 15.247 (e)<br>RSS-247 6.3.1                                     | Test Method(s): | C63.10 11.10.5 |
| Additional Reference(s): | 662911 D01 v02r01 E)2)b)                                        |                 |                |
| Note(s):                 | DCCF was added to the spectrum analyser reference level offset. |                 |                |

| DUT Configuration         |                       |                          |      |
|---------------------------|-----------------------|--------------------------|------|
| Mode:                     | 802.11ax HE20 RU52    | Duty Cycle (%):          | 98.9 |
| Modulation Coding Scheme: | MCS2x2                | DCCF (dB):               | 0.05 |
| Antenna Configuration:    | MIMO SDM              | Peak Antenna Gain (dBi): | 4.22 |
| Active Port(s):           | A+B (Core 0 + Core 1) | Active Chain(s):         | 0+1  |

| Test Frequency (MHz) | RBW (kHz) | PSD (dBm/RBW) |        |   |   |          | Limit (dBm/3 kHz) | Margin (dB) |
|----------------------|-----------|---------------|--------|---|---|----------|-------------------|-------------|
|                      |           | A             | B      | C | D | $\Sigma$ |                   |             |
| 2412 (RU52.37)       | 100.0     | 1.32          | 0.57   | - | - | 3.97     | 8.00              | -4.03       |
| 2442 (RU52.37)       | 100.0     | 1.23          | 0.56   | - | - | 3.92     | 8.00              | -4.08       |
| 2472 (RU52.40)       | 100.0     | -17.16        | -17.50 | - | - | -14.32   | 8.00              | -22.32      |

**Table 180 - Maximum Power Spectral Density Results**



| Test Configuration       |                                                                 |                 |                |
|--------------------------|-----------------------------------------------------------------|-----------------|----------------|
| Frequency Range:         | 2400-2483.5 MHz                                                 | Band:           | 2.4 GHz        |
| Limit Clause(s):         | 15.247 (e)<br>RSS-247 6.3.1                                     | Test Method(s): | C63.10 11.10.5 |
| Additional Reference(s): | 662911 D01 v02r01 E)2)b)                                        |                 |                |
| Note(s):                 | DCCF was added to the spectrum analyser reference level offset. |                 |                |

| DUT Configuration         |                       |                          |      |
|---------------------------|-----------------------|--------------------------|------|
| Mode:                     | 802.11ax HE20 RU106   | Duty Cycle (%):          | 98.9 |
| Modulation Coding Scheme: | MCS2x2                | DCCF (dB):               | 0.05 |
| Antenna Configuration:    | MIMO SDM              | Peak Antenna Gain (dBi): | 4.22 |
| Active Port(s):           | A+B (Core 0 + Core 1) | Active Chain(s):         | 0+1  |

| Test Frequency (MHz) | RBW (kHz) | PSD (dBm/RBW) |        |   |   |          | Limit (dBm/3 kHz) | Margin (dB) |
|----------------------|-----------|---------------|--------|---|---|----------|-------------------|-------------|
|                      |           | A             | B      | C | D | $\Sigma$ |                   |             |
| 2412 (RU106.53)      | 100.0     | 0.05          | -0.42  | - | - | 2.83     | 8.00              | -5.17       |
| 2442 (RU106.53)      | 100.0     | 1.27          | 0.89   | - | - | 4.09     | 8.00              | -3.91       |
| 2472 (RU106.54)      | 100.0     | -19.06        | -19.32 | - | - | -16.18   | 8.00              | -24.18      |

**Table 181 - Maximum Power Spectral Density Results**



| Test Configuration       |                                                                 |                 |                |
|--------------------------|-----------------------------------------------------------------|-----------------|----------------|
| Frequency Range:         | 2400-2483.5 MHz                                                 | Band:           | 2.4 GHz        |
| Limit Clause(s):         | 15.247 (e)<br>RSS-247 6.3.1                                     | Test Method(s): | C63.10 11.10.5 |
| Additional Reference(s): | 662911 D01 v02r01 E)2)b)                                        |                 |                |
| Note(s):                 | DCCF was added to the spectrum analyser reference level offset. |                 |                |

| DUT Configuration         |                                         |                          |      |
|---------------------------|-----------------------------------------|--------------------------|------|
| Mode:                     | 802.11be EHT20 RU Size 106 + RU Size 26 | Duty Cycle (%):          | 97.8 |
| Modulation Coding Scheme: | MCS2x2                                  | DCCF (dB):               | 0.10 |
| Antenna Configuration:    | MIMO SDM                                | Peak Antenna Gain (dBi): | 4.22 |
| Active Port(s):           | A+B (Core 0 + Core 1)                   | Active Chain(s):         | 0+1  |

| Test Frequency (MHz)               | RBW (kHz) | PSD (dBm/RBW) |        |   |   |          | Limit (dBm/3 kHz) | Margin (dB) |
|------------------------------------|-----------|---------------|--------|---|---|----------|-------------------|-------------|
|                                    |           | A             | B      | C | D | $\Sigma$ |                   |             |
| 2412 (RU Size 106 + RU Size 26.82) | 100.0     | -1.09         | -1.00  | - | - | 1.97     | 8.00              | -6.03       |
| 2442 (RU Size 106 + RU Size 26.82) | 100.0     | 0.71          | 0.38   | - | - | 3.56     | 8.00              | -4.44       |
| 2472 (RU Size 106 + RU Size 26.83) | 100.0     | -19.62        | -19.86 | - | - | -16.73   | 8.00              | -24.73      |

**Table 182 - Maximum Power Spectral Density Results**



| Test Configuration       |                                                                 |                 |                |
|--------------------------|-----------------------------------------------------------------|-----------------|----------------|
| Frequency Range:         | 2400-2483.5 MHz                                                 | Band:           | 2.4 GHz        |
| Limit Clause(s):         | 15.247 (e)<br>RSS-247 6.3.1                                     | Test Method(s): | C63.10 11.10.5 |
| Additional Reference(s): | 662911 D01 v02r01 E)2)b)                                        |                 |                |
| Note(s):                 | DCCF was added to the spectrum analyser reference level offset. |                 |                |

| DUT Configuration         |                                        |                          |      |
|---------------------------|----------------------------------------|--------------------------|------|
| Mode:                     | 802.11be EHT20 RU Size 52 + RU Size 26 | Duty Cycle (%):          | 97.8 |
| Modulation Coding Scheme: | MCS2x2                                 | DCCF (dB):               | 0.10 |
| Antenna Configuration:    | MIMO SDM                               | Peak Antenna Gain (dBi): | 4.22 |
| Active Port(s):           | A+B (Core 0 + Core 1)                  | Active Chain(s):         | 0+1  |

| Test Frequency (MHz)              | RBW (kHz) | PSD (dBm/RBW) |        |   |   |        | Limit (dBm/3 kHz) | Margin (dB) |
|-----------------------------------|-----------|---------------|--------|---|---|--------|-------------------|-------------|
|                                   |           | A             | B      | C | D | Σ      |                   |             |
| 2412 (RU Size 52 + RU Size 26.70) | 100.0     | 1.13          | 0.65   | - | - | 3.91   | 8.00              | -4.09       |
| 2442 (RU Size 52 + RU Size 26.70) | 100.0     | 0.59          | 0.31   | - | - | 3.46   | 8.00              | -4.54       |
| 2472 (RU Size 52 + RU Size 26.72) | 100.0     | -18.84        | -19.22 | - | - | -16.01 | 8.00              | -24.01      |

**Table 183 - Maximum Power Spectral Density Results**



| Test Configuration       |                                                                 |                 |                |
|--------------------------|-----------------------------------------------------------------|-----------------|----------------|
| Frequency Range:         | 2400-2483.5 MHz                                                 | Band:           | 2.4 GHz        |
| Limit Clause(s):         | 15.247 (e)<br>RSS-247 6.3.1                                     | Test Method(s): | C63.10 11.10.5 |
| Additional Reference(s): | 662911 D01 v02r01 E)2)b)                                        |                 |                |
| Note(s):                 | DCCF was added to the spectrum analyser reference level offset. |                 |                |

| DUT Configuration         |                       |                          |      |
|---------------------------|-----------------------|--------------------------|------|
| Mode:                     | 802.11ac VHT20        | Duty Cycle (%):          | 99.0 |
| Modulation Coding Scheme: | MCS2x1                | DCCF (dB):               | 0.04 |
| Antenna Configuration:    | TxBF                  | Peak Antenna Gain (dBi): | 7.22 |
| Active Port(s):           | A+B (Core 0 + Core 1) | Active Chain(s):         | 0+1  |

| Test Frequency (MHz) | RBW (kHz) | PSD (dBm/RBW) |        |   |   |          | Limit (dBm/3 kHz) | Margin (dB) |
|----------------------|-----------|---------------|--------|---|---|----------|-------------------|-------------|
|                      |           | A             | B      | C | D | $\Sigma$ |                   |             |
| 2412                 | 100.0     | -6.53         | -6.73  | - | - | -3.62    | 6.78              | -10.40      |
| 2432                 | 100.0     | 0.42          | 0.44   | - | - | 3.44     | 6.78              | -3.34       |
| 2442                 | 100.0     | -1.31         | -1.30  | - | - | 1.71     | 6.78              | -5.07       |
| 2472                 | 100.0     | -17.18        | -17.27 | - | - | -14.21   | 6.78              | -20.99      |

**Table 184 - FCC Maximum Power Spectral Density Results**

| Test Frequency (MHz) | RBW (kHz) | PSD (dBm/3 kHz) |        |   |   |          | Limit (dBm) | Margin (dB) |
|----------------------|-----------|-----------------|--------|---|---|----------|-------------|-------------|
|                      |           | A               | B      | C | D | $\Sigma$ |             |             |
| 2412                 | 100.0     | -6.53           | -6.73  | - | - | -3.62    | 8.00        | -11.62      |
| 2432                 | 100.0     | 0.42            | 0.44   | - | - | 3.44     | 8.00        | -4.56       |
| 2442                 | 100.0     | -1.31           | -1.30  | - | - | 1.71     | 8.00        | -6.29       |
| 2472                 | 100.0     | -17.18          | -17.27 | - | - | -14.21   | 8.00        | -22.21      |

**Table 185 - ISED Maximum Power Spectral Density Results**



| Test Configuration       |                                                                 |                 |                |
|--------------------------|-----------------------------------------------------------------|-----------------|----------------|
| Frequency Range:         | 2400-2483.5 MHz                                                 | Band:           | 2.4 GHz        |
| Limit Clause(s):         | 15.247 (e)<br>RSS-247 6.3.1                                     | Test Method(s): | C63.10 11.10.5 |
| Additional Reference(s): | 662911 D01 v02r01 E)2)b)                                        |                 |                |
| Note(s):                 | DCCF was added to the spectrum analyser reference level offset. |                 |                |

| DUT Configuration         |                       |                          |      |
|---------------------------|-----------------------|--------------------------|------|
| Mode:                     | 802.11ax HE20 SU      | Duty Cycle (%):          | 99.0 |
| Modulation Coding Scheme: | MCS2x1                | DCCF (dB):               | 0.04 |
| Antenna Configuration:    | TxBF                  | Peak Antenna Gain (dBi): | 7.22 |
| Active Port(s):           | A+B (Core 0 + Core 1) | Active Chain(s):         | 0+1  |

| Test Frequency (MHz) | RBW (kHz) | PSD (dBm/RBW) |        |   |   |          | Limit (dBm/3 kHz) | Margin (dB) |
|----------------------|-----------|---------------|--------|---|---|----------|-------------------|-------------|
|                      |           | A             | B      | C | D | $\Sigma$ |                   |             |
| 2412                 | 100.0     | -8.02         | -8.47  | - | - | -5.23    | 6.78              | -12.01      |
| 2437                 | 100.0     | -0.41         | -0.42  | - | - | 2.60     | 6.78              | -4.19       |
| 2442                 | 100.0     | -1.96         | -2.39  | - | - | 0.84     | 6.78              | -5.94       |
| 2472                 | 100.0     | -18.11        | -18.30 | - | - | -15.20   | 6.78              | -21.98      |

**Table 186 - FCC Maximum Power Spectral Density Results**

| Test Frequency (MHz) | RBW (kHz) | PSD (dBm/3 kHz) |        |   |   |          | Limit (dBm) | Margin (dB) |
|----------------------|-----------|-----------------|--------|---|---|----------|-------------|-------------|
|                      |           | A               | B      | C | D | $\Sigma$ |             |             |
| 2412                 | 100.0     | -8.02           | -8.47  | - | - | -5.23    | 8.00        | -13.23      |
| 2437                 | 100.0     | -0.41           | -0.42  | - | - | 2.60     | 8.00        | -5.40       |
| 2442                 | 100.0     | -1.96           | -2.39  | - | - | 0.84     | 8.00        | -7.16       |
| 2472                 | 100.0     | -18.11          | -18.30 | - | - | -15.20   | 8.00        | -23.20      |

**Table 187 - ISED Maximum Power Spectral Density Results**



FCC 47 CFR Part 15, Limit Clause 15.247 (e)

The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

ISED RSS-247, Limit Clause 6.3.1

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission

**2.6.7 Test Location and Test Equipment Used**

This test was carried out in EMC Laboratory 2.

| Instrument                     | Manufacturer          | Type No.        | TE No. | Calibration Period (months) | Calibration Expiry Date |
|--------------------------------|-----------------------|-----------------|--------|-----------------------------|-------------------------|
| Multimeter                     | Iso-tech              | IDM101          | 2421   | 12                          | 11-Nov-2026             |
| Hygrometer                     | Rotronic              | HP21            | 4741   | 12                          | 29-May-2026             |
| AC Programmable Power Supply   | iTech                 | IT7324          | 5226   | -                           | O/P Mon                 |
| MXA Signal Analyser            | Keysight Technologies | N9020B          | 5528   | 24                          | 10-Sep-2027             |
| Modular Power System Mainframe | Keysight Technologies | N6701C          | 5835   | -                           | TU                      |
| DC Power Module 60V 20A 300W   | Keysight Technologies | N6754A          | 5836   | -                           | O/P Mon                 |
| Signal Conditioning Unit       | TUV SUD               | SPECTRUM_SCU001 | 6350   | 12                          | 02-Sep-2026             |
| SCU Cable Assembly             | TUV SUD               | SPECTRUM_SCU_CA | 6638   | 12                          | 29-Aug-2026             |
| SCU Cable Assembly             | TUV SUD               | SPECTRUM_SCU_CA | 6639   | 12                          | 29-Aug-2026             |
| SCU Cable Assembly             | TUV SUD               | SPECTRUM_SCU_CA | 7137   | 12                          | 29-Aug-2026             |

**Table 188**

TU - Traceability Unscheduled

O/P Mon - Output Monitored using calibrated equipment



### 3 Measurement Uncertainty

For a 95% confidence level, the measurement uncertainties for defined systems are:

| Test Name                      | Measurement Uncertainty                                        |
|--------------------------------|----------------------------------------------------------------|
| Restricted Band Edges          | 30 MHz to 1 GHz: $\pm 5.2$ dB<br>1 GHz to 40 GHz: $\pm 6.3$ dB |
| Emission Bandwidth             | $\pm 349.29$ kHz                                               |
| Maximum Conducted Output Power | Method PM: $\pm 0.65$ dB<br>Method SA: $\pm 1.05$ dB           |
| Authorised Band Edges          | 30 MHz to 1 GHz: $\pm 5.2$ dB<br>1 GHz to 40 GHz: $\pm 6.3$ dB |
| Spurious Radiated Emissions    | 30 MHz to 1 GHz: $\pm 5.2$ dB<br>1 GHz to 40 GHz: $\pm 6.3$ dB |
| Power Spectral Density         | $\pm 1.00$ dB                                                  |

**Table 189**

#### Measurement Uncertainty Decision Rule – Accuracy Method

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115:2021, Clause 4.4.3 (Procedure 2). The measurement results are directly compared with the test limit to determine conformance with the requirements of the standard.

Risk: The uncertainty of measurement about the measured result is negligible with regard to the final pass/fail decision. The measurement result can be directly compared with the test limit to determine conformance with the requirement (compare IEC Guide 115). The level of risk to falsely accept and falsely reject items is further described in ILAC-G8.