

FCC and ISED Test Report

Apple Inc
Model: A3428



In accordance with FCC 47 CFR Part 15B and
ICES-003 and ISED RSS-GEN

Prepared for: Apple Inc
One Apple Park Way
Cupertino
California
95014
USA

TUV SUD
SERVICES
(UK) LIMITED

Digitally signed by
TUV SUD SERVICES
(UK) LIMITED
Date: 2026.01.07
09:46:29 Z

FCC ID: BCGA3428

IC: 579C-A3428

COMMERCIAL-IN-CONFIDENCE



Document 75963993-11 Issue 01

SIGNATURE

NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Andrew Lawson	Chief Engineer, EMC	Authorised Signatory	07 January 2026

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD document control rules.

ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC 47 CFR Part 15B and ICES-003 and ISED RSS-GEN. The sample tested was found to comply with the requirements defined in the applied rules.

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Testing	Sreemon Jayachandran Nair	07 January 2026	
	Matthew Dawkins	07 January 2026	

FCC Accreditation

492497/UK2010 Octagon House, Fareham Test Laboratory

ISED Accreditation

12669A/UK0003 Octagon House, Fareham Test Laboratory

EXECUTIVE SUMMARY

A sample of this product was tested and found to be compliant with FCC 47 CFR Part 15B, ICES-003 and ISED RSS-GEN: 2024, Issue 7: 2020 and Issue 5 and A2 (2021-02) for the tests detailed in section 1.3.



DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD. No part of this document may be reproduced without the prior written approval of TÜV SÜD. © 2026 TÜV SÜD. This report relates only to the actual item/items tested.

ACCREDITATION

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation. Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited). Results of tests covered by our Flexible UKAS Accreditation Schedule are marked FS (Flexible Scope).

TÜV SÜD
is a trading name of TÜV SÜD Ltd
Registered in Scotland at East Kilbride,
Glasgow G75 0QF, United Kingdom
Registered number: SC215164

TÜV SÜD Ltd is a
TÜV SÜD Group Company

Phone: +44 (0) 1489 558100
Fax: +44 (0) 1489 558101
www.tuvsud.com/en

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire PO15 5RL
United Kingdom



Contents

1	Report Summary	2
1.1	Report Modification Record.....	2
1.2	Introduction.....	2
1.3	Brief Summary of Results	3
1.4	Product Information	4
1.5	Deviations from the Standard.....	4
1.6	Identification of the EUT	5
1.7	EUT Modification Record	5
1.8	Test Location	5
2	Test Details	6
2.1	Conducted Emissions, AC Power Port.....	6
2.2	Radiated Emissions.....	11
3	Test Equipment Information	20
3.1	General Test Equipment Used	20
4	Incident Reports	21
5	Measurement Uncertainty	22



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
1	First Issue	07-Jan-2026

Table 1

1.2 Introduction

Applicant	Apple Inc
Manufacturer	Apple Inc
EUT/Sample Identification	Refer to section 1.6
Test Specification/Issue/Date	FCC 47 CFR Part 15B: 2024 ICES-003, Issue 7: 2020 ISED RSS-GEN, Issue 5, A2 (2021-02)
Start of Test	21-November-2025
Finish of Test	04-December-2025
Name of Engineer(s)	Sreemon Jayachandran Nair and Matthew Dawkins
Related Document(s)	ANSI C63.4: 2014



1.3 Brief Summary of Results

A brief summary of the tests carried out in accordance with FCC 47 CFR Part 15B, and ICES-003 and ISED RSS-GEN is shown below.

Section	Specification Clause	Test Description	Result	Comments/Base Standard
Configuration and Mode: AC Powered - Transmitter Idle				
2.1	15.107, 3.2.1 and 4.4	Conducted Emissions, AC Power Port	Pass	ANSI C63.4: 2014
2.2	15.109, 3.2.2 and 4.4	Radiated Emissions	Pass	ANSI C63.4: 2014

Table 2



1.4 Product Information

1.4.1 Technical Description

The equipment under test (EUT) was a portable laptop computer.

1.4.2 EUT Port/Cable Identification

Port	Max Cable Length specified	Usage	Type	Screened
Configuration and Mode: AC Powered - Transmitters Idle				
AC Power Port	2 m	Main Power	AC to DC Power Adapter with USB-C output.	No
USB Port 1	1.5 m	Power/Data	USB Type-C	Yes
USB Port 2	1.5 m	Power/Data	USB Type-C	Yes
USB Port 3	1.5 m	Power/Data	USB Type-C	Yes
HDMI Port	1.5 m	Display out.	HDMI	No
Audio Jack Port	1 m	Analogue Audio Output	3.5 mm Jack	No

Table 3

1.4.3 Test Configuration

Configuration	Description
AC Powered	The EUT was powered from a 115 V 60 Hz AC supply using an AC to DC adapter with USB-C output and MagSafe cable. PSU Model: A2452 The EUT had the following connections made: • A keyboard was used to terminate USB Port 1. • USB Port 2 was unterminated. • USB Port 3 was unterminated. • A set of headphones were used to terminate the Audio Jack Port. • A monitor was used to terminate the HDMI port.

Table 4

1.4.4 Modes of Operation

Mode	Description
Transmitter Idle	The EUT was powered with all internal transmitters disabled.

Table 5

1.5 Deviations from the Standard

No deviations from the applicable test standard were made during testing.



1.6 Identification of the EUT

The table below details identification of the EUT(s) that have been used to carry out the testing within this report.

Serial Number	Hardware Version	Software Version
G7T22C0MXX	REV1.0	25D53

Table 6

1.7 EUT Modification Record

The table below details modifications made to the EUT during the test programme.

The modifications incorporated during each test are recorded on the appropriate test pages.

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
Model: A3428, Serial Number: G7T22C0MXX			
0	As supplied by the customer	Not Applicable	Not Applicable

Table 7

1.8 Test Location

TÜV SÜD conducted the following tests at our Octagon House Test Laboratory.

Test Name	Name of Engineer(s)	Accreditation
Configuration and Mode: AC Powered - Transmitter Idle		
Conducted Emissions, AC Power Port	Matthew Dawkins	UKAS
Radiated Emissions	Sreemon Jayachandran Nair	UKAS

Table 8

Office Address:

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire
PO15 5RL
United Kingdom



2 Test Details

2.1 Conducted Emissions, AC Power Port

2.1.1 Specification Reference

FCC 47 CFR Part 15B, ICES-003 and ISSED RSS-GEN, Clause 15.107, 3.2.1 and 4.4

2.1.2 Equipment Under Test and Modification State

A3428, S/N: G7T22C0MXX - Modification State 0

2.1.3 Date of Test

21-November-2025

2.1.4 Test Method

The EUT was setup according to ANSI C63.4, clause 5.2.

The EUT was placed on a non-conductive table 0.8 m above a reference ground plane. A vertical coupling plane was placed 0.4 m from the EUT boundary

A Line Impedance Stabilisation Network (LISN) was directly bonded to the ground-plane. The EUT was located so that the distance between the boundary of the EUT and the closest surface of the LISN was 0.8 m.

Interconnecting cables that hanged closer than 0.4 m to the ground plane were folded back and forth in the centre forming a bundle 0.3 m to 0.4 m long.

Input and output cables were terminated with equipment or loads representative of real usage conditions.

The EUT was configured to give the highest level of emissions within reason of a typical installation as described by the manufacturer.

A Peak detector pre-scan of the EUT emissions profile was measured across the appropriate frequency range.

Where all pre-scan peak emissions measured were greater than 20 dB below the CISPR Average test limit, no final measurements were made in accordance with ANSI C63.4.

Where any pre-scan peak emissions were within 20 dB of the CISPR Average test limit, the six highest pre-scan emissions seen across the frequency range were measured for at least 15 seconds using a Peak, Quasi-Peak or CISPR Average detector as appropriate to the test limit being measured against.

2.1.5 Example Calculation

Quasi-Peak level (dB μ V) = Receiver level (dB μ V) + Correction Factor (dB)
Margin (dB) = Quasi-Peak level (dB μ V) - Limit (dB μ V)

CISPR Average level (dB μ V) = Receiver level (dB μ V) + Correction Factor (dB)
Margin (dB) = CISPR Average level (dB μ V) - Limit (dB μ V)



2.1.6 Example Test Setup Diagram




Figure 1 - Conducted Emissions Example Test Setup

2.1.7 Environmental Conditions

Ambient Temperature 18.9 °C
Relative Humidity 42.7 %
Atmospheric Pressure 1003.0 mbar

2.1.8 Specification Limits

Required Specification Limits - Class B			
Line Under Test	Frequency Range (MHz)	Quasi-Peak Test Limit (dBμV)	CISPR Average Test Limit (dBμV)
AC Power Port	0.15 to 0.5	66 to 56 ⁽¹⁾	56 to 46 ⁽¹⁾
	0.5 to 5	56	46
	5 to 30	60	50
Supplementary information: Note 1. Decreases with the logarithm of the frequency.			

Table 9

2.1.9 Test Results

Results for Configuration and Mode: AC Powered - Transmitter Idle.

This test was performed to the requirements of the Class B limits.

Performance assessment of the EUT made during this test: Pass.

Detailed results are shown below.




Figure 2 - Graphical Results - AC Power Port - Live

Frequency (MHz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
0.150	49.06	66.00	-16.94	Q-Peak
0.150	35.57	56.00	-20.43	CISPR Avg
0.168	45.60	65.10	-19.50	Q-Peak
0.168	24.14	55.10	-30.96	CISPR Avg
0.195	38.78	63.80	-25.02	Q-Peak
0.195	22.60	53.80	-31.20	CISPR Avg
0.217	37.49	62.90	-25.41	Q-Peak
0.217	32.87	52.90	-20.03	CISPR Avg
0.452	27.64	56.80	-29.16	Q-Peak
0.452	17.67	46.80	-29.13	CISPR Avg
16.995	39.21	60.00	-20.79	Q-Peak
16.995	26.24	50.00	-23.76	CISPR Avg

Table 10




Figure 3 - Graphical Results - AC Power Port - Neutral

Frequency (MHz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
0.159	45.88	65.50	-19.62	Q-Peak
0.159	40.21	55.50	-15.29	CISPR Avg
0.231	33.36	62.40	-29.04	Q-Peak
0.231	20.24	52.40	-32.16	CISPR Avg
0.303	29.56	60.20	-30.64	Q-Peak
0.303	16.72	50.20	-33.48	CISPR Avg
0.469	29.10	56.50	-27.40	Q-Peak
0.469	20.92	46.50	-25.58	CISPR Avg
0.789	27.71	56.00	-28.29	Q-Peak
0.789	18.29	46.00	-27.71	CISPR Avg
17.156	45.52	60.00	-14.48	Q-Peak
17.156	26.47	50.00	-23.53	CISPR Avg

Table 11



2.1.10 Test Location and Test Equipment Used

This test was carried out in EMC Chamber 12.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
3m Semi-Anechoic Chamber	MVG	EMC Chamber 12	5621	36	07-Aug-2026
Emissions Software	TUV SUD	EmX V3.5.5	5125	-	Software
Test Receiver	Rohde & Schwarz	ESW44	5382	12	09-Oct-2026
Transient Limiter	Hewlett Packard	11947A	1032	12	16-Jan-2026
Cable (N-Type to N-Type, 2 m)	Teledyne	269-0078-2000	3325	12	12-Sep-2026
Cable (N-Type to N-Type, 8 m)	Junkosha	MWX221-08000NMSNMS/B	7054	12	01-Jun-2026
LISN (CISPR 16, Single Phase)	Rohde & Schwarz	ESH3-Z5	1390	12	04-Feb-2026
Thermo-Hygro-Barometer	PCE Instruments	PCE-THB-40	5471	12	14-May-2026

Table 12



2.2 Radiated Emissions

2.2.1 Specification Reference

FCC 47 CFR Part 15B, ICES-003 and ISSED RSS-GEN, Clause 15.109, 3.2.2 and 4.4

2.2.2 Equipment Under Test and Modification State

A3428, S/N: G7T22C0MXX - Modification State 0

2.2.3 Date of Test

24-November-2025 to 04-December-2025

2.2.4 Test Method

The EUT was set up in a semi-anechoic chamber in the centre of a remotely controlled turntable and placed on a non-conductive table 0.8 m above a reference ground plane

A Peak detector pre-scan of the EUT emissions profile was measured across the appropriate frequency range while varying the antenna-to-EUT azimuth and polarisation. Measurements were made using a 3 m distance between the declared antenna measurement point and the EUT.

Where all pre-scan peak emissions measured were greater than 20 dB below the test limit, no final measurements were made in accordance with ANSI C63.4.

Where any pre-scan peak emissions were within 20 dB of the test limit, the six highest pre-scan peak emissions seen across the frequency range were maximised by adjusting antenna height, polarisation and angle and then measured for at least 15 seconds using a Peak, Quasi-Peak or CISPR Average detector as appropriate to the test limit being measured against.

2.2.5 Example Calculation


Below 1 GHz:

$$\begin{aligned}\text{Quasi-Peak level (dB}\mu\text{V/m)} &= \text{Receiver level (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} \\ \text{Margin (dB)} &= \text{Quasi-Peak level (dB}\mu\text{V/m)} - \text{Limit (dB}\mu\text{V/m)}\end{aligned}$$

Above 1 GHz:

$$\begin{aligned}\text{CISPR Average level (dB}\mu\text{V/m)} &= \text{Receiver level (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} \\ \text{Margin (dB)} &= \text{CISPR Average level (dB}\mu\text{V/m)} - \text{Limit (dB}\mu\text{V/m)}\end{aligned}$$

$$\begin{aligned}\text{Peak level (dB}\mu\text{V/m)} &= \text{Receiver level (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} \\ \text{Margin (dB)} &= \text{Peak level (dB}\mu\text{V/m)} - \text{Limit (dB}\mu\text{V/m)}\end{aligned}$$



Required Specification Limits, Field Strength - Class B Test Limit at a 3 m Measurement Distance		
Frequency Range (MHz)	Test Limit ($\mu\text{V/m}$)	Test Limit ($\text{dB}\mu\text{V/m}$)
30 to 88	100	40.0
88 to 216	150	43.5
216 to 960	200	46.0
Above 960	500	54.0

Supplementary information:
 Note 1. A Quasi-peak detector is to be used for measurements below 1 GHz.
 Note 2. A CISPR Average detector is to be used for measurements above 1 GHz.
 Note 3. The Peak test limit above 1 GHz is 20 dB higher than the CISPR Average test limit.

2.2.9 Test Results

Results for Configuration and Mode: AC Powered - Transmitter Idle.

This test was performed to the requirements of Class B limits.

Performance assessment of the EUT made during this test: Pass.

Detailed results are shown below.

Highest internally generated frequency within the EUT: 6 GHz
Which necessitates an upper frequency test limit of: 30 GHz

Applied Supply Voltage: 115 V AC
Applied Supply Frequency: 60 Hz




Figure 5 - 30 MHz to 1 GHz, Quasi-Peak, Horizontal

Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
30.780	20.54	40.00	-19.46	Q-Peak	163	238	Horizontal
33.120	18.39	40.00	-21.61	Q-Peak	0	375	Horizontal
34.440	17.26	40.00	-22.74	Q-Peak	131	277	Horizontal
75.119	5.38	40.00	-34.62	Q-Peak	272	340	Horizontal
540.530	17.28	46.00	-28.72	Q-Peak	0	256	Horizontal
597.949	19.20	46.00	-26.80	Q-Peak	220	245	Horizontal

Table 14




Figure 6 - 30 MHz to 1 GHz, Quasi-Peak, Vertical

Frequency (MHz)	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
30.840	23.18	40.00	-16.82	Q-Peak	226	103	Vertical
39.660	31.00	40.00	-9.00	Q-Peak	230	109	Vertical
42.060	27.35	40.00	-12.65	Q-Peak	239	110	Vertical
70.079	23.60	40.00	-16.40	Q-Peak	241	100	Vertical
71.399	18.00	40.00	-22.00	Q-Peak	350	347	Vertical
77.459	13.88	40.00	-26.12	Q-Peak	236	108	Vertical

Table 15




Figure 7 - 1 GHz to 30 GHz, Peak & CISPR Average, Horizontal



Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
1002.682	38.09	74.00	-35.91	Peak	0	100	Horizontal
1002.682	25.38	54.00	-28.62	CISPR Avg	0	100	Horizontal
1036.201	37.04	74.00	-36.96	Peak	10	100	Horizontal
1036.201	23.84	54.00	-30.16	CISPR Avg	10	100	Horizontal
1080.035	38.22	74.00	-35.78	Peak	240	100	Horizontal
1080.035	25.21	54.00	-28.79	CISPR Avg	240	100	Horizontal
1181.526	37.81	74.00	-36.19	Peak	36	110	Horizontal
1181.526	25.02	54.00	-28.98	CISPR Avg	36	110	Horizontal
6575.571	37.36	74.00	-36.64	Peak	5	100	Horizontal
6575.571	24.72	54.00	-29.28	CISPR Avg	5	100	Horizontal
7670.612	38.32	74.00	-35.68	Peak	103	110	Horizontal
7670.612	26.33	54.00	-27.67	CISPR Avg	103	110	Horizontal
16099.804	41.14	74.00	-32.86	Peak	322	100	Horizontal
16099.804	28.99	54.00	-25.01	CISPR Avg	322	100	Horizontal
16441.368	41.30	74.00	-32.70	Peak	277	103	Horizontal
16441.368	29.09	54.00	-24.91	CISPR Avg	277	103	Horizontal
16540.598	42.24	74.00	-31.76	Peak	227	110	Horizontal
16540.598	29.62	54.00	-24.38	CISPR Avg	227	110	Horizontal
16989.186	42.29	74.00	-31.71	Peak	330	192	Horizontal
16989.186	30.09	54.00	-23.91	CISPR Avg	330	192	Horizontal
17547.686	42.46	74.00	-31.54	Peak	55	267	Horizontal
17547.686	29.68	54.00	-24.32	CISPR Avg	55	267	Horizontal
17933.927	42.13	74.00	-31.87	Peak	344	109	Horizontal
17933.927	30.12	54.00	-23.88	CISPR Avg	344	109	Horizontal
23403.685	48.16	83.50	-35.34	Peak	13	100	Horizontal
23403.685	36.70	63.50	-26.80	CISPR Avg	13	100	Horizontal
24796.213	49.31	83.50	-34.19	Peak	211	100	Horizontal
24796.213	37.73	63.50	-25.77	CISPR Avg	211	100	Horizontal
26202.797	49.06	83.50	-34.44	Peak	344	100	Horizontal
26202.797	37.81	63.50	-25.69	CISPR Avg	344	100	Horizontal
26755.134	50.01	83.50	-33.49	Peak	7	100	Horizontal
26755.134	38.03	63.50	-25.47	CISPR Avg	7	100	Horizontal
27180.312	48.98	83.50	-34.52	Peak	0	100	Horizontal
27180.312	37.53	63.50	-25.97	CISPR Avg	0	100	Horizontal
29027.000	49.24	83.50	-34.26	Peak	0	100	Horizontal
29027.000	37.84	63.50	-25.66	CISPR Avg	0	100	Horizontal

Table 16




Figure 8 - 1 GHz to 30 GHz, Peak & CISPR Average, Vertical



Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
1007.997	37.90	74.00	-36.10	Peak	185	110	Vertical
1007.997	25.11	54.00	-28.89	CISPR Avg	185	110	Vertical
1088.965	37.59	74.00	-36.41	Peak	349	101	Vertical
1088.965	24.75	54.00	-29.25	CISPR Avg	349	101	Vertical
1103.729	37.30	74.00	-36.70	Peak	140	105	Vertical
1103.729	24.19	54.00	-29.81	CISPR Avg	140	105	Vertical
1185.235	37.78	74.00	-36.22	Peak	305	100	Vertical
1185.235	24.96	54.00	-29.04	CISPR Avg	305	100	Vertical
1272.986	36.47	74.00	-37.53	Peak	323	110	Vertical
1272.986	23.10	54.00	-30.90	CISPR Avg	323	110	Vertical
7669.805	38.55	74.00	-35.45	Peak	141	110	Vertical
7669.805	26.34	54.00	-27.66	CISPR Avg	141	110	Vertical
15608.562	42.21	74.00	-31.79	Peak	144	106	Vertical
15608.562	29.56	54.00	-24.44	CISPR Avg	144	106	Vertical
16056.854	42.46	74.00	-31.54	Peak	71	336	Vertical
16056.854	29.21	54.00	-24.79	CISPR Avg	71	336	Vertical
16479.820	41.46	74.00	-32.54	Peak	1	182	Vertical
16479.820	29.57	54.00	-24.43	CISPR Avg	1	182	Vertical
16978.911	41.76	74.00	-32.24	Peak	0	105	Vertical
16978.911	30.03	54.00	-23.97	CISPR Avg	0	105	Vertical
17428.893	41.98	74.00	-32.02	Peak	332	101	Vertical
17428.893	29.48	54.00	-24.52	CISPR Avg	332	101	Vertical
17875.590	42.97	74.00	-31.03	Peak	9	100	Vertical
17875.590	29.93	54.00	-24.07	CISPR Avg	9	100	Vertical
25231.717	49.09	83.50	-34.41	Peak	56	100	Vertical
25231.717	37.36	63.50	-26.14	CISPR Avg	56	100	Vertical
26111.819	48.97	83.50	-34.53	Peak	0	100	Vertical
26111.819	37.31	63.50	-26.19	CISPR Avg	0	100	Vertical
26885.474	49.88	83.50	-33.62	Peak	21	100	Vertical
26885.474	37.70	63.50	-25.80	CISPR Avg	21	100	Vertical
28057.845	48.56	83.50	-34.94	Peak	306	100	Vertical
28057.845	37.12	63.50	-26.38	CISPR Avg	306	100	Vertical
28724.572	50.22	83.50	-33.28	Peak	359	100	Vertical
28724.572	37.98	63.50	-25.52	CISPR Avg	359	100	Vertical
29044.843	50.02	83.50	-33.48	Peak	255	100	Vertical
29044.843	37.90	63.50	-25.60	CISPR Avg	255	100	Vertical

Table 17



2.2.10 Test Location and Test Equipment Used

This test was carried out in EMC Chamber 12.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
3m Semi-Anechoic Chamber	MVG	EMC Chamber 12	5621	36	07-Aug-2026
Emissions Software	TUV SUD	EmX V3.5.5	5125	-	Software
Test Receiver	Rohde & Schwarz	ESW44	5382	12	09-Oct-2026
Turntable & Mast Controller	Maturo Gmbh	NCD/498/2799.01	5612	-	TU
Tilt Antenna Mast	Maturo Gmbh	TAM 4.0-P	5613	-	TU
3.5 mm 1m Cable	Junkosha	MWX221-01000DMS	5419	12	15-Aug-2026
2m Coaxial Cable Assy	Junkosha	MWX221-02000AMSAMS/A	6357	12	13-May-2026
Cable (2.92 mm(f)-N(m), 2 m)	Junkosha	MWX241-02000KFSNMS/B	6965	6	14-Feb-2026
Cable (N-Type to N-Type, 8 m)	Junkosha	MWX221-08000NMSNMS/B	7054	12	01-Jun-2026
Pre-Amplifier (1 GHz to 18 GHz)	Schwarzbeck	BBV 9718 C	5350	12	16-Dec-2025
Pre-Amplifier (8 - 18GHz)	Wright Technologies	APS06-0061	6306	12	18-Jul-2026
Pre-Amplifier (18 GHz to 40 GHz)	Schwarzbeck	BBV 9721	5218	12	12-May-2026
Antenna (Bilog with attenuator, 30 MHz to 3 GHz)	Schaffner	CBL6143	287	24	29-Aug-2026
Antenna (DRG, 1 GHz to 10.5 GHz)	Schwarzbeck	BBHA9120B	5611	12	14-Sep-2026
Antenna (DRG, 7.5 GHz to 18 GHz)	Schwarzbeck	HWRD750	5216	12	12-Jul-2026
Antenna (DRG, 15 GHz to 40 GHz)	Schwarzbeck	BBHA 9170	5217	12	12-May-2026
Thermo-Hygro-Barometer	PCE Instruments	PCE-THB-40	5471	12	14-May-2026

Table 18

TU - Traceability Unscheduled



3 Test Equipment Information

3.1 General Test Equipment Used

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Multimeter	Fluke	79 Series III	498	12	26-Feb-2026
Milliohm Meter	VICI	2682132	7012	12	21-May-2026

Table 19



4 Incident Reports

No incidents reports were raised.



5 Measurement Uncertainty

For a 95% confidence level, the measurement uncertainties for defined systems are:

Test Name	Measurement Uncertainty
Conducted Emissions, AC Power Port	150 kHz to 30 MHz, LISN ± 3.3 dB
Radiated Emissions	30 MHz to 1 GHz, Bilog Antenna ± 5.17 dB 1 GHz to 6 GHz, Horn Antenna ± 5.05 dB 6 GHz to 18 GHz, Horn Antenna ± 4.94 dB 18 GHz to 40 GHz, Horn Antenna ± 6.28 dB

Table 20

Worst case error for both Time and Frequency measurement 12 parts in 10^6 .

Measurement Uncertainty Decision Rule

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115:2021, Clause 4.4.3 (Procedure 2). The measurement results are directly compared with the test limit to determine conformance with the requirements of the standard.

Risk: The uncertainty of measurement about the measured result is negligible with regard to the final pass/fail decision. The measurement result can be directly compared with the test limit to determine conformance with the requirement (compare IEC Guide 115). The level of risk to falsely accept and falsely reject items is further described in ILAC-G8.