




Figure 147 - 802.11a40 LPI Minimum 99% OBW



Figure 148 - 802.11a40 LPI Maximum 99% OBW



Figure 149 - 802.11a80 LPI Minimum 99% OBW




Figure 150 - 802.11a80 LPI Maximum 99% OBW




Figure 151 - 802.11a160 LPI Minimum 99% OBW




Figure 152 - 802.11a160 LPI Maximum 99% OBW




Figure 153 - 802.11ax HE20 SU LPI Minimum 99% OBW




Figure 154 - 802.11ax HE20 SU LPI Maximum 99% OBW




Figure 155 - 802.11ax HE40 SU LPI Minimum 99% OBW




Figure 156 - 802.11ax HE40 SU LPI Maximum 99% OBW




Figure 157 - 802.11ax HE80 SU LPI Minimum 99% OBW




Figure 158 - 802.11ax HE80 SU LPI Maximum 99% OBW




Figure 159 - 802.11ax HE160 SU LPI Minimum 99% OBW




Figure 160 - 802.11ax HE160 SU LPI Maximum 99% OBW




Figure 161 - 802.11a20 SP Minimum 99% OBW




Figure 162 - 802.11a20 SP Maximum 99% OBW




Figure 163 - 802.11a40 SP Minimum 99% OBW




Figure 164 - 802.11a40 SP Maximum 99% OBW




Figure 165 - 802.11a80 SP Minimum 99% OBW




Figure 166 - 802.11a80 SP Maximum 99% OBW




Figure 167 - 802.11a160 SP Minimum 99% OBW




Figure 168 - 802.11a160 SP Maximum 99% OBW




Figure 169 - 802.11ax HE20 SU SP Minimum 99% OBW




Figure 170 - 802.11ax HE20 SU SP Maximum 99% OBW




Figure 171 - 802.11ax HE40 SU SP Minimum 99% OBW




Figure 172 - 802.11ax HE40 SU SP Maximum 99% OBW




Figure 173 - 802.11ax HE80 SU SP Minimum 99% OBW




Figure 174 - 802.11ax HE80 SU SP Maximum 99% OBW




Figure 175 - 802.11ax HE160 SU SP Minimum 99% OBW




Figure 176 - 802.11ax HE160 SU SP Maximum 99% OBW




Figure 177 - 802.11a20 VLP Minimum 99% OBW




Figure 178 - 802.11a20 VLP Maximum 99% OBW




Figure 179 - 802.11a40 VLP Minimum 99% OBW




Figure 180 - 802.11a40 VLP Maximum 99% OBW



Figure 181 - 802.11a80 VLP Minimum 99% OBW



Figure 182 - 802.11a80 VLP Maximum 99% OBW




Figure 183 - 802.11a160 VLP Minimum 99% OBW




Figure 184 - 802.11a160 VLP Maximum 99% OBW




Figure 185 - 802.11ax HE20 SU VLP Minimum 99% OBW




Figure 186 - 802.11ax HE20 SU VLP Maximum 99% OBW




Figure 187 - 802.11ax HE40 SU VLP Minimum 99% OBW




Figure 188 - 802.11ax HE40 SU VLP Maximum 99% OBW




Figure 189 - 802.11ax HE80 SU VLP Minimum
99% OBW




Figure 190 - 802.11ax HE80 SU VLP Maximum
99% OBW




Figure 191 - 802.11ax HE160 SU VLP Minimum
99% OBW




Figure 192 - 802.11ax HE160 SU VLP Maximum
99% OBW



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a20 LPI	Duty Cycle (%):	-
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5955	-	22.920	-	-	320.0
6175	-	22.788	-	-	320.0
6415	-	22.728	-	-	320.0
6435	-	22.596	-	-	320.0
6475	-	22.662	-	-	320.0
6515	-	22.476	-	-	320.0
6535	-	22.692	-	-	320.0
6695	-	22.548	-	-	320.0
6855	-	22.848	-	-	320.0
6875	-	22.644	-	-	320.0
6895	-	22.584	-	-	320.0
6995	-	22.578	-	-	320.0
7095	-	22.452	-	-	320.0
7115	-	21.066	-	-	320.0

Table 58 - 26 dB Bandwidth Results



Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5955	-	17.820	-	-	320.0
6175	-	17.820	-	-	320.0
6415	-	17.814	-	-	320.0
6435	-	17.820	-	-	320.0
6475	-	17.826	-	-	320.0
6515	-	17.820	-	-	320.0
6535	-	17.814	-	-	320.0
6695	-	17.820	-	-	320.0
6855	-	17.814	-	-	320.0
6875	-	17.826	-	-	320.0
6895	-	17.814	-	-	320.0
6995	-	17.820	-	-	320.0
7095	-	17.808	-	-	320.0
7115	-	17.586	-	-	320.0

Table 59 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a40 LPI	Duty Cycle (%):	-
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5965	-	43.812	-	-	320.0
6165	-	43.452	-	-	320.0
6405	-	44.160	-	-	320.0
6445	-	43.080	-	-	320.0
6485	-	42.936	-	-	320.0
6525	-	43.080	-	-	320.0
6565	-	43.548	-	-	320.0
6685	-	43.236	-	-	320.0
6845	-	43.368	-	-	320.0
6885	-	43.320	-	-	320.0
6925	-	43.032	-	-	320.0
7005	-	42.720	-	-	320.0
7085	-	43.608	-	-	320.0

Table 60 - 26 dB Bandwidth Results



Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5965	-	36.648	-	-	320.0
6165	-	36.636	-	-	320.0
6405	-	36.648	-	-	320.0
6445	-	36.636	-	-	320.0
6485	-	36.588	-	-	320.0
6525	-	36.636	-	-	320.0
6565	-	36.624	-	-	320.0
6685	-	36.660	-	-	320.0
6845	-	36.636	-	-	320.0
6885	-	36.600	-	-	320.0
6925	-	36.660	-	-	320.0
7005	-	36.576	-	-	320.0
7085	-	36.588	-	-	320.0

Table 61 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 LPI	Duty Cycle (%):	-
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5985	-	106.756	-	-	320.0
6145	-	106.368	-	-	320.0
6385	-	110.396	-	-	320.0
6465	-	107.354	-	-	320.0
6545	-	111.816	-	-	320.0
6625	-	107.276	-	-	320.0
6705	-	105.924	-	-	320.0
6785	-	111.576	-	-	320.0
6865	-	106.756	-	-	320.0
6945	-	111.566	-	-	320.0
7025	-	110.136	-	-	320.0

Table 62 - 26 dB Bandwidth Results



Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5985	-	76.362	-	-	320.0
6145	-	76.368	-	-	320.0
6385	-	76.388	-	-	320.0
6465	-	76.388	-	-	320.0
6545	-	76.392	-	-	320.0
6625	-	76.284	-	-	320.0
6705	-	76.336	-	-	320.0
6785	-	76.320	-	-	320.0
6865	-	76.362	-	-	320.0
6945	-	76.362	-	-	320.0
7025	-	76.368	-	-	320.0

Table 63 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 LPI	Duty Cycle (%):	-
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6025	-	163.842	-	-	320.0
6185	-	163.674	-	-	320.0
6345	-	163.464	-	-	320.0
6505	-	163.590	-	-	320.0
6665	-	163.884	-	-	320.0
6825	-	163.128	-	-	320.0
6985	-	163.422	-	-	320.0

Table 64 - 26 dB Bandwidth Results

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6025	-	155.022	-	-	320.0
6185	-	155.064	-	-	320.0
6345	-	155.148	-	-	320.0
6505	-	155.148	-	-	320.0
6665	-	155.106	-	-	320.0
6825	-	155.148	-	-	320.0
6985	-	155.022	-	-	320.0

Table 65 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 SU LPI	Duty Cycle (%):	-
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5955	-	22.590	-	-	320.0
6175	-	22.596	-	-	320.0
6415	-	22.506	-	-	320.0
6435	-	22.458	-	-	320.0
6475	-	22.542	-	-	320.0
6515	-	22.398	-	-	320.0
6535	-	22.338	-	-	320.0
6695	-	22.470	-	-	320.0
6855	-	22.638	-	-	320.0
6875	-	22.326	-	-	320.0
6895	-	22.476	-	-	320.0
6995	-	22.416	-	-	320.0
7095	-	22.710	-	-	320.0
7115	-	22.098	-	-	320.0

Table 66 - 26 dB Bandwidth Results



Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5955	-	19.002	-	-	320.0
6175	-	19.002	-	-	320.0
6415	-	19.002	-	-	320.0
6435	-	18.996	-	-	320.0
6475	-	19.008	-	-	320.0
6515	-	19.008	-	-	320.0
6535	-	19.008	-	-	320.0
6695	-	19.008	-	-	320.0
6855	-	19.008	-	-	320.0
6875	-	19.002	-	-	320.0
6895	-	19.002	-	-	320.0
6995	-	18.996	-	-	320.0
7095	-	19.014	-	-	320.0
7115	-	18.774	-	-	320.0

Table 67 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE40 SU LPI	Duty Cycle (%):	-
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5965	-	44.748	-	-	320.0
6165	-	44.556	-	-	320.0
6405	-	44.484	-	-	320.0
6445	-	44.964	-	-	320.0
6485	-	44.508	-	-	320.0
6525	-	44.976	-	-	320.0
6565	-	44.304	-	-	320.0
6685	-	44.544	-	-	320.0
6845	-	44.412	-	-	320.0
6885	-	44.772	-	-	320.0
6925	-	44.700	-	-	320.0
7005	-	45.036	-	-	320.0
7085	-	44.856	-	-	320.0

Table 68 - 26 dB Bandwidth Results



Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5965	-	38.016	-	-	320.0
6165	-	38.004	-	-	320.0
6405	-	38.028	-	-	320.0
6445	-	37.992	-	-	320.0
6485	-	38.016	-	-	320.0
6525	-	38.016	-	-	320.0
6565	-	38.016	-	-	320.0
6685	-	38.040	-	-	320.0
6845	-	38.004	-	-	320.0
6885	-	38.016	-	-	320.0
6925	-	38.004	-	-	320.0
7005	-	38.004	-	-	320.0
7085	-	38.004	-	-	320.0

Table 69 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU LPI	Duty Cycle (%):	-
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5985	-	82.830	-	-	320.0
6145	-	82.588	-	-	320.0
6385	-	82.786	-	-	320.0
6465	-	82.566	-	-	320.0
6545	-	82.588	-	-	320.0
6625	-	82.874	-	-	320.0
6705	-	82.698	-	-	320.0
6785	-	82.478	-	-	320.0
6865	-	82.742	-	-	320.0
6945	-	82.742	-	-	320.0
7025	-	82.676	-	-	320.0

Table 70 - 26 dB Bandwidth Results



Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5985	-	77.484	-	-	320.0
6145	-	77.462	-	-	320.0
6385	-	77.462	-	-	320.0
6465	-	77.440	-	-	320.0
6545	-	77.484	-	-	320.0
6625	-	77.440	-	-	320.0
6705	-	77.440	-	-	320.0
6785	-	77.440	-	-	320.0
6865	-	77.440	-	-	320.0
6945	-	77.484	-	-	320.0
7025	-	77.418	-	-	320.0

Table 71 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU LPI	Duty Cycle (%):	-
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6025	-	164.262	-	-	320.0
6185	-	164.766	-	-	320.0
6345	-	164.598	-	-	320.0
6505	-	164.808	-	-	320.0
6665	-	164.766	-	-	320.0
6825	-	165.102	-	-	320.0
6985	-	164.598	-	-	320.0

Table 72 - 26 dB Bandwidth Results

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6025	-	156.240	-	-	320.0
6185	-	156.366	-	-	320.0
6345	-	156.366	-	-	320.0
6505	-	156.450	-	-	320.0
6665	-	156.366	-	-	320.0
6825	-	156.450	-	-	320.0
6985	-	156.282	-	-	320.0

Table 73 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a20 SP	Duty Cycle (%):	-
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5955	-	21.024	-	-	320.0
6175	-	22.482	-	-	320.0
6415	-	22.446	-	-	320.0
6435	-	22.734	-	-	320.0
6475	-	22.452	-	-	320.0
6515	-	22.632	-	-	320.0
6535	-	22.770	-	-	320.0
6695	-	22.734	-	-	320.0
6855	-	22.500	-	-	320.0

Table 74 - 26 dB Bandwidth Results

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5955	-	17.574	-	-	320.0
6175	-	17.814	-	-	320.0
6415	-	17.814	-	-	320.0
6435	-	17.820	-	-	320.0
6475	-	17.814	-	-	320.0
6515	-	17.820	-	-	320.0
6535	-	17.814	-	-	320.0
6695	-	17.820	-	-	320.0
6855	-	17.808	-	-	320.0

Table 75 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a40 SP	Duty Cycle (%):	-
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5965	-	42.408	-	-	320.0
6165	-	48.576	-	-	320.0
6405	-	45.828	-	-	320.0
6445	-	46.596	-	-	320.0
6485	-	44.496	-	-	320.0
6525	-	43.092	-	-	320.0
6565	-	47.100	-	-	320.0
6685	-	44.436	-	-	320.0
6845	-	48.360	-	-	320.0

Table 76 - 26 dB Bandwidth Results

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5965	-	36.192	-	-	320.0
6165	-	36.828	-	-	320.0
6405	-	36.756	-	-	320.0
6445	-	36.708	-	-	320.0
6485	-	36.696	-	-	320.0
6525	-	36.744	-	-	320.0
6565	-	36.708	-	-	320.0
6685	-	36.684	-	-	320.0
6845	-	36.756	-	-	320.0

Table 77 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 SP	Duty Cycle (%):	-
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5985	-	84.722	-	-	320.0
6145	-	112.944	-	-	320.0
6385	-	112.918	-	-	320.0
6465	-	111.878	-	-	320.0
6625	-	112.814	-	-	320.0
6705	-	111.202	-	-	320.0
6785	-	113.464	-	-	320.0

Table 78 - 26 dB Bandwidth Results

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5985	-	75.438	-	-	320.0
6145	-	76.622	-	-	320.0
6385	-	76.570	-	-	320.0
6465	-	76.544	-	-	320.0
6545	-	76.552	-	-	320.0
6625	-	76.492	-	-	320.0
6705	-	76.466	-	-	320.0
6785	-	76.544	-	-	320.0

Table 79 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 SP	Duty Cycle (%):	-
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6025	-	162.918	-	-	320.0
6185	-	165.984	-	-	320.0
6345	-	163.296	-	-	320.0
6505	-	163.590	-	-	320.0
6665	-	162.708	-	-	320.0

Table 80 - 26 dB Bandwidth Results

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6025	-	154.434	-	-	320.0
6185	-	154.686	-	-	320.0
6345	-	154.560	-	-	320.0
6505	-	154.560	-	-	320.0
6665	-	154.602	-	-	320.0

Table 81 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 SU SP	Duty Cycle (%):	-
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5955	-	21.066	-	-	320.0
6175	-	22.230	-	-	320.0
6415	-	22.440	-	-	320.0
6435	-	22.272	-	-	320.0
6475	-	22.266	-	-	320.0
6515	-	22.554	-	-	320.0
6535	-	22.188	-	-	320.0
6695	-	22.542	-	-	320.0
6855	-	22.818	-	-	320.0

Table 82 - 26 dB Bandwidth Results

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5955	-	18.768	-	-	320.0
6175	-	19.008	-	-	320.0
6415	-	19.002	-	-	320.0
6435	-	19.002	-	-	320.0
6475	-	18.990	-	-	320.0
6515	-	19.008	-	-	320.0
6535	-	19.002	-	-	320.0
6695	-	18.996	-	-	320.0
6855	-	19.002	-	-	320.0

Table 83 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	-
Modulation Coding Scheme:	MCS2x1	DCCC (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5965	-	42.816	-	-	320.0
6165	-	44.388	-	-	320.0
6405	-	44.832	-	-	320.0
6445	-	44.892	-	-	320.0
6485	-	44.676	-	-	320.0
6525	-	45.024	-	-	320.0
6565	-	45.000	-	-	320.0
6685	-	44.340	-	-	320.0
6845	-	45.108	-	-	320.0

Table 84 - 26 dB Bandwidth Results

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5965	-	37.596	-	-	320.0
6165	-	38.016	-	-	320.0
6405	-	38.016	-	-	320.0
6445	-	38.004	-	-	320.0
6485	-	37.992	-	-	320.0
6525	-	38.004	-	-	320.0
6565	-	38.016	-	-	320.0
6685	-	37.992	-	-	320.0
6845	-	37.992	-	-	320.0

Table 85 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	-
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5985	-	81.620	-	-	320.0
6145	-	82.478	-	-	320.0
6385	-	82.632	-	-	320.0
6465	-	82.676	-	-	320.0
6625	-	82.632	-	-	320.0
6705	-	82.698	-	-	320.0
6785	-	82.764	-	-	320.0

Table 86 - 26 dB Bandwidth Results

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
5985	-	76.714	-	-	320.0
6145	-	77.462	-	-	320.0
6385	-	77.440	-	-	320.0
6465	-	77.462	-	-	320.0
6545	-	77.484	-	-	320.0
6625	-	77.440	-	-	320.0
6705	-	77.440	-	-	320.0
6785	-	77.440	-	-	320.0

Table 87 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-6 U-NII-7
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	-
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6025	-	163.926	-	-	320.0
6185	-	164.640	-	-	320.0
6345	-	163.926	-	-	320.0
6505	-	164.178	-	-	320.0
6665	-	164.262	-	-	320.0

Table 88 - 26 dB Bandwidth Results

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6025	-	155.526	-	-	320.0
6185	-	155.778	-	-	320.0
6345	-	155.694	-	-	320.0
6505	-	155.820	-	-	320.0
6665	-	155.652	-	-	320.0

Table 89 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a20 VLP	Duty Cycle (%):	-
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6115	-	22.710	-	-	320.0
6275	-	22.536	-	-	320.0
6415	-	22.422	-	-	320.0
6435	-	22.800	-	-	320.0
6475	-	22.638	-	-	320.0
6515	-	22.764	-	-	320.0
6535	-	22.668	-	-	320.0
6695	-	22.812	-	-	320.0
6855	-	22.902	-	-	320.0
6875	-	22.644	-	-	320.0
6895	-	22.506	-	-	320.0
6995	-	22.992	-	-	320.0
7115	-	21.042	-	-	320.0

Table 90 - 26 dB Bandwidth Results



Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6115	-	17.826	-	-	320.0
6275	-	17.814	-	-	320.0
6415	-	17.814	-	-	320.0
6435	-	17.826	-	-	320.0
6475	-	17.826	-	-	320.0
6515	-	17.838	-	-	320.0
6535	-	17.826	-	-	320.0
6695	-	17.832	-	-	320.0
6855	-	17.838	-	-	320.0
6875	-	17.832	-	-	320.0
6895	-	17.826	-	-	320.0
6995	-	17.826	-	-	320.0
7115	-	17.586	-	-	320.0

Table 91 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a40 VLP	Duty Cycle (%):	-
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6125	-	43.236	-	-	320.0
6285	-	44.124	-	-	320.0
6405	-	43.476	-	-	320.0
6445	-	43.908	-	-	320.0
6485	-	43.776	-	-	320.0
6525	-	43.092	-	-	320.0
6565	-	43.608	-	-	320.0
6685	-	43.824	-	-	320.0
6845	-	42.924	-	-	320.0
6885	-	43.764	-	-	320.0
6925	-	43.164	-	-	320.0
7005	-	42.912	-	-	320.0
7085	-	42.816	-	-	320.0

Table 92 - 26 dB Bandwidth Results



Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6125	-	36.720	-	-	320.0
6285	-	36.660	-	-	320.0
6405	-	36.624	-	-	320.0
6445	-	36.612	-	-	320.0
6485	-	36.612	-	-	320.0
6525	-	36.660	-	-	320.0
6565	-	36.636	-	-	320.0
6685	-	36.672	-	-	320.0
6845	-	36.660	-	-	320.0
6885	-	36.600	-	-	320.0
6925	-	36.660	-	-	320.0
7005	-	36.612	-	-	320.0
7085	-	36.600	-	-	320.0

Table 93 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 VLP	Duty Cycle (%):	-
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6145	-	111.046	-	-	320.0
6225	-	108.862	-	-	320.0
6385	-	110.976	-	-	320.0
6465	-	107.952	-	-	320.0
6545	-	112.060	-	-	320.0
6625	-	107.666	-	-	320.0
6705	-	111.264	-	-	320.0
6785	-	110.526	-	-	320.0
6865	-	111.576	-	-	320.0
6945	-	108.498	-	-	320.0
7025	-	110.318	-	-	320.0

Table 94 - 26 dB Bandwidth Results



Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6145	-	76.414	-	-	320.0
6225	-	76.440	-	-	320.0
6385	-	76.392	-	-	320.0
6465	-	76.416	-	-	320.0
6545	-	76.544	-	-	320.0
6625	-	76.362	-	-	320.0
6705	-	76.464	-	-	320.0
6785	-	76.440	-	-	320.0
6865	-	76.440	-	-	320.0
6945	-	76.440	-	-	320.0
7025	-	76.336	-	-	320.0

Table 95 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 VLP	Duty Cycle (%):	-
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6185	-	164.430	-	-	320.0
6345	-	163.926	-	-	320.0
6505	-	163.296	-	-	320.0
6665	-	163.632	-	-	320.0
6825	-	164.094	-	-	320.0
6985	-	163.380	-	-	320.0

Table 96 - 26 dB Bandwidth Results

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6185	-	155.148	-	-	320.0
6345	-	155.106	-	-	320.0
6505	-	155.190	-	-	320.0
6665	-	155.106	-	-	320.0
6825	-	155.190	-	-	320.0
6985	-	155.022	-	-	320.0

Table 97 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 SU VLP	Duty Cycle (%):	-
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6115	-	22.518	-	-	320.0
6275	-	22.614	-	-	320.0
6415	-	22.122	-	-	320.0
6435	-	22.818	-	-	320.0
6475	-	22.416	-	-	320.0
6515	-	22.320	-	-	320.0
6535	-	22.410	-	-	320.0
6695	-	22.248	-	-	320.0
6855	-	22.434	-	-	320.0
6875	-	22.368	-	-	320.0
6895	-	22.482	-	-	320.0
6995	-	22.572	-	-	320.0
7095	-	22.506	-	-	320.0

Table 98 - 26 dB Bandwidth Results



Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6115	-	19.002	-	-	320.0
6275	-	18.996	-	-	320.0
6415	-	18.984	-	-	320.0
6435	-	19.008	-	-	320.0
6475	-	19.008	-	-	320.0
6515	-	19.014	-	-	320.0
6535	-	19.002	-	-	320.0
6695	-	19.014	-	-	320.0
6855	-	19.008	-	-	320.0
6875	-	19.008	-	-	320.0
6895	-	19.008	-	-	320.0
6995	-	19.026	-	-	320.0
7095	-	19.002	-	-	320.0

Table 99 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE40 SU VLP	Duty Cycle (%):	-
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6125	-	44.784	-	-	320.0
6285	-	44.520	-	-	320.0
6405	-	44.376	-	-	320.0
6445	-	44.424	-	-	320.0
6485	-	44.748	-	-	320.0
6525	-	44.820	-	-	320.0
6565	-	44.700	-	-	320.0
6685	-	45.048	-	-	320.0
6845	-	44.364	-	-	320.0
6885	-	44.556	-	-	320.0
6925	-	44.616	-	-	320.0
7005	-	44.748	-	-	320.0
7085	-	44.712	-	-	320.0

Table 100 - 26 dB Bandwidth Results



Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6125	-	38.064	-	-	320.0
6285	-	38.040	-	-	320.0
6405	-	38.028	-	-	320.0
6445	-	38.028	-	-	320.0
6485	-	38.028	-	-	320.0
6525	-	38.016	-	-	320.0
6565	-	38.040	-	-	320.0
6685	-	38.016	-	-	320.0
6845	-	38.028	-	-	320.0
6885	-	38.028	-	-	320.0
6925	-	38.016	-	-	320.0
7005	-	38.004	-	-	320.0
7085	-	38.028	-	-	320.0

Table 101 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU VLP	Duty Cycle (%):	-
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6145	-	82.566	-	-	320.0
6225	-	82.676	-	-	320.0
6385	-	82.764	-	-	320.0
6465	-	82.830	-	-	320.0
6545	-	82.808	-	-	320.0
6625	-	82.434	-	-	320.0
6705	-	82.654	-	-	320.0
6785	-	82.830	-	-	320.0
6865	-	83.050	-	-	320.0
6945	-	82.940	-	-	320.0
7025	-	82.566	-	-	320.0

Table 102 - 26 dB Bandwidth Results



Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6145	-	77.506	-	-	320.0
6225	-	77.440	-	-	320.0
6385	-	77.440	-	-	320.0
6465	-	77.462	-	-	320.0
6545	-	77.506	-	-	320.0
6625	-	77.440	-	-	320.0
6705	-	77.462	-	-	320.0
6785	-	77.462	-	-	320.0
6865	-	77.462	-	-	320.0
6945	-	77.418	-	-	320.0
7025	-	77.462	-	-	320.0

Table 103 - 99% Bandwidth Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a) (11) RSS-248 4.4	Test Method(s):	C63.10 6.9.3 C63.10 6.9.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU VLP	Duty Cycle (%):	-
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	26 dB Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6185	-	164.850	-	-	320.0
6345	-	165.102	-	-	320.0
6505	-	164.640	-	-	320.0
6665	-	164.640	-	-	320.0
6825	-	164.472	-	-	320.0
6985	-	164.766	-	-	320.0

Table 104 - 26 dB Bandwidth Results



Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (MHz)
	A	B	C	D	
6185	-	156.366	-	-	320.0
6345	-	156.366	-	-	320.0
6505	-	156.450	-	-	320.0
6665	-	156.408	-	-	320.0
6825	-	156.324	-	-	320.0
6985	-	156.282	-	-	320.0

Table 105 - 99% Bandwidth Results



Protocol	26 dB Bandwidth (MHz)	
	Minimum	Maximum
802.11a20 LPI	20.982	22.992
802.11a40 LPI	42.840	44.352
802.11a80 LPI	106.872	115.918
802.11a160 LPI	163.212	164.682
802.11ax HE20 SU LPI	21.930	22.776
802.11ax HE40 SU LPI	44.292	45.372
802.11ax HE80 SU LPI	82.434	82.962
802.11ax HE160 SU LPI	164.430	165.186
802.11a20 SP	20.826	22.818
802.11a40 SP	41.100	54.156
802.11a80 SP	85.910	113.984
802.11a160 SP	162.708	169.050
802.11ax HE20 SU SP	21.066	22.650
802.11ax HE40 SU SP	42.288	45.180
802.11ax HE80 SU SP	81.686	82.874
802.11ax HE160 SU SP	163.758	164.514
802.11a20 VLP	20.922	22.812
802.11a40 VLP	42.684	44.196
802.11a80 VLP	107.302	115.674
802.11a160 VLP	163.296	164.724
802.11ax HE20 SU VLP	22.152	22.824
802.11ax HE40 SU VLP	44.268	45.396
802.11ax HE80 SU VLP	82.434	82.896
802.11ax HE160 SU VLP	164.598	165.144

Table 106 - 26 dB Bandwidth Summary Results - MIMO CDD






Figure 195 - 802.11a40 LPI Minimum 26 dB EBW



Figure 196 - 802.11a40 LPI Maximum 26 dB EBW




Figure 197 - 802.11a80 LPI Minimum 26 dB EBW




Figure 198 - 802.11a80 LPI Maximum 26 dB EBW




Figure 199 - 802.11a160 LPI Minimum 26 dB EBW




Figure 200 - 802.11a160 LPI Maximum 26 dB EBW

