

MEASUREMENT REPORT**FCC PART 15.407 / ISSED RSS-248 UNII 6GHz OFDM 802.11a/ax/be (OFDM)****Applicant Name:**

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

09/18/2025 - 12/4/2025

Test Report Issue Date:

1/28/2026

Test Site/Location:

Element Materials Technology, Morgan Hill, CA, USA

Test Report Serial No.:

1C2509100080-24-R2.BCG

FCC ID:

BCGA3460

IC:

579C-A3460

APPLICANT:

Apple Inc.

Application Type:

Certification

Model/HVIN:

A3460, A3463

EUT Type:

Tablet Device

Frequency Range:

5955 – 7115MHz

Modulation Type:

OFDM

FCC Classification:

15E 6GHz Low Power Dual Client (6CD)

FCC Rule Part(s):

Part 15 Subpart E (15.407)

ISSED Specification:

RSS-248 Issue 3

Test Procedure(s):

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to
C63.10a:2024, KDB 789033 D02 v02r01

KDB 662911 D01 v02r01, KDB 987594 D02 v03


KDB 987594 D03 v03r04, KDB 987594 D04 v03

KDB 987594 D01 v03r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 and KDB 789033 D02 v02r01. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1C2509100080-24-R2.BCG) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



RJ Ortanez
Executive Vice President



FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 1 of 259

Revision Summary

Revision	Date	Comments	Revised By
-	12/5/2025	Initial release	WKR0000010733
R1	1/5/2025	Addressed TCB comments in sections 7.4.9, 7.4.10, and 7.7.7	WKR0000010733
R2	1/8/2026	Addressed TCB comments in sections 2.0, 6.0, 7.3, 7.4, 7.6, 7.7	WKR0000007358

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 2 of 259

V 11.0 5/2025


TABLE OF CONTENTS

1.0	INTRODUCTION	5
1.1	Scope	5
1.2	Element Materials Technology Test Location	5
1.3	Test Facility / Accreditations	5
2.0	PRODUCT INFORMATION	6
2.1	Equipment Description	6
2.2	Device Capabilities	6
2.3	Antenna Description	10
2.4	Test Support Equipment	11
2.5	Test Configuration	11
2.6	Software and Firmware	12
2.7	EMI Suppression Device(s)/Modifications	12
3.0	DESCRIPTION OF TESTS	13
3.1	Evaluation Procedure	13
3.2	AC Line Conducted Emissions	13
3.3	Radiated Emissions	14
3.4	Environmental Conditions	14
4.0	ANTENNA REQUIREMENTS	15
5.0	MEASUREMENT UNCERTAINTY	16
6.0	TEST EQUIPMENT CALIBRATION DATA	17
7.0	TEST RESULTS	18
7.1	Summary	18
7.2	26dB & 99% Bandwidth Measurement	19
7.3	Conducted Output Power and Max EIRP Measurement	43
7.4	Maximum Power Spectral Density	60
7.5	In-Band Emissions	109
7.6	Contention Based Protocol	147
7.7	Radiated Spurious Emissions – Above 1GHz	176
7.8	Radiated Spurious Emissions – Below 1GHz	244
7.9	AC Line-Conducted Emissions Measurement	253
8.0	CONCLUSION	259


FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 3 of 259

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



MEASUREMENT REPORT



UNII Band	Channel Bandwidth (MHz)	Mode	Tx Frequency (MHz)	SISO						CDD/SDM Primary		CDD/SDM Diversity	
				Antenna 3c		Antenna 3a		Antenna 1b		Summed		Summed	
				Max e.i.r.p (mW)	Max e.i.r.p (dBm)	Max e.i.r.p (mW)	Max e.i.r.p (dBm)	Max e.i.r.p (mW)	Max e.i.r.p (dBm)	Max e.i.r.p (mW)	Max e.i.r.p (dBm)	Max e.i.r.p (mW)	Max e.i.r.p (dBm)
5	20	802.11a/be	5955 - 6415	8.913	9.50	8.147	9.11	8.851	9.47	8.453	9.27	8.590	9.34
6		802.11a/be	6435 - 6515	8.610	9.35	8.260	9.17	7.621	8.82	8.337	9.21	7.943	9.00
7		802.11a/be	6535 - 6875	8.453	9.27	5.035	7.02	8.511	9.30	6.546	8.16	7.852	8.95
8		802.11a/be	6895 - 7115	7.727	8.88	7.638	8.83	7.943	9.00	7.586	8.80	7.656	8.84
5	40	802.11be	5965 - 6405	16.827	12.26	16.482	12.17	17.100	12.33	16.520	12.18	16.866	12.27
6		802.11be	6445 - 6525	16.982	12.30	16.406	12.15	16.634	12.21	16.406	12.15	16.255	12.11
7		802.11be	6565 - 6845	16.482	12.17	9.863	9.94	16.711	12.23	13.677	11.36	16.406	12.15
8		802.11be	6885 - 7085	16.904	12.28	15.346	11.86	16.558	12.19	16.520	12.18	16.482	12.17
5	80	802.11be	5985 - 6385	33.884	15.30	33.037	15.19	35.400	15.49	32.359	15.10	32.211	15.08
6		802.11be	6465	33.037	15.19	33.729	15.28	29.923	14.76	32.137	15.07	30.479	14.84
7		802.11be	6545 - 6865	34.435	15.37	20.091	13.03	34.514	15.38	27.797	14.44	33.266	15.22
8		802.11be	6945 - 7025	33.037	15.19	27.353	14.37	28.510	14.55	30.832	14.89	32.137	15.07
5	160	802.11be	6025 - 6345	66.069	18.20	57.544	17.60	49.659	16.96	65.013	18.13	62.517	17.96
6		802.11be	6505	59.020	17.71	39.264	15.94	36.224	15.59	52.119	17.17	49.888	16.98
7		802.11be	6665 - 6825	62.087	17.93	32.211	15.08	55.081	17.41	50.466	17.03	61.376	17.88
8		802.11be	6985	61.660	17.90	27.353	14.37	28.445	14.54	58.749	17.69	59.979	17.78

EUT Overview Low Power Indoor

UNII Band	Channel Bandwidth (MHz)	Mode	Tx Frequency (MHz)	SISO						CDD/SDM Primary		CDD/SDM Diversity	
				Antenna 3c		Antenna 3a		Antenna 1b		Summed		Summed	
				Max e.i.r.p (mW)	Max e.i.r.p (dBm)	Max e.i.r.p (mW)	Max e.i.r.p (dBm)	Max e.i.r.p (mW)	Max e.i.r.p (dBm)	Max e.i.r.p (mW)	Max e.i.r.p (dBm)	Max e.i.r.p (mW)	Max e.i.r.p (dBm)
5	20	802.11a/be	5955 - 6415	133.660	21.26	56.885	17.55	49.888	16.98	167.880	22.25	167.494	22.24
6		802.11a/be	6435 - 6515	140.281	21.47	39.811	16.00	35.318	15.48	156.675	21.95	157.761	21.98
7		802.11a/be	6535 - 6855	140.281	21.47	33.037	15.19	55.590	17.45	155.239	21.91	157.036	21.96
5		802.11be	5965 - 6405	133.045	21.24	54.200	17.34	50.350	17.02	171.396	22.34	174.985	22.43
6	40	802.11be	6445 - 6525	136.144	21.34	38.637	15.87	53.827	17.31	157.398	21.97	155.597	21.92
7		802.11be	6565 - 6845	138.995	21.43	32.211	15.08	55.590	17.45	183.231	22.63	181.134	22.58
5		802.11be	5985 - 6385	133.045	21.24	56.885	17.55	47.643	16.78	175.388	22.44	165.959	22.20
6		802.11be	6465	135.519	21.32	38.905	15.90	36.224	15.59	146.218	21.65	148.936	21.73
7	80	802.11be	6545 - 6755	137.404	21.38	33.113	15.20	56.105	17.49	155.239	21.91	152.405	21.83
5		802.11be	6025 - 6345	137.721	21.39	56.364	17.51	49.431	16.94	170.608	22.32	168.655	22.27
6		802.11be	6505	138.995	21.43	39.446	15.96	35.318	15.48	154.525	21.89	155.239	21.91
7		802.11be	6665	138.357	21.41	31.769	15.02	55.208	17.42	150.314	21.77	150.314	21.77

EUT Overview Standard Power

FCC ID: BCGA3460 IC: 579C-A3460	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 4 of 259

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Materials Technology Test Location

These measurement tests were conducted at the Element Materials Technology facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element Materials Technology located in Morgan Hill, CA 95037, U.S.A.

- Element Materials Technology is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Materials Technology facility is a registered (22831) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 5 of 259

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Tablet Device FCC ID: BCGA3460** and **IC: 579C-A3460**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter while operating in the 6GHz band.

Test Device Serial No.: QPC2DN40YW, H2KYFYWQTT, WR4GQV9FQ2, VWLP4NP645, DLXHKV0001700013YR, DLXHKV0001A00013YR

2.2 Device Capabilities

This device contains the following capabilities:

850/1700/1900 WCDMA/HSPA, Multi-band LTE, 5G NR (FR1), 802.11b/g/n/ax/be WLAN, 802.11a/n/ac/ax/be UNII (5GHz and 6GHz), 802.15.4, Bluetooth (1x, EDR, LE, HDR, HDT), Narrowband (NB) UNII (5GHz and 6GHz), WPT.

This device supports BT Beamforming.

This device supports channel puncturing and channel bandwidth reduction.

Standard Power (SP) mode is supported in U-NII Bands 5 and 7 for FCC and U-NII Bands 5, 6 and 7 for ISSED. Low Power Indoor (LPI) mode is supported in U-NII Bands 5, 6, 7, 8. Throughout report, data of Standard Power mode is denoted as SP while data of Low Power Indoor mode is denoted as LPI.

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 6 of 259

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Band 5

Ch.	Frequency (MHz)
1	5955
:	:
45	6175
:	:
93	6415

Band 6

Ch.	Frequency (MHz)
97	6435
:	:
105	6475
:	:
113	6515

Band 7

Ch.	Frequency (MHz)
117	6535
:	:
149	6695
:	:
185	6875

Band 8

Ch.	Frequency (MHz)
189	6895
:	:
209	6995
:	:
233	7115

Table 2-1. 802.11a/ax/be (20MHz) Frequency / Channel Operations

Band 5

Ch.	Frequency (MHz)
3	5965
:	:
43	6165
:	:
91	6405

Band 6

Ch.	Frequency (MHz)
99	6445
:	:
107	6485
:	:
115	6525

Band 7

Ch.	Frequency (MHz)
123	6565
:	:
155	6725
:	:
179	6845

Band 8

Ch.	Frequency (MHz)
187	6885
:	:
211	7005
:	:
227	7085

Table 2-2. 802.11ax/be (40MHz BW) Frequency / Channel Operations

Band 5

Ch.	Frequency (MHz)
7	5985
:	:
39	6145
:	:
87	6385

Band 6

Ch.	Frequency (MHz)
103	6465

Band 7

Ch.	Frequency (MHz)
119	6545
:	:
151	6705
:	:
183	6865

Band 8

Ch.	Frequency (MHz)
199	6945
:	:
215	7025

Table 2-3. 802.11ax/be (80MHz BW) Frequency / Channel Operations

Band 5

Ch.	Frequency (MHz)
15	6025
:	:
47	6185
:	:
79	6345

Band 6

Ch.	Frequency (MHz)
111	6505

Band 7

Ch.	Frequency (MHz)
143	6665
:	:
175	6825

Band 8

Ch.	Frequency (MHz)
207	6985

Table 2-4. 802.11ax/be (160MHz BW) Frequency / Channel Operations

6GHz NII operation is possible in 20MHz, 40MHz, 80MHz, and 160MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) KDB 789033 D02 v02r01 and ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

802.11 Mode/Band	Duty Cycle [%]									
	Antenna 3c		Antenna 3a		Antenna 1b		CDD/SDM Primary		CDD/SDM Diversity	
	Duty Cycle [%]	DCCF [dB]	Duty Cycle [%]	DCCF [dB]	Duty Cycle [%]	DCCF [dB]	Duty Cycle [%]	DCCF [dB]	Duty Cycle [%]	DCCF [dB]
a (Low Data Rate)	98.378	0.071	98.583	0.062	98.787	0.053	98.378	0.071	98.787	0.053
a (Mid Data Rate)	100.000	0.000	98.628	0.060	98.628	0.060	100.000	0.000	100.000	0.000
a (High Data Rate)	98.719	0.056	100.000	0.000	100.000	0.000	98.992	0.044	100.000	0.000
be(SU)(EHT20) (Low Data Rate)	98.742	0.055	98.764	0.054	98.651	0.059	98.742	0.055	98.833	0.051
be(SU)(EHT20) (Mid Data Rate)	98.719	0.056	98.492	0.066	100.000	0.000	98.855	0.050	98.719	0.056
be(SU)(EHT20) (High Data Rate)	100.000	0.000	98.924	0.047	100.000	0.000	98.492	0.066	98.924	0.047
be(SU)(EHT40) (Low Data Rate)	98.492	0.066	98.492	0.066	98.992	0.044	98.924	0.047	98.492	0.066
be(SU)(EHT40) (Mid Data Rate)	98.492	0.066	98.924	0.047	98.992	0.044	98.992	0.044	98.288	0.075
be(SU)(EHT40) (High Data Rate)	98.742	0.055	100.000	0.000	98.742	0.055	98.514	0.065	98.855	0.050
be(SU)(EHT80) (Low Data Rate)	98.946	0.046	98.946	0.046	100.000	0.000	98.651	0.059	98.946	0.046
be(SU)(EHT80) (Mid Data Rate)	98.992	0.044	98.719	0.056	98.514	0.065	98.719	0.056	98.288	0.075
be(SU)(EHT80) (High Data Rate)	98.424	0.069	98.583	0.062	98.764	0.054	98.764	0.054	98.583	0.062
be(SU)(EHT160) (Low Data Rate)	98.969	0.045	98.492	0.066	98.969	0.045	98.924	0.047	98.469	0.067
be(SU)(EHT160) (Mid Data Rate)	98.583	0.062	100.000	0.000	100.000	0.000	98.175	0.080	98.696	0.057
be(SU)(EHT160) (High Data Rate)	98.175	0.080	97.701	0.101	98.130	0.082	97.836	0.095	98.288	0.075

Table 2-5. Measured Duty Cycles

CDD/SDM Primary = Antenna 3c + Antenna 3a
CDD/SDM Diversity = Antenna 3c + Antenna 1b

FCC ID: BCGA3460 IC: 579C-A3460	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 8 of 259

1. The device employs MIMO technology. Below are the possible configurations.

WiFi Configurations		SISO			CDD			SDM			STBC		
		Antenna 3c	Antenna 3a	Antenna 1b	Antenna 3c	Antenna 3a	Antenna 1b	Antenna 3c	Antenna 3a	Antenna 1b	Antenna 3c	Antenna 3a	Antenna 1b
6GHz	11a	✓	✓	✓	✓	✓	✓	✗	✗	✗	✗	✗	✗
	11ax/be(SU) (20MHz)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	11ax/be(SU) (40MHz)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	11ax/be(SU) (80MHz)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	11ax/be(SU) (160MHz)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

Table 2-6. WIFI Configurations

✓ = Support ; ✗ = NOT Support

SISO = Single Input Single Output

SDM = Spatial Diversity Multiplexing – MIMO function

CDD = Cyclic Delay Diversity - 2Tx Function

STBC = Space-Time Block Coding – 2Tx Function

2. The device supports the following data rates (shown in Mbps):

802.11a 20MHz	MCS Index		Spatial Stream	OFDM (802.11ax/be)												
				20MHz			40MHz			80MHz			160MHz			
	HE	EHT		0.8μs GI	1.6μs GI	3.2μs GI	0.8μs GI	1.6μs GI	3.2μs GI	0.8μs GI	1.6μs GI	3.2μs GI	0.8μs GI	1.6μs GI	3.2μs GI	
6	0	0	1	8.6	8.1	7.3	17.2	16.3	14.6	36	34	30.6	72.1	68.1	61.3	Low Rate
9	1	1	1	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3	144.1	136.1	122.5	
12	2	2	1	25.8	24.4	21.9	51.6	48.8	43.9	108.1	102.1	91.5	216.2	204.2	183.8	
18	3	3	1	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5	288.2	272.2	245	Mid Rate
24	4	4	1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8	432.4	408.3	367.5	
36	5	5	1	68.8	65	58.5	137.6	130	117	288.2	272.2	245	576.5	544.4	490	
48	6	6	1	77.4	73.1	65.8	154.9	146.3	131.6	324.3	306.3	275.6	648.5	612.5	551.3	High Rate
54	7	7	1	86	81.3	73.1	172.1	162.5	146.3	360.3	340.3	306.3	720.6	680.6	612.5	
-	8	8	1	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5	864.7	816.7	735	
-	9	9	1	114.7	108.3	97.5	229.4	216.7	195	480.4	453.7	408.3	960.8	907.4	816.7	
-	10	10	1	129	121.9	109.7	258.1	243.8	219.4	540.4	510.4	459.4	1080.9	1020.8	918.8	
-	11	11	1	143.4	135.4	121.9	286.8	270.8	243.8	600.5	567.1	510.4	1201	1134.3	1020.8	
6	0	0	2	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3	144.1	136.1	122.5	Low Rate
9	1	1	2	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5	288.2	272.2	245	
12	2	2	2	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8	432.4	408.3	367.5	
18	3	3	2	68.8	65	58.5	137.6	130	117	288.2	272.2	245	576.5	544.4	490	Mid Rate
24	4	4	2	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5	864.7	816.7	735	
36	5	5	2	137.6	130	117	275.3	260	234	576.5	544.4	490	1152.9	1089	980	
48	6	6	2	154.9	146.3	131.6	309.8	292.6	263.3	648.5	612.5	551.3	1296.9	1225	1102.5	High Rate
54	7	7	2	172.1	162.5	146.3	344.1	325	292.5	720.6	680.6	612.5	1441.2	1361.1	1225	
-	8	8	2	206.5	195	175.5	412.9	390	351	864.7	816.7	735	1729.4	1633.3	1470	
-	9	9	2	229.4	216.7	195	458.8	433	390	960.8	907.4	816.7	1921.6	1814.8	1633.3	
-	10	10	2	258.1	243.8	219.4	516.2	487.5	438.8	1080.9	1020.8	918.8	2161.8	2041.7	1837.5	
-	11	11	2	286.8	270.8	243.8	573.5	541.7	487.5	1201	1134.3	1020.8	2402	2268.5	2041.7	

Table 2-7. Supported Data Rates

FCC ID: BCGA3460 IC: 579C-A3460	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 9 of 259

3. This device supports simultaneous transmission operations, which allows multiple transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.

Antenna	Simultaneous Tx Config	Bluetooth 2.4GHz	Thread	WLAN	NB UNII	WIFI 5GHz	WIFI 6GHz	LTE / FR1 NR		
		BDR, EDR, LE HDR, HDT	802.15.4	802.11 b/g/n/ax/be	BDR, EDR, LE HDR, HDT	802.11 a/n/ac/ax/be	802.11 a/ax/be	LB	MB/HB	UHB
Ant 1a	Config 1	✗	✗	✓	✗	✗	✗	✗	✓	✗
Ant 1a	Config 2	✗	✗	✓	✗	✗	✗	✗	✗	✓
Ant 1a	Config 3	✓	✗	✗	✗	✗	✗	✗	✓	✗
Ant 1a	Config 4	✓	✗	✗	✗	✗	✗	✗	✗	✓
Ant 1a	Config 5	✗	✓	✗	✗	✗	✗	✗	✓	✗
Ant 1a	Config 6	✗	✓	✗	✗	✗	✗	✗	✗	✓
Ant 1b	Config 7	✗	✗	✗	✗	✓	✗	✗	✓	✗
Ant 1b	Config 8	✗	✗	✗	✗	✗	✓	✗	✓	✗
Ant 1b	Config 9	✗	✗	✗	✓	✗	✗	✗	✓	✗
Ant 3a	Config 10	✗	✗	✓	✓	✗	✗	✗	✓	✗
Ant 3a	Config 11	✓	✗	✗	✗	✓	✗	✗	✓	✗
Ant 3a	Config 12	✗	✓	✗	✗	✓	✗	✗	✓	✗
Ant 3a	Config 13	✓	✗	✗	✗	✗	✓	✗	✓	✗
Ant 3a	Config 14	✗	✓	✗	✗	✗	✓	✗	✓	✗

Table 2-8. Simultaneous Transmission Configurations

✓ = Support; ✗ = Not Support

Note:

All the above simultaneous transmission configurations have been tested and the worst-case configuration was found to be Config 11 and reported in RF Bluetooth, RF UNII 5GHz OFDM, RSS-199 and RF Part 27b test reports.

2.3 Antenna Description

Following antenna gains provided by the manufacturer were used for the testing.

UNII Band	Frequency [GHz]	Highest Antenna Gain (dBi)			Lowest Antenna Gain (dBi)		
		Antenna 3c	Antenna 3a	Antenna 1b	Antenna 3c	Antenna 3a	Antenna 1b
5	5.925 – 6.095	2.2	0.6	-1.1	1.8	0.5	-1.7
	6.115 – 6.255	1.9	0.5	0.1	1.2	0.4	-0.8
	6.275 – 6.415	2.4	-0.7	-0.4	2.4	-0.7	-0.4
6	6.435 – 6.515	2.5	-0.5	-0.9	2.5	-0.5	-0.9
7	6.535 – 6.855	2.5	-1.3	1.0	1.8	-1.9	-0.5
8	6.895 – 7.115	3.3	-2.0	-1.8	1.8	-2.3	-3.4

Table 2-9. Antenna Gains

FCC ID: BCGA3460 IC: 579C-A3460	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 10 of 259

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

2.4 Test Support Equipment

1	Apple MacBook Pro	Model:	A2141	S/N:	C02H604EQ05D
	w/AC/DC Adapter	Model:	A2166	S/N:	C4H042705ZNPM0WA6
2	Apple USB-C Cable	Model:	Spartan	S/N:	GXXK1336018XKTR024
3	USB-C Cable	Model:	A2795	S/N:	DWH80115BK826GV19
	w/ AC Adapter	Model:	A2305	S/N:	C4H95160004PF4F4V
4	Apple Pencil	Model:	A2538	S/N:	KJ26TCFXJW
5	DC Power Supply	Model:	KPS3010D	S/N:	N/A
6	ASUS ROG Rapture	Model:	GT-BE98 Pro	S/N:	S4IG6M200654J6F

Table 2-10. Test Support Equipment List

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024, KDB 789033 D02 v02r01 and KDB 987594 D02 v03. ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, and 7.5 for antenna port conducted emissions test setups.

There are two vendors of the WiFi/Bluetooth radio modules, variant 1 and variant 2. Both radio modules have the same mechanical outline, same on-board antenna matching circuit, identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances. The worst case configuration was found between the two variants. The EUT was also investigated with and without charger.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power and the worst case channel were reported.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

For AC line conducted and radiated test below 1GHz, following configuration were investigated and EUT powered by AC/DC was the worst case.

- EUT powered by AC/DC adaptor via USB-C cable with wire charger
- EUT powered by host PC via USB-C cable with wire charger

802.11be-mode test data provided in this report covers 802.11ax as target powers are identical.

802.11ax/be HE20/40/80/160 2TX SDM mode test data provided in this report covers 802.11ax/be HE20/40/80/160 2TX STBC mode.

The data rates have been categorized into three groups: low, middle, and high data rates (see Table 2-7). All three groups have been investigated, and only the worst-case data rate has been reported.

For 802.11be-RU test results, see separate UNII 6GHz OFDMA report 1C2509100080-25-R2.BCG.

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 11 of 259

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

2.6 Software and Firmware

The test was conducted with firmware version 23D40 installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 12 of 259

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024) and the guidance provided in KDB 789033 D02 v02r01 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14kHz - 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.9. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.50.40.

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 13 of 259

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

Per KDB 414788, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was used while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BCGA3460 IC: 579C-A3460	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 14 of 259

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 15 of 259

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	2.00
Line Conducted Disturbance	1.88
Radiated Disturbance (<30MHz)	4.24
Radiated Disturbance (30MHz - 1GHz)	4.96
Radiated Disturbance (1 - 18GHz)	5.18
Radiated Disturbance (>18GHz)	5.18

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 16 of 259

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance with the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Anritsu	ML2496A	Power Meter	2/10/2025	Annual	2/10/2026	1306009
Anritsu	MA2411B	Pulse Power Sensor	2/10/2025	Annual	2/10/2026	1315051
Anritsu	MA2411B	Pulse Power Sensor	2/10/2025	Annual	2/10/2026	1339027
ATM	180-442-KF	20dB Nominal Gain Horn Antenna	3/24/2025	Annual	3/24/2026	T058601-02
ETS-Lindgren	3117	Double Ridged Guide Horn (1-18 GHz)	4/16/2025	Annual	4/16/2026	218555
Fairview Microwave/MCL	FMCA1975-36/BW-K10-2W44+	30MHz-40GHz RF Cable/Attenuator *	6/10/2025	Annual	6/10/2026	-
Fairview Microwave	FM2CP1122-10	Directional Coupler *	6/10/2025	Annual	6/10/2026	1946
Keysight Technology	N9040B	UXA Signal Analyzer	9/8/2025	Annual	9/8/2026	MY61320121
Keysight Technology	N9030A	PXA Signal Analyzer	9/15/2025	Annual	9/15/2026	MY49430494
Mini-Circuits	ZN2PD-9G	Power Splitter*	9/16/2025	Annual	9/16/2026	SF456200530
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	8/6/2025	Annual	8/6/2026	101639
Rohde & Schwarz	FSW43	Spectrum Analyzer 2Hz to 43GHz	11/21/2024	Annual	11/21/2025	104093
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	5/13/2025	Annual	5/13/2026	101867
Rohde & Schwarz	SMW200A	Vector Signal Generator	3/10/2025	Annual	3/10/2026	110589
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	11/15/2024	Annual	11/15/2025	102326
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	10/14/2025	Annual	10/14/2026	102328
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	6/3/2025	Annual	6/3/2026	100052
Rohde & Schwarz	HFH2-Z2	Loop Antenna	5/12/2025	Annual	5/12/2026	100546
Rohde & Schwarz	ENV216	Two-Line V-Network	4/24/2025	Annual	4/24/2026	101364
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	3/4/2025	Annual	3/4/2026	164715
Rohde & Schwarz	CMX500	Wideband Radio Communication Tester	11/11/2024	Annual	11/11/2025	100298
Schwarzbeck	VULB 9162	Bilog Antenna (30MHz - 6GHz)	10/8/2025	Annual	10/8/2026	00358

Table 6-1. Test Equipment List

Note:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- * denotes passive equipment that have been internally verified/calibrated.

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 17 of 259

V 11.0 5/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.
 FCC ID: BCGA3460
 IC: 579C-A3460
 FCC Classification: 15E 6GHz Low Power Dual Client (6CD)

FCC Part Section(s) / KDB Reference	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049, 15.407(a)(11)	RSS Gen [6.7], RSS-248 [4.4]	Occupied Bandwidth/ 26dB Bandwidth	99% of the occupied bandwidth of any channel must be contained within each of its respective U-NII sub bands < 320MHz (5.925 - 7.125GHz)	CONDUCTED	PASS	Section 7.2
15.407(a)(8)	RSS-248 [4.5.3]	Maximum Power Spectral Density	< -1dBm/MHz e.i.r.p. for Low Power Indoor		PASS	Section 7.4
15.407(a)(7)	RSS-248 [4.5.5]		< 17dBm/MHz e.i.r.p. for Standard Power		PASS	
15.407(a)(8)	RSS-248 [4.5.3]	Maximum EIRP	< 24dBm over the frequency band of operation		PASS	Section 7.3
15.407(a)(7)	RSS-248 [4.5.5]		< 30dBm over the frequency band of operation		PASS	
15.407(b)(7)	RSS-248 [4.6.2]	In-Band Emissions	EUT must meet the limits detailed in 15.407(b)(7) and RSS-248 [4.6.2] b)		PASS	Section 7.5
15.407(d)(6)	RSS-248 [4.7]	Contention Based Protocol	EUT must detect AWGN signal with 90% (or better) certainty		PASS	Section 7.6
15.407(a)(7)	RSS-248 [4.5.5]	Proper Power Adjustment, Client Devices Connected to a Standard Power Access Point	EUT maintains its power level at least 6 dB lower than that of the standard-power access point		PASS	See UNII 6GHz OFDMA Report 1C25091000 80-25-R2.BCG
987594 D02 v03	987594 D02 v03	Dual Client Test, Demonstration of Proper Power Adjustment based on Associated AP	EUT maximum power level shall not exceed 30dBm EIRP when connected to Standard Power AP, and 24dBm EIRP when connected to Low Power Indoor AP		PASS	
15.407(b)(6)	RSS-248 [4.6.2]	Undesirable Emissions	< -27dBm/MHz e.i.r.p. outside of the 5.925 – 7.125GHz band	RADIATED	PASS	Section 7.7
15.205, 15.209	RSS-248 [4.6.2] RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])		PASS	Section 7.7, 7.8
15.407(b)(9)	RSS-Gen [8.8]	AC Conducted Emissions (150kHz – 30MHz)	< FCC 15.207 (RSS-Gen [8.8]) limits	LINE CONDUCTED	PASS	Section 7.9

Table 7-1. Summary of Test Results

Notes:

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “Conducted Automation,” Version 1.4.0.
- 5) For radiated testing, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “Chamber Automation,” Version 3.4.2.
- 6) All radiated measurements were tested at the highest supported power setting per band.

FCC ID: BCGA3460 IC: 579C-A3460	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 18 of 259

V 11.0 5/2025

7.2 26dB & 99% Bandwidth Measurement

\$2.1049; \$15.407; RSS-Gen [6.7]

Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 and KDB 789033 D02 v02r01, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

Test Procedure Used

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 – Section 12.5.2
KDB 789033 D02 v02r01 – Section C

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 26$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = in the range of 1% to 5% of the emission bandwidth
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

1. All data rates and antenna configurations were investigated, and tabular data has been reported. Only the worst-case plot per bandwidth was reported.

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 19 of 259

V 11.0 5/2025





Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.2.1 Antenna 3c 26dB & 99% Bandwidth Measurements – SP


	Frequency [MHz]	Channel	802.11 MODE	Data Rate	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	a	6Mbps	17.98	22.74	320	Pass
	6175	45	a	6Mbps	17.98	22.61	320	Pass
	6415	93	a	6Mbps	17.99	22.91	320	Pass
	5955	1	be (20MHz)	MCS0	19.03	22.92	320	Pass
	6175	45	be (20MHz)	MCS0	19.06	22.97	320	Pass
	6415	93	be (20MHz)	MCS5	19.04	22.93	320	Pass
	5965	3	be (40MHz)	MCS0	38.06	44.26	320	Pass
	6165	43	be (40MHz)	MCS0	38.13	43.83	320	Pass
	6405	91	be (40MHz)	MCS0	38.06	44.48	320	Pass
	5985	7	be (80MHz)	MCS0	77.69	82.51	320	Pass
	6145	39	be (80MHz)	MCS5	77.52	82.87	320	Pass
	6385	87	be (80MHz)	MCS3	77.49	82.47	320	Pass
	6025	15	be (160MHz)	MCS5	156.71	174.61	320	Pass
	6185	47	be (160MHz)	MCS5	156.64	176.78	320	Pass
	6345	79	be (160MHz)	MCS5	156.94	174.35	320	Pass
Band 6	6435	97	a	6Mbps	18.03	23.23	320	Pass
	6475	105	a	6Mbps	18.02	22.64	320	Pass
	6515	113	a	6Mbps	18.03	23.39	320	Pass
	6435	97	be (20MHz)	MCS0	19.06	23.09	320	Pass
	6475	105	be (20MHz)	MCS0	19.08	23.14	320	Pass
	6515	113	be (20MHz)	MCS0	19.05	23.47	320	Pass
	6445	99	be (40MHz)	MCS0	38.05	43.97	320	Pass
	6485	107	be (40MHz)	MCS0	38.06	44.80	320	Pass
	6525	115	be (40MHz)	MCS3	38.12	44.68	320	Pass
	6465	103	be (80MHz)	MCS3	77.52	82.51	320	Pass
	6505	111	be (160MHz)	MCS5	156.80	177.76	320	Pass
	6535	117	a	6Mbps	18.02	23.88	320	Pass
	6695	149	a	6Mbps	18.00	23.37	320	Pass
	6855	181	a	12Mbps	17.91	23.10	320	Pass
Band 7	6535	117	be (20MHz)	MCS0	19.07	22.68	320	Pass
	6695	149	be (20MHz)	MCS0	19.07	24.74	320	Pass
	6855	181	be (20MHz)	MCS0	19.10	23.15	320	Pass
	6565	123	be (40MHz)	MCS0	38.01	44.36	320	Pass
	6725	155	be (40MHz)	MCS3	38.11	44.69	320	Pass
	6845	179	be (40MHz)	MCS3	38.10	45.98	320	Pass
	6545	119	be (80MHz)	MCS3	77.67	83.00	320	Pass
	6705	151	be (80MHz)	MCS3	77.60	82.70	320	Pass
	6785	167	be (80MHz)	MCS0	77.60	82.40	320	Pass
	6665	143	be (160MHz)	MCS5	156.91	178.59	320	Pass

Table 7-2. Conducted Bandwidth Measurements Antenna 3c


FCC ID: BCGA3460 IC: 579C-A3460	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 20 of 259




FCC ID: BCGA3460 IC: 579C-A3460			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 21 of 259	




Plot 7-5 26dB BW & 99% OBW Antenna 3c (20MHz BW 802.11be(SU) - Ch.113)



Plot 7-7 26dB BW & 99% OBW Antenna 3c (80MHz BW 802.11be(SU) - Ch.103)



Plot 7-6 26dB BW & 99% OBW Antenna 3c (40MHz BW 802.11be(SU) - Ch.107)




Plot 7-8 26dB BW & 99% OBW Antenna 3c (160MHz BW 802.11be(SU) - Ch.111)


FCC ID: BCGA3460 IC: 579C-A3460	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 22 of 259




Plot 7-9 26dB BW & 99% OBW Antenna 3c (20MHz BW 802.11be(SU) - Ch.149)



Plot 7-11 26dB BW & 99% OBW Antenna 3c (80MHz BW 802.11be(SU) - Ch.119)



Plot 7-10 26dB BW & 99% OBW Antenna 3c (40MHz BW 802.11be(SU) - Ch.179)



Plot 7-12 26dB BW & 99% OBW Antenna 3c (160MHz BW 802.11be(SU) - Ch.143)

FCC ID: BCGA3460 IC: 579C-A3460			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 23 of 259	

7.2.2 Antenna 3c 26dB & 99% Bandwidth Measurements – LPI

	Frequency [MHz]	Channel	802.11 MODE	Data Rate	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	a	36Mbps	18.34	31.02	320	Pass
	6175	45	a	36Mbps	18.28	29.22	320	Pass
	6415	93	a	36Mbps	18.36	29.49	320	Pass
	5955	1	be (20MHz)	MCS5	19.41	31.45	320	Pass
	6175	45	be (20MHz)	MCS5	19.35	30.31	320	Pass
	6415	93	be (20MHz)	MCS5	19.34	31.94	320	Pass
	5965	3	be (40MHz)	MCS5	38.68	62.26	320	Pass
	6165	43	be (40MHz)	MCS5	38.70	62.93	320	Pass
	6405	91	be (40MHz)	MCS5	38.76	63.14	320	Pass
	5985	7	be (80MHz)	MCS5	77.84	118.35	320	Pass
	6145	39	be (80MHz)	MCS5	77.84	111.22	320	Pass
	6385	87	be (80MHz)	MCS5	77.75	104.57	320	Pass
	6025	15	be (160MHz)	MCS5	156.66	173.60	320	Pass
	6185	47	be (160MHz)	MCS5	156.59	173.96	320	Pass
Band 6	6345	79	be (160MHz)	MCS5	156.59	170.92	320	Pass
	6435	97	a	36Mbps	18.27	29.74	320	Pass
	6475	105	a	36Mbps	18.31	29.57	320	Pass
	6515	113	a	36Mbps	18.36	30.02	320	Pass
	6435	97	be (20MHz)	MCS5	19.40	31.15	320	Pass
	6475	105	be (20MHz)	MCS5	19.36	30.24	320	Pass
	6515	113	be (20MHz)	MCS5	19.33	31.24	320	Pass
	6445	99	be (40MHz)	MCS5	38.92	64.47	320	Pass
	6485	107	be (40MHz)	MCS0	38.27	45.87	320	Pass
	6525	115	be (40MHz)	MCS0	38.25	45.10	320	Pass
	6465	103	be (80MHz)	MCS5	77.80	102.87	320	Pass
	6505	111	be (160MHz)	MCS5	156.58	170.43	320	Pass
	6535	117	a	36Mbps	18.32	30.53	320	Pass
	6695	149	a	36Mbps	18.28	31.04	320	Pass
Band 7	6875	185	a	36Mbps	18.35	29.37	320	Pass
	6535	117	be (20MHz)	MCS5	19.39	31.74	320	Pass
	6695	149	be (20MHz)	MCS5	19.34	30.65	320	Pass
	6875	185	be (20MHz)	MCS5	19.42	31.59	320	Pass
	6565	123	be (40MHz)	MCS5	38.72	62.95	320	Pass
	6725	155	be (40MHz)	MCS5	38.61	61.44	320	Pass
	6845	179	be (40MHz)	MCS5	38.68	63.54	320	Pass
	6545	119	be (80MHz)	MCS5	77.77	103.08	320	Pass
	6705	151	be (80MHz)	MCS5	77.81	97.13	320	Pass
	6865	183	be (80MHz)	MCS5	77.75	102.87	320	Pass
	6665	143	be (160MHz)	MCS5	156.62	171.63	320	Pass
	6825	175	be (160MHz)	MCS5	156.42	171.28	320	Pass
	6895	189	a	36Mbps	18.30	28.54	320	Pass
	6995	209	a	36Mbps	18.31	30.40	320	Pass
Band 8	7115	233	a	36Mbps	18.39	30.78	320	Pass
	6895	189	be (20MHz)	MCS5	19.36	31.26	320	Pass
	6995	209	be (20MHz)	MCS5	19.38	30.63	320	Pass
	7115	233	be (20MHz)	MCS5	19.35	30.49	320	Pass
	6885	187	be (40MHz)	MCS5	38.74	63.24	320	Pass
	7005	211	be (40MHz)	MCS5	38.65	64.34	320	Pass
	7085	227	be (40MHz)	MCS5	38.82	63.99	320	Pass
	6945	199	be (80MHz)	MCS5	77.84	102.53	320	Pass
	7025	215	be (80MHz)	MCS5	77.86	118.59	320	Pass
	6985	207	be (160MHz)	MCS5	156.60	173.15	320	Pass

Table 7-3. Conducted Bandwidth Measurements Antenna 3c

FCC ID: BCGA3460 IC: 579C-A3460	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 24 of 259

V 11.0 5/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-13 26dB BW & 99% OBW Antenna 3c (20MHz BW 802.11be(SU) - Ch.93)



Plot 7-15 26dB BW & 99% OBW Antenna 3c (80MHz BW 802.11be(SU) - Ch.7)




Plot 7-14 26dB BW & 99% OBW Antenna 3c (40MHz BW 802.11be(SU) - Ch.91)



Plot 7-16 26dB BW & 99% OBW Antenna 3c (160MHz BW 802.11be(SU) - Ch.47)

FCC ID: BCGA3460 IC: 579C-A3460			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 25 of 259	




Plot 7-17 26dB BW & 99% OBW Antenna 3c (20MHz BW 802.11be(SU) - Ch.113)



Plot 7-19 26dB BW & 99% OBW Antenna 3c (80MHz BW 802.11be(SU) - Ch.103)



Plot 7-18 26dB BW & 99% OBW Antenna 3c (40MHz BW 802.11be(SU) - Ch.99)



Plot 7-20 26dB BW & 99% OBW Antenna 3c (160MHz BW 802.11be(SU) - Ch.111)




Plot 7-21 26dB BW & 99% OBW Antenna 3c (20MHz BW 802.11be(SU) - Ch.117)



Plot 7-23 26dB BW & 99% OBW Antenna 3c (80MHz BW 802.11be(SU) - Ch.119)



Plot 7-22 26dB BW & 99% OBW Antenna 3c (40MHz BW 802.11be(SU) - Ch.179)




Plot 7-24 26dB BW & 99% OBW Antenna 3c (160MHz BW 802.11be(SU) - Ch.143)


FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG			Page 26 of 259

Test Dates:
09/18/2025 - 12/4/2025

EUT Type:
Tablet Device




Plot 7-25 26dB BW & 99% OBW Antenna 3c (20MHz BW 802.11be(SU) - Ch.189)



Plot 7-27 26dB BW & 99% OBW Antenna 3c (80MHz BW 802.11be(SU) - Ch.215)



Plot 7-26 26dB BW & 99% OBW Antenna 3c (40MHz BW 802.11be(SU) - Ch.211)



Plot 7-28 26dB BW & 99% OBW Antenna 3c (160MHz BW 802.11be(SU) - Ch.207)


FCC ID: BCGA3460 IC: 579C-A3460			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device		Page 27 of 259

7.2.3 Antenna 3a 26dB & 99% Bandwidth Measurements – SP

	Frequency [MHz]	Channel	802.11 MODE	Data Rate	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	a	6Mbps	17.95	22.65	320	Pass
	6175	45	a	36Mbps	17.87	22.53	320	Pass
	6415	93	a	6Mbps	17.98	22.45	320	Pass
	5955	1	be (20MHz)	MCS0	19.04	23.00	320	Pass
	6175	45	be (20MHz)	MCS0	19.09	23.35	320	Pass
	6415	93	be (20MHz)	MCS3	19.06	23.20	320	Pass
	5965	3	be (40MHz)	MCS0	38.06	44.58	320	Pass
	6165	43	be (40MHz)	MCS0	38.07	44.08	320	Pass
	6405	91	be (40MHz)	MCS3	38.02	44.23	320	Pass
	5985	7	be (80MHz)	MCS3	77.54	82.40	320	Pass
	6145	39	be (80MHz)	MCS3	77.62	82.74	320	Pass
	6385	87	be (80MHz)	MCS5	77.58	82.69	320	Pass
	6025	15	be (160MHz)	MCS5	156.69	170.15	320	Pass
	6185	47	be (160MHz)	MCS5	156.50	174.22	320	Pass
Band 6	6345	79	be (160MHz)	MCS5	156.76	169.74	320	Pass
	6435	97	a	6Mbps	18.00	22.75	320	Pass
	6475	105	a	6Mbps	17.97	22.93	320	Pass
	6515	113	a	6Mbps	17.98	22.80	320	Pass
	6435	97	be (20MHz)	MCS0	19.04	23.11	320	Pass
	6475	105	be (20MHz)	MCS0	19.08	22.48	320	Pass
	6515	113	be (20MHz)	MCS0	19.07	22.80	320	Pass
	6445	99	be (40MHz)	MCS3	38.02	43.89	320	Pass
	6485	107	be (40MHz)	MCS0	38.09	44.46	320	Pass
	6525	115	be (40MHz)	MCS3	38.06	44.10	320	Pass
	6465	103	be (80MHz)	MCS0	77.51	82.64	320	Pass
Band 7	6505	111	be (160MHz)	MCS5	156.58	170.47	320	Pass
	6535	117	a	6Mbps	17.99	22.96	320	Pass
	6695	149	a	6Mbps	18.01	22.65	320	Pass
	6855	181	a	6Mbps	18.01	22.72	320	Pass
	6535	117	be (20MHz)	MCS0	19.10	23.19	320	Pass
	6695	149	be (20MHz)	MCS0	19.09	23.23	320	Pass
	6855	181	be (20MHz)	MCS3	19.03	22.44	320	Pass
	6565	123	be (40MHz)	MCS0	38.09	44.00	320	Pass
	6725	155	be (40MHz)	MCS0	38.03	44.58	320	Pass
	6845	179	be (40MHz)	MCS0	38.10	44.66	320	Pass
	6545	119	be (80MHz)	MCS0	77.64	82.69	320	Pass
	6705	151	be (80MHz)	MCS0	77.58	82.67	320	Pass
	6785	167	be (80MHz)	MCS3	77.45	82.59	320	Pass
	6665	143	be (160MHz)	MCS5	156.62	174.30	320	Pass

Table 7-4. Conducted Bandwidth Measurements Antenna 3a


FCC ID: BCGA3460 IC: 579C-A3460	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 28 of 259




Plot 7-29 26dB BW & 99% OBW Antenna 3a (20MHz BW 802.11be(SU) - Ch.45)



Plot 7-31 26dB BW & 99% OBW Antenna 3a (80MHz BW 802.11be(SU) - Ch.39)







Plot 7-30 26dB BW & 99% OBW Antenna 3a (40MHz BW 802.11be(SU) - Ch.3)



Plot 7-32 26dB BW & 99% OBW Antenna 3a (160MHz BW 802.11be(SU) - Ch.47)

FCC ID: BCGA3460 IC: 579C-A3460	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 29 of 259



FCC ID: BCGA3460 IC: 579C-A3460	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 30 of 259

7.2.4 Antenna 3a 26dB & 99% Bandwidth Measurements – LPI

	Frequency [MHz]	Channel	802.11 MODE	Data Rate	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	a	36Mbps	18.27	29.64	320	Pass
	6175	45	a	36Mbps	18.34	30.92	320	Pass
	6415	93	a	36Mbps	18.23	29.36	320	Pass
	5955	1	be (20MHz)	MCS5	19.45	32.20	320	Pass
	6175	45	be (20MHz)	MCS5	19.36	31.73	320	Pass
	6415	93	be (20MHz)	MCS5	19.34	31.41	320	Pass
	5965	3	be (40MHz)	MCS5	38.56	62.13	320	Pass
	6165	43	be (40MHz)	MCS5	38.67	62.92	320	Pass
	6405	91	be (40MHz)	MCS5	38.56	64.11	320	Pass
	5985	7	be (80MHz)	MCS5	77.82	109.08	320	Pass
	6145	39	be (80MHz)	MCS5	77.88	108.43	320	Pass
	6385	87	be (80MHz)	MCS5	77.94	104.43	320	Pass
	6025	15	be (160MHz)	MCS5	156.53	170.21	320	Pass
	6185	47	be (160MHz)	MCS5	156.42	171.79	320	Pass
Band 6	6345	79	be (160MHz)	MCS5	156.62	174.41	320	Pass
	6435	97	a	36Mbps	18.37	31.16	320	Pass
	6475	105	a	36Mbps	18.28	29.26	320	Pass
	6515	113	a	36Mbps	18.25	29.69	320	Pass
	6435	97	be (20MHz)	MCS5	19.37	31.18	320	Pass
	6475	105	be (20MHz)	MCS5	19.30	32.51	320	Pass
	6515	113	be (20MHz)	MCS5	19.36	31.19	320	Pass
	6445	99	be (40MHz)	MCS5	38.56	63.28	320	Pass
	6485	107	be (40MHz)	MCS0	38.23	45.55	320	Pass
	6525	115	be (40MHz)	MCS0	38.26	45.37	320	Pass
	6465	103	be (80MHz)	MCS5	77.84	114.78	320	Pass
	6505	111	be (160MHz)	MCS5	156.74	171.19	320	Pass
	6535	117	a	36Mbps	18.36	30.41	320	Pass
	6695	149	a	36Mbps	18.20	29.60	320	Pass
Band 7	6875	185	a	36Mbps	18.21	30.49	320	Pass
	6535	117	be (20MHz)	MCS5	19.31	31.25	320	Pass
	6695	149	be (20MHz)	MCS5	19.35	32.00	320	Pass
	6875	185	be (20MHz)	MCS5	19.36	31.62	320	Pass
	6565	123	be (40MHz)	MCS5	38.71	60.99	320	Pass
	6725	155	be (40MHz)	MCS5	38.68	62.54	320	Pass
	6845	179	be (40MHz)	MCS5	38.57	63.47	320	Pass
	6545	119	be (80MHz)	MCS5	77.75	104.59	320	Pass
	6705	151	be (80MHz)	MCS5	77.76	111.92	320	Pass
	6865	183	be (80MHz)	MCS5	77.86	112.36	320	Pass
	6665	143	be (160MHz)	MCS5	156.47	178.98	320	Pass
	6825	175	be (160MHz)	MCS5	156.61	170.98	320	Pass
	6895	189	a	36Mbps	18.20	27.48	320	Pass
	6995	209	a	36Mbps	18.34	29.81	320	Pass
Band 8	7115	233	a	36Mbps	18.23	30.84	320	Pass
	6895	189	be (20MHz)	MCS5	19.45	31.18	320	Pass
	6995	209	be (20MHz)	MCS5	19.39	31.91	320	Pass
	7115	233	be (20MHz)	MCS5	19.32	29.60	320	Pass
	6885	187	be (40MHz)	MCS5	38.63	62.18	320	Pass
	7005	211	be (40MHz)	MCS5	38.61	61.83	320	Pass
	7085	227	be (40MHz)	MCS5	38.75	58.92	320	Pass
	6945	199	be (80MHz)	MCS5	77.89	110.76	320	Pass
	7025	215	be (80MHz)	MCS5	77.95	114.03	320	Pass
	6985	207	be (160MHz)	MCS5	156.69	173.04	320	Pass

Table 7-5. Conducted Bandwidth Measurements Antenna 3a


FCC ID: BCGA3460 IC: 579C-A3460	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 32 of 259




Plot 7-41 26dB BW & 99% OBW Antenna 3a (20MHz BW 802.11be(SU) - Ch.1)




Plot 7-43 26dB BW & 99% OBW Antenna 3a (80MHz BW 802.11be(SU) - Ch.7)



Plot 7-42 26dB BW & 99% OBW Antenna 3a (40MHz BW 802.11be(SU) - Ch.91)




Plot 7-44 26dB BW & 99% OBW Antenna 3a (160MHz BW 802.11be(SU) - Ch.79)




Plot 7-45 26dB BW & 99% OBW Antenna 3a (20MHz BW 802.11be(SU) - Ch.105)




Plot 7-47 26dB BW & 99% OBW Antenna 3a (80MHz BW 802.11be(SU) - Ch.103)






Plot 7-46 26dB BW & 99% OBW Antenna 3a (40MHz BW 802.11be(SU) - Ch.99)



Plot 7-48 26dB BW & 99% OBW Antenna 3a (160MHz BW 802.11be(SU) - Ch.111)

FCC ID: BCGA3460 IC: 579C-A3460 Test Report S/N: 1C2509100080-24-R2.BCG	 Test Dates: 09/18/2025 - 12/4/2025	MEASUREMENT REPORT (CERTIFICATION) EUT Type: Tablet Device	Approved by: Technical Manager Page 33 of 259
---	--	--	---




FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 34 of 259

7.2.5 Antenna 1b 26dB & 99% Bandwidth Measurements – SP


	Frequency [MHz]	Channel	802.11 MODE	Data Rate	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	a	6Mbps	18.02	22.82	320	Pass
	6175	45	a	6Mbps	17.94	22.82	320	Pass
	6415	93	a	6Mbps	17.99	22.72	320	Pass
	5955	1	be (20MHz)	MCS0	19.08	23.06	320	Pass
	6175	45	be (20MHz)	MCS0	19.02	23.10	320	Pass
	6415	93	be (20MHz)	MCS0	19.06	23.05	320	Pass
	5965	3	be (40MHz)	MCS3	38.04	43.99	320	Pass
	6165	43	be (40MHz)	MCS0	38.05	44.43	320	Pass
	6405	91	be (40MHz)	MCS0	38.07	44.22	320	Pass
	5985	7	be (80MHz)	MCS0	77.56	82.39	320	Pass
	6145	39	be (80MHz)	MCS0	77.47	82.73	320	Pass
	6385	87	be (80MHz)	MCS0	77.48	82.80	320	Pass
	6025	15	be (160MHz)	MCS5	156.50	173.56	320	Pass
	6185	47	be (160MHz)	MCS5	156.79	176.67	320	Pass
Band 6	6345	79	be (160MHz)	MCS5	156.65	177.34	320	Pass
	6435	97	a	6Mbps	17.98	22.74	320	Pass
	6475	105	a	6Mbps	17.98	22.91	320	Pass
	6515	113	a	6Mbps	17.97	22.81	320	Pass
	6435	97	be (20MHz)	MCS0	19.09	23.11	320	Pass
	6475	105	be (20MHz)	MCS5	19.05	22.89	320	Pass
	6515	113	be (20MHz)	MCS0	19.07	22.96	320	Pass
	6445	99	be (40MHz)	MCS0	38.16	44.31	320	Pass
	6485	107	be (40MHz)	MCS3	38.00	44.52	320	Pass
	6525	115	be (40MHz)	MCS3	38.09	44.61	320	Pass
	6465	103	be (80MHz)	MCS3	77.54	82.51	320	Pass
	6505	111	be (160MHz)	MCS5	156.58	171.09	320	Pass
Band 7	6535	117	a	6Mbps	17.95	23.07	320	Pass
	6695	149	a	12Mbps	17.88	23.04	320	Pass
	6855	181	a	6Mbps	18.01	22.94	320	Pass
	6535	117	be (20MHz)	MCS0	19.07	22.87	320	Pass
	6695	149	be (20MHz)	MCS0	19.10	23.06	320	Pass
	6855	181	be (20MHz)	MCS0	19.08	22.79	320	Pass
	6565	123	be (40MHz)	MCS0	38.07	44.26	320	Pass
	6725	155	be (40MHz)	MCS0	38.06	44.24	320	Pass
	6845	179	be (40MHz)	MCS5	38.11	44.94	320	Pass
	6545	119	be (80MHz)	MCS3	77.65	82.66	320	Pass
	6705	151	be (80MHz)	MCS3	77.55	82.63	320	Pass
	6785	167	be (80MHz)	MCS3	77.65	82.66	320	Pass
	6665	143	be (160MHz)	MCS5	156.57	174.47	320	Pass

Table 7-6. Conducted Bandwidth Measurements Antenna 1b


FCC ID: BCGA3460 IC: 579C-A3460	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 35 of 259




Plot 7-57 26dB BW & 99% OBW Antenna 1b (20MHz BW 802.11be(SU) - Ch.45)



Plot 7-59 26dB BW & 99% OBW Antenna 1b (80MHz BW 802.11be(SU) - Ch.87)







Plot 7-58 26dB BW & 99% OBW Antenna 1b (40MHz BW 802.11be(SU) - Ch.43)




Plot 7-60 26dB BW & 99% OBW Antenna 1b (160MHz BW 802.11be(SU) - Ch.79)


FCC ID: BCGA3460 IC: 579C-A3460	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 36 of 259




FCC ID: BCGA3460 IC: 579C-A3460			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 37 of 259	



Plot 7-65 26dB BW & 99% OBW Antenna 1b (20MHz BW 802.11a - Ch.117)



Plot 7-67 26dB BW & 99% OBW Antenna 1b (80MHz BW 802.11be(SU) - Ch.167)



Plot 7-66 26dB BW & 99% OBW Antenna 1b (40MHz BW 802.11be(SU) - Ch.179)



Plot 7-68 26dB BW & 99% OBW Antenna 1b (160MHz BW 802.11be(SU) - Ch.143)

FCC ID: BCGA3460 IC: 579C-A3460			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device		Page 38 of 259

7.2.6 Antenna 1b 26dB & 99% Bandwidth Measurements – LPI


	Frequency [MHz]	Channel	802.11 MODE	Data Rate	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]	Maximum Bandwidth Limit [MHz]	Pass / Fail
Band 5	5955	1	a	36Mbps	18.27	30.61	320	Pass
	6175	45	a	36Mbps	18.29	29.07	320	Pass
	6415	93	a	36Mbps	18.37	28.61	320	Pass
	5955	1	be (20MHz)	MCS5	19.33	31.39	320	Pass
	6175	45	be (20MHz)	MCS5	19.29	31.81	320	Pass
	6415	93	be (20MHz)	MCS5	19.39	32.06	320	Pass
	5965	3	be (40MHz)	MCS5	38.71	62.35	320	Pass
	6165	43	be (40MHz)	MCS5	38.82	62.05	320	Pass
	6405	91	be (40MHz)	MCS5	38.67	63.10	320	Pass
	5985	7	be (80MHz)	MCS5	77.79	113.59	320	Pass
	6145	39	be (80MHz)	MCS5	77.85	108.07	320	Pass
	6385	87	be (80MHz)	MCS5	77.85	107.41	320	Pass
	6025	15	be (160MHz)	MCS5	156.56	170.54	320	Pass
	6185	47	be (160MHz)	MCS5	156.55	173.88	320	Pass
Band 6	6345	79	be (160MHz)	MCS5	156.69	179.25	320	Pass
	6435	97	a	36Mbps	18.21	30.66	320	Pass
	6475	105	a	36Mbps	18.31	30.18	320	Pass
	6515	113	a	36Mbps	18.33	29.10	320	Pass
	6435	97	be (20MHz)	MCS5	19.41	31.20	320	Pass
	6475	105	be (20MHz)	MCS5	19.36	30.08	320	Pass
	6515	113	be (20MHz)	MCS5	19.35	31.24	320	Pass
	6445	99	be (40MHz)	MCS5	38.70	64.28	320	Pass
	6485	107	be (40MHz)	MCS0	38.29	45.77	320	Pass
	6525	115	be (40MHz)	MCS0	38.34	45.02	320	Pass
	6465	103	be (80MHz)	MCS5	77.77	109.69	320	Pass
	6505	111	be (160MHz)	MCS5	156.77	174.30	320	Pass
	6535	117	a	36Mbps	18.23	29.81	320	Pass
	6695	149	a	36Mbps	18.21	30.01	320	Pass
Band 7	6875	185	a	36Mbps	18.32	30.77	320	Pass
	6535	117	be (20MHz)	MCS5	19.41	31.33	320	Pass
	6695	149	be (20MHz)	MCS5	19.38	31.52	320	Pass
	6875	185	be (20MHz)	MCS5	19.38	32.09	320	Pass
	6565	123	be (40MHz)	MCS5	38.73	61.77	320	Pass
	6725	155	be (40MHz)	MCS5	38.75	62.90	320	Pass
	6845	179	be (40MHz)	MCS5	38.60	62.46	320	Pass
	6545	119	be (80MHz)	MCS5	77.76	95.64	320	Pass
	6705	151	be (80MHz)	MCS5	77.72	91.31	320	Pass
	6865	183	be (80MHz)	MCS5	77.87	105.22	320	Pass
	6665	143	be (160MHz)	MCS5	156.65	178.81	320	Pass
	6825	175	be (160MHz)	MCS5	156.47	181.89	320	Pass
	6895	189	a	36Mbps	18.37	30.21	320	Pass
	6995	209	a	36Mbps	18.25	29.19	320	Pass
Band 8	7115	233	a	36Mbps	18.31	29.87	320	Pass
	6895	189	be (20MHz)	MCS5	19.33	31.54	320	Pass
	6995	209	be (20MHz)	MCS5	19.31	30.82	320	Pass
	7115	233	be (20MHz)	MCS5	19.31	30.79	320	Pass
	6885	187	be (40MHz)	MCS5	38.54	60.45	320	Pass
	7005	211	be (40MHz)	MCS5	38.71	61.79	320	Pass
	7085	227	be (40MHz)	MCS5	38.69	61.31	320	Pass
	6945	199	be (80MHz)	MCS5	77.87	109.50	320	Pass
	7025	215	be (80MHz)	MCS5	77.93	112.13	320	Pass
	6985	207	be (160MHz)	MCS5	156.61	180.21	320	Pass

Table 7-7. Conducted Bandwidth Measurements Antenna 1b


FCC ID: BCGA3460 IC: 579C-A3460	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 39 of 259




Plot 7-69 26dB BW & 99% OBW Antenna 1b (20MHz BW 802.11be(SU) - Ch.93)



Plot 7-71 26dB BW & 99% OBW Antenna 1b (80MHz BW 802.11be(SU) - Ch.7)




Plot 7-70 26dB BW & 99% OBW Antenna 1b (40MHz BW 802.11be(SU) - Ch.91)



Plot 7-72 26dB BW & 99% OBW Antenna 1b (160MHz BW 802.11be(SU) - Ch.79)

FCC ID: BCGA3460 IC: 579C-A3460			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device		Page 40 of 259




Plot 7-73 26dB BW & 99% OBW Antenna 1b (20MHz BW 802.11be(SU) - Ch.113)




Plot 7-75 26dB BW & 99% OBW Antenna 1b (80MHz BW 802.11be(SU) - Ch.103)



Plot 7-74 26dB BW & 99% OBW Antenna 1b (40MHz BW 802.11be(SU) - Ch.99)



Plot 7-76 26dB BW & 99% OBW Antenna 1b (160MHz BW 802.11be(SU) - Ch.111)




Plot 7-77 26dB BW & 99% OBW Antenna 1b (20MHz BW 802.11be(SU) - Ch.185)



Plot 7-79 26dB BW & 99% OBW Antenna 1b (80MHz BW 802.11be(SU) - Ch.183)




Plot 7-78 26dB BW & 99% OBW Antenna 1b (40MHz BW 802.11be(SU) - Ch.155)



Plot 7-80 26dB BW & 99% OBW Antenna 1b (160MHz BW 802.11be(SU) - Ch.175)

FCC ID: BCGA3460 IC: 579C-A3460	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device	Page 41 of 259




Plot 7-81 26dB BW & 99% OBW Antenna 1b (20MHz BW 802.11be(SU) - Ch.189)



Plot 7-83 26dB BW & 99% OBW Antenna 1b (80MHz BW 802.11be(SU) - Ch.215)



Plot 7-82 26dB BW & 99% OBW Antenna 1b (40MHz BW 802.11be(SU) - Ch.211)



Plot 7-84 26dB BW & 99% OBW Antenna 1b (160MHz BW 802.11be(SU) - Ch.207)

FCC ID: BCGA3460 IC: 579C-A3460			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-24-R2.BCG	Test Dates: 09/18/2025 - 12/4/2025	EUT Type: Tablet Device		Page 42 of 259