



7.8.18 SDM Primary Radiated Band Edge Measurements (160MHz BW)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6185MHz
Channel	47



Plot 7-415 SDM Primary Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6825MHz
Channel	175




Plot 7-416 SDM Primary Radiated Upper Band Edge (Peak & Average – UNII Band 7)

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 177 of 197

V 11.0 05/2025

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6985MHz
Channel	207




Plot 7-417 SDM Primary Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 178 of 197

V 11.0 05/2025


7.8.19 CDD/SDM Diversity Radiated Band Edge Measurements (20MHz BW)

Mode	802.11a
Data Rate	54Mbps
Distance of Measurement	3 Meters
Operating Frequency	6115MHz
Channel	33



Plot 7-418 CDD Diversity Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11a
Data Rate	54Mbps
Distance of Measurement	3 Meters
Operating Frequency	7095MHz
Channel	229




Plot 7-419 CDD Diversity Radiated Upper Band Edge (Peak & Average – UNII Band 8)


FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 179 of 197

V 11.0 05/2025

Mode	802.11a
Data Rate	54Mbps
Distance of Measurement	3 Meters
Operating Frequency	7115MHz
Channel	233




Plot 7-420 CDD Diversity Radiated Integrated Band Edge (Peak – UNII Band 8)



Plot 7-421 CDD Diversity Radiated Integrated Band Edge (Average – UNII Band 8)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6115MHz
Channel	33




Plot 7-422 SDM Diversity Radiated Lower Band Edge (Peak & Average – UNII Band 5)

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 180 of 197

V 11.0 05/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7095MHz
Channel	229




Plot 7-423 SDM Diversity Radiated Upper Band Edge (Peak & Average – UNII Band 8)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7115MHz
Channel	233



Plot 7-424 SDM Diversity Radiated Integrated Band Edge (Peak – UNII Band 8)




Plot 7-425 SDM Diversity Radiated Integrated Band Edge (Average – UNII Band 8)

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 181 of 197


7.8.21 SDM Diversity Radiated Band Edge Measurements (80MHz BW)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6145MHz
Channel	39



Plot 7-428 SDM Diversity Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7025MHz
Channel	215




Plot 7-429 SDM Diversity Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 183 of 197

V 11.0 05/2025


7.8.22 SDM Diversity Radiated Band Edge Measurements (160MHz BW)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6185MHz
Channel	47



Plot 7-430 SDM Diversity Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6825MHz
Channel	175




Plot 7-431 SDM Diversity Radiated Upper Band Edge (Peak & Average – UNII Band 7)

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 184 of 197

V 11.0 05/2025

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6985MHz
Channel	207



Plot 7-432 SDM Diversity Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 185 of 197

V 11.0 05/2025

7.9 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 7-70 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-70. Radiated Limits

Test Procedures Used

ANSI C63.10:2020 + COR. 1:2023 + C63.10A:2024 + ERRATA TO C63.10A:2024

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = quasi-peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 186 of 197

V 11.0 05/2025

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-8. Radiated Test Setup < 30MHz




Figure 7-9. Radiated Test Setup < 1GHz

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 187 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-70.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector on emissions that were within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
10. All antenna configurations were investigated and only the worst case is reported.
11. The unit was tested with all possible modes and only the highest emission is reported.

Sample Calculations


Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]} - \text{Preamp Gain}_{[dB]}$
- $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 188 of 197

V 11.0 05/2025

7.9.1 SDM Primary Radiated Spurious Emissions Measurements (Below 1GHz)



Plot 7-433. Radiated Spurious Emissions below 1GHz SDM Primary, 802.11be, Ch.61 with AC/DC Adapter


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
30.21	Max-Peak	V	100	-	-55.06	-19.23	32.71	40.00	-7.29
55.11	Max-Peak	V	100	-	-65.87	-15.69	25.45	40.00	-14.55
115.35	Max-Peak	H	300	-	-59.95	-18.92	28.13	43.50	-15.37
195.81	Max-Peak	H	100	-	-53.95	-17.62	35.43	43.50	-8.07
244.35	Max-Peak	H	100	-	-61.52	-16.40	29.08	46.00	-16.92
917.29	Max-Peak	H	300	-	-73.17	-4.10	29.73	46.00	-16.27

Table 7-71. Radiated Spurious Emissions Measurement below 1GHz SDM Primary, 802.11be, Ch.61 with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 189 of 197

V 11.0 05/2025

7.9.2 SDM Diversity Radiated Spurious Emissions Measurements (Below 1GHz)



Plot 7-434. Radiated Spurious Emissions below 1GHz SDM Diversity, 802.11be, Ch.61 with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
30.03	Max-Peak	V	100	-	-54.14	-19.01	33.85	40.00	-6.15
55.47	Max-Peak	V	200	-	-64.41	-15.66	26.93	40.00	-13.07
116.13	Max-Peak	H	200	-	-60.36	-19.19	27.45	43.50	-16.05
196.89	Max-Peak	H	100	-	-54.06	-17.49	35.45	43.50	-8.05
281.00	Max-Peak	H	100	-	-63.41	-15.78	27.82	46.00	-18.18
994.03	Max-Peak	H	100	-	-73.67	-3.58	29.75	54.00	-24.25

Table 7-72. Radiated Spurious Emissions Measurement below 1GHz SDM Diversity, 802.11be, Ch.61 with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 190 of 197

V 11.0 05/2025

7.10 AC Line-Conducted Emissions Measurement

§15.407; RSS-Gen[8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-73. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10:2020 + COR. 1:2023 + C63.10A:2024 + ERRATA TO C63.10A:2024, Section 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 191 of 197

V 11.0 05/2025

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-10. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated, and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
2. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
3. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
4. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
5. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Correction Factor (dB)}$
6. $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
7. Traces shown in plots are made using quasi-peak and average detectors.
8. Deviations to the Specifications: None.
9. The unit was tested with all possible modes and only the highest emission is reported.

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 192 of 197

V 11.0 05/2025




Plot 7-435. AC Line Conducted Plot with 802.11be SDM Primary – Ch.61 (L1), with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.17	FINAL	---	34.08	54.95	-20.87	L1	GND
0.17	FINAL	49.10	---	64.95	-15.85	L1	GND
0.25	FINAL	---	28.18	51.72	-23.54	L1	GND
0.25	FINAL	44.97	---	61.72	-16.75	L1	GND
0.52	FINAL	---	17.84	46.00	-28.16	L1	GND
0.52	FINAL	38.05	---	56.00	-17.95	L1	GND
0.75	FINAL	34.95	---	56.00	-21.05	L1	GND
0.75	FINAL	---	15.43	46.00	-30.57	L1	GND
5.04	FINAL	33.69	---	60.00	-26.31	L1	GND
5.04	FINAL	---	20.26	50.00	-29.74	L1	GND
16.11	FINAL	---	10.60	50.00	-39.40	L1	GND
16.11	FINAL	14.70	---	60.00	-45.30	L1	GND

Table 7-74. AC Line Conducted Data with 802.11be SDM Primary – Ch. 61 (L1) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 193 of 197

V 11.0 05/2025




Plot 7-436. AC Line Conducted Plot with 802.11be SDM Primary – Ch. 61 (N), with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	37.30	54.95	-17.65	N	GND
0.17	FINAL	52.76	---	64.95	-12.19	N	GND
0.26	FINAL	---	30.65	51.57	-20.92	N	GND
0.26	FINAL	47.51	---	61.57	-14.06	N	GND
0.51	FINAL	---	20.65	46.00	-25.35	N	GND
0.52	FINAL	38.94	---	56.00	-17.06	N	GND
0.75	FINAL	34.94	---	56.00	-21.06	N	GND
0.75	FINAL	---	16.10	46.00	-29.90	N	GND
5.04	FINAL	36.29	---	60.00	-23.71	N	GND
5.04	FINAL	---	23.04	50.00	-26.96	N	GND
16.12	FINAL	---	9.95	50.00	-40.05	N	GND
16.12	FINAL	15.59	---	60.00	-44.41	N	GND

Table 7-75. AC Line Conducted Data with 802.11be SDM Primary – Ch. 61 (N), with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 194 of 197

V 11.0 05/2025




Plot 7-437. AC Line Conducted Plot with 802.11be SDM Diversity – Ch.61 (L1), with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	34.55	54.95	-20.40	L1	GND
0.17	FINAL	49.34	---	64.95	-15.61	L1	GND
0.26	FINAL	---	29.10	51.57	-22.47	L1	GND
0.26	FINAL	45.21	---	61.57	-16.36	L1	GND
0.52	FINAL	38.21	---	56.00	-17.79	L1	GND
0.52	FINAL	---	18.79	46.00	-27.21	L1	GND
0.92	FINAL	33.46	---	56.00	-22.54	L1	GND
0.92	FINAL	---	17.76	46.00	-28.24	L1	GND
5.05	FINAL	---	20.16	50.00	-29.84	L1	GND
5.05	FINAL	34.08	---	60.00	-25.92	L1	GND
16.06	FINAL	---	11.05	50.00	-38.95	L1	GND
16.06	FINAL	14.80	---	60.00	-45.20	L1	GND

Table 7-76. AC Line Conducted Data with 802.11be SDM Diversity – Ch. 61 (L1) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 195 of 197

V 11.0 05/2025



Plot 7-438. AC Line Conducted Plot with 802.11be SDM Diversity – Ch. 61 (N), with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	36.13	54.95	-18.82	N	GND
0.17	FINAL	51.11	---	64.95	-13.84	N	GND
0.26	FINAL	---	29.29	51.50	-22.21	N	GND
0.26	FINAL	46.37	---	61.50	-15.13	N	GND
0.52	FINAL	---	20.60	46.00	-25.40	N	GND
0.52	FINAL	38.65	---	56.00	-17.35	N	GND
0.91	FINAL	33.74	---	56.00	-22.26	N	GND
0.91	FINAL	---	18.45	46.00	-27.55	N	GND
5.05	FINAL	36.15	---	60.00	-23.85	N	GND
5.05	FINAL	---	22.77	50.00	-27.23	N	GND
16.08	FINAL	---	10.16	50.00	-39.84	N	GND
16.08	FINAL	15.68	---	60.00	-44.32	N	GND

Table 7-77. AC Line Conducted Data with 802.11be SDM Diversity – Ch. 61 (N), with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 196 of 197

V 11.0 05/2025

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device FCC ID: BCGA3460** and **IC: 579C-A3460** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-248 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-26-R3.BCG	Test Dates: 09/18/2025 - 12/15/2025	EUT Type: Tablet Device	Page 197 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.