




MRU




Plot 7-1206. CDD Diversity (Peak & Average, RU996+484, Index 94 (L), Ch.50, MCS11)




Plot 7-1209. CDD Diversity (Peak & Average, RU996+484, Index 95 (H), Ch.50, MCS11)




Plot 7-1207. CDD Diversity (Peak & Average, RU996+484, Index 94 (H), Ch.50, MCS11)



Plot 7-1210. CDD Diversity (Peak & Average, RU996+484, Index 94 (L), Ch.50, MCS11)



Plot 7-1208. CDD Diversity (Peak & Average, RU996+484, Index 95 (L), Ch.50, MCS11)




Plot 7-1211. CDD Diversity (Peak & Average, RU996+484, Index 94 (H), Ch.50, MCS11)


FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 366 of 398

V 10.6 10/27/2023


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-1212. CDD Diversity (Peak & Average, RU996+484, Index 95 (L), Ch.50, MCS11)




Plot 7-1215. CDD Diversity (Peak & Average, RU996+484, Index 94 (H), Ch.114, MCS11)




Plot 7-1213. CDD Diversity (Peak & Average, RU996+484, Index 95 (H), Ch.50, MCS11)



Plot 7-1216. CDD Diversity (Peak & Average, RU996+484, Index 95 (L), Ch.114, MCS11)




Plot 7-1214. CDD Diversity (Peak & Average, RU996+484, Index 94 (L), Ch.114, MCS11)




Plot 7-1217. CDD Diversity (Peak & Average, RU996+484, Index 95 (H), Ch.114, MCS11)


FCC ID: BCGA3460 IC: 579C-A3460	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 367 of 398




Plot 7-1218. CDD Diversity (Peak, RU996+484, Index 94 (L), Ch.114, MCS11)




Plot 7-1221. CDD Diversity (Peak, RU996+484, Index 95 (L), Ch.114, MCS11)




Plot 7-1219. CDD Diversity (Peak, RU996+484, Index 94 (H), Ch.114, MCS11)



Plot 7-1222. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (L), Ch.50, MCS11)



Plot 7-1220. CDD Diversity (Peak, RU996+484, Index 95 (H), Ch.114, MCS11)




Plot 7-1223. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (H), Ch.50, MCS11)


FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 368 of 398

V 10.6 10/27/2023


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-1224. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (L), Ch.50, MCS11)




Plot 7-1227. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (H), Ch.50, MCS11)




Plot 7-1225. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (H), Ch.50, MCS11)



Plot 7-1228. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (L), Ch.50, MCS11)




Plot 7-1226. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (L), Ch.50, MCS11)




Plot 7-1229. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (H), Ch.50, MCS11)


FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 369 of 398




Plot 7-1230. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (L), Ch.50, MCS11)




Plot 7-1233. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (H), Ch.50, MCS11)




Plot 7-1231. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (H), Ch.50, MCS11)



Plot 7-1234. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (H), Ch.50, MCS11)




Plot 7-1232. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (L), Ch.50, MCS11)




Plot 7-1235. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (L), Ch.50, MCS11)


FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 370 of 398




Plot 7-1236. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (H), Ch.50, MCS11)




Plot 7-1239. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (H), Ch.114, MCS11)




Plot 7-1237. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (L), Ch.50, MCS11)



Plot 7-1240. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (L), Ch.114, MCS11)




Plot 7-1238. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (L), Ch.114, MCS11)




Plot 7-1241. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (H), Ch.114, MCS11)


FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 371 of 398




Plot 7-1242. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (H), Ch.114, MCS11)




Plot 7-1245. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (H), Ch.114, MCS11)




Plot 7-1243. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (L), Ch.114, MCS11)



Plot 7-1246. CDD Diversity (Peak, RU996+484+242, Index 96 (L), Ch.114, MCS11)




Plot 7-1244. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (L), Ch.114, MCS11)




Plot 7-1247. CDD Diversity (Peak, RU996+484+242, Index 96 (H), Ch.114, MCS11)


FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 372 of 398




Plot 7-1248. CDD Diversity (Peak, RU996+484+242, Index 97 (L), Ch.114, MCS11)




Plot 7-1251. CDD Diversity (Peak, RU996+484+242, Index 98 (H), Ch.114, MCS11)




Plot 7-1249. CDD Diversity (Peak, RU996+484+242, Index 97 (H), Ch.114, MCS11)



Plot 7-1252. CDD Diversity (Peak, RU996+484+242, Index 99 (L), Ch.114, MCS11)




Plot 7-1250. CDD Diversity (Peak, RU996+484+242, Index 98 (L), Ch.114, MCS11)




Plot 7-1253. CDD Diversity (Peak, RU996+484+242, Index 99 (H), Ch.114, MCS11)

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 373 of 398


RU996X2




Plot 7-1254. CDD Diversity (Peak & Average, RU996X2, Index 68, Ch.50, MCS11)



Plot 7-1257. CDD Diversity (Peak, RU996X2, Index 68, Ch.114, MCS11)



Plot 7-1255. CDD Diversity (Peak & Average, RU996X2, Index 68, Ch.50, MCS11)



Plot 7-1256. CDD Diversity (Peak & Average, RU996X2, Index 68, Ch.114, MCS11)

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 374 of 398

V 10.6 10/27/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.7 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-243 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-243. Radiated Limits

Test Procedures Used

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 375 of 398

V 10.6 10/27/2023

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-6. Radiated Test Setup < 30MHz




Figure 7-7. Radiated Test Setup < 1GHz

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 376 of 398

V 10.6 10/27/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-243.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector for emissions within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. All antenna configurations and data rates were investigated and only the worst case are reported.
10. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger

Sample Calculations


Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]} - \text{Preamplifier Gain }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device		Page 377 of 398

V 10.6 10/27/2023

7.7.1 CDD Primary Radiated Spurious Emissions (Below 1GHz)




Plot 7-1258. RSE below 1GHz CDD Primary (RU26 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
30.33	Max-Peak	V	200	-	-55.05	-19.12	32.83	40.00	-7.17
55.17	Max-Peak	V	100	-	-66.31	-15.60	25.09	40.00	-14.91
112.59	Max-Peak	H	300	-	-61.45	-18.66	26.89	43.50	-16.61
196.41	Max-Peak	V	100	-	-58.81	-17.55	30.64	43.50	-12.86
378.44	Max-Peak	H	100	-	-66.81	-13.32	26.88	46.00	-19.12
855.55	Max-Peak	H	300	-	-72.59	-4.58	29.84	46.00	-16.16

Table 7-244. RSE below 1GHz CDD Primary (RU26 – Ch.40), with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 378 of 398




Plot 7-1259. RSE below 1GHz CDD Primary (RU78 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
30.57	Max-Peak	V	100	-	-55.00	-19.20	32.80	40.00	-7.20
58.05	Max-Peak	V	100	-	-65.80	-16.22	24.98	40.00	-15.02
108.33	Max-Peak	H	300	-	-62.51	-18.11	26.38	43.50	-17.12
195.27	Max-Peak	H	200	-	-58.53	-17.75	30.72	43.50	-12.78
378.50	Max-Peak	H	100	-	-65.84	-13.32	27.84	46.00	-18.16
899.95	Max-Peak	V	100	-	-73.09	-4.13	29.79	46.00	-16.21

Table 7-245. RSE below 1GHz CDD Primary (RU78 – Ch.40), with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 379 of 398




Plot 7-1260. RSE below 1GHz CDD Primary (RU242 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
30.15	Max-Peak	V	100	-	-54.87	-19.06	33.07	40.00	-6.93
55.53	Max-Peak	V	300	-	-66.62	-15.67	24.71	40.00	-15.29
109.41	Max-Peak	H	300	-	-62.12	-18.22	26.66	43.50	-16.84
195.27	Max-Peak	V	100	-	-57.83	-17.75	31.43	43.50	-12.07
378.14	Max-Peak	H	100	-	-67.01	-13.30	26.69	46.00	-19.31
984.61	Max-Peak	H	200	-	-73.25	-3.63	30.12	54.00	-23.88

Table 7-246. RSE below 1GHz CDD Primary (RU242– Ch.40), with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 380 of 398

7.7.2 CDD Diversity Radiated Spurious Emissions (Below 1GHz)




Plot 7-1261. RSE below 1GHz CDD Diversity (RU26 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
30.15	Max-Peak	V	100	-	-55.90	-19.06	32.05	40.00	-7.95
57.57	Max-Peak	V	100	-	-65.51	-16.10	25.38	40.00	-14.62
140.55	Max-Peak	H	200	-	-59.19	-21.49	26.33	43.50	-17.17
195.39	Max-Peak	H	200	-	-54.21	-17.73	35.06	43.50	-8.44
378.86	Max-Peak	H	100	-	-68.79	-13.34	24.87	46.00	-21.13
954.73	Max-Peak	H	100	-	-72.96	-3.96	30.08	46.00	-15.92

Table 7-247. RSE below 1GHz CDD Diversity (RU26 – Ch.40), with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 381 of 398




Plot 7-1262. RSE below 1GHz CDD Diversity (RU78 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
30.39	Max-Peak	V	100	-	-55.87	-19.14	31.99	40.00	-8.01
55.89	Max-Peak	V	100	-	-65.24	-15.74	26.01	40.00	-13.99
139.65	Max-Peak	H	200	-	-59.36	-21.42	26.22	43.50	-17.28
192.33	Max-Peak	H	100	-	-57.88	-18.13	30.99	43.50	-12.51
354.08	Max-Peak	H	100	-	-67.33	-13.94	25.72	46.00	-20.28
907.87	Max-Peak	H	200	-	-73.18	-3.95	29.87	46.00	-16.13

Table 7-248. RSE below 1GHz CDD Diversity (RU78– Ch.40), with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 382 of 398



Plot 7-1263. RSE below 1GHz CDD Diversity (RU242 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
30.51	Max-Peak	V	100	-	-55.20	-19.18	32.62	40.00	-7.38
55.53	Max-Peak	V	200	-	-65.35	-15.67	25.98	40.00	-14.02
139.77	Max-Peak	H	200	-	-58.66	-21.42	26.92	43.50	-16.58
196.53	Max-Peak	H	100	-	-55.90	-17.54	33.57	43.50	-9.93
354.62	Max-Peak	H	100	-	-68.16	-14.00	24.84	46.00	-21.16
919.51	Max-Peak	V	100	-	-72.27	-4.14	30.59	46.00	-15.41

Table 7-249. RSE below 1GHz CDD Diversity (RU242– Ch.40), with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 383 of 398

7.8 AC Line Conducted Emissions Measurement

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. All data rates and modes were investigated for AC Line conducted spurious emissions.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-250. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024, Subclause 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 384 of 398

V 10.6 10/27/2023

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-8. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
2. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
3. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
4. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
5. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Correction Factor (dB)}$
6. $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
7. Traces shown in plots are made using quasi-peak and average detectors.
8. Deviations to the Specifications: None.

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 385 of 398

7.8.1 CDD Primary AC Line Conducted Emissions Measurement




Plot 7-1264. AC Line Conducted Plot with 11be CDD Primary – RU26 – Ch.40 (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	33.29	55.17	-21.88	L1	GND
0.17	FINAL	49.96	---	65.17	-15.21	L1	GND
0.25	FINAL	---	28.82	51.64	-22.82	L1	GND
0.25	FINAL	45.34	---	61.64	-16.30	L1	GND
0.52	FINAL	38.28	---	56.00	-17.72	L1	GND
0.52	FINAL	---	18.19	46.00	-27.81	L1	GND
0.92	FINAL	33.64	---	56.00	-22.36	L1	GND
0.92	FINAL	---	17.59	46.00	-28.41	L1	GND
5.05	FINAL	---	20.45	50.00	-29.55	L1	GND
5.05	FINAL	33.98	---	60.00	-26.02	L1	GND
16.23	FINAL	---	10.76	50.00	-39.24	L1	GND
16.23	FINAL	14.52	---	60.00	-45.48	L1	GND

Table 7-251. AC Line Conducted with 11be CDD Primary – RU26 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 386 of 398

V 10.6 10/27/2023




Plot 7-1265. AC Line Conducted Plot with 11be CDD Primary – RU26 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.17	FINAL	---	36.01	54.95	-18.94	N	GND
0.17	FINAL	51.37	---	64.95	-13.58	N	GND
0.26	FINAL	---	29.59	51.57	-21.98	N	GND
0.26	FINAL	46.41	---	61.57	-15.16	N	GND
0.52	FINAL	38.35	---	56.00	-17.65	N	GND
0.52	FINAL	---	19.02	46.00	-26.98	N	GND
0.91	FINAL	33.93	---	56.00	-22.07	N	GND
0.91	FINAL	---	18.30	46.00	-27.70	N	GND
5.04	FINAL	---	22.98	50.00	-27.02	N	GND
5.04	FINAL	36.11	---	60.00	-23.89	N	GND
16.23	FINAL	---	9.74	50.00	-40.26	N	GND
16.23	FINAL	15.41	---	60.00	-44.59	N	GND

Table 7-252. AC Line Conducted with 11be CDD Primary – RU26 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 387 of 398

V 10.6 10/27/2023




Plot 7-1266. AC Line Conducted Plot with 11be CDD Primary – RU78 – Ch.40 (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	34.68	54.95	-20.27	L1	GND
0.17	FINAL	49.89	---	64.95	-15.06	L1	GND
0.26	FINAL	---	27.45	51.50	-24.05	L1	GND
0.26	FINAL	45.08	---	61.50	-16.42	L1	GND
0.52	FINAL	---	18.25	46.00	-27.75	L1	GND
0.52	FINAL	38.25	---	56.00	-17.75	L1	GND
0.92	FINAL	33.52	---	56.00	-22.48	L1	GND
0.92	FINAL	---	17.63	46.00	-28.37	L1	GND
5.04	FINAL	33.87	---	60.00	-26.13	L1	GND
5.04	FINAL	---	20.29	50.00	-29.71	L1	GND
16.22	FINAL	---	11.01	50.00	-38.99	L1	GND
16.22	FINAL	14.63	---	60.00	-45.37	L1	GND

Table 7-253. AC Line Conducted with 11be CDD Primary – RU78 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 388 of 398




Plot 7-1267. AC Line Conducted Plot with 11be CDD Primary – RU78 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.17	FINAL	---	36.11	54.95	-18.84	N	GND
0.17	FINAL	51.22	---	64.95	-13.73	N	GND
0.26	FINAL	---	28.62	51.50	-22.88	N	GND
0.26	FINAL	45.98	---	61.50	-15.52	N	GND
0.51	FINAL	38.12	---	56.00	-27.12	N	GND
0.51	FINAL	---	19.96	46.00	-26.04	N	GND
0.91	FINAL	34.01	---	56.00	-21.99	N	GND
0.91	FINAL	---	18.59	46.00	-27.41	N	GND
5.05	FINAL	---	22.88	50.00	-27.12	N	GND
5.06	FINAL	36.26	---	60.00	-23.74	N	GND
16.22	FINAL	---	9.88	50.00	-40.12	N	GND
16.22	FINAL	15.47	---	60.00	-44.53	N	GND

Table 7-254. AC Line Conducted with 11be CDD Primary – RU78 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 389 of 398

V 10.6 10/27/2023




Plot 7-1268. AC Line Conducted Plot with 11be CDD Primary – RU242 – Ch.40 (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.17	FINAL	---	35.42	54.95	-19.53	L1	GND
0.17	FINAL	50.74	---	64.95	-14.21	L1	GND
0.26	FINAL	---	27.91	51.50	-23.59	L1	GND
0.26	FINAL	45.73	---	61.50	-15.77	L1	GND
0.51	FINAL	---	19.57	46.00	-26.43	L1	GND
0.52	FINAL	38.61	---	56.00	-17.39	L1	GND
0.91	FINAL	33.60	---	56.00	-22.40	L1	GND
0.91	FINAL	---	17.59	46.00	-28.41	L1	GND
5.04	FINAL	---	20.43	50.00	-29.57	L1	GND
5.05	FINAL	34.20	---	60.00	-25.80	L1	GND
16.23	FINAL	---	11.01	50.00	-38.99	L1	GND
16.23	FINAL	14.59	---	60.00	-45.41	L1	GND

Table 7-255. AC Line Conducted with 11be CDD Primary – RU242 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 390 of 398




Plot 7-1269. AC Line Conducted Plot with 11be CDD Primary – RU242 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	37.00	54.95	-17.95	N	GND
0.17	FINAL	52.35	---	64.95	-12.60	N	GND
0.26	FINAL	---	29.27	51.50	-22.23	N	GND
0.26	FINAL	46.87	---	61.50	-14.63	N	GND
0.52	FINAL	---	19.63	46.00	-26.37	N	GND
0.52	FINAL	38.74	---	56.00	-17.26	N	GND
0.91	FINAL	34.04	---	56.00	-21.96	N	GND
0.91	FINAL	---	18.53	46.00	-27.47	N	GND
5.03	FINAL	36.02	---	60.00	-23.98	N	GND
5.03	FINAL	---	22.80	50.00	-27.20	N	GND
16.23	FINAL	---	9.73	50.00	-40.27	N	GND
16.23	FINAL	15.28	---	60.00	-44.72	N	GND

Table 7-256. AC Line Conducted with 11be CDD Primary – RU242 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 391 of 398

7.8.2 CDD Diversity AC Line Conducted Emissions Measurement



Plot 7-1270. AC Line Conducted Plot with 11be CDD Diversity – RU26 – Ch.40 (L1) with AC/DC Adapter


Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.17	FINAL	---	34.28	54.95	-20.67	L1	GND
0.17	FINAL	49.41	---	64.95	-15.54	L1	GND
0.26	FINAL	---	27.29	51.50	-24.21	L1	GND
0.26	FINAL	44.96	---	61.50	-16.54	L1	GND
0.52	FINAL	---	18.32	46.00	-27.68	L1	GND
0.52	FINAL	38.27	---	56.00	-17.73	L1	GND
0.92	FINAL	33.58	---	56.00	-22.42	L1	GND
0.92	FINAL	---	17.57	46.00	-28.43	L1	GND
5.05	FINAL	33.89	---	60.00	-26.11	L1	GND
5.05	FINAL	---	20.29	50.00	-29.71	L1	GND
16.24	FINAL	---	10.79	50.00	-39.21	L1	GND
16.24	FINAL	14.58	---	60.00	-45.42	L1	GND

Table 7-257. AC Line Conducted with 11be CDD Diversity – RU26 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 392 of 398

V 10.6 10/27/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-1271. AC Line Conducted Plot with 11be CDD Diversity – RU26 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.17	FINAL	---	35.67	54.95	-19.28	N	GND
0.17	FINAL	50.73	---	64.95	-14.22	N	GND
0.26	FINAL	---	28.38	51.50	-23.12	N	GND
0.26	FINAL	45.74	---	61.50	-15.76	N	GND
0.52	FINAL	---	19.18	46.00	-26.82	N	GND
0.52	FINAL	38.28	---	56.00	-17.72	N	GND
0.91	FINAL	33.93	---	56.00	-22.07	N	GND
0.91	FINAL	---	18.50	46.00	-27.50	N	GND
5.04	FINAL	36.02	---	60.00	-23.98	N	GND
5.04	FINAL	---	22.87	50.00	-27.13	N	GND
16.24	FINAL	---	9.95	50.00	-40.05	N	GND
16.24	FINAL	15.53	---	60.00	-44.47	N	GND

Table 7-258. AC Line Conducted with 11be CDD Diversity – RU26 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 393 of 398

V 10.6 10/27/2023




Plot 7-1272. AC Line Conducted Plot with 11be CDD Diversity – RU78 – Ch.40 (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	34.25	54.95	-20.70	L1	GND
0.17	FINAL	49.35	---	64.95	-15.60	L1	GND
0.26	FINAL	---	27.49	51.50	-24.01	L1	GND
0.26	FINAL	44.98	---	61.50	-16.52	L1	GND
0.52	FINAL	---	18.94	46.00	-25.98	L1	GND
0.52	FINAL	38.23	---	56.00	-17.77	L1	GND
0.92	FINAL	33.61	---	56.00	-22.39	L1	GND
0.92	FINAL	---	17.81	46.00	-28.19	L1	GND
5.05	FINAL	34.02	---	60.00	-25.98	L1	GND
5.05	FINAL	---	20.26	50.00	-29.74	L1	GND
16.24	FINAL	---	11.08	50.00	-38.92	L1	GND
16.24	FINAL	14.65	---	60.00	-45.35	L1	GND

Table 7-259. AC Line Conducted with 11be CDD Diversity – RU78 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 394 of 398

V 10.6 10/27/2023




Plot 7-1273. AC Line Conducted Plot with 11be CDD Diversity – RU78 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.17	FINAL	---	35.08	54.95	-19.87	N	GND
0.17	FINAL	50.24	---	64.95	-14.71	N	GND
0.26	FINAL	---	28.07	51.50	-23.43	N	GND
0.26	FINAL	45.51	---	61.50	-15.99	N	GND
0.43	FINAL	---	21.13	47.27	-23.76	N	GND
0.43	FINAL	39.12	---	57.27	-18.15	N	GND
0.92	FINAL	34.00	---	56.00	-22.00	N	GND
0.92	FINAL	---	18.44	46.00	-27.56	N	GND
5.05	FINAL	36.24	---	60.00	-23.76	N	GND
5.05	FINAL	---	22.97	50.00	-27.03	N	GND
16.24	FINAL	---	10.01	50.00	-39.99	N	GND
16.24	FINAL	15.63	---	60.00	-44.37	N	GND

Table 7-260. AC Line Conducted with 11be CDD Diversity – RU78 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 395 of 398

V 10.6 10/27/2023




Plot 7-1274. AC Line Conducted Plot with 11be CDD Diversity – RU242 – Ch.40 (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	34.80	54.95	-20.15	L1	GND
0.17	FINAL	49.50	---	64.95	-15.45	L1	GND
0.26	FINAL	---	27.92	51.50	-23.58	L1	GND
0.26	FINAL	44.97	---	61.50	-16.53	L1	GND
0.52	FINAL	38.31	---	56.00	-17.69	L1	GND
0.52	FINAL	---	19.09	46.00	-26.91	L1	GND
0.92	FINAL	33.80	---	56.00	-22.20	L1	GND
0.92	FINAL	---	18.03	46.00	-27.97	L1	GND
5.05	FINAL	---	20.23	50.00	-29.77	L1	GND
5.05	FINAL	33.98	---	60.00	-26.02	L1	GND
16.23	FINAL	---	11.17	50.00	-38.83	L1	GND
16.23	FINAL	14.72	---	60.00	-45.28	L1	GND

Table 7-261. AC Line Conducted with 11be CDD Diversity – RU242 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 396 of 398

V 10.6 10/27/2023



Plot 7-1275. AC Line Conducted Plot with 11be CDD Diversity – RU242 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	35.69	54.95	-19.26	N	GND
0.17	FINAL	50.65	---	64.95	-14.30	N	GND
0.26	FINAL	---	28.61	51.50	-22.89	N	GND
0.26	FINAL	45.71	---	61.50	-15.79	N	GND
0.52	FINAL	---	19.63	46.00	-26.37	N	GND
0.52	FINAL	38.32	---	56.00	-17.68	N	GND
0.91	FINAL	34.02	---	56.00	-21.98	N	GND
0.91	FINAL	---	18.62	46.00	-27.38	N	GND
5.04	FINAL	36.22	---	60.00	-23.78	N	GND
5.05	FINAL	---	22.90	50.00	-27.10	N	GND
16.22	FINAL	---	9.97	50.00	-40.03	N	GND
16.22	FINAL	15.56	---	60.00	-44.44	N	GND

Table 7-262. AC Line Conducted with 11be CDD Diversity – RU242 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 397 of 398

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device FCC ID: BCGA3460** and **IC: 579C-A3460** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA3460 IC: 579C-A3460		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100080-23-R3.BCG	Test Dates: 09/15/2025 - 1/5/2025	EUT Type: Tablet Device	Page 398 of 398

V 10.6 10/27/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.