


Channel Power Plots


Peak



05:33:02 01.10.2025

Plot 7-289. Channel Power – UNII 5 – 20MHz

Peak



05:35:48 01.10.2025


Plot 7-290. Channel Power – UNII 5 – 160MHz - Low

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG				Page 103 of 197
Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device			

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



05:37:08 01.10.2025

Plot 7-291. Channel Power – UNII 5 – 160MHz – Mid

Peak



05:38:26 01.10.2025


Plot 7-292. Channel Power – UNII 5 – 160MHz - High

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 104 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



05:41:26 01.10.2025

Plot 7-293. Channel Power – UNII 6 – 20MHz

Peak



05:44:14 01.10.2025


Plot 7-294. Channel Power – UNII 6 – 160MHz - Low

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 105 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



05:45:50 01.10.2025

Plot 7-295. Channel Power – UNII 6 – 160MHz – Mid

Peak



05:46:59 01.10.2025


Plot 7-296. Channel Power – UNII 6 – 160MHz - High

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 106 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



05:48:09 01.10.2025

Plot 7-297. Channel Power – UNII 7 – 20MHz

Peak



05:54:01 01.10.2025


Plot 7-298. Channel Power – UNII 7 – 160MHz - Low

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 107 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



05:55:26 01.10.2025

Plot 7-299. Channel Power – UNII 7 – 160MHz – Mid

Peak



05:57:49 01.10.2025


Plot 7-300. Channel Power – UNII 7 – 160MHz - High

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 108 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



05:58:51 01.10.2025

Plot 7-301. Channel Power – UNII 8 – 20MHz

Peak



06:00:02 01.10.2025


Plot 7-302. Channel Power – UNII 8 – 160MHz - Low

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG		Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 109 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



06:01:10 01.10.2025

Plot 7-303. Channel Power – UNII 8 – 160MHz – Mid

Peak



06:02:48 01.10.2025


Plot 7-304. Channel Power – UNII 8 – 160MHz - High

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 110 of 197

V 11.0 05/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Contention-Based Protocol Timing Plots



06:17:54 01.10.2025

Plot 7-305. Contention Based Protocol Timing Plot – UNII 5 – 20MHz Channel 53



06:21:42 01.10.2025


Plot 7-306. Contention Based Protocol Timing Plot – UNII 5 – 160MHz Channel 47 – Low

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 111 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



06:27:53 01.10.2025

Plot 7-307. Contention Based Protocol Timing Plot –UNII 5 – 160MHz Channel 47 – Mid

Peak



06:30:36 01.10.2025


Plot 7-308. Contention Based Protocol Timing Plot – UNII 5 – 160MHz Channel 47 – High

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 112 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



06:41:31 01.10.2025

Plot 7-309. Contention Based Protocol Timing Plot – UNII 6 – 20MHz Channel 101

Peak



06:43:59 01.10.2025


Plot 7-310. Contention Based Protocol Timing Plot – UNII 6 – 160MHz Channel 111 – Low

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 113 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



06:49:11 01.10.2025

Plot 7-311. Contention Based Protocol Timing Plot – UNII 6 – 160MHz Channel 111 – Mid

Peak



06:52:05 01.10.2025


Plot 7-312. Contention Based Protocol Timing Plot – UNII 6 – 160MHz Channel 111 – High

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 114 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



06:53:42 01.10.2025

Plot 7-313. Contention Based Protocol Timing Plot – UNII 7 – 20MHz Channel 149

Peak



06:57:14 01.10.2025


Plot 7-314. Contention Based Protocol Timing Plot – UNII 7 – 160MHz Channel 143 – Low

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 115 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



07:01:14 01.10.2025

Plot 7-315. Contention Based Protocol Timing Plot – UNII 7 – 160MHz Channel 143 – Mid

Peak



07:03:02 01.10.2025


Plot 7-316. Contention Based Protocol Timing Plot – UNII 7 – 160MHz Channel 143 – High

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 116 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



07:05:53 01.10.2025

Plot 7-317. Contention Based Protocol Timing Plot – UNII 8 – 20MHz Channel 197

Peak



07:08:41 01.10.2025


Plot 7-318. Contention Based Protocol Timing Plot – UNII 8 – 160MHz Channel 207 – Low

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 117 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Peak



07:10:26 01.10.2025

Plot 7-319. Contention Based Protocol Timing Plot – UNII 8 – 160MHz Channel 207 – Mid

Peak



07:12:02 01.10.2025


Plot 7-320. Contention Based Protocol Timing Plot – UNII 8 – 160MHz Channel 207 – High

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 118 of 197

V 11.0 05/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

CBP Bandwidth Reduction Plots



22:21:52 04.12.2025

Plot 7-321. 160MHz Bandwidth, AWGN Signal Injected – 6430Mhz



20:35:38 04.12.2025


Plot 7-322. 160MHz Bandwidth, AWGN Signal Injected – 6505MHz

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 119 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Peak



22:32:29 04.12.2025

Plot 7-323. 160MHz Bandwidth, AWGN Signal Injected – 6580MHz

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 120 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.7 Transmit Power Control (TPC)

§15.407(d)(10); RSS-248[4.5.6]

Test Overview and Limit

Very low power devices operating in the 5.925-6.425 and 6.525-6.875 GHz bands shall employ a transmit power control (TPC) mechanism. A very low power device is required to have the capability to operate at least 6 dB below the maximum EIRP power spectral density (PSD) value of -5 dBm/MHz.

Test Procedure Used

ANSI C63.10:2020 + COR. 1:2023 + C63.10A:2024 + ERRATA TO C63.10A:2024 – Section 12.4.2.6
KDB 789033 D02 v02r01 – Section F

Test Settings

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Set span to encompass the entire 99% OBW of the signal.
3. Set sweep trigger to “free run.”
4. Set RBW = 1 MHz
5. Set VBW $\geq$ 3 MHz
6. Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$.
7. Sweep time $\leq (\text{number of points in sweep}) \times T$, where T is defined
8. Detector = power averaging (rms).
9. Trace mode = max hold.
10. Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Test Instrument & Measurement Setup

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 121 of 197

V 11.0 05/2025

This test demonstrates the ability of the device to increase and decrease power by the required 6dB as the RSSI is decreased and increased.

1. Configure EUT and companion device for peer-to-peer communication as shown in Figure 7-6.
2. Set variable attenuator to 0dB (noise free spectral environment, high RSSI simulation)
3. Establish a link and start communication between EUT and companion device
4. Capture PSD on spectrum analyzer
5. Set attenuator to 20dB (noisy spectral environment, low RSSI simulation)
6. Capture PSD on spectrum analyzer
7. Compare the highest PSD captured in step 4 to the highest PSD on step 6 and determine the delta.

Test Notes

1. The companion device used was model: A3360 (refer to Table 2-10)
2. Per manufacturer's declaration, after establishing communication between the EUT and the companion device, 6GHz UNII signal was used to maintain communication and traffic.
3. TPC is triggered when a high RSSI is detected. As RSSI detected signal decreases, the transmitters output power will increase back to maximum allowed power.

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 122 of 197


V 11.0 05/2025

BW [MHz]	Frequency [MHz]	MIMO		Summed Power Density [dBm/MHz]	Antenna Gain [dBi]	e.i.r.p. Power Density [dBm/MHz]	e.i.r.p. Power Density Limit [dBm/MHz]	Pass/Fail
		Measured Power Density [dBm/MHz]						
		Antenna WF7a	Antenna WF2a					
160	6185	-12.25	-12.81	-9.51	1.00	-8.51	-5.00	Pass

Table 7-43. PSD Measurements (No TPC)

BW [MHz]	Frequency [MHz]	MIMO		Summed Power Density [dBm/MHz]	Antenna Gain [dBi]	e.i.r.p. Power Density [dBm/MHz]	e.i.r.p. Power Density Limit [dBm/MHz]	Pass/Fail
		Measured Power Density [dBm/MHz]						
		Antenna WF7a	Antenna WF2a					
160	6185	-17.98	-17.94	-14.95	1.00	-13.95	-11.00	Pass

Table 7-44. PSD Measurements (with TPC)



Plot 7-324. 160MHz Bandwidth – 6185MHz Antenna WF2a

Plot 7-325. 160MHz Bandwidth – 6185MHz Antenna WF7a

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 123 of 197

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.8 Radiated Spurious Emissions – Above 1GHz

§15.407(b) §15.205 §15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10:2020 + COR. 1:2023 + C63.10A:2024 + ERRATA TO C63.10A:2024 and KDB 789033 D02 v02r01, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11be(SU) (20MHz BW), 802.11be(SU) (40MHz BW), 802.11be(SU) (80MHz), 802.11be(SU) (160MHz) and modulations/data rates were investigated among the UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

For transmitters operating in the 5.925-7.125 GHz band: All emissions outside of the 5.925-7.125 GHz band shall not exceed an EIRP of -27 dBm/MHz. Emissions found in a restricted band are subject to the limits of 15.209 and RSS-Gen (8.9) as shown in the table below.

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-45. Radiated Limits

Test Procedures Used

ANSI C63.10:2020 + COR. 1:2023 + C63.10A:2024 + ERRATA TO C63.10A:2024 – Sections 12.7.7, 12.7.6.
KDB 789033 D02 v02r01 – Section G

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 124 of 197

V 11.0 05/2025

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup

FCC ID: BCGA3461 IC: 579C-A3461			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 125 of 197	

Test Notes

1. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 and section 8.10 of RSS-Gen are below the limit shown in Table 7-45.
2. All spurious emissions lying in restricted bands specified in §15.205 and section 8.10 of RSS-Gen are below the limit shown in Table 7-45. All spurious emissions that do not lie in a restricted band are subject to a limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dB μ V/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB μ V/m.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas.
6. D is the measurement test distance and emissions 1-18GHz were measured at a 3 meters test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. All data rates were investigated and only the worse case is reported
9. The unit was tested with all possible modes and only the highest emission is reported.
10. The “-” shown in the following RSE tables are used to denote a noise floor measurement.
11. All radiated measurements were tested at the highest supported power setting per band.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level [dB μ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB] – Preamplifier Gain [dB]
- Margin [dB] = Field Strength Level [dB μ V/m] – Limit [dB μ V/m]


Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.8.3 to 7.8.22 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 126 of 197

V 11.0 05/2025

7.8.1 SDM Primary Radiated Spurious Emission



Plot 7-326. Radiated Spurious Emissions 1-18GHz SDM Primary (802.11be – Ch. 33)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6115MHz
Channel:	33

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 12230.00	Average	V	-	-	-84.23	17.53	40.30	53.98	-13.68
* 12230.00	Peak	V	-	-	-73.24	17.53	51.29	73.98	-22.69


Table 7-46. Radiated Spurious Emission Measurements SDM Primary

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 127 of 197

V 11.0 05/2025



Plot 7-327. Radiated Spurious Emissions 1-18GHz SDM Primary (802.11be – Ch. 61)




Plot 7-328. Radiated Spurious Emissions 18-40GHz SDM Primary (802.11be – Ch. 61)

Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6255MHz
Channel: 61

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 12510.00	Average	H	-	-	-84.19	18.18	0.00	40.99	53.98	-12.99
* 12510.00	Peak	H	-	-	-73.17	18.18	0.00	52.01	73.98	-21.97
* 18765.00	Average	V	-	-	-64.29	-5.83	-9.54	27.34	53.98	-26.64
* 18765.00	Peak	V	-	-	-53.07	-5.83	-9.54	38.56	73.98	-35.42
25020.00	Average	V	-	-	-66.43	-5.50	-9.54	25.53	68.23	-42.70
25020.00	Peak	V	-	-	-55.44	-5.50	-9.54	36.52	88.23	-51.71
* 31275.00	Average	V	-	-	-65.23	-3.15	-9.54	29.08	53.98	-24.90
* 31275.00	Peak	V	-	-	-53.77	-3.15	-9.54	40.54	73.98	-33.44

Table 7-47. Radiated Spurious Emission Measurements SDM Primary

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 128 of 197



Plot 7-329. Radiated Spurious Emissions 1-18GHz SDM (802.11be – Ch. 93)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6415MHz
Channel:	93

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
12830.00	Average	V	-	-	-84.10	18.32	41.22	68.23	-27.01
12830.00	Peak	V	-	-	-73.14	18.32	52.19	88.23	-36.04

Table 7-48. Radiated Spurious Emission Measurements SDM Primary

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 129 of 197

V 11.0 05/2025



Plot 7-330. Radiated Spurious Emissions 1-18GHz SDM Primary (802.11be – Ch. 97)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6435MHz
Channel:	97

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
12870.00	Average	V	-	-	-84.33	18.29	40.97	68.23	-27.26
12870.00	Peak	V	-	-	-72.84	18.29	52.46	88.23	-35.77


Table 7-49. Radiated Spurious Emission Measurements SDM Primary

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 130 of 197

V 11.0 05/2025



Plot 7-331. Radiated Spurious Emissions 1-18GHz SDM Primary (802.11be – Ch. 105)




Plot 7-332. Radiated Spurious Emissions 18-40GHz SDM Primary (802.11be – Ch. 105)

Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6475MHz
Channel:	105

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
12950.00	Average	V	-	-	-84.15	18.82	0.00	41.67	68.23	-26.56
12950.00	Peak	V	-	-	-73.26	18.82	0.00	52.56	88.23	-35.67
* 19425.00	Average	V	-	-	-61.64	-7.74	-9.54	28.08	53.98	-25.90
* 19425.00	Peak	V	-	-	-50.61	-7.74	-9.54	39.11	73.98	-34.87
25900.00	Average	V	-	-	-61.25	-5.72	-9.54	30.49	68.23	-37.74
25900.00	Peak	V	-	-	-49.62	-5.72	-9.54	42.12	88.23	-46.11
32375.00	Average	V	-	-	-63.21	-3.92	-9.54	30.33	68.23	-37.90
32375.00	Peak	V	-	-	-51.67	-3.92	-9.54	41.87	88.23	-46.36

Table 7-50. Radiated Spurious Emission Measurements SDM Primary

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 131 of 197



Plot 7-333. Radiated Spurious Emissions 1-18GHz SDM Primary (802.11be – Ch. 113)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6515MHz
Channel:	113

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13030.00	Average	V	-	-	-84.08	18.43	41.36	68.23	-26.87
13030.00	Peak	V	-	-	-72.84	18.43	52.59	88.23	-35.64

Table 7-51. Radiated Spurious Emission Measurements SDM Primary

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 132 of 197

V 11.0 05/2025



Plot 7-334. Radiated Spurious Emissions 1-18GHz SDM Primary (802.11be – Ch. 117)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6535MHz
Channel:	117

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13070.00	Average	V	-	-	-83.89	18.65	41.76	68.23	-26.47
13070.00	Peak	V	-	-	-72.49	18.65	53.16	88.23	-35.07


Table 7-52. Radiated Spurious Emission Measurements SDM Primary

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 133 of 197

V 11.0 05/2025



Plot 7-335. Radiated Spurious Emissions 1-18GHz SDM Primary (802.11be – Ch. 149)




Plot 7-336. Radiated Spurious Emissions 18-40GHz SDM Primary (802.11be – Ch. 149)

Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6695MHz
Channel:	149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 13390.00	Average	V	-	-	-83.62	18.39	0.00	41.78	53.98	-12.20
* 13390.00	Peak	V	-	-	-72.58	18.39	0.00	52.81	73.98	-21.17
* 20085.00	Average	V	-	-	-60.10	-8.03	-9.54	29.33	53.98	-24.65
* 20085.00	Peak	V	-	-	-48.34	-8.03	-9.54	41.09	73.98	-32.89
26780.00	Average	V	-	-	-62.49	-5.23	-9.54	29.74	68.23	-38.49
26780.00	Peak	V	-	-	-50.68	-5.23	-9.54	41.55	88.23	-46.68
33475.00	Average	V	-	-	-61.36	-4.28	-9.54	31.82	68.23	-36.41
33475.00	Peak	V	-	-	-50.13	-4.28	-9.54	43.05	88.23	-45.18

Table 7-53. Radiated Spurious Emission Measurements SDM Primary

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 134 of 197



Plot 7-337. Radiated Spurious Emissions 1-18GHz SDM Primary (802.11be – Ch. 185)


Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6875MHz
Channel: 185

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13750.00	Average	H	-	-	-83.51	18.52	42.00	68.23	-26.23
13750.00	Peak	H	-	-	-71.67	18.52	53.85	88.23	-34.38

Table 7-54. Radiated Spurious Emission Measurements SDM Primary

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 135 of 197

V 11.0 05/2025



Plot 7-338. Radiated Spurious Emissions 1-18GHz SDM Primary (802.11be – Ch. 189)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6895MHz
Channel:	189

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13790.00	Average	H	-	-	-83.31	18.27	41.96	68.23	-26.27
13790.00	Peak	H	-	-	-72.45	18.27	52.82	88.23	-35.41


Table 7-55. Radiated Spurious Emission Measurements SDM Primary

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 136 of 197

V 11.0 05/2025



Plot 7-339. Radiated Spurious Emissions 1-18GHz SDM Primary (802.11be – Ch. 209)



Plot 7-340. Radiated Spurious Emissions 18-40GHz SDM Primary (802.11be – Ch. 209)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6995MHz
Channel:	209

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13990.00	Average	V	-	-	-84.26	18.45	0.00	41.19	68.23	-27.04
13990.00	Peak	V	-	-	-72.81	18.45	0.00	52.64	88.23	-35.59
* 20985.00	Average	V	-	-	-61.35	-7.58	-9.54	28.53	53.98	-25.45
* 20985.00	Peak	V	-	-	-50.35	-7.58	-9.54	39.53	73.98	-34.45
27980.00	Average	V	-	-	-64.03	-4.29	-9.54	29.14	68.23	-39.09
27980.00	Peak	V	-	-	-52.37	-4.29	-9.54	40.80	88.23	-47.43
34975.00	Average	V	-	-	-61.41	-4.53	-9.54	31.52	68.23	-36.71
34975.00	Peak	V	-	-	-50.01	-4.53	-9.54	42.92	88.23	-45.31

Table 7-56. Radiated Spurious Emission Measurements SDM Primary

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 137 of 197

V 11.0 05/2025



Plot 7-341. Radiated Spurious Emissions 1-18GHz SDM Primary (802.11be – Ch. 233)

Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 7115MHz
Channel: 233


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
14230.00	Average	H	-	-	-84.26	18.49	41.23	68.23	-27.00
14230.00	Peak	H	-	-	-72.85	18.49	52.65	88.23	-35.58

Table 7-57. Radiated Spurious Emission Measurements SDM Primary

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 138 of 197

V 11.0 05/2025

7.8.2 SDM Diversity Radiated Spurious Emission



Plot 7-342. Radiated Spurious Emissions 1-18GHz SDM Diversity (802.11be – Ch. 33)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6115MHz
Channel:	33

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 12230.00	Average	H	-	-	-84.54	17.65	40.11	53.98	-13.87
* 12230.00	Peak	H	-	-	-72.94	17.65	51.72	73.98	-22.26


Table 7-58. Radiated Spurious Emission Measurements SDM Diversity

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 139 of 197

V 11.0 05/2025



Plot 7-343. Radiated Spurious Emissions 1-18GHz SDM Diversity (802.11be – Ch. 61)




Plot 7-344. Radiated Spurious Emissions 18-40GHz SDM Primary (802.11be – Ch. 61)

Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6255MHz
Channel:	61

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 12510.00	Average	V	-	-	-84.11	18.21	0.00	41.09	53.98	-12.89
* 12510.00	Peak	V	-	-	-72.88	18.21	0.00	52.33	73.98	-21.65
* 18765.00	Average	V	-	-	-63.92	-5.84	-9.54	27.70	53.98	-26.28
* 18765.00	Peak	V	-	-	-52.57	-5.84	-9.54	39.05	73.98	-34.93
25020.00	Average	V	-	-	-65.03	-5.50	-9.54	26.93	68.23	-41.30
25020.00	Peak	V	-	-	-53.64	-5.50	-9.54	38.32	88.23	-49.91
* 31275.00	Average	V	-	-	-65.03	-3.15	-9.54	29.28	53.98	-24.70
* 31275.00	Peak	V	-	-	-53.26	-3.15	-9.54	41.05	73.98	-32.93

Table 7-59. Radiated Spurious Emission Measurements SDM Diversity

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 140 of 197



Plot 7-345. Radiated Spurious Emissions 1-18GHz SDM Diversity (802.11be – Ch. 93)


Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6415MHz
Channel: 93

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
12830.00	Average	V	-	-	-84.92	22.09	44.17	68.23	-24.06
12830.00	Peak	V	-	-	-73.18	22.09	55.91	88.23	-32.32

Table 7-60. Radiated Spurious Emission Measurements SDM Diversity

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 141 of 197

V 11.0 05/2025



Plot 7-346. Radiated Spurious Emissions 1-18GHz SDM Diversity (802.11be – Ch. 97)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6435MHz
Channel:	97

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
12870.00	Average	V	-	-	-84.65	21.67	44.02	68.23	-24.21
12870.00	Peak	V	-	-	-73.41	21.67	55.26	88.23	-32.97


Table 7-61. Radiated Spurious Emission Measurements SDM Diversity

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 142 of 197

V 11.0 05/2025



Plot 7-347. Radiated Spurious Emissions 1-18GHz SDM Diversity (802.11be – Ch. 105)



Plot 7-348. Radiated Spurious Emissions 18-40GHz SDM Diversity (802.11be – Ch. 105)

Mode: 802.11be

Data Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 6475MHz


Channel: 105

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
12950.00	Average	V	-	-	-85.11	21.73	0.00	43.63	68.23	-24.60
12950.00	Peak	V	-	-	-73.11	21.73	0.00	55.62	88.23	-32.61
* 19425.00	Average	V	-	-	-61.74	-7.74	-9.54	27.98	53.98	-26.00
* 19425.00	Peak	V	-	-	-50.27	-7.74	-9.54	39.45	73.98	-34.53
25900.00	Average	V	-	-	-61.23	-5.91	-9.54	30.32	68.23	-37.91
25900.00	Peak	V	-	-	-49.31	-5.91	-9.54	42.24	88.23	-45.99
32375.00	Average	V	-	-	-63.16	-3.92	-9.54	30.38	68.23	-37.85
32375.00	Peak	V	-	-	-51.83	-3.92	-9.54	41.71	88.23	-46.52

Table 7-62. Radiated Spurious Emission Measurements SDM Diversity

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 143 of 197

V 11.0 05/2025



Plot 7-349. Radiated Spurious Emissions 1-18GHz SDM Diversity (802.11be – Ch. 113)


Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6515MHz
Channel: 113

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13030.00	Average	V	-	-	-85.36	22.04	43.68	68.23	-24.55
13030.00	Peak	V	-	-	-74.01	22.04	55.03	88.23	-33.20

Table 7-63. Radiated Spurious Emission Measurements SDM Diversity

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 144 of 197

V 11.0 05/2025



Plot 7-350. Radiated Spurious Emissions 1-18GHz SDM Diversity (802.11be – Ch. 117)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6535MHz
Channel:	117

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13070.00	Average	V	-	-	-85.21	21.85	43.65	68.23	-24.58
13070.00	Peak	V	-	-	-74.15	21.85	54.71	88.23	-33.52


Table 7-64. Radiated Spurious Emission Measurements SDM Diversity

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 145 of 197

V 11.0 05/2025



Plot 7-351. Radiated Spurious Emissions 1-18GHz SDM Diversity (802.11be – Ch. 149)



Plot 7-352. Radiated Spurious Emissions 18-40GHz SDM Diversity (802.11be – Ch. 149)


Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6695MHz
Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 13390.00	Average	H	-	-	-84.61	21.77	0.00	44.16	53.98	-9.82
* 13390.00	Peak	H	-	-	-73.44	21.77	0.00	55.33	73.98	-18.65
* 20085.00	Average	V	-	-	-60.11	-8.00	-9.54	29.35	53.98	-24.63
* 20085.00	Peak	V	-	-	-48.14	-8.00	-9.54	41.32	73.98	-32.66
26780.00	Average	V	-	-	-62.67	-5.10	-9.54	29.69	68.23	-38.54
26780.00	Peak	V	-	-	-51.45	-5.10	-9.54	40.91	88.23	-47.32
33475.00	Average	V	-	-	-61.68	-4.21	-9.54	31.57	68.23	-36.66
33475.00	Peak	V	-	-	-49.60	-4.21	-9.54	43.65	88.23	-44.58

Table 7-65. Radiated Spurious Emission Measurements SDM Diversity

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 146 of 197

V 11.0 05/2025



Plot 7-353. Radiated Spurious Emissions 1-18GHz SDM Diversity (802.11be – Ch. 185)


Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6875MHz
Channel: 185

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13750.00	Average	V	-	-	-82.90	21.84	45.94	68.23	-22.29
13750.00	Peak	V	-	-	-71.30	21.84	57.53	88.23	-30.70

Table 7-66. Radiated Spurious Emission Measurements SDM Diversity

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 147 of 197

V 11.0 05/2025



Plot 7-354. Radiated Spurious Emissions 1-18GHz SDM Diversity (802.11be – Ch. 189)


Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6895MHz
Channel: 189

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13790.00	Average	V	-	-	-83.38	22.27	45.89	68.23	-22.34
13790.00	Peak	V	-	-	-71.95	22.27	57.32	88.23	-30.91


Table 7-67. Radiated Spurious Emission Measurements SDM Diversity

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 148 of 197

V 11.0 05/2025



Plot 7-355. Radiated Spurious Emissions 1-18GHz SDM Diversity (802.11be – Ch. 209)



Plot 7-356. Radiated Spurious Emissions 18-40GHz SDM Diversity (802.11be – Ch. 209)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6995MHz
Channel:	209

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13990.00	Average	H	-	-	-83.59	22.07	0.00	45.48	68.23	-22.75
13990.00	Peak	H	-	-	-72.26	22.07	0.00	56.81	88.23	-31.42
* 20985.00	Average	V	-	-	-68.97	-7.58	-9.54	30.45	53.98	-23.53
* 20985.00	Peak	V	-	-	-57.72	-7.58	-9.54	41.70	73.98	-32.28
27980.00	Average	V	-	-	-68.14	-4.51	-9.54	34.35	68.23	-33.88
27980.00	Peak	V	-	-	-56.76	-4.51	-9.54	45.73	88.23	-42.50
34975.00	Average	V	-	-	-66.01	-4.53	-9.54	36.46	68.23	-31.77
34975.00	Peak	V	-	-	-54.82	-4.62	-9.54	47.56	88.23	-40.67

Table 7-68. Radiated Spurious Emission Measurements SDM Diversity

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 149 of 197

V 11.0 05/2025



Plot 7-357. Radiated Spurious Emissions 1-18GHz SDM Diversity (802.11be – Ch. 233)

Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 7115MHz
Channel: 233


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
14230.00	Average	H	-	-	-84.33	22.84	45.52	68.23	-22.71
14230.00	Peak	H	-	-	-72.64	22.84	57.20	88.23	-31.03

Table 7-69. Radiated Spurious Emission Measurements SDM Diversity


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 150 of 197

V 11.0 05/2025

Mode	802.11a
Data Rate	54Mbps
Distance of Measurement	3 Meters
Operating Frequency	7115MHz
Channel	233




Plot 7-360 Antenna WF7a Radiated Integrated Band Edge (Peak – UNII Band 8)



Plot 7-361 Antenna WF7a Radiated Integrated Band Edge (Average – UNII Band 8)


Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6115MHz
Channel	33



Plot 7-362 Antenna WF7a Radiated Lower Band Edge (Peak & Average – UNII Band 5)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 152 of 197

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7095MHz
Channel	229




Plot 7-363 Antenna WF7a Radiated Upper Band Edge (Peak & Average – UNII Band 8)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7115MHz
Channel	233



Plot 7-364 Antenna WF7a Radiated Integrated Band Edge (Peak – UNII Band 8)




Plot 7-365 Antenna WF7a Radiated Integrated Band Edge (Average – UNII Band 8)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 153 of 197

V 11.0 05/2025


7.8.4 Antenna WF7a Radiated Band Edge Measurements (40MHz BW)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6125MHz
Channel	35



Plot 7-366 Antenna WF7a Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7085MHz
Channel	227




Plot 7-367 Antenna WF7a Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 154 of 197

V 11.0 05/2025


7.8.5 Antenna WF7a Radiated Band Edge Measurements (80MHz BW)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6145MHz
Channel	39



Plot 7-368 Antenna WF7a Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	7025MHz
Channel	215




Plot 7-369 Antenna WF7a Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 155 of 197

V 11.0 05/2025


7.8.6 Antenna WF7a Radiated Band Edge Measurements (160MHz BW)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6185MHz
Channel	47



Plot 7-370 Antenna WF7a Radiated Lower Band Edge (Peak & Average – UNII Band 5)

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6825MHz
Channel	175




Plot 7-371 Antenna WF7a Radiated Upper Band Edge (Peak & Average – UNII Band 7)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 156 of 197

V 11.0 05/2025

Mode	802.11be-SU
Data Rate	MCS11
Distance of Measurement	3 Meters
Operating Frequency	6985MHz
Channel	207



Plot 7-372 Antenna WF7a Radiated Upper Band Edge (Peak & Average – UNII Band 8)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-17-R3.BCG	Test Dates: 9/15/2025 - 01/09/2026	EUT Type: Tablet Device	Page 157 of 197

V 11.0 05/2025

