







Plot 7-397. CDD Primary (Peak & Average, Ch.42, 802.11ac, MCS9)




Plot 7-400. CDD Primary (Peak & Average, Ch.122, 802.11ac, MCS9)




Plot 7-398. CDD Primary (Peak & Average, Ch.58, 802.11ac, MCS9)



Plot 7-401. CDD Primary (Peak, Ch.122, 802.11ac, MCS9)




Plot 7-399. CDD Primary (Peak & Average, Ch.106, 802.11ac, MCS9)




Plot 7-402. CDD Primary (Peak, Ch.155, 802.11ac, MCS9)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device		Page 239 of 273




Plot 7-403. CDD Primary (Peak, Ch.155, 802.11ac, MCS9)




Plot 7-406. CDD Primary (Peak & Average, Ch.106, 802.11be(SU), MCS11)




Plot 7-404. CDD Primary (Peak & Average, Ch.42, 802.11be(SU), MCS11)



Plot 7-407. CDD Primary (Peak & Average, Ch.122, 802.11be(SU), MCS11)




Plot 7-405. CDD Primary (Peak & Average, Ch.58, 802.11be(SU), MCS11)




Plot 7-408. CDD Primary (Peak, Ch.122, 802.11be(SU), MCS11)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device		Page 240 of 273




Plot 7-409. CDD Primary (Peak, Ch.155, 802.11be(SU), MCS11)




Plot 7-410. CDD Primary (Peak, Ch.155, 802.11be(SU), MCS11)


7.6.19 CDD Primary Radiated Band Edge Measurements (160MHz BW)



Plot 7-411. CDD Primary (Peak & Average, Ch.50, 802.11ac, MCS9)



Plot 7-413. CDD Primary (Peak & Average, Ch.114, 802.11ac, MCS9)




Plot 7-412. CDD Primary (Peak & Average, Ch.50, 802.11ac, MCS9)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device		Page 241 of 273

V 11.0 05/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-414. CDD Primary (Peak, Ch.114, 802.11ac, MCS9)




Plot 7-417. CDD Primary (Peak & Average, Ch.114, 802.11be(SU), MCS11)



Plot 7-415. CDD Primary (Peak & Average, Ch.50, 802.11be(SU), MCS11)



Plot 7-418. CDD Primary (Peak, Ch.114, 802.11be(SU), MCS11)




Plot 7-416. CDD Primary (Peak & Average, Ch.50, 802.11be(SU), MCS11)

7.6.20 CDD Diversity Radiated Band Edge Measurements (20MHz BW)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 242 of 273

V 11.0 05/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-419. CDD Diversity (Peak & Average, Ch.36, 802.11n, MCS7)




Plot 7-422. CDD Diversity (Peak & Average, Ch.64, 802.11n, MCS7)




Plot 7-420. CDD Diversity (Peak & Average, Ch.40, 802.11n, MCS7)



Plot 7-423. CDD Diversity (Peak & Average, Ch.100, 802.11n, MCS7)




Plot 7-421. CDD Diversity (Peak & Average, Ch.60, 802.11n, MCS7)




Plot 7-424. CDD Diversity (Peak & Average, Ch.104, 802.11n, MCS7)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device		Page 243 of 273




Plot 7-425. CDD Diversity (Peak & Average, Ch.108, 802.11n, MCS7)




Plot 7-428. CDD Diversity (Peak, Ch.140, 802.11n, MCS7)




Plot 7-426. CDD Diversity (Peak, Ch.132, 802.11n, MCS7)



Plot 7-429. CDD Diversity (Peak, Ch.149, 802.11n, MCS7)




Plot 7-427. CDD Diversity (Peak, Ch.136, 802.11n, MCS7)




Plot 7-430. CDD Diversity (Peak, Ch.165, 802.11n, MCS7)


FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 244 of 273




Plot 7-431. CDD Diversity (Peak & Average, Ch.36, 802.11be(SU), MCS11)




Plot 7-434. CDD Diversity (Peak & Average, Ch.64, 802.11be(SU), MCS11)




Plot 7-432. CDD Diversity (Peak & Average, Ch.40, 802.11be(SU), MCS11)



Plot 7-435. CDD Diversity (Peak & Average, Ch.100, 802.11be(SU), MCS11)




Plot 7-433. CDD Diversity (Peak & Average, Ch.60, 802.11be(SU), MCS11)




Plot 7-436. CDD Diversity (Peak & Average, Ch.104, 802.11be(SU), MCS11)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 245 of 273




Plot 7-437. CDD Diversity (Peak & Average, Ch.108, 802.11be(SU), MCS11)




Plot 7-440. CDD Diversity (Peak, Ch.140, 802.11be(SU), MCS11)




Plot 7-438. CDD Diversity (Peak, Ch.132, 802.11be(SU), MCS11)



Plot 7-441. CDD Diversity (Peak, Ch.149, 802.11be(SU), MCS11)



Plot 7-439. CDD Diversity (Peak, Ch.136, 802.11be(SU), MCS11)




Plot 7-442. CDD Diversity (Peak, Ch.165, 802.11be(SU), MCS11)

7.6.21 CDD Diversity Radiated Band Edge Measurements (40MHz BW)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 246 of 273

V 11.0 05/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-443. CDD Diversity (Peak & Average, Ch.38, 802.11n, MCS7)




Plot 7-446. CDD Diversity (Peak & Average, Ch.62, 802.11n, MCS7)




Plot 7-444. CDD Diversity (Peak & Average, Ch.46, 802.11n, MCS7)



Plot 7-447. CDD Diversity (Peak & Average, Ch.102, 802.11n, MCS7)




Plot 7-445. CDD Diversity (Peak & Average, Ch.54, 802.11n, MCS7)




Plot 7-448. CDD Diversity (Peak & Average, Ch.110, 802.11n, MCS7)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device		Page 247 of 273




Plot 7-449. CDD Diversity (Peak & Average, Ch.118, 802.11n, MCS7)




Plot 7-452. CDD Diversity (Peak, Ch.159, 802.11n, MCS7)




Plot 7-450. CDD Diversity (Peak, Ch.134, 802.11n, MCS7)



Plot 7-453. CDD Diversity (Peak & Average, Ch.38, 802.11be(SU), MCS11)




Plot 7-451. CDD Diversity (Peak, Ch.151, 802.11n, MCS7)




Plot 7-454. CDD Diversity (Peak & Average, Ch.46, 802.11be(SU), MCS11)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 248 of 273




Plot 7-455. CDD Diversity (Peak & Average, Ch.54, 802.11be(SU), MCS11)




Plot 7-458. CDD Diversity (Peak & Average, Ch.110, 802.11be(SU), MCS11)




Plot 7-456. CDD Diversity (Peak & Average, Ch.62, 802.11be(SU), MCS11)



Plot 7-459. CDD Diversity (Peak & Average, Ch.118, 802.11be(SU), MCS11)




Plot 7-457. CDD Diversity (Peak & Average, Ch.102, 802.11be(SU), MCS11)




Plot 7-460. CDD Diversity (Peak, Ch.134, 802.11be(SU), MCS11)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device		Page 249 of 273




Plot 7-461. CDD Diversity (Peak, Ch.151, 802.11be(SU), MCS11)




Plot 7-462. CDD Diversity (Peak, Ch.159, 802.11be(SU), MCS11)


7.6.22 CDD Diversity Radiated Band Edge Measurements (80MHz BW)



Plot 7-463. CDD Diversity (Peak & Average, Ch.42, 802.11ac, MCS9)



Plot 7-465. CDD Diversity (Peak & Average, Ch.106, 802.11ac, MCS9)




Plot 7-464. CDD Diversity (Peak & Average, Ch.58, 802.11ac, MCS9)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device		Page 250 of 273

V 11.0 05/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-466. CDD Diversity (Peak & Average, Ch.122, 802.11ac, MCS9)




Plot 7-469. CDD Diversity (Peak, Ch.155, 802.11ac, MCS9)




Plot 7-467. CDD Diversity (Peak, Ch.122, 802.11ac, MCS9)



Plot 7-470. CDD Diversity (Peak & Average, Ch.42, 802.11be(SU), MCS11)




Plot 7-468. CDD Diversity (Peak, Ch.155, 802.11ac, MCS9)




Plot 7-471. CDD Diversity (Peak & Average, Ch.58, 802.11be(SU), MCS11)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG			Page 251 of 273
Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device		




Plot 7-472. CDD Diversity (Peak & Average, Ch.106, 802.11be(SU), MCS11)




Plot 7-475. CDD Diversity (Peak, Ch.155, 802.11be(SU), MCS11)



Plot 7-473. CDD Diversity (Peak & Average, Ch.122, 802.11be(SU), MCS11)



Plot 7-476. CDD Diversity (Peak, Ch.155, 802.11be(SU), MCS11)




Plot 7-474. CDD Diversity (Peak, Ch.122, 802.11be(SU), MCS11)

7.6.23 CDD Diversity Radiated Band Edge Measurements (160MHz BW)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 252 of 273

V 11.0 05/2025


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-477. CDD Diversity (Peak & Average, Ch.50, 802.11ac, MCS9)




Plot 7-480. CDD Diversity (Peak, Ch.114, 802.11ac, MCS9)




Plot 7-478. CDD Diversity (Peak & Average, Ch.50, 802.11ac, MCS9)



Plot 7-481. CDD Diversity (Peak & Average, Ch.50, 802.11be(SU), MCS11)




Plot 7-479. CDD Diversity (Peak & Average, Ch.114, 802.11ac, MCS9)




Plot 7-482. CDD Diversity (Peak & Average, Ch.50, 802.11be(SU), MCS11)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 253 of 273



Plot 7-483. CDD Diversity (Peak & Average, Ch.114, 802.11be(SU), MCS11)



Plot 7-484. CDD Diversity (Peak, Ch.114, 802.11be(SU), MCS11)

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 254 of 273

7.7 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-168 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-168. Radiated Limits

Test Procedures Used

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = quasi-peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 255 of 273

V 11.0 05/2025

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-6. Radiated Test Setup < 30MHz




Figure 7-7. Radiated Test Setup < 1GHz

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 256 of 273

V 11.0 05/2025

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-168.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector on emissions that were within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
10. All antenna configurations were investigated and only the worst case is reported.
11. The unit was tested with all possible modes and only the highest emission is reported.

Sample Calculations


Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]} - \text{Preamplifier Gain}_{[dB]}$
- $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 257 of 273

V 11.0 05/2025

7.7.1 CDD Primary Radiated Spurious Emissions Measurements (Below 1GHz)




Plot 7-485. Radiated Spurious Emissions below 1GHz CDD Primary, 802.11n, Ch.40 with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
30.27	Max-Peak	V	100	-	-57.02	-19.24	30.73	40.00	-9.27
85.89	Max-Peak	V	100	-	-60.98	-20.82	25.20	40.00	-14.80
116.73	Max-Peak	H	300	-	-60.07	-19.13	27.81	43.50	-15.69
186.99	Max-Peak	H	100	-	-50.90	-18.85	37.25	43.50	-6.25
226.05	Max-Peak	H	100	-	-59.78	-17.07	30.15	46.00	-15.85
892.33	Max-Peak	H	200	-	-72.65	-4.39	29.97	46.00	-16.03

Table 7-169. Radiated Spurious Emissions below 1GHz CDD Primary, 802.11n, Ch.40 with AC/DC Adapter

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 258 of 273

V 11.0 05/2025



Plot 7-486. Radiated Spurious Emissions below 1GHz CDD Primary, 802.11be (SU), Ch.40 with AC/DC Adapter


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
30.27	Max-Peak	V	100	-	-55.57	-19.24	32.19	40.00	-7.81
48.87	Max-Peak	V	100	-	-63.57	-15.01	28.42	40.00	-11.58
116.07	Max-Peak	H	300	-	-59.75	-18.99	28.25	43.50	-15.25
188.13	Max-Peak	H	100	-	-51.66	-18.72	36.62	43.50	-6.88
227.49	Max-Peak	H	100	-	-60.29	-16.93	29.78	46.00	-16.22
887.29	Max-Peak	V	100	-	-72.45	-4.64	29.92	46.00	-16.08

Table 7-170. Radiated Spurious Emissions below 1GHz CDD Primary, 802.11be (SU), Ch.40 with AC/DC Adapter

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 259 of 273

V 11.0 05/2025

7.7.2 CDD Diversity Radiated Spurious Emissions Measurements (Below 1GHz)




Plot 7-487. Radiated Spurious Emissions below 1GHz CDD Diversity, 802.11n, Ch.40 with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
30.03	Max-Peak	V	200	-	-54.25	-19.21	33.55	40.00	-6.45
44.43	Max-Peak	V	100	-	-62.07	-15.33	29.60	40.00	-10.40
118.59	Max-Peak	H	200	-	-60.97	-19.43	26.61	43.50	-16.89
195.51	Max-Peak	H	100	-	-51.97	-17.65	37.38	43.50	-6.12
219.93	Max-Peak	H	100	-	-58.61	-17.44	30.95	46.00	-15.05
897.31	Max-Peak	V	300	-	-72.94	-4.38	29.67	46.00	-16.33

Table 7-171. Radiated Spurious Emissions below 1GHz CDD Diversity, 802.11n, Ch.40 with AC/DC Adapter

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 260 of 273

V 11.0 05/2025



Plot 7-488. Radiated Spurious Emissions below 1GHz CDD Diversity, 802.11be (SU), Ch.40 with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
42.93	Max-Peak	V	100	-	-61.85	-15.57	29.58	40.00	-10.42
59.37	Max-Peak	V	100	-	-65.05	-16.74	25.21	40.00	-14.79
118.47	Max-Peak	H	200	-	-60.01	-19.40	27.59	43.50	-15.91
195.45	Max-Peak	H	100	-	-54.76	-17.66	34.59	43.50	-8.91
220.17	Max-Peak	H	100	-	-56.65	-17.42	32.93	46.00	-13.07
862.75	Max-Peak	H	200	-	-71.99	-4.78	30.23	46.00	-15.77

Table 7-172. Radiated Spurious Emissions below 1GHz CDD Diversity, 802.11be (SU), Ch.40 with AC/DC Adapter


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 261 of 273

V 11.0 05/2025

7.7.3 Simultaneous TX Radiated Spurious Emissions Measurements (Below 1GHz)

Description	Bluetooth	UNII
Antenna	Antenna WF7b	Antenna WF7b
Channel	78	36
Operating Frequency (MHz)	2480	5180
Mode/Modulation	GFSK ePA	802.11n

Table 7-173. Worst Case Simultaneous Transmission Configuration



Plot 7-489. Radiated Spurious Emissions – Simultaneous Transmission 30MHz – 1GHz, with AC/DC Adapter)

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
31.32	Max-Peak	V	100	-	-65.24	-14.03	27.73	40.00	-12.27
63.18	Max-Peak	V	100	-	-68.16	-22.37	16.47	40.00	-23.53
131.58	Max-Peak	H	200	-	-59.08	-20.96	26.95	43.50	-16.55
191.11	Max-Peak	H	200	-	-58.28	-18.36	30.35	43.50	-13.15
493.52	Max-Peak	H	300	-	-74.37	-9.67	22.97	46.00	-23.03
930.94	Max-Peak	V	100	-	-74.77	-2.84	29.39	46.00	-16.61

Table 7-174. Radiated Spurious Emissions – Simultaneous Transmission 30MHz – 1GHz, with AC/DC Adapter)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 262 of 273

V 11.0 05/2025

7.8 AC Line-Conducted Emissions Measurement

§15.407; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-175. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024, Section 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 263 of 273

V 11.0 05/2025

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-8. Test Instrument & Measurement Setup


Test Notes

- All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
- Both configurations below were investigated, and the worst case has been reported.
 - EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - EUT powered by host PC via USB-C cable with wire charger
- The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
- $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
- $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Correction Factor (dB)}$
- $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
- Traces shown in plots are made using quasi-peak and average detectors.
- Deviations to the Specifications: None.
- The unit was tested with all possible modes and only the highest emission is reported.

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 264 of 273

V 11.0 05/2025

7.8.1 CDD Primary AC Line-Conducted Emissions Measurement



Plot 7-490. AC Line Conducted Plot with 802.11n CDD Primary – Ch.40 (L1), with AC/DC adapter


Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	34.25	55.17	-20.92	L1	GND
0.17	FINAL	51.09	---	65.17	-14.08	L1	GND
0.25	FINAL	---	26.89	51.79	-24.90	L1	GND
0.25	FINAL	45.10	---	61.79	-16.69	L1	GND
0.51	FINAL	---	17.79	46.00	-28.21	L1	GND
0.51	FINAL	36.51	---	56.00	-19.49	L1	GND
1.35	FINAL	30.50	---	56.00	-25.50	L1	GND
1.35	FINAL	---	14.97	46.00	-31.03	L1	GND
5.01	FINAL	24.78	---	60.00	-35.22	L1	GND
5.01	FINAL	---	12.77	50.00	-37.23	L1	GND
16.17	FINAL	---	11.13	50.00	-38.87	L1	GND
16.17	FINAL	15.03	---	60.00	-44.97	L1	GND

Table 7-176. AC Line Conducted Data with 802.11n CDD Primary – Ch.40 (L1) with AC/DC adapter

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 265 of 273

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-491. AC Line Conducted Plot with 802.11n CDD Primary – Ch.40 (N), with AC/DC adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.17	FINAL	---	37.48	55.17	-17.69	N	GND
0.17	FINAL	54.00	---	65.17	-11.17	N	GND
0.25	FINAL	---	29.99	51.87	-21.88	N	GND
0.25	FINAL	47.24	---	61.87	-14.63	N	GND
0.51	FINAL	---	18.22	46.00	-27.78	N	GND
0.51	FINAL	38.09	---	56.00	-17.91	N	GND
1.35	FINAL	32.06	---	56.00	-23.94	N	GND
1.35	FINAL	---	16.04	46.00	-29.96	N	GND
5.01	FINAL	28.13	---	60.00	-31.87	N	GND
5.01	FINAL	---	17.31	50.00	-32.69	N	GND
16.17	FINAL	---	8.70	50.00	-41.30	N	GND
16.17	FINAL	14.31	---	60.00	-45.69	N	GND

Table 7-177. AC Line Conducted Data with 802.11n CDD Primary – Ch.40 (N), with AC/DC adapter

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 266 of 273




Plot 7-492. AC Line Conducted Plot with 802.11be(SU) CDD Primary – Ch.40 (L1), with AC/DC adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.17	FINAL	---	34.12	55.17	-21.05	L1	GND
0.17	FINAL	50.92	---	65.17	-14.25	L1	GND
0.24	FINAL	---	28.77	52.02	-23.25	L1	GND
0.24	FINAL	44.87	---	62.02	-17.15	L1	GND
0.51	FINAL	---	18.01	46.00	-27.99	L1	GND
0.51	FINAL	36.63	---	56.00	-19.37	L1	GND
1.35	FINAL	30.47	---	56.00	-25.53	L1	GND
1.35	FINAL	---	15.09	46.00	-30.91	L1	GND
5.01	FINAL	24.78	---	60.00	-35.22	L1	GND
5.01	FINAL	---	12.68	50.00	-37.32	L1	GND
16.16	FINAL	---	10.81	50.00	-39.19	L1	GND
16.16	FINAL	14.91	---	60.00	-45.09	L1	GND

Table 7-178. AC Line Conducted Data with 802.11be(SU) CDD Primary – Ch.40 (L1) with AC/DC adapter

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 267 of 273

V 11.0 05/2025



Plot 7-493. AC Line Conducted Plot with 802.11be(SU) CDD Primary – Ch.40 (N), with AC/DC adapter


Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.17	FINAL	---	37.37	55.17	-17.80	N	GND
0.17	FINAL	53.84	---	65.17	-11.33	N	GND
0.25	FINAL	---	29.89	51.87	-21.98	N	GND
0.25	FINAL	47.12	---	61.87	-14.75	N	GND
0.51	FINAL	---	18.30	46.00	-27.70	N	GND
0.51	FINAL	38.08	---	56.00	-17.92	N	GND
1.33	FINAL	32.39	---	56.00	-23.61	N	GND
1.33	FINAL	---	14.79	46.00	-31.21	N	GND
5.01	FINAL	28.19	---	60.00	-31.81	N	GND
5.01	FINAL	---	17.40	50.00	-32.60	N	GND
16.16	FINAL	---	8.60	50.00	-41.40	N	GND
16.16	FINAL	14.33	---	60.00	-45.67	N	GND

Table 7-179. AC Line Conducted Data with 802.11be(SU) CDD Primary – Ch.40 (N), with AC/DC adapter

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 268 of 273

V 11.0 05/2025

7.8.2 CDD Diversity AC Line-Conducted Emissions Measurement



Plot 7-494. AC Line Conducted Plot with 802.11n CDD Diversity – Ch.40 (L1), with AC/DC adapter


Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.17	FINAL	---	31.90	55.17	-23.27	L1	GND
0.17	FINAL	48.35	---	65.17	-16.82	L1	GND
0.24	FINAL	---	27.72	52.10	-24.38	L1	GND
0.24	FINAL	43.17	---	62.10	-18.93	L1	GND
0.51	FINAL	---	17.84	46.00	-28.16	L1	GND
0.51	FINAL	36.09	---	56.00	-19.91	L1	GND
1.35	FINAL	30.22	---	56.00	-25.78	L1	GND
1.35	FINAL	---	14.89	46.00	-31.11	L1	GND
5.00	FINAL	25.46	---	60.00	-34.54	L1	GND
5.00	FINAL	---	13.48	50.00	-36.52	L1	GND
16.16	FINAL	---	11.25	50.00	-38.75	L1	GND
16.16	FINAL	15.28	---	60.00	-44.72	L1	GND

Table 7-180. AC Line Conducted Data with 802.11n CDD Diversity – Ch.40 (L1) with AC/DC adapter

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 269 of 273

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-495. AC Line Conducted Plot with 802.11n CDD Diversity – Ch.40 (N), with AC/DC adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	34.16	55.17	-21.01	N	GND
0.17	FINAL	50.23	---	65.17	-14.94	N	GND
0.24	FINAL	---	28.28	52.10	-23.82	N	GND
0.24	FINAL	44.09	---	62.10	-18.01	N	GND
0.51	FINAL	---	18.01	46.00	-27.99	N	GND
0.51	FINAL	37.08	---	56.00	-18.92	N	GND
1.35	FINAL	31.83	---	56.00	-24.17	N	GND
1.35	FINAL	---	15.95	46.00	-30.05	N	GND
5.00	FINAL	28.75	---	60.00	-31.25	N	GND
5.00	FINAL	---	18.42	50.00	-31.58	N	GND
16.16	FINAL	---	8.97	50.00	-41.03	N	GND
16.16	FINAL	14.66	---	60.00	-45.34	N	GND

Table 7-181. AC Line Conducted Data with 802.11n CDD Diversity – Ch.40 (N), with AC/DC adapter

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 270 of 273



Plot 7-496. AC Line Conducted Plot with 802.11be(SU) CDD Diversity – Ch.40 (L1), with AC/DC adapter


Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.17	FINAL	---	34.62	55.17	-20.55	L1	GND
0.17	FINAL	51.12	---	65.17	-14.05	L1	GND
0.24	FINAL	---	29.20	52.10	-22.90	L1	GND
0.24	FINAL	45.31	---	62.10	-16.79	L1	GND
0.51	FINAL	---	18.50	46.00	-27.50	L1	GND
0.51	FINAL	36.83	---	56.00	-19.17	L1	GND
1.35	FINAL	30.61	---	56.00	-25.39	L1	GND
1.35	FINAL	---	15.50	46.00	-30.50	L1	GND
5.00	FINAL	24.94	---	60.00	-35.06	L1	GND
5.00	FINAL	---	12.68	50.00	-37.32	L1	GND
16.18	FINAL	---	11.09	50.00	-38.91	L1	GND
16.18	FINAL	15.06	---	60.00	-44.94	L1	GND

Table 7-182. AC Line Conducted Data with 802.11be(SU) CDD Diversity – Ch.40 (L1) with AC/DC adapter

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 271 of 273

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-497. AC Line Conducted Plot with 802.11be(SU) CDD Diversity – Ch.40 (N), with AC/DC adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.17	FINAL	---	37.58	55.17	-17.59	N	GND
0.17	FINAL	54.16	---	65.17	-11.01	N	GND
0.25	FINAL	---	30.14	51.87	-21.73	N	GND
0.25	FINAL	47.38	---	61.87	-14.49	N	GND
0.51	FINAL	---	19.09	46.00	-26.91	N	GND
0.51	FINAL	38.41	---	56.00	-17.59	N	GND
1.35	FINAL	31.98	---	56.00	-24.02	N	GND
1.35	FINAL	---	16.26	46.00	-29.74	N	GND
5.01	FINAL	27.91	---	60.00	-32.09	N	GND
5.01	FINAL	---	17.08	50.00	-32.92	N	GND
16.18	FINAL	---	8.82	50.00	-41.18	N	GND
16.18	FINAL	14.52	---	60.00	-45.48	N	GND

Table 7-183. AC Line Conducted Data with 802.11be(SU) CDD Diversity – Ch.40 (N), with AC/DC adapter

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 272 of 273

V 11.0 05/2025

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device FCC ID: BCGA3461** and **IC: 579C-A3461** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-13-R4.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 273 of 273

V 11.0 05/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.