






Plot 7-75. Conducted Spurious Plot (WCDMA Ch. 4233)



Plot 7-76. Conducted Spurious Plot (WCDMA Ch. 4233)

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 57 of 113

V2.2 08/24/2023



Plot 7-77. Conducted Spurious Plot (WCDMA Ch. 4233)

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 58 of 113

7.4 Band Edge Emissions at Antenna Terminal

§2.1051, 22.917(a)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section. All ports were tested and only the worst case data was reported.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW $\geq$ 1% of the emission bandwidth
4. VBW $\geq$ 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq$ 2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. LTE Test Instrument & Measurement Setup




Figure 7-6. FR1 Test Instrument & Measurement Setup

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 59 of 113

V2.2 08/24/2023


Test Notes

1. Per 22.917(b), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
2. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 60 of 113


V2.2 08/24/2023

LTE Band 26



09:11:53 AM 09/30/2025

Plot 7-78. Lower BE Plot (LTE Band 26 – 1.4MHz QPSK – Full RB Configuration)




09:13:12 AM 09/30/2025

Plot 7-79. Upper BE Plot (LTE Band 26 – 1.4MHz QPSK – Full RB Configuration)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 61 of 113


V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



09:15:03 AM 09/30/2025

Plot 7-80. Lower BE Plot (LTE Band 26 - 3MHz QPSK – Full RB Configuration)



09:16:19 AM 09/30/2025


Plot 7-81. Upper BE Plot (LTE Band 26 - 3MHz QPSK – Full RB Configuration)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 62 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



09:18:15 AM 09/30/2025

Plot 7-82. Lower BE Plot (LTE Band 26 - 5MHz QPSK – Full RB Configuration)

Test Plot



09:19:30 AM 09/30/2025


Plot 7-83. Upper BE Plot (LTE Band 26 - 5MHz QPSK – Full RB Configuration)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 63 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



09:21:27 AM 09/30/2025

Plot 7-84. Lower BE Plot (LTE Band 26 - 10MHz QPSK – Full RB Configuration)

Test Plot



09:22:43 AM 09/30/2025


Plot 7-85. Upper BE Plot (LTE Band 26 - 10MHz QPSK – Full RB Configuration)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 64 of 113

V2.2 08/24/2023


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

LTE Band 5



08:29:54 AM 09/30/2025

Plot 7-86. Lower BE Plot (LTE Band 5 – 1.4MHz QPSK – Full RB Configuration)



08:31:13 AM 09/30/2025


Plot 7-87. Upper BE Plot (LTE Band 5 – 1.4MHz QPSK – Full RB Configuration)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 65 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



08:33:04 AM 09/30/2025

Plot 7-88. Lower BE Plot (LTE Band 5 - 3MHz QPSK – Full RB Configuration)

Test Plot



08:34:20 AM 09/30/2025


Plot 7-89. Upper BE Plot (LTE Band 5 - 3MHz QPSK – Full RB Configuration)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 66 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



08:36:15 AM 09/30/2025

Plot 7-90. Lower BE Plot (LTE Band 5 - 5MHz QPSK – Full RB Configuration)

Test Plot



08:37:32 AM 09/30/2025


Plot 7-91. Upper BE Plot (LTE Band 5 - 5MHz QPSK – Full RB Configuration)

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 67 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



08:39:27 AM 09/30/2025

Plot 7-92. Lower BE Plot (LTE Band 5 - 10MHz QPSK – Full RB Configuration)

Test Plot



08:40:48 AM 09/30/2025



Plot 7-93. Upper BE Plot (LTE Band 5 - 10MHz QPSK – Full RB Configuration)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 68 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

ULCA - LTE Band 5




FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 69 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


NR Band n26



FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 70 of 113

V2.2 08/24/2023


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



FCC ID: BCGA3462	element	PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 71 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-100. Lower BE Plot (NR Band n26 DFT-s-OFDM $\pi/2$ BPSK – 15.0MHz - Full RB)





Plot 7-101. Upper BE Plot (NR Band n26 DFT-s-OFDM QPSK – 15.0MHz - Full RB)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 72 of 113


V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



FCC ID: BCGA3462	element	PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 73 of 113


NR Band n5



FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 74 of 113

V2.2 08/24/2023



Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



FCC ID: BCGA3462	element	PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 75 of 113

V2.2 08/24/2023



Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 76 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.





FCC ID: BCGA3462	element	PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 77 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

WCDMA Cell



FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 78 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.5 Radiated Power (ERP)

§22.913(a)(5)

Test Overview

Effective Radiated Power (ERP) measurements are calculated by adding highest antenna gain to maximum measured conducted output power. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1

ANSI C63.26-2015 – Section 5.2.5.5

Test Settings

The relevant equation for determining the ERP or EIRP from the conducted RF output power measured is:

$$ERP = P_{Meas} - LC + GT$$

Where:

ERP = Effective Radiated Power, respectively (expressed in the same units as P_{Meas} , typically dBW or dBm)

P_{Meas} = measured transmitter output power or PSD, in dBW or dBm

LC = signal attenuation in the connecting cable between the transmitter and antenna in dB

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. LTE Test Instrument & Measurement Setup




Figure 7-8. FR1 Test Instrument & Measurement Setup

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 79 of 113

V2.2 08/24/2023

Test Notes:

1. The EUT was tested in all possible test configurations. The worst case emissions are reported with the EUT modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
2. This unit was tested with its standard battery.
3. The Level (dBm) readings in the table were taken with a correction table loaded into the base station simulator. The correction table was used to account for the signal attenuation in the connecting cable between the transmitter and antenna.
4. Uplink carrier aggregation for LTE B5 is only supported in this EUT while operating in Power Class 3.
5. Conducted power measurements were evaluated for the two contiguous channels using various combinations of RB size, RB offset, modulation, and channel bandwidth. Channel bandwidth data is shown in the tables below based only on the channel bandwidths that were supported in this device.
6. The Ant. Gains (GT) are listed in dBi.
7. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 80 of 113

V2.2 08/24/2023

7.5.1 Antenna 4 – ERP

LTE Band 26

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
1.4 MHz	QPSK	824.7	-2.30	1 / 3	25.23	20.78	0.120	38.45	-17.67
		836.5	-2.30	1 / 3	25.23	20.78	0.120	38.45	-17.67
		848.3	-2.30	1 / 3	25.38	20.93	0.124	38.45	-17.52
	16-QAM	848.3	-2.30	1 / 3	24.74	20.29	0.107	38.45	-18.16
	64-QAM	848.3	-2.30	1 / 3	23.52	19.07	0.081	38.45	-19.38
	256-QAM	836.5	-2.30	6 / 0	20.90	16.45	0.044	38.45	-22.00
3 MHz	QPSK	825.5	-2.30	1 / 7	25.23	20.78	0.120	38.45	-17.67
		836.5	-2.30	1 / 7	25.28	20.83	0.121	38.45	-17.62
		847.5	-2.30	1 / 7	25.34	20.89	0.123	38.45	-17.56
	16-QAM	847.5	-2.30	1 / 7	24.77	20.32	0.108	38.45	-18.13
	64-QAM	847.5	-2.30	1 / 7	23.62	19.17	0.083	38.45	-19.28
	256-QAM	847.5	-2.30	15 / 0	20.92	16.47	0.044	38.45	-21.98
5 MHz	QPSK	826.5	-2.30	1 / 24	25.19	20.74	0.119	38.45	-17.71
		836.5	-2.30	1 / 24	25.27	20.82	0.121	38.45	-17.63
		846.5	-2.30	1 / 0	25.05	20.60	0.115	38.45	-17.85
	16-QAM	836.5	-2.30	1 / 24	24.60	20.15	0.104	38.45	-18.30
	64-QAM	836.5	-2.30	1 / 24	23.52	19.07	0.081	38.45	-19.38
	256-QAM	846.5	-2.30	25 / 0	20.52	16.07	0.040	38.45	-22.38
10 MHz	QPSK	829.0	-2.30	1 / 49	25.03	20.58	0.114	38.45	-17.87
		836.5	-2.30	1 / 49	25.19	20.74	0.119	38.45	-17.71
		844.0	-2.30	1 / 25	25.04	20.59	0.115	38.45	-17.86
	16-QAM	836.5	-2.30	1 / 49	24.59	20.14	0.103	38.45	-18.31
	64-QAM	829.0	-2.30	1 / 49	23.40	18.95	0.079	38.45	-19.50
	256-QAM	844.0	-2.30	50 / 0	20.57	16.12	0.041	38.45	-22.33

Table 7-2. Antenna 4 ERP Data (LTE Band 26)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device		Page 81 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

LTE Band 5

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
1.4 MHz	QPSK	824.7	-2.30	1 / 3	25.25	20.80	0.120	38.45	-17.65
		836.5	-2.30	1 / 3	25.41	20.96	0.125	38.45	-17.49
		848.3	-2.30	1 / 3	25.31	20.86	0.122	38.45	-17.59
	16-QAM	848.3	-2.30	1 / 3	24.70	20.25	0.106	38.45	-18.20
	64-QAM	848.3	-2.30	1 / 3	23.60	19.15	0.082	38.45	-19.30
	256-QAM	824.7	-2.30	6 / 0	22.03	17.58	0.057	38.45	-20.87
3 MHz	QPSK	825.5	-2.30	1 / 7	25.18	20.73	0.118	38.45	-17.72
		836.5	-2.30	1 / 7	25.23	20.78	0.120	38.45	-17.67
		847.5	-2.30	1 / 7	25.30	20.85	0.122	38.45	-17.60
	16-QAM	847.5	-2.30	1 / 7	24.75	20.30	0.107	38.45	-18.15
	64-QAM	847.5	-2.30	1 / 7	23.58	19.13	0.082	38.45	-19.32
	256-QAM	825.5	-2.30	15 / 0	21.96	17.51	0.056	38.45	-20.94
5 MHz	QPSK	826.5	-2.30	1 / 0	25.21	20.76	0.119	38.45	-17.69
		836.5	-2.30	1 / 24	25.35	20.90	0.123	38.45	-17.55
		846.5	-2.30	1 / 12	25.14	20.69	0.117	38.45	-17.76
	16-QAM	836.5	-2.30	1 / 24	24.76	20.31	0.107	38.45	-18.14
	64-QAM	836.5	-2.30	1 / 24	23.60	19.15	0.082	38.45	-19.30
	256-QAM	846.5	-2.30	25 / 0	20.58	16.13	0.041	38.45	-22.32
10 MHz	QPSK	829.0	-2.30	1 / 49	25.15	20.70	0.117	38.45	-17.75
		836.5	-2.30	1 / 49	25.19	20.74	0.119	38.45	-17.71
		844.0	-2.30	1 / 25	25.19	20.74	0.119	38.45	-17.71
	16-QAM	836.5	-2.30	1 / 49	24.60	20.15	0.104	38.45	-18.30
	64-QAM	844.0	-2.30	1 / 0	23.49	19.04	0.080	38.45	-19.41
	256-QAM	844.0	-2.30	50 / 0	20.66	16.21	0.042	38.45	-22.24

Table 7-3. Antenna 4 ERP Data (LTE Band 5)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 82 of 113

V2.2 08/24/2023

ULCA - LTE Band 5

Power State	Band	Bandwidth (PCC + SCC)	PCC					SCC					ULCA Tx. Power [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
			Modulation	UL Channel	UL Frequency	UL # RB	UL RB Offset	Modulation	UL Channel	UL Frequency	UL # RB	UL RB Offset						
Max	LTE B5	10MHz + 10MHz	QPSK	20450	829.0	1	49	QPSK	20549	838.9	1	0	25.32	-2.30	20.87	0.122	38.45	-17.58
				20475	831.5	1	49		20574	841.4	1	0	25.43	-2.30	20.98	0.125	38.45	-17.47
				20600	844.0	1	0		20501	834.1	1	49	25.38	-2.30	20.93	0.124	38.45	-17.52
				20475	831.5	50	0		20574	841.4	50	0	24.77	-2.30	20.32	0.108	38.45	-18.13
			16-QAM	20475	831.5	50	0	16-QAM	20574	841.4	50	0	23.86	-2.30	19.41	0.087	38.45	-19.04
			64-QAM	20475	831.5	50	0	64-QAM	20574	841.4	50	0	22.84	-2.30	18.39	0.069	38.45	-20.06
			256-QAM	20475	831.5	50	0	256-QAM	20574	841.4	50	0	21.95	-2.30	17.50	0.056	38.45	-20.95

Table 7-4. Antenna 4 ERP Data (ULCA LTE Band 5)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 83 of 113

V2.2 08/24/2023

NR Band n26

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
5 MHz	$\pi/2$ BPSK	826.5	-2.30	25 / 0	25.26	20.81	0.121	38.45	-17.64
		836.5	-2.30	25 / 0	25.18	20.73	0.118	38.45	-17.72
		846.5	-2.30	25 / 0	25.10	20.65	0.116	38.45	-17.80
	QPSK	826.5	-2.30	1 / 12	25.26	20.81	0.121	38.45	-17.64
		836.5	-2.30	1 / 1	25.19	20.74	0.119	38.45	-17.71
		846.5	-2.30	1 / 1	25.03	20.58	0.114	38.45	-17.87
	16-QAM	846.5	-2.30	1 / 23	24.01	19.56	0.090	38.45	-18.89
	64-QAM	826.5	-2.30	25 / 0	23.28	18.83	0.076	38.45	-19.62
	256-QAM	826.5	-2.30	25 / 0	21.29	16.84	0.048	38.45	-21.61
10 MHz	$\pi/2$ BPSK	829.0	-2.30	50 / 0	25.28	20.83	0.121	38.45	-17.62
		836.5	-2.30	50 / 0	25.31	20.86	0.122	38.45	-17.59
		844.0	-2.30	50 / 0	25.22	20.77	0.119	38.45	-17.68
	QPSK	829.0	-2.30	1 / 50	25.23	20.78	0.120	38.45	-17.67
		836.5	-2.30	1 / 1	25.20	20.75	0.119	38.45	-17.70
		844.0	-2.30	1 / 1	25.18	20.73	0.118	38.45	-17.72
	16-QAM	844.0	-2.30	1 / 25	24.18	19.73	0.094	38.45	-18.72
	64-QAM	829.0	-2.30	50 / 0	23.26	18.81	0.076	38.45	-19.64
	256-QAM	829.0	-2.30	50 / 0	21.30	16.85	0.048	38.45	-21.60
15 MHz	$\pi/2$ BPSK	831.5	-2.30	75 / 0	25.13	20.68	0.117	38.45	-17.77
		836.5	-2.30	75 / 0	25.15	20.70	0.117	38.45	-17.75
		841.5	-2.30	75 / 0	25.13	20.68	0.117	38.45	-17.77
	QPSK	831.5	-2.30	1 / 36	25.15	20.70	0.117	38.45	-17.75
		836.5	-2.30	1 / 77	25.15	20.70	0.117	38.45	-17.75
		841.5	-2.30	1 / 77	25.19	20.74	0.119	38.45	-17.71
	16-QAM	841.5	-2.30	1 / 77	23.98	19.53	0.090	38.45	-18.92
	64-QAM	831.5	-2.30	75 / 0	23.23	18.78	0.076	38.45	-19.67
	256-QAM	831.5	-2.30	75 / 0	21.18	16.73	0.047	38.45	-21.72
20 MHz	$\pi/2$ BPSK	834.0	-2.30	100 / 0	25.29	20.84	0.121	38.45	-17.61
		836.5	-2.30	100 / 0	25.15	20.70	0.117	38.45	-17.75
		839.0	-2.30	100 / 0	25.17	20.72	0.118	38.45	-17.73
	QPSK	834.0	-2.30	1 / 104	25.18	20.73	0.118	38.45	-17.72
		836.5	-2.30	1 / 1	25.10	20.65	0.116	38.45	-17.80
		839.0	-2.30	1 / 1	25.16	20.71	0.118	38.45	-17.74
	16-QAM	834.0	-2.30	1 / 1	24.02	19.57	0.091	38.45	-18.88
	64-QAM	834.0	-2.30	100 / 0	23.25	18.80	0.076	38.45	-19.65
	256-QAM	836.5	-2.30	100 / 0	21.17	16.72	0.047	38.45	-21.73

Table 7-5. Antenna 4 ERP Data (NR Band n26)

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 84 of 113

V2.2 08/24/2023

NR Band n5

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
5 MHz	$\pi/2$ BPSK	826.5	-2.30	25 / 0	25.09	20.64	0.116	38.45	-17.81
		836.5	-2.30	25 / 0	25.14	20.69	0.117	38.45	-17.76
		846.5	-2.30	25 / 0	25.07	20.62	0.115	38.45	-17.83
	QPSK	826.5	-2.30	1 / 12	25.18	20.73	0.118	38.45	-17.72
		836.5	-2.30	1 / 1	25.06	20.61	0.115	38.45	-17.84
		846.5	-2.30	1 / 12	25.06	20.61	0.115	38.45	-17.84
	16-QAM	826.5	-2.30	1 / 23	23.97	19.52	0.090	38.45	-18.93
	64-QAM	826.5	-2.30	25 / 0	23.16	18.71	0.074	38.45	-19.74
	256-QAM	826.5	-2.30	25 / 0	21.14	16.69	0.047	38.45	-21.76
10 MHz	$\pi/2$ BPSK	829.0	-2.30	50 / 0	25.15	20.70	0.117	38.45	-17.75
		836.5	-2.30	50 / 0	25.13	20.68	0.117	38.45	-17.77
		844.0	-2.30	50 / 0	25.07	20.62	0.115	38.45	-17.83
	QPSK	829.0	-2.30	1 / 50	25.16	20.71	0.118	38.45	-17.74
		836.5	-2.30	1 / 1	25.11	20.66	0.116	38.45	-17.79
		844.0	-2.30	1 / 1	25.10	20.65	0.116	38.45	-17.80
	16-QAM	844.0	-2.30	1 / 25	24.01	19.56	0.090	38.45	-18.89
	64-QAM	829.0	-2.30	50 / 0	23.22	18.77	0.075	38.45	-19.68
	256-QAM	829.0	-2.30	50 / 0	21.25	16.80	0.048	38.45	-21.65
15 MHz	$\pi/2$ BPSK	831.5	-2.30	75 / 0	25.12	20.67	0.117	38.45	-17.78
		836.5	-2.30	75 / 0	25.11	20.66	0.116	38.45	-17.79
		841.5	-2.30	75 / 0	25.15	20.70	0.117	38.45	-17.75
	QPSK	831.5	-2.30	1 / 36	25.06	20.61	0.115	38.45	-17.84
		836.5	-2.30	1 / 1	25.10	20.65	0.116	38.45	-17.80
		841.5	-2.30	1 / 1	25.09	20.64	0.116	38.45	-17.81
	16-QAM	836.5	-2.30	1 / 77	24.05	19.60	0.091	38.45	-18.85
	64-QAM	831.5	-2.30	75 / 0	23.15	18.70	0.074	38.45	-19.75
	256-QAM	831.5	-2.30	75 / 0	21.11	16.66	0.046	38.45	-21.79
20 MHz	$\pi/2$ BPSK	834.0	-2.30	100 / 0	25.06	20.61	0.115	38.45	-17.84
		836.5	-2.30	100 / 0	25.07	20.62	0.115	38.45	-17.83
		839.0	-2.30	100 / 0	25.08	20.63	0.116	38.45	-17.82
	QPSK	834.0	-2.30	1 / 1	25.03	20.58	0.114	38.45	-17.87
		836.5	-2.30	1 / 1	25.22	20.77	0.119	38.45	-17.68
		839.0	-2.30	1 / 1	25.11	20.66	0.116	38.45	-17.79
	16-QAM	836.5	-2.30	1 / 1	23.97	19.52	0.090	38.45	-18.93
	64-QAM	836.5	-2.30	100 / 0	23.15	18.70	0.074	38.45	-19.75
	256-QAM	836.5	-2.30	100 / 0	21.09	16.64	0.046	38.45	-21.81

Table 7-6. Antenna 4 ERP Data (NR Band n5)

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 85 of 113

V2.2 08/24/2023

WCDMA Cell

Frequency [MHz]	Mode	Conducted Power [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
826.40	WCDMA850	25.45	-2.30	21.00	0.126	38.45	-17.45
836.60	WCDMA850	25.52	-2.30	21.07	0.128	38.45	-17.38
846.60	WCDMA850	25.43	-2.30	20.98	0.125	38.45	-17.47

Table 7-7. Antenna 4 ERP Data (WCDMA Cell)

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 86 of 113

V2.2 08/24/2023

7.5.2 Antenna 2 – ERP

LTE Band 26

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
1.4 MHz	QPSK	824.7	-0.40	1 / 3	24.80	22.25	0.168	38.45	-16.20
		836.5	-0.40	1 / 3	24.76	22.21	0.166	38.45	-16.24
		848.3	-0.40	1 / 3	24.60	22.05	0.160	38.45	-16.40
	16-QAM	836.5	-0.40	1 / 3	23.99	21.44	0.139	38.45	-17.01
	64-QAM	824.7	-0.40	1 / 3	23.03	20.48	0.112	38.45	-17.97
	256-QAM	836.5	-0.40	6 / 0	20.40	17.85	0.061	38.45	-20.60
3 MHz	QPSK	825.5	-0.40	1 / 7	24.62	22.07	0.161	38.45	-16.38
		836.5	-0.40	1 / 7	24.77	22.22	0.167	38.45	-16.23
		847.5	-0.40	1 / 7	24.69	22.14	0.164	38.45	-16.31
	16-QAM	836.5	-0.40	1 / 7	24.26	21.71	0.148	38.45	-16.74
	64-QAM	825.5	-0.40	1 / 7	22.94	20.39	0.109	38.45	-18.06
	256-QAM	836.5	-0.40	15 / 0	20.38	17.83	0.061	38.45	-20.62
5 MHz	QPSK	826.5	-0.40	1 / 0	24.77	22.22	0.167	38.45	-16.23
		836.5	-0.40	1 / 24	24.81	22.26	0.168	38.45	-16.19
		846.5	-0.40	1 / 12	24.60	22.05	0.160	38.45	-16.40
	16-QAM	836.5	-0.40	1 / 24	24.28	21.73	0.149	38.45	-16.72
	64-QAM	836.5	-0.40	1 / 12	23.29	20.74	0.119	38.45	-17.71
	256-QAM	836.5	-0.40	25 / 0	20.25	17.70	0.059	38.45	-20.75
10 MHz	QPSK	829.0	-0.40	1 / 49	24.64	22.09	0.162	38.45	-16.36
		836.5	-0.40	1 / 25	24.76	22.21	0.166	38.45	-16.24
		844.0	-0.40	1 / 25	24.72	22.17	0.165	38.45	-16.28
	16-QAM	844.0	-0.40	1 / 25	24.09	21.54	0.143	38.45	-16.91
	64-QAM	829.0	-0.40	1 / 49	23.16	20.61	0.115	38.45	-17.84
	256-QAM	836.5	-0.40	50 / 0	20.31	17.76	0.060	38.45	-20.69

Table 7-8. Antenna 2 ERP Data (LTE Band 26)

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 87 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

LTE Band 5

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
1.4 MHz	QPSK	824.7	-0.40	1 / 3	24.83	22.28	0.169	38.45	-16.17
		836.5	-0.40	1 / 3	24.77	22.22	0.167	38.45	-16.23
		848.3	-0.40	1 / 3	24.69	22.14	0.164	38.45	-16.31
	16-QAM	836.5	-0.40	1 / 3	24.14	21.59	0.144	38.45	-16.86
	64-QAM	836.5	-0.40	1 / 3	23.00	20.45	0.111	38.45	-18.00
	256-QAM	836.5	-0.40	6 / 0	20.41	17.86	0.061	38.45	-20.59
3 MHz	QPSK	825.5	-0.40	1 / 7	24.63	22.08	0.161	38.45	-16.37
		836.5	-0.40	1 / 7	24.78	22.23	0.167	38.45	-16.22
		847.5	-0.40	1 / 7	24.69	22.14	0.164	38.45	-16.31
	16-QAM	836.5	-0.40	1 / 7	24.18	21.63	0.146	38.45	-16.82
	64-QAM	847.5	-0.40	1 / 7	22.97	20.42	0.110	38.45	-18.03
	256-QAM	836.5	-0.40	15 / 0	20.41	17.86	0.061	38.45	-20.59
5 MHz	QPSK	826.5	-0.40	1 / 0	24.76	22.21	0.166	38.45	-16.24
		836.5	-0.40	1 / 24	24.90	22.35	0.172	38.45	-16.10
		846.5	-0.40	1 / 24	24.60	22.05	0.160	38.45	-16.40
	16-QAM	836.5	-0.40	1 / 0	24.23	21.68	0.147	38.45	-16.77
	64-QAM	836.5	-0.40	1 / 12	23.18	20.63	0.116	38.45	-17.82
	256-QAM	836.5	-0.40	25 / 0	20.27	17.72	0.059	38.45	-20.73
10 MHz	QPSK	829.0	-0.40	1 / 49	24.64	22.09	0.162	38.45	-16.36
		836.5	-0.40	1 / 25	24.75	22.20	0.166	38.45	-16.25
		844.0	-0.40	1 / 25	24.70	22.15	0.164	38.45	-16.30
	16-QAM	836.5	-0.40	1 / 25	24.20	21.65	0.146	38.45	-16.80
	64-QAM	829.0	-0.40	1 / 49	22.99	20.44	0.111	38.45	-18.01
	256-QAM	836.5	-0.40	50 / 0	20.30	17.75	0.060	38.45	-20.70

Table 7-9. Antenna 2 ERP Data (LTE Band 5)

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 88 of 113

V2.2 08/24/2023

ULCA - LTE Band 5

Power State	Band	Bandwidth (PCC + SCC)	PCC				SCC				ULCATx. Power [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]		
			Modulation	UL Channel	UL Frequency	UL # RB	UL RB Offset	Modulation	UL Channel	UL Frequency							UL # RB	UL RB Offset
Max	LTE B5	10MHz + 10MHz	QPSK	20450	829.0	1	49	QPSK	20549	838.9	1	0	24.80	-0.40	22.25	0.168	38.45	-16.20
				20475	831.5	1	49		20574	841.4	1	0	24.93	-0.40	22.38	0.173	38.45	-16.07
				20600	844.0	1	0		20501	834.1	1	49	24.85	-0.40	22.30	0.170	38.45	-16.15
			QPSK	20475	831.5	50	0	QPSK	20574	841.4	50	0	24.27	-0.40	21.72	0.149	38.45	-16.73
			16-QAM	20475	831.5	50	0	16-QAM	20574	841.4	50	0	23.25	-0.40	20.70	0.117	38.45	-17.75
			64-QAM	20475	831.5	50	0	64-QAM	20574	841.4	50	0	22.24	-0.40	19.69	0.093	38.45	-18.76
			256-QAM	20475	831.5	50	0	256-QAM	20574	841.4	50	0	20.24	-0.40	17.69	0.059	38.45	-20.76

Table 7-10. Antenna 2 ERP Data (ULCA LTE Band 5)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 89 of 113

V2.2 08/24/2023

NR Band n26

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
5 MHz	$\pi/2$ BPSK	826.5	-0.40	25 / 0	24.87	22.32	0.171	38.45	-16.13
		836.5	-0.40	25 / 0	24.77	22.22	0.167	38.45	-16.23
		846.5	-0.40	25 / 0	24.72	22.17	0.165	38.45	-16.28
	QPSK	826.5	-0.40	1 / 23	24.81	22.26	0.168	38.45	-16.19
		836.5	-0.40	1 / 23	24.89	22.34	0.171	38.45	-16.11
		846.5	-0.40	1 / 1	24.65	22.10	0.162	38.45	-16.35
	16-QAM	826.5	-0.40	1 / 23	23.62	21.07	0.128	38.45	-17.38
	64-QAM	836.5	-0.40	25 / 0	22.88	20.33	0.108	38.45	-18.12
	256-QAM	836.5	-0.40	25 / 0	20.86	18.31	0.068	38.45	-20.14
10 MHz	$\pi/2$ BPSK	829.0	-0.40	50 / 0	24.83	22.28	0.169	38.45	-16.17
		836.5	-0.40	50 / 0	24.80	22.25	0.168	38.45	-16.20
		844.0	-0.40	50 / 0	24.82	22.27	0.169	38.45	-16.18
	QPSK	829.0	-0.40	1 / 50	24.84	22.29	0.169	38.45	-16.16
		836.5	-0.40	1 / 1	24.79	22.24	0.167	38.45	-16.21
		844.0	-0.40	1 / 1	24.68	22.13	0.163	38.45	-16.32
	16-QAM	844.0	-0.40	1 / 1	23.63	21.08	0.128	38.45	-17.37
	64-QAM	829.0	-0.40	50 / 0	22.84	20.29	0.107	38.45	-18.16
	256-QAM	829.0	-0.40	50 / 0	20.92	18.37	0.069	38.45	-20.08
15 MHz	$\pi/2$ BPSK	831.5	-0.40	75 / 0	24.76	22.21	0.166	38.45	-16.24
		836.5	-0.40	75 / 0	24.69	22.14	0.164	38.45	-16.31
		841.5	-0.40	75 / 0	24.73	22.18	0.165	38.45	-16.27
	QPSK	831.5	-0.40	1 / 77	24.80	22.25	0.168	38.45	-16.20
		836.5	-0.40	1 / 1	24.75	22.20	0.166	38.45	-16.25
		841.5	-0.40	1 / 77	24.70	22.15	0.164	38.45	-16.30
	16-QAM	831.5	-0.40	1 / 77	23.78	21.23	0.133	38.45	-17.22
	64-QAM	831.5	-0.40	75 / 0	22.76	20.21	0.105	38.45	-18.24
	256-QAM	831.5	-0.40	75 / 0	20.81	18.26	0.067	38.45	-20.19
20 MHz	$\pi/2$ BPSK	834.0	-0.40	100 / 0	24.73	22.18	0.165	38.45	-16.27
		836.5	-0.40	100 / 0	24.75	22.20	0.166	38.45	-16.25
		839.0	-0.40	100 / 0	24.73	22.18	0.165	38.45	-16.27
	QPSK	834.0	-0.40	1 / 104	24.76	22.21	0.166	38.45	-16.24
		836.5	-0.40	1 / 1	24.75	22.20	0.166	38.45	-16.25
		839.0	-0.40	1 / 1	24.68	22.13	0.163	38.45	-16.32
	16-QAM	834.0	-0.40	1 / 104	23.56	21.01	0.126	38.45	-17.44
	64-QAM	834.0	-0.40	100 / 0	22.78	20.23	0.105	38.45	-18.22
	256-QAM	839.0	-0.40	100 / 0	20.79	18.24	0.067	38.45	-20.21

Table 7-11. Antenna 2 ERP Data (NR Band n26)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 90 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

NR Band n5

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
5 MHz	$\pi/2$ BPSK	826.5	-0.40	25 / 0	24.85	22.30	0.170	38.45	-16.15
		836.5	-0.40	25 / 0	24.83	22.28	0.169	38.45	-16.17
		846.5	-0.40	25 / 0	24.77	22.22	0.167	38.45	-16.23
	QPSK	826.5	-0.40	1 / 23	24.75	22.20	0.166	38.45	-16.25
		836.5	-0.40	1 / 23	24.85	22.30	0.170	38.45	-16.15
		846.5	-0.40	1 / 12	24.67	22.12	0.163	38.45	-16.33
	16-QAM	836.5	-0.40	1 / 1	23.60	21.05	0.127	38.45	-17.40
	64-QAM	826.5	-0.40	25 / 0	22.85	20.30	0.107	38.45	-18.15
	256-QAM	846.5	-0.40	25 / 0	20.85	18.30	0.068	38.45	-20.15
10 MHz	$\pi/2$ BPSK	829.0	-0.40	50 / 0	24.89	22.34	0.171	38.45	-16.11
		836.5	-0.40	50 / 0	24.82	22.27	0.169	38.45	-16.18
		844.0	-0.40	50 / 0	24.83	22.28	0.169	38.45	-16.17
	QPSK	829.0	-0.40	1 / 50	24.87	22.32	0.171	38.45	-16.13
		836.5	-0.40	1 / 1	24.80	22.25	0.168	38.45	-16.20
		844.0	-0.40	1 / 1	24.74	22.19	0.166	38.45	-16.26
	16-QAM	829.0	-0.40	1 / 50	23.69	21.14	0.130	38.45	-17.31
	64-QAM	829.0	-0.40	50 / 0	22.86	20.31	0.107	38.45	-18.14
	256-QAM	829.0	-0.40	50 / 0	20.90	18.35	0.068	38.45	-20.10
15 MHz	$\pi/2$ BPSK	831.5	-0.40	75 / 0	24.74	22.19	0.166	38.45	-16.26
		836.5	-0.40	75 / 0	24.72	22.17	0.165	38.45	-16.28
		841.5	-0.40	75 / 0	24.69	22.14	0.164	38.45	-16.31
	QPSK	831.5	-0.40	1 / 36	24.69	22.14	0.164	38.45	-16.31
		836.5	-0.40	1 / 1	24.72	22.17	0.165	38.45	-16.28
		841.5	-0.40	1 / 1	24.64	22.09	0.162	38.45	-16.36
	16-QAM	841.5	-0.40	1 / 1	23.62	21.07	0.128	38.45	-17.38
	64-QAM	831.5	-0.40	75 / 0	22.82	20.27	0.106	38.45	-18.18
	256-QAM	831.5	-0.40	75 / 0	20.75	18.20	0.066	38.45	-20.25
20 MHz	$\pi/2$ BPSK	834.0	-0.40	100 / 0	24.75	22.20	0.166	38.45	-16.25
		836.5	-0.40	100 / 0	24.71	22.16	0.164	38.45	-16.29
		839.0	-0.40	100 / 0	24.77	22.22	0.167	38.45	-16.23
	QPSK	834.0	-0.40	1 / 104	24.76	22.21	0.166	38.45	-16.24
		836.5	-0.40	1 / 1	24.74	22.19	0.166	38.45	-16.26
		839.0	-0.40	1 / 1	24.76	22.21	0.166	38.45	-16.24
	16-QAM	834.0	-0.40	1 / 104	23.64	21.09	0.129	38.45	-17.36
	64-QAM	834.0	-0.40	100 / 0	22.86	20.31	0.107	38.45	-18.14
	256-QAM	834.0	-0.40	100 / 0	20.79	18.24	0.067	38.45	-20.21

Table 7-12. Antenna 2 ERP Data (NR Band n5)

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 91 of 113

V2.2 08/24/2023

WCDMA Cell

Frequency [MHz]	Mode	Conducted Power [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
826.40	WCDMA850	24.94	-0.40	22.39	0.173	38.45	-16.06
836.60	WCDMA850	25.01	-0.40	22.46	0.176	38.45	-15.99
846.60	WCDMA850	24.89	-0.40	22.34	0.171	38.45	-16.11

Table 7-13. Antenna 2 ERP Data (WCDMA Cell)

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 92 of 113

V2.2 08/24/2023

7.6 Radiated Spurious Emissions

§2.1053, 22.917(a)

Test Overview

Radiated spurious emissions measurements are performed using the field strength conversion method described in KDB 971168 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 93 of 113

V2.2 08/24/2023

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-9. Test Instrument & Measurement Setup < 1GHz




Figure 7-10. Test Instrument & Measurement Setup >1 GHz

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 94 of 113

V2.2 08/24/2023

Test Notes

1. Field strengths are calculated using the Measurement quantity conversions in KDB 971168 Section 5.8.4.
 - a. $E(\text{dB}\mu\text{V}/\text{m}) = \text{Measured amplitude level (dBm)} + 107 + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$
 - b. $\text{EIRP (dBm)} = E(\text{dB}\mu\text{V}/\text{m}) + 20\log D - 104.8$; where D is the measurement distance in meters.
2. This device employs UMTS technology with WCDMA (AMR/RMC) and HSDPA capabilities. The EUT was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1".
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
6. D is the measurement test distance and emissions 1-18GHz were measured at a 3 meters test distance.
7. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
8. ULCA spurious emissions measurements were evaluated for the two contiguous channels using various combinations of RB size, RB offset, modulation, and channel bandwidth. Channel bandwidth data is shown in the tables below based only on the channel bandwidths that were supported in this device.
9. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.
10. Spurious emission in EN-DC Operating mode with Sub 6GHz NR carrier as well as an LTE carrier (anchor) has been checked and was found to not to be the worst case.
11. Uplink carrier aggregation inter-band emission was investigated and found to not be the worst case.
12. Pre-scan plots have been reported for the highest power antenna while measurements have been reported for all antennas.

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 95 of 113

V2.2 08/24/2023

7.6.1 Antenna 4 – Radiated Spurious Emission Measurements

LTE Band 26/5

Bandwidth (MHz):	10
Frequency (MHz):	829.0
RB / Offset:	1 / 24

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1658.0	H	-	-	-77.37	-2.29	27.33	-67.92	-13.00	-54.92
2487.0	H	-	-	-77.87	2.09	31.23	-64.03	-13.00	-51.03
3316.0	H	-	-	-78.72	3.97	32.25	-63.01	-13.00	-50.01

Table 7-14. Antenna 4 Radiated Spurious Data (LTE Band 26/5 – Low Channel)

Bandwidth (MHz):	10
Frequency (MHz):	836.5
RB / Offset:	1 / 24

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1673.0	H	-	-	-77.17	-2.29	27.54	-67.72	-13.00	-54.72
2509.5	H	-	-	-77.81	1.99	31.18	-64.08	-13.00	-51.08
3346.0	H	-	-	-78.64	3.97	32.33	-62.93	-13.00	-49.93

Table 7-15. Antenna 4 Radiated Spurious Data (LTE Band 26/5 – Mid Channel)

Bandwidth (MHz):	10
Frequency (MHz):	844.0
RB / Offset:	1 / 24

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1688.0	H	251	166	-71.97	-2.29	32.74	-62.52	-13.00	-49.52
2532.0	V	-	-	-77.94	2.08	31.14	-64.12	-13.00	-51.12
3376.0	H	-	-	-78.62	3.72	32.10	-63.16	-13.00	-50.16
4220.0	H	-	-	-79.48	5.61	33.12	-62.13	-13.00	-49.13

Table 7-16. Antenna 4 Radiated Spurious Data (LTE Band 26/5 – High Channel)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 96 of 113

V2.2 08/24/2023

ULCA LTE Band 5

PCC Bandwidth (MHz):	10
PCC Frequency (MHz):	829.0
PCC RB / Offset:	1 / 49
SCC Bandwidth (MHz):	10
SCC Frequency (MHz):	838.9
SCC RB / Offset:	1 / 0

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1658.0	H	-	-	-76.83	-3.26	26.91	-68.35	-13.00	-55.35
2487.0	H	-	-	-77.37	1.32	30.94	-64.31	-13.00	-51.31
3316.0	V	-	-	-78.12	3.97	32.84	-62.41	-13.00	-49.41

Table 7-17. Antenna 4 Radiated Spurious Data (ULCA LTE Band 5 – Low Channel)

PCC Bandwidth (MHz):	10
PCC Frequency (MHz):	831.5
PCC RB / Offset:	1 / 49
SCC Bandwidth (MHz):	10
SCC Frequency (MHz):	841.4
SCC RB / Offset:	1 / 0

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1663.0	H	-	-	-76.81	-3.26	26.93	-68.32	-13.00	-55.32
2494.5	V	-	-	-77.75	1.59	30.84	-64.42	-13.00	-51.42
3326.0	H	-	-	-78.15	3.07	31.92	-63.34	-13.00	-50.34

Table 7-18. Antenna 4 Radiated Spurious Data (ULCA LTE Band 5 – Mid Channel)

PCC Bandwidth (MHz):	10
PCC Frequency (MHz):	844.0
PCC RB / Offset:	1 / 0
SCC Bandwidth (MHz):	10
SCC Frequency (MHz):	834.1
SCC RB / Offset:	1 / 49

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1688.0	H	-	-	-77.61	-2.41	26.98	-68.28	-13.00	-55.28
2532.0	H	-	-	-77.61	1.59	30.98	-64.28	-13.00	-51.28
3376.0	V	-	-	-78.52	3.16	31.64	-63.61	-13.00	-50.61

Table 7-19. Antenna 4 Radiated Spurious Data (ULCA LTE Band 5 – High Channel)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT						Approved by: Technical Manager	
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device						Page 97 of 113	

V2.2 08/24/2023

NR Band n26/n5

Bandwidth (MHz):	20
Frequency (MHz):	834.0
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1668.0	H	-	-	-75.55	-2.33	29.12	-66.14	-13.00	-53.14
2502.0	H	-	-	-77.94	1.99	31.06	-64.20	-13.00	-51.20
3336.0	H	-	-	-78.70	3.97	32.27	-62.99	-13.00	-49.99

Table 7-20. Antenna 4 Radiated Spurious Data (NR Band n26/n5 – Low Channel)

Bandwidth (MHz):	20
Frequency (MHz):	836.5
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1673.0	H	-	-	-76.89	-2.33	27.78	-67.48	-13.00	-54.48
2509.5	V	-	-	-78.03	1.99	30.97	-64.29	-13.00	-51.29
3346.0	V	-	-	-78.91	3.97	32.06	-63.20	-13.00	-50.20

Table 7-21. Antenna 4 Radiated Spurious Data (NR Band n26/n5 – Mid Channel)

Bandwidth (MHz):	20
Frequency (MHz):	839.0
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1678.0	H	254	339	-75.28	-2.33	29.39	-65.87	-13.00	-52.87
2517.0	H	-	-	-77.83	1.99	31.16	-64.10	-13.00	-51.10
3356.0	H	-	-	-78.70	3.72	32.01	-63.25	-13.00	-50.25
4195.0	V	-	-	-79.83	5.87	33.04	-62.22	-13.00	-49.22

Table 7-22. Antenna 4 Radiated Spurious Data (NR Band n26/n5 – High Channel)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 98 of 113

V2.2 08/24/2023

WCDMA Cell

Mode:	WCDMA RMC
Channel:	4132
Frequency (MHz):	826.4

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1652.8	V	-	-	-68.22	-2.32	36.46	-58.80	-13.00	-45.80
2479.2	H	-	-	-64.19	2.00	44.81	-50.45	-13.00	-37.45
3305.6	V	-	-	-63.03	3.85	47.82	-47.44	-13.00	-34.44

Table 7-23. Antenna 4 Radiated Spurious Data (WCDMA Cell – Low Channel)

Mode:	WCDMA RMC
Channel:	4183
Frequency (MHz):	836.6

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1673.2	V	-	-	-67.59	-2.01	37.40	-57.86	-13.00	-44.86
2509.8	V	-	-	-64.30	2.02	44.72	-50.54	-13.00	-37.54
3346.4	H	-	-	-63.02	4.07	48.05	-47.21	-13.00	-34.21

Table 7-24. Antenna 4 Radiated Spurious Data (WCDMA Cell – Mid Channel)

Mode:	WCDMA RMC
Channel:	4233
Frequency (MHz):	846.6

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1693.2	H	268	181	-62.05	-1.70	43.25	-52.01	-13.00	-39.01
2539.8	V	-	-	-64.26	2.22	44.96	-50.30	-13.00	-37.30
3386.4	V	-	-	-63.31	3.57	47.26	-48.00	-13.00	-35.00
4233.0	H	-	-	-62.17	5.32	50.15	-45.11	-13.00	-32.11


Table 7-25. Antenna 4 Radiated Spurious Data (WCDMA Cell – High Channel)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device		Page 99 of 113


V2.2 08/24/2023

7.6.2 Antenna 2 – Radiated Spurious Emission Measurements

LTE Band 26/5



Plot 7-114. Antenna 2 Radiated Spurious Plot below 1GHz (LTE Band 26/5)



Plot 7-115. Antenna 2 Radiated Spurious Plot above 1GHz (LTE Band 26/5)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 100 of 113

V2.2 08/24/2023

Bandwidth (MHz):	10
Frequency (MHz):	829.0
RB / Offset:	1 / 24

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1658.0	H	-	-	-77.13	-2.37	27.50	-67.76	-13.00	-54.76
2487.0	V	-	-	-77.97	2.09	31.13	-64.13	-13.00	-51.13
3316.0	H	-	-	-78.80	3.97	32.17	-63.09	-13.00	-50.09

Table 7-26. Antenna 2 Radiated Spurious Data (LTE Band 26/5 – Low Channel)

Bandwidth (MHz):	10
Frequency (MHz):	836.5
RB / Offset:	1 / 24

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1673.0	H	-	-	-76.33	-2.33	28.33	-66.92	-13.00	-53.92
2509.5	H	-	-	-78.01	1.99	30.98	-64.28	-13.00	-51.28
3346.0	V	-	-	-78.78	3.97	32.19	-63.07	-13.00	-50.07

Table 7-27. Antenna 2 Radiated Spurious Data (LTE Band 26/5 – Mid Channel)


Bandwidth (MHz):	10
Frequency (MHz):	844.0
RB / Offset:	1 / 24

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1688.0	H	138	322	-74.53	-2.29	30.18	-65.08	-13.00	-52.08
2532.0	V	-	-	-77.91	2.08	31.16	-64.10	-13.00	-51.10
3376.0	H	-	-	-78.64	3.66	32.02	-63.23	-13.00	-50.23
4220.0	H	-	-	-79.49	5.61	33.12	-62.14	-13.00	-49.14


Table 7-28. Antenna 2 Radiated Spurious Data (LTE Band 26/5 – High Channel)

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 101 of 113

ULCA LTE Band 5



Plot 7-116. Antenna 2 Radiated Spurious Plot below 1GHz (ULCA LTE Band 5)



Plot 7-117. Antenna 2 Radiated Spurious Plot above 1GHz (ULCA LTE Band 5)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 102 of 113

V2.2 08/24/2023

PCC Bandwidth (MHz):	10
PCC Frequency (MHz):	829.0
PCC RB / Offset:	1 / 49
SCC Bandwidth (MHz):	10
SCC Frequency (MHz):	838.9
SCC RB / Offset:	1 / 0

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1658.0	V	-	-	-76.78	-3.26	26.97	-68.29	-13.00	-55.29
2487.0	H	-	-	-77.21	1.32	31.11	-64.15	-13.00	-51.15
3316.0	H	-	-	-78.48	3.04	31.56	-63.70	-13.00	-50.70

Table 7-29. Antenna 2 Radiated Spurious Data (ULCA LTE Band 5 – Low Channel)

PCC Bandwidth (MHz):	10
PCC Frequency (MHz):	831.5
PCC RB / Offset:	1 / 49
SCC Bandwidth (MHz):	10
SCC Frequency (MHz):	841.4
SCC RB / Offset:	1 / 0

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1663.0	H	-	-	-76.70	-3.26	27.04	-68.21	-13.00	-55.21
2494.5	V	-	-	-77.58	1.59	31.01	-64.25	-13.00	-51.25
3326.0	H	-	-	-78.71	3.32	31.61	-63.65	-13.00	-50.65

Table 7-30. Antenna 2 Radiated Spurious Data (ULCA LTE Band 5 – Mid Channel)

PCC Bandwidth (MHz):	10
PCC Frequency (MHz):	844.0
PCC RB / Offset:	1 / 0
SCC Bandwidth (MHz):	10
SCC Frequency (MHz):	834.1
SCC RB / Offset:	1 / 49


Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1688.0	H	-	-	-76.60	-3.26	27.15	-68.11	-13.00	-55.11
2532.0	V	-	-	-77.65	1.64	30.99	-64.27	-13.00	-51.27
3376.0	V	-	-	-78.55	3.32	31.77	-63.49	-13.00	-50.49

Table 7-31. Antenna 2 Radiated Spurious Data (ULCA LTE Band 5 – High Channel)


FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 103 of 113

V2.2 08/24/2023

NR Band n26/n5



Plot 7-118. Antenna 2 Radiated Spurious Plot below 1GHz (NR Band n26/n5)



Plot 7-119. Antenna 2 Radiated Spurious Plot above 1GHz (NR Band n26/n5)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 104 of 113

V2.2 08/24/2023

Bandwidth (MHz):	20
Frequency (MHz):	834.0
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1668.0	H	-	-	-77.12	-2.33	27.55	-67.71	-13.00	-54.71
2502.0	V	-	-	-77.95	1.99	31.04	-64.22	-13.00	-51.22
3336.0	V	-	-	-78.38	3.72	32.34	-62.92	-13.00	-49.92

Table 7-32. Antenna 2 Radiated Spurious Data (NR Band n26/n5 – Low Channel)

Bandwidth (MHz):	20
Frequency (MHz):	836.5
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1673.0	H	-	-	-77.02	-2.29	27.69	-67.57	-13.00	-54.57
2509.5	H	-	-	-78.02	1.99	30.97	-64.29	-13.00	-51.29
3346.0	H	-	-	-78.87	3.97	32.09	-63.17	-13.00	-50.17

Table 7-33. Antenna 2 Radiated Spurious Data (NR Band n26/n5 – Mid Channel)

Bandwidth (MHz):	20
Frequency (MHz):	839.0
RB / Offset:	1 / 50


Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1678.0	H	-	-	-76.63	-2.33	28.04	-67.22	-13.00	-54.22
2517.0	V	-	-	-78.00	1.99	30.99	-64.27	-13.00	-51.27
3356.0	V	-	-	-78.51	3.66	32.15	-63.11	-13.00	-50.11

Table 7-34. Antenna 2 Radiated Spurious Data (NR Band n26/n5 – High Channel)


FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 105 of 113

V2.2 08/24/2023

WCDMA Cell



Plot 7-120. Antenna 2 Radiated Spurious Plot below 1GHz (WCDMA Cell)



Plot 7-121. Antenna 2 Radiated Spurious Plot above 1GHz (WCDMA Cell)

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 106 of 113

V2.2 08/24/2023

Mode:	WCDMA RMC
Channel:	4132
Frequency (MHz):	826.4

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1652.8	H	-	-	-68.12	-2.32	36.56	-58.70	-13.00	-45.70
2479.2	H	-	-	-64.18	2.00	44.82	-50.44	-13.00	-37.44
3305.6	H	-	-	-63.17	3.85	47.68	-47.58	-13.00	-34.58

Table 7-35. Antenna 2 Radiated Spurious Data (WCDMA Cell – Low Channel)

Mode:	WCDMA RMC
Channel:	4183
Frequency (MHz):	836.6

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1673.2	H	-	-	-67.65	-2.01	37.34	-57.92	-13.00	-44.92
2509.8	V	-	-	-64.15	2.02	44.87	-50.39	-13.00	-37.39
3346.4	V	-	-	-62.85	4.07	48.22	-47.04	-13.00	-34.04

Table 7-36. Antenna 2 Radiated Spurious Data (WCDMA Cell – Mid Channel)

Mode:	WCDMA RMC
Channel:	4233
Frequency (MHz):	846.6

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1693.2	H	134	352	-62.64	-1.70	42.66	-52.60	-13.00	-39.60
2539.8	V	-	-	-64.13	2.22	45.09	-50.17	-13.00	-37.17
3386.4	V	-	-	-63.12	3.57	47.45	-47.81	-13.00	-34.81
4233.0	V	-	-	-62.09	5.32	50.23	-45.03	-13.00	-32.03

Table 7-37. Antenna 2 Radiated Spurious Data (WCDMA Cell – High Channel)

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 107 of 113

7.7 Frequency Stability / Temperature Variation

§2.1055, 22.355

Test Overview and Limit

Frequency Tolerance testing is performed in accordance with the guidelines of ANSI C63.26-2015 and TIA-603-E-2016. All port were tested and only the worst case data were reported. The Frequency Tolerance of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, the Frequency Tolerance of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Test Procedure Used

ANSI C63.26-2015

TIA-603-E-2016

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 108 of 113

V2.2 08/24/2023

Test Setup




Figure 7-11. LTE Test Instrument & Measurement Setup




Figure 7-12. FR1 Test Instrument & Measurement Setup

Test Notes

1. All port were tested and only the worst case data were reported.

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 109 of 113

V2.2 08/24/2023

Frequency Tolerance / Temperature Variation

LTE Band 26/5					
		Operating Frequency (Hz):		836,500,000	
		Ref. Voltage (VDC):		3.80	
		Deviation Limit:		± 0.00025% or 2.5 ppm	
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	- 30	836,499,910	-129.00	-0.0000154
		- 20	836,499,941	-98.00	-0.0000117
		- 10	836,499,907	-132.00	-0.0000158
		0	836,500,095	56.00	0.0000067
		+ 10	836,500,083	44.00	0.0000053
		+ 20 (Ref)	836,500,039	0.00	0.0000000
		+ 30	836,499,984	-55.00	-0.0000066
		+ 40	836,500,088	49.00	0.0000059
		+ 50	836,499,884	-155.00	-0.0000185
Battery Endpoint	3.40	+ 20	836,499,840	-199.00	-0.0000238

Table 7-38. LTE Band 26/5 Frequency Tolerance Data

FCC ID: BCGA3462		PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device		Page 110 of 113

V2.2 08/24/2023

Frequency Tolerance / Temperature Variation

NR Band n26/n5					
		Operating Frequency (Hz):		836,500,000	
		Ref. Voltage (VDC):		3.80	
		Deviation Limit:		± 0.00025% or 2.5 ppm	
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	- 30	836,500,137	96.00	0.0000115
		- 20	836,500,176	135.00	0.0000161
		- 10	836,499,976	-65.00	-0.0000078
		0	836,499,964	-77.00	-0.0000092
		+ 10	836,500,066	25.00	0.0000030
		+ 20 (Ref)	836,500,041	0.00	0.0000000
		+ 30	836,500,093	52.00	0.0000062
		+ 40	836,499,982	-59.00	-0.0000071
		+ 50	836,499,882	-159.00	-0.0000190
Battery Endpoint	3.40	+ 20	836,499,785	-256.00	-0.0000306

Table 7-39. NR Band n26/n5 Frequency Tolerance Data

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 111 of 113

V2.2 08/24/2023

Frequency Tolerance / Temperature Variation

WCDMA Cellular					
		Operating Frequency (Hz):		836,600,000	
		Ref. Voltage (VDC):		3.80	
		Deviation Limit:		± 0.00025% or 2.5 ppm	
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	- 30	836,599,921	-111.00	-0.0000133
		- 20	836,599,947	-85.00	-0.0000102
		- 10	836,599,983	-49.00	-0.0000059
		0	836,600,122	90.00	0.0000108
		+ 10	836,600,117	85.00	0.0000102
		+ 20 (Ref)	836,600,032	0.00	0.0000000
		+ 30	836,599,912	-120.00	-0.0000143
		+ 40	836,600,128	96.00	0.0000115
		+ 50	836,600,081	49.00	0.0000059
Battery Endpoint	3.40	+ 20	836,599,963	-69.00	-0.0000082

Table 7-40. WCDMA Cell Frequency Tolerance Data

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device	Page 112 of 113

V2.2 08/24/2023

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the Apple **Tablet Device** **FCC ID: BCGA3462** complies with all the requirements of Part 22 of the FCC rules.

FCC ID: BCGA3462	 PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-07-R2.BCG	Test Dates: 7/15/2025 - 11/11/2025	EUT Type: Tablet Device
		Page 113 of 113

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.