



Test Plot



09:29:38 AM 09/30/2025

Plot 7-83. Upper Band Edge Plot (LTE Band 26 – 1.4MHz QPSK – High Channel)

Test Plot



09:32:57 AM 09/30/2025


Plot 7-84. Extended Upper Band Edge Plot (LTE Band 26 – 1.4MHz QPSK – High Channel)

FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 63 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



09:34:30 AM 09/30/2025

Plot 7-85. Lower Band Edge Plot (LTE Band 26 – 3MHz QPSK – Low Channel)

Test Plot



09:37:46 AM 09/30/2025


Plot 7-86. Extended Lower Band Edge Plot (LTE Band 26 – 3MHz QPSK – Low Channel)

FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 64 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



09:36:08 AM 09/30/2025

Plot 7-87. Upper Band Edge Plot (LTE Band 26 – 3MHz QPSK – High Channel)

Test Plot



09:39:24 AM 09/30/2025


Plot 7-88. Extended Upper Band Edge Plot (LTE Band 26 – 3MHz QPSK – High Channel)

FCC ID: BCGA3462	PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 65 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



09:40:58 AM 09/30/2025

Plot 7-89. Lower Band Edge Plot (LTE Band 26 – 5MHz QPSK – Low Channel)

Test Plot



09:44:09 AM 09/30/2025


Plot 7-90. Extended Lower Band Edge Plot (LTE Band 26 – 5MHz QPSK – Low Channel)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 66 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



09:42:31 AM 09/30/2025

Plot 7-91. Upper Band Edge Plot (LTE Band 26 – 5MHz QPSK – High Channel)

Test Plot



09:45:42 AM 09/30/2025


Plot 7-92. Extended Upper Band Edge Plot (LTE Band 26 – 5MHz QPSK – High Channel)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 67 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



09:47:33 AM 09/30/2025

Plot 7-93. Lower Band Edge Plot (LTE Band 26 – 10MHz QPSK – Low Channel)

Test Plot



09:48:45 AM 09/30/2025


Plot 7-94. Extended Lower Band Edge Plot (LTE Band 26 – 10MHz QPSK – Low Channel)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 68 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



09:47:52 AM 09/30/2025

Plot 7-95. Upper Band Edge Plot (LTE Band 26 – 10MHz QPSK – High Channel)

Test Plot



09:49:03 AM 09/30/2025


Plot 7-96. Extended Upper Band Edge Plot (LTE Band 26 – 10MHz QPSK – High Channel)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 69 of 109

V2.2 09/07/2023


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

LTE Band 14



12:10:22 PM 09/30/2025

Plot 7-97. Lower Band Edge Plot (LTE Band 14 - 5MHz QPSK – RB Size 25)



12:10:40 PM 09/30/2025


Plot 7-98. Lower Emission Mask Plot (LTE Band 14 - 5MHz QPSK – RB Size 25)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 70 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



12:13:41 PM 09/30/2025

Plot 7-99. Upper Band Edge Plot (LTE Band 14 - 5MHz QPSK – RB Size 25)

Test Plot



12:14:17 PM 09/30/2025


Plot 7-100. Upper Emission Mask Plot (LTE Band 14 - 5MHz QPSK – RB Size 25)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 71 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



12:17:05 PM 09/30/2025

Plot 7-101. Lower Band Edge Plot (LTE Band 14 - 10MHz QPSK – RB Size 50)

Test Plot



12:17:23 PM 09/30/2025


Plot 7-102. Lower Emission Mask Plot (LTE Band 14 - 10MHz QPSK – RB Size 50)

FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 72 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Test Plot



12:18:17 PM 09/30/2025

Plot 7-103. Upper Band Edge Plot (LTE Band 14 - 10MHz QPSK – RB Size 50)

Test Plot



12:17:41 PM 09/30/2025


Plot 7-104. Upper Emission Mask Plot (LTE Band 14 - 10MHz QPSK – RB Size 50)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 73 of 109


V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

NR Band n26



Plot 7-105. Lower Band Edge Plot (NR Band n26 - 5MHz DFT-s-OFDM QPSK – Low Channel)



Plot 7-106. Extended Lower Band Edge Plot (NR Band n26 - 5MHz DFT-s-OFDM QPSK – Low Channel)


FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device
		Page 74 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-107. Upper Band Edge Plot (NR Band n26 - 5MHz DFT-s-OFDM QPSK – High Channel)




Plot 7-108. Extended Upper Band Edge Plot (NR Band n26 - 5MHz DFT-s-OFDM QPSK – High Channel)


FCC ID: BCGA3462	PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	Page 75 of 109
	EUT Type: Tablet Device	

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-109. Lower Band Edge Plot (NR Band n26 - 10MHz DFT-s-OFDM QPSK – Low Channel)




Plot 7-110. Extended Lower Band Edge Plot (NR Band n26 - 10MHz DFT-s-OFDM QPSK – Low Channel)

FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device
		Page 76 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.





FCC ID: BCGA3462	element	PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 77 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


NR Band n14




FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device
		Page 78 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-115. Upper Band Edge Plot (NR Band n14 - 5MHz DFT-s-OFDM QPSK – RB Size 25)





Plot 7-116. Upper Emission Mask Plot (NR Band n14 - 5MHz DFT-s-OFDM QPSK – RB Size 25)

FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device
		Page 79 of 109

V2.2 09/07/2023


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




FCC ID: BCGA3462	element	PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 80 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-119. Upper Band Edge Plot (NR Band n14 - 10MHz DFT-s-OFDM QPSK – RB Size 50)



Plot 7-120. Emission Mask Plot (NR Band n14 - 10MHz DFT-s-OFDM QPSK – RB Size 50)

FCC ID: BCGA3462	PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device
		Page 81 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.5 Conducted Power Output Data

\$2.1046 \$90.635

Test Overview

Conducted power measurements are performed to measure the average output power of the EUT. The averaging is to be performed only over duration of active transmissions at maximum output power level. The average measurements do not include averaging over periods when the transmitter is quiescent or when operating at reduced power level.

Test Procedures Used

KDB 971168 D01 v03r01

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. LTE Conducted Power Measurement Setup




Figure 7-8. FR1 Conducted Power Measurement Setup

Test Notes

1. The EUT was tested in all possible test configurations. The worst case emissions are reported with the EUT modulations and channel bandwidth configurations shown in the tables below.
2. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 82 of 109

V2.2 09/07/2023

7.5.1 Antenna 4 – Conducted Power

Bandwidth	Modulation	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
1.4 MHz	QPSK	814.7	1 / 3	25.28	0.337	50.00	-24.72
		819.0	1 / 0	25.22	0.333	50.00	-24.78
		823.3	1 / 3	25.29	0.338	50.00	-24.71
	16-QAM	823.3	1 / 3	24.19	0.262	50.00	-25.81
	64-QAM	823.3	1 / 3	23.40	0.219	50.00	-26.60
	256-QAM	823.3	6 / 0	21.29	0.135	50.00	-28.71
3 MHz	QPSK	815.5	1 / 0	25.23	0.333	50.00	-24.77
		819.0	1 / 14	25.27	0.337	50.00	-24.73
		822.5	1 / 7	25.37	0.344	50.00	-24.63
	16-QAM	822.5	1 / 7	24.17	0.261	50.00	-25.83
	64-QAM	819.0	1 / 7	23.39	0.218	50.00	-26.61
	256-QAM	822.5	15 / 0	21.30	0.135	50.00	-28.70
5 MHz	QPSK	816.5	1 / 0	25.25	0.335	50.00	-24.75
		819.0	1 / 0	25.24	0.334	50.00	-24.76
		821.5	1 / 0	25.28	0.337	50.00	-24.72
	16-QAM	821.5	1 / 0	24.15	0.260	50.00	-25.85
	64-QAM	821.5	1 / 0	23.37	0.217	50.00	-26.63
	256-QAM	821.5	25 / 0	21.34	0.136	50.00	-28.66
10 MHz	QPSK	819.0	1 / 49	25.35	0.343	50.00	-24.65
	16-QAM	819.0	1 / 25	24.13	0.259	50.00	-25.87
	64-QAM	819.0	1 / 25	23.32	0.215	50.00	-26.68
	256-QAM	819.0	50 / 0	21.38	0.137	50.00	-28.62

Table 7-2. Antenna 4 Conducted Output Data (LTE Band 26)

Bandwidth	Modulation	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
5 MHz	$\pi/2$ BPSK	816.5	25 / 0	25.32	0.340	50.00	-24.68
		819.0	25 / 0	25.34	0.342	50.00	-24.66
		821.5	25 / 0	25.30	0.339	50.00	-24.70
	QPSK	816.5	1 / 12	25.29	0.338	50.00	-24.71
		819.0	1 / 1	25.32	0.340	50.00	-24.68
		821.5	1 / 12	25.38	0.345	50.00	-24.62
	16-QAM	821.5	1 / 12	24.23	0.265	50.00	-25.77
	64-QAM	821.5	25 / 0	23.42	0.220	50.00	-26.58
	256-QAM	821.5	25 / 0	21.38	0.137	50.00	-28.62
10 MHz	$\pi/2$ BPSK	819.0	50 / 0	25.31	0.340	50.00	-24.69
	QPSK	819.0	1 / 50	25.29	0.338	50.00	-24.71
	16-QAM	819.0	1 / 25	24.14	0.259	50.00	-25.86
	64-QAM	819.0	50 / 0	23.39	0.218	50.00	-26.61
	256-QAM	819.0	50 / 0	21.39	0.138	50.00	-28.61

Table 7-3. Antenna 4 Conducted Output Data (NR Band n26)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device		Page 83 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.5.2 Antenna 2 – Conducted Power

Bandwidth	Modulation	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
1.4 MHz	QPSK	814.7	1 / 0	24.77	0.300	50.00	-25.23
		819.0	1 / 5	24.78	0.301	50.00	-25.22
		823.3	1 / 3	24.83	0.304	50.00	-25.17
	16-QAM	823.3	1 / 3	23.72	0.236	50.00	-26.28
	64-QAM	823.3	1 / 3	22.93	0.196	50.00	-27.07
	256-QAM	823.3	6 / 0	20.87	0.122	50.00	-29.13
3 MHz	QPSK	815.5	1 / 7	24.70	0.295	50.00	-25.30
		819.0	1 / 14	24.84	0.305	50.00	-25.16
		822.5	1 / 7	24.91	0.310	50.00	-25.09
	16-QAM	819.0	1 / 0	23.71	0.235	50.00	-26.29
	64-QAM	822.5	1 / 14	22.89	0.195	50.00	-27.11
	256-QAM	822.5	15 / 0	20.85	0.122	50.00	-29.15
5 MHz	QPSK	816.5	1 / 0	24.82	0.303	50.00	-25.18
		819.0	1 / 24	24.76	0.299	50.00	-25.24
		821.5	1 / 12	24.79	0.301	50.00	-25.21
	16-QAM	819.0	1 / 24	23.72	0.236	50.00	-26.28
	64-QAM	821.5	1 / 0	22.89	0.195	50.00	-27.11
	256-QAM	821.5	25 / 0	20.88	0.122	50.00	-29.12
10 MHz	QPSK	819.0	1 / 49	24.86	0.306	50.00	-25.14
	16-QAM	819.0	1 / 25	23.64	0.231	50.00	-26.36
	64-QAM	819.0	1 / 25	22.81	0.191	50.00	-27.19
	256-QAM	819.0	50 / 0	20.90	0.123	50.00	-29.10

Table 7-4. Antenna 2 Conducted Output Data (LTE Band 26)

Bandwidth	Modulation	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
5 MHz	$\pi/2$ BPSK	816.5	1 / 1	24.85	0.305	50.00	-25.15
		819.0	25 / 0	24.68	0.294	50.00	-25.32
		821.5	25 / 0	24.66	0.292	50.00	-25.34
	QPSK	816.5	1 / 1	24.74	0.298	50.00	-25.26
		819.0	1 / 1	24.71	0.296	50.00	-25.29
		821.5	1 / 23	24.77	0.300	50.00	-25.23
	16-QAM	821.5	1 / 23	23.61	0.230	50.00	-26.39
	64-QAM	819.0	25 / 0	22.74	0.188	50.00	-27.26
10 MHz	256-QAM	821.5	25 / 0	20.71	0.118	50.00	-29.29
	$\pi/2$ BPSK	819.0	1 / 1	24.79	0.301	50.00	-25.21
	QPSK	819.0	1 / 1	24.72	0.296	50.00	-25.28
	16-QAM	819.0	1 / 50	23.58	0.228	50.00	-26.42
	64-QAM	819.0	50 / 0	22.73	0.187	50.00	-27.27
	256-QAM	819.0	50 / 0	20.78	0.120	50.00	-29.22

Table 7-5. Antenna 2 Conducted Output Data (NR Band n26)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device		Page 84 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.6 Radiated Power (ERP)

§90.542(a)(7)

Test Overview

Effective Radiated Power (ERP) measurements are calculated by adding highest antenna gain to maximum measured conducted output power. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1
ANSI C63.26-2015

Test Settings

The relevant equation for determining the ERP from the conducted RF output power measured is:

$$\text{ERP} = \text{PMeas} - \text{LC} + \text{GT}$$

Where:

ERP = Effective Radiated Power (expressed in the same units as PMeas, typically dBW or dBm)

PMeas = measured transmitter output power or PSD, in dBW or dBm

LC = signal attenuation in the connecting cable between the transmitter and antenna in dB

GT = gain of the transmitting antenna, in dBd (ERP)

FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device
		Page 85 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-9. LTE ERP Measurement Setup




Figure 7-10. FR1 ERP Measurement Setup

Test Notes

1. The worst case emissions are reported with the modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
2. This unit was tested with its standard battery.
3. The Level (dBm) readings in the table were taken with a correction table loaded into the base station simulator. The correction table was used to account for the signal attenuation in the connecting cable between the transmitter and antenna.
4. The Ant. Gains (GT) are listed in dBi.
5. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 86 of 109

V2.2 09/07/2023

7.6.1 Antenna 4 - ERP

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
5 MHz	QPSK	790.5	-2.00	1 / 0	25.41	21.26	0.134	34.77	-13.51
		793.0	-2.00	1 / 12	25.43	21.28	0.134	34.77	-13.49
		795.5	-2.00	1 / 0	25.10	20.95	0.124	34.77	-13.82
	16-QAM	790.5	-2.00	1 / 0	24.70	20.55	0.114	34.77	-14.22
	64-QAM	795.5	-2.00	1 / 24	23.67	19.52	0.090	34.77	-15.25
	256-QAM	795.5	-2.00	25 / 0	20.76	16.61	0.046	34.77	-18.16
10 MHz	QPSK	793.0	-2.00	1 / 49	25.14	20.99	0.126	34.77	-13.78
	16-QAM	793.0	-2.00	1 / 49	24.39	20.24	0.106	34.77	-14.53
	64-QAM	793.0	-2.00	1 / 49	23.46	19.31	0.085	34.77	-15.46
	256-QAM	793.0	-2.00	50 / 0	20.71	16.56	0.045	34.77	-18.21

Table 7-6. Antenna 4 ERP Data (LTE Band 14)

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
5 MHz	$\pi/2$ BPSK	790.5	-2.00	25 / 0	25.29	21.14	0.130	34.77	-13.63
		793.0	-2.00	25 / 0	25.07	20.92	0.124	34.77	-13.85
		795.5	-2.00	25 / 0	25.19	21.04	0.127	34.77	-13.73
	QPSK	790.5	-2.00	1 / 1	25.09	20.94	0.124	34.77	-13.83
		793.0	-2.00	1 / 23	25.14	20.99	0.126	34.77	-13.78
		795.5	-2.00	1 / 1	25.12	20.97	0.125	34.77	-13.80
	16-QAM	793.0	-2.00	1 / 12	24.18	20.03	0.101	34.77	-14.74
	64-QAM	795.5	-2.00	25 / 0	23.25	19.10	0.081	34.77	-15.67
10 MHz	256-QAM	795.5	-2.00	25 / 0	21.20	17.05	0.051	34.77	-17.72
	$\pi/2$ BPSK	793.0	-2.00	1 / 50	25.07	20.92	0.124	34.77	-13.85
	QPSK	793.0	-2.00	1 / 1	25.38	21.23	0.133	34.77	-13.54
	16-QAM	793.0	-2.00	1 / 25	23.90	19.75	0.094	34.77	-15.02
	64-QAM	793.0	-2.00	50 / 0	23.04	18.89	0.077	34.77	-15.88
	256-QAM	793.0	-2.00	50 / 0	21.10	16.95	0.050	34.77	-17.82

Table 7-7. Antenna 4 ERP Data (NR Band n14)

FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 87 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.6.2 Antenna 2 - ERP

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
5 MHz	QPSK	790.5	-1.10	1 / 24	24.80	21.55	0.143	34.77	-13.22
		793.0	-1.10	1 / 24	24.88	21.63	0.146	34.77	-13.14
		795.5	-1.10	1 / 24	24.82	21.57	0.144	34.77	-13.20
	16-QAM	795.5	-1.10	1 / 0	24.19	20.94	0.124	34.77	-13.83
	64-QAM	790.5	-1.10	1 / 0	23.13	19.88	0.097	34.77	-14.89
	256-QAM	790.5	-1.10	25 / 0	20.20	16.95	0.050	34.77	-17.82
10 MHz	QPSK	793.0	-1.10	1 / 49	24.67	21.42	0.139	34.77	-13.35
	16-QAM	793.0	-1.10	1 / 25	23.93	20.68	0.117	34.77	-14.09
	64-QAM	793.0	-1.10	1 / 49	23.04	19.79	0.095	34.77	-14.98
	256-QAM	793.0	-1.10	50 / 0	20.19	16.94	0.049	34.77	-17.83

Table 7-8. Antenna 2 ERP Data (LTE Band 14)

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
5 MHz	$\pi/2$ BPSK	790.5	-1.10	1 / 12	24.87	21.62	0.145	34.77	-13.15
		793.0	-1.10	25 / 0	24.89	21.64	0.146	34.77	-13.13
		795.5	-1.10	1 / 23	24.87	21.62	0.145	34.77	-13.15
	QPSK	790.5	-1.10	1 / 23	24.88	21.63	0.146	34.77	-13.14
		793.0	-1.10	1 / 12	24.87	21.62	0.145	34.77	-13.15
		795.5	-1.10	1 / 23	24.85	21.60	0.145	34.77	-13.17
10 MHz	16-QAM	790.5	-1.10	1 / 12	23.69	20.44	0.111	34.77	-14.33
	64-QAM	790.5	-1.10	25 / 0	23.01	19.76	0.095	34.77	-15.01
	256-QAM	793.0	-1.10	25 / 0	20.95	17.70	0.059	34.77	-17.07
	$\pi/2$ BPSK	793.0	-1.10	1 / 1	24.81	21.56	0.143	34.77	-13.21
	QPSK	793.0	-1.10	1 / 50	24.89	21.64	0.146	34.77	-13.13
	16-QAM	793.0	-1.10	1 / 50	23.73	20.48	0.112	34.77	-14.29
	64-QAM	793.0	-1.10	50 / 0	22.83	19.58	0.091	34.77	-15.19
	256-QAM	793.0	-1.10	50 / 0	20.89	17.64	0.058	34.77	-17.13

Table 7-9. Antenna 2 ERP Data (NR Band n14)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device		Page 88 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.7 Radiated Spurious Emissions

§2.1053 §90.691(a) §90.543(e) §90.543(f)

Test Overview

Radiated spurious emissions measurements are performed using the field strength conversion method described in KDB 971168 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized broadband hybrid antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed while the EUT is operating at maximum power and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8

ANSI C63.26-2015

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 89 of 109

V2.2 09/07/2023

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-11. Test Instrument & Measurement Setup < 1GHz




Figure 7-12. Test Instrument & Measurement Setup >1 GHz

FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device
		Page 90 of 109

Test Notes

1. Field strengths are calculated using the Measurement quantity conversions in KDB 971168 D01 v03r01 Section 5.8.4.
 - a. $E(\text{dB}\mu\text{V}/\text{m}) = \text{Measured amplitude level (dBm)} + 107 + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$
 - b. $\text{EIRP (dBm)} = E(\text{dB}\mu\text{V}/\text{m}) + 20\log D - 104.8$; where D is the measurement distance in meters.
2. The device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
3. This unit was tested with its standard battery.
4. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
5. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
6. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.
7. Pre-scan plots have been reported for the highest power antenna while measurements have been reported for all antennas.

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 91 of 109

V2.2 09/07/2023

7.7.1 Antenna 4 – Radiated Spurious Emission Measurements

LTE Band 26

Bandwidth (MHz):	5
Frequency (MHz):	816.5
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1633.0	H	-	-	-76.88	-2.88	27.23	-68.02	-13.00	-55.02
2449.5	V	-	-	-77.85	2.12	31.27	-63.99	-13.00	-50.99
3266.0	V	-	-	-78.53	3.56	32.03	-63.23	-13.00	-50.23

Table 7-10. Antenna 4 Radiated Spurious Data (LTE Band 26 – Low Channel)

Bandwidth (MHz):	10
Frequency (MHz):	819.0
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1638.0	H	-	-	-77.51	-2.37	27.11	-68.14	-13.00	-55.14
2457.0	V	-	-	-77.88	2.16	31.28	-63.98	-13.00	-50.98
3276.0	H	-	-	-78.33	3.39	32.06	-63.20	-13.00	-50.20

Table 7-11. Antenna 4 Radiated Spurious Data (LTE Band 26 – Mid Channel)

Bandwidth (MHz):	5
Frequency (MHz):	821.5
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1643.0	V	-	-	-77.44	-2.33	27.23	-68.03	-13.00	-55.03
2464.5	H	-	-	-77.89	2.12	31.24	-64.02	-13.00	-51.02
3286.0	V	-	-	-78.24	3.56	32.32	-62.93	-13.00	-49.93

Table 7-12. Antenna 4 Radiated Spurious Data (LTE Band 26 – High Channel)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 92 of 109

V2.2 09/07/2023

LTE Band 14

Bandwidth (MHz):	5
Frequency (MHz):	790.5
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1581.0	H	-	-	-76.18	-3.23	27.59	-67.67	-40.00	-27.67
2371.5	V	-	-	-77.74	2.03	31.30	-63.96	-13.00	-50.96
3162.0	H	-	-	-78.96	4.08	32.12	-63.14	-13.00	-50.14

Table 7-13. Antenna 4 Radiated Spurious Data (LTE Band 14 – Low Channel)

Bandwidth (MHz):	10
Frequency (MHz):	793.0
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1586.0	H	-	-	-77.38	-2.96	26.66	-68.60	-40.00	-28.60
2379.0	V	-	-	-78.10	2.23	31.13	-64.13	-13.00	-51.13
3172.0	H	-	-	-78.97	3.76	31.79	-63.47	-13.00	-50.47

Table 7-14. Antenna 4 Radiated Spurious Data (LTE Band 14 – Mid Channel)

Bandwidth (MHz):	5
Frequency (MHz):	795.5
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1591.0	H	-	-	-77.35	-2.96	26.69	-68.57	-40.00	-28.57
2386.5	V	-	-	-78.10	2.23	31.12	-64.13	-13.00	-51.13
3182.0	H	-	-	-78.73	3.46	31.73	-63.53	-13.00	-50.53

Table 7-15. Antenna 4 Radiated Spurious Data (LTE Band 14 – High Channel)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device		Page 93 of 109

V2.2 09/07/2023

NR Band n14

Bandwidth (MHz):	5
Frequency (MHz):	790.5
Modulation Signal:	QPSK
RB / Offset:	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1581.0	H	-	-	-76.78	-3.23	26.99	-68.27	-40.00	-28.27
2371.5	V	-	-	-78.30	2.47	31.17	-64.09	-13.00	-51.09
3162.0	H	-	-	-78.99	4.02	32.03	-63.23	-13.00	-50.23

Table 7-16. Antenna 4 Radiated Spurious Data (NR Band n14 – Low Channel)

Bandwidth (MHz):	10
Frequency (MHz):	793.0
Modulation Signal:	QPSK
RB / Offset:	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1586.0	V	-	-	-77.15	-3.24	26.61	-68.65	-40.00	-28.65
2379.0	H	-	-	-77.65	1.94	31.29	-63.97	-13.00	-50.97
3172.0	H	-	-	-78.97	3.76	31.79	-63.47	-13.00	-50.47

Table 7-17. Antenna 4 Radiated Spurious Data (NR Band n14 – Mid Channel)

Bandwidth (MHz):	5
Frequency (MHz):	795.5
Modulation Signal:	QPSK
RB / Offset:	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1591.0	H	-	-	-77.22	-2.96	26.82	-68.44	-40.00	-28.44
2386.5	V	-	-	-77.76	2.03	31.28	-63.98	-13.00	-50.98
3182.0	H	-	-	-78.34	3.19	31.85	-63.41	-13.00	-50.41

Table 7-18. Antenna 4 Radiated Spurious Data (NR Band n14 – High Channel)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device		Page 94 of 109

V2.2 09/07/2023

NR Band n26

Bandwidth (MHz):	5
Frequency (MHz):	816.5
Modulation Signal:	QPSK
RB / Offset:	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1633.0	H	339	11	-75.62	-2.63	28.75	-66.51	-13.00	-53.51
2449.5	V	-	-	-77.85	1.05	30.20	-65.06	-13.00	-52.06
3266.0	H	-	-	-78.20	3.05	31.85	-63.41	-13.00	-50.41
4082.5	V	-	-	-78.44	4.09	32.65	-62.60	-13.00	-49.60

Table 7-19. Antenna 4 Radiated Spurious Data (NR Band n26 – Low Channel)

Bandwidth (MHz):	10
Frequency (MHz):	819.0
Modulation Signal:	QPSK
RB / Offset:	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1638.0	H	-	-	-76.87	-2.88	27.25	-68.01	-13.00	-55.01
2457.0	V	-	-	-77.98	2.12	31.14	-64.11	-13.00	-51.11
3276.0	V	-	-	-78.61	3.56	31.95	-63.31	-13.00	-50.31

Table 7-20. Antenna 4 Radiated Spurious Data (NR Band n26 – Mid Channel)

Bandwidth (MHz):	5
Frequency (MHz):	821.5
Modulation Signal:	QPSK
RB / Offset:	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1643.0	H	-	-	-77.58	-2.33	27.09	-68.17	-13.00	-55.17
2464.5	H	-	-	-77.82	2.09	31.27	-63.98	-13.00	-50.98
3286.0	V	-	-	-78.31	3.53	32.22	-63.03	-13.00	-50.03


Table 7-21. Antenna 4 Radiated Spurious Data (NR Band n26 – High Channel)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device		Page 95 of 109


V2.2 09/07/2023

7.7.2 Antenna 2 – Radiated Spurious Emission Measurements

LTE Band 26



Plot 7-121. Antenna 2 Radiated Spurious Plot Below 1GHz (LTE Band 26)



Plot 7-122. Antenna 2 Radiated Spurious Plot Above 1GHz (LTE Band 26)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 96 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Bandwidth (MHz):	5
Frequency (MHz):	816.5
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1633.0	V	-	-	-77.43	-2.37	27.20	-68.06	-13.00	-55.06
2449.5	H	-	-	-77.88	2.11	31.24	-64.02	-13.00	-51.02
3266.0	H	-	-	-78.43	3.39	31.96	-63.29	-13.00	-50.29

Table 7-22. Antenna 2 Radiated Spurious Data (LTE Band 26 – Low Channel)

Bandwidth (MHz):	10
Frequency (MHz):	819.0
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1638.0	H	-	-	-77.56	-2.37	27.06	-68.19	-13.00	-55.19
2457.0	V	-	-	-78.03	2.16	31.13	-64.13	-13.00	-51.13
3276.0	V	-	-	-78.51	3.53	32.02	-63.23	-13.00	-50.23

Table 7-23. Antenna 2 Radiated Spurious Data (LTE Band 26 – Mid Channel)


Bandwidth (MHz):	5
Frequency (MHz):	821.5
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1643.0	V	-	-	-77.37	-2.33	27.30	-67.96	-13.00	-54.96
2464.5	V	-	-	-77.74	2.03	31.29	-63.97	-13.00	-50.97
3286.0	V	-	-	-78.76	3.68	31.92	-63.34	-13.00	-50.34


Table 7-24. Antenna 2 Radiated Spurious Data (LTE Band 26 – High Channel)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 97 of 109

LTE Band 14



Plot 7-123. Antenna 2 Radiated Spurious Plot Below 1GHz (LTE Band 14)



Plot 7-124. Antenna 2 Radiated Spurious Plot Above 1GHz (LTE Band 14)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 98 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Bandwidth (MHz):	5
Frequency (MHz):	790.5
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1581.0	V	-	-	-76.32	-3.23	27.45	-67.81	-40.00	-27.81
2371.5	V	-	-	-77.89	2.03	31.14	-64.11	-13.00	-51.11
3162.0	H	-	-	-78.80	3.76	31.96	-63.30	-13.00	-50.30

Table 7-25. Antenna 2 Radiated Spurious Data (LTE Band 14 – Low Channel)

Bandwidth (MHz):	10
Frequency (MHz):	793.0
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1586.0	V	-	-	-77.32	-3.15	26.53	-68.73	-40.00	-28.73
2379.0	H	-	-	-78.06	2.23	31.17	-64.09	-13.00	-51.09
3172.0	V	-	-	-78.88	3.76	31.87	-63.38	-13.00	-50.38

Table 7-26. Antenna 2 Radiated Spurious Data (LTE Band 14 – Mid Channel)

Bandwidth (MHz):	5
Frequency (MHz):	795.5
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 12


Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1591.0	V	-	-	-77.33	-2.88	26.79	-68.47	-40.00	-28.47
2386.5	H	-	-	-78.04	2.23	31.18	-64.07	-13.00	-51.07
3182.0	H	-	-	-78.69	3.46	31.76	-63.50	-13.00	-50.50

Table 7-27. Antenna 2 Radiated Spurious Data (LTE Band 14 – High Channel)


FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device
		Page 99 of 109

V2.2 09/07/2023

NR Band n14



Plot 7-125. Antenna 2 Radiated Spurious Plot Below 1GHz (NR Band n14)



Plot 7-126. Antenna 2 Radiated Spurious Plot Above 1GHz (NR Band n14)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 100 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Bandwidth (MHz):	5
Frequency (MHz):	790.5
Modulation Signal:	QPSK
RB / Offset:	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1581.0	H	-	-	-77.45	-2.96	26.59	-68.67	-40.00	-28.67
2371.5	H	-	-	-78.05	2.23	31.18	-64.08	-13.00	-51.08
3162.0	V	-	-	-78.94	4.02	32.08	-63.17	-13.00	-50.17

Table 7-28. Antenna 2 Radiated Spurious Data (NR Band n14 – Low Channel)

Bandwidth (MHz):	10
Frequency (MHz):	793.0
Modulation Signal:	QPSK
RB / Offset:	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1586.0	H	-	-	-77.40	-2.96	26.63	-68.63	-40.00	-28.63
2379.0	H	-	-	-77.80	2.23	31.43	-63.82	-13.00	-50.82
3172.0	H	-	-	-78.60	3.46	31.86	-63.40	-13.00	-50.40

Table 7-29. Antenna 2 Radiated Spurious Data (NR Band n14 – Mid Channel)

Bandwidth (MHz):	5
Frequency (MHz):	795.5
Modulation Signal:	QPSK
RB / Offset:	1 / 12


Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1591.0	H	-	-	-77.41	-2.96	26.63	-68.63	-40.00	-28.63
2386.5	V	-	-	-78.23	2.23	31.00	-64.26	-13.00	-51.26
3182.0	H	-	-	-78.85	3.46	31.61	-63.65	-13.00	-50.65

Table 7-30. Antenna 2 Radiated Spurious Data (NR Band n14 – High Channel)


FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device
		Page 101 of 109

V2.2 09/07/2023

NR Band n26



Plot 7-127. Antenna 2 Radiated Spurious Plot Below 1GHz (NR Band n26)



Plot 7-128. Antenna 2 Radiated Spurious Plot Above 1GHz (NR Band n26)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 102 of 109

V2.2 09/07/2023

Bandwidth (MHz):	5
Frequency (MHz):	816.5
Modulation Signal:	QPSK
RB / Offset:	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1633.0	H	-	-	-76.95	-2.88	27.17	-68.09	-13.00	-55.09
2449.5	V	-	-	-78.00	2.12	31.12	-64.14	-13.00	-51.14
3266.0	V	-	-	-78.38	3.46	32.08	-63.18	-13.00	-50.18

Table 7-31. Antenna 2 Radiated Spurious Data (NR Band n26 – Low Channel)

Bandwidth (MHz):	10
Frequency (MHz):	819.0
Modulation Signal:	QPSK
RB / Offset:	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1638.0	H	-	-	-77.63	-2.37	27.00	-68.26	-13.00	-55.26
2457.0	V	-	-	-77.92	2.16	31.24	-64.02	-13.00	-51.02
3276.0	V	-	-	-78.68	3.62	31.94	-63.32	-13.00	-50.32

Table 7-32. Antenna 2 Radiated Spurious Data (NR Band n26 – Mid Channel)

Bandwidth (MHz):	5
Frequency (MHz):	821.5
Modulation Signal:	QPSK
RB / Offset:	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1643.0	V	-	-	-77.42	-2.33	27.25	-68.01	-13.00	-55.01
2464.5	V	-	-	-77.80	2.16	31.36	-63.90	-13.00	-50.90
3286.0	H	-	-	-78.41	3.68	32.26	-62.99	-13.00	-49.99

Table 7-33. Antenna 2 Radiated Spurious Data (NR Band n26 – High Channel)

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 103 of 109

V2.2 09/07/2023

7.8 Frequency Stability / Temperature Variation

§2.1055 §90.213

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For LTE Band 26 and NR Band n26, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For LTE Band 14 and NR Band n14 the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI C63.26-2015

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup




Figure 7-13. LTE Test Instrument & Measurement Setup




Figure 7-14. FR1 Test Instrument & Measurement Setup

Test Notes

All ports were tested and only the worst case data were reported.

FCC ID: BCGA3462		PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 104 of 109

V2.2 09/07/2023

Frequency Stability / Temperature Variation

LTE Band 26					
		Operating Frequency (GHz):		0.819	
		Ref. Voltage (VDC):		3.80	
		Deviation Limit:		± 0.00025% or 2.5 ppm	
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (GHz)	Freq. Dev. (GHz)	Deviation (%)
100 %	3.80	- 30	0.819000036	-0.000000047	-0.000005739
		- 20	0.819000219	0.000000136	0.000016606
		- 10	0.818999892	-0.000000191	-0.000023321
		0	0.819000165	0.000000082	0.000010012
		+ 10	0.819000078	-0.000000005	-0.000000611
		+ 20 (Ref)	0.819000083	0.000000000	0.000000000
		+ 30	0.818999961	-0.000000122	-0.000014896
		+ 40	0.819000182	0.000000099	0.000012088
		+ 50	0.818999915	-0.000000168	-0.000020513
Battery Endpoint	3.40	+ 20	0.819000106	0.000000023	0.000002808

Table 7-34. LTE Band 26 Frequency Stability Data

FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 105 of 109

V2.2 09/07/2023

Frequency Stability / Temperature Variation

LTE Band 14				
Operating Band Lower Boundary (GHz)		0.788		
Ref. Voltage (VDC):		3.80		
Voltage (%)	Power (VDC)	Temp (°C)	Measured Freq. (GHz)	Freq. Delta from Operating Range (GHz)
100 %	3.80	- 30	0.788463918	-0.000463918
		- 20	0.788251706	-0.000251706
		- 10	0.788701235	-0.000701235
		0	0.788932510	-0.000932510
		+ 10	0.788124398	-0.000124398
		+ 20 (Ref)	0.788597042	-0.000597042
		+ 30	0.788819357	-0.000819357
		+ 40	0.788354690	-0.000354690
		+ 50	0.788779425	-0.000779425
Battery Endpoint	3.40	+ 20	0.788045132	-0.000045132

Table 7-35. LTE Band 14 Lower Boundary Frequency Stability Data

LTE Band 14				
Operating Band Upper Boundary (GHz)		0.798		
Ref. Voltage (VDC):		3.80		
Voltage (%)	Power (VDC)	Temp (°C)	Measured Freq. (GHz)	Freq. Delta from Operating Range (GHz)
100 %	3.80	- 30	0.797813205	-0.000186795
		- 20	0.797052348	-0.000947652
		- 10	0.797729694	-0.000270306
		0	0.797197560	-0.000802440
		+ 10	0.797985003	-0.000014997
		+ 20 (Ref)	0.797612448	-0.000387552
		+ 30	0.797324895	-0.000675105
		+ 40	0.797876120	-0.000123880
		+ 50	0.797483211	-0.000516789
Battery Endpoint	3.40	+ 20	0.797109537	-0.000890463

Table 7-36. LTE Band 14 Upper Boundary Frequency Stability Data

FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 106 of 109

V2.2 09/07/2023

Frequency Stability / Temperature Variation

NR Band n26					
		Operating Frequency (GHz):		0.819	
		Ref. Voltage (VDC):		3.80	
		Deviation Limit:		± 0.00025% or 2.5 ppm	
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (GHz)	Freq. Dev. (GHz)	Deviation (%)
100 %	3.80	- 30	0.818999955	-0.000000143	-0.000017460
		- 20	0.819000155	0.000000057	0.000006960
		- 10	0.819000296	0.000000198	0.000024176
		0	0.819000074	-0.000000024	-0.000002930
		+ 10	0.819000210	0.000000112	0.000013675
		+ 20 (Ref)	0.819000098	0.000000000	0.000000000
		+ 30	0.819000131	0.000000033	0.000004029
		+ 40	0.819000010	-0.000000088	-0.000010745
		+ 50	0.819000272	0.000000174	0.000021245
Battery Endpoint	3.40	+ 20	0.819000092	-0.000000006	-0.000000733

Table 7-37. NR Band n26 Frequency Stability Data

FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 107 of 109

V2.2 09/07/2023

Frequency Stability / Temperature Variation

NR Band n14				
Operating Band Lower Boundary (GHz)			0.788	
Ref. Voltage (VDC):			3.80	
Voltage (%)	Power (VDC)	Temp (°C)	Measured Freq. (GHz)	Freq. Delta from Operating Range (GHz)
100 %	3.80	- 30	0.788502163	-0.000502163
		- 20	0.788062948	-0.000062948
		- 10	0.788941022	-0.000941022
		0	0.788236705	-0.000236705
		+ 10	0.788765491	-0.000765491
		+ 20 (Ref)	0.788398270	-0.000398270
		+ 30	0.788593010	-0.000593010
		+ 40	0.788157824	-0.000157824
		+ 50	0.788828347	-0.000828347
Battery Endpoint	3.40	+ 20	0.788319600	-0.000319600

Table 7-38. NR Band n14 Lower Boundary Frequency Stability Data

NR Band n14				
Operating Band Upper Boundary (GHz)			0.798	
Ref. Voltage (VDC):			3.80	
Voltage (%)	Power (VDC)	Temp (°C)	Measured Freq. (GHz)	Freq. Delta from Operating Range (GHz)
100 %	3.80	- 30	0.797094813	-0.000905187
		- 20	0.797684725	-0.000315275
		- 10	0.797437900	-0.000562100
		0	0.797910258	-0.000089742
		+ 10	0.797271543	-0.000728457
		+ 20 (Ref)	0.797856219	-0.000143781
		+ 30	0.797145082	-0.000854918
		+ 40	0.797992874	-0.000007126
		+ 50	0.797528316	-0.000471684
Battery Endpoint	3.40	+ 20	0.797353469	-0.000646531

Table 7-39. NR Band n14 Upper Boundary Frequency Stability Data

FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device	Page 108 of 109

V2.2 09/07/2023

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Apple Tablet Device** **FCC ID: BCGA3462** complies with all the requirements of Part 90 of the FCC rules.

FCC ID: BCGA3462	 PART 90 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2509100082-12-R1.BCG	Test Dates: 7/15/2025 - 11/4/2025	EUT Type: Tablet Device
		Page 109 of 109

V2.2 09/07/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.