



7.6.21 CDD Diversity Radiated Band Edge Measurements (80MHz BW)


RU26




Plot 7-1069. CDD Diversity (Peak & Average, RU26, Index 0, Ch.42, MCS11)




Plot 7-1072. CDD Diversity (Peak, RU26, Index 36, Ch.155, MCS11)




Plot 7-1070. CDD Diversity (Peak & Average, RU26, Index 36, Ch.42, MCS11)



Plot 7-1073. CDD Diversity (Peak, RU26, Index 0, Ch.155, MCS11)



Plot 7-1071. CDD Diversity (Peak, RU26, Index 0, Ch.155, MCS11)




Plot 7-1074. CDD Diversity (Peak, RU26, Index 36, Ch.155, MCS11)


FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 337 of 380

V 10.6 10/27/2023


MRU




Plot 7-1081. CDD Diversity (Peak & Average, RU484+242, Index 90, Ch.42, MCS11)




Plot 7-1084. CDD Diversity (Peak & Average, RU484+242, Index 93, Ch.42, MCS11)




Plot 7-1082. CDD Diversity (Peak & Average, RU484+242, Index 91, Ch.42, MCS11)



Plot 7-1085. CDD Diversity (Peak & Average, RU484+242, Index 90, Ch.58, MCS11)



Plot 7-1083. CDD Diversity (Peak & Average, RU484+242, Index 92, Ch.42, MCS11)




Plot 7-1086. CDD Diversity (Peak & Average, RU484+242, Index 91, Ch.58, MCS11)


FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 339 of 380

V 10.6 10/27/2023


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-1087. CDD Diversity (Peak & Average, RU484+242, Index 92, Ch.58, MCS11)




Plot 7-1090. CDD Diversity (Peak & Average, RU484+242, Index 91, Ch.106, MCS11)




Plot 7-1088. CDD Diversity (Peak & Average, RU484+242, Index 93, Ch.58, MCS11)



Plot 7-1091. CDD Diversity (Peak & Average, RU484+242, Index 92, Ch.106, MCS11)




Plot 7-1089. CDD Diversity (Peak & Average, RU484+242, Index 90, Ch.106, MCS11)




Plot 7-1092. CDD Diversity (Peak & Average, RU484+242, Index 93, Ch.106, MCS11)


FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 340 of 380




Plot 7-1093. CDD Diversity (Peak & Average, RU484+242, Index 90, Ch.122, MCS11)




Plot 7-1096. CDD Diversity (Peak & Average, RU484+242, Index 93, Ch.122, MCS11)




Plot 7-1094. CDD Diversity (Peak & Average, RU484+242, Index 91, Ch.122, MCS11)



Plot 7-1097. CDD Diversity (Peak, RU484+242, Index 90, Ch.122, MCS11)




Plot 7-1095. CDD Diversity (Peak & Average, RU484+242, Index 92, Ch.122, MCS11)




Plot 7-1098. CDD Diversity (Peak, RU484+242, Index 91, Ch.122, MCS11)


FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 341 of 380




Plot 7-1099. CDD Diversity (Peak, RU484+242, Index 92, Ch.122, MCS11)




Plot 7-1102. CDD Diversity (Peak, RU484+242, Index 91, Ch.155, MCS11)




Plot 7-1100. CDD Diversity (Peak, RU484+242, Index 93, Ch.122, MCS11)



Plot 7-1103. CDD Diversity (Peak, RU484+242, Index 92, Ch.155, MCS11)



Plot 7-1101. CDD Diversity (Peak, RU484+242, Index 90, Ch.155, MCS11)




Plot 7-1104. CDD Diversity (Peak, RU484+242, Index 93, Ch.155, MCS11)


FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 342 of 380

V 10.6 10/27/2023


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-1105. CDD Diversity (Peak, RU484+242, Index 90, Ch.155, MCS11)



Plot 7-1108. CDD Diversity (Peak, RU484+242, Index 93, Ch.155, MCS11)




Plot 7-1106. CDD Diversity (Peak, RU484+242, Index 91, Ch.155, MCS11)




Plot 7-1107. CDD Diversity (Peak, RU484+242, Index 92, Ch.155, MCS11)

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 343 of 380


RU996




Plot 7-1109. CDD Diversity (Peak & Average, RU996, Index 67, Ch.42, MCS11)




Plot 7-1112. CDD Diversity (Peak & Average, RU996, Index 67, Ch.122, MCS11)




Plot 7-1110. CDD Diversity (Peak & Average, RU996, Index 67, Ch.58, MCS11)



Plot 7-1113. CDD Diversity (Peak, RU996, Index 67, Ch.122, MCS11)



Plot 7-1111. CDD Diversity (Peak & Average, RU996, Index 67, Ch.106, MCS11)




Plot 7-1114. CDD Diversity (Peak, RU996, Index 67, Ch.155, MCS11)

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 344 of 380

V 10.6 10/27/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-1115. CDD Diversity (Peak, RU996, Index 67, Ch.155, MCS11)

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 345 of 380


V 10.6 10/27/2023

7.6.22 CDD Diversity Radiated Band Edge Measurements (160MHz BW)


RU52




Plot 7-1116. CDD Diversity (Peak & Average, RU52, Index 37 (L), Ch.50, MCS11)




Plot 7-1119. CDD Diversity (Peak & Average, RU52, Index 52 (H), Ch.50, MCS11)




Plot 7-1117. CDD Diversity (Peak & Average, RU52, Index 52 (H), Ch.50, MCS11)



Plot 7-1120. CDD Diversity (Peak & Average, RU52, Index 37 (L), Ch.114, MCS11)



Plot 7-1118. CDD Diversity (Peak & Average, RU52, Index 37 (L), Ch.50, MCS11)




Plot 7-1121. CDD Diversity (Peak & Average, RU52, Index 52 (H), Ch.114, MCS11)


FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 346 of 380

V 10.6 10/27/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-1122. CDD Diversity (Peak, RU52, Index 37 (L), Ch.114, MCS11)




Plot 7-1123. CDD Diversity (Peak, RU52, Index 52 (H), Ch.114, MCS11)

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 347 of 380


V 10.6 10/27/2023




Plot 7-1130. CDD Diversity (Peak & Average, RU996+484, Index 95 (L), Ch.50, MCS11)




Plot 7-1133. CDD Diversity (Peak & Average, RU996+484, Index 94 (H), Ch.114, MCS11)




Plot 7-1131. CDD Diversity (Peak & Average, RU996+484, Index 95 (H), Ch.50, MCS11)



Plot 7-1134. CDD Diversity (Peak & Average, RU996+484, Index 95 (L), Ch.114, MCS11)




Plot 7-1132. CDD Diversity (Peak & Average, RU996+484, Index 94 (L), Ch.114, MCS11)




Plot 7-1135. CDD Diversity (Peak & Average, RU996+484, Index 95 (H), Ch.114, MCS11)


FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 349 of 380




Plot 7-1136. CDD Diversity (Peak, RU996+484, Index 94 (L), Ch.114, MCS11)




Plot 7-1139. CDD Diversity (Peak, RU996+484, Index 95 (L), Ch.114, MCS11)




Plot 7-1137. CDD Diversity (Peak, RU996+484, Index 94 (H), Ch.114, MCS11)



Plot 7-1140. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (L), Ch.50, MCS11)




Plot 7-1138. CDD Diversity (Peak, RU996+484, Index 95 (H), Ch.114, MCS11)




Plot 7-1141. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (H), Ch.50, MCS11)


FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 350 of 380




Plot 7-1142. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (L), Ch.50, MCS11)




Plot 7-1145. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (L), Ch.50, MCS11)




Plot 7-1143. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (H), Ch.50, MCS11)



Plot 7-1146. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (L), Ch.50, MCS11)




Plot 7-1144. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (H), Ch.50, MCS11)




Plot 7-1147. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (H), Ch.50, MCS11)


FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 351 of 380




Plot 7-1148. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (L), Ch.50, MCS11)




Plot 7-1151. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (H), Ch.50, MCS11)




Plot 7-1149. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (H), Ch.50, MCS11)



Plot 7-1152. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (L), Ch.50, MCS11)




Plot 7-1150. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (L), Ch.50, MCS11)




Plot 7-1153. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (H), Ch.50, MCS11)


FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 352 of 380




Plot 7-1154. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (L), Ch.50, MCS11)




Plot 7-1157. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (H), Ch.114, MCS11)




Plot 7-1155. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (H), Ch.50, MCS11)



Plot 7-1158. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (L), Ch.114, MCS11)




Plot 7-1156. CDD Diversity (Peak & Average, RU996+484+242, Index 96 (L), Ch.114, MCS11)




Plot 7-1159. CDD Diversity (Peak & Average, RU996+484+242, Index 97 (H), Ch.114, MCS11)


FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 353 of 380




Plot 7-1160. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (L), Ch.114, MCS11)




Plot 7-1163. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (H), Ch.114, MCS11)




Plot 7-1161. CDD Diversity (Peak & Average, RU996+484+242, Index 98 (H), Ch.114, MCS11)



Plot 7-1164. CDD Diversity (Peak, RU996+484+242, Index 96 (H), Ch.114, MCS11)




Plot 7-1162. CDD Diversity (Peak & Average, RU996+484+242, Index 99 (L), Ch.114, MCS11)




Plot 7-1165. CDD Diversity (Peak, RU996+484+242, Index 96 (L), Ch.114, MCS11)


FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 354 of 380




Plot 7-1166. CDD Diversity (Peak, RU996+484+242, Index 97 (L), Ch.114, MCS11)




Plot 7-1169. CDD Diversity (Peak, RU996+484+242, Index 98 (H), Ch.114, MCS11)




Plot 7-1167. CDD Diversity (Peak, RU996+484+242, Index 97 (H), Ch.114, MCS11)



Plot 7-1170. CDD Diversity (Peak, RU996+484+242, Index 99 (H), Ch.114, MCS11)




Plot 7-1168. CDD Diversity (Peak, RU996+484+242, Index 98 (L), Ch.114, MCS11)




Plot 7-1171. CDD Diversity (Peak, RU996+484+242, Index 99 (L), Ch.114, MCS11)

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 355 of 380


RU996X2




Plot 7-1172. CDD Diversity (Peak & Average, RU996X2, Index 68, Ch.50, MCS11)



Plot 7-1175. CDD Diversity (Peak, RU996X2, Index 68, Ch.114, MCS11)



Plot 7-1173. CDD Diversity (Peak & Average, RU996X2, Index 68, Ch.50, MCS11)



Plot 7-1174. CDD Diversity (Peak & Average, RU996X2, Index 68, Ch.114, MCS11)

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 356 of 380

V 10.6 10/27/2023

7.7 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-243 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-243. Radiated Limits

Test Procedures Used

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 357 of 380

V 10.6 10/27/2023

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-6. Radiated Test Setup < 30MHz




Figure 7-7. Radiated Test Setup < 1GHz

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 358 of 380

V 10.6 10/27/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-243.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector for emissions within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. All antenna configurations and data rates were investigated and only the worst case are reported.
10. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger

Sample Calculations


Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]} - \text{Preamplifier Gain }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 359 of 380

V 10.6 10/27/2023

7.7.1 CDD Primary Radiated Spurious Emissions (Below 1GHz)




Plot 7-1176. RSE below 1GHz CDD Primary (RU26 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
36.15	Max-Peak	V	100	-	-60.08	-17.71	29.21	40.00	-10.79
85.65	Max-Peak	V	100	-	-58.65	-20.88	27.47	40.00	-12.53
113.79	Max-Peak	H	300	-	-61.84	-18.71	26.45	43.50	-17.05
183.09	Max-Peak	H	100	-	-52.03	-19.28	35.69	43.50	-7.81
378.62	Max-Peak	H	300	-	-69.30	-13.33	24.37	46.00	-21.63
995.65	Max-Peak	H	100	-	-73.06	-3.51	30.44	54.00	-23.56

Table 7-244. RSE below 1GHz CDD Primary (RU26 – Ch.40), with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 360 of 380

V 10.6 10/27/2023




Plot 7-1177. RSE below 1GHz CDD Primary (RU78 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
36.63	Max-Peak	V	100	-	-59.83	-17.48	29.69	40.00	-10.31
85.35	Max-Peak	V	100	-	-58.51	-20.96	27.52	40.00	-12.48
115.05	Max-Peak	H	200	-	-60.93	-18.90	27.17	43.50	-16.33
183.27	Max-Peak	H	200	-	-51.59	-19.26	36.14	43.50	-7.36
378.62	Max-Peak	H	100	-	-70.35	-13.33	23.32	46.00	-22.68
944.83	Max-Peak	H	100	-	-72.24	-4.27	30.49	46.00	-15.51

Table 7-245. RSE below 1GHz CDD Primary (RU78 – Ch.40), with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 361 of 380




Plot 7-1178. RSE below 1GHz CDD Primary (RU242 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
43.47	Max-Peak	V	100	-	-62.17	-15.46	29.37	40.00	-10.63
84.69	Max-Peak	V	100	-	-58.64	-21.16	27.20	40.00	-12.80
114.33	Max-Peak	H	200	-	-62.54	-18.78	25.68	43.50	-17.82
177.15	Max-Peak	H	200	-	-52.47	-19.69	34.84	43.50	-8.66
378.68	Max-Peak	H	100	-	-69.99	-13.33	23.69	46.00	-22.31
999.25	Max-Peak	V	200	-	-72.78	-3.56	30.65	54.00	-23.35

Table 7-246. RSE below 1GHz CDD Primary (RU242– Ch.40), with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 362 of 380

7.7.2 CDD Diversity Radiated Spurious Emissions (Below 1GHz)




Plot 7-1179. RSE below 1GHz CDD Diversity (RU26 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
36.33	Max-Peak	V	100	-	-59.84	-17.62	29.54	40.00	-10.46
85.65	Max-Peak	V	100	-	-58.42	-20.88	27.70	40.00	-12.30
116.13	Max-Peak	H	300	-	-62.02	-19.01	25.97	43.50	-17.53
184.65	Max-Peak	H	200	-	-51.90	-19.14	35.96	43.50	-7.54
227.31	Max-Peak	H	100	-	-58.54	-16.93	31.53	46.00	-14.47
913.81	Max-Peak	H	100	-	-72.92	-4.24	29.84	46.00	-16.16

Table 7-247. RSE below 1GHz CDD Diversity (RU26 – Ch.40), with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 363 of 380

V 10.6 10/27/2023




Plot 7-1180. RSE below 1GHz CDD Diversity (RU78 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
30.57	Max-Peak	V	300	-	-57.65	-19.28	30.07	40.00	-9.93
85.53	Max-Peak	V	100	-	-58.37	-20.92	27.72	40.00	-12.28
115.89	Max-Peak	H	300	-	-60.47	-18.97	27.56	43.50	-15.94
172.29	Max-Peak	H	200	-	-51.97	-20.04	34.99	43.50	-8.51
220.11	Max-Peak	H	100	-	-59.36	-17.42	30.22	46.00	-15.78
903.25	Max-Peak	H	200	-	-71.80	-4.30	30.90	46.00	-15.10

Table 7-248. RSE below 1GHz CDD Diversity (RU78– Ch.40), with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 364 of 380

V 10.6 10/27/2023



Plot 7-1181. RSE below 1GHz CDD Diversity (RU242 – Ch.40), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
36.09	Max-Peak	V	100	-	-59.72	-17.74	29.54	40.00	-10.46
62.01	Max-Peak	V	100	-	-65.38	-17.51	24.10	40.00	-15.90
114.45	Max-Peak	H	200	-	-62.04	-18.80	26.16	43.50	-17.34
179.97	Max-Peak	H	100	-	-52.53	-19.53	34.95	43.50	-8.55
378.68	Max-Peak	H	100	-	-68.45	-13.33	25.22	46.00	-20.78
973.03	Max-Peak	H	100	-	-73.10	-3.82	30.08	54.00	-23.92

Table 7-249. RSE below 1GHz CDD Diversity (RU242– Ch.40), with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 365 of 380

V 10.6 10/27/2023

7.8 AC Line Conducted Emissions Measurement

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. All data rates and modes were investigated for AC Line conducted spurious emissions.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-250. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024, Subclause 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 366 of 380

V 10.6 10/27/2023

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-8. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
2. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
3. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
4. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
5. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Correction Factor (dB)}$
6. $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
7. Traces shown in plots are made using quasi-peak and average detectors.
8. Deviations to the Specifications: None.

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 367 of 380

7.8.1 CDD Primary AC Line Conducted Emissions Measurement



Plot 7-1182. AC Line Conducted Plot with 11be CDD Primary – RU26 – Ch.40 (L1) with AC/DC Adapter


Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.16	FINAL	---	35.60	55.40	-19.80	L1	GND
0.16	FINAL	50.68	---	65.40	-14.72	L1	GND
0.24	FINAL	---	28.48	52.10	-23.62	L1	GND
0.24	FINAL	44.43	---	62.10	-17.67	L1	GND
0.51	FINAL	---	17.54	46.00	-28.46	L1	GND
0.51	FINAL	37.05	---	56.00	-18.95	L1	GND
1.35	FINAL	31.68	---	56.00	-24.32	L1	GND
1.35	FINAL	---	15.41	46.00	-30.59	L1	GND
5.08	FINAL	29.25	---	60.00	-30.75	L1	GND
5.08	FINAL	---	18.97	50.00	-31.03	L1	GND
16.15	FINAL	---	11.70	50.00	-38.30	L1	GND
16.15	FINAL	16.45	---	60.00	-43.55	L1	GND

Table 7-251. AC Line Conducted with 11be CDD Primary – RU26 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 368 of 380

V 10.6 10/27/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-1183. AC Line Conducted Plot with 11be CDD Primary – RU26 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	35.05	55.17	-20.12	N	GND
0.17	FINAL	52.12	---	65.17	-13.05	N	GND
0.24	FINAL	---	29.68	52.10	-22.42	N	GND
0.24	FINAL	46.14	---	62.10	-15.96	N	GND
0.51	FINAL	---	17.98	46.00	-28.02	N	GND
0.51	FINAL	36.79	---	56.00	-19.21	N	GND
1.33	FINAL	30.50	---	56.00	-25.50	N	GND
1.33	FINAL	---	14.27	46.00	-31.73	N	GND
5.08	FINAL	25.06	---	60.00	-34.94	N	GND
5.08	FINAL	---	12.88	50.00	-37.12	N	GND
16.14	FINAL	---	7.32	50.00	-42.68	N	GND
16.14	FINAL	12.92	---	60.00	-47.08	N	GND

Table 7-252. AC Line Conducted with 11be CDD Primary – RU26 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 369 of 380

V 10.6 10/27/2023



Plot 7-1184. AC Line Conducted Plot with 11be CDD Primary – RU78 – Ch.40 (L1) with AC/DC Adapter


Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	33.51	55.17	-21.66	L1	GND
0.17	FINAL	49.72	---	65.17	-15.45	L1	GND
0.24	FINAL	---	28.20	52.10	-23.90	L1	GND
0.24	FINAL	43.81	---	62.10	-18.29	L1	GND
0.51	FINAL	---	18.38	46.00	-27.62	L1	GND
0.51	FINAL	36.87	---	56.00	-19.13	L1	GND
1.33	FINAL	31.90	---	56.00	-24.10	L1	GND
1.33	FINAL	---	13.86	46.00	-32.14	L1	GND
5.08	FINAL	29.18	---	60.00	-30.82	L1	GND
5.08	FINAL	---	19.02	50.00	-30.98	L1	GND
16.15	FINAL	---	11.80	50.00	-38.20	L1	GND
16.15	FINAL	16.70	---	60.00	-43.30	L1	GND

Table 7-253. AC Line Conducted with 11be CDD Primary – RU78 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 370 of 380

V 10.6 10/27/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-1185. AC Line Conducted Plot with 11be CDD Primary – RU78 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.16	FINAL	---	35.38	55.40	-20.02	N	GND
0.16	FINAL	50.33	---	65.40	-15.07	N	GND
0.24	FINAL	---	28.66	52.10	-23.44	N	GND
0.24	FINAL	44.61	---	62.10	-17.49	N	GND
0.51	FINAL	---	18.33	46.00	-27.67	N	GND
0.51	FINAL	36.42	---	56.00	-19.58	N	GND
1.35	FINAL	30.28	---	56.00	-25.72	N	GND
1.35	FINAL	---	14.94	46.00	-31.06	N	GND
5.08	FINAL	25.85	---	60.00	-34.15	N	GND
5.08	FINAL	---	13.67	50.00	-36.33	N	GND
16.15	FINAL	---	7.61	50.00	-42.39	N	GND
16.15	FINAL	13.23	---	60.00	-46.77	N	GND

Table 7-254. AC Line Conducted with 11be CDD Primary – RU78 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 371 of 380




Plot 7-1186. AC Line Conducted Plot with 11be CDD Primary – RU242 – Ch.40 (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	33.52	55.17	-21.65	L1	GND
0.17	FINAL	50.15	---	65.17	-15.02	L1	GND
0.24	FINAL	---	28.35	52.10	-23.75	L1	GND
0.24	FINAL	44.30	---	62.10	-17.80	L1	GND
0.51	FINAL	---	17.90	46.00	-28.10	L1	GND
0.51	FINAL	36.93	---	56.00	-19.07	L1	GND
1.35	FINAL	31.72	---	56.00	-24.28	L1	GND
1.35	FINAL	---	15.65	46.00	-30.35	L1	GND
5.01	FINAL	28.94	---	60.00	-31.06	L1	GND
5.01	FINAL	---	18.77	50.00	-31.23	L1	GND
16.15	FINAL	---	11.96	50.00	-38.04	L1	GND
16.15	FINAL	16.70	---	60.00	-43.30	L1	GND

Table 7-255. AC Line Conducted with 11be CDD Primary – RU242 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 372 of 380

V 10.6 10/27/2023



Plot 7-1187. AC Line Conducted Plot with 11be CDD Primary – RU242 – Ch.40 (N) with AC/DC Adapter


Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.16	FINAL	---	35.85	55.40	-19.55	N	GND
0.16	FINAL	50.83	---	65.40	-14.57	N	GND
0.24	FINAL	---	28.92	52.10	-23.18	N	GND
0.24	FINAL	45.02	---	62.10	-17.08	N	GND
0.51	FINAL	---	18.61	46.00	-27.39	N	GND
0.51	FINAL	36.62	---	56.00	-19.38	N	GND
1.35	FINAL	30.50	---	56.00	-25.50	N	GND
1.35	FINAL	---	15.25	46.00	-30.75	N	GND
5.08	FINAL	25.46	---	60.00	-34.54	N	GND
5.08	FINAL	---	13.42	50.00	-36.58	N	GND
16.15	FINAL	---	7.53	50.00	-42.47	N	GND
16.15	FINAL	13.23	---	60.00	-46.77	N	GND

Table 7-256. AC Line Conducted with 11be CDD Primary – RU242 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 373 of 380

V 10.6 10/27/2023

7.8.2 CDD Diversity AC Line Conducted Emissions Measurement



Plot 7-1188. AC Line Conducted Plot with 11be CDD Diversity – RU26 – Ch.40 (L1) with AC/DC Adapter


Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.16	FINAL	---	35.60	55.40	-19.80	L1	GND
0.16	FINAL	50.68	---	65.40	-14.72	L1	GND
0.24	FINAL	---	28.48	52.10	-23.62	L1	GND
0.24	FINAL	44.43	---	62.10	-17.67	L1	GND
0.51	FINAL	---	17.54	46.00	-28.46	L1	GND
0.51	FINAL	37.05	---	56.00	-18.95	L1	GND
1.35	FINAL	31.68	---	56.00	-24.32	L1	GND
1.35	FINAL	---	15.41	46.00	-30.59	L1	GND
5.08	FINAL	29.25	---	60.00	-30.75	L1	GND
5.08	FINAL	---	18.97	50.00	-31.03	L1	GND
16.15	FINAL	---	11.70	50.00	-38.30	L1	GND
16.15	FINAL	16.45	---	60.00	-43.55	L1	GND

Table 7-257. AC Line Conducted with 11be CDD Diversity – RU26 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 374 of 380

V 10.6 10/27/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-1189. AC Line Conducted Plot with 11be CDD Diversity – RU26 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	35.05	55.17	-20.12	N	GND
0.17	FINAL	52.12	---	65.17	-13.05	N	GND
0.24	FINAL	---	29.68	52.10	-22.42	N	GND
0.24	FINAL	46.14	---	62.10	-15.96	N	GND
0.51	FINAL	---	17.98	46.00	-28.02	N	GND
0.51	FINAL	36.79	---	56.00	-19.21	N	GND
1.33	FINAL	30.50	---	56.00	-25.50	N	GND
1.33	FINAL	---	14.27	46.00	-31.73	N	GND
5.08	FINAL	25.06	---	60.00	-34.94	N	GND
5.08	FINAL	---	12.88	50.00	-37.12	N	GND
16.14	FINAL	---	7.32	50.00	-42.68	N	GND
16.14	FINAL	12.92	---	60.00	-47.08	N	GND

Table 7-258. AC Line Conducted with 11be CDD Diversity – RU26 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 375 of 380

V 10.6 10/27/2023



Plot 7-1190. AC Line Conducted Plot with 11be CDD Diversity – RU78 – Ch.40 (L1) with AC/DC Adapter


Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.16	FINAL	---	35.35	55.40	-20.05	L1	GND
0.16	FINAL	50.16	---	65.40	-15.24	L1	GND
0.24	FINAL	---	28.28	52.10	-23.82	L1	GND
0.24	FINAL	44.03	---	62.10	-18.07	L1	GND
0.51	FINAL	---	18.20	46.00	-27.80	L1	GND
0.51	FINAL	36.86	---	56.00	-19.14	L1	GND
1.35	FINAL	31.84	---	56.00	-24.16	L1	GND
1.35	FINAL	---	16.02	46.00	-29.98	L1	GND
5.07	FINAL	28.96	---	60.00	-31.04	L1	GND
5.07	FINAL	---	18.81	50.00	-31.19	L1	GND
16.17	FINAL	---	11.83	50.00	-38.17	L1	GND
16.17	FINAL	16.54	---	60.00	-43.46	L1	GND

Table 7-259. AC Line Conducted with 11be CDD Diversity – RU78 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 376 of 380

V 10.6 10/27/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-1191. AC Line Conducted Plot with 11be CDD Diversity – RU78 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.16	FINAL	---	36.11	55.40	-19.29	N	GND
0.16	FINAL	50.53	---	65.40	-14.87	N	GND
0.24	FINAL	---	29.35	52.10	-22.75	N	GND
0.24	FINAL	44.71	---	62.10	-17.39	N	GND
0.51	FINAL	---	19.50	46.00	-26.50	N	GND
0.51	FINAL	36.59	---	56.00	-19.41	N	GND
1.35	FINAL	30.61	---	56.00	-25.39	N	GND
1.35	FINAL	---	15.71	46.00	-30.29	N	GND
5.07	FINAL	25.49	---	60.00	-34.51	N	GND
5.07	FINAL	---	13.39	50.00	-36.61	N	GND
16.16	FINAL	---	7.37	50.00	-42.63	N	GND
16.16	FINAL	13.04	---	60.00	-46.96	N	GND

Table 7-260. AC Line Conducted with 11be CDD Diversity – RU78 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 377 of 380




Plot 7-1192. AC Line Conducted Plot with 11be CDD Diversity – RU242 – Ch.40 (L1) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.17	FINAL	---	33.68	55.17	-21.49	L1	GND
0.17	FINAL	50.05	---	65.17	-15.12	L1	GND
0.24	FINAL	---	28.47	52.10	-23.63	L1	GND
0.24	FINAL	44.09	---	62.10	-18.01	L1	GND
0.51	FINAL	37.05	---	56.00	-18.95	L1	GND
0.51	FINAL	---	18.52	46.00	-27.48	L1	GND
1.26	FINAL	31.86	---	56.00	-24.14	L1	GND
1.26	FINAL	---	16.88	46.00	-29.12	L1	GND
5.08	FINAL	---	18.93	50.00	-31.07	L1	GND
5.09	FINAL	29.23	---	60.00	-30.77	L1	GND
16.16	FINAL	---	11.66	50.00	-38.34	L1	GND
16.16	FINAL	16.50	---	60.00	-43.50	L1	GND

Table 7-261. AC Line Conducted with 11be CDD Diversity – RU242 – Ch.40 (L1) with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 378 of 380



Plot 7-1193. AC Line Conducted Plot with 11be CDD Diversity – RU242 – Ch.40 (N) with AC/DC Adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.16	FINAL	---	36.43	55.40	-18.97	N	GND
0.16	FINAL	51.02	---	65.40	-14.38	N	GND
0.24	FINAL	---	29.46	52.10	-22.64	N	GND
0.24	FINAL	45.05	---	62.10	-17.05	N	GND
0.51	FINAL	36.74	---	56.00	-19.26	N	GND
0.51	FINAL	---	19.27	46.00	-26.73	N	GND
1.35	FINAL	30.69	---	56.00	-25.31	N	GND
1.35	FINAL	---	15.72	46.00	-30.28	N	GND
5.09	FINAL	---	13.30	50.00	-36.70	N	GND
5.09	FINAL	25.33	---	60.00	-34.67	N	GND
16.16	FINAL	---	7.38	50.00	-42.62	N	GND
16.16	FINAL	13.00	---	60.00	-47.00	N	GND

Table 7-262. AC Line Conducted with 11be CDD Diversity – RU242 – Ch.40 (N) with AC/DC Adapter

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 379 of 380

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device FCC ID: BCGA3462** and **IC: 579C-A3462** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA3462 IC: 579C-A3462		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100082-23-R2.BCG	Test Dates: 08/22/2025 - 1/19/2025	EUT Type: Tablet Device	Page 380 of 380

V 10.6 10/27/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.