

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	7.22	-	-	-	-	2.60	9.82	14.00	4.18
6305	8.58	-	-	-	-	0.90	9.48	14.00	4.52
6385	9.16	-	-	-	-	0.90	10.06	14.00	3.94

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	10.17	-	-	-	-	2.60	12.77	14.00	1.23
6345	11.87	-	-	-	-	0.90	12.77	14.00	1.23

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	9.71	-	-	-	-	2.60	12.31	14.00	1.69
6345	12.01	-	-	-	-	0.90	12.91	14.00	1.09

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	10.10	-	-	-	-	2.60	12.70	14.00	1.30
6345	11.87	-	-	-	-	0.90	12.77	14.00	1.23

Maximum EIRP (U-NII-5) / VLP (continued)**Results: VLP / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	1.74	-	-	-	2.90	4.64	14.00	9.36
6175	-	1.65	-	-	-	2.90	4.55	14.00	9.45
6415	-	2.32	-	-	-	2.60	4.92	14.00	9.08

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6125	-	5.24	-	-	-	2.90	8.14	14.00	5.86
6285	-	5.54	-	-	-	2.60	8.14	14.00	5.86
6405	-	5.54	-	-	-	2.60	8.14	14.00	5.86

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	-	8.17	-	-	-	2.90	11.07	14.00	2.93
6305	-	8.63	-	-	-	2.60	11.23	14.00	2.77
6385	-	8.40	-	-	-	2.60	11.00	14.00	3.00

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	-	9.83	-	-	-	2.90	12.73	14.00	1.27
6345	-	10.39	-	-	-	2.60	12.99	14.00	1.01

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	2.39	-	-	-	2.90	5.29	14.00	8.71
6175	-	2.34	-	-	-	2.90	5.24	14.00	8.76
6415	-	2.49	-	-	-	2.60	5.09	14.00	8.91

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	-6.83	-	-	-	2.90	-3.93	14.00	17.93
6175	-	-6.80	-	-	-	2.90	-3.90	14.00	17.90
6415	-	-6.84	-	-	-	2.60	-4.24	14.00	18.24

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	-4.30	-	-	-	2.90	-1.40	14.00	15.40
6175	-	-4.14	-	-	-	2.90	-1.24	14.00	15.24
6415	-	-4.02	-	-	-	2.60	-1.42	14.00	15.42

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	-1.19	-	-	-	2.90	1.71	14.00	12.29
6175	-	-1.33	-	-	-	2.90	1.57	14.00	12.43
6415	-	-0.99	-	-	-	2.60	1.61	14.00	12.39

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	-2.35	-	-	-	2.90	0.55	14.00	13.45
6175	-	-2.17	-	-	-	2.90	0.73	14.00	13.27
6415	-	-1.97	-	-	-	2.60	0.63	14.00	13.37

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	-0.14	-	-	-	2.90	2.76	14.00	11.24
6175	-	-0.26	-	-	-	2.90	2.64	14.00	11.36
6415	-	0.20	-	-	-	2.60	2.80	14.00	11.20

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6125	-	5.15	-	-	-	2.90	8.05	14.00	5.95
6285	-	5.60	-	-	-	2.60	8.20	14.00	5.80
6405	-	5.55	-	-	-	2.60	8.15	14.00	5.85

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	-	8.30	-	-	-	2.90	11.20	14.00	2.80
6305	-	8.65	-	-	-	2.60	11.25	14.00	2.75
6385	-	8.42	-	-	-	2.60	11.02	14.00	2.98

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	-	6.98	-	-	-	2.90	9.88	14.00	4.12
6305	-	7.21	-	-	-	2.60	9.81	14.00	4.19
6385	-	7.30	-	-	-	2.60	9.90	14.00	4.10

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	-	10.00	-	-	-	2.90	12.90	14.00	1.10
6345	-	10.22	-	-	-	2.60	12.82	14.00	1.18

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	-	9.73	-	-	-	2.90	12.63	14.00	1.37
6345	-	10.18	-	-	-	2.60	12.78	14.00	1.22

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	-	10.06	-	-	-	2.90	12.96	14.00	1.04
6345	-	10.28	-	-	-	2.60	12.88	14.00	1.12

Maximum EIRP (U-NII-5) / VLP (continued)**Results: VLP / MIMO CDD**

Antenna Configuration:	MIMO CDD	Mode:	802.11a20
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-3.85	-3.88	-	-	-0.86	2.90	2.04	14.00	11.96
6175	-3.94	-3.85	-	-	-0.89	2.90	2.01	14.00	11.99
6415	-3.30	-2.93	-	-	-0.11	2.60	2.49	14.00	11.51

Antenna Configuration:	MIMO CDD	Mode:	802.11a40
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6125	-0.70	-0.74	-	-	2.28	2.90	5.18	14.00	8.82
6285	0.23	0.03	-	-	3.13	2.60	5.73	14.00	8.27
6405	-0.07	-0.19	-	-	2.87	2.60	5.47	14.00	8.53

Antenna Configuration:	MIMO CDD	Mode:	802.11a80
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	2.36	2.31	-	-	5.34	2.90	8.24	14.00	5.76
6305	3.01	3.12	-	-	6.06	2.60	8.66	14.00	5.34
6385	2.83	3.02	-	-	5.93	2.60	8.53	14.00	5.47

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11a160
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	4.68	5.17	-	-	7.92	2.90	10.82	14.00	3.18
6345	5.39	5.95	-	-	8.67	2.60	11.27	14.00	2.73

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-4.24	-3.80	-	-	-1.00	2.90	1.90	14.00	12.10
6175	-4.11	-3.69	-	-	-0.88	2.90	2.02	14.00	11.98
6415	-3.60	-2.83	-	-	-0.19	2.60	2.41	14.00	11.59

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6415	-9.36	-9.60	-	-	-6.47	2.60	-3.87	14.00	17.87

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-7.10	-7.36	-	-	-4.22	2.90	-1.32	14.00	15.32
6175	-6.92	-7.17	-	-	-4.04	2.90	-1.14	14.00	15.14
6415	-6.27	-6.27	-	-	-3.26	2.60	-0.66	14.00	14.66

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-8.15	-8.57	-	-	-5.34	2.90	-2.44	14.00	16.44
6175	-8.14	-8.41	-	-	-5.26	2.90	-2.36	14.00	16.36
6415	-7.29	-7.31	-	-	-4.29	2.60	-1.69	14.00	15.69

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-6.01	-6.23	-	-	-3.11	2.90	-0.21	14.00	14.21
6175	-6.11	-6.20	-	-	-3.15	2.90	-0.25	14.00	14.25
6415	-5.17	-5.16	-	-	-2.16	2.60	0.44	14.00	13.56

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6125	-1.36	-0.85	-	-	1.91	2.90	4.81	14.00	9.19
6285	-0.27	0.22	-	-	2.99	2.60	5.59	14.00	8.41
6405	-0.48	0.30	-	-	2.94	2.60	5.54	14.00	8.46

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	2.05	2.33	-	-	5.18	2.90	8.08	14.00	5.92
6305	2.40	3.02	-	-	5.71	2.60	8.31	14.00	5.69
6385	2.16	2.89	-	-	5.54	2.60	8.14	14.00	5.86

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	0.91	1.05	-	-	3.99	2.90	6.89	14.00	7.11
6305	1.80	1.77	-	-	4.79	2.60	7.39	14.00	6.61
6385	2.14	1.61	-	-	4.89	2.60	7.49	14.00	6.51

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	4.32	5.05	-	-	7.70	2.90	10.60	14.00	3.40
6345	5.07	6.18	-	-	8.65	2.60	11.25	14.00	2.75

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	3.37	3.33	-	-	6.35	2.90	9.25	14.00	4.75
6345	4.22	4.79	-	-	7.51	2.60	10.11	14.00	3.89

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	4.08	4.59	-	-	7.32	2.90	10.22	14.00	3.78
6345	5.02	5.51	-	-	8.25	2.60	10.85	14.00	3.15

Maximum EIRP (U-NII-5) / VLP (continued)**Results: VLP / MIMO SDM**

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-1.48	-0.75	-	-	1.91	2.75	4.66	14.00	9.34
6175	-1.32	-0.67	-	-	2.02	2.75	4.78	14.00	9.22
6415	-0.85	0.08	-	-	2.65	1.83	4.48	14.00	9.52

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6415	-9.34	-9.56	-	-	-6.44	1.83	-4.60	14.00	18.60

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-7.20	-7.25	-	-	-4.21	2.75	-1.46	14.00	15.46
6175	-7.24	-7.58	-	-	-4.40	2.75	-1.65	14.00	15.65
6415	-6.35	-6.41	-	-	-3.38	1.83	-1.54	14.00	15.54

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-3.90	-4.10	-	-	-0.99	2.75	1.76	14.00	12.24
6175	-3.91	-4.28	-	-	-1.08	2.75	1.67	14.00	12.33
6415	-3.13	-3.33	-	-	-0.22	1.83	1.61	14.00	12.39

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-5.20	-5.42	-	-	-2.30	2.75	0.45	14.00	13.55
6175	-5.18	-5.26	-	-	-2.21	2.75	0.54	14.00	13.46
6415	-4.34	-4.33	-	-	-1.32	1.83	0.51	14.00	13.49

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-3.05	-3.20	-	-	-0.12	2.75	2.64	14.00	11.36
6175	-3.12	-3.30	-	-	-0.19	2.75	2.56	14.00	11.44
6415	-2.19	-2.11	-	-	0.86	1.83	2.69	14.00	11.31

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6125	1.95	2.39	-	-	5.16	2.75	7.91	14.00	6.09
6285	2.54	3.04	-	-	5.78	1.83	7.62	14.00	6.38
6405	2.23	2.84	-	-	5.55	1.83	7.39	14.00	6.61

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	4.48	5.36	-	-	7.94	2.75	10.69	14.00	3.31
6305	5.31	6.36	-	-	8.86	1.83	10.69	14.00	3.31
6385	5.06	6.15	-	-	8.62	1.83	10.45	14.00	3.55

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	3.63	4.13	-	-	6.89	2.75	9.64	14.00	4.36
6305	4.21	4.88	-	-	7.57	1.83	9.40	14.00	4.60
6385	4.57	5.16	-	-	7.87	1.83	9.70	14.00	4.30

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	6.54	7.20	-	-	9.88	2.75	12.64	14.00	1.36
6345	7.24	8.09	-	-	10.69	1.83	12.52	14.00	1.48

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	6.32	6.79	-	-	9.56	2.75	12.31	14.00	1.69
6345	7.37	7.90	-	-	10.65	1.83	12.49	14.00	1.51

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	6.55	7.00	-	-	9.78	2.75	12.53	14.00	1.47
6345	7.51	7.95	-	-	10.73	1.83	12.56	14.00	1.44

Maximum EIRP (U-NII-5) / VLP (continued)**Results: VLP / TxBF**

Antenna Configuration:	TxBF	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-4.41	-4.01	-	-	-1.20	5.76	4.57	14.00	9.43
6175	-4.01	-3.67	-	-	-0.83	5.76	4.94	14.00	9.06
6415	-3.46	-2.80	-	-	-0.11	4.80	4.69	14.00	9.31

Antenna Configuration:	TxBF	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6125	-1.00	-0.61	-	-	2.21	5.76	7.97	14.00	6.03
6285	-0.08	0.26	-	-	3.10	4.80	7.90	14.00	6.10
6405	-0.55	0.09	-	-	2.79	4.80	7.59	14.00	6.41

Antenna Configuration:	TxBF	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	2.20	2.39	-	-	5.30	5.76	11.06	14.00	2.94
6305	2.61	3.08	-	-	5.85	4.80	10.66	14.00	3.34
6385	2.47	2.89	-	-	5.67	4.80	10.47	14.00	3.53

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	TxBF	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	3.36	4.07	-	-	6.74	5.76	12.50	14.00	1.50
6345	4.32	5.15	-	-	7.75	4.80	12.55	14.00	1.45

Maximum EIRP (U-NII-6) / LPI (continued)**4.3.2 6.425-6.525 GHz band (U-NII-6)****Results: LPI / SISO / Core 0**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	8.35	-	-	-	-	0.60	8.95	24.00	15.05
6475	8.39	-	-	-	-	0.60	8.99	24.00	15.01
6515	8.47	-	-	-	-	0.60	9.07	24.00	14.93

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	11.56	-	-	-	-	0.60	12.16	24.00	11.84
6485	11.67	-	-	-	-	0.60	12.27	24.00	11.73
6525	11.58	-	-	-	-	0.60	12.18	24.00	11.82

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	14.77	-	-	-	-	0.60	15.37	24.00	8.63

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	17.37	-	-	-	-	0.60	17.97	24.00	6.03

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	8.21	-	-	-	-	0.60	8.81	24.00	15.19
6475	8.36	-	-	-	-	0.60	8.96	24.00	15.04
6515	8.57	-	-	-	-	0.60	9.17	24.00	14.83

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-1.04	-	-	-	-	0.60	-0.44	24.00	24.44
6475	-0.86	-	-	-	-	0.60	-0.26	24.00	24.26
6515	-0.91	-	-	-	-	0.60	-0.31	24.00	24.31

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	1.95	-	-	-	-	0.60	2.55	24.00	21.45
6475	2.16	-	-	-	-	0.60	2.76	24.00	21.24
6515	2.11	-	-	-	-	0.60	2.71	24.00	21.29

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	5.16	-	-	-	-	0.60	5.76	24.00	18.24
6475	5.19	-	-	-	-	0.60	5.79	24.00	18.21
6515	5.14	-	-	-	-	0.60	5.74	24.00	18.26

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	3.82	-	-	-	-	0.60	4.42	24.00	19.58
6475	3.95	-	-	-	-	0.60	4.55	24.00	19.45
6515	3.90	-	-	-	-	0.60	4.50	24.00	19.50

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	6.19	-	-	-	-	0.60	6.79	24.00	17.21
6475	6.27	-	-	-	-	0.60	6.87	24.00	17.13
6515	6.10	-	-	-	-	0.60	6.70	24.00	17.30

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	11.69	-	-	-	-	0.60	12.29	24.00	11.71
6485	11.46	-	-	-	-	0.60	12.06	24.00	11.94
6525	11.44	-	-	-	-	0.60	12.04	24.00	11.96

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	14.54	-	-	-	-	0.60	15.14	24.00	8.86

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	13.45	-	-	-	-	0.60	14.05	24.00	9.95

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	17.32	-	-	-	-	0.60	17.92	24.00	6.08

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	15.87	-	-	-	-	0.60	16.47	24.00	7.53

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	16.87	-	-	-	-	0.60	17.47	24.00	6.53

Maximum EIRP (U-NII-6) / LPI (continued)**Results: LPI / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	6.45	-	-	-	2.60	9.05	24.00	14.95
6475	-	6.50	-	-	-	2.60	9.10	24.00	14.90
6515	-	6.25	-	-	-	2.60	8.85	24.00	15.15

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-	9.31	-	-	-	2.60	11.91	24.00	12.09
6485	-	9.39	-	-	-	2.60	11.99	24.00	12.01
6525	-	9.71	-	-	-	2.60	12.31	24.00	11.69

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	12.60	-	-	-	2.60	15.20	24.00	8.80

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	15.49	-	-	-	2.60	18.09	24.00	5.91

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	6.53	-	-	-	2.60	9.13	24.00	14.87
6475	-	6.63	-	-	-	2.60	9.23	24.00	14.77
6515	-	6.70	-	-	-	2.60	9.30	24.00	14.70

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	-3.03	-	-	-	2.60	-0.43	24.00	24.43
6475	-	-2.82	-	-	-	2.60	-0.22	24.00	24.22
6515	-	-2.73	-	-	-	2.60	-0.13	24.00	24.13

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	0.14	-	-	-	2.60	2.74	24.00	21.26
6475	-	0.27	-	-	-	2.60	2.87	24.00	21.13
6515	-	0.22	-	-	-	2.60	2.82	24.00	21.18

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	3.19	-	-	-	2.60	5.79	24.00	18.21
6475	-	3.06	-	-	-	2.60	5.66	24.00	18.34
6515	-	3.30	-	-	-	2.60	5.90	24.00	18.10

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	1.82	-	-	-	2.60	4.42	24.00	19.58
6475	-	1.93	-	-	-	2.60	4.53	24.00	19.47
6515	-	1.89	-	-	-	2.60	4.49	24.00	19.51

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	3.90	-	-	-	2.60	6.50	24.00	17.50
6475	-	3.94	-	-	-	2.60	6.54	24.00	17.46
6515	-	4.06	-	-	-	2.60	6.66	24.00	17.34

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-	9.41	-	-	-	2.60	12.01	24.00	11.99
6485	-	9.40	-	-	-	2.60	12.00	24.00	12.00
6525	-	9.76	-	-	-	2.60	12.36	24.00	11.64

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	12.68	-	-	-	2.60	15.28	24.00	8.72

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	11.28	-	-	-	2.60	13.88	24.00	10.12

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	15.36	-	-	-	2.60	17.96	24.00	6.04

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	14.28	-	-	-	2.60	16.88	24.00	7.12

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	14.74	-	-	-	2.60	17.34	24.00	6.66

Maximum EIRP (U-NII-6) / LPI (continued)**Results: LPI / MIMO CDD**

Antenna Configuration:	MIMO CDD	Mode:	802.11a20
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	0.64	1.26	-	-	3.97	2.60	6.57	24.00	17.43
6475	0.54	1.17	-	-	3.87	2.60	6.47	24.00	17.53
6515	0.39	1.28	-	-	3.86	2.60	6.46	24.00	17.54

Antenna Configuration:	MIMO CDD	Mode:	802.11a40
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	4.01	4.21	-	-	7.12	2.60	9.72	24.00	14.28
6485	4.19	4.20	-	-	7.20	2.60	9.80	24.00	14.20
6525	4.54	4.26	-	-	7.40	2.60	10.00	24.00	14.00

Antenna Configuration:	MIMO CDD	Mode:	802.11a80
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	7.26	7.59	-	-	10.43	2.60	13.03	24.00	10.97

Antenna Configuration:	MIMO CDD	Mode:	802.11a160
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	10.03	10.35	-	-	13.14	2.60	15.74	24.00	8.26

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	0.28	1.50	-	-	3.94	2.60	6.54	24.00	17.46
6475	0.17	1.42	-	-	3.85	2.60	6.45	24.00	17.55
6515	0.09	1.50	-	-	3.86	2.60	6.46	24.00	17.54

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-7.87	-7.85	-	-	-4.85	2.60	-2.25	24.00	26.25
6475	-8.14	-7.86	-	-	-4.99	2.60	-2.39	24.00	26.39
6515	-8.38	-7.87	-	-	-5.11	2.60	-2.51	24.00	26.51

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-5.34	-5.17	-	-	-2.25	2.60	0.35	24.00	23.65
6475	-5.33	-4.92	-	-	-2.11	2.60	0.49	24.00	23.51
6515	-5.54	-5.02	-	-	-2.26	2.60	0.34	24.00	23.66

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-2.17	-2.11	-	-	0.87	2.60	3.47	24.00	20.53
6475	-2.36	-1.95	-	-	0.85	2.60	3.45	24.00	20.55
6515	-2.29	-1.82	-	-	0.96	2.60	3.56	24.00	20.44

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-3.25	-3.30	-	-	-0.27	2.60	2.33	24.00	21.67
6475	-3.44	-3.18	-	-	-0.30	2.60	2.30	24.00	21.70
6515	-3.72	-3.13	-	-	-0.41	2.60	2.19	24.00	21.81

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-1.11	-1.16	-	-	1.87	2.60	4.47	24.00	19.53
6475	-1.23	-0.90	-	-	1.95	2.60	4.55	24.00	19.45
6515	-1.54	-0.96	-	-	1.77	2.60	4.37	24.00	19.63

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	3.15	4.34	-	-	6.79	2.60	9.39	24.00	14.61
6485	3.00	4.22	-	-	6.66	2.60	9.26	24.00	14.74
6525	3.94	4.64	-	-	7.26	2.60	9.86	24.00	14.14

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	6.58	7.50	-	-	10.07	2.60	12.67	24.00	11.33

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	5.98	6.30	-	-	9.15	2.60	11.75	24.00	12.25

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	9.69	10.31	-	-	13.02	2.60	15.62	24.00	8.38

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	8.76	8.91	-	-	11.84	2.60	14.44	24.00	9.56

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	9.53	9.71	-	-	12.61	2.60	15.21	24.00	8.79

Maximum EIRP (U-NII-6) / LPI (continued)**Results: LPI / MIMO SDM**

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	3.19	4.41	-	-	6.85	1.71	8.57	24.00	15.43
6475	3.17	4.30	-	-	6.77	1.71	8.48	24.00	15.52
6515	3.55	4.31	-	-	6.94	1.71	8.66	24.00	15.34

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-5.34	-5.16	-	-	-2.25	1.71	-0.53	24.00	24.53
6475	-5.25	-4.93	-	-	-2.08	1.71	-0.36	24.00	24.36
6515	-5.44	-4.83	-	-	-2.12	1.71	-0.40	24.00	24.40

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-2.36	-2.30	-	-	0.68	1.71	2.40	24.00	21.60
6475	-2.35	-2.00	-	-	0.83	1.71	2.55	24.00	21.45
6515	-2.42	-1.96	-	-	0.83	1.71	2.54	24.00	21.46

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	0.76	1.03	-	-	3.90	1.71	5.61	24.00	18.39
6475	0.51	1.10	-	-	3.83	1.71	5.54	24.00	18.46
6515	0.46	1.07	-	-	3.78	1.71	5.50	24.00	18.50

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-0.32	-0.23	-	-	2.74	1.71	4.45	24.00	19.55
6475	-0.73	-0.34	-	-	2.48	1.71	4.19	24.00	19.81
6515	-1.04	-0.44	-	-	2.28	1.71	4.00	24.00	20.00

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	1.85	2.20	-	-	5.02	1.71	6.74	24.00	17.26
6475	1.34	2.06	-	-	4.72	1.71	6.44	24.00	17.56
6515	1.29	2.03	-	-	4.68	1.71	6.40	24.00	17.60

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	6.21	7.25	-	-	9.73	1.71	11.44	24.00	12.56
6485	6.47	7.32	-	-	9.92	1.71	11.63	24.00	12.37
6525	6.97	7.69	-	-	10.34	1.71	12.05	24.00	11.95

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	9.71	10.55	-	-	13.13	1.71	14.84	24.00	9.16

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	9.04	9.04	-	-	12.05	1.71	13.76	24.00	10.24

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	12.36	13.17	-	-	15.79	1.71	17.50	24.00	6.50

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	11.90	12.02	-	-	14.96	1.71	16.68	24.00	7.32

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	12.36	12.57	-	-	15.46	1.71	17.17	24.00	6.83

Maximum EIRP (U-NII-6) / LPI (continued)**Results: LPI / TxBF**

Antenna Configuration:	TxBF	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	0.21	1.47	-	-	3.90	4.67	8.56	24.00	15.44
6475	0.13	1.41	-	-	3.83	4.67	8.50	24.00	15.50
6515	-0.14	1.28	-	-	3.64	4.67	8.31	24.00	15.69

Antenna Configuration:	TxBF	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	3.16	4.40	-	-	6.83	4.67	11.50	24.00	12.50
6485	3.02	4.21	-	-	6.65	4.67	11.32	24.00	12.68
6525	3.89	4.61	-	-	7.26	4.67	11.93	24.00	12.07

Antenna Configuration:	TxBF	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	6.66	7.54	-	-	10.12	4.67	14.79	24.00	9.21

Antenna Configuration:	TxBF	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	9.74	10.28	-	-	13.02	4.67	17.69	24.00	6.31

Maximum EIRP (U-NII-6) / SP (continued)**Results: ISSED / SP / SISO / Core 0**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	19.32	-	-	-	-	0.60	19.92	30.00	10.08
6475	19.35	-	-	-	-	0.60	19.95	30.00	10.05
6515	19.42	-	-	-	-	0.60	20.02	30.00	9.98

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	19.29	-	-	-	-	0.60	19.89	30.00	10.11
6485	19.36	-	-	-	-	0.60	19.96	30.00	10.04
6525	19.23	-	-	-	-	0.60	19.83	30.00	10.17

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	19.45	-	-	-	-	0.60	20.05	30.00	9.95

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.42	-	-	-	-	0.60	20.02	30.00	9.98

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	19.39	-	-	-	-	0.60	19.99	30.00	10.01
6475	19.05	-	-	-	-	0.60	19.65	30.00	10.35
6515	19.24	-	-	-	-	0.60	19.84	30.00	10.16

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	11.86	-	-	-	-	0.60	12.46	30.00	17.54
6475	11.93	-	-	-	-	0.60	12.53	30.00	17.47
6515	11.74	-	-	-	-	0.60	12.34	30.00	17.66

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	14.99	-	-	-	-	0.60	15.59	30.00	14.41
6475	14.87	-	-	-	-	0.60	15.47	30.00	14.53
6515	14.96	-	-	-	-	0.60	15.56	30.00	14.44

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	17.96	-	-	-	-	0.60	18.56	30.00	11.44
6475	17.89	-	-	-	-	0.60	18.49	30.00	11.51
6515	17.94	-	-	-	-	0.60	18.54	30.00	11.46

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	16.39	-	-	-	-	0.60	16.99	30.00	13.01
6475	16.31	-	-	-	-	0.60	16.91	30.00	13.09
6515	16.33	-	-	-	-	0.60	16.93	30.00	13.07

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	18.34	-	-	-	-	0.60	18.94	30.00	11.06
6475	18.30	-	-	-	-	0.60	18.90	30.00	11.10
6515	18.36	-	-	-	-	0.60	18.96	30.00	11.04

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	19.38	-	-	-	-	0.60	19.98	30.00	10.02
6485	19.08	-	-	-	-	0.60	19.68	30.00	10.32
6525	19.15	-	-	-	-	0.60	19.75	30.00	10.25

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	19.00	-	-	-	-	0.60	19.60	30.00	10.40

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	19.50	-	-	-	-	0.60	20.10	30.00	9.90

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.32	-	-	-	-	0.60	19.92	30.00	10.08

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.41	-	-	-	-	0.60	20.01	30.00	9.99

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.30	-	-	-	-	0.60	19.90	30.00	10.10

Maximum EIRP (U-NII-6) / SP (continued)**Results: ISSED / SP / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	19.27	-	-	-	2.60	21.87	30.00	8.13
6475	-	19.36	-	-	-	2.60	21.96	30.00	8.04
6515	-	19.32	-	-	-	2.60	21.92	30.00	8.08

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-	19.42	-	-	-	2.60	22.02	30.00	7.98
6485	-	19.46	-	-	-	2.60	22.06	30.00	7.94
6525	-	19.26	-	-	-	2.60	21.86	30.00	8.14

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	19.48	-	-	-	2.60	22.08	30.00	7.92

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	19.33	-	-	-	2.60	21.93	30.00	8.07

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	19.32	-	-	-	2.60	21.92	30.00	8.08
6475	-	19.44	-	-	-	2.60	22.04	30.00	7.96
6515	-	19.35	-	-	-	2.60	21.95	30.00	8.05

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	11.98	-	-	-	2.60	14.58	30.00	15.42
6475	-	11.94	-	-	-	2.60	14.54	30.00	15.46
6515	-	12.00	-	-	-	2.60	14.60	30.00	15.40

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	14.92	-	-	-	2.60	17.52	30.00	12.48
6475	-	14.88	-	-	-	2.60	17.48	30.00	12.52
6515	-	14.87	-	-	-	2.60	17.47	30.00	12.53

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	17.78	-	-	-	2.60	20.38	30.00	9.62
6475	-	17.93	-	-	-	2.60	20.53	30.00	9.47
6515	-	17.85	-	-	-	2.60	20.45	30.00	9.55

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	16.37	-	-	-	2.60	18.97	30.00	11.03
6475	-	16.35	-	-	-	2.60	18.95	30.00	11.05
6515	-	16.31	-	-	-	2.60	18.91	30.00	11.09

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	18.44	-	-	-	2.60	21.04	30.00	8.96
6475	-	18.31	-	-	-	2.60	20.91	30.00	9.09
6515	-	18.45	-	-	-	2.60	21.05	30.00	8.95

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-	19.29	-	-	-	2.60	21.89	30.00	8.11
6485	-	19.33	-	-	-	2.60	21.93	30.00	8.07
6525	-	19.48	-	-	-	2.60	22.08	30.00	7.92

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	19.32	-	-	-	2.60	21.92	30.00	8.08

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	19.43	-	-	-	2.60	22.03	30.00	7.97

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	19.48	-	-	-	2.60	22.08	30.00	7.92

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	19.45	-	-	-	2.60	22.05	30.00	7.95

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	19.32	-	-	-	2.60	21.92	30.00	8.08

Maximum EIRP (U-NII-6) / SP (continued)**Results: ISSED / SP / MIMO CDD**

Antenna Configuration:	MIMO CDD	Mode:	802.11a20
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	18.93	19.36	-	-	22.15	2.60	24.75	30.00	5.25
6475	19.03	19.32	-	-	22.19	2.60	24.79	30.00	5.21
6515	19.08	19.28	-	-	22.19	2.60	24.79	30.00	5.21

Antenna Configuration:	MIMO CDD	Mode:	802.11a40
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	19.09	19.38	-	-	22.25	2.60	24.85	30.00	5.15
6485	19.01	19.33	-	-	22.18	2.60	24.78	30.00	5.22
6525	18.86	19.28	-	-	22.07	2.60	24.67	30.00	5.33

Antenna Configuration:	MIMO CDD	Mode:	802.11a80
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	19.08	19.42	-	-	22.25	2.60	24.85	30.00	5.15

Antenna Configuration:	MIMO CDD	Mode:	802.11a160
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.03	19.36	-	-	22.19	2.60	24.79	30.00	5.21

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	18.35	19.42	-	-	21.90	2.60	24.50	30.00	5.50
6475	18.49	19.32	-	-	21.92	2.60	24.52	30.00	5.48
6515	18.72	19.34	-	-	22.05	2.60	24.65	30.00	5.35

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	9.99	10.29	-	-	13.13	2.60	15.73	30.00	14.27
6475	9.94	10.07	-	-	12.99	2.60	15.59	30.00	14.41
6515	10.00	10.25	-	-	13.10	2.60	15.70	30.00	14.30

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	12.47	12.79	-	-	15.63	2.60	18.23	30.00	11.77
6475	12.59	12.76	-	-	15.67	2.60	18.27	30.00	11.73
6515	12.49	12.69	-	-	15.57	2.60	18.17	30.00	11.83

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	15.62	15.95	-	-	18.79	2.60	21.39	30.00	8.61
6475	15.82	16.11	-	-	18.97	2.60	21.57	30.00	8.43
6515	15.86	16.14	-	-	18.98	2.60	21.58	30.00	8.42

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	14.38	14.72	-	-	17.55	2.60	20.15	30.00	9.85
6475	14.52	14.77	-	-	17.65	2.60	20.25	30.00	9.75
6515	14.55	14.88	-	-	17.73	2.60	20.33	30.00	9.67

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	16.78	17.13	-	-	19.95	2.60	22.55	30.00	7.45
6475	16.73	17.03	-	-	19.88	2.60	22.48	30.00	7.52
6515	16.77	17.01	-	-	19.88	2.60	22.48	30.00	7.52

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	18.52	19.40	-	-	21.99	2.60	24.59	30.00	5.41
6485	18.52	19.32	-	-	21.94	2.60	24.54	30.00	5.46
6525	18.83	19.50	-	-	22.17	2.60	24.77	30.00	5.23

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	18.39	19.26	-	-	21.84	2.60	24.44	30.00	5.56

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	19.38	19.38	-	-	22.37	2.60	24.97	30.00	5.03

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	18.79	19.48	-	-	22.16	2.60	24.76	30.00	5.24

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.32	19.48	-	-	22.39	2.60	24.99	30.00	5.01

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.26	19.32	-	-	22.26	2.60	24.86	30.00	5.14

Maximum EIRP (U-NII-6) / SP (continued)**Results: ISED / SP / MIMO SDM**

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	18.24	19.37	-	-	21.85	1.71	23.56	30.00	6.44
6475	18.39	19.27	-	-	21.85	1.71	23.56	30.00	6.44
6515	18.58	19.26	-	-	21.94	1.71	23.65	30.00	6.35

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	11.49	11.74	-	-	14.60	1.71	16.32	30.00	13.68
6475	11.66	11.86	-	-	14.77	1.71	16.48	30.00	13.52
6515	11.57	11.94	-	-	14.77	1.71	16.48	30.00	13.52

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	14.44	14.83	-	-	17.64	1.71	19.35	30.00	10.65
6475	14.56	14.82	-	-	17.69	1.71	19.40	30.00	10.60
6515	14.63	14.95	-	-	17.78	1.71	19.50	30.00	10.50

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	17.60	17.89	-	-	20.76	1.71	22.47	30.00	7.53
6475	17.57	17.79	-	-	20.68	1.71	22.39	30.00	7.61
6515	17.58	17.83	-	-	20.72	1.71	22.43	30.00	7.57

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	15.85	16.27	-	-	19.07	1.71	20.78	30.00	9.22
6475	15.97	16.29	-	-	19.14	1.71	20.86	30.00	9.14
6515	16.08	16.39	-	-	19.22	1.71	20.94	30.00	9.06

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	18.07	18.36	-	-	21.20	1.71	22.91	30.00	7.09
6475	17.99	18.29	-	-	21.14	1.71	22.85	30.00	7.15
6515	18.01	18.26	-	-	21.13	1.71	22.85	30.00	7.15

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	18.36	19.28	-	-	21.84	1.71	23.55	30.00	6.45
6485	18.60	19.38	-	-	21.99	1.71	23.71	30.00	6.29
6525	18.61	19.30	-	-	21.96	1.71	23.68	30.00	6.32

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	18.62	19.48	-	-	22.08	1.71	23.79	30.00	6.21

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	19.41	19.43	-	-	22.41	1.71	24.13	30.00	5.87

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	18.79	19.49	-	-	22.15	1.71	23.86	30.00	6.14

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.11	19.28	-	-	22.19	1.71	23.90	30.00	6.10

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.21	19.33	-	-	22.26	1.71	23.98	30.00	6.02

Maximum EIRP (U-NII-6) / SP (continued)**Results: ISED / SP / TxBF**

Antenna Configuration:	TxBF	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	18.42	19.48	-	-	21.97	4.67	26.64	30.00	3.36
6475	18.52	19.33	-	-	21.93	4.67	26.60	30.00	3.40
6515	18.74	19.36	-	-	22.07	4.67	26.74	30.00	3.26

Antenna Configuration:	TxBF	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	18.58	19.46	-	-	22.04	4.67	26.71	30.00	3.29
6485	18.58	19.31	-	-	21.95	4.67	26.62	30.00	3.38
6525	18.86	19.46	-	-	22.16	4.67	26.83	30.00	3.17

Antenna Configuration:	TxBF	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	18.51	19.29	-	-	21.92	4.67	26.59	30.00	3.41

Antenna Configuration:	TxBF	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	18.86	19.48	-	-	22.19	4.67	26.85	30.00	3.15

Maximum EIRP (U-NII-6) / VLP (continued)**Results: VLP / SISO / Core 0**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	4.29	-	-	-	-	0.60	4.89	14.00	9.11
6475	4.28	-	-	-	-	0.60	4.88	14.00	9.12
6515	4.43	-	-	-	-	0.60	5.03	14.00	8.97

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	7.52	-	-	-	-	0.60	8.12	14.00	5.88
6485	7.51	-	-	-	-	0.60	8.11	14.00	5.89
6525	7.66	-	-	-	-	0.60	8.26	14.00	5.74

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	10.66	-	-	-	-	0.60	11.26	14.00	2.74

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	12.23	-	-	-	-	0.60	12.83	14.00	1.17

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	4.36	-	-	-	-	0.60	4.96	14.00	9.04
6475	4.48	-	-	-	-	0.60	5.08	14.00	8.92
6515	4.45	-	-	-	-	0.60	5.05	14.00	8.95

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-5.01	-	-	-	-	0.60	-4.41	14.00	18.41
6475	-4.82	-	-	-	-	0.60	-4.22	14.00	18.22
6515	-4.90	-	-	-	-	0.60	-4.30	14.00	18.30

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-2.05	-	-	-	-	0.60	-1.45	14.00	15.45
6475	-1.88	-	-	-	-	0.60	-1.28	14.00	15.28
6515	-2.14	-	-	-	-	0.60	-1.54	14.00	15.54

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	1.29	-	-	-	-	0.60	1.89	14.00	12.11
6475	1.22	-	-	-	-	0.60	1.82	14.00	12.18
6515	1.15	-	-	-	-	0.60	1.75	14.00	12.25

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-0.19	-	-	-	-	0.60	0.41	14.00	13.59
6475	-0.12	-	-	-	-	0.60	0.48	14.00	13.52
6515	-0.05	-	-	-	-	0.60	0.55	14.00	13.45

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	2.23	-	-	-	-	0.60	2.83	14.00	11.17
6475	2.26	-	-	-	-	0.60	2.86	14.00	11.14
6515	2.20	-	-	-	-	0.60	2.80	14.00	11.20

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	7.27	-	-	-	-	0.60	7.87	14.00	6.13
6485	7.53	-	-	-	-	0.60	8.13	14.00	5.87
6525	7.46	-	-	-	-	0.60	8.06	14.00	5.94

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	10.70	-	-	-	-	0.60	11.30	14.00	2.70

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	9.40	-	-	-	-	0.60	10.00	14.00	4.00

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	12.28	-	-	-	-	0.60	12.88	14.00	1.12

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	11.99	-	-	-	-	0.60	12.59	14.00	1.41

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	12.17	-	-	-	-	0.60	12.77	14.00	1.23

Maximum EIRP (U-NII-6) / VLP (continued)**Results: VLP / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	2.16	-	-	-	2.60	4.76	14.00	9.24
6475	-	2.23	-	-	-	2.60	4.83	14.00	9.17
6515	-	2.31	-	-	-	2.60	4.91	14.00	9.09

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-	5.41	-	-	-	2.60	8.01	14.00	5.99
6485	-	5.44	-	-	-	2.60	8.04	14.00	5.96
6525	-	5.71	-	-	-	2.60	8.31	14.00	5.69

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	8.71	-	-	-	2.60	11.31	14.00	2.69

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	10.31	-	-	-	2.60	12.91	14.00	1.09

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	2.65	-	-	-	2.60	5.25	14.00	8.75
6475	-	2.69	-	-	-	2.60	5.29	14.00	8.71
6515	-	2.67	-	-	-	2.60	5.27	14.00	8.73

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	-7.10	-	-	-	2.60	-4.50	14.00	18.50
6475	-	-6.93	-	-	-	2.60	-4.33	14.00	18.33
6515	-	-6.79	-	-	-	2.60	-4.19	14.00	18.19

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	-3.83	-	-	-	2.60	-1.23	14.00	15.23
6475	-	-3.95	-	-	-	2.60	-1.35	14.00	15.35
6515	-	-3.81	-	-	-	2.60	-1.21	14.00	15.21

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	-0.78	-	-	-	2.60	1.82	14.00	12.18
6475	-	-0.89	-	-	-	2.60	1.71	14.00	12.29
6515	-	-0.76	-	-	-	2.60	1.84	14.00	12.16

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	-1.93	-	-	-	2.60	0.67	14.00	13.33
6475	-	-1.99	-	-	-	2.60	0.61	14.00	13.39
6515	-	-2.17	-	-	-	2.60	0.43	14.00	13.57

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	0.30	-	-	-	2.60	2.90	14.00	11.10
6475	-	0.01	-	-	-	2.60	2.61	14.00	11.39
6515	-	0.13	-	-	-	2.60	2.73	14.00	11.27

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-	5.44	-	-	-	2.60	8.04	14.00	5.96
6485	-	5.28	-	-	-	2.60	7.88	14.00	6.12
6525	-	5.78	-	-	-	2.60	8.38	14.00	5.62

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	8.72	-	-	-	2.60	11.32	14.00	2.68

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	7.24	-	-	-	2.60	9.84	14.00	4.16

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	10.20	-	-	-	2.60	12.80	14.00	1.20

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	10.26	-	-	-	2.60	12.86	14.00	1.14

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	10.28	-	-	-	2.60	12.88	14.00	1.12

Maximum EIRP (U-NII-6) / VLP (continued)**Results: VLP / MIMO CDD**

Antenna Configuration:	MIMO CDD	Mode:	802.11a20
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-3.21	-2.79	-	-	0.01	2.60	2.61	14.00	11.39
6475	-3.31	-2.82	-	-	-0.05	2.60	2.55	14.00	11.45
6515	-3.45	-2.78	-	-	-0.09	2.60	2.51	14.00	11.49

Antenna Configuration:	MIMO CDD	Mode:	802.11a40
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	0.07	0.40	-	-	3.24	2.60	5.84	14.00	8.16
6485	0.01	0.33	-	-	3.18	2.60	5.78	14.00	8.22
6525	0.15	0.64	-	-	3.41	2.60	6.01	14.00	7.99

Antenna Configuration:	MIMO CDD	Mode:	802.11a80
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	2.70	3.22	-	-	5.97	2.60	8.57	14.00	5.43

Antenna Configuration:	MIMO CDD	Mode:	802.11a160
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	5.96	6.21	-	-	9.07	2.60	11.67	14.00	2.33

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-3.42	-2.56	-	-	0.04	2.60	2.64	14.00	11.36
6475	-3.51	-2.54	-	-	0.02	2.60	2.62	14.00	11.38
6515	-3.92	-2.81	-	-	-0.32	2.60	2.28	14.00	11.72

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-9.43	-9.39	-	-	-6.41	2.60	-3.81	14.00	17.81
6475	-9.23	-8.93	-	-	-6.07	2.60	-3.47	14.00	17.47
6515	-9.39	-8.93	-	-	-6.15	2.60	-3.55	14.00	17.55

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-6.14	-6.04	-	-	-3.08	2.60	-0.48	14.00	14.48
6475	-6.31	-5.87	-	-	-3.07	2.60	-0.47	14.00	14.47
6515	-6.36	-5.89	-	-	-3.11	2.60	-0.51	14.00	14.51

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-7.22	-7.21	-	-	-4.21	2.60	-1.61	14.00	15.61
6475	-7.59	-7.15	-	-	-4.35	2.60	-1.75	14.00	15.75
6515	-7.89	-7.36	-	-	-4.61	2.60	-2.01	14.00	16.01

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-5.09	-4.94	-	-	-2.00	2.60	0.60	14.00	13.40
6475	-5.50	-4.83	-	-	-2.14	2.60	0.46	14.00	13.54
6515	-5.58	-4.89	-	-	-2.22	2.60	0.38	14.00	13.62

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-0.80	0.27	-	-	2.78	2.60	5.38	14.00	8.62
6485	-0.84	0.23	-	-	2.74	2.60	5.34	14.00	8.66
6525	-0.65	0.63	-	-	3.05	2.60	5.65	14.00	8.35

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	2.62	3.70	-	-	6.19	2.60	8.79	14.00	5.21

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	1.96	2.29	-	-	5.14	2.60	7.74	14.00	6.26

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	5.65	6.40	-	-	9.04	2.60	11.64	14.00	2.36

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	4.89	5.06	-	-	7.98	2.60	10.58	14.00	3.42

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	5.48	5.66	-	-	8.57	2.60	11.17	14.00	2.83

Maximum EIRP (U-NII-6) / VLP (continued)**Results: VLP / MIMO SDM**

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-0.64	0.47	-	-	2.96	1.71	4.68	14.00	9.32
6475	-0.68	0.43	-	-	2.92	1.71	4.63	14.00	9.37
6515	-1.08	0.23	-	-	2.63	1.71	4.34	14.00	9.66

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-9.25	-9.15	-	-	-6.19	1.71	-4.48	14.00	18.48
6475	-9.25	-8.85	-	-	-6.03	1.71	-4.32	14.00	18.32
6515	-9.30	-8.84	-	-	-6.06	1.71	-4.34	14.00	18.34

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-6.35	-6.23	-	-	-3.28	1.71	-1.57	14.00	15.57
6475	-6.34	-5.96	-	-	-3.14	1.71	-1.42	14.00	15.42
6515	-6.60	-6.13	-	-	-3.35	1.71	-1.63	14.00	15.63

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-3.17	-3.08	-	-	-0.11	1.71	1.60	14.00	12.40
6475	-3.27	-2.84	-	-	-0.04	1.71	1.67	14.00	12.33
6515	-3.35	-2.94	-	-	-0.13	1.71	1.59	14.00	12.41

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-4.23	-4.11	-	-	-1.16	1.71	0.56	14.00	13.44
6475	-4.94	-4.37	-	-	-1.64	1.71	0.07	14.00	13.93
6515	-4.97	-4.28	-	-	-1.60	1.71	0.11	14.00	13.89

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-2.05	-2.00	-	-	0.99	1.71	2.70	14.00	11.30
6475	-2.43	-1.84	-	-	0.88	1.71	2.60	14.00	11.40
6515	-2.50	-1.93	-	-	0.80	1.71	2.52	14.00	11.48

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	2.19	3.00	-	-	5.62	1.71	7.33	14.00	6.67
6485	2.49	3.20	-	-	5.84	1.71	7.56	14.00	6.44
6525	2.34	3.53	-	-	5.96	1.71	7.68	14.00	6.32

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	5.72	6.60	-	-	9.19	1.71	10.90	14.00	3.10

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	4.88	5.16	-	-	8.03	1.71	9.74	14.00	4.26

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	7.59	8.23	-	-	10.91	1.71	12.63	14.00	1.37

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	7.87	8.01	-	-	10.93	1.71	12.65	14.00	1.35

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	8.10	8.26	-	-	11.17	1.71	12.88	14.00	1.12

Maximum EIRP (U-NII-6) / VLP (continued)**Results: VLP / TxBF**

Antenna Configuration:	TxBF	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-3.51	-2.77	-	-	-0.12	4.67	4.55	14.00	9.45
6475	-3.41	-2.54	-	-	0.06	4.67	4.72	14.00	9.28
6515	-3.86	-2.81	-	-	-0.29	4.67	4.38	14.00	9.62

Antenna Configuration:	TxBF	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-0.74	0.19	-	-	2.76	4.67	7.42	14.00	6.58
6485	-0.72	0.22	-	-	2.79	4.67	7.45	14.00	6.55
6525	-0.57	0.63	-	-	3.08	4.67	7.75	14.00	6.25

Antenna Configuration:	TxBF	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	2.48	3.24	-	-	5.89	4.67	10.55	14.00	3.45

Antenna Configuration:	TxBF	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	4.51	5.08	-	-	7.79	4.67	12.46	14.00	1.54

Maximum EIRP (U-NII-7) / LPI (continued)**4.3.3 6.525-6.875 GHz band (U-NII-7)****Results: LPI / SISO / Core 0**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	8.10	-	-	-	-	0.60	8.70	24.00	15.30
6715	8.12	-	-	-	-	0.60	8.72	24.00	15.28
6875	7.51	-	-	-	-	1.50	9.01	24.00	14.99

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	11.48	-	-	-	-	0.60	12.08	24.00	11.92
6685	11.51	-	-	-	-	0.60	12.11	24.00	11.89
6845	11.42	-	-	-	-	0.60	12.02	24.00	11.98

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	14.56	-	-	-	-	0.60	15.16	24.00	8.84
6705	14.47	-	-	-	-	0.60	15.07	24.00	8.93
6865	13.61	-	-	-	-	1.50	15.11	24.00	8.89

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	17.16	-	-	-	-	0.60	17.76	24.00	6.24
6825	16.09	-	-	-	-	1.50	17.59	24.00	6.41

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	8.21	-	-	-	-	0.60	8.81	24.00	15.19
6715	8.40	-	-	-	-	0.60	9.00	24.00	15.00
6875	7.90	-	-	-	-	1.50	9.40	24.00	14.60

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-0.95	-	-	-	-	0.60	-0.35	24.00	24.35
6715	-0.69	-	-	-	-	0.60	-0.09	24.00	24.09
6875	-1.78	-	-	-	-	1.50	-0.28	24.00	24.28

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	2.04	-	-	-	-	0.60	2.64	24.00	21.36
6715	1.68	-	-	-	-	0.60	2.28	24.00	21.72
6875	1.14	-	-	-	-	1.50	2.64	24.00	21.36

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	4.85	-	-	-	-	0.60	5.45	24.00	18.55
6715	4.95	-	-	-	-	0.60	5.55	24.00	18.45
6875	4.27	-	-	-	-	1.50	5.77	24.00	18.23

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	3.85	-	-	-	-	0.60	4.45	24.00	19.55
6715	3.81	-	-	-	-	0.60	4.41	24.00	19.59
6875	3.22	-	-	-	-	1.50	4.72	24.00	19.28

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	5.88	-	-	-	-	0.60	6.48	24.00	17.52
6715	5.98	-	-	-	-	0.60	6.58	24.00	17.42
6875	5.08	-	-	-	-	1.50	6.58	24.00	17.42

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	11.58	-	-	-	-	0.60	12.18	24.00	11.82
6685	11.57	-	-	-	-	0.60	12.17	24.00	11.83
6845	11.45	-	-	-	-	0.60	12.05	24.00	11.95

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	14.46	-	-	-	-	0.60	15.06	24.00	8.94
6705	14.49	-	-	-	-	0.60	15.09	24.00	8.91
6865	13.76	-	-	-	-	1.50	15.26	24.00	8.74

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	13.02	-	-	-	-	0.60	13.62	24.00	10.38
6705	13.17	-	-	-	-	0.60	13.77	24.00	10.23
6865	12.17	-	-	-	-	1.50	13.67	24.00	10.33

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	17.25	-	-	-	-	0.60	17.85	24.00	6.15
6825	15.95	-	-	-	-	1.50	17.45	24.00	6.55

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	15.91	-	-	-	-	0.60	16.51	24.00	7.49
6825	14.77	-	-	-	-	1.50	16.27	24.00	7.73

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	16.69	-	-	-	-	0.60	17.29	24.00	6.71
6825	15.75	-	-	-	-	1.50	17.25	24.00	6.75

Maximum EIRP (U-NII-7) / LPI (continued)**Results: LPI / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	7.05	-	-	-	1.90	8.95	24.00	15.05
6715	-	6.86	-	-	-	1.90	8.76	24.00	15.24
6875	-	6.99	-	-	-	1.90	8.89	24.00	15.11

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-	9.98	-	-	-	1.90	11.88	24.00	12.12
6685	-	10.20	-	-	-	1.90	12.10	24.00	11.90
6845	-	9.94	-	-	-	1.90	11.84	24.00	12.16

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	12.68	-	-	-	2.60	15.28	24.00	8.72
6705	-	13.14	-	-	-	1.90	15.04	24.00	8.96
6865	-	13.08	-	-	-	1.90	14.98	24.00	9.02

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	16.20	-	-	-	1.90	18.10	24.00	5.90
6825	-	16.06	-	-	-	1.90	17.96	24.00	6.04

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	7.11	-	-	-	1.90	9.01	24.00	14.99
6715	-	6.96	-	-	-	1.90	8.86	24.00	15.14
6875	-	7.29	-	-	-	1.90	9.19	24.00	14.81

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	-2.38	-	-	-	1.90	-0.48	24.00	24.48
6715	-	-2.24	-	-	-	1.90	-0.34	24.00	24.34
6875	-	-1.80	-	-	-	1.90	0.10	24.00	23.90

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	0.83	-	-	-	1.90	2.73	24.00	21.27
6715	-	0.76	-	-	-	1.90	2.66	24.00	21.34
6875	-	0.83	-	-	-	1.90	2.73	24.00	21.27

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	3.82	-	-	-	1.90	5.72	24.00	18.28
6715	-	3.86	-	-	-	1.90	5.76	24.00	18.24
6875	-	4.14	-	-	-	1.90	6.04	24.00	17.96

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	2.36	-	-	-	1.90	4.26	24.00	19.74
6715	-	2.20	-	-	-	1.90	4.10	24.00	19.90
6875	-	2.70	-	-	-	1.90	4.60	24.00	19.40

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	4.61	-	-	-	1.90	6.51	24.00	17.49
6715	-	4.75	-	-	-	1.90	6.65	24.00	17.35
6875	-	4.68	-	-	-	1.90	6.58	24.00	17.42

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-	10.09	-	-	-	1.90	11.99	24.00	12.01
6685	-	10.09	-	-	-	1.90	11.99	24.00	12.01
6845	-	10.07	-	-	-	1.90	11.97	24.00	12.03

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	12.77	-	-	-	2.60	15.37	24.00	8.63
6705	-	13.16	-	-	-	1.90	15.06	24.00	8.94
6865	-	13.07	-	-	-	1.90	14.97	24.00	9.03

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	11.24	-	-	-	2.60	13.84	24.00	10.16
6705	-	11.72	-	-	-	1.90	13.62	24.00	10.38
6865	-	11.76	-	-	-	1.90	13.66	24.00	10.34

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	16.11	-	-	-	1.90	18.01	24.00	5.99
6825	-	16.12	-	-	-	1.90	18.02	24.00	5.98

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	14.73	-	-	-	1.90	16.63	24.00	7.37
6825	-	14.62	-	-	-	1.90	16.52	24.00	7.48

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	15.51	-	-	-	1.90	17.41	24.00	6.59
6825	-	15.39	-	-	-	1.90	17.29	24.00	6.71

Maximum EIRP (U-NII-7) / LPI (continued)**Results: LPI / MIMO CDD**

Antenna Configuration:	MIMO CDD	Mode:	802.11a20
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	0.47	1.30	-	-	3.91	1.90	5.81	24.00	18.19
6715	0.40	1.49	-	-	3.98	1.90	5.88	24.00	18.12
6875	0.40	1.21	-	-	3.83	1.90	5.73	24.00	18.27

Antenna Configuration:	MIMO CDD	Mode:	802.11a40
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	4.78	4.49	-	-	7.64	1.90	9.54	24.00	14.46
6685	4.63	4.28	-	-	7.46	1.90	9.36	24.00	14.64
6845	4.72	4.67	-	-	7.69	1.90	9.59	24.00	14.41

Antenna Configuration:	MIMO CDD	Mode:	802.11a80
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	7.07	7.31	-	-	10.18	2.60	12.78	24.00	11.22
6705	7.65	7.73	-	-	10.70	1.90	12.60	24.00	11.40
6865	6.99	7.39	-	-	10.20	1.90	12.10	24.00	11.90

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11a160
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	10.30	10.50	-	-	13.38	1.90	15.28	24.00	8.72
6825	9.59	9.94	-	-	12.75	1.90	14.65	24.00	9.35

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	0.50	1.76	-	-	4.19	1.90	6.09	24.00	17.91
6715	0.70	1.69	-	-	4.23	1.90	6.13	24.00	17.87
6875	0.60	1.39	-	-	4.02	1.90	5.92	24.00	18.08

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-8.12	-7.73	-	-	-4.91	1.90	-3.01	24.00	27.01
6715	-7.88	-7.43	-	-	-4.64	1.90	-2.74	24.00	26.74
6875	-8.34	-7.90	-	-	-5.10	1.90	-3.20	24.00	27.20

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-5.24	-4.75	-	-	-1.98	1.90	-0.08	24.00	24.08
6715	-5.33	-4.86	-	-	-2.08	1.90	-0.18	24.00	24.18
6875	-5.36	-4.95	-	-	-2.14	1.90	-0.24	24.00	24.24

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-2.03	-1.70	-	-	1.15	1.90	3.05	24.00	20.95
6715	-2.34	-1.77	-	-	0.96	1.90	2.86	24.00	21.14
6875	-2.06	-1.75	-	-	1.11	1.90	3.01	24.00	20.99

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-3.28	-3.08	-	-	-0.17	1.90	1.73	24.00	22.27
6715	-3.36	-3.00	-	-	-0.17	1.90	1.73	24.00	22.27
6875	-3.77	-3.14	-	-	-0.43	1.90	1.47	24.00	22.53

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-1.02	-0.81	-	-	2.10	1.90	4.00	24.00	20.00
6715	-1.22	-0.71	-	-	2.06	1.90	3.96	24.00	20.04
6875	-1.53	-1.01	-	-	1.75	1.90	3.65	24.00	20.35

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	3.94	4.64	-	-	7.31	1.90	9.21	24.00	14.79
6685	4.47	4.74	-	-	7.61	1.90	9.51	24.00	14.49
6845	4.27	4.57	-	-	7.41	1.90	9.31	24.00	14.69

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	6.80	7.46	-	-	10.13	2.60	12.73	24.00	11.27
6705	7.51	7.60	-	-	10.54	1.90	12.44	24.00	11.56
6865	6.93	7.26	-	-	10.10	1.90	12.00	24.00	12.00

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	5.71	6.07	-	-	8.91	2.60	11.51	24.00	12.49
6705	6.26	6.29	-	-	9.27	1.90	11.17	24.00	12.83
6865	5.64	5.88	-	-	8.72	1.90	10.62	24.00	13.38

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	10.46	10.59	-	-	13.53	1.90	15.43	24.00	8.57
6825	9.69	10.08	-	-	12.89	1.90	14.79	24.00	9.21

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	9.29	9.37	-	-	12.32	1.90	14.22	24.00	9.78
6825	8.27	8.55	-	-	11.41	1.90	13.31	24.00	10.69

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	10.13	10.16	-	-	13.12	1.90	15.02	24.00	8.98
6825	9.22	9.54	-	-	12.38	1.90	14.28	24.00	9.72

Maximum EIRP (U-NII-7) / LPI (continued)**Results: LPI / MIMO SDM**

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	3.88	4.69	-	-	7.31	1.30	8.61	24.00	15.39
6715	4.62	4.70	-	-	7.65	1.30	8.95	24.00	15.05
6875	3.83	4.37	-	-	7.08	1.70	8.78	24.00	15.22

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-5.20	-4.72	-	-	-1.94	1.30	-0.64	24.00	24.64
6715	-4.96	-4.59	-	-	-1.76	1.30	-0.46	24.00	24.46
6875	-5.37	-4.94	-	-	-2.14	1.70	-0.44	24.00	24.44

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-2.13	-1.78	-	-	1.06	1.30	2.35	24.00	21.65
6715	-2.30	-1.77	-	-	0.98	1.30	2.28	24.00	21.72
6875	-2.40	-1.98	-	-	0.82	1.70	2.53	24.00	21.47

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	0.78	1.27	-	-	4.04	1.30	5.34	24.00	18.66
6715	0.82	1.35	-	-	4.10	1.30	5.40	24.00	18.60
6875	0.89	1.22	-	-	4.07	1.70	5.78	24.00	18.22

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-0.36	-0.01	-	-	2.82	1.30	4.12	24.00	19.88
6715	-0.82	-0.20	-	-	2.51	1.30	3.81	24.00	20.19
6875	-0.44	0.02	-	-	2.80	1.70	4.51	24.00	19.49

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	1.96	2.21	-	-	5.09	1.30	6.39	24.00	17.61
6715	1.44	2.15	-	-	4.82	1.30	6.12	24.00	17.88
6875	1.19	1.70	-	-	4.46	1.70	6.17	24.00	17.83

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	7.05	7.75	-	-	10.41	1.30	11.71	24.00	12.29
6685	7.32	7.62	-	-	10.47	1.30	11.76	24.00	12.24
6845	7.41	7.72	-	-	10.57	1.30	11.87	24.00	12.13

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	9.93	10.51	-	-	13.23	1.71	14.94	24.00	9.06
6705	10.65	10.77	-	-	13.71	1.30	15.01	24.00	8.99
6865	9.92	10.18	-	-	13.05	1.70	14.75	24.00	9.25

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	8.89	9.09	-	-	11.99	1.71	13.70	24.00	10.30
6705	9.25	9.29	-	-	12.28	1.30	13.57	24.00	10.43
6865	8.65	8.90	-	-	11.78	1.70	13.48	24.00	10.52

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	13.30	13.58	-	-	16.45	1.30	17.74	24.00	6.26
6825	12.64	13.06	-	-	15.86	1.70	17.56	24.00	6.44

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	12.11	12.18	-	-	15.15	1.30	16.44	24.00	7.56
6825	11.32	11.64	-	-	14.48	1.70	16.19	24.00	7.81

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	13.08	13.16	-	-	16.13	1.30	17.43	24.00	6.57
6825	12.19	12.60	-	-	15.41	1.70	17.11	24.00	6.89

Maximum EIRP (U-NII-7) / LPI (continued)**Results: LPI / TxBF**

Antenna Configuration:	TxBF	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	0.50	1.77	-	-	4.19	4.28	8.47	24.00	15.53
6715	0.69	1.70	-	-	4.23	4.28	8.51	24.00	15.49
6875	0.61	1.40	-	-	4.03	4.71	8.74	24.00	15.26

Antenna Configuration:	TxBF	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	4.00	4.68	-	-	7.32	4.28	11.61	24.00	12.39
6685	4.54	4.76	-	-	7.64	4.28	11.92	24.00	12.08
6845	4.32	4.61	-	-	7.45	4.28	11.74	24.00	12.26

Antenna Configuration:	TxBF	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	6.87	7.44	-	-	10.17	4.67	14.84	24.00	9.16
6705	7.55	7.61	-	-	10.58	4.28	14.87	24.00	9.13
6865	6.96	7.30	-	-	10.13	4.71	14.84	24.00	9.16

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	TxBF	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	10.40	10.59	-	-	13.49	4.28	17.78	24.00	6.22
6825	9.79	10.11	-	-	12.96	4.71	17.67	24.00	6.33

Maximum EIRP (U-NII-7) / SP (continued)**Results: SP / SISO / Core 0**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	19.50	-	-	-	-	0.60	20.10	30.00	9.90
6715	19.24	-	-	-	-	0.60	19.84	30.00	10.16
6855	19.16	-	-	-	-	0.60	19.76	30.00	10.24

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	19.16	-	-	-	-	0.60	19.76	30.00	10.24
6685	19.06	-	-	-	-	0.60	19.66	30.00	10.34
6845	19.49	-	-	-	-	0.60	20.09	30.00	9.91

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	19.36	-	-	-	-	0.60	19.96	30.00	10.04
6625	19.46	-	-	-	-	0.60	20.06	30.00	9.94
6705	19.23	-	-	-	-	0.60	19.83	30.00	10.17
6785	19.13	-	-	-	-	0.60	19.73	30.00	10.27

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.45	-	-	-	-	0.60	20.05	30.00	9.95

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	19.20	-	-	-	-	0.60	19.80	30.00	10.20
6715	19.32	-	-	-	-	0.60	19.92	30.00	10.08
6855	19.26	-	-	-	-	0.60	19.86	30.00	10.14

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	11.62	-	-	-	-	0.60	12.22	30.00	17.78
6715	11.86	-	-	-	-	0.60	12.46	30.00	17.54
6855	11.99	-	-	-	-	0.60	12.59	30.00	17.41

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	14.81	-	-	-	-	0.60	15.41	30.00	14.59
6715	14.97	-	-	-	-	0.60	15.57	30.00	14.43
6855	14.97	-	-	-	-	0.60	15.57	30.00	14.43

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	18.00	-	-	-	-	0.60	18.60	30.00	11.40
6715	17.94	-	-	-	-	0.60	18.54	30.00	11.46
6855	17.59	-	-	-	-	0.60	18.19	30.00	11.81

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	16.48	-	-	-	-	0.60	17.08	30.00	12.92
6715	16.46	-	-	-	-	0.60	17.06	30.00	12.94
6855	16.33	-	-	-	-	0.60	16.93	30.00	13.07

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	18.45	-	-	-	-	0.60	19.05	30.00	10.95
6715	18.33	-	-	-	-	0.60	18.93	30.00	11.07
6855	18.20	-	-	-	-	0.60	18.80	30.00	11.20

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	19.23	-	-	-	-	0.60	19.83	30.00	10.17
6685	19.37	-	-	-	-	0.60	19.97	30.00	10.03
6845	19.25	-	-	-	-	0.60	19.85	30.00	10.15

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	19.17	-	-	-	-	0.60	19.77	30.00	10.23
6625	19.47	-	-	-	-	0.60	20.07	30.00	9.93
6705	19.45	-	-	-	-	0.60	20.05	30.00	9.95
6785	19.34	-	-	-	-	0.60	19.94	30.00	10.06

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	19.35	-	-	-	-	0.60	19.95	30.00	10.05
6625	19.47	-	-	-	-	0.60	20.07	30.00	9.93
6705	19.34	-	-	-	-	0.60	19.94	30.00	10.06
6785	19.35	-	-	-	-	0.60	19.95	30.00	10.05

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.35	-	-	-	-	0.60	19.95	30.00	10.05

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.40	-	-	-	-	0.60	20.00	30.00	10.00

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.35	-	-	-	-	0.60	19.95	30.00	10.05

Maximum EIRP (U-NII-7) / SP (continued)**Results: SP / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	19.41	-	-	-	1.90	21.31	30.00	8.69
6715	-	19.42	-	-	-	1.90	21.32	30.00	8.68
6855	-	19.40	-	-	-	1.90	21.30	30.00	8.70

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-	19.31	-	-	-	1.90	21.21	30.00	8.79
6685	-	19.38	-	-	-	1.90	21.28	30.00	8.72
6845	-	19.30	-	-	-	1.90	21.20	30.00	8.80

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	19.37	-	-	-	2.60	21.97	30.00	8.03
6625	-	19.47	-	-	-	1.90	21.37	30.00	8.63
6705	-	19.48	-	-	-	1.90	21.38	30.00	8.62
6785	-	19.46	-	-	-	1.90	21.36	30.00	8.64

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	19.38	-	-	-	1.90	21.28	30.00	8.72

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	19.48	-	-	-	1.90	21.38	30.00	8.62
6715	-	19.40	-	-	-	1.90	21.30	30.00	8.70
6855	-	19.42	-	-	-	1.90	21.32	30.00	8.68

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	11.88	-	-	-	1.90	13.78	30.00	16.22
6715	-	11.93	-	-	-	1.90	13.83	30.00	16.17
6855	-	11.78	-	-	-	1.90	13.68	30.00	16.32

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	14.80	-	-	-	1.90	16.70	30.00	13.30
6715	-	14.86	-	-	-	1.90	16.76	30.00	13.24
6855	-	14.95	-	-	-	1.90	16.85	30.00	13.15

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	17.93	-	-	-	1.90	19.83	30.00	10.17
6715	-	17.87	-	-	-	1.90	19.77	30.00	10.23
6855	-	17.82	-	-	-	1.90	19.72	30.00	10.28

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	16.25	-	-	-	1.90	18.15	30.00	11.85
6715	-	16.35	-	-	-	1.90	18.25	30.00	11.75
6855	-	16.46	-	-	-	1.90	18.36	30.00	11.64

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	18.39	-	-	-	1.90	20.29	30.00	9.71
6715	-	18.37	-	-	-	1.90	20.27	30.00	9.73
6855	-	18.29	-	-	-	1.90	20.19	30.00	9.81

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-	19.26	-	-	-	1.90	21.16	30.00	8.84
6685	-	19.25	-	-	-	1.90	21.15	30.00	8.85
6845	-	19.38	-	-	-	1.90	21.28	30.00	8.72

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	19.49	-	-	-	2.60	22.09	30.00	7.91
6625	-	19.48	-	-	-	1.90	21.38	30.00	8.62
6705	-	19.36	-	-	-	1.90	21.26	30.00	8.74
6785	-	19.33	-	-	-	1.90	21.23	30.00	8.77

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	19.32	-	-	-	2.60	21.92	30.00	8.08
6625	-	19.46	-	-	-	1.90	21.36	30.00	8.64
6705	-	19.42	-	-	-	1.90	21.32	30.00	8.68
6785	-	19.44	-	-	-	1.90	21.34	30.00	8.66

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	19.50	-	-	-	1.90	21.40	30.00	8.60

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	19.46	-	-	-	1.90	21.36	30.00	8.64

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	19.33	-	-	-	1.90	21.23	30.00	8.77

Maximum EIRP (U-NII-7) / SP (continued)**Results: SP / MIMO CDD**

Antenna Configuration:	MIMO CDD	Mode:	802.11a20
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	18.90	19.28	-	-	22.09	1.90	23.99	30.00	6.01
6715	19.16	19.40	-	-	22.29	1.90	24.19	30.00	5.81
6855	18.79	19.33	-	-	22.07	1.90	23.97	30.00	6.03

Antenna Configuration:	MIMO CDD	Mode:	802.11a40
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	18.83	19.32	-	-	22.10	1.90	24.00	30.00	6.00
6685	18.88	19.20	-	-	22.05	1.90	23.95	30.00	6.05
6845	18.59	19.08	-	-	21.84	1.90	23.74	30.00	6.26

Antenna Configuration:	MIMO CDD	Mode:	802.11a80
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	18.99	19.39	-	-	22.20	2.60	24.80	30.00	5.20
6625	19.10	19.29	-	-	22.20	1.90	24.10	30.00	5.90
6705	19.08	19.44	-	-	22.27	1.90	24.17	30.00	5.83
6785	18.92	19.30	-	-	22.12	1.90	24.02	30.00	5.98

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11a160
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	18.99	19.26	-	-	22.09	1.90	23.99	30.00	6.01

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	18.59	19.27	-	-	21.94	1.90	23.84	30.00	6.16
6715	19.23	19.41	-	-	22.31	1.90	24.21	30.00	5.79
6855	18.85	19.37	-	-	22.10	1.90	24.00	30.00	6.00

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	10.30	10.59	-	-	13.46	1.90	15.36	30.00	14.64
6715	10.29	10.30	-	-	13.31	1.90	15.21	30.00	14.79
6855	9.78	10.40	-	-	13.11	1.90	15.01	30.00	14.99

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	12.75	13.12	-	-	15.92	1.90	17.82	30.00	12.18
6715	12.96	13.16	-	-	16.05	1.90	17.95	30.00	12.05
6855	12.59	13.23	-	-	15.93	1.90	17.83	30.00	12.17

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	15.97	16.26	-	-	19.10	1.90	21.00	30.00	9.00
6715	16.15	16.39	-	-	19.26	1.90	21.16	30.00	8.84
6855	15.77	16.32	-	-	19.04	1.90	20.94	30.00	9.06

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	14.46	14.82	-	-	17.64	1.90	19.54	30.00	10.46
6715	14.62	14.84	-	-	17.74	1.90	19.64	30.00	10.36
6855	14.28	14.87	-	-	17.59	1.90	19.49	30.00	10.51

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	16.85	17.17	-	-	20.01	1.90	21.91	30.00	8.09
6715	17.06	17.38	-	-	20.22	1.90	22.12	30.00	7.88
6855	16.66	17.28	-	-	19.99	1.90	21.89	30.00	8.11

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	18.62	19.32	-	-	21.99	1.90	23.89	30.00	6.11
6685	19.00	19.28	-	-	22.15	1.90	24.05	30.00	5.95
6845	19.07	19.46	-	-	22.27	1.90	24.17	30.00	5.83

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	18.62	19.25	-	-	21.93	2.60	24.53	30.00	5.47
6625	19.16	19.43	-	-	22.28	1.90	24.18	30.00	5.82
6705	19.07	19.32	-	-	22.19	1.90	24.09	30.00	5.91
6785	19.20	19.50	-	-	22.34	1.90	24.24	30.00	5.76

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	19.26	19.41	-	-	22.33	2.60	24.93	30.00	5.07
6625	19.34	19.35	-	-	22.34	1.90	24.24	30.00	5.76
6705	19.21	19.39	-	-	22.31	1.90	24.21	30.00	5.79
6785	19.08	19.35	-	-	22.22	1.90	24.12	30.00	5.88

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.05	19.28	-	-	22.15	1.90	24.05	30.00	5.95

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.26	19.43	-	-	22.34	1.90	24.24	30.00	5.76

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.22	19.32	-	-	22.28	1.90	24.18	30.00	5.82

Maximum EIRP (U-NII-7) / SP (continued)**Results: SP / MIMO SDM**

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	18.72	19.43	-	-	22.08	1.30	23.38	30.00	6.62
6715	19.15	19.34	-	-	22.25	1.30	23.55	30.00	6.45
6855	18.93	19.47	-	-	22.21	1.30	23.51	30.00	6.49

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	11.51	11.86	-	-	14.70	1.30	16.00	30.00	14.00
6715	11.79	11.88	-	-	14.85	1.30	16.15	30.00	13.85
6855	11.06	11.70	-	-	14.39	1.30	15.69	30.00	14.31

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	14.50	14.88	-	-	17.68	1.30	18.98	30.00	11.02
6715	14.69	14.87	-	-	17.76	1.30	19.06	30.00	10.94
6855	14.25	14.87	-	-	17.58	1.30	18.88	30.00	11.12

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	17.65	17.98	-	-	20.81	1.30	22.11	30.00	7.89
6715	17.67	17.89	-	-	20.75	1.30	22.05	30.00	7.95
6855	17.38	17.94	-	-	20.68	1.30	21.98	30.00	8.02

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	15.97	16.34	-	-	19.15	1.30	20.45	30.00	9.55
6715	16.12	16.31	-	-	19.19	1.30	20.49	30.00	9.51
6855	15.75	16.37	-	-	19.05	1.30	20.35	30.00	9.65

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	18.12	18.42	-	-	21.25	1.30	22.55	30.00	7.45
6715	17.97	18.33	-	-	21.14	1.30	22.44	30.00	7.56
6855	17.88	18.44	-	-	21.17	1.30	22.47	30.00	7.53

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	18.72	19.41	-	-	22.06	1.30	23.36	30.00	6.64
6685	19.06	19.34	-	-	22.20	1.30	23.50	30.00	6.50
6845	18.85	19.36	-	-	22.11	1.30	23.41	30.00	6.59

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	18.78	19.43	-	-	22.11	1.71	23.82	30.00	6.18
6625	19.09	19.36	-	-	22.23	1.30	23.53	30.00	6.47
6705	19.15	19.47	-	-	22.31	1.30	23.61	30.00	6.39
6785	19.07	19.42	-	-	22.26	1.30	23.56	30.00	6.44

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	19.30	19.41	-	-	22.36	1.71	24.08	30.00	5.92
6625	19.36	19.34	-	-	22.35	1.30	23.65	30.00	6.35
6705	19.22	19.42	-	-	22.32	1.30	23.62	30.00	6.38
6785	19.10	19.39	-	-	22.24	1.30	23.54	30.00	6.46

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.00	19.27	-	-	22.12	1.30	23.41	30.00	6.59

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.30	19.45	-	-	22.35	1.30	23.65	30.00	6.35

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.23	19.32	-	-	22.26	1.30	23.56	30.00	6.44

Maximum EIRP (U-NII-7) / SP (continued)**Results: SP / TxBF**

Antenna Configuration:	TxBF	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	18.63	19.28	-	-	21.97	4.28	26.25	30.00	3.75
6715	19.31	19.45	-	-	22.37	4.28	26.65	30.00	3.35
6855	18.88	19.38	-	-	22.13	4.28	26.41	30.00	3.59

Antenna Configuration:	TxBF	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	18.68	19.31	-	-	22.00	4.28	26.29	30.00	3.71
6685	19.29	19.50	-	-	22.39	4.28	26.67	30.00	3.33
6845	18.88	19.25	-	-	22.05	4.28	26.33	30.00	3.67

Antenna Configuration:	TxBF	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	18.65	19.24	-	-	21.95	4.67	26.62	30.00	3.38
6625	19.20	19.41	-	-	22.30	4.28	26.58	30.00	3.42
6705	19.32	19.50	-	-	22.41	4.28	26.70	30.00	3.30
6785	19.15	19.48	-	-	22.32	4.28	26.61	30.00	3.39

Antenna Configuration:	TxBF	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.05	19.27	-	-	22.16	4.28	26.45	30.00	3.55

Maximum EIRP (U-NII-7) / VLP (continued)**Results: VLP / SISO / Core 0**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	4.05	-	-	-	-	0.60	4.65	14.00	9.35
6715	4.14	-	-	-	-	0.60	4.74	14.00	9.26
6875	3.47	-	-	-	-	1.50	4.97	14.00	9.03

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	7.50	-	-	-	-	0.60	8.10	14.00	5.90
6685	7.42	-	-	-	-	0.60	8.02	14.00	5.98
6845	7.41	-	-	-	-	0.60	8.01	14.00	5.99

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	10.39	-	-	-	-	0.60	10.99	14.00	3.01
6705	10.38	-	-	-	-	0.60	10.98	14.00	3.02
6865	9.56	-	-	-	-	1.50	11.06	14.00	2.94

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	12.28	-	-	-	-	0.60	12.88	14.00	1.12
6825	11.25	-	-	-	-	1.50	12.75	14.00	1.25

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	4.37	-	-	-	-	0.60	4.97	14.00	9.03
6715	4.45	-	-	-	-	0.60	5.05	14.00	8.95
6875	3.86	-	-	-	-	1.50	5.36	14.00	8.64

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-4.84	-	-	-	-	0.60	-4.24	14.00	18.24
6715	-4.75	-	-	-	-	0.60	-4.15	14.00	18.15
6875	-5.78	-	-	-	-	1.50	-4.28	14.00	18.28

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-2.14	-	-	-	-	0.60	-1.54	14.00	15.54
6715	-1.92	-	-	-	-	0.60	-1.32	14.00	15.32
6875	-2.89	-	-	-	-	1.50	-1.39	14.00	15.39

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	0.94	-	-	-	-	0.60	1.54	14.00	12.46
6715	1.02	-	-	-	-	0.60	1.62	14.00	12.38
6875	0.33	-	-	-	-	1.50	1.83	14.00	12.17

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-0.33	-	-	-	-	0.60	0.27	14.00	13.73
6715	-0.10	-	-	-	-	0.60	0.50	14.00	13.50
6875	-0.74	-	-	-	-	1.50	0.76	14.00	13.24

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	2.09	-	-	-	-	0.60	2.69	14.00	11.31
6715	1.62	-	-	-	-	0.60	2.22	14.00	11.78
6875	1.14	-	-	-	-	1.50	2.64	14.00	11.36

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	7.49	-	-	-	-	0.60	8.09	14.00	5.91
6685	7.52	-	-	-	-	0.60	8.12	14.00	5.88
6845	7.41	-	-	-	-	0.60	8.01	14.00	5.99

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	10.52	-	-	-	-	0.60	11.12	14.00	2.88
6705	10.46	-	-	-	-	0.60	11.06	14.00	2.94
6865	9.79	-	-	-	-	1.50	11.29	14.00	2.71

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	9.04	-	-	-	-	0.60	9.64	14.00	4.36
6705	9.17	-	-	-	-	0.60	9.77	14.00	4.23
6865	8.21	-	-	-	-	1.50	9.71	14.00	4.29

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	12.14	-	-	-	-	0.60	12.74	14.00	1.26
6825	11.06	-	-	-	-	1.50	12.56	14.00	1.44

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	11.99	-	-	-	-	0.60	12.59	14.00	1.41
6825	10.91	-	-	-	-	1.50	12.41	14.00	1.59

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	12.17	-	-	-	-	0.60	12.77	14.00	1.23
6825	11.36	-	-	-	-	1.50	12.86	14.00	1.14

Maximum EIRP (U-NII-7) / VLP (continued)**Results: VLP / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	3.02	-	-	-	1.90	4.92	14.00	9.08
6715	-	2.97	-	-	-	1.90	4.87	14.00	9.13
6875	-	3.14	-	-	-	1.90	5.04	14.00	8.96

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-	6.03	-	-	-	1.90	7.93	14.00	6.07
6685	-	6.15	-	-	-	1.90	8.05	14.00	5.95
6845	-	6.13	-	-	-	1.90	8.03	14.00	5.97

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	8.78	-	-	-	2.60	11.38	14.00	2.62
6705	-	9.12	-	-	-	1.90	11.02	14.00	2.98
6865	-	9.04	-	-	-	1.90	10.94	14.00	3.06

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	10.78	-	-	-	1.90	12.68	14.00	1.32
6825	-	10.85	-	-	-	1.90	12.75	14.00	1.25

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	3.08	-	-	-	1.90	4.98	14.00	9.02
6715	-	3.06	-	-	-	1.90	4.96	14.00	9.04
6875	-	3.18	-	-	-	1.90	5.08	14.00	8.92

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	-6.43	-	-	-	1.90	-4.53	14.00	18.53
6715	-	-6.02	-	-	-	1.90	-4.12	14.00	18.12
6875	-	-5.82	-	-	-	1.90	-3.92	14.00	17.92

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	-3.22	-	-	-	1.90	-1.32	14.00	15.32
6715	-	-3.12	-	-	-	1.90	-1.22	14.00	15.22
6875	-	-3.01	-	-	-	1.90	-1.11	14.00	15.11

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	-0.43	-	-	-	1.90	1.47	14.00	12.53
6715	-	-0.27	-	-	-	1.90	1.63	14.00	12.37
6875	-	-0.02	-	-	-	1.90	1.88	14.00	12.12

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	-1.75	-	-	-	1.90	0.15	14.00	13.85
6715	-	-1.77	-	-	-	1.90	0.13	14.00	13.87
6875	-	-1.40	-	-	-	1.90	0.50	14.00	13.50

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	0.76	-	-	-	1.90	2.66	14.00	11.34
6715	-	0.53	-	-	-	1.90	2.43	14.00	11.57
6875	-	0.79	-	-	-	1.90	2.69	14.00	11.31

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-	6.02	-	-	-	1.90	7.92	14.00	6.08
6685	-	5.99	-	-	-	1.90	7.89	14.00	6.11
6845	-	6.17	-	-	-	1.90	8.07	14.00	5.93

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	8.83	-	-	-	2.60	11.43	14.00	2.57
6705	-	9.06	-	-	-	1.90	10.96	14.00	3.04
6865	-	9.07	-	-	-	1.90	10.97	14.00	3.03

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	7.14	-	-	-	2.60	9.74	14.00	4.26
6705	-	7.67	-	-	-	1.90	9.57	14.00	4.43
6865	-	7.71	-	-	-	1.90	9.61	14.00	4.39

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	10.90	-	-	-	1.90	12.80	14.00	1.20
6825	-	10.96	-	-	-	1.90	12.86	14.00	1.14

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	10.94	-	-	-	1.90	12.84	14.00	1.16
6825	-	10.70	-	-	-	1.90	12.60	14.00	1.40

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	11.00	-	-	-	1.90	12.90	14.00	1.10
6825	-	10.87	-	-	-	1.90	12.77	14.00	1.23

Maximum EIRP (U-NII-7) / VLP (continued)**Results: VLP / MIMO CDD**

Antenna Configuration:	MIMO CDD	Mode:	802.11a20
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-3.13	-2.50	-	-	0.20	1.90	2.10	14.00	11.90
6715	-3.60	-2.55	-	-	-0.03	1.90	1.87	14.00	12.13
6875	-3.54	-2.69	-	-	-0.09	1.90	1.81	14.00	12.19

Antenna Configuration:	MIMO CDD	Mode:	802.11a40
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-0.02	0.59	-	-	3.29	1.90	5.19	14.00	8.81
6685	0.22	0.69	-	-	3.46	1.90	5.36	14.00	8.64
6845	0.29	0.80	-	-	3.56	1.90	5.46	14.00	8.54

Antenna Configuration:	MIMO CDD	Mode:	802.11a80
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	3.21	3.55	-	-	6.39	2.60	8.99	14.00	5.01
6705	2.88	3.54	-	-	6.23	1.90	8.13	14.00	5.87
6865	2.86	3.35	-	-	6.11	1.90	8.01	14.00	5.99

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11a160
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	6.49	6.56	-	-	9.50	1.90	11.40	14.00	2.60
6825	5.73	6.15	-	-	8.95	1.90	10.85	14.00	3.15

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-3.28	-2.23	-	-	0.28	1.90	2.18	14.00	11.82
6715	-3.39	-2.30	-	-	0.19	1.90	2.09	14.00	11.91
6875	-3.61	-2.69	-	-	-0.12	1.90	1.78	14.00	12.22

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-9.08	-8.77	-	-	-5.91	1.90	-4.01	14.00	18.01
6715	-9.20	-8.71	-	-	-5.94	1.90	-4.04	14.00	18.04
6875	-9.41	-8.85	-	-	-6.11	1.90	-4.21	14.00	18.21

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-6.11	-5.73	-	-	-2.91	1.90	-1.01	14.00	15.01
6715	-6.23	-5.71	-	-	-2.96	1.90	-1.06	14.00	15.06
6875	-6.06	-5.76	-	-	-2.90	1.90	-1.00	14.00	15.00

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-7.30	-7.00	-	-	-4.14	1.90	-2.24	14.00	16.24
6715	-7.80	-7.14	-	-	-4.45	1.90	-2.55	14.00	16.55
6875	-7.66	-7.15	-	-	-4.39	1.90	-2.49	14.00	16.49

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-5.05	-4.71	-	-	-1.87	1.90	0.03	14.00	13.97
6715	-5.35	-4.73	-	-	-2.02	1.90	-0.12	14.00	14.12
6875	-5.48	-4.97	-	-	-2.21	1.90	-0.31	14.00	14.31

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-0.93	0.53	-	-	2.87	1.90	4.77	14.00	9.23
6685	-0.40	0.70	-	-	3.19	1.90	5.09	14.00	8.91
6845	-0.29	0.79	-	-	3.29	1.90	5.19	14.00	8.81