

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	10.15	-	-	-	-	2.60	12.75	14.00	1.25
6345	11.88	-	-	-	-	0.90	12.78	14.00	1.22

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	2.28	-	-	-	-	2.60	4.88	14.00	9.12
6175	2.50	-	-	-	-	2.60	5.10	14.00	8.90
6415	4.06	-	-	-	-	0.90	4.96	14.00	9.04

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-6.69	-	-	-	-	2.60	-4.09	14.00	18.09
6175	-6.73	-	-	-	-	2.60	-4.13	14.00	18.13
6415	-5.13	-	-	-	-	0.90	-4.23	14.00	18.23

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-3.89	-	-	-	-	2.60	-1.29	14.00	15.29
6175	-3.94	-	-	-	-	2.60	-1.34	14.00	15.34
6415	-2.29	-	-	-	-	0.90	-1.39	14.00	15.39

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-0.84	-	-	-	-	2.60	1.76	14.00	12.24
6175	-1.03	-	-	-	-	2.60	1.57	14.00	12.43
6415	0.85	-	-	-	-	0.90	1.75	14.00	12.25

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-2.02	-	-	-	-	2.60	0.58	14.00	13.42
6175	-2.11	-	-	-	-	2.60	0.49	14.00	13.51
6415	-0.26	-	-	-	-	0.90	0.64	14.00	13.36

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	0.01	-	-	-	-	2.60	2.61	14.00	11.39
6175	0.08	-	-	-	-	2.60	2.68	14.00	11.32
6415	2.19	-	-	-	-	0.90	3.09	14.00	10.91

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6125	5.40	-	-	-	-	2.60	8.00	14.00	6.00
6285	7.01	-	-	-	-	0.90	7.91	14.00	6.09
6405	6.80	-	-	-	-	0.90	7.70	14.00	6.30

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	8.39	-	-	-	-	2.60	10.99	14.00	3.01
6305	10.10	-	-	-	-	0.90	11.00	14.00	3.00
6385	9.90	-	-	-	-	0.90	10.80	14.00	3.20

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	7.24	-	-	-	-	2.60	9.84	14.00	4.16
6305	8.77	-	-	-	-	0.90	9.67	14.00	4.33
6385	8.99	-	-	-	-	0.90	9.89	14.00	4.11

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	9.93	-	-	-	-	2.60	12.53	14.00	1.47
6345	12.10	-	-	-	-	0.90	13.00	14.00	1.00

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	9.49	-	-	-	-	2.60	12.09	14.00	1.91
6345	11.65	-	-	-	-	0.90	12.55	14.00	1.45

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	9.97	-	-	-	-	2.60	12.57	14.00	1.43
6345	11.75	-	-	-	-	0.90	12.65	14.00	1.35

Maximum EIRP (U-NII-5) / VLP (continued)**Results: VLP / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	2.02	-	-	-	2.90	4.92	14.00	9.08
6175	-	1.90	-	-	-	2.90	4.80	14.00	9.20
6415	-	2.28	-	-	-	2.60	4.88	14.00	9.12

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6125	-	5.17	-	-	-	2.90	8.07	14.00	5.93
6285	-	5.59	-	-	-	2.60	8.19	14.00	5.81
6405	-	5.50	-	-	-	2.60	8.10	14.00	5.90

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	-	8.17	-	-	-	2.90	11.07	14.00	2.93
6305	-	8.52	-	-	-	2.60	11.12	14.00	2.88
6385	-	8.57	-	-	-	2.60	11.17	14.00	2.83

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	-	9.89	-	-	-	2.90	12.79	14.00	1.21
6345	-	10.18	-	-	-	2.60	12.78	14.00	1.22

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	2.22	-	-	-	2.90	5.12	14.00	8.88
6175	-	2.17	-	-	-	2.90	5.07	14.00	8.93
6415	-	2.57	-	-	-	2.60	5.17	14.00	8.83

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	-6.84	-	-	-	2.90	-3.94	14.00	17.94
6175	-	-6.71	-	-	-	2.90	-3.81	14.00	17.81
6415	-	-6.83	-	-	-	2.60	-4.23	14.00	18.23

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	-4.12	-	-	-	2.90	-1.22	14.00	15.22
6175	-	-4.32	-	-	-	2.90	-1.42	14.00	15.42
6415	-	-3.74	-	-	-	2.60	-1.14	14.00	15.14

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	-1.02	-	-	-	2.90	1.88	14.00	12.12
6175	-	-1.04	-	-	-	2.90	1.86	14.00	12.14
6415	-	-0.88	-	-	-	2.60	1.72	14.00	12.28

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	-2.20	-	-	-	2.90	0.70	14.00	13.30
6175	-	-2.14	-	-	-	2.90	0.76	14.00	13.24
6415	-	-2.10	-	-	-	2.60	0.50	14.00	13.50

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-	-0.23	-	-	-	2.90	2.67	14.00	11.33
6175	-	-0.22	-	-	-	2.90	2.68	14.00	11.32
6415	-	0.28	-	-	-	2.60	2.88	14.00	11.12

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6125	-	5.14	-	-	-	2.90	8.04	14.00	5.96
6285	-	5.60	-	-	-	2.60	8.20	14.00	5.80
6405	-	5.55	-	-	-	2.60	8.15	14.00	5.85

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	-	8.14	-	-	-	2.90	11.04	14.00	2.96
6305	-	8.57	-	-	-	2.60	11.17	14.00	2.83
6385	-	8.59	-	-	-	2.60	11.19	14.00	2.81

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	-	6.89	-	-	-	2.90	9.79	14.00	4.21
6305	-	7.35	-	-	-	2.60	9.95	14.00	4.05
6385	-	7.40	-	-	-	2.60	10.00	14.00	4.00

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	-	9.95	-	-	-	2.90	12.85	14.00	1.15
6345	-	10.16	-	-	-	2.60	12.76	14.00	1.24

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	-	9.69	-	-	-	2.90	12.59	14.00	1.41
6345	-	10.20	-	-	-	2.60	12.80	14.00	1.20

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	-	9.94	-	-	-	2.90	12.84	14.00	1.16
6345	-	10.15	-	-	-	2.60	12.75	14.00	1.25

Maximum EIRP (U-NII-5) / VLP (continued)**Results: VLP / MIMO CDD**

Antenna Configuration:	MIMO CDD	Mode:	802.11a20
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-3.94	-4.00	-	-	-0.96	2.90	1.94	14.00	12.06
6175	-4.01	-4.07	-	-	-1.03	2.90	1.87	14.00	12.13
6415	-3.04	-2.91	-	-	0.03	2.60	2.63	14.00	11.37

Antenna Configuration:	MIMO CDD	Mode:	802.11a40
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6125	-0.66	-0.63	-	-	2.35	2.90	5.25	14.00	8.75
6285	0.37	0.29	-	-	3.34	2.60	5.94	14.00	8.06
6405	0.14	0.15	-	-	3.14	2.60	5.74	14.00	8.26

Antenna Configuration:	MIMO CDD	Mode:	802.11a80
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	2.20	2.07	-	-	5.13	2.90	8.03	14.00	5.97
6305	3.15	3.37	-	-	6.27	2.60	8.87	14.00	5.13
6385	2.77	2.96	-	-	5.87	2.60	8.47	14.00	5.53

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11a160
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	5.07	5.17	-	-	8.13	2.90	11.03	14.00	2.97
6345	5.37	5.86	-	-	8.59	2.60	11.19	14.00	2.81

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-3.69	-3.61	-	-	-0.65	2.90	2.25	14.00	11.75
6175	-3.75	-3.74	-	-	-0.74	2.90	2.16	14.00	11.84
6415	-3.09	-2.89	-	-	0.02	2.60	2.62	14.00	11.38

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6415	-9.48	-9.57	-	-	-6.52	2.60	-3.92	14.00	17.92

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-6.94	-6.91	-	-	-3.92	2.90	-1.02	14.00	15.02
6175	-7.17	-7.33	-	-	-4.24	2.90	-1.34	14.00	15.34
6415	-5.94	-5.97	-	-	-2.95	2.60	-0.35	14.00	14.35

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-8.18	-8.16	-	-	-5.16	2.90	-2.26	14.00	16.26
6175	-8.00	-8.14	-	-	-5.06	2.90	-2.16	14.00	16.16
6415	-7.29	-7.34	-	-	-4.30	2.60	-1.70	14.00	15.70

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-6.33	-6.22	-	-	-3.26	2.90	-0.36	14.00	14.36
6175	-6.27	-6.37	-	-	-3.31	2.90	-0.41	14.00	14.41
6415	-4.93	-4.80	-	-	-1.86	2.60	0.74	14.00	13.26

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6125	-0.77	-0.73	-	-	2.25	2.90	5.15	14.00	8.85
6285	0.35	0.30	-	-	3.34	2.60	5.94	14.00	8.06
6405	-0.07	0.13	-	-	3.04	2.60	5.64	14.00	8.36

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	2.50	2.27	-	-	5.39	2.90	8.29	14.00	5.71
6305	3.12	3.38	-	-	6.24	2.60	8.84	14.00	5.16
6385	2.74	2.96	-	-	5.86	2.60	8.46	14.00	5.54

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	1.16	1.14	-	-	4.16	2.90	7.06	14.00	6.94
6305	1.93	1.86	-	-	4.90	2.60	7.50	14.00	6.50
6385	2.21	2.28	-	-	5.24	2.60	7.84	14.00	6.16

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	4.63	4.97	-	-	7.80	2.90	10.70	14.00	3.30
6345	5.38	5.99	-	-	8.70	2.60	11.30	14.00	2.70

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	3.04	3.63	-	-	6.35	2.90	9.25	14.00	4.75
6345	3.89	4.86	-	-	7.39	2.60	9.99	14.00	4.01

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	4.11	4.58	-	-	7.35	2.90	10.25	14.00	3.75
6345	4.87	5.51	-	-	8.19	2.60	10.79	14.00	3.21

Maximum EIRP (U-NII-5) / VLP (continued)**Results: VLP / MIMO SDM**

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-0.89	-0.83	-	-	2.15	2.75	4.90	14.00	9.10
6175	-0.82	-0.77	-	-	2.21	2.75	4.96	14.00	9.04
6415	-0.14	0.14	-	-	3.01	1.83	4.84	14.00	9.16

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6415	-9.22	-9.33	-	-	-6.27	1.83	-4.44	14.00	18.44

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-7.10	-7.05	-	-	-4.06	2.75	-1.31	14.00	15.31
6175	-7.00	-7.14	-	-	-4.06	2.75	-1.31	14.00	15.31
6415	-6.32	-6.31	-	-	-3.31	1.83	-1.47	14.00	15.47

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-3.94	-3.99	-	-	-0.96	2.75	1.80	14.00	12.20
6175	-4.13	-4.38	-	-	-1.24	2.75	1.51	14.00	12.49
6415	-3.12	-3.22	-	-	-0.16	1.83	1.67	14.00	12.33

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-5.31	-5.24	-	-	-2.26	2.75	0.49	14.00	13.51
6175	-5.00	-5.13	-	-	-2.06	2.75	0.70	14.00	13.30
6415	-4.35	-4.32	-	-	-1.33	1.83	0.51	14.00	13.49

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-3.09	-3.01	-	-	-0.05	2.75	2.70	14.00	11.30
6175	-3.02	-3.17	-	-	-0.09	2.75	2.67	14.00	11.33
6415	-2.18	-2.16	-	-	0.84	1.83	2.67	14.00	11.33

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6125	2.21	1.99	-	-	5.11	2.75	7.86	14.00	6.14
6285	3.28	3.34	-	-	6.31	1.83	8.15	14.00	5.85
6405	2.83	3.13	-	-	5.98	1.83	7.81	14.00	6.19

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	4.92	5.28	-	-	8.11	2.75	10.86	14.00	3.14
6305	5.62	6.26	-	-	8.96	1.83	10.79	14.00	3.21
6385	5.48	6.07	-	-	8.78	1.83	10.61	14.00	3.39

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	3.71	4.08	-	-	6.90	2.75	9.65	14.00	4.35
6305	4.38	4.89	-	-	7.65	1.83	9.48	14.00	4.52
6385	4.65	5.11	-	-	7.89	1.83	9.72	14.00	4.28

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	6.54	6.89	-	-	9.73	2.75	12.48	14.00	1.52
6345	7.12	7.72	-	-	10.44	1.83	12.27	14.00	1.73

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	6.32	6.80	-	-	9.53	2.75	12.28	14.00	1.72
6345	6.84	7.75	-	-	10.31	1.83	12.14	14.00	1.86

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	6.51	6.93	-	-	9.70	2.75	12.46	14.00	1.54
6345	7.33	7.68	-	-	10.51	1.83	12.35	14.00	1.65

Maximum EIRP (U-NII-5) / VLP (continued)**Results: VLP / TxBF**

Antenna Configuration:	TxBF	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6115	-3.72	-3.72	-	-	-0.71	5.76	5.05	14.00	8.95
6175	-3.74	-3.82	-	-	-0.77	5.76	4.99	14.00	9.01
6415	-3.06	-2.90	-	-	0.03	4.80	4.83	14.00	9.17

Antenna Configuration:	TxBF	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6125	-0.73	-0.71	-	-	2.29	5.76	8.05	14.00	5.95
6285	0.32	0.27	-	-	3.31	4.80	8.11	14.00	5.89
6405	0.11	0.30	-	-	3.21	4.80	8.02	14.00	5.98

Antenna Configuration:	TxBF	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6145	2.46	2.29	-	-	5.38	5.76	11.14	14.00	2.86
6305	3.18	3.42	-	-	6.30	4.80	11.10	14.00	2.90
6385	2.81	3.04	-	-	5.93	4.80	10.73	14.00	3.27

Maximum EIRP (U-NII-5) / VLP (continued)

Antenna Configuration:	TxBF		Mode:	802.11ax HE160 SU	
Test Port:	1+2 (Core 0+Core1)		Rate/Modulation:	MCS2x2 (QPSK)	

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6185	3.58	4.03	-	-	6.81	5.76	12.57	14.00	1.43
6345	4.32	5.05	-	-	7.69	4.80	12.49	14.00	1.51

Maximum EIRP (U-NII-6) / LPI (continued)**4.3.2 6.425-6.525 GHz band (U-NII-6)****Results: LPI / SISO / Core 0**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	8.48	-	-	-	-	0.60	9.08	24.00	14.92
6475	8.21	-	-	-	-	0.60	8.81	24.00	15.19
6515	8.40	-	-	-	-	0.60	9.00	24.00	15.00

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	11.61	-	-	-	-	0.60	12.21	24.00	11.79
6485	11.53	-	-	-	-	0.60	12.13	24.00	11.87
6525	11.57	-	-	-	-	0.60	12.17	24.00	11.83

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	14.69	-	-	-	-	0.60	15.29	24.00	8.71

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	17.28	-	-	-	-	0.60	17.88	24.00	6.12

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	8.55	-	-	-	-	0.60	9.15	24.00	14.85
6475	8.60	-	-	-	-	0.60	9.20	24.00	14.80
6515	8.53	-	-	-	-	0.60	9.13	24.00	14.87

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-0.88	-	-	-	-	0.60	-0.28	24.00	24.28
6475	-0.65	-	-	-	-	0.60	-0.05	24.00	24.05
6515	-0.84	-	-	-	-	0.60	-0.24	24.00	24.24

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	2.17	-	-	-	-	0.60	2.77	24.00	21.23
6475	2.16	-	-	-	-	0.60	2.76	24.00	21.24
6515	2.00	-	-	-	-	0.60	2.60	24.00	21.40

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	5.12	-	-	-	-	0.60	5.72	24.00	18.28
6475	5.28	-	-	-	-	0.60	5.88	24.00	18.12
6515	5.17	-	-	-	-	0.60	5.77	24.00	18.23

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	3.81	-	-	-	-	0.60	4.41	24.00	19.59
6475	3.58	-	-	-	-	0.60	4.18	24.00	19.82
6515	3.89	-	-	-	-	0.60	4.49	24.00	19.51

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	6.16	-	-	-	-	0.60	6.76	24.00	17.24
6475	6.17	-	-	-	-	0.60	6.77	24.00	17.23
6515	6.07	-	-	-	-	0.60	6.67	24.00	17.33

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	11.53	-	-	-	-	0.60	12.13	24.00	11.87
6485	11.65	-	-	-	-	0.60	12.25	24.00	11.75
6525	11.65	-	-	-	-	0.60	12.25	24.00	11.75

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	14.58	-	-	-	-	0.60	15.18	24.00	8.82

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	13.39	-	-	-	-	0.60	13.99	24.00	10.01

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	17.40	-	-	-	-	0.60	18.00	24.00	6.00

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	16.07	-	-	-	-	0.60	16.67	24.00	7.33

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	16.85	-	-	-	-	0.60	17.45	24.00	6.55

Maximum EIRP (U-NII-6) / LPI (continued)**Results: LPI / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	6.27	-	-	-	2.60	8.87	24.00	15.13
6475	-	6.48	-	-	-	2.60	9.08	24.00	14.92
6515	-	6.41	-	-	-	2.60	9.01	24.00	14.99

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-	9.47	-	-	-	2.60	12.07	24.00	11.93
6485	-	9.44	-	-	-	2.60	12.04	24.00	11.96
6525	-	9.50	-	-	-	2.60	12.10	24.00	11.90

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	12.78	-	-	-	2.60	15.38	24.00	8.62

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	15.34	-	-	-	2.60	17.94	24.00	6.06

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	6.49	-	-	-	2.60	9.09	24.00	14.91
6475	-	6.66	-	-	-	2.60	9.26	24.00	14.74
6515	-	6.60	-	-	-	2.60	9.20	24.00	14.80

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	-2.66	-	-	-	2.60	-0.06	24.00	24.06
6475	-	-2.68	-	-	-	2.60	-0.08	24.00	24.08
6515	-	-2.64	-	-	-	2.60	-0.04	24.00	24.04

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	0.29	-	-	-	2.60	2.89	24.00	21.11
6475	-	0.15	-	-	-	2.60	2.75	24.00	21.25
6515	-	0.14	-	-	-	2.60	2.74	24.00	21.26

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	3.17	-	-	-	2.60	5.77	24.00	18.23
6475	-	3.21	-	-	-	2.60	5.81	24.00	18.19
6515	-	3.12	-	-	-	2.60	5.72	24.00	18.28

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	1.91	-	-	-	2.60	4.51	24.00	19.49
6475	-	2.09	-	-	-	2.60	4.69	24.00	19.31
6515	-	2.05	-	-	-	2.60	4.65	24.00	19.35

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	4.02	-	-	-	2.60	6.62	24.00	17.38
6475	-	4.11	-	-	-	2.60	6.71	24.00	17.29
6515	-	4.07	-	-	-	2.60	6.67	24.00	17.33

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-	9.40	-	-	-	2.60	12.00	24.00	12.00
6485	-	9.41	-	-	-	2.60	12.01	24.00	11.99
6525	-	9.75	-	-	-	2.60	12.35	24.00	11.65

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	12.69	-	-	-	2.60	15.29	24.00	8.71

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	11.38	-	-	-	2.60	13.98	24.00	10.02

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	15.03	-	-	-	2.60	17.63	24.00	6.37

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	14.08	-	-	-	2.60	16.68	24.00	7.32

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	14.72	-	-	-	2.60	17.32	24.00	6.68

Maximum EIRP (U-NII-6) / LPI (continued)**Results: LPI / MIMO CDD**

Antenna Configuration:	MIMO CDD	Mode:	802.11a20
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	0.80	1.20	-	-	4.00	2.60	6.60	24.00	17.40
6475	0.91	1.22	-	-	4.07	2.60	6.67	24.00	17.33
6515	0.85	1.40	-	-	4.14	2.60	6.74	24.00	17.26

Antenna Configuration:	MIMO CDD	Mode:	802.11a40
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	3.62	4.19	-	-	6.92	2.60	9.52	24.00	14.48
6485	3.80	4.20	-	-	7.00	2.60	9.60	24.00	14.40
6525	4.39	4.59	-	-	7.50	2.60	10.10	24.00	13.90

Antenna Configuration:	MIMO CDD	Mode:	802.11a80
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	7.23	7.64	-	-	10.44	2.60	13.04	24.00	10.96

Antenna Configuration:	MIMO CDD	Mode:	802.11a160
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	9.78	9.96	-	-	12.79	2.60	15.39	24.00	8.61

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	1.01	1.35	-	-	4.20	2.60	6.80	24.00	17.20
6475	1.11	1.41	-	-	4.27	2.60	6.87	24.00	17.13
6515	0.79	1.33	-	-	4.08	2.60	6.68	24.00	17.32

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-7.90	-7.93	-	-	-4.90	2.60	-2.30	24.00	26.30
6475	-8.45	-7.95	-	-	-5.18	2.60	-2.58	24.00	26.58
6515	-8.51	-7.89	-	-	-5.18	2.60	-2.58	24.00	26.58

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-5.04	-5.07	-	-	-2.04	2.60	0.56	24.00	23.44
6475	-5.48	-5.00	-	-	-2.22	2.60	0.38	24.00	23.62
6515	-5.74	-5.16	-	-	-2.43	2.60	0.17	24.00	23.83

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-2.04	-1.97	-	-	1.00	2.60	3.60	24.00	20.40
6475	-2.34	-1.81	-	-	0.94	2.60	3.54	24.00	20.46
6515	-2.60	-2.01	-	-	0.71	2.60	3.31	24.00	20.69

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-3.50	-3.17	-	-	-0.32	2.60	2.28	24.00	21.72
6475	-3.84	-3.23	-	-	-0.52	2.60	2.08	24.00	21.92
6515	-3.90	-3.17	-	-	-0.51	2.60	2.09	24.00	21.91

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-1.35	-1.04	-	-	1.82	2.60	4.42	24.00	19.58
6475	-1.38	-0.82	-	-	1.92	2.60	4.52	24.00	19.48
6515	-1.44	-0.80	-	-	1.90	2.60	4.50	24.00	19.50

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	3.72	4.37	-	-	7.05	2.60	9.65	24.00	14.35
6485	3.83	4.20	-	-	7.00	2.60	9.60	24.00	14.40
6525	3.83	4.55	-	-	7.20	2.60	9.80	24.00	14.20

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	7.21	7.62	-	-	10.42	2.60	13.02	24.00	10.98

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	5.72	6.19	-	-	8.95	2.60	11.55	24.00	12.45

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	9.89	10.17	-	-	13.03	2.60	15.63	24.00	8.37

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	8.69	8.90	-	-	11.78	2.60	14.38	24.00	9.62

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	9.42	9.67	-	-	12.55	2.60	15.15	24.00	8.85

Maximum EIRP (U-NII-6) / LPI (continued)**Results: LPI / MIMO SDM**

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	3.83	4.41	-	-	7.12	1.71	8.84	24.00	15.16
6475	3.96	4.40	-	-	7.19	1.71	8.90	24.00	15.10
6515	3.73	4.39	-	-	7.07	1.71	8.78	24.00	15.22

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-4.82	-4.71	-	-	-1.75	1.71	-0.04	24.00	24.04
6475	-5.48	-4.97	-	-	-2.21	1.71	-0.49	24.00	24.49
6515	-5.49	-4.91	-	-	-2.18	1.71	-0.46	24.00	24.46

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-2.07	-1.97	-	-	0.99	1.71	2.70	24.00	21.30
6475	-2.57	-2.11	-	-	0.68	1.71	2.39	24.00	21.61
6515	-2.52	-1.92	-	-	0.80	1.71	2.51	24.00	21.49

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	1.08	1.20	-	-	4.15	1.71	5.86	24.00	18.14
6475	0.68	1.14	-	-	3.92	1.71	5.64	24.00	18.36
6515	0.67	1.18	-	-	3.94	1.71	5.66	24.00	18.34

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-0.77	-0.29	-	-	2.49	1.71	4.20	24.00	19.80
6475	-0.73	-0.32	-	-	2.49	1.71	4.21	24.00	19.79
6515	-0.77	-0.12	-	-	2.58	1.71	4.29	24.00	19.71

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	1.56	2.02	-	-	4.80	1.71	6.52	24.00	17.48
6475	1.65	2.09	-	-	4.88	1.71	6.60	24.00	17.40
6515	1.32	1.93	-	-	4.65	1.71	6.36	24.00	17.64

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	6.91	7.37	-	-	10.15	1.71	11.87	24.00	12.13
6485	6.91	7.28	-	-	10.10	1.71	11.81	24.00	12.19
6525	7.31	7.66	-	-	10.49	1.71	12.21	24.00	11.79

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	10.37	10.66	-	-	13.53	1.71	15.24	24.00	8.76

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	9.11	9.27	-	-	12.20	1.71	13.91	24.00	10.09

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	12.82	13.12	-	-	15.98	1.71	17.69	24.00	6.31

Maximum EIRP (U-NII-6) / LPI (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	11.90	12.10	-	-	15.00	1.71	16.71	24.00	7.29

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	12.38	12.63	-	-	15.51	1.71	17.22	24.00	6.78

Maximum EIRP (U-NII-6) / LPI (continued)**Results: LPI / TxBF**

Antenna Configuration:	TxBF	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	0.99	1.36	-	-	4.19	4.67	8.85	24.00	15.15
6475	1.09	1.40	-	-	4.25	4.67	8.92	24.00	15.08
6515	0.79	1.33	-	-	4.08	4.67	8.74	24.00	15.26

Antenna Configuration:	TxBF	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	3.76	4.39	-	-	7.10	4.67	11.77	24.00	12.23
6485	3.95	4.24	-	-	7.10	4.67	11.76	24.00	12.24
6525	3.91	4.59	-	-	7.27	4.67	11.94	24.00	12.06

Antenna Configuration:	TxBF	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	7.11	7.47	-	-	10.28	4.67	14.94	24.00	9.06

Antenna Configuration:	TxBF	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	9.90	10.17	-	-	13.04	4.67	17.70	24.00	6.30

Maximum EIRP (U-NII-6) / SP (continued)**Results: ISSED / SP / SISO / Core 0**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	19.39	-	-	-	-	0.60	19.99	30.00	10.01
6475	19.38	-	-	-	-	0.60	19.98	30.00	10.02
6515	19.48	-	-	-	-	0.60	20.08	30.00	9.92

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	19.18	-	-	-	-	0.60	19.78	30.00	10.22
6485	19.30	-	-	-	-	0.60	19.90	30.00	10.10
6525	19.20	-	-	-	-	0.60	19.80	30.00	10.20

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	19.23	-	-	-	-	0.60	19.83	30.00	10.17

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.24	-	-	-	-	0.60	19.84	30.00	10.16

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	19.39	-	-	-	-	0.60	19.99	30.00	10.01
6475	19.35	-	-	-	-	0.60	19.95	30.00	10.05
6515	19.43	-	-	-	-	0.60	20.03	30.00	9.97

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	11.93	-	-	-	-	0.60	12.53	30.00	17.47
6475	11.78	-	-	-	-	0.60	12.38	30.00	17.62
6515	11.90	-	-	-	-	0.60	12.50	30.00	17.50

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	14.93	-	-	-	-	0.60	15.53	30.00	14.47
6475	14.52	-	-	-	-	0.60	15.12	30.00	14.88
6515	14.85	-	-	-	-	0.60	15.45	30.00	14.55

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	17.80	-	-	-	-	0.60	18.40	30.00	11.60
6475	17.97	-	-	-	-	0.60	18.57	30.00	11.43
6515	17.94	-	-	-	-	0.60	18.54	30.00	11.46

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	16.32	-	-	-	-	0.60	16.92	30.00	13.08
6475	16.46	-	-	-	-	0.60	17.06	30.00	12.94
6515	16.32	-	-	-	-	0.60	16.92	30.00	13.08

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	18.36	-	-	-	-	0.60	18.96	30.00	11.04
6475	18.39	-	-	-	-	0.60	18.99	30.00	11.01
6515	18.42	-	-	-	-	0.60	19.02	30.00	10.98

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	19.32	-	-	-	-	0.60	19.92	30.00	10.08
6485	19.26	-	-	-	-	0.60	19.86	30.00	10.14
6525	19.38	-	-	-	-	0.60	19.98	30.00	10.02

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	19.35	-	-	-	-	0.60	19.95	30.00	10.05

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	19.50	-	-	-	-	0.60	20.10	30.00	9.90

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.26	-	-	-	-	0.60	19.86	30.00	10.14

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.27	-	-	-	-	0.60	19.87	30.00	10.13

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.25	-	-	-	-	0.60	19.85	30.00	10.15

Maximum EIRP (U-NII-6) / SP (continued)**Results: ISSED / SP / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	19.34	-	-	-	2.60	21.94	30.00	8.06
6475	-	19.30	-	-	-	2.60	21.90	30.00	8.10
6515	-	19.43	-	-	-	2.60	22.03	30.00	7.97

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-	19.48	-	-	-	2.60	22.08	30.00	7.92
6485	-	19.28	-	-	-	2.60	21.88	30.00	8.12
6525	-	19.42	-	-	-	2.60	22.02	30.00	7.98

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	19.45	-	-	-	2.60	22.05	30.00	7.95

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	19.44	-	-	-	2.60	22.04	30.00	7.96

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	19.30	-	-	-	2.60	21.90	30.00	8.10
6475	-	19.49	-	-	-	2.60	22.09	30.00	7.91
6515	-	19.43	-	-	-	2.60	22.03	30.00	7.97

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	11.84	-	-	-	2.60	14.44	30.00	15.56
6475	-	11.95	-	-	-	2.60	14.55	30.00	15.45
6515	-	11.98	-	-	-	2.60	14.58	30.00	15.42

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	14.78	-	-	-	2.60	17.38	30.00	12.62
6475	-	14.90	-	-	-	2.60	17.50	30.00	12.50
6515	-	14.91	-	-	-	2.60	17.51	30.00	12.49

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	17.96	-	-	-	2.60	20.56	30.00	9.44
6475	-	17.94	-	-	-	2.60	20.54	30.00	9.46
6515	-	17.89	-	-	-	2.60	20.49	30.00	9.51

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	16.41	-	-	-	2.60	19.01	30.00	10.99
6475	-	16.28	-	-	-	2.60	18.88	30.00	11.12
6515	-	16.35	-	-	-	2.60	18.95	30.00	11.05

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	18.33	-	-	-	2.60	20.93	30.00	9.07
6475	-	18.28	-	-	-	2.60	20.88	30.00	9.12
6515	-	18.32	-	-	-	2.60	20.92	30.00	9.08

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-	19.41	-	-	-	2.60	22.01	30.00	7.99
6485	-	19.44	-	-	-	2.60	22.04	30.00	7.96
6525	-	19.30	-	-	-	2.60	21.90	30.00	8.10

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	19.46	-	-	-	2.60	22.06	30.00	7.94

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	19.48	-	-	-	2.60	22.08	30.00	7.92

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	19.32	-	-	-	2.60	21.92	30.00	8.08

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	19.29	-	-	-	2.60	21.89	30.00	8.11

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	19.42	-	-	-	2.60	22.02	30.00	7.98

Maximum EIRP (U-NII-6) / SP (continued)**Results: ISSED / SP / MIMO CDD**

Antenna Configuration:	MIMO CDD	Mode:	802.11a20
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	19.01	19.38	-	-	22.20	2.60	24.80	30.00	5.20
6475	18.98	19.37	-	-	22.19	2.60	24.79	30.00	5.21
6515	19.12	19.36	-	-	22.24	2.60	24.84	30.00	5.16

Antenna Configuration:	MIMO CDD	Mode:	802.11a40
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	18.88	19.28	-	-	22.09	2.60	24.69	30.00	5.31
6485	19.14	19.33	-	-	22.24	2.60	24.84	30.00	5.16
6525	19.01	19.23	-	-	22.13	2.60	24.73	30.00	5.27

Antenna Configuration:	MIMO CDD	Mode:	802.11a80
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	18.91	19.28	-	-	22.10	2.60	24.70	30.00	5.30

Antenna Configuration:	MIMO CDD	Mode:	802.11a160
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.25	19.45	-	-	22.35	2.60	24.95	30.00	5.05

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	18.99	19.38	-	-	22.19	2.60	24.79	30.00	5.21
6475	19.01	19.36	-	-	22.18	2.60	24.78	30.00	5.22
6515	19.12	19.40	-	-	22.26	2.60	24.86	30.00	5.14

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	9.25	10.17	-	-	12.73	2.60	15.33	30.00	14.67
6475	9.07	10.14	-	-	12.63	2.60	15.23	30.00	14.77
6515	8.56	10.02	-	-	12.35	2.60	14.95	30.00	15.05

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	11.67	12.80	-	-	15.27	2.60	17.87	30.00	12.13
6475	11.71	12.86	-	-	15.32	2.60	17.92	30.00	12.08
6515	11.29	12.78	-	-	15.09	2.60	17.69	30.00	12.31

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	15.03	16.14	-	-	18.60	2.60	21.20	30.00	8.80
6475	14.91	16.14	-	-	18.57	2.60	21.17	30.00	8.83
6515	14.73	16.20	-	-	18.51	2.60	21.11	30.00	8.89

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	13.13	14.67	-	-	16.98	2.60	19.58	30.00	10.42
6475	13.20	14.80	-	-	17.08	2.60	19.68	30.00	10.32
6515	13.14	14.69	-	-	16.95	2.60	19.55	30.00	10.45

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	15.58	17.04	-	-	19.36	2.60	21.96	30.00	8.04
6475	15.76	17.04	-	-	19.42	2.60	22.02	30.00	7.98
6515	15.54	17.12	-	-	19.40	2.60	22.00	30.00	8.00

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	19.19	19.49	-	-	22.35	2.60	24.95	30.00	5.05
6485	19.19	19.34	-	-	22.25	2.60	24.85	30.00	5.15
6525	19.08	19.27	-	-	22.17	2.60	24.77	30.00	5.23

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	19.04	19.33	-	-	22.17	2.60	24.77	30.00	5.23

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	17.98	19.46	-	-	21.78	2.60	24.38	30.00	5.62

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.04	19.26	-	-	22.16	2.60	24.76	30.00	5.24

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	17.56	19.40	-	-	21.58	2.60	24.18	30.00	5.82

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	17.51	19.27	-	-	21.49	2.60	24.09	30.00	5.91

Maximum EIRP (U-NII-6) / SP (continued)**Results: ISED / SP / MIMO SDM**

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	18.95	19.31	-	-	22.14	1.71	23.85	30.00	6.15
6475	19.20	19.50	-	-	22.34	1.71	24.06	30.00	5.94
6515	19.07	19.31	-	-	22.18	1.71	23.89	30.00	6.11

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	10.89	11.94	-	-	14.46	1.71	16.17	30.00	13.83
6475	10.80	11.90	-	-	14.39	1.71	16.10	30.00	13.90
6515	10.31	11.87	-	-	14.16	1.71	15.87	30.00	14.13

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	13.91	14.98	-	-	17.48	1.71	19.20	30.00	10.80
6475	13.73	14.87	-	-	17.34	1.71	19.06	30.00	10.94
6515	13.29	14.82	-	-	17.10	1.71	18.81	30.00	11.19

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	16.78	17.88	-	-	20.34	1.71	22.06	30.00	7.94
6475	16.65	17.89	-	-	20.32	1.71	22.03	30.00	7.97
6515	16.43	17.97	-	-	20.27	1.71	21.98	30.00	8.02

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	14.89	16.40	-	-	18.71	1.71	20.43	30.00	9.57
6475	15.31	16.50	-	-	18.96	1.71	20.67	30.00	9.33
6515	14.85	16.42	-	-	18.71	1.71	20.42	30.00	9.58

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	16.86	18.27	-	-	20.63	1.71	22.34	30.00	7.66
6475	17.00	18.31	-	-	20.71	1.71	22.42	30.00	7.58
6515	16.87	18.33	-	-	20.64	1.71	22.36	30.00	7.64

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	19.07	19.37	-	-	22.22	1.71	23.93	30.00	6.07
6485	19.24	19.44	-	-	22.34	1.71	24.05	30.00	5.95
6525	19.20	19.34	-	-	22.27	1.71	23.99	30.00	6.01

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	19.25	19.47	-	-	22.37	1.71	24.08	30.00	5.92

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	18.00	19.46	-	-	21.80	1.71	23.51	30.00	6.49

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.06	19.28	-	-	22.17	1.71	23.88	30.00	6.12

Maximum EIRP (U-NII-6) / SP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	17.55	19.42	-	-	21.57	1.71	23.28	30.00	6.72

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	17.53	19.29	-	-	21.48	1.71	23.20	30.00	6.80

Maximum EIRP (U-NII-6) / SP (continued)**Results: ISED / SP / TxBF**

Antenna Configuration:	TxBF	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	19.15	19.44	-	-	22.30	4.67	26.97	30.00	3.03
6475	19.13	19.41	-	-	22.25	4.67	26.92	30.00	3.08
6515	19.22	19.40	-	-	22.30	4.67	26.97	30.00	3.03

Antenna Configuration:	TxBF	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	19.10	19.31	-	-	22.19	4.67	26.85	30.00	3.15
6485	19.27	19.40	-	-	22.31	4.67	26.98	30.00	3.02
6525	19.44	19.50	-	-	22.46	4.67	27.13	30.00	2.87

Antenna Configuration:	TxBF	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	19.13	19.33	-	-	22.23	4.67	26.90	30.00	3.10

Antenna Configuration:	TxBF	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	19.11	19.33	-	-	22.22	4.67	26.88	30.00	3.12

Maximum EIRP (U-NII-6) / VLP (continued)**Results: VLP / SISO / Core 0**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	4.49	-	-	-	-	0.60	5.09	14.00	8.91
6475	4.50	-	-	-	-	0.60	5.10	14.00	8.90
6515	4.33	-	-	-	-	0.60	4.93	14.00	9.07

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	7.48	-	-	-	-	0.60	8.08	14.00	5.92
6485	7.46	-	-	-	-	0.60	8.06	14.00	5.94
6525	7.68	-	-	-	-	0.60	8.28	14.00	5.72

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	10.71	-	-	-	-	0.60	11.31	14.00	2.69

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	12.28	-	-	-	-	0.60	12.88	14.00	1.12

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	4.53	-	-	-	-	0.60	5.13	14.00	8.87
6475	4.50	-	-	-	-	0.60	5.10	14.00	8.90
6515	4.43	-	-	-	-	0.60	5.03	14.00	8.97

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-4.74	-	-	-	-	0.60	-4.14	14.00	18.14
6475	-4.66	-	-	-	-	0.60	-4.06	14.00	18.06
6515	-4.90	-	-	-	-	0.60	-4.30	14.00	18.30

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-1.86	-	-	-	-	0.60	-1.26	14.00	15.26
6475	-1.85	-	-	-	-	0.60	-1.25	14.00	15.25
6515	-1.98	-	-	-	-	0.60	-1.38	14.00	15.38

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	1.29	-	-	-	-	0.60	1.89	14.00	12.11
6475	1.28	-	-	-	-	0.60	1.88	14.00	12.12
6515	1.16	-	-	-	-	0.60	1.76	14.00	12.24

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-0.06	-	-	-	-	0.60	0.54	14.00	13.46
6475	-0.20	-	-	-	-	0.60	0.40	14.00	13.60
6515	-0.13	-	-	-	-	0.60	0.47	14.00	13.53

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	2.29	-	-	-	-	0.60	2.89	14.00	11.11
6475	2.11	-	-	-	-	0.60	2.71	14.00	11.29
6515	2.22	-	-	-	-	0.60	2.82	14.00	11.18

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	7.46	-	-	-	-	0.60	8.06	14.00	5.94
6485	7.49	-	-	-	-	0.60	8.09	14.00	5.91
6525	7.70	-	-	-	-	0.60	8.30	14.00	5.70

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	10.64	-	-	-	-	0.60	11.24	14.00	2.76

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	9.36	-	-	-	-	0.60	9.96	14.00	4.04

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	12.07	-	-	-	-	0.60	12.67	14.00	1.33

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	12.02	-	-	-	-	0.60	12.62	14.00	1.38

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	12.16	-	-	-	-	0.60	12.76	14.00	1.24

Maximum EIRP (U-NII-6) / VLP (continued)**Results: VLP / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	2.50	-	-	-	2.60	5.10	14.00	8.90
6475	-	2.27	-	-	-	2.60	4.87	14.00	9.13
6515	-	2.49	-	-	-	2.60	5.09	14.00	8.91

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-	5.48	-	-	-	2.60	8.08	14.00	5.92
6485	-	5.50	-	-	-	2.60	8.10	14.00	5.90
6525	-	5.75	-	-	-	2.60	8.35	14.00	5.65

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	8.79	-	-	-	2.60	11.39	14.00	2.61

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	10.15	-	-	-	2.60	12.75	14.00	1.25

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	2.63	-	-	-	2.60	5.23	14.00	8.77
6475	-	2.59	-	-	-	2.60	5.19	14.00	8.81
6515	-	2.55	-	-	-	2.60	5.15	14.00	8.85

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	-6.64	-	-	-	2.60	-4.04	14.00	18.04
6475	-	-6.85	-	-	-	2.60	-4.25	14.00	18.25
6515	-	-6.61	-	-	-	2.60	-4.01	14.00	18.01

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	-3.94	-	-	-	2.60	-1.34	14.00	15.34
6475	-	-3.97	-	-	-	2.60	-1.37	14.00	15.37
6515	-	-3.89	-	-	-	2.60	-1.29	14.00	15.29

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	-0.73	-	-	-	2.60	1.87	14.00	12.13
6475	-	-0.71	-	-	-	2.60	1.89	14.00	12.11
6515	-	-0.78	-	-	-	2.60	1.82	14.00	12.18

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	-2.01	-	-	-	2.60	0.59	14.00	13.41
6475	-	-2.05	-	-	-	2.60	0.55	14.00	13.45
6515	-	-1.94	-	-	-	2.60	0.66	14.00	13.34

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-	0.11	-	-	-	2.60	2.71	14.00	11.29
6475	-	0.25	-	-	-	2.60	2.85	14.00	11.15
6515	-	0.20	-	-	-	2.60	2.80	14.00	11.20

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-	5.48	-	-	-	2.60	8.08	14.00	5.92
6485	-	5.33	-	-	-	2.60	7.93	14.00	6.07
6525	-	5.77	-	-	-	2.60	8.37	14.00	5.63

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	8.73	-	-	-	2.60	11.33	14.00	2.67

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	-	7.26	-	-	-	2.60	9.86	14.00	4.14

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	10.28	-	-	-	2.60	12.88	14.00	1.12

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	10.29	-	-	-	2.60	12.89	14.00	1.11

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	-	10.32	-	-	-	2.60	12.92	14.00	1.08

Maximum EIRP (U-NII-6) / VLP (continued)**Results: VLP / MIMO CDD**

Antenna Configuration:	MIMO CDD	Mode:	802.11a20
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-3.24	-2.86	-	-	-0.03	2.60	2.57	14.00	11.43
6475	-3.07	-2.70	-	-	0.12	2.60	2.72	14.00	11.28
6515	-3.46	-2.88	-	-	-0.16	2.60	2.44	14.00	11.56

Antenna Configuration:	MIMO CDD	Mode:	802.11a40
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	0.04	0.40	-	-	3.22	2.60	5.82	14.00	8.18
6485	-0.18	0.32	-	-	3.08	2.60	5.68	14.00	8.32
6525	0.30	0.66	-	-	3.49	2.60	6.09	14.00	7.91

Antenna Configuration:	MIMO CDD	Mode:	802.11a80
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	3.09	3.23	-	-	6.17	2.60	8.77	14.00	5.23

Antenna Configuration:	MIMO CDD	Mode:	802.11a160
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	5.89	5.98	-	-	8.93	2.60	11.53	14.00	2.47

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-2.98	-2.51	-	-	0.27	2.60	2.87	14.00	11.13
6475	-3.12	-2.71	-	-	0.10	2.60	2.70	14.00	11.30
6515	-3.19	-2.53	-	-	0.16	2.60	2.76	14.00	11.24

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-9.16	-8.90	-	-	-6.02	2.60	-3.42	14.00	17.42
6475	-9.48	-8.96	-	-	-6.21	2.60	-3.61	14.00	17.61
6515	-9.79	-9.15	-	-	-6.45	2.60	-3.85	14.00	17.85

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-6.16	-5.95	-	-	-3.05	2.60	-0.45	14.00	14.45
6475	-6.47	-5.91	-	-	-3.17	2.60	-0.57	14.00	14.57
6515	-6.58	-5.96	-	-	-3.25	2.60	-0.65	14.00	14.65

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-7.67	-7.38	-	-	-4.52	2.60	-1.92	14.00	15.92
6475	-7.75	-7.20	-	-	-4.46	2.60	-1.86	14.00	15.86
6515	-7.81	-7.10	-	-	-4.43	2.60	-1.83	14.00	15.83

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-5.25	-4.97	-	-	-2.10	2.60	0.50	14.00	13.50
6475	-5.36	-4.80	-	-	-2.07	2.60	0.53	14.00	13.47
6515	-5.66	-5.04	-	-	-2.33	2.60	0.27	14.00	13.73

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-0.24	0.15	-	-	2.97	2.60	5.57	14.00	8.43
6485	-0.35	0.20	-	-	2.94	2.60	5.54	14.00	8.46
6525	0.00	0.57	-	-	3.30	2.60	5.90	14.00	8.10

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	2.77	3.49	-	-	6.15	2.60	8.75	14.00	5.25

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	1.72	2.27	-	-	5.01	2.60	7.61	14.00	6.39

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	5.85	6.23	-	-	9.05	2.60	11.65	14.00	2.35

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	4.61	4.98	-	-	7.80	2.60	10.40	14.00	3.60

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	5.29	5.70	-	-	8.50	2.60	11.10	14.00	2.90

Maximum EIRP (U-NII-6) / VLP (continued)**Results: VLP / MIMO SDM**

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	0.06	0.48	-	-	3.28	1.71	4.99	14.00	9.01
6475	-0.21	0.24	-	-	3.02	1.71	4.74	14.00	9.26
6515	-0.38	0.24	-	-	2.95	1.71	4.67	14.00	9.33

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-9.06	-8.84	-	-	-5.94	1.71	-4.22	14.00	18.22
6475	-9.40	-8.89	-	-	-6.13	1.71	-4.42	14.00	18.42
6515	-9.45	-8.84	-	-	-6.13	1.71	-4.42	14.00	18.42

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-6.34	-6.11	-	-	-3.22	1.71	-1.50	14.00	15.50
6475	-6.48	-5.95	-	-	-3.20	1.71	-1.48	14.00	15.48
6515	-6.78	-6.12	-	-	-3.43	1.71	-1.72	14.00	15.72

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-3.17	-2.98	-	-	-0.06	1.71	1.65	14.00	12.35
6475	-3.61	-3.00	-	-	-0.29	1.71	1.43	14.00	12.57
6515	-3.36	-2.80	-	-	-0.07	1.71	1.65	14.00	12.35

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-4.43	-4.14	-	-	-1.27	1.71	0.44	14.00	13.56
6475	-4.77	-4.22	-	-	-1.48	1.71	0.23	14.00	13.77
6515	-4.82	-4.15	-	-	-1.46	1.71	0.25	14.00	13.75

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-2.30	-2.02	-	-	0.85	1.71	2.56	14.00	11.44
6475	-2.38	-1.80	-	-	0.92	1.71	2.64	14.00	11.36
6515	-2.18	-2.35	-	-	0.73	1.71	2.45	14.00	11.55

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	3.06	3.32	-	-	6.19	1.71	7.90	14.00	6.10
6485	2.75	3.18	-	-	5.98	1.71	7.69	14.00	6.31
6525	3.18	3.43	-	-	6.31	1.71	8.03	14.00	5.97

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	6.15	6.59	-	-	9.36	1.71	11.08	14.00	2.92

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	4.59	5.11	-	-	7.85	1.71	9.57	14.00	4.43

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	7.90	8.16	-	-	11.03	1.71	12.75	14.00	1.25

Maximum EIRP (U-NII-6) / VLP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	7.61	7.93	-	-	10.76	1.71	12.47	14.00	1.53

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	7.84	8.18	-	-	11.00	1.71	12.72	14.00	1.28

Maximum EIRP (U-NII-6) / VLP (continued)**Results: VLP / TxBF**

Antenna Configuration:	TxBF	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6435	-2.98	-2.57	-	-	0.24	4.67	4.91	14.00	9.09
6475	-3.03	-2.67	-	-	0.17	4.67	4.84	14.00	9.16
6515	-3.20	-2.62	-	-	0.11	4.67	4.78	14.00	9.22

Antenna Configuration:	TxBF	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6445	-0.31	0.04	-	-	2.88	4.67	7.54	14.00	6.46
6485	-0.31	0.19	-	-	2.95	4.67	7.62	14.00	6.38
6525	0.04	0.52	-	-	3.29	4.67	7.96	14.00	6.04

Antenna Configuration:	TxBF	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6465	2.69	3.29	-	-	6.01	4.67	10.68	14.00	3.32

Antenna Configuration:	TxBF	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6505	4.83	5.19	-	-	8.02	4.67	12.69	14.00	1.31

Maximum EIRP (U-NII-7) / LPI (continued)**4.3.3 6.525-6.875 GHz band (U-NII-7)****Results: LPI / SISO / Core 0**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	8.18	-	-	-	-	0.60	8.78	24.00	15.22
6715	8.19	-	-	-	-	0.60	8.79	24.00	15.21
6875	7.73	-	-	-	-	1.50	9.23	24.00	14.77

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	11.39	-	-	-	-	0.60	11.99	24.00	12.01
6685	11.39	-	-	-	-	0.60	11.99	24.00	12.01
6845	11.43	-	-	-	-	0.60	12.03	24.00	11.97

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	14.43	-	-	-	-	0.60	15.03	24.00	8.97
6705	14.47	-	-	-	-	0.60	15.07	24.00	8.93
6865	13.69	-	-	-	-	1.50	15.19	24.00	8.81

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	17.19	-	-	-	-	0.60	17.79	24.00	6.21
6825	16.34	-	-	-	-	1.50	17.84	24.00	6.16

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	8.29	-	-	-	-	0.60	8.89	24.00	15.11
6715	8.29	-	-	-	-	0.60	8.89	24.00	15.11
6875	7.84	-	-	-	-	1.50	9.34	24.00	14.66

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-0.88	-	-	-	-	0.60	-0.28	24.00	24.28
6715	-0.77	-	-	-	-	0.60	-0.17	24.00	24.17
6875	-1.49	-	-	-	-	1.50	0.01	24.00	23.99

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	1.98	-	-	-	-	0.60	2.58	24.00	21.42
6715	1.87	-	-	-	-	0.60	2.47	24.00	21.53
6875	1.31	-	-	-	-	1.50	2.81	24.00	21.19

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	4.98	-	-	-	-	0.60	5.58	24.00	18.42
6715	5.07	-	-	-	-	0.60	5.67	24.00	18.33
6875	4.42	-	-	-	-	1.50	5.92	24.00	18.08

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	3.89	-	-	-	-	0.60	4.49	24.00	19.51
6715	3.40	-	-	-	-	0.60	4.00	24.00	20.00
6875	3.28	-	-	-	-	1.50	4.78	24.00	19.22

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	6.08	-	-	-	-	0.60	6.68	24.00	17.32
6715	6.06	-	-	-	-	0.60	6.66	24.00	17.34
6875	5.29	-	-	-	-	1.50	6.79	24.00	17.21

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	11.49	-	-	-	-	0.60	12.09	24.00	11.91
6685	11.53	-	-	-	-	0.60	12.13	24.00	11.87
6845	11.52	-	-	-	-	0.60	12.12	24.00	11.88

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	14.32	-	-	-	-	0.60	14.92	24.00	9.08
6705	14.39	-	-	-	-	0.60	14.99	24.00	9.01
6865	13.54	-	-	-	-	1.50	15.04	24.00	8.96

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	13.20	-	-	-	-	0.60	13.80	24.00	10.20
6705	13.00	-	-	-	-	0.60	13.60	24.00	10.40
6865	12.27	-	-	-	-	1.50	13.77	24.00	10.23

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	17.08	-	-	-	-	0.60	17.68	24.00	6.32
6825	15.92	-	-	-	-	1.50	17.42	24.00	6.58

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	16.08	-	-	-	-	0.60	16.68	24.00	7.32
6825	14.72	-	-	-	-	1.50	16.22	24.00	7.78

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	16.75	-	-	-	-	0.60	17.35	24.00	6.65
6825	15.78	-	-	-	-	1.50	17.28	24.00	6.72

Maximum EIRP (U-NII-7) / LPI (continued)**Results: LPI / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	7.05	-	-	-	1.90	8.95	24.00	15.05
6715	-	6.85	-	-	-	1.90	8.75	24.00	15.25
6875	-	7.04	-	-	-	1.90	8.94	24.00	15.06

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-	10.01	-	-	-	1.90	11.91	24.00	12.09
6685	-	10.09	-	-	-	1.90	11.99	24.00	12.01
6845	-	10.01	-	-	-	1.90	11.91	24.00	12.09

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	12.76	-	-	-	2.60	15.36	24.00	8.64
6705	-	13.27	-	-	-	1.90	15.17	24.00	8.83
6865	-	13.15	-	-	-	1.90	15.05	24.00	8.95

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	16.01	-	-	-	1.90	17.91	24.00	6.09
6825	-	15.95	-	-	-	1.90	17.85	24.00	6.15

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	7.05	-	-	-	1.90	8.95	24.00	15.05
6715	-	7.07	-	-	-	1.90	8.97	24.00	15.03
6875	-	7.22	-	-	-	1.90	9.12	24.00	14.88

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	-2.05	-	-	-	1.90	-0.15	24.00	24.15
6715	-	-2.03	-	-	-	1.90	-0.13	24.00	24.13
6875	-	-1.78	-	-	-	1.90	0.12	24.00	23.88

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	0.90	-	-	-	1.90	2.80	24.00	21.20
6715	-	0.85	-	-	-	1.90	2.75	24.00	21.25
6875	-	0.76	-	-	-	1.90	2.66	24.00	21.34

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	3.82	-	-	-	1.90	5.72	24.00	18.28
6715	-	3.85	-	-	-	1.90	5.75	24.00	18.25
6875	-	3.96	-	-	-	1.90	5.86	24.00	18.14

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	2.29	-	-	-	1.90	4.19	24.00	19.81
6715	-	2.30	-	-	-	1.90	4.20	24.00	19.80
6875	-	2.87	-	-	-	1.90	4.77	24.00	19.23

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	4.67	-	-	-	1.90	6.57	24.00	17.43
6715	-	4.69	-	-	-	1.90	6.59	24.00	17.41
6875	-	4.78	-	-	-	1.90	6.68	24.00	17.32

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-	10.00	-	-	-	1.90	11.90	24.00	12.10
6685	-	10.06	-	-	-	1.90	11.96	24.00	12.04
6845	-	10.12	-	-	-	1.90	12.02	24.00	11.98

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	12.77	-	-	-	2.60	15.37	24.00	8.63
6705	-	13.12	-	-	-	1.90	15.02	24.00	8.98
6865	-	13.08	-	-	-	1.90	14.98	24.00	9.02

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	11.17	-	-	-	2.60	13.77	24.00	10.23
6705	-	11.71	-	-	-	1.90	13.61	24.00	10.39
6865	-	11.75	-	-	-	1.90	13.65	24.00	10.35

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	15.72	-	-	-	1.90	17.62	24.00	6.38
6825	-	15.70	-	-	-	1.90	17.60	24.00	6.40

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	14.62	-	-	-	1.90	16.52	24.00	7.48
6825	-	14.60	-	-	-	1.90	16.50	24.00	7.50

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	15.34	-	-	-	1.90	17.24	24.00	6.76
6825	-	15.34	-	-	-	1.90	17.24	24.00	6.76

Maximum EIRP (U-NII-7) / LPI (continued)**Results: LPI / MIMO CDD**

Antenna Configuration:	MIMO CDD	Mode:	802.11a20
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	0.84	1.20	-	-	4.03	1.90	5.93	24.00	18.07
6715	0.76	1.30	-	-	4.05	1.90	5.95	24.00	18.05
6875	1.12	1.35	-	-	4.24	1.90	6.14	24.00	17.86

Antenna Configuration:	MIMO CDD	Mode:	802.11a40
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	4.66	4.77	-	-	7.72	1.90	9.62	24.00	14.38
6685	4.60	4.69	-	-	7.64	1.90	9.54	24.00	14.46
6845	4.36	4.67	-	-	7.53	1.90	9.43	24.00	14.57

Antenna Configuration:	MIMO CDD	Mode:	802.11a80
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	7.32	7.52	-	-	10.43	2.60	13.03	24.00	10.97
6705	7.67	7.65	-	-	10.67	1.90	12.57	24.00	11.43
6865	7.31	7.25	-	-	10.29	1.90	12.19	24.00	11.81

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11a160
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	10.34	9.89	-	-	13.10	1.90	15.00	24.00	9.00
6825	10.19	9.89	-	-	13.03	1.90	14.93	24.00	9.07

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	1.16	1.60	-	-	4.39	1.90	6.29	24.00	17.71
6715	1.20	1.57	-	-	4.40	1.90	6.30	24.00	17.70
6875	1.26	1.46	-	-	4.37	1.90	6.27	24.00	17.73

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-7.75	-7.55	-	-	-4.64	1.90	-2.74	24.00	26.74
6715	-7.82	-7.54	-	-	-4.67	1.90	-2.77	24.00	26.77
6875	-7.94	-7.76	-	-	-4.84	1.90	-2.94	24.00	26.94

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-4.86	-4.66	-	-	-1.75	1.90	0.15	24.00	23.85
6715	-5.27	-4.81	-	-	-2.02	1.90	-0.12	24.00	24.12
6875	-5.31	-5.07	-	-	-2.18	1.90	-0.28	24.00	24.28

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-1.97	-1.79	-	-	1.13	1.90	3.03	24.00	20.97
6715	-2.23	-1.84	-	-	0.98	1.90	2.88	24.00	21.12
6875	-2.21	-1.96	-	-	0.93	1.90	2.83	24.00	21.17

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-3.55	-3.07	-	-	-0.30	1.90	1.60	24.00	22.40
6715	-3.53	-3.05	-	-	-0.28	1.90	1.62	24.00	22.38
6875	-3.38	-3.12	-	-	-0.24	1.90	1.66	24.00	22.34

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-1.06	-0.62	-	-	2.17	1.90	4.07	24.00	19.93
6715	-1.03	-0.64	-	-	2.18	1.90	4.08	24.00	19.92
6875	-1.27	-1.05	-	-	1.85	1.90	3.75	24.00	20.25

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	3.88	4.55	-	-	7.24	1.90	9.14	24.00	14.86
6685	4.59	4.77	-	-	7.67	1.90	9.57	24.00	14.43
6845	4.55	4.76	-	-	7.66	1.90	9.56	24.00	14.44

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	7.33	7.54	-	-	10.44	2.60	13.04	24.00	10.96
6705	7.62	7.59	-	-	10.59	1.90	12.49	24.00	11.51
6865	7.23	7.20	-	-	10.21	1.90	12.11	24.00	11.89

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	5.97	6.10	-	-	9.04	2.60	11.64	24.00	12.36
6705	6.23	6.26	-	-	9.25	1.90	11.15	24.00	12.85
6865	5.68	5.81	-	-	8.75	1.90	10.65	24.00	13.35

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	10.32	10.19	-	-	13.26	1.90	15.16	24.00	8.84
6825	10.06	10.05	-	-	13.04	1.90	14.94	24.00	9.06

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	9.04	9.02	-	-	12.03	1.90	13.93	24.00	10.07
6825	8.02	8.79	-	-	11.42	1.90	13.32	24.00	10.68

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	9.74	9.66	-	-	12.70	1.90	14.60	24.00	9.40
6825	9.36	9.42	-	-	12.40	1.90	14.30	24.00	9.70

Maximum EIRP (U-NII-7) / LPI (continued)**Results: LPI / MIMO SDM**

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	4.17	4.62	-	-	7.36	1.30	8.66	24.00	15.34
6855	4.53	4.76	-	-	7.65	1.30	8.94	24.00	15.06
6875	4.15	4.32	-	-	7.24	1.70	8.94	24.00	15.06

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-4.84	-4.53	-	-	-1.67	1.30	-0.37	24.00	24.37
6715	-4.90	-4.49	-	-	-1.69	1.30	-0.39	24.00	24.39
6875	-5.01	-4.77	-	-	-1.88	1.70	-0.17	24.00	24.17

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-2.12	-1.83	-	-	1.04	1.30	2.34	24.00	21.66
6715	-2.08	-1.60	-	-	1.18	1.30	2.48	24.00	21.52
6875	-2.16	-1.84	-	-	1.01	1.70	2.71	24.00	21.29

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	0.96	1.27	-	-	4.12	1.30	5.42	24.00	18.58
6715	0.95	1.36	-	-	4.17	1.30	5.47	24.00	18.53
6875	0.85	1.11	-	-	3.99	1.70	5.69	24.00	18.31

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-0.54	-0.10	-	-	2.69	1.30	3.99	24.00	20.01
6715	-0.57	-0.18	-	-	2.63	1.30	3.93	24.00	20.07
6875	-0.20	0.01	-	-	2.91	1.70	4.62	24.00	19.38

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	1.85	2.27	-	-	5.08	1.30	6.37	24.00	17.63
6715	1.78	2.22	-	-	5.01	1.30	6.31	24.00	17.69
6875	1.67	1.89	-	-	4.79	1.70	6.50	24.00	17.50

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	7.41	7.66	-	-	10.54	1.30	11.84	24.00	12.16
6685	7.46	7.61	-	-	10.53	1.30	11.83	24.00	12.17
6845	7.46	7.47	-	-	10.47	1.30	11.77	24.00	12.23

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	10.43	10.58	-	-	13.52	1.71	15.23	24.00	8.77
6705	10.69	10.68	-	-	13.68	1.30	14.98	24.00	9.02
6865	10.16	10.04	-	-	13.10	1.70	14.80	24.00	9.20

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	9.14	9.05	-	-	12.11	1.71	13.82	24.00	10.18
6705	9.09	9.00	-	-	12.05	1.30	13.35	24.00	10.65
6865	8.90	8.91	-	-	11.92	1.70	13.62	24.00	10.38

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	13.26	13.32	-	-	16.30	1.30	17.60	24.00	6.40
6825	12.74	12.78	-	-	15.76	1.70	17.47	24.00	6.53

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	12.20	12.08	-	-	15.14	1.30	16.44	24.00	7.56
6825	10.79	11.58	-	-	14.21	1.70	15.91	24.00	8.09

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	12.87	12.79	-	-	15.83	1.30	17.13	24.00	6.87
6825	12.56	12.48	-	-	15.52	1.70	17.23	24.00	6.77

Maximum EIRP (U-NII-7) / LPI (continued)**Results: LPI / TxBF**

Antenna Configuration:	TxBF	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	1.24	1.65	-	-	4.46	4.28	8.74	24.00	15.26
6715	1.20	1.57	-	-	4.40	4.28	8.68	24.00	15.32
6875	1.22	1.43	-	-	4.34	4.71	9.05	24.00	14.95

Antenna Configuration:	TxBF	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	4.40	4.66	-	-	7.52	4.28	11.80	24.00	12.20
6685	4.48	4.60	-	-	7.54	4.28	11.82	24.00	12.18
6845	4.62	4.78	-	-	7.68	4.28	11.97	24.00	12.03

Antenna Configuration:	TxBF	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	7.40	7.58	-	-	10.48	4.67	15.15	24.00	8.85
6705	7.66	7.60	-	-	10.62	4.28	14.91	24.00	9.09
6865	7.22	7.24	-	-	10.24	4.71	14.95	24.00	9.05

Maximum EIRP (U-NII-7) / LPI (continued)

Antenna Configuration:	TxBF	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	10.35	10.25	-	-	13.30	4.28	17.59	24.00	6.41
6825	9.72	9.68	-	-	12.71	4.71	17.42	24.00	6.58

Maximum EIRP (U-NII-7) / SP (continued)**Results: SP / SISO / Core 0**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	19.46	-	-	-	-	0.60	20.06	30.00	9.94
6715	19.17	-	-	-	-	0.60	19.77	30.00	10.23
6855	19.33	-	-	-	-	0.60	19.93	30.00	10.07

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	19.31	-	-	-	-	0.60	19.91	30.00	10.09
6685	19.04	-	-	-	-	0.60	19.64	30.00	10.36
6845	19.12	-	-	-	-	0.60	19.72	30.00	10.28

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	19.32	-	-	-	-	0.60	19.92	30.00	10.08
6625	19.44	-	-	-	-	0.60	20.04	30.00	9.96
6705	19.38	-	-	-	-	0.60	19.98	30.00	10.02
6785	19.38	-	-	-	-	0.60	19.98	30.00	10.02

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.50	-	-	-	-	0.60	20.10	30.00	9.90

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	19.26	-	-	-	-	0.60	19.86	30.00	10.14
6715	19.48	-	-	-	-	0.60	20.08	30.00	9.92
6855	19.35	-	-	-	-	0.60	19.95	30.00	10.05

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	11.94	-	-	-	-	0.60	12.54	30.00	17.46
6715	11.86	-	-	-	-	0.60	12.46	30.00	17.54
6855	11.91	-	-	-	-	0.60	12.51	30.00	17.49

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	14.92	-	-	-	-	0.60	15.52	30.00	14.48
6715	14.91	-	-	-	-	0.60	15.51	30.00	14.49
6855	14.98	-	-	-	-	0.60	15.58	30.00	14.42

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	17.97	-	-	-	-	0.60	18.57	30.00	11.43
6715	17.84	-	-	-	-	0.60	18.44	30.00	11.56
6855	17.98	-	-	-	-	0.60	18.58	30.00	11.42

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	16.43	-	-	-	-	0.60	17.03	30.00	12.97
6715	16.37	-	-	-	-	0.60	16.97	30.00	13.03
6855	16.34	-	-	-	-	0.60	16.94	30.00	13.06

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	18.50	-	-	-	-	0.60	19.10	30.00	10.90
6715	18.31	-	-	-	-	0.60	18.91	30.00	11.09
6855	18.39	-	-	-	-	0.60	18.99	30.00	11.01

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	19.49	-	-	-	-	0.60	20.09	30.00	9.91
6685	19.28	-	-	-	-	0.60	19.88	30.00	10.12
6845	19.34	-	-	-	-	0.60	19.94	30.00	10.06

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	19.50	-	-	-	-	0.60	20.10	30.00	9.90
6625	19.39	-	-	-	-	0.60	19.99	30.00	10.01
6705	19.45	-	-	-	-	0.60	20.05	30.00	9.95
6785	19.01	-	-	-	-	0.60	19.61	30.00	10.39

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	19.37	-	-	-	-	0.60	19.97	30.00	10.03
6625	19.26	-	-	-	-	0.60	19.86	30.00	10.14
6705	19.38	-	-	-	-	0.60	19.98	30.00	10.02
6785	19.49	-	-	-	-	0.60	20.09	30.00	9.91

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.33	-	-	-	-	0.60	19.93	30.00	10.07

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.47	-	-	-	-	0.60	20.07	30.00	9.93

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.35	-	-	-	-	0.60	19.95	30.00	10.05

Maximum EIRP (U-NII-7) / SP (continued)**Results: SP / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	19.39	-	-	-	1.90	21.29	30.00	8.71
6715	-	19.39	-	-	-	1.90	21.29	30.00	8.71
6855	-	19.37	-	-	-	1.90	21.27	30.00	8.73

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-	19.43	-	-	-	1.90	21.33	30.00	8.67
6685	-	19.33	-	-	-	1.90	21.23	30.00	8.77
6845	-	19.20	-	-	-	1.90	21.10	30.00	8.90

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	19.33	-	-	-	2.60	21.93	30.00	8.07
6625	-	19.42	-	-	-	1.90	21.32	30.00	8.68
6705	-	19.49	-	-	-	1.90	21.39	30.00	8.61
6785	-	19.49	-	-	-	1.90	21.39	30.00	8.61

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	19.22	-	-	-	1.90	21.12	30.00	8.88

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	19.46	-	-	-	1.90	21.36	30.00	8.64
6715	-	19.32	-	-	-	1.90	21.22	30.00	8.78
6855	-	19.34	-	-	-	1.90	21.24	30.00	8.76

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	11.82	-	-	-	1.90	13.72	30.00	16.28
6715	-	11.94	-	-	-	1.90	13.84	30.00	16.16
6855	-	11.82	-	-	-	1.90	13.72	30.00	16.28

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	15.00	-	-	-	1.90	16.90	30.00	13.10
6715	-	14.90	-	-	-	1.90	16.80	30.00	13.20
6855	-	14.77	-	-	-	1.90	16.67	30.00	13.33

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	17.92	-	-	-	1.90	19.82	30.00	10.18
6715	-	17.84	-	-	-	1.90	19.74	30.00	10.26
6855	-	17.93	-	-	-	1.90	19.83	30.00	10.17

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	16.34	-	-	-	1.90	18.24	30.00	11.76
6715	-	16.28	-	-	-	1.90	18.18	30.00	11.82
6855	-	16.47	-	-	-	1.90	18.37	30.00	11.63

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	18.30	-	-	-	1.90	20.20	30.00	9.80
6715	-	18.47	-	-	-	1.90	20.37	30.00	9.63
6855	-	18.35	-	-	-	1.90	20.25	30.00	9.75

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-	19.32	-	-	-	1.90	21.22	30.00	8.78
6685	-	19.31	-	-	-	1.90	21.21	30.00	8.79
6845	-	19.43	-	-	-	1.90	21.33	30.00	8.67

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	19.43	-	-	-	2.60	22.03	30.00	7.97
6625	-	19.43	-	-	-	1.90	21.33	30.00	8.67
6705	-	19.29	-	-	-	1.90	21.19	30.00	8.81
6785	-	19.39	-	-	-	1.90	21.29	30.00	8.71

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	19.31	-	-	-	2.60	21.91	30.00	8.09
6625	-	19.34	-	-	-	1.90	21.24	30.00	8.76
6705	-	19.32	-	-	-	1.90	21.22	30.00	8.78
6785	-	19.37	-	-	-	1.90	21.27	30.00	8.73

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	19.26	-	-	-	1.90	21.16	30.00	8.84

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	19.45	-	-	-	1.90	21.35	30.00	8.65

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	19.26	-	-	-	1.90	21.16	30.00	8.84

Maximum EIRP (U-NII-7) / SP (continued)**Results: SP / MIMO CDD**

Antenna Configuration:	MIMO CDD	Mode:	802.11a20
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	19.37	19.42	-	-	22.39	1.90	24.29	30.00	5.71
6715	19.12	19.32	-	-	22.21	1.90	24.11	30.00	5.89
6855	19.10	19.37	-	-	22.25	1.90	24.15	30.00	5.85

Antenna Configuration:	MIMO CDD	Mode:	802.11a40
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	19.09	19.26	-	-	22.18	1.90	24.08	30.00	5.92
6685	18.84	19.17	-	-	22.02	1.90	23.92	30.00	6.08
6845	18.89	19.00	-	-	21.94	1.90	23.84	30.00	6.16

Antenna Configuration:	MIMO CDD	Mode:	802.11a80
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	18.68	19.41	-	-	22.04	2.60	24.64	30.00	5.36
6625	18.58	19.33	-	-	21.97	1.90	23.87	30.00	6.13
6705	18.75	19.46	-	-	22.12	1.90	24.02	30.00	5.98
6785	18.52	19.30	-	-	21.92	1.90	23.82	30.00	6.18

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11a160
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.42	19.37	-	-	22.39	1.90	24.29	30.00	5.71

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	19.37	19.42	-	-	22.39	1.90	24.29	30.00	5.71
6715	19.12	19.28	-	-	22.20	1.90	24.10	30.00	5.90
6855	19.12	19.38	-	-	22.26	1.90	24.16	30.00	5.84

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	9.46	10.55	-	-	13.04	1.90	14.94	30.00	15.06
6715	9.12	10.41	-	-	12.82	1.90	14.72	30.00	15.28
6855	9.06	10.48	-	-	12.83	1.90	14.73	30.00	15.27

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	11.90	13.12	-	-	15.55	1.90	17.45	30.00	12.55
6715	11.85	13.21	-	-	15.58	1.90	17.48	30.00	12.52
6855	11.59	13.11	-	-	15.42	1.90	17.32	30.00	12.68

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	15.01	16.24	-	-	18.67	1.90	20.57	30.00	9.43
6715	14.77	16.20	-	-	18.55	1.90	20.45	30.00	9.55
6855	14.59	16.21	-	-	18.48	1.90	20.38	30.00	9.62

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	13.11	14.99	-	-	17.15	1.90	19.05	30.00	10.95
6715	13.78	14.87	-	-	17.35	1.90	19.25	30.00	10.75
6855	13.95	14.99	-	-	17.51	1.90	19.41	30.00	10.59

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	15.30	17.16	-	-	19.34	1.90	21.24	30.00	8.76
6715	16.16	17.29	-	-	19.76	1.90	21.66	30.00	8.34
6855	16.18	17.37	-	-	19.80	1.90	21.70	30.00	8.30

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	19.17	19.28	-	-	22.21	1.90	24.11	30.00	5.89
6685	19.10	19.38	-	-	22.25	1.90	24.15	30.00	5.85
6845	19.24	19.29	-	-	22.26	1.90	24.16	30.00	5.84

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	18.58	19.47	-	-	22.04	2.60	24.64	30.00	5.36
6625	18.57	19.46	-	-	22.04	1.90	23.94	30.00	6.06
6705	18.60	19.33	-	-	21.99	1.90	23.89	30.00	6.11
6785	18.64	19.37	-	-	22.02	1.90	23.92	30.00	6.08

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	18.85	19.29	-	-	22.07	2.60	24.67	30.00	5.33
6625	18.62	19.26	-	-	21.94	1.90	23.84	30.00	6.16
6705	18.83	19.31	-	-	22.08	1.90	23.98	30.00	6.02
6785	18.74	19.36	-	-	22.06	1.90	23.96	30.00	6.04

Antenna Configuration:	MIMO CDD	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.30	19.25	-	-	22.28	1.90	24.18	30.00	5.82

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	18.10	19.33	-	-	21.75	1.90	23.65	30.00	6.35

Antenna Configuration:	MIMO CDD	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	18.33	19.41	-	-	21.86	1.90	23.76	30.00	6.24

Maximum EIRP (U-NII-7) / SP (continued)**Results: SP / MIMO SDM**

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	19.29	19.31	-	-	22.30	1.30	23.60	30.00	6.40
6715	19.28	19.39	-	-	22.33	1.30	23.63	30.00	6.37
6855	19.06	19.31	-	-	22.18	1.30	23.48	30.00	6.52

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	10.59	11.82	-	-	14.25	1.30	15.55	30.00	14.45
6715	10.67	11.94	-	-	14.36	1.30	15.66	30.00	14.34
6855	10.34	11.83	-	-	14.15	1.30	15.44	30.00	14.56

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU52
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	13.56	14.88	-	-	17.27	1.30	18.57	30.00	11.43
6715	13.53	14.97	-	-	17.32	1.30	18.62	30.00	11.38
6855	13.20	14.84	-	-	17.09	1.30	18.39	30.00	11.61

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE20 RU106
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS11x2 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	16.42	17.75	-	-	20.13	1.30	21.43	30.00	8.57
6715	16.42	17.88	-	-	20.21	1.30	21.51	30.00	8.49
6855	16.25	17.96	-	-	20.17	1.30	21.47	30.00	8.53

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	14.40	16.28	-	-	18.44	1.30	19.74	30.00	10.26
6715	15.22	16.38	-	-	18.83	1.30	20.13	30.00	9.87
6855	15.26	16.47	-	-	18.90	1.30	20.20	30.00	9.80

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	16.51	18.42	-	-	20.57	1.30	21.87	30.00	8.13
6715	17.11	18.30	-	-	20.73	1.30	22.02	30.00	7.98
6855	17.17	18.35	-	-	20.80	1.30	22.10	30.00	7.90

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	19.22	19.38	-	-	22.31	1.30	23.61	30.00	6.39
6685	18.95	19.24	-	-	22.10	1.30	23.39	30.00	6.61
6845	19.07	19.11	-	-	22.09	1.30	23.39	30.00	6.61

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	18.61	19.45	-	-	22.04	1.71	23.75	30.00	6.25
6625	18.58	19.36	-	-	21.96	1.30	23.26	30.00	6.74
6705	18.55	19.25	-	-	21.90	1.30	23.20	30.00	6.80
6785	18.59	19.30	-	-	21.94	1.30	23.24	30.00	6.76

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	18.77	19.35	-	-	22.08	1.71	23.79	30.00	6.21
6625	18.66	19.28	-	-	21.97	1.30	23.27	30.00	6.73
6705	18.75	19.40	-	-	22.09	1.30	23.39	30.00	6.61
6785	18.70	19.39	-	-	22.05	1.30	23.35	30.00	6.65

Antenna Configuration:	MIMO SDM	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x2 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.26	19.25	-	-	22.26	1.30	23.56	30.00	6.44

Maximum EIRP (U-NII-7) / SP (continued)

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	18.19	19.30	-	-	21.78	1.30	23.07	30.00	6.93

Antenna Configuration:	MIMO SDM	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS9x2 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	18.27	19.38	-	-	21.86	1.30	23.16	30.00	6.84

Maximum EIRP (U-NII-7) / SP (continued)**Results: SP / TxBF**

Antenna Configuration:	TxBF	Mode:	802.11ax HE20 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	19.44	19.42	-	-	22.44	4.28	26.73	30.00	3.27
6715	19.40	19.49	-	-	22.44	4.28	26.72	30.00	3.28
6855	19.20	19.39	-	-	22.29	4.28	26.58	30.00	3.42

Antenna Configuration:	TxBF	Mode:	802.11ax HE40 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	19.41	19.50	-	-	22.46	4.28	26.75	30.00	3.25
6685	19.18	19.43	-	-	22.30	4.28	26.59	30.00	3.41
6845	19.26	19.27	-	-	22.26	4.28	26.54	30.00	3.46

Antenna Configuration:	TxBF	Mode:	802.11ax HE80 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	18.73	19.48	-	-	22.10	4.67	26.76	30.00	3.24
6625	18.64	19.38	-	-	22.01	4.28	26.30	30.00	3.70
6705	18.67	19.30	-	-	22.00	4.28	26.28	30.00	3.72
6785	18.68	19.32	-	-	21.99	4.28	26.27	30.00	3.73

Antenna Configuration:	TxBF	Mode:	802.11ax HE160 SU
Test Port:	1+2 (Core 0+Core1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	19.36	19.20	-	-	22.29	4.28	26.57	30.00	3.43

Maximum EIRP (U-NII-7) / VLP (continued)**Results: VLP / SISO / Core 0**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	3.89	-	-	-	-	0.60	4.49	14.00	9.51
6715	4.17	-	-	-	-	0.60	4.77	14.00	9.23
6875	3.79	-	-	-	-	1.50	5.29	14.00	8.71

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	7.49	-	-	-	-	0.60	8.09	14.00	5.91
6685	7.32	-	-	-	-	0.60	7.92	14.00	6.08
6845	7.46	-	-	-	-	0.60	8.06	14.00	5.94

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	10.57	-	-	-	-	0.60	11.17	14.00	2.83
6705	10.33	-	-	-	-	0.60	10.93	14.00	3.07
6865	9.77	-	-	-	-	1.50	11.27	14.00	2.73

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	1 (Core 0)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	12.27	-	-	-	-	0.60	12.87	14.00	1.13
6825	11.23	-	-	-	-	1.50	12.73	14.00	1.27

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	4.46	-	-	-	-	0.60	5.06	14.00	8.94
6715	4.49	-	-	-	-	0.60	5.09	14.00	8.91
6875	3.82	-	-	-	-	1.50	5.32	14.00	8.68

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-4.84	-	-	-	-	0.60	-4.24	14.00	18.24
6715	-4.61	-	-	-	-	0.60	-4.01	14.00	18.01
6875	-5.64	-	-	-	-	1.50	-4.14	14.00	18.14

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-2.15	-	-	-	-	0.60	-1.55	14.00	15.55
6715	-2.09	-	-	-	-	0.60	-1.49	14.00	15.49
6875	-2.64	-	-	-	-	1.50	-1.14	14.00	15.14

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	1 (Core 0)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	1.05	-	-	-	-	0.60	1.65	14.00	12.35
6715	1.00	-	-	-	-	0.60	1.60	14.00	12.40
6875	0.29	-	-	-	-	1.50	1.79	14.00	12.21

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-0.22	-	-	-	-	0.60	0.38	14.00	13.62
6715	-0.29	-	-	-	-	0.60	0.31	14.00	13.69
6875	-0.87	-	-	-	-	1.50	0.63	14.00	13.37

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	1.91	-	-	-	-	0.60	2.51	14.00	11.49
6715	2.10	-	-	-	-	0.60	2.70	14.00	11.30
6875	1.27	-	-	-	-	1.50	2.77	14.00	11.23

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	7.57	-	-	-	-	0.60	8.17	14.00	5.83
6685	7.50	-	-	-	-	0.60	8.10	14.00	5.90
6845	7.40	-	-	-	-	0.60	8.00	14.00	6.00

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	10.45	-	-	-	-	0.60	11.05	14.00	2.95
6705	10.48	-	-	-	-	0.60	11.08	14.00	2.92
6865	9.75	-	-	-	-	1.50	11.25	14.00	2.75

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	9.21	-	-	-	-	0.60	9.81	14.00	4.19
6705	9.20	-	-	-	-	0.60	9.80	14.00	4.20
6865	8.17	-	-	-	-	1.50	9.67	14.00	4.33

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	1 (Core 0)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	12.20	-	-	-	-	0.60	12.80	14.00	1.20
6825	11.19	-	-	-	-	1.50	12.69	14.00	1.31

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	11.96	-	-	-	-	0.60	12.56	14.00	1.44
6825	10.84	-	-	-	-	1.50	12.34	14.00	1.66

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	1 (Core 0)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	12.12	-	-	-	-	0.60	12.72	14.00	1.28
6825	11.39	-	-	-	-	1.50	12.89	14.00	1.11

Maximum EIRP (U-NII-7) / VLP (continued)**Results: VLP / SISO / Core 1**

Antenna Configuration:	SISO	Mode:	802.11a20
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	3.10	-	-	-	1.90	5.00	14.00	9.00
6715	-	2.94	-	-	-	1.90	4.84	14.00	9.16
6875	-	2.93	-	-	-	1.90	4.83	14.00	9.17

Antenna Configuration:	SISO	Mode:	802.11a40
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-	6.18	-	-	-	1.90	8.08	14.00	5.92
6685	-	6.11	-	-	-	1.90	8.01	14.00	5.99
6845	-	6.08	-	-	-	1.90	7.98	14.00	6.02

Antenna Configuration:	SISO	Mode:	802.11a80
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	8.83	-	-	-	2.60	11.43	14.00	2.57
6705	-	9.24	-	-	-	1.90	11.14	14.00	2.86
6865	-	9.13	-	-	-	1.90	11.03	14.00	2.97

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11a160
Test Port:	2 (Core 1)	Rate/Modulation:	12 Mbps (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	10.89	-	-	-	1.90	12.79	14.00	1.21
6825	-	10.76	-	-	-	1.90	12.66	14.00	1.34

Antenna Configuration:	SISO	Mode:	802.11ax HE20 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	3.17	-	-	-	1.90	5.07	14.00	8.93
6715	-	3.17	-	-	-	1.90	5.07	14.00	8.93
6875	-	3.21	-	-	-	1.90	5.11	14.00	8.89

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	-6.19	-	-	-	1.90	-4.29	14.00	18.29
6715	-	-6.14	-	-	-	1.90	-4.24	14.00	18.24
6875	-	-5.75	-	-	-	1.90	-3.85	14.00	17.85

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU52
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	-3.29	-	-	-	1.90	-1.39	14.00	15.39
6715	-	-3.16	-	-	-	1.90	-1.26	14.00	15.26
6875	-	-3.00	-	-	-	1.90	-1.10	14.00	15.10

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE20 RU106
Test Port:	2 (Core 1)	Rate/Modulation:	MCS11x1 (1024QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	-0.10	-	-	-	1.90	1.80	14.00	12.20
6715	-	-0.29	-	-	-	1.90	1.61	14.00	12.39
6875	-	0.20	-	-	-	1.90	2.10	14.00	11.90

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 52+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	-1.71	-	-	-	1.90	0.19	14.00	13.81
6715	-	-1.64	-	-	-	1.90	0.26	14.00	13.74
6875	-	-1.24	-	-	-	1.90	0.66	14.00	13.34

Antenna Configuration:	SISO	Mode:	802.11be EHT20 MRU 106+26
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6535	-	0.71	-	-	-	1.90	2.61	14.00	11.39
6715	-	0.76	-	-	-	1.90	2.66	14.00	11.34
6875	-	0.85	-	-	-	1.90	2.75	14.00	11.25

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11ax HE40 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6565	-	6.05	-	-	-	1.90	7.95	14.00	6.05
6685	-	6.13	-	-	-	1.90	8.03	14.00	5.97
6845	-	6.08	-	-	-	1.90	7.98	14.00	6.02

Antenna Configuration:	SISO	Mode:	802.11ax HE80 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	8.81	-	-	-	2.60	11.41	14.00	2.59
6705	-	9.16	-	-	-	1.90	11.06	14.00	2.94
6865	-	9.08	-	-	-	1.90	10.98	14.00	3.02

Antenna Configuration:	SISO	Mode:	802.11be EHT80 MRU 484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6545	-	7.25	-	-	-	2.60	9.85	14.00	4.15
6705	-	7.69	-	-	-	1.90	9.59	14.00	4.41
6865	-	7.74	-	-	-	1.90	9.64	14.00	4.36

Antenna Configuration:	SISO	Mode:	802.11ax HE160 SU
Test Port:	2 (Core 1)	Rate/Modulation:	MCS2x1 (QPSK)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	10.70	-	-	-	1.90	12.60	14.00	1.40
6825	-	10.69	-	-	-	1.90	12.59	14.00	1.41

Maximum EIRP (U-NII-7) / VLP (continued)

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	10.70	-	-	-	1.90	12.60	14.00	1.40
6825	-	10.62	-	-	-	1.90	12.52	14.00	1.48

Antenna Configuration:	SISO	Mode:	802.11be EHT160 MRU 996+484+242
Test Port:	2 (Core 1)	Rate/Modulation:	MCS9x1 (256QAM)

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	1	2	3	4	Σ				
6665	-	10.74	-	-	-	1.90	12.64	14.00	1.36
6825	-	10.89	-	-	-	1.90	12.79	14.00	1.21