

RF Exposure Exemption Report

Apple Inc
Model: A3545



Add value.
Inspire trust.

In accordance with FCC CFR 47 Part 1.1307

Prepared for: Apple Inc
One Apple Park Way
Cupertino
California
95014
USA

TUV SUD
SERVICES
(UK)
LIMITED

Digitally signed
by TUV SUD
SERVICES (UK)
LIMITED
Date: 2026.07.07
14:16:50 +01'00'

COMMERCIAL-IN-CONFIDENCE

FCC ID: BCGA3545



Document 75966523-40 Issue: 01

SIGNATURE

NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Matthew Russell	Chief Engineer, RF	Authorised Signatory	07 July 2026

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD document control rules.

FCC Accreditation
294497/UK2010 Octagon House, Fareham Test Laboratory

EXECUTIVE SUMMARY

The wireless devices described within this report are compliant with the exemption criteria related to human exposure to electromagnetic fields laid out in FCC CFR Title 47 Part 1.1307.



DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care. The document is confidential to the Client and TÜV SÜD. This document may not be reproduced except in entirety, without the prior written approval of TÜV SÜD. © 2026 TÜV SÜD. This report relates only to the actual item/items tested.

ACCREDITATION

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation. Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited). Results of tests covered by our Flexible UKAS Accreditation Schedule are marked FS (Flexible Scope).

TÜV SÜD
is a trading name of TÜV SÜD Ltd
Registered in Scotland at East Kilbride,
Glasgow G75 0AF, United Kingdom
Registered number: SC215164

TÜV SÜD Ltd is a
TÜV SÜD Group Company

Phone: +44 (0) 1489 558100
Fax: +44 (0) 1489 558101
www.tuvsud.com/en

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire PO15 5RL
United Kingdom



Contents

1 Report Summary2

1.1 Report Modification Record.....2

1.2 Introduction.....2

1.3 Brief Summary of Results3

1.4 Product Information4

1.5 Test Location7

2 Assessment Details8

2.1 Single RF Source Options for Determination of Exemption.....8

2.2 Multiple RF Sources Options for Determination of Exemption9

2.3 Individual Antenna Port Exposure Results.....10

2.4 Combined Antenna Port RF Exposure Results FCC 1.1307(b)(3)(ii)(B) SAR / MPE Exemption13



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
1	First Issue	07 July 2026

Table 1

1.2 Introduction

Applicant	Apple Inc
Manufacturer	Apple Inc
Model Number(s)	A3545
Hardware Version(s)	REV1.0
Specification/Issue/Date	FCC 47 CFR Part 1.1307: 2024
Related Document(s)	• KDB 447498 D04 v01 • FCC 47 CFR Part 2.1091: 2024



1.3 Brief Summary of Results

The wireless devices described within this report are compliant with the exemption criteria related to human exposure to electromagnetic fields laid out in FCC CFR Title 47 Part 1.1307 for both general public and worker/occupational exposures for a separation distance of greater than 20 cm.

The calculations shown in this report were made in accordance with the procedures specified in the applied test specification(s).



1.4 Product Information

1.4.1 Technical Description

The equipment under test (EUT) was a desktop computer.

1.4.2 Transmitter Description

The following radio access technologies and frequency bands are supported by the equipment under test.

Radio Access Technology	Frequency Band (MHz)	Minimum Frequency (MHz)	Conducted Output Power (dBm)	Duty Cycle (%)
Bluetooth (SISO) Core 0	2400-2483.5	2402	19.75	100
Bluetooth (SISO) Core 1	2400-2483.5	2402	19.50	100
Bluetooth (SISO) Core 2	2400-2483.5	2402	13.00	100
Bluetooth (2x2 (MIMO) Core 0 and Core 1	2400-2483.5	2402	22.75	100
Thread (SISO) Core 0	2400-2483.5	2405	21.00	100
Thread (SISO) Core 1	2400-2483.5	2405	21.00	100
Thread (SISO) Core 2	2400-2483.5	2405	13.00	100
2.4 GHz WLAN (SISO) Core 0	2400-2483.5	2412	22.00	100
2.4 GHz WLAN (SISO) Core 1	2400-2483.5	2412	22.00	100
2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1	2400-2483.5	2412	25.00	100
5 GHz WLAN (SISO) Core 0	5150-5850	5180	20.50	100
5 GHz WLAN (SISO) Core 1	5150-5850	5180	20.50	100
5 GHz WLAN (2x2 MIMO) Core 0 and Core 1	5150-5850	5180	23.50	100
6 GHz WLAN (SISO) Core 0	5925-7125	5955	21.50	100
6 GHz WLAN (SISO) Core 1	5925-7125	5955	21.50	100
6 GHz WLAN (2x2 MIMO) Core 0 and Core 1	5925-7125	5955	24.50	100
Narrowband U-NII-1 Core 0	5150-5250	5162	13.00	100
Narrowband U-NII-1 Core 1	5150-5250	5162	13.00	100
Narrowband U-NII-1 Core 0 and Core 1	5150-5250	5162	16.00	100
Narrowband U-NII-3 Core 0	5725-5850	5733	19.00	100
Narrowband U-NII-3 Core 1	5725-5850	5733	19.00	100
Narrowband U-NII-3 Core 0 and Core 1	5725-5850	5733	22.00	100
Narrowband U-NII-5 Core 0	5925-6425	6106	-1.00	100
Narrowband U-NII-5 Core 1	5925-6425	6106	0.25	100
Narrowband U-NII-5 Core 0 and Core 1	5925-6425	6106	-3.50	100

Table 2 - Transmitter Description - FCC

Note: Transmitter power includes upper bounds of uncertainty therefore maximum values are used.



1.4.3 Antenna Description

The following antennas are supported by the equipment under test.

Radio Access Technology	Antenna Model	Frequency Band (MHz)	Gain (dBi)	Minimum Separation Distance (cm)
Bluetooth / Thread / 2.4 GHz WLAN – Core 0	Cavity-backed Slot Antenna	2400-2483.5	1.2	20.1
Bluetooth / Thread / 2.4 GHz WLAN – Core 1	Cavity-backed Slot Antenna	2400-2483.5	1.4	20.1
Bluetooth / Thread / 2.4 GHz WLAN – Core 2	Cavity-backed Slot Antenna	2400-2483.5	1.0	20.1
5 GHz WLAN – Core 0	Cavity-backed Slot Antenna	5150-5850	2.2	20.1
5 GHz WLAN – Core 1	Cavity-backed Slot Antenna	5150-5850	2.0	20.1
6 GHz WLAN – Core 0	Cavity-backed Slot Antenna	5925-7125	2.6	20.1
6 GHz WLAN – Core 1	Cavity-backed Slot Antenna	5925-7125	1.3	20.1
NB UNII-1 Core 0	Cavity-backed Slot Antenna	5150-5250	1.3	20.1
NB UNII-1 Core 1	Cavity-backed Slot Antenna	5150-5250	2.0	20.1
NB UNII-3 Core 0	Cavity-backed Slot Antenna	5725-5850	1.2	20.1
NB UNII-3 Core 1	Cavity-backed Slot Antenna	5725-5850	0.4	20.1
NB UNII-5 Core 0	Cavity-backed Slot Antenna	5925-6425	2.6	20.1
NB UNII-5 Core 1	Cavity-backed Slot Antenna	5925-6425	1.3	20.1

Table 3 - Antenna Description

In the case of more than one type of antenna being supported by the equipment, the calculation is based on the maximum of the antenna gains. If other antennas can be used that have greater gains, the minimum separation distances will need to be recalculated.

Note: Antenna gain includes upper bounds of uncertainty therefore maximum values are used.



1.4.4 Equipment Configuration

The device supports the following modes:-

- Bluetooth can operate in SISO modes on Core 0, 1, 2 & MIMO modes on Core 0 & 1
- Thread can operate in SISO modes on Core 0, 1, 2
- WLAN can operate in SISO modes on Core 0, 1 & MIMO modes on Core 0 & 1
- NB can operate in SISO modes on Core 0, 1 & MIMO modes on Core 0 & 1

The device supports simultaneous operation in the following modes:

- WLAN + BT
- WLAN + NB
- WLAN+Thread
- BT + NB
- WLAN + BT + NB
- WLAN + NB + Thread
- NB + Thread

Worst case configurations for simultaneous transmission were identified as;

Combination 1

- 6 GHz WLAN 2x2 (MIMO) Core 0 and Core 1 + Bluetooth 2x2 (MIMO) Core 0 and Core 1

Combination 2

- 2.4 GHz WLAN 2x2 (MIMO) Core 0 and Core 1 + NB U-NII-3 Core 0 and Core 1

Combination 3

- 2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1 + 6 GHz WLAN 2x2 (MIMO) Core 0 and Core 1 + Thread Core 2

Combination 4

- Bluetooth (2x2 (MIMO) Core 0 and Core 1 + Narrowband U-NII-3 Core 0 and Core 1

Combination 5

- 2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1 + Bluetooth (SISO) Core 2 + Narrowband U-NII-3 Core 0 and Core 1

Combination 6

- 2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1 + Narrowband U-NII-3 Core 0 and Core 1 + Thread (SISO) Core 2

Combination 7

- Narrowband U-NII-3 Core 0 and Core 1 + Thread (SISO) Core 0



1.5 Test Location

TÜV SÜD conducted the following tests at our Octagon House Test Laboratory.

Test Name	Name of Engineer(s)	Accreditation
Exposure Assessment	Steve Marshall	UKAS

Table 4

Office Address:

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire
PO15 5RL
United Kingdom



2 Assessment Details

2.1 Single RF Source Options for Determination of Exemption

Option	Reference	RF Exposure Test Exemptions for Single Source												
A (1-mW Test Exemption)	FCC 1.1307(b)(3)(i)(A)	The available maximum time averaged power is no more than 1 mW, regardless of separation distance.												
B (SAR-Based Exemption)	FCC 1.1307(b)(3)(i)(B)	The available maximum timeaveraged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold Pth (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by: $P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ Where $x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$ and $ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ d = the separation distance (cm);												
C (MPE-Based Exemption)	FCC 1.1307(b)(3)(i)(C)	Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least λ/2π, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of λ/4 or if the antenna gain is less than that of a half-wave dipole (1.64 linear value). TABLE 1 TO § 1.1307(b)(3)(i)(C)—SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION <table><tr><th>RF Source frequency (MHz)</th><th>Threshold ERP (watts)</th></tr><tr><td>0.3–1.34</td><td>1,920 R².</td></tr><tr><td>1.34–30</td><td>3,450 R²/f².</td></tr><tr><td>30–300</td><td>3.83 R².</td></tr><tr><td>300–1,500</td><td>0.0128 R²f.</td></tr><tr><td>1,500–100,000</td><td>19.2R².</td></tr></table>	RF Source frequency (MHz)	Threshold ERP (watts)	0.3–1.34	1,920 R².	1.34–30	3,450 R²/f².	30–300	3.83 R².	300–1,500	0.0128 R²f.	1,500–100,000	19.2R².
RF Source frequency (MHz)	Threshold ERP (watts)													
0.3–1.34	1,920 R².													
1.34–30	3,450 R²/f².													
30–300	3.83 R².													
300–1,500	0.0128 R²f.													
1,500–100,000	19.2R².													

Table 5



2.2 Multiple RF Sources Options for Determination of Exemption

Option	Reference	
A 1-mW Test Exemption for Multiple Sources	FCC 1.1307(b)(3)(ii)(A)	The available maximum time averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).
B Simultaneous Transmission with both SAR-based and MPE- Based Test Exemptions	FCC 1.1307(b)(3)(ii)(B)	In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation. $\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$

Table 6



2.3 Individual Antenna Port Exposure Results

2.3.1 Single Source Calculation of Exposure at Specified Separation Distance FCC 1.1307(b)(3)(i)(B) 'Option B' (SAR Based Exemption)

The frequencies shown in the tables below have been chosen based on the lowest possible frequency that the EUT can transmit.

RAT	Frequency (MHz)	Conducted Power Output mW	Duty Cycle %	Time Average Conducted Power Output mW	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Minimum Antenna to User Separation Distance (mm)	Pth (mW) 1.1307 (b)(3)(i)(B)	Greater of Max time averaged conducted power or ERP? mW	1.1307(b)(3)(i)(B) Exemption (Yes/No) (300 MHz to 6 GHz, 0.5 cm to 40 cm)
Bluetooth (SISO) Core 0	2402	94.41	100	94.41	1.32	124.45	75.89	201	3060.0	94.41	Yes
Bluetooth (SISO) Core 1	2402	89.13	100	89.13	1.38	123.03	75.02	201	3060.0	89.13	Yes
Bluetooth (SISO) Core 2	2402	19.95	100	19.95	1.26	25.12	15.32	201	3060.0	19.95	Yes
Bluetooth (2x2 MIMO) Core 0 and Core 1	2402	188.36	100	188.36	1.38	260.02	158.55	201	3060.0	188.36	Yes
Thread (SISO) Core 0	2405	125.89	100	125.89	1.32	165.96	101.19	201	3060.0	125.89	Yes
Thread (SISO) Core 1	2405	125.89	100	125.89	1.38	173.78	105.96	201	3060.0	125.89	Yes
Thread (SISO) Core 2	2405	19.95	100	19.95	1.26	25.12	15.32	201	3060.0	19.95	Yes
2.4 GHz WLAN (SISO) Core 0	2412	158.49	100	158.49	1.32	208.93	127.40	201	3060.0	158.49	Yes
2.4 GHz WLAN (SISO) Core 1	2412	158.49	100	158.49	1.38	218.78	133.40	201	3060.0	158.49	Yes
2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1	2412	316.23	100	316.23	1.38	436.52	266.17	201	3060.0	316.23	Yes
5 GHz WLAN (SISO) Core 0	5180	112.20	100	112.20	1.66	186.21	113.54	201	3060.0	113.54	Yes
5 GHz WLAN (SISO) Core 1	5180	112.20	100	112.20	1.58	177.83	108.43	201	3060.0	112.20	Yes
5 GHz WLAN (2x2 MIMO) Core 0 and Core 1	5180	223.87	100	223.87	1.66	371.54	226.55	201	3060.0	226.55	Yes
Narrowband U-NII-1 Core 0	5162	19.95	100	19.95	1.35	26.92	16.41	201	3060.0	19.95	Yes
Narrowband U-NII-1 Core 1	5162	19.95	100	19.95	1.58	31.62	19.28	201	3060.0	19.95	Yes
Narrowband U-NII-1 Core 0 and Core 1	5162	39.81	100	39.81	1.58	63.10	38.47	201	3060.0	39.81	Yes
Narrowband U-NII-3 Core 0	5733	79.43	100	79.43	1.32	104.71	63.85	201	3060.0	79.43	Yes



RAT	Frequency (MHz)	Conducted Power Output mW	Duty Cycle %	Time Average Conducted Power Output mW	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Minimum Antenna to User Separation Distance (mm)	Pth (mW) 1.1307 (b)(3)(i)(B)	Greater of Max time averaged conducted power or ERP? mW	1.1307(b)(3)(i)(B) Exemption (Yes/No) (300 MHz to 6 GHz, 0.5 cm to 40 cm)
Narrowband U-NII-3 Core 1	5733	79.43	100	79.43	1.10	87.10	53.11	201	3060.0	79.43	Yes
Narrowband U-NII-3 Core 0 and Core 1	5733	158.49	100	158.49	1.32	208.93	127.40	201	3060.0	158.49	Yes

Table 7 - Transmitter Result

The calculations show that the individual transmitters comply with FCC 1.1307(b)(3)(i)(B) SAR-based exemption at a minimum distance of 201 mm.



2.3.2 Single Source Calculation of Exposure at Specified Separation Distance FCC 1.1307(b)(3)(i)(C) 'Option C' (MPE Based Exemption)

RAT	Frequency (MHz)	Conducted Power Output (mW)	Duty Cycle %	Time Average Conducted Power Output (mW)	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Minimum separation distance for MPE evaluation $\lambda/2$ π mm	Actual Distance (mm)	Threshold ERP (mW)	1.1307(b)(3)(i)(C) Exemption (Yes/No) (300 kHz to 100 GHz)
6 GHz WLAN (SISO) Core 0	5955	141.25	100	141.25	1.82	257.04	156.73	8.02	201	775.70	Yes
6 GHz WLAN (SISO) Core 1	5955	141.25	100	141.25	1.35	190.55	116.19	8.02	201	775.70	Yes
6 GHz WLAN (2x2 MIMO) Core 0 and Core 1	5955	281.84	100	281.84	1.82	512.86	312.72	8.02	201	775.70	Yes
Narrowband U-NII-5 Core 0	6106	0.79	100	0.79	1.82	1.45	0.88	7.82	201	775.70	Yes
Narrowband U-NII-5 Core 1	6106	1.06	100	1.06	1.35	1.43	0.87	7.82	201	775.70	Yes
Narrowband U-NII-5 Core 0 and Core 1	6106	0.45	100	0.45	1.82	0.81	0.50	7.82	201	775.70	Yes

Table 8 - Transmitter Result

The calculations show that the individual transmitters comply with FCC 1.1307(b)(3)(i)(C) MPE-based exception at a minimum distance of 201 mm.



2.4 Combined Antenna Port RF Exposure Results FCC 1.1307(b)(3)(ii)(B) SAR / MPE Exemption

2.4.1 Combination 1 - 6 GHz WLAN 2x2 (MIMO) Core 0 and Core 1 + Bluetooth 2x2 (MIMO) Core 0 and Core 1

RAT	Frequency (MHz)	Conducted Power Output mW	Duty Cycle %	Time Average Conducted Power Output mW	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Test Separation Distance (mm)	ERP _j / ERP _{th,j} <or> P _i / P _{th}	Sum of the fractional contributions to the applicable thresholds is less than or equal to 1. Compliant? (Yes/No)
Bluetooth (2x2 (MIMO) Core 0 and Core 1	2402	188.36	100	188.36	1.38	260.02	158.55	201	0.06156	
6 GHz WLAN (2x2 MIMO) Core 0 and Core 1	5955	281.84	100	281.84	1.82	512.86	312.72	201	0.34313	
Calculated RF exposure level at minimum compliance boundary of 0.201 m as a fraction of the limit									0.40469	Yes

Table 9 - Transmitter Result

The calculations show that the multiple transmitters comply with FCC 1.1307(b)(3)(ii)(B) summation-based exemption.



2.4.2 Combination 2 - 2.4 GHz WLAN 2x2 (MIMO) Core 0 and Core 1 + NB U-NII-3 Core 0 and Core 1

RAT	Frequency (MHz)	Conducted Power Output mW	Duty Cycle %	Time Average Conducted Power Output mW	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Test Separation Distance (mm)	ERP _j / ERP _{th,j} <or> P _i / P _{th}	Sum of the fractional contributions to the applicable thresholds is less than or equal to 1. Compliant? (Yes/No)
2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1	2412	316.23	100	316.23	1.38	436.52	266.17	201	0.10334	
Narrowband U-NII-3 Core 0 and Core 1	5733	158.49	100	158.49	1.32	208.93	127.40	201	0.05179	
Calculated RF exposure level at minimum compliance boundary of 0.201 m as a fraction of the limit									0.15514	Yes

Table 10 - Transmitter Result

The calculations show that the multiple transmitters comply with FCC 1.1307(b)(3)(ii)(B) summation-based exemption



2.4.3 Combination 3 - 2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1 + 6 GHz WLAN 2x2 (MIMO) Core 0 and Core 1 + Thread Core 2

RAT	Frequency (MHz)	Conducted Power Output mW	Duty Cycle %	Time Average Conducted Power Output mW	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Test Separation Distance (mm)	ERP _j / ERP _{th,j} <or> P _i / P _{th}	Sum of the fractional contributions to the applicable thresholds is less than or equal to 1. Compliant? (Yes/No)
2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1	2412	316.23	100	316.23	1.38	436.52	266.17	201	0.10334	
6 GHz WLAN (2x2 MIMO) Core 0 and Core 1	5955	281.84	100	281.84	1.82	512.86	312.72	201	0.34313	
Thread (SISO) Core 2	2405	19.95	100	19.95	1.26	25.12	15.32	201	0.00652	
Calculated RF exposure level at minimum compliance boundary of 0.201 m as a fraction of the limit									0.45299	Yes

Table 11 - Transmitter Result

The calculations show that the multiple transmitters comply with FCC 1.1307(b)(3)(ii)(B) summation-based exemption



2.4.4 Combination 4 - Bluetooth (2x2 (MIMO) Core 0 and Core 1 + Narrowband U-NII-3 Core 0 and Core 1

RAT	Frequency (MHz)	Conducted Power Output mW	Duty Cycle %	Time Average Conducted Power Output mW	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Test Separation Distance (mm)	ERP _j / ERP _{th,j} <or> P _i / P _{th}	Sum of the fractional contributions to the applicable thresholds is less than or equal to 1. Compliant? (Yes/No)
Bluetooth (2x2 (MIMO) Core 0 and Core 1	2402	188.36	100	188.36	1.38	260.02	158.55	201	0.06156	
Narrowband U-NII-3 Core 0 and Core 1	5733	158.49	100	158.49	1.32	208.93	127.40	201	0.05179	
Calculated RF exposure level at minimum compliance boundary of 0.201 m as a fraction of the limit									0.11335	Yes

Table 12 - Transmitter Result

The calculations show that the multiple transmitters comply with FCC 1.1307(b)(3)(ii)(B) summation-based exemption



2.4.5 Combination 5 - 2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1 + Bluetooth (SISO) Core 2 + Narrowband U-NII-3 Core 0 and Core 1

RAT	Frequency (MHz)	Conducted Power Output mW	Duty Cycle %	Time Average Conducted Power Output mW	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Test Separation Distance (mm)	ERP _j / ERP _{th,j} <or> P _i / P _{th}	Sum of the fractional contributions to the applicable thresholds is less than or equal to 1. Compliant? (Yes/No)
2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1	2412	316.23	100	316.23	1.38	436.52	266.17	201	0.10334	
Bluetooth (SISO) Core 2	2402	19.95	100	19.95	1.26	25.12	15.32	201	0.00652	
Narrowband U-NII-3 Core 0 and Core 1	5733	158.49	100	158.49	1.32	208.93	127.40	201	0.05179	
Calculated RF exposure level at minimum compliance boundary of 0.201 m as a fraction of the limit									0.16165	Yes

Table 13 - Transmitter Result

The calculations show that the multiple transmitters comply with FCC 1.1307(b)(3)(ii)(B) summation-based exemption



2.4.6 Combination 6 - 2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1+ Narrowband U-NII-3 Core 0 and Core 1 + Thread (SISO) Core 2

RAT	Frequency (MHz)	Conducted Power Output mW	Duty Cycle %	Time Average Conducted Power Output mW	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Test Separation Distance (mm)	ERPj / ERPth,j <or> Pi / Pth	Sum of the fractional contributions to the applicable thresholds is less than or equal to 1. Compliant? (Yes/No)
2.4 GHz WLAN (2x2 MIMO) Core 0 and Core 1	2412	316.23	100	316.23	1.38	436.52	266.17	201	0.10334	
Narrowband U-NII-3 Core 0 and Core 1	5733	158.49	100	158.49	1.32	208.93	127.40	201	0.05179	
Thread (SISO) Core 2	2405	19.95	100	19.95	1.26	25.12	15.32	201	0.00652	
Calculated RF exposure level at minimum compliance boundary of 0.201 m as a fraction of the limit									0.16165	Yes

Table 14 - Transmitter Result

The calculations show that the multiple transmitters comply with FCC 1.1307(b)(3)(ii)(B) summation-based exemption



2.4.7 Combination 7 - Narrowband U-NII-3 Core 0 and Core 1 + Thread (SISO) Core 0

RAT	Frequency (MHz)	Conducted Power Output mW	Duty Cycle %	Time Average Conducted Power Output mW	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Test Separation Distance (mm)	ERP _j / ERP _{th,j} <or> P _i / P _{th}	Sum of the fractional contributions to the applicable thresholds is less than or equal to 1. Compliant? (Yes/No)
Narrowband U-NII-3 Core 0 and Core 1	5733	158.49	100	158.49	1.32	208.93	127.40	201	0.05179	
Thread (SISO) Core 0	2405	125.89	100	125.89	1.32	165.96	101.19	201	0.04114	
Calculated RF exposure level at minimum compliance boundary of 0.201 m as a fraction of the limit									0.09293	Yes

Table 15 - Transmitter Result

The calculations show that the multiple transmitters comply with FCC 1.1307(b)(3)(ii)(B) summation-based exemption