



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE40 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	5.26	-	-	-	5.26	2.60	7.86	14.00	-6.14
6245	5.21	-	-	-	5.21	2.60	7.81	14.00	-6.19
6405	6.34	-	-	-	6.34	1.50	7.84	14.00	-6.16
6445	6.65	-	-	-	6.65	1.40	8.05	14.00	-5.95
6485	6.50	-	-	-	6.50	1.40	7.90	14.00	-6.10
6525	6.53	-	-	-	6.53	1.40	7.93	14.00	-6.07
6565	6.30	-	-	-	6.30	1.60	7.90	14.00	-6.10
6725	6.27	-	-	-	6.27	1.60	7.87	14.00	-6.13
6845	6.29	-	-	-	6.29	1.60	7.89	14.00	-6.11
6885	6.38	-	-	-	6.38	1.60	7.98	14.00	-6.02
6925	6.60	-	-	-	6.60	1.30	7.90	14.00	-6.10
7005	6.71	-	-	-	6.71	1.30	8.01	14.00	-5.99
7085	6.70	-	-	-	6.70	1.30	8.00	14.00	-6.00

Table 124 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a40 LPI	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	-	10.20	-	-	10.20	1.30	11.50	24.00	-12.50
6165	-	10.87	-	-	10.87	1.00	11.87	24.00	-12.13
6365	-	11.14	-	-	11.14	0.50	11.64	24.00	-12.36
6405	-	11.13	-	-	11.13	0.50	11.63	24.00	-12.37
6445	-	11.43	-	-	11.43	0.50	11.93	24.00	-12.07
6485	-	11.31	-	-	11.31	0.50	11.81	24.00	-12.19
6525	-	11.33	-	-	11.33	0.50	11.83	24.00	-12.17
6885	-	11.09	-	-	11.09	0.60	11.69	24.00	-12.31
6925	-	12.61	-	-	12.61	-1.20	11.41	24.00	-12.59
7005	-	12.83	-	-	12.83	-1.20	11.63	24.00	-12.37
7085	-	12.99	-	-	12.99	-1.20	11.79	24.00	-12.21

Table 125 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.525-6.875 GHz	Band:	U-NII-7
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a40 LPI	Duty Cycle (%):	95.3
Data Rate:	24 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.60
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6565	-	10.88	-	-	10.88	0.60	11.48	24.00	-12.52
6725	-	11.17	-	-	11.17	0.60	11.77	24.00	-12.23
6845	-	10.87	-	-	10.87	0.60	11.47	24.00	-12.53

Table 126 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE40 SU LPI	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	-	10.41	-	-	10.41	1.30	11.71	24.00	-12.29
6165	-	11.07	-	-	11.07	1.00	12.07	24.00	-11.93
6405	-	11.58	-	-	11.58	0.50	12.08	24.00	-11.92
6445	-	11.36	-	-	11.36	0.50	11.86	24.00	-12.14
6485	-	11.34	-	-	11.34	0.50	11.84	24.00	-12.16
6525	-	11.31	-	-	11.31	0.50	11.81	24.00	-12.19
6565	-	11.34	-	-	11.34	0.60	11.94	24.00	-12.06
6725	-	11.29	-	-	11.29	0.60	11.89	24.00	-12.11
6845	-	11.34	-	-	11.34	0.60	11.94	24.00	-12.06
6885	-	11.56	-	-	11.56	0.60	12.16	24.00	-11.84
6925	-	13.39	-	-	13.39	-1.20	12.19	24.00	-11.81
7005	-	13.36	-	-	13.36	-1.20	12.16	24.00	-11.84
7085	-	13.31	-	-	13.31	-1.20	12.11	24.00	-11.89

Table 127 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a40 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	-	19.09	-	-	19.09	1.30	20.39	30.00	-9.61
6165	-	19.10	-	-	19.10	1.00	20.10	30.00	-9.90
6405	-	19.05	-	-	19.05	0.50	19.55	30.00	-10.45
6565	-	19.01	-	-	19.01	0.60	19.61	30.00	-10.39
6685	-	19.05	-	-	19.05	0.60	19.65	30.00	-10.35
6845	-	19.23	-	-	19.23	0.60	19.83	30.00	-10.17

Table 128 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	-	19.16	-	-	19.16	1.30	20.46	30.00	-9.54
6165	-	19.02	-	-	19.02	1.00	20.02	30.00	-9.98
6405	-	19.17	-	-	19.17	0.50	19.67	30.00	-10.33
6565	-	19.13	-	-	19.13	0.60	19.73	30.00	-10.27
6685	-	19.20	-	-	19.20	0.60	19.80	30.00	-10.20
6845	-	19.14	-	-	19.14	0.60	19.74	30.00	-10.26

Table 129 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a40 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.50
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6445	-	19.16	-	-	19.16	0.50	19.66	30.00	-10.34
6485	-	19.17	-	-	19.17	0.50	19.67	30.00	-10.33
6525	-	19.04	-	-	19.04	0.50	19.54	30.00	-10.46

Table 130 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.50
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6445	-	17.41	-	-	17.41	0.50	17.91	30.00	-12.09
6485	-	17.32	-	-	17.32	0.50	17.82	30.00	-12.18
6525	-	17.30	-	-	17.30	0.50	17.80	30.00	-12.20

Table 131 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a40 VLP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	-	6.67	-	-	6.67	1.00	7.67	14.00	-6.33
6245	-	6.74	-	-	6.74	1.00	7.74	14.00	-6.26
6405	-	7.11	-	-	7.11	0.50	7.61	14.00	-6.39
6445	-	7.29	-	-	7.29	0.50	7.79	14.00	-6.21
6485	-	7.31	-	-	7.31	0.50	7.81	14.00	-6.19
6525	-	7.45	-	-	7.45	0.50	7.95	14.00	-6.05
6885	-	7.11	-	-	7.11	0.60	7.71	14.00	-6.29
6925	-	8.73	-	-	8.73	-1.20	7.53	14.00	-6.47
7005	-	8.83	-	-	8.83	-1.20	7.63	14.00	-6.37
7085	-	9.07	-	-	9.07	-1.20	7.87	14.00	-6.13

Table 132 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.525-6.875 GHz	Band:	U-NII-7
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a40 VLP	Duty Cycle (%):	95.2
Data Rate:	24 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.60
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6565	-	6.87	-	-	6.87	0.60	7.47	14.00	-6.53
6725	-	6.98	-	-	6.98	0.60	7.58	14.00	-6.42
6845	-	6.95	-	-	6.95	0.60	7.55	14.00	-6.45

Table 133 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE40 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	-	6.92	-	-	6.92	1.00	7.92	14.00	-6.08
6245	-	7.07	-	-	7.07	1.00	8.07	14.00	-5.93
6405	-	7.63	-	-	7.63	0.50	8.13	14.00	-5.87
6445	-	7.30	-	-	7.30	0.50	7.80	14.00	-6.20
6485	-	7.31	-	-	7.31	0.50	7.81	14.00	-6.19
6525	-	7.29	-	-	7.29	0.50	7.79	14.00	-6.21
6565	-	7.21	-	-	7.21	0.60	7.81	14.00	-6.19
6725	-	7.03	-	-	7.03	0.60	7.63	14.00	-6.37
6845	-	7.13	-	-	7.13	0.60	7.73	14.00	-6.27
6885	-	7.62	-	-	7.62	0.60	8.22	14.00	-5.78
6925	-	9.17	-	-	9.17	-1.20	7.97	14.00	-6.03
7005	-	9.08	-	-	9.08	-1.20	7.88	14.00	-6.12
7085	-	9.09	-	-	9.09	-1.20	7.89	14.00	-6.11

Table 134 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a40 LPI	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	3.99	4.57	-	-	7.30	1.30	8.60	24.00	-15.40
6165	3.53	2.13	-	-	5.90	2.60	8.50	24.00	-15.50
6405	3.84	4.50	-	-	7.19	1.50	8.69	24.00	-15.31
6445	3.81	4.71	-	-	7.30	1.40	8.70	24.00	-15.30
6485	3.83	4.67	-	-	7.28	1.40	8.68	24.00	-15.32
6525	3.59	4.46	-	-	7.06	1.40	8.46	24.00	-15.54
6885	4.32	4.62	-	-	7.48	1.60	9.08	24.00	-14.92
6925	5.00	5.21	-	-	8.12	1.30	9.42	24.00	-14.58
7005	4.88	5.17	-	-	8.04	1.30	9.34	24.00	-14.66
7085	4.96	5.36	-	-	8.17	1.30	9.47	24.00	-14.53

Table 135 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.525-6.875 GHz	Band:	U-NII-7
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a40 LPI	Duty Cycle (%):	95.1
Data Rate:	24 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6565	3.58	4.52	-	-	7.09	1.60	8.69	24.00	-15.31
6725	4.11	4.47	-	-	7.31	1.60	8.91	24.00	-15.09
6845	3.90	4.27	-	-	7.10	1.60	8.70	24.00	-15.30

Table 136 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU LPI	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	4.30	4.85	-	-	7.60	1.30	8.90	24.00	-15.10
6165	3.84	2.39	-	-	6.19	2.60	8.79	24.00	-15.21
6405	4.07	4.85	-	-	7.49	1.50	8.99	24.00	-15.01
6445	4.03	5.02	-	-	7.56	1.40	8.96	24.00	-15.04
6485	4.09	4.88	-	-	7.52	1.40	8.92	24.00	-15.08
6525	4.08	4.87	-	-	7.50	1.40	8.90	24.00	-15.10
6565	4.00	4.88	-	-	7.47	1.60	9.07	24.00	-14.93
6725	4.30	4.65	-	-	7.49	1.60	9.09	24.00	-14.91
6845	4.28	4.69	-	-	7.50	1.60	9.10	24.00	-14.90
6885	4.59	4.86	-	-	7.73	1.60	9.33	24.00	-14.67
6925	5.58	5.77	-	-	8.68	1.30	9.98	24.00	-14.02
7005	5.42	5.72	-	-	8.59	1.30	9.89	24.00	-14.11
7085	5.29	5.73	-	-	8.52	1.30	9.82	24.00	-14.18

Table 137 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a40 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	18.42	19.03	-	-	21.75	1.30	23.05	30.00	-6.95
6165	18.68	19.04	-	-	21.87	2.60	24.47	30.00	-5.53
6405	18.34	19.30	-	-	21.85	1.50	23.35	30.00	-6.65
6565	18.51	19.25	-	-	21.91	1.60	23.51	30.00	-6.49
6685	18.31	19.01	-	-	21.69	1.60	23.29	30.00	-6.71
6845	18.60	19.17	-	-	21.91	1.60	23.51	30.00	-6.49

Table 138 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	18.53	19.12	-	-	21.85	1.30	23.15	30.00	-6.85
6165	18.82	19.25	-	-	22.05	2.60	24.65	30.00	-5.35
6405	18.18	19.11	-	-	21.68	1.50	23.18	30.00	-6.82
6565	18.29	19.12	-	-	21.73	1.60	23.33	30.00	-6.67
6685	18.50	19.18	-	-	21.87	1.60	23.47	30.00	-6.53
6845	18.58	19.14	-	-	21.88	1.60	23.48	30.00	-6.52

Table 139 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a40 SP	Duty Cycle (%):	97.5
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6445	18.27	19.11	-	-	21.72	1.40	23.12	30.00	-6.88
6485	18.39	19.04	-	-	21.73	1.40	23.13	30.00	-6.87
6525	18.38	19.01	-	-	21.72	1.40	23.12	30.00	-6.88

Table 140 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	99.2
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6445	13.38	14.37	-	-	16.91	1.40	18.31	30.00	-11.69
6485	13.50	14.21	-	-	16.88	1.40	18.28	30.00	-11.72
6525	13.50	14.28	-	-	16.92	1.40	18.32	30.00	-11.68

Table 141 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a40 VLP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	-0.55	-0.37	-	-	2.55	2.60	5.15	14.00	-8.85
6245	-0.63	-0.39	-	-	2.50	2.60	5.10	14.00	-8.90
6405	0.54	0.32	-	-	3.44	1.50	4.94	14.00	-9.06
6445	0.24	0.40	-	-	3.33	1.40	4.73	14.00	-9.27
6485	0.50	0.52	-	-	3.52	1.40	4.92	14.00	-9.08
6525	0.33	0.36	-	-	3.36	1.40	4.76	14.00	-9.24
6885	0.21	0.43	-	-	3.33	1.60	4.93	14.00	-9.07
6925	1.12	1.51	-	-	4.33	1.30	5.63	14.00	-8.37
7005	1.05	1.54	-	-	4.31	1.30	5.61	14.00	-8.39
7085	1.03	1.54	-	-	4.30	1.30	5.60	14.00	-8.40

Table 142 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.525-6.875 GHz	Band:	U-NII-7
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a40 VLP	Duty Cycle (%):	94.9
Data Rate:	24 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6565	0.21	0.35	-	-	3.29	1.60	4.89	14.00	-9.11
6725	-0.03	0.25	-	-	3.12	1.60	4.72	14.00	-9.28
6845	-0.35	0.14	-	-	2.91	1.60	4.51	14.00	-9.49

Table 143 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	-0.33	-0.15	-	-	2.77	2.60	5.37	14.00	-8.63
6245	-0.35	-0.00	-	-	2.84	2.60	5.44	14.00	-8.56
6405	0.75	0.55	-	-	3.66	1.50	5.16	14.00	-8.84
6445	0.53	0.70	-	-	3.63	1.40	5.03	14.00	-8.97
6485	0.70	0.69	-	-	3.71	1.40	5.11	14.00	-8.89
6525	0.79	0.89	-	-	3.85	1.40	5.25	14.00	-8.75
6565	0.46	0.70	-	-	3.59	1.60	5.19	14.00	-8.81
6725	0.37	0.63	-	-	3.51	1.60	5.11	14.00	-8.89
6845	0.18	0.66	-	-	3.44	1.60	5.04	14.00	-8.96
6885	0.55	0.76	-	-	3.67	1.60	5.27	14.00	-8.73
6925	1.15	1.56	-	-	4.37	1.30	5.67	14.00	-8.33
7005	1.02	1.60	-	-	4.33	1.30	5.63	14.00	-8.37
7085	1.32	1.83	-	-	4.60	1.30	5.90	14.00	-8.10

Table 144 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU LPI	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	7.23	7.65	-	-	10.46	1.06	11.51	24.00	-12.49
6165	6.92	5.50	-	-	9.28	1.87	11.15	24.00	-12.85
6405	7.34	8.20	-	-	10.81	1.03	11.83	24.00	-12.17
6445	7.10	8.06	-	-	10.62	0.97	11.59	24.00	-12.41
6485	7.24	7.91	-	-	10.60	0.97	11.58	24.00	-12.42
6525	6.98	7.77	-	-	10.41	0.97	11.38	24.00	-12.62
6565	6.86	7.73	-	-	10.33	1.13	11.46	24.00	-12.54
6725	7.52	7.82	-	-	10.68	1.13	11.81	24.00	-12.19
6845	7.33	7.63	-	-	10.49	1.13	11.62	24.00	-12.38
6885	7.69	7.88	-	-	10.79	1.13	11.92	24.00	-12.08
6925	8.40	8.72	-	-	11.57	0.23	11.80	24.00	-12.20
7005	8.27	8.63	-	-	11.46	0.23	11.69	24.00	-12.31
7085	8.19	8.57	-	-	11.39	0.23	11.62	24.00	-12.38

Table 145 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	18.38	19.01	-	-	21.72	1.06	22.77	30.00	-7.23
6165	18.69	19.12	-	-	21.92	1.87	23.79	30.00	-6.21
6405	18.07	19.03	-	-	21.59	1.03	22.61	30.00	-7.39
6565	18.45	19.20	-	-	21.85	1.13	22.98	30.00	-7.02
6685	18.60	19.29	-	-	21.97	1.13	23.10	30.00	-6.90
6845	18.61	19.26	-	-	21.96	1.13	23.09	30.00	-6.91

Table 146 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	99.2
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	0.97
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6445	16.13	17.20	-	-	19.71	0.97	20.68	30.00	-9.32
6485	16.18	17.10	-	-	19.68	0.97	20.65	30.00	-9.35
6525	16.27	17.14	-	-	19.74	0.97	20.71	30.00	-9.29

Table 147 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	2.55	2.91	-	-	5.74	1.87	7.62	14.00	-6.38
6245	2.39	2.85	-	-	5.64	1.87	7.51	14.00	-6.49
6405	3.02	3.85	-	-	6.46	1.03	7.49	14.00	-6.51
6445	3.05	4.00	-	-	6.56	0.97	7.54	14.00	-6.46
6485	3.14	3.93	-	-	6.56	0.97	7.54	14.00	-6.46
6525	3.12	3.92	-	-	6.55	0.97	7.52	14.00	-6.48
6565	2.98	3.96	-	-	6.51	1.13	7.64	14.00	-6.36
6725	3.32	3.61	-	-	6.48	1.13	7.61	14.00	-6.39
6845	3.34	3.69	-	-	6.53	1.13	7.66	14.00	-6.34
6885	3.62	3.86	-	-	6.75	1.13	7.88	14.00	-6.12
6925	4.54	4.75	-	-	7.66	0.23	7.88	14.00	-6.12
7005	4.45	4.70	-	-	7.59	0.23	7.81	14.00	-6.19
7085	4.31	4.70	-	-	7.52	0.23	7.75	14.00	-6.25

Table 148 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU LPI	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.85
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	4.28	4.87	-	-	7.60	4.06	11.66	24.00	-12.34
6165	3.82	2.45	-	-	6.20	4.85	11.05	24.00	-12.95
6405	4.09	4.81	-	-	7.48	4.02	11.50	24.00	-12.50
6445	4.16	5.09	-	-	7.66	3.97	11.63	24.00	-12.37
6485	4.22	4.88	-	-	7.57	3.97	11.55	24.00	-12.45
6525	4.22	4.91	-	-	7.59	3.97	11.56	24.00	-12.44
6565	4.06	4.92	-	-	7.52	4.12	11.65	24.00	-12.35
6725	4.58	4.78	-	-	7.69	4.12	11.82	24.00	-12.18
6845	4.41	4.62	-	-	7.53	4.12	11.65	24.00	-12.35
6885	4.55	4.75	-	-	7.66	4.12	11.79	24.00	-12.21
6925	5.50	5.71	-	-	8.62	3.15	11.77	24.00	-12.23
7005	5.46	5.72	-	-	8.60	3.15	11.75	24.00	-12.25
7085	5.30	5.71	-	-	8.52	3.15	11.67	24.00	-12.33

Table 149 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.85
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	18.43	19.15	-	-	21.81	4.06	25.87	30.00	-4.13
6165	18.63	19.13	-	-	21.90	4.85	26.75	30.00	-3.25
6405	18.26	19.17	-	-	21.75	4.02	25.77	30.00	-4.23
6565	18.42	19.05	-	-	21.76	4.12	25.88	30.00	-4.12
6685	18.53	19.11	-	-	21.84	4.12	25.97	30.00	-4.03
6845	18.78	19.33	-	-	22.08	4.12	26.20	30.00	-3.80

Table 150 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	3.97
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6445	12.41	13.37	-	-	15.93	3.97	19.90	30.00	-10.10
6485	12.56	13.29	-	-	15.95	3.97	19.92	30.00	-10.08
6525	12.55	13.28	-	-	15.94	3.97	19.91	30.00	-10.09

Table 151 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.85
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	-0.30	-0.16	-	-	2.78	4.85	7.63	14.00	-6.37
6245	-0.46	-0.20	-	-	2.68	4.85	7.53	14.00	-6.47
6405	0.76	0.60	-	-	3.69	4.02	7.72	14.00	-6.28
6445	0.71	0.98	-	-	3.86	3.97	7.83	14.00	-6.17
6485	0.70	0.72	-	-	3.72	3.97	7.69	14.00	-6.31
6525	0.80	0.92	-	-	3.87	3.97	7.85	14.00	-6.15
6565	0.49	0.73	-	-	3.62	4.12	7.74	14.00	-6.26
6725	0.38	0.62	-	-	3.51	4.12	7.64	14.00	-6.36
6845	0.18	0.63	-	-	3.42	4.12	7.55	14.00	-6.45
6885	0.47	0.65	-	-	3.57	4.12	7.69	14.00	-6.31
6925	1.05	1.56	-	-	4.32	3.15	7.47	14.00	-6.53
7005	1.00	1.56	-	-	4.30	3.15	7.45	14.00	-6.55
7085	1.28	1.78	-	-	4.55	3.15	7.70	14.00	-6.30

Table 152 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 LPI	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6065	13.76	-	-	-	13.76	0.80	14.56	24.00	-9.44
6145	11.62	-	-	-	11.62	2.60	14.22	24.00	-9.78
6305	12.70	-	-	-	12.70	1.50	14.20	24.00	-9.80
6385	13.02	-	-	-	13.02	1.50	14.52	24.00	-9.48
6465	13.25	-	-	-	13.25	1.40	14.65	24.00	-9.35
6545	12.94	-	-	-	12.94	1.60	14.54	24.00	-9.46
6625	12.69	-	-	-	12.69	1.60	14.29	24.00	-9.71
6705	12.63	-	-	-	12.63	1.60	14.23	24.00	-9.77
6785	12.57	-	-	-	12.57	1.60	14.17	24.00	-9.83
6865	12.69	-	-	-	12.69	1.60	14.29	24.00	-9.71
6945	13.13	-	-	-	13.13	1.30	14.43	24.00	-9.57
7025	13.15	-	-	-	13.15	1.30	14.45	24.00	-9.55

Table 153 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz	Band:	U-NII-5
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 LPI	Duty Cycle (%):	95.1
Data Rate:	24 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.80
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	13.52	-	-	-	13.52	0.80	14.32	24.00	-9.68

Table 154 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU LPI	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	14.05	-	-	-	14.05	0.80	14.85	24.00	-9.15
6145	11.98	-	-	-	11.98	2.60	14.58	24.00	-9.42
6385	13.26	-	-	-	13.26	1.50	14.76	24.00	-9.24
6465	13.39	-	-	-	13.39	1.40	14.79	24.00	-9.21
6545	13.23	-	-	-	13.23	1.60	14.83	24.00	-9.17
6625	12.96	-	-	-	12.96	1.60	14.56	24.00	-9.44
6705	12.91	-	-	-	12.91	1.60	14.51	24.00	-9.49
6785	13.10	-	-	-	13.10	1.60	14.70	24.00	-9.30
6865	12.96	-	-	-	12.96	1.60	14.56	24.00	-9.44
6945	13.59	-	-	-	13.59	1.30	14.89	24.00	-9.11
7025	13.63	-	-	-	13.63	1.30	14.93	24.00	-9.07

Table 155 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 LPI	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985 (RU Size 484 + RU Size 242.93)	12.64	-	-	-	12.64	0.80	13.44	24.00	-10.56
6065 (RU Size 484 + RU Size 242.90)	12.43	-	-	-	12.43	0.80	13.23	24.00	-10.77
6145 (RU Size 484 + RU Size 242.92)	10.91	-	-	-	10.91	2.60	13.51	24.00	-10.49
6385 (RU Size 484 + RU Size 242.90)	12.12	-	-	-	12.12	1.50	13.62	24.00	-10.38
6465 (RU Size 484 + RU Size 242.93)	12.31	-	-	-	12.31	1.40	13.71	24.00	-10.29
6545 (RU Size 484 + RU Size 242.90)	11.64	-	-	-	11.64	1.60	13.24	24.00	-10.76
6545 (RU Size 484 + RU Size 242.93)	11.60	-	-	-	11.60	1.60	13.20	24.00	-10.80
6625 (RU Size 484 + RU Size 242.93)	11.66	-	-	-	11.66	1.60	13.26	24.00	-10.74
6705 (RU Size 484 + RU Size 242.91)	11.62	-	-	-	11.62	1.60	13.22	24.00	-10.78
6785 (RU Size 484 + RU Size 242.90)	11.66	-	-	-	11.66	1.60	13.26	24.00	-10.74
6865 (RU Size 484 + RU Size 242.90)	11.85	-	-	-	11.85	1.60	13.45	24.00	-10.55
6865 (RU Size 484 + RU Size 242.93)	11.81	-	-	-	11.81	1.60	13.41	24.00	-10.59
6945 (RU Size 484 + RU Size 242.93)	12.22	-	-	-	12.22	1.30	13.52	24.00	-10.48
7025 (RU Size 484 + RU Size 242.90)	12.09	-	-	-	12.09	1.30	13.39	24.00	-10.61

Table 156 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	19.21	-	-	-	19.21	0.80	20.01	30.00	-9.99
6145	19.02	-	-	-	19.02	2.60	21.62	30.00	-8.38
6385	19.04	-	-	-	19.04	1.50	20.54	30.00	-9.46
6625	19.07	-	-	-	19.07	1.60	20.67	30.00	-9.33
6705	19.19	-	-	-	19.19	1.60	20.79	30.00	-9.21
6785	19.13	-	-	-	19.13	1.60	20.73	30.00	-9.27

Table 157 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	19.05	-	-	-	19.05	0.80	19.85	30.00	-10.15
6145	19.16	-	-	-	19.16	2.60	21.76	30.00	-8.24
6385	19.19	-	-	-	19.19	1.50	20.69	30.00	-9.31
6625	19.14	-	-	-	19.14	1.60	20.74	30.00	-9.26
6705	19.06	-	-	-	19.06	1.60	20.66	30.00	-9.34
6785	19.04	-	-	-	19.04	1.60	20.64	30.00	-9.36

Table 158 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 SP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985 (RU Size 484 + RU Size 242.93)	19.26	-	-	-	19.26	0.80	20.06	30.00	-9.94
6145 (RU Size 484 + RU Size 242.92)	19.19	-	-	-	19.19	2.60	21.79	30.00	-8.21
6385 (RU Size 484 + RU Size 242.90)	19.13	-	-	-	19.13	1.50	20.63	30.00	-9.37
6625 (RU Size 484 + RU Size 242.93)	19.17	-	-	-	19.17	1.60	20.77	30.00	-9.23
6705 (RU Size 484 + RU Size 242.91)	19.10	-	-	-	19.10	1.60	20.70	30.00	-9.30
6785 (RU Size 484 + RU Size 242.90)	19.16	-	-	-	19.16	1.60	20.76	30.00	-9.24

Table 159 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 SP	Duty Cycle (%):	97.4
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465	19.14	-	-	-	19.14	1.40	20.54	30.00	-9.46
6545	19.13	-	-	-	19.13	1.60	20.73	30.00	-9.27

Table 160 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465	17.09	-	-	-	17.09	1.40	18.49	30.00	-11.51
6545	17.08	-	-	-	17.08	1.60	18.68	30.00	-11.32

Table 161 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 SP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465 (RU Size 484 + RU Size 242.93)	19.04	-	-	-	19.04	1.40	20.44	30.00	-9.56
6545 (RU Size 484 + RU Size 242.90)	19.18	-	-	-	19.18	1.60	20.78	30.00	-9.22

Table 162 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 VLP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	7.77	-	-	-	7.77	2.60	10.37	14.00	-3.63
6225	7.62	-	-	-	7.62	2.60	10.22	14.00	-3.78
6305	8.71	-	-	-	8.71	1.50	10.21	14.00	-3.79
6385	9.02	-	-	-	9.02	1.50	10.52	14.00	-3.48
6465	9.05	-	-	-	9.05	1.40	10.45	14.00	-3.55
6545	8.91	-	-	-	8.91	1.60	10.51	14.00	-3.49
6625	8.75	-	-	-	8.75	1.60	10.35	14.00	-3.65
6705	8.75	-	-	-	8.75	1.60	10.35	14.00	-3.65
6785	8.74	-	-	-	8.74	1.60	10.34	14.00	-3.66
6865	8.63	-	-	-	8.63	1.60	10.23	14.00	-3.77
6945	9.31	-	-	-	9.31	1.30	10.61	14.00	-3.39
7025	9.12	-	-	-	9.12	1.30	10.42	14.00	-3.58

Table 163 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU VLP	Duty Cycle (%):	99.2
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	8.03	-	-	-	8.03	2.60	10.63	14.00	-3.37
6225	7.89	-	-	-	7.89	2.60	10.49	14.00	-3.51
6385	9.25	-	-	-	9.25	1.50	10.75	14.00	-3.25
6465	9.57	-	-	-	9.57	1.40	10.97	14.00	-3.03
6545	9.07	-	-	-	9.07	1.60	10.67	14.00	-3.33
6625	9.01	-	-	-	9.01	1.60	10.61	14.00	-3.39
6705	8.96	-	-	-	8.96	1.60	10.56	14.00	-3.44
6865	9.11	-	-	-	9.11	1.60	10.71	14.00	-3.29
6945	9.46	-	-	-	9.46	1.30	10.76	14.00	-3.24
7025	9.73	-	-	-	9.73	1.30	11.03	14.00	-2.97

Table 164 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 VLP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145 (RU Size 484 + RU Size 242.93)	6.77	-	-	-	6.77	2.60	9.37	14.00	-4.63
6225 (RU Size 484 + RU Size 242.92)	6.99	-	-	-	6.99	2.60	9.59	14.00	-4.41
6385 (RU Size 484 + RU Size 242.90)	8.08	-	-	-	8.08	1.50	9.58	14.00	-4.42
6465 (RU Size 484 + RU Size 242.93)	8.18	-	-	-	8.18	1.40	9.58	14.00	-4.42
6545 (RU Size 484 + RU Size 242.90)	7.68	-	-	-	7.68	1.60	9.28	14.00	-4.72
6545 (RU Size 484 + RU Size 242.93)	7.72	-	-	-	7.72	1.60	9.32	14.00	-4.68
6625 (RU Size 484 + RU Size 242.93)	7.55	-	-	-	7.55	1.60	9.15	14.00	-4.85
6705 (RU Size 484 + RU Size 242.91)	7.75	-	-	-	7.75	1.60	9.35	14.00	-4.65
6785 (RU Size 484 + RU Size 242.90)	7.73	-	-	-	7.73	1.60	9.33	14.00	-4.67
6865 (RU Size 484 + RU Size 242.90)	7.97	-	-	-	7.97	1.60	9.57	14.00	-4.43
6865 (RU Size 484 + RU Size 242.93)	7.94	-	-	-	7.94	1.60	9.54	14.00	-4.46
6945 (RU Size 484 + RU Size 242.93)	8.31	-	-	-	8.31	1.30	9.61	14.00	-4.39
7025 (RU Size 484 + RU Size 242.90)	8.26	-	-	-	8.26	1.30	9.56	14.00	-4.44

Table 165 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 LPI	Duty Cycle (%):	97.3
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	-	12.72	-	-	12.72	1.30	14.02	24.00	-9.98
6145	-	13.13	-	-	13.13	1.00	14.13	24.00	-9.87
6305	-	14.01	-	-	14.01	0.50	14.51	24.00	-9.49
6385	-	13.59	-	-	13.59	0.50	14.09	24.00	-9.91
6465	-	13.81	-	-	13.81	0.50	14.31	24.00	-9.69
6545	-	13.50	-	-	13.50	0.60	14.10	24.00	-9.90
6625	-	13.45	-	-	13.45	0.60	14.05	24.00	-9.95
6705	-	13.65	-	-	13.65	0.60	14.25	24.00	-9.75
6785	-	13.86	-	-	13.86	0.60	14.46	24.00	-9.54
6865	-	13.69	-	-	13.69	0.60	14.29	24.00	-9.71
6945	-	15.48	-	-	15.48	-1.20	14.28	24.00	-9.72

Table 166 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.875-7.125 GHz	Band:	U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 LPI	Duty Cycle (%):	95.5
Data Rate:	24 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-1.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
7025	-	15.48	-	-	15.48	-1.20	14.28	24.00	-9.72

Table 167- Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU LPI	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	-	13.21	-	-	13.21	1.30	14.51	24.00	-9.49
6145	-	13.87	-	-	13.87	1.00	14.87	24.00	-9.13
6385	-	14.53	-	-	14.53	0.50	15.03	24.00	-8.97
6465	-	14.22	-	-	14.22	0.50	14.72	24.00	-9.28
6545	-	13.96	-	-	13.96	0.60	14.56	24.00	-9.44
6625	-	13.91	-	-	13.91	0.60	14.51	24.00	-9.49
6705	-	14.15	-	-	14.15	0.60	14.75	24.00	-9.25
6785	-	14.34	-	-	14.34	0.60	14.94	24.00	-9.06
6865	-	14.14	-	-	14.14	0.60	14.74	24.00	-9.26
6945	-	15.99	-	-	15.99	-1.20	14.79	24.00	-9.21
7025	-	16.00	-	-	16.00	-1.20	14.80	24.00	-9.20

Table 168 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 LPI	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985 (RU Size 484 + RU Size 242.93)	-	12.17	-	-	12.17	1.30	13.47	24.00	-10.53
6145 (RU Size 484 + RU Size 242.92)	-	12.69	-	-	12.69	1.00	13.69	24.00	-10.31
6385 (RU Size 484 + RU Size 242.90)	-	13.03	-	-	13.03	0.50	13.53	24.00	-10.47
6465 (RU Size 484 + RU Size 242.93)	-	12.74	-	-	12.74	0.50	13.24	24.00	-10.76
6545 (RU Size 484 + RU Size 242.90)	-	12.85	-	-	12.85	0.60	13.45	24.00	-10.55
6545 (RU Size 484 + RU Size 242.93)	-	12.85	-	-	12.85	0.60	13.45	24.00	-10.55
6625 (RU Size 484 + RU Size 242.93)	-	12.71	-	-	12.71	0.60	13.31	24.00	-10.69
6705 (RU Size 484 + RU Size 242.91)	-	12.77	-	-	12.77	0.60	13.37	24.00	-10.63
6785 (RU Size 484 + RU Size 242.90)	-	12.62	-	-	12.62	0.60	13.22	24.00	-10.78
6865 (RU Size 484 + RU Size 242.90)	-	12.85	-	-	12.85	0.60	13.45	24.00	-10.55
6865 (RU Size 484 + RU Size 242.93)	-	12.92	-	-	12.92	0.60	13.52	24.00	-10.48
6945 (RU Size 484 + RU Size 242.93)	-	14.71	-	-	14.71	-1.20	13.51	24.00	-10.49
7025 (RU Size 484 + RU Size 242.90)	-	14.73	-	-	14.73	-1.20	13.53	24.00	-10.47

Table 169 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	-	19.26	-	-	19.26	1.30	20.56	30.00	-9.44
6145	-	19.28	-	-	19.28	1.00	20.28	30.00	-9.72
6385	-	19.12	-	-	19.12	0.50	19.62	30.00	-10.38
6625	-	19.00	-	-	19.00	0.60	19.60	30.00	-10.40
6705	-	19.02	-	-	19.02	0.60	19.62	30.00	-10.38
6785	-	19.23	-	-	19.23	0.60	19.83	30.00	-10.17

Table 170 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	-	19.27	-	-	19.27	1.30	20.57	30.00	-9.43
6145	-	19.07	-	-	19.07	1.00	20.07	30.00	-9.93
6385	-	19.02	-	-	19.02	0.50	19.52	30.00	-10.48
6625	-	19.00	-	-	19.00	0.60	19.60	30.00	-10.40
6705	-	19.12	-	-	19.12	0.60	19.72	30.00	-10.28
6785	-	19.31	-	-	19.31	0.60	19.91	30.00	-10.09

Table 171 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 SP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985 (RU Size 484 + RU Size 242.93)	-	19.10	-	-	19.10	1.30	20.40	30.00	-9.60
6145 (RU Size 484 + RU Size 242.92)	-	19.15	-	-	19.15	1.00	20.15	30.00	-9.85
6385 (RU Size 484 + RU Size 242.90)	-	19.12	-	-	19.12	0.50	19.62	30.00	-10.38
6625 (RU Size 484 + RU Size 242.93)	-	19.03	-	-	19.03	0.60	19.63	30.00	-10.37
6705 (RU Size 484 + RU Size 242.91)	-	19.15	-	-	19.15	0.60	19.75	30.00	-10.25
6785 (RU Size 484 + RU Size 242.90)	-	19.33	-	-	19.33	0.60	19.93	30.00	-10.07

Table 172 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.60
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465	-	19.19	-	-	19.19	0.50	19.69	30.00	-10.31
6545	-	19.16	-	-	19.16	0.60	19.76	30.00	-10.24

Table 173 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.60
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465	-	17.28	-	-	17.28	0.50	17.78	30.00	-12.22
6545	-	17.18	-	-	17.18	0.60	17.78	30.00	-12.22

Table 174 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 SP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.60
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465 (RU Size 484 + RU Size 242.93)	-	19.32	-	-	19.32	0.50	19.82	30.00	-10.18
6545 (RU Size 484 + RU Size 242.90)	-	19.35	-	-	19.35	0.60	19.95	30.00	-10.05

Table 175 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 VLP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	-	9.17	-	-	9.17	1.00	10.17	14.00	-3.83
6225	-	9.13	-	-	9.13	1.00	10.13	14.00	-3.87
6305	-	10.02	-	-	10.02	0.50	10.52	14.00	-3.48
6385	-	9.57	-	-	9.57	0.50	10.07	14.00	-3.93
6465	-	9.81	-	-	9.81	0.50	10.31	14.00	-3.69
6545	-	9.51	-	-	9.51	0.60	10.11	14.00	-3.89
6625	-	9.42	-	-	9.42	0.60	10.02	14.00	-3.98
6705	-	9.73	-	-	9.73	0.60	10.33	14.00	-3.67
6785	-	9.84	-	-	9.84	0.60	10.44	14.00	-3.56
6865	-	9.68	-	-	9.68	0.60	10.28	14.00	-3.72
6945	-	11.44	-	-	11.44	-1.20	10.24	14.00	-3.76

Table 176 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.875-7.125 GHz	Band:	U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 VLP	Duty Cycle (%):	95.5
Data Rate:	24 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-1.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
7025	-	11.67	-	-	11.67	-1.20	10.47	14.00	-3.53

Table 177 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	-	9.88	-	-	9.88	1.00	10.88	14.00	-3.12
6225	-	9.86	-	-	9.86	1.00	10.86	14.00	-3.14
6385	-	10.67	-	-	10.67	0.50	11.17	14.00	-2.83
6465	-	10.27	-	-	10.27	0.50	10.77	14.00	-3.23
6545	-	10.01	-	-	10.01	0.60	10.61	14.00	-3.39
6625	-	9.92	-	-	9.92	0.60	10.52	14.00	-3.48
6705	-	10.25	-	-	10.25	0.60	10.85	14.00	-3.15
6785	-	10.35	-	-	10.35	0.60	10.95	14.00	-3.05
6865	-	10.22	-	-	10.22	0.60	10.82	14.00	-3.18
6945	-	11.86	-	-	11.86	-1.20	10.66	14.00	-3.34
7025	-	12.14	-	-	12.14	-1.20	10.94	14.00	-3.06

Table 178 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 VLP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145 (RU Size 484 + RU Size 242.93)	-	8.46	-	-	8.46	1.00	9.46	14.00	-4.54
6225 (RU Size 484 + RU Size 242.92)	-	8.60	-	-	8.60	1.00	9.60	14.00	-4.40
6385 (RU Size 484 + RU Size 242.90)	-	8.93	-	-	8.93	0.50	9.43	14.00	-4.57
6465 (RU Size 484 + RU Size 242.93)	-	8.80	-	-	8.80	0.50	9.30	14.00	-4.70
6545 (RU Size 484 + RU Size 242.90)	-	8.77	-	-	8.77	0.60	9.37	14.00	-4.63
6545 (RU Size 484 + RU Size 242.93)	-	8.84	-	-	8.84	0.60	9.44	14.00	-4.56
6625 (RU Size 484 + RU Size 242.93)	-	8.73	-	-	8.73	0.60	9.33	14.00	-4.67
6705 (RU Size 484 + RU Size 242.91)	-	8.67	-	-	8.67	0.60	9.27	14.00	-4.73
6785 (RU Size 484 + RU Size 242.90)	-	8.78	-	-	8.78	0.60	9.38	14.00	-4.62
6865 (RU Size 484 + RU Size 242.90)	-	9.05	-	-	9.05	0.60	9.65	14.00	-4.35
6865 (RU Size 484 + RU Size 242.93)	-	9.01	-	-	9.01	0.60	9.61	14.00	-4.39
6945 (RU Size 484 + RU Size 242.93)	-	10.70	-	-	10.70	-1.20	9.50	14.00	-4.50
7025 (RU Size 484 + RU Size 242.90)	-	10.54	-	-	10.54	-1.20	9.34	14.00	-4.66

Table 179 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a80 LPI	Duty Cycle (%):	97.3
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	6.58	7.17	-	-	9.89	1.30	11.19	24.00	-12.81
6065	6.80	7.21	-	-	10.02	1.30	11.32	24.00	-12.68
6145	5.74	6.12	-	-	8.94	2.60	11.54	24.00	-12.46
6385	6.18	7.12	-	-	9.68	1.50	11.18	24.00	-12.82
6465	6.43	7.14	-	-	9.81	1.40	11.21	24.00	-12.79
6545	5.93	6.73	-	-	9.36	1.60	10.96	24.00	-13.04
6625	6.48	6.99	-	-	9.75	1.60	11.35	24.00	-12.65
6705	6.62	7.13	-	-	9.90	1.60	11.50	24.00	-12.50
6785	7.21	7.22	-	-	10.22	1.60	11.82	24.00	-12.18
6865	7.04	7.15	-	-	10.11	1.60	11.71	24.00	-12.29
6945	8.10	8.22	-	-	11.17	1.30	12.47	24.00	-11.53
7025	7.79	8.04	-	-	10.93	1.30	12.23	24.00	-11.77

Table 180 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU LPI	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	7.13	7.64	-	-	10.40	1.30	11.70	24.00	-12.30
6145	6.48	6.84	-	-	9.67	2.60	12.27	24.00	-11.73
6385	6.95	7.80	-	-	10.41	1.50	11.91	24.00	-12.09
6465	7.06	7.71	-	-	10.40	1.40	11.80	24.00	-12.20
6545	6.71	7.46	-	-	10.11	1.60	11.71	24.00	-12.29
6625	6.96	7.57	-	-	10.28	1.60	11.88	24.00	-12.12
6705	7.15	7.56	-	-	10.37	1.60	11.97	24.00	-12.03
6785	7.46	7.45	-	-	10.46	1.60	12.06	24.00	-11.94
6865	7.53	7.59	-	-	10.57	1.60	12.17	24.00	-11.83
6945	8.66	8.79	-	-	11.74	1.30	13.04	24.00	-10.96
7025	8.58	8.78	-	-	11.69	1.30	12.99	24.00	-11.01

Table 181 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 LPI	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985 (RU Size 484 + RU Size 242.93)	5.57	5.93	-	-	8.76	1.30	10.06	24.00	-13.94
6145 (RU Size 484 + RU Size 242.92)	5.28	5.74	-	-	8.53	2.60	11.13	24.00	-12.87
6385 (RU Size 484 + RU Size 242.90)	5.64	6.48	-	-	9.09	1.50	10.59	24.00	-13.41
6465 (RU Size 484 + RU Size 242.93)	5.72	6.37	-	-	9.07	1.40	10.47	24.00	-13.53
6545 (RU Size 484 + RU Size 242.90)	5.47	6.12	-	-	8.82	1.60	10.42	24.00	-13.58
6545 (RU Size 484 + RU Size 242.93)	5.65	6.30	-	-	9.00	1.60	10.60	24.00	-13.40
6625 (RU Size 484 + RU Size 242.93)	5.51	6.30	-	-	8.93	1.60	10.53	24.00	-13.47
6705 (RU Size 484 + RU Size 242.91)	5.66	6.12	-	-	8.91	1.60	10.51	24.00	-13.49
6785 (RU Size 484 + RU Size 242.90)	6.03	6.06	-	-	9.05	1.60	10.65	24.00	-13.35
6865 (RU Size 484 + RU Size 242.90)	6.49	6.51	-	-	9.51	1.60	11.11	24.00	-12.89
6865 (RU Size 484 + RU Size 242.93)	6.11	6.23	-	-	9.18	1.60	10.78	24.00	-13.22
6945 (RU Size 484 + RU Size 242.93)	7.27	7.35	-	-	10.32	1.30	11.62	24.00	-12.38
7025 (RU Size 484 + RU Size 242.90)	7.27	7.54	-	-	10.42	1.30	11.72	24.00	-12.28

Table 182 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a80 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	18.38	19.16	-	-	21.80	1.30	23.10	30.00	-6.90
6145	18.83	19.28	-	-	22.07	2.60	24.67	30.00	-5.33
6385	18.35	19.13	-	-	21.77	1.50	23.27	30.00	-6.73
6625	18.56	19.19	-	-	21.90	1.60	23.50	30.00	-6.50
6705	18.65	19.26	-	-	21.98	1.60	23.58	30.00	-6.42
6785	18.86	19.20	-	-	22.04	1.60	23.64	30.00	-6.36

Table 183 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	18.45	19.24	-	-	21.87	1.30	23.17	30.00	-6.83
6145	18.61	19.06	-	-	21.85	2.60	24.45	30.00	-5.55
6385	18.44	19.24	-	-	21.87	1.50	23.37	30.00	-6.63
6625	18.68	19.21	-	-	21.97	1.60	23.57	30.00	-6.43
6705	18.79	19.31	-	-	22.07	1.60	23.67	30.00	-6.33
6785	19.02	19.24	-	-	22.14	1.60	23.74	30.00	-6.26

Table 184 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 SP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985 (RU Size 484 + RU Size 242.93)	18.37	19.18	-	-	21.81	1.30	23.11	30.00	-6.89
6145 (RU Size 484 + RU Size 242.92)	18.62	19.17	-	-	21.91	2.60	24.51	30.00	-5.49
6385 (RU Size 484 + RU Size 242.90)	18.33	19.10	-	-	21.74	1.50	23.24	30.00	-6.76
6625 (RU Size 484 + RU Size 242.93)	18.45	19.05	-	-	21.77	1.60	23.37	30.00	-6.63
6705 (RU Size 484 + RU Size 242.91)	18.63	19.15	-	-	21.91	1.60	23.51	30.00	-6.49
6785 (RU Size 484 + RU Size 242.90)	18.84	19.09	-	-	21.98	1.60	23.58	30.00	-6.42

Table 185 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a80 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465	18.39	19.16	-	-	21.81	1.40	23.21	30.00	-6.79
6545	18.40	19.16	-	-	21.81	1.60	23.41	30.00	-6.59

Table 186 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465	16.55	17.25	-	-	19.92	1.40	21.32	30.00	-8.68
6545	16.55	17.19	-	-	19.90	1.60	21.50	30.00	-8.50

Table 187 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 SP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465 (RU Size 484 + RU Size 242.93)	18.55	19.21	-	-	21.90	1.40	23.30	30.00	-6.70
6545 (RU Size 484 + RU Size 242.90)	18.66	19.20	-	-	21.95	1.60	23.55	30.00	-6.45

Table 188 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a80 VLP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	1.63	2.26	-	-	4.97	2.60	7.57	14.00	-6.43
6225	1.63	2.20	-	-	4.94	2.60	7.54	14.00	-6.46
6385	2.57	3.46	-	-	6.05	1.50	7.55	14.00	-6.45
6465	2.85	3.45	-	-	6.17	1.40	7.57	14.00	-6.43
6545	2.35	3.09	-	-	5.75	1.60	7.35	14.00	-6.65
6625	2.53	3.14	-	-	5.85	1.60	7.45	14.00	-6.55
6705	2.49	2.99	-	-	5.76	1.60	7.36	14.00	-6.64
6785	2.67	2.99	-	-	5.84	1.60	7.44	14.00	-6.56
6865	3.10	3.13	-	-	6.12	1.60	7.72	14.00	-6.28
6945	4.14	4.13	-	-	7.14	1.30	8.44	14.00	-5.56
7025	3.70	3.96	-	-	6.85	1.30	8.15	14.00	-5.85

Table 189 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	2.36	2.70	-	-	5.55	2.60	8.15	14.00	-5.85
6225	2.34	2.65	-	-	5.51	2.60	8.11	14.00	-5.89
6385	3.12	3.94	-	-	6.56	1.50	8.06	14.00	-5.94
6465	3.36	3.94	-	-	6.67	1.40	8.07	14.00	-5.93
6545	3.09	3.68	-	-	6.40	1.60	8.00	14.00	-6.00
6625	2.86	3.43	-	-	6.16	1.60	7.76	14.00	-6.24
6705	3.17	3.67	-	-	6.44	1.60	8.04	14.00	-5.96
6785	3.50	3.55	-	-	6.54	1.60	8.14	14.00	-5.86
6865	2.83	3.40	-	-	6.13	1.60	7.73	14.00	-6.27
6945	4.40	3.52	-	-	6.99	1.30	8.29	14.00	-5.71
7025	4.76	4.12	-	-	7.46	1.30	8.76	14.00	-5.24

Table 190 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 VLP	Duty Cycle (%):	97.8
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145 (RU Size 484 + RU Size 242.90)	1.72	0.37	-	-	4.11	2.60	6.71	14.00	-7.29
6145 (RU Size 484 + RU Size 242.93)	1.54	0.14	-	-	3.91	2.60	6.51	14.00	-7.49
6225 (RU Size 484 + RU Size 242.90)	1.40	0.27	-	-	3.88	2.60	6.48	14.00	-7.52
6225 (RU Size 484 + RU Size 242.92)	1.52	0.26	-	-	3.95	2.60	6.55	14.00	-7.45
6385 (RU Size 484 + RU Size 242.90)	2.29	1.07	-	-	4.74	1.50	6.24	14.00	-7.76
6465 (RU Size 484 + RU Size 242.90)	2.36	1.00	-	-	4.74	1.40	6.14	14.00	-7.86
6465 (RU Size 484 + RU Size 242.93)	2.25	0.73	-	-	4.56	1.40	5.96	14.00	-8.04
6545 (RU Size 484 + RU Size 242.90)	2.16	0.91	-	-	4.59	1.60	6.19	14.00	-7.81
6545 (RU Size 484 + RU Size 242.93)	2.19	0.71	-	-	4.52	1.60	6.12	14.00	-7.88
6625 (RU Size 484 + RU Size 242.90)	2.23	1.51	-	-	4.89	1.60	6.49	14.00	-7.51
6625 (RU Size 484 + RU Size 242.93)	2.25	1.30	-	-	4.81	1.60	6.41	14.00	-7.59
6705 (RU Size 484 + RU Size 242.90)	2.33	2.07	-	-	5.21	1.60	6.81	14.00	-7.19
6705 (RU Size 484 + RU Size 242.91)	2.30	1.95	-	-	5.14	1.60	6.74	14.00	-7.26
6785 (RU Size 484 + RU Size 242.90)	2.06	1.48	-	-	4.79	1.60	6.39	14.00	-7.61
6865 (RU Size 484 + RU Size 242.90)	2.15	1.80	-	-	4.99	1.60	6.59	14.00	-7.41
6865 (RU Size 484 + RU Size 242.93)	2.24	1.83	-	-	5.05	1.60	6.65	14.00	-7.35



Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6945 (RU Size 484 + RU Size 242.90)	3.48	2.79	-	-	6.16	1.30	7.46	14.00	-6.54
6945 (RU Size 484 + RU Size 242.93)	3.11	2.45	-	-	5.80	1.30	7.10	14.00	-6.90
7025 (RU Size 484 + RU Size 242.90)	3.27	2.63	-	-	5.97	1.30	7.27	14.00	-6.73

Table 191- Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU LPI	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	10.08	10.60	-	-	13.36	1.06	14.42	24.00	-9.58
6145	9.38	9.83	-	-	12.62	1.87	14.50	24.00	-9.50
6385	9.98	10.83	-	-	13.44	1.03	14.47	24.00	-9.53
6465	9.95	10.63	-	-	13.31	0.97	14.29	24.00	-9.71
6545	9.99	10.65	-	-	13.34	1.13	14.47	24.00	-9.53
6625	9.91	10.50	-	-	13.22	1.13	14.35	24.00	-9.65
6705	10.05	10.63	-	-	13.36	1.13	14.49	24.00	-9.51
6785	10.67	10.69	-	-	13.69	1.13	14.82	24.00	-9.18
6865	10.53	10.59	-	-	13.57	1.13	14.70	24.00	-9.30
6945	11.40	11.53	-	-	14.48	0.23	14.70	24.00	-9.30
7025	11.25	11.56	-	-	14.42	0.23	14.65	24.00	-9.35

Table 192 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 LPI	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985 (RU Size 484 + RU Size 242.93)	8.64	9.13	-	-	11.90	1.06	12.96	24.00	-11.04
6145 (RU Size 484 + RU Size 242.92)	8.17	8.68	-	-	11.44	1.87	13.32	24.00	-10.68
6385 (RU Size 484 + RU Size 242.90)	8.79	9.68	-	-	12.27	1.03	13.30	24.00	-10.70
6465 (RU Size 484 + RU Size 242.93)	9.69	8.78	-	-	12.27	0.97	13.24	24.00	-10.76
6545 (RU Size 484 + RU Size 242.90)	8.63	9.16	-	-	11.92	1.13	13.05	24.00	-10.95
6545 (RU Size 484 + RU Size 242.93)	8.61	9.28	-	-	11.97	1.13	13.10	24.00	-10.90
6625 (RU Size 484 + RU Size 242.93)	8.44	9.10	-	-	11.80	1.13	12.92	24.00	-11.08
6705 (RU Size 484 + RU Size 242.91)	8.71	9.13	-	-	11.93	1.13	13.06	24.00	-10.94
6785 (RU Size 484 + RU Size 242.90)	9.28	9.26	-	-	12.28	1.13	13.41	24.00	-10.59
6865 (RU Size 484 + RU Size 242.90)	9.42	9.37	-	-	12.40	1.13	13.53	24.00	-10.47
6865 (RU Size 484 + RU Size 242.93)	9.34	9.40	-	-	12.38	1.13	13.51	24.00	-10.49
6945 (RU Size 484 + RU Size 242.93)	9.95	10.09	-	-	13.03	0.23	13.26	24.00	-10.74
7025 (RU Size 484 + RU Size 242.90)	9.98	10.20	-	-	13.10	0.23	13.33	24.00	-10.67

Table 193 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	18.44	19.25	-	-	21.87	1.06	22.93	30.00	-7.07
6145	18.74	19.26	-	-	22.02	1.87	23.89	30.00	-6.11
6385	18.40	19.20	-	-	21.83	1.03	22.86	30.00	-7.14
6625	18.63	19.21	-	-	21.94	1.13	23.06	30.00	-6.94
6705	18.77	19.24	-	-	22.02	1.13	23.15	30.00	-6.85
6785	19.02	19.19	-	-	22.12	1.13	23.25	30.00	-6.75

Table 194 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 SP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985 (RU Size 484 + RU Size 242.93)	18.44	19.12	-	-	21.80	1.06	22.86	30.00	-7.14
6145 (RU Size 484 + RU Size 242.92)	18.62	19.09	-	-	21.87	1.87	23.74	30.00	-6.26
6385 (RU Size 484 + RU Size 242.90)	18.29	19.12	-	-	21.73	1.03	22.76	30.00	-7.24
6625 (RU Size 484 + RU Size 242.93)	18.42	19.05	-	-	21.75	1.13	22.88	30.00	-7.12
6705 (RU Size 484 + RU Size 242.91)	18.56	19.12	-	-	21.86	1.13	22.99	30.00	-7.01
6785 (RU Size 484 + RU Size 242.90)	19.12	19.29	-	-	22.22	1.13	23.35	30.00	-6.65

Table 195 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.13
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465	16.47	17.20	-	-	19.86	0.97	20.83	30.00	-9.17
6545	16.43	17.21	-	-	19.85	1.13	20.98	30.00	-9.02

Table 196 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 SP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.13
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465 (RU Size 484 + RU Size 242.93)	18.57	19.24	-	-	21.93	0.97	22.90	30.00	-7.10
6545 (RU Size 484 + RU Size 242.90)	18.62	19.21	-	-	21.94	1.13	23.06	30.00	-6.94

Table 197 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU VLP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	5.47	5.94	-	-	8.72	1.87	10.59	14.00	-3.41
6225	5.41	5.93	-	-	8.68	1.87	10.56	14.00	-3.44
6385	5.80	6.75	-	-	9.31	1.03	10.34	14.00	-3.66
6465	6.06	6.88	-	-	9.50	0.97	10.47	14.00	-3.53
6545	5.84	6.67	-	-	9.29	1.13	10.41	14.00	-3.59
6625	5.79	6.52	-	-	9.18	1.13	10.31	14.00	-3.69
6705	5.98	6.60	-	-	9.31	1.13	10.44	14.00	-3.56
6785	6.29	6.50	-	-	9.41	1.13	10.53	14.00	-3.47
6865	6.18	6.36	-	-	9.28	1.13	10.41	14.00	-3.59
6945	7.21	7.47	-	-	10.35	0.23	10.58	14.00	-3.42
7025	7.17	7.53	-	-	10.37	0.23	10.59	14.00	-3.41

Table 198 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 VLP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145 (RU Size 484 + RU Size 242.93)	3.97	4.36	-	-	7.18	1.87	9.05	14.00	-4.95
6225 (RU Size 484 + RU Size 242.92)	3.92	4.50	-	-	7.23	1.87	9.10	14.00	-4.90
6385 (RU Size 484 + RU Size 242.90)	4.63	5.51	-	-	8.10	1.03	9.13	14.00	-4.87
6465 (RU Size 484 + RU Size 242.93)	4.50	5.20	-	-	7.87	0.97	8.85	14.00	-5.15
6545 (RU Size 484 + RU Size 242.90)	4.41	5.15	-	-	7.81	1.13	8.94	14.00	-5.06
6545 (RU Size 484 + RU Size 242.93)	4.43	5.22	-	-	7.85	1.13	8.98	14.00	-5.02
6625 (RU Size 484 + RU Size 242.93)	4.39	5.08	-	-	7.76	1.13	8.89	14.00	-5.11
6705 (RU Size 484 + RU Size 242.91)	4.32	5.05	-	-	7.71	1.13	8.84	14.00	-5.16
6785 (RU Size 484 + RU Size 242.90)	4.98	5.16	-	-	8.08	1.13	9.21	14.00	-4.79
6865 (RU Size 484 + RU Size 242.90)	5.19	5.35	-	-	8.28	1.13	9.41	14.00	-4.59
6865 (RU Size 484 + RU Size 242.93)	5.10	5.34	-	-	8.24	1.13	9.36	14.00	-4.64
6945 (RU Size 484 + RU Size 242.93)	5.95	6.24	-	-	9.11	0.23	9.34	14.00	-4.66
7025 (RU Size 484 + RU Size 242.90)	5.93	6.31	-	-	9.13	0.23	9.36	14.00	-4.64

Table 199 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU LPI	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.85
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	7.16	7.71	-	-	10.46	4.06	14.52	24.00	-9.48
6145	6.47	6.97	-	-	9.74	4.85	14.59	24.00	-9.41
6385	6.80	7.60	-	-	10.23	4.02	14.26	24.00	-9.74
6465	7.08	7.68	-	-	10.40	3.97	14.37	24.00	-9.63
6545	7.09	7.72	-	-	10.43	4.12	14.55	24.00	-9.45
6625	7.04	7.45	-	-	10.26	4.12	14.39	24.00	-9.61
6705	7.16	7.51	-	-	10.35	4.12	14.47	24.00	-9.53
6785	7.43	7.35	-	-	10.40	4.12	14.53	24.00	-9.47
6865	7.50	7.53	-	-	10.53	4.12	14.65	24.00	-9.35
6945	8.65	8.74	-	-	11.71	3.15	14.86	24.00	-9.14
7025	8.59	8.77	-	-	11.69	3.15	14.84	24.00	-9.16

Table 200 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.85
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	18.43	19.32	-	-	21.91	4.06	25.97	30.00	-4.03
6145	18.63	19.18	-	-	21.93	4.85	26.77	30.00	-3.23
6385	18.19	19.05	-	-	21.65	4.02	25.67	30.00	-4.33
6625	18.67	19.14	-	-	21.92	4.12	26.04	30.00	-3.96
6705	18.78	19.24	-	-	22.02	4.12	26.15	30.00	-3.85
6785	18.98	19.10	-	-	22.05	4.12	26.18	30.00	-3.82

Table 201 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.12
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465	16.67	17.25	-	-	19.98	3.97	23.95	30.00	-6.05
6545	16.64	17.24	-	-	19.96	4.12	24.09	30.00	-5.91

Table 202 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	TxBF	Peak Antenna Gain (dBi):	4.85
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	2.06	2.63	-	-	5.36	4.85	10.21	14.00	-3.79
6225	2.00	2.61	-	-	5.32	4.85	10.17	14.00	-3.83
6385	2.78	3.74	-	-	6.30	4.02	10.32	14.00	-3.68
6465	3.12	3.85	-	-	6.51	3.97	10.48	14.00	-3.52
6545	2.80	3.56	-	-	6.21	4.12	10.33	14.00	-3.67
6625	2.98	3.66	-	-	6.35	4.12	10.47	14.00	-3.53
6705	2.87	3.42	-	-	6.16	4.12	10.29	14.00	-3.71
6785	3.36	3.53	-	-	6.46	4.12	10.58	14.00	-3.42
6865	3.49	3.64	-	-	6.58	4.12	10.70	14.00	-3.30
6945	4.45	4.82	-	-	7.65	3.15	10.80	14.00	-3.20
7025	4.32	4.73	-	-	7.54	3.15	10.69	14.00	-3.31

Table 203 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 LPI	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	14.30	-	-	-	14.30	2.60	16.90	24.00	-7.10
6345	15.75	-	-	-	15.75	1.50	17.25	24.00	-6.75
6505	15.54	-	-	-	15.54	1.40	16.94	24.00	-7.06
6665	15.68	-	-	-	15.68	1.60	17.28	24.00	-6.72
6825	15.24	-	-	-	15.24	1.60	16.84	24.00	-7.16
6985	15.91	-	-	-	15.91	1.30	17.21	24.00	-6.79

Table 204 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz	Band:	U-NII-5
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 LPI	Duty Cycle (%):	95.4
Data Rate:	24 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.80
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	16.02	-	-	-	16.02	0.80	16.82	24.00	-7.18

Table 205 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU LPI	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	16.61	-	-	-	16.61	0.80	17.41	24.00	-6.59
6185	14.69	-	-	-	14.69	2.60	17.29	24.00	-6.71
6345	15.98	-	-	-	15.98	1.50	17.48	24.00	-6.52
6505	15.80	-	-	-	15.80	1.40	17.20	24.00	-6.80
6665	16.12	-	-	-	16.12	1.60	17.72	24.00	-6.28
6825	15.74	-	-	-	15.74	1.60	17.34	24.00	-6.66
6985	15.92	-	-	-	15.92	1.30	17.22	24.00	-6.78

Table 206 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 LPI (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	13.58	-	-	-	13.58	2.60	16.18	24.00	-7.82
6345 (RU Size 996 + RU Size 484.94)	14.64	-	-	-	14.64	1.50	16.14	24.00	-7.86
6505 (RU Size 996 + RU Size 484.94)	14.62	-	-	-	14.62	1.40	16.02	24.00	-7.98
6665 (RU Size 996 + RU Size 484.94)	14.42	-	-	-	14.42	1.60	16.02	24.00	-7.98
6825 (RU Size 996 + RU Size 484.94)	14.22	-	-	-	14.22	1.60	15.82	24.00	-8.18
6985 (RU Size 996 + RU Size 484.94)	14.62	-	-	-	14.62	1.30	15.92	24.00	-8.08

Table 207 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 LPI (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484.95)	15.70	-	-	-	15.70	0.80	16.50	24.00	-7.50
6185 (RU Size 996 + RU Size 484.94)	13.49	-	-	-	13.49	2.60	16.09	24.00	-7.91
6505 (RU Size 996 + RU Size 484.95)	14.58	-	-	-	14.58	1.40	15.98	24.00	-8.02
6665 (RU Size 996 + RU Size 484.95)	14.63	-	-	-	14.63	1.60	16.23	24.00	-7.77
6825 (RU Size 996 + RU Size 484.95)	14.38	-	-	-	14.38	1.60	15.98	24.00	-8.02
6985 (RU Size 996 + RU Size 484.95)	14.66	-	-	-	14.66	1.30	15.96	24.00	-8.04

Table 208 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 LPI (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	14.29	-	-	-	14.29	2.60	16.89	24.00	-7.11
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	14.10	-	-	-	14.10	2.60	16.70	24.00	-7.30
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	14.07	-	-	-	14.07	2.60	16.67	24.00	-7.33
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	15.45	-	-	-	15.45	1.50	16.95	24.00	-7.05
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	15.11	-	-	-	15.11	1.40	16.51	24.00	-7.49
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	15.20	-	-	-	15.20	1.60	16.80	24.00	-7.20
6825 (RU Size 996 + RU Size 484 + RU Size 242.96)	15.02	-	-	-	15.02	1.60	16.62	24.00	-7.38
6985 (RU Size 996 + RU Size 484 + RU Size 242.96)	15.61	-	-	-	15.61	1.30	16.91	24.00	-7.09

Table 209 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 LPI (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484 + RU Size 242.99)	15.97	-	-	-	15.97	0.80	16.77	24.00	-7.23
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	15.13	-	-	-	15.13	1.40	16.53	24.00	-7.47
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	15.07	-	-	-	15.07	1.60	16.67	24.00	-7.33
6825 (RU Size 996 + RU Size 484 + RU Size 242.99)	15.11	-	-	-	15.11	1.60	16.71	24.00	-7.29
6985 (RU Size 996 + RU Size 484 + RU Size 242.99)	15.54	-	-	-	15.54	1.30	16.84	24.00	-7.16

Table 210 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	19.14	-	-	-	19.14	0.80	19.94	30.00	-10.06
6185	19.12	-	-	-	19.12	2.60	21.72	30.00	-8.28
6345	19.04	-	-	-	19.04	1.50	20.54	30.00	-9.46
6665	19.03	-	-	-	19.03	1.60	20.63	30.00	-9.37

Table 211 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	19.08	-	-	-	19.08	0.80	19.88	30.00	-10.12
6185	19.25	-	-	-	19.25	2.60	21.85	30.00	-8.15
6345	19.10	-	-	-	19.10	1.50	20.60	30.00	-9.40
6665	19.04	-	-	-	19.04	1.60	20.64	30.00	-9.36

Table 212 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	19.15	-	-	-	19.15	2.60	21.75	30.00	-8.25
6345 (RU Size 996 + RU Size 484.94)	19.24	-	-	-	19.24	1.50	20.74	30.00	-9.26
6665 (RU Size 996 + RU Size 484.94)	19.17	-	-	-	19.17	1.60	20.77	30.00	-9.23

Table 213 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484.95)	19.16	-	-	-	19.16	0.80	19.96	30.00	-10.04
6185 (RU Size 996 + RU Size 484.94)	19.29	-	-	-	19.29	2.60	21.89	30.00	-8.11
6665 (RU Size 996 + RU Size 484.95)	19.37	-	-	-	19.37	1.60	20.97	30.00	-9.03

Table 214 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	19.16	-	-	-	19.16	2.60	21.76	30.00	-8.24
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	19.14	-	-	-	19.14	2.60	21.74	30.00	-8.26
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	19.12	-	-	-	19.12	2.60	21.72	30.00	-8.28
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	19.15	-	-	-	19.15	1.50	20.65	30.00	-9.35
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	19.10	-	-	-	19.10	1.60	20.70	30.00	-9.30

Table 215 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484 + RU Size 242.99)	19.23	-	-	-	19.23	0.80	20.03	30.00	-9.97
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	19.11	-	-	-	19.11	1.60	20.71	30.00	-9.29

Table 216 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505	19.13	-	-	-	19.13	1.40	20.53	30.00	-9.47

Table 217 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505	17.19	-	-	-	17.19	1.40	18.59	30.00	-11.41

Table 218 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484.94)	19.16	-	-	-	19.16	1.40	20.56	30.00	-9.44

Table 219 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484.95)	19.11	-	-	-	19.11	1.40	20.51	30.00	-9.49

Table 220 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	19.28	-	-	-	19.28	1.40	20.68	30.00	-9.32

Table 221 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	19.02	-	-	-	19.02	1.40	20.42	30.00	-9.58

Table 222 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 VLP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	10.18	-	-	-	10.18	2.60	12.78	14.00	-1.22
6345	11.22	-	-	-	11.22	1.50	12.72	14.00	-1.28
6505	11.06	-	-	-	11.06	1.40	12.46	14.00	-1.54
6665	11.20	-	-	-	11.20	1.60	12.80	14.00	-1.20
6825	11.32	-	-	-	11.32	1.60	12.92	14.00	-1.08
6985	11.48	-	-	-	11.48	1.30	12.78	14.00	-1.22

Table 223 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU VLP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	10.10	-	-	-	10.10	2.60	12.70	14.00	-1.30
6345	11.20	-	-	-	11.20	1.50	12.70	14.00	-1.30
6505	11.03	-	-	-	11.03	1.40	12.43	14.00	-1.57
6665	11.19	-	-	-	11.19	1.60	12.79	14.00	-1.21
6825	11.28	-	-	-	11.28	1.60	12.88	14.00	-1.12
6985	11.48	-	-	-	11.48	1.30	12.78	14.00	-1.22

Table 224 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 VLP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	9.60	-	-	-	9.60	2.60	12.20	14.00	-1.80
6345 (RU Size 996 + RU Size 484.94)	10.67	-	-	-	10.67	1.50	12.17	14.00	-1.83
6505 (RU Size 996 + RU Size 484.94)	10.68	-	-	-	10.68	1.40	12.08	14.00	-1.92
6665 (RU Size 996 + RU Size 484.94)	10.50	-	-	-	10.50	1.60	12.10	14.00	-1.90
6825 (RU Size 996 + RU Size 484.94)	10.36	-	-	-	10.36	1.60	11.96	14.00	-2.04
6985 (RU Size 996 + RU Size 484.94)	10.71	-	-	-	10.71	1.30	12.01	14.00	-1.99

Table 225 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 VLP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.94)	9.48	-	-	-	9.48	2.60	12.08	14.00	-1.92
6505 (RU Size 996 + RU Size 484.95)	10.62	-	-	-	10.62	1.40	12.02	14.00	-1.98
6665 (RU Size 996 + RU Size 484.95)	10.64	-	-	-	10.64	1.60	12.24	14.00	-1.76
6825 (RU Size 996 + RU Size 484.95)	10.43	-	-	-	10.43	1.60	12.03	14.00	-1.97
6985 (RU Size 996 + RU Size 484.95)	10.42	-	-	-	10.42	1.30	11.72	14.00	-2.28

Table 226 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 VLP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	10.12	-	-	-	10.12	2.60	12.72	14.00	-1.28
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	9.87	-	-	-	9.87	2.60	12.47	14.00	-1.53
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	9.96	-	-	-	9.96	2.60	12.56	14.00	-1.44
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	11.32	-	-	-	11.32	1.50	12.82	14.00	-1.18
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	11.25	-	-	-	11.25	1.40	12.65	14.00	-1.35
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	11.35	-	-	-	11.35	1.60	12.95	14.00	-1.05
6825 (RU Size 996 + RU Size 484 + RU Size 242.96)	11.17	-	-	-	11.17	1.60	12.77	14.00	-1.23
6985 (RU Size 996 + RU Size 484 + RU Size 242.96)	11.58	-	-	-	11.58	1.30	12.88	14.00	-1.12

Table 227 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 VLP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	11.25	-	-	-	11.25	1.40	12.65	14.00	-1.35
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	11.16	-	-	-	11.16	1.60	12.76	14.00	-1.24
6825 (RU Size 996 + RU Size 484 + RU Size 242.99)	10.98	-	-	-	10.98	1.60	12.58	14.00	-1.42
6985 (RU Size 996 + RU Size 484 + RU Size 242.99)	11.68	-	-	-	11.68	1.30	12.98	14.00	-1.02

Table 228 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 LPI	Duty Cycle (%):	97.3
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	-	16.15	-	-	16.15	1.30	17.45	24.00	-6.55
6185	-	16.04	-	-	16.04	1.00	17.04	24.00	-6.96
6345	-	16.58	-	-	16.58	0.50	17.08	24.00	-6.92
6505	-	16.61	-	-	16.61	0.50	17.11	24.00	-6.89
6665	-	16.78	-	-	16.78	0.60	17.38	24.00	-6.62
6825	-	16.45	-	-	16.45	0.60	17.05	24.00	-6.95
6985	-	18.19	-	-	18.19	-1.20	16.99	24.00	-7.01

Table 229 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU LPI	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	-	16.36	-	-	16.36	1.30	17.66	24.00	-6.34
6185	-	16.30	-	-	16.30	1.00	17.30	24.00	-6.70
6345	-	17.10	-	-	17.10	0.50	17.60	24.00	-6.40
6505	-	16.99	-	-	16.99	0.50	17.49	24.00	-6.51
6665	-	17.00	-	-	17.00	0.60	17.60	24.00	-6.40
6825	-	16.81	-	-	16.81	0.60	17.41	24.00	-6.59
6985	-	17.01	-	-	17.01	-1.20	15.81	24.00	-8.19

Table 230 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 LPI (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	-	15.12	-	-	15.12	1.00	16.12	24.00	-7.88
6345 (RU Size 996 + RU Size 484.94)	-	15.44	-	-	15.44	0.50	15.94	24.00	-8.06
6505 (RU Size 996 + RU Size 484.94)	-	15.32	-	-	15.32	0.50	15.82	24.00	-8.18
6665 (RU Size 996 + RU Size 484.94)	-	15.79	-	-	15.79	0.60	16.39	24.00	-7.61
6825 (RU Size 996 + RU Size 484.94)	-	15.70	-	-	15.70	0.60	16.30	24.00	-7.70
6985 (RU Size 996 + RU Size 484.94)	-	17.27	-	-	17.27	-1.20	16.07	24.00	-7.93

Table 231 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 LPI (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484.95)	-	14.63	-	-	14.63	1.30	15.93	24.00	-8.07
6185 (RU Size 996 + RU Size 484.94)	-	14.97	-	-	14.97	1.00	15.97	24.00	-8.03
6505 (RU Size 996 + RU Size 484.95)	-	15.34	-	-	15.34	0.50	15.84	24.00	-8.16
6665 (RU Size 996 + RU Size 484.95)	-	15.85	-	-	15.85	0.60	16.45	24.00	-7.55
6825 (RU Size 996 + RU Size 484.95)	-	15.71	-	-	15.71	0.60	16.31	24.00	-7.69
6985 (RU Size 996 + RU Size 484.95)	-	17.11	-	-	17.11	-1.20	15.91	24.00	-8.09

Table 232 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 LPI (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	-	15.83	-	-	15.83	1.00	16.83	24.00	-7.17
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	-	15.83	-	-	15.83	1.00	16.83	24.00	-7.17
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	15.84	-	-	15.84	1.00	16.84	24.00	-7.16
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	16.35	-	-	16.35	0.50	16.85	24.00	-7.15
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	16.38	-	-	16.38	0.50	16.88	24.00	-7.12
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	16.21	-	-	16.21	0.60	16.81	24.00	-7.19
6825 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	16.25	-	-	16.25	0.60	16.85	24.00	-7.15
6985 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	18.06	-	-	18.06	-1.20	16.86	24.00	-7.14

Table 233- Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 LPI (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	15.35	-	-	15.35	1.30	16.65	24.00	-7.35
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	16.39	-	-	16.39	0.50	16.89	24.00	-7.11
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	16.33	-	-	16.33	0.60	16.93	24.00	-7.07
6825 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	16.16	-	-	16.16	0.60	16.76	24.00	-7.24
6985 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	18.11	-	-	18.11	-1.20	16.91	24.00	-7.09

Table 234 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	-	19.10	-	-	19.10	1.30	20.40	30.00	-9.60
6185	-	19.10	-	-	19.10	1.00	20.10	30.00	-9.90
6345	-	19.18	-	-	19.18	0.50	19.68	30.00	-10.32
6665	-	19.05	-	-	19.05	0.60	19.65	30.00	-10.35

Table 235 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	-	19.13	-	-	19.13	1.30	20.43	30.00	-9.57
6185	-	19.16	-	-	19.16	1.00	20.16	30.00	-9.84
6345	-	19.19	-	-	19.19	0.50	19.69	30.00	-10.31
6665	-	19.06	-	-	19.06	0.60	19.66	30.00	-10.34

Table 236 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	-	19.23	-	-	19.23	1.00	20.23	30.00	-9.77
6345 (RU Size 996 + RU Size 484.94)	-	19.26	-	-	19.26	0.50	19.76	30.00	-10.24
6665 (RU Size 996 + RU Size 484.94)	-	19.34	-	-	19.34	0.60	19.94	30.00	-10.06

Table 237 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484.95)	-	19.23	-	-	19.23	1.30	20.53	30.00	-9.47
6185 (RU Size 996 + RU Size 484.94)	-	19.18	-	-	19.18	1.00	20.18	30.00	-9.82
6665 (RU Size 996 + RU Size 484.95)	-	19.11	-	-	19.11	0.60	19.71	30.00	-10.29

Table 238 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	-	19.19	-	-	19.19	1.00	20.19	30.00	-9.81
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	-	19.29	-	-	19.29	1.00	20.29	30.00	-9.71
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	19.21	-	-	19.21	1.00	20.21	30.00	-9.79
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	19.29	-	-	19.29	0.50	19.79	30.00	-10.21
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	19.16	-	-	19.16	0.60	19.76	30.00	-10.24

Table 239 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	19.27	-	-	19.27	1.30	20.57	30.00	-9.43
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	19.11	-	-	19.11	0.60	19.71	30.00	-10.29

Table 240 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 SP	Duty Cycle (%):	97.5
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.50
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505	-	19.09	-	-	19.09	0.50	19.59	30.00	-10.41

Table 241 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.50
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505	-	17.10	-	-	17.10	0.50	17.60	30.00	-12.40

Table 242 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.50
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484.94)	-	19.09	-	-	19.09	0.50	19.59	30.00	-10.41

Table 243 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.50
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484.95)	-	19.16	-	-	19.16	0.50	19.66	30.00	-10.34

Table 244 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.50
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	19.16	-	-	19.16	0.50	19.66	30.00	-10.34

Table 245 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.50
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	19.17	-	-	19.17	0.50	19.67	30.00	-10.33

Table 246 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 VLP	Duty Cycle (%):	97.4
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	-	11.66	-	-	11.66	1.00	12.66	14.00	-1.34
6345	-	12.18	-	-	12.18	0.50	12.68	14.00	-1.32
6505	-	12.08	-	-	12.08	0.50	12.58	14.00	-1.42
6665	-	12.10	-	-	12.10	0.60	12.70	14.00	-1.30
6825	-	12.05	-	-	12.05	0.60	12.65	14.00	-1.35
6985	-	14.03	-	-	14.03	-1.20	12.83	14.00	-1.17

Table 247 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU VLP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	-	11.70	-	-	11.70	1.00	12.70	14.00	-1.30
6345	-	12.24	-	-	12.24	0.50	12.74	14.00	-1.26
6505	-	12.11	-	-	12.11	0.50	12.61	14.00	-1.39
6665	-	12.00	-	-	12.00	0.60	12.60	14.00	-1.40
6825	-	12.27	-	-	12.27	0.60	12.87	14.00	-1.13
6985	-	14.17	-	-	14.17	-1.20	12.97	14.00	-1.03

Table 248 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 VLP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	-	11.02	-	-	11.02	1.00	12.02	14.00	-1.98
6345 (RU Size 996 + RU Size 484.94)	-	11.38	-	-	11.38	0.50	11.88	14.00	-2.12
6505 (RU Size 996 + RU Size 484.94)	-	11.48	-	-	11.48	0.50	11.98	14.00	-2.02
6665 (RU Size 996 + RU Size 484.94)	-	11.67	-	-	11.67	0.60	12.27	14.00	-1.73
6825 (RU Size 996 + RU Size 484.94)	-	11.87	-	-	11.87	0.60	12.47	14.00	-1.53
6985 (RU Size 996 + RU Size 484.94)	-	13.13	-	-	13.13	-1.20	11.93	14.00	-2.07

Table 249 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 VLP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.94)	-	10.93	-	-	10.93	1.00	11.93	14.00	-2.07
6505 (RU Size 996 + RU Size 484.95)	-	11.51	-	-	11.51	0.50	12.01	14.00	-1.99
6665 (RU Size 996 + RU Size 484.95)	-	11.74	-	-	11.74	0.60	12.34	14.00	-1.66
6825 (RU Size 996 + RU Size 484.95)	-	11.84	-	-	11.84	0.60	12.44	14.00	-1.56
6985 (RU Size 996 + RU Size 484.95)	-	13.03	-	-	13.03	-1.20	11.83	14.00	-2.17

Table 250 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 VLP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	1.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	-	11.70	-	-	11.70	1.00	12.70	14.00	-1.30
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	-	11.73	-	-	11.73	1.00	12.73	14.00	-1.27
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	11.70	-	-	11.70	1.00	12.70	14.00	-1.30
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	12.12	-	-	12.12	0.50	12.62	14.00	-1.38
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	12.16	-	-	12.16	0.50	12.66	14.00	-1.34
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	12.19	-	-	12.19	0.60	12.79	14.00	-1.21
6825 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	12.16	-	-	12.16	0.60	12.76	14.00	-1.24
6985 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	14.11	-	-	14.11	-1.20	12.91	14.00	-1.09

Table 251 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 VLP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	0.60
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	12.20	-	-	12.20	0.50	12.70	14.00	-1.30
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	12.12	-	-	12.12	0.60	12.72	14.00	-1.28
6825 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	12.19	-	-	12.19	0.60	12.79	14.00	-1.21
6985 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	13.98	-	-	13.98	-1.20	12.78	14.00	-1.22

Table 252 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a160 LPI	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	9.71	9.41	-	-	12.57	1.30	13.87	24.00	-10.13
6185	9.09	8.68	-	-	11.90	2.60	14.50	24.00	-9.50
6345	9.98	8.69	-	-	12.39	1.50	13.89	24.00	-10.11
6505	10.19	10.09	-	-	13.15	1.40	14.55	24.00	-9.45
6665	10.26	10.01	-	-	13.15	1.60	14.75	24.00	-9.25
6825	9.59	9.04	-	-	12.33	1.60	13.93	24.00	-10.07
6985	10.55	10.45	-	-	13.51	1.30	14.81	24.00	-9.19

Table 253 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE160 SU LPI	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	10.39	10.19	-	-	13.30	1.30	14.60	24.00	-9.40
6185	9.52	9.15	-	-	12.35	2.60	14.95	24.00	-9.05
6345	10.09	10.23	-	-	13.17	1.50	14.67	24.00	-9.33
6505	10.06	10.13	-	-	13.10	1.40	14.50	24.00	-9.50
6665	10.46	10.29	-	-	13.39	1.60	14.99	24.00	-9.01
6825	10.34	9.85	-	-	13.11	1.60	14.71	24.00	-9.29
6985	11.22	11.14	-	-	14.19	1.30	15.49	24.00	-8.51

Table 254 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 LPI (Primary)	Duty Cycle (%):	97.8
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	8.05	7.64	-	-	10.86	2.60	13.46	24.00	-10.54
6345 (RU Size 996 + RU Size 484.94)	9.14	9.15	-	-	12.16	1.50	13.66	24.00	-10.34
6505 (RU Size 996 + RU Size 484.94)	9.12	9.06	-	-	12.10	1.40	13.50	24.00	-10.50
6665 (RU Size 996 + RU Size 484.94)	8.91	8.67	-	-	11.80	1.60	13.40	24.00	-10.60
6825 (RU Size 996 + RU Size 484.94)	8.79	8.14	-	-	11.49	1.60	13.09	24.00	-10.91
6985 (RU Size 996 + RU Size 484.94)	9.66	9.55	-	-	12.62	1.30	13.92	24.00	-10.08

Table 255 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 LPI (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484.95)	8.86	8.62	-	-	11.75	1.30	13.05	24.00	-10.95
6185 (RU Size 996 + RU Size 484.94)	8.15	7.62	-	-	10.90	2.60	13.50	24.00	-10.50
6505 (RU Size 996 + RU Size 484.95)	9.16	9.06	-	-	12.12	1.40	13.52	24.00	-10.48
6665 (RU Size 996 + RU Size 484.95)	9.08	8.79	-	-	11.95	1.60	13.55	24.00	-10.45
6825 (RU Size 996 + RU Size 484.95)	8.98	8.34	-	-	11.68	1.60	13.28	24.00	-10.72
6985 (RU Size 996 + RU Size 484.95)	9.70	9.45	-	-	12.59	1.30	13.89	24.00	-10.11

Table 256 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 LPI (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	9.01	8.60	-	-	11.82	2.60	14.42	24.00	-9.58
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	9.15	8.67	-	-	11.93	2.60	14.53	24.00	-9.47
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	9.08	8.67	-	-	11.89	2.60	14.49	24.00	-9.51
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	9.42	9.55	-	-	12.50	1.50	14.00	24.00	-10.00
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	9.68	9.63	-	-	12.66	1.40	14.06	24.00	-9.94
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	9.53	9.36	-	-	12.46	1.60	14.06	24.00	-9.94
6825 (RU Size 996 + RU Size 484 + RU Size 242.96)	9.42	8.75	-	-	12.11	1.60	13.71	24.00	-10.29
6985 (RU Size 996 + RU Size 484 + RU Size 242.96)	10.73	10.71	-	-	13.73	1.30	15.03	24.00	-8.97

Table 257 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 LPI (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484 + RU Size 242.99)	9.43	9.28	-	-	12.36	1.30	13.66	24.00	-10.34
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	9.74	9.72	-	-	12.74	1.40	14.14	24.00	-9.86
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	9.61	9.28	-	-	12.45	1.60	14.05	24.00	-9.95
6825 (RU Size 996 + RU Size 484 + RU Size 242.99)	9.54	8.87	-	-	12.23	1.60	13.83	24.00	-10.17
6985 (RU Size 996 + RU Size 484 + RU Size 242.99)	10.81	10.77	-	-	13.80	1.30	15.10	24.00	-8.90

Table 258 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a160 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	19.23	18.89	-	-	22.08	1.30	23.38	30.00	-6.62
6185	19.13	18.67	-	-	21.91	2.60	24.51	30.00	-5.49
6345	19.29	19.11	-	-	22.21	1.50	23.71	30.00	-6.29
6665	19.23	19.04	-	-	22.14	1.60	23.74	30.00	-6.26

Table 259 - Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	19.13	18.89	-	-	22.02	1.30	23.32	30.00	-6.68
6185	19.29	18.86	-	-	22.09	2.60	24.69	30.00	-5.31
6345	19.03	18.91	-	-	21.98	1.50	23.48	30.00	-6.52
6665	18.77	18.55	-	-	21.67	1.60	23.27	30.00	-6.73

Table 260 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	19.08	18.61	-	-	21.86	2.60	24.46	30.00	-5.54
6345 (RU Size 996 + RU Size 484.94)	19.25	19.20	-	-	22.23	1.50	23.73	30.00	-6.27
6665 (RU Size 996 + RU Size 484.94)	19.14	18.94	-	-	22.05	1.60	23.65	30.00	-6.35

Table 261 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484.95)	19.08	18.87	-	-	21.99	1.30	23.29	30.00	-6.71
6185 (RU Size 996 + RU Size 484.94)	19.23	18.81	-	-	22.03	2.60	24.63	30.00	-5.37
6665 (RU Size 996 + RU Size 484.95)	19.24	19.06	-	-	22.16	1.60	23.76	30.00	-6.24

Table 262 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	19.34	18.84	-	-	22.11	2.60	24.71	30.00	-5.29
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	19.13	18.65	-	-	21.91	2.60	24.51	30.00	-5.49
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	19.09	18.64	-	-	21.88	2.60	24.48	30.00	-5.52
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	19.04	18.98	-	-	22.02	1.50	23.52	30.00	-6.48
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	19.01	18.74	-	-	21.89	1.60	23.49	30.00	-6.51

Table 263 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484 + RU Size 242.99)	19.21	18.98	-	-	22.11	1.30	23.41	30.00	-6.59
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	19.08	18.81	-	-	21.96	1.60	23.56	30.00	-6.44

Table 264 - Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a160 SP	Duty Cycle (%):	97.4
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505	19.21	19.05	-	-	22.14	1.40	23.54	30.00	-6.46

Table 265 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505	17.11	17.14	-	-	20.13	1.40	21.53	30.00	-8.47

Table 266 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484.94)	19.12	19.01	-	-	22.07	1.40	23.47	30.00	-6.53

Table 267 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484.95)	19.16	19.02	-	-	22.10	1.40	23.50	30.00	-6.50

Table 268 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	19.28	19.14	-	-	22.22	1.40	23.62	30.00	-6.38

Table 269 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.40
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	19.23	19.14	-	-	22.20	1.40	23.60	30.00	-6.40

Table 270 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a160 VLP	Duty Cycle (%):	97.4
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	4.84	4.32	-	-	7.60	2.60	10.20	14.00	-3.80
6345	6.02	6.04	-	-	9.04	1.50	10.54	14.00	-3.46
6505	6.15	6.13	-	-	9.15	1.40	10.55	14.00	-3.45
6665	6.35	5.98	-	-	9.18	1.60	10.78	14.00	-3.22
6825	5.58	5.07	-	-	8.34	1.60	9.94	14.00	-4.06
6985	6.56	6.41	-	-	9.50	1.30	10.80	14.00	-3.20

Table 271 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE160 SU VLP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	5.47	4.99	-	-	8.24	2.60	10.84	14.00	-3.16
6345	6.28	6.32	-	-	9.31	1.50	10.81	14.00	-3.19
6505	6.10	6.13	-	-	9.13	1.40	10.53	14.00	-3.47
6665	6.29	6.09	-	-	9.20	1.60	10.80	14.00	-3.20
6825	6.15	5.67	-	-	8.93	1.60	10.53	14.00	-3.47
6985	7.32	7.17	-	-	10.26	1.30	11.56	14.00	-2.44

Table 272 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 VLP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	4.09	3.72	-	-	6.92	2.60	9.52	14.00	-4.48
6345 (RU Size 996 + RU Size 484.94)	4.76	4.90	-	-	7.84	1.50	9.34	14.00	-4.66
6505 (RU Size 996 + RU Size 484.94)	4.73	4.73	-	-	7.74	1.40	9.14	14.00	-4.86
6665 (RU Size 996 + RU Size 484.94)	5.01	4.92	-	-	7.97	1.60	9.57	14.00	-4.43
6825 (RU Size 996 + RU Size 484.94)	4.86	4.34	-	-	7.62	1.60	9.22	14.00	-4.78
6985 (RU Size 996 + RU Size 484.94)	5.64	5.56	-	-	8.61	1.30	9.91	14.00	-4.09

Table 273 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 VLP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.94)	4.10	3.68	-	-	6.91	2.60	9.51	14.00	-4.49
6505 (RU Size 996 + RU Size 484.95)	4.76	4.82	-	-	7.80	1.40	9.20	14.00	-4.80
6665 (RU Size 996 + RU Size 484.95)	5.17	5.00	-	-	8.10	1.60	9.70	14.00	-4.30
6825 (RU Size 996 + RU Size 484.95)	4.81	4.36	-	-	7.60	1.60	9.20	14.00	-4.80
6985 (RU Size 996 + RU Size 484.95)	5.65	5.52	-	-	8.59	1.30	9.89	14.00	-4.11

Table 274 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 VLP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	2.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	5.07	4.56	-	-	7.83	2.60	10.43	14.00	-3.57
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	5.04	4.60	-	-	7.83	2.60	10.43	14.00	-3.57
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	5.00	4.56	-	-	7.80	2.60	10.40	14.00	-3.60
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	5.49	5.55	-	-	8.53	1.50	10.03	14.00	-3.97
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	5.62	5.67	-	-	8.65	1.40	10.05	14.00	-3.95
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	5.69	5.57	-	-	8.64	1.60	10.24	14.00	-3.76
6825 (RU Size 996 + RU Size 484 + RU Size 242.96)	5.62	5.05	-	-	8.36	1.60	9.96	14.00	-4.04
6985 (RU Size 996 + RU Size 484 + RU Size 242.96)	6.68	6.65	-	-	9.68	1.30	10.98	14.00	-3.02

Table 275 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 VLP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	1.60
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	5.54	5.55	-	-	8.56	1.40	9.96	14.00	-4.04
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	5.68	5.48	-	-	8.59	1.60	10.19	14.00	-3.81
6825 (RU Size 996 + RU Size 484 + RU Size 242.99)	5.51	4.98	-	-	8.26	1.60	9.86	14.00	-4.14
6985 (RU Size 996 + RU Size 484 + RU Size 242.99)	6.81	6.71	-	-	9.77	1.30	11.07	14.00	-2.93

Table 276 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE160 SU LPI	Duty Cycle (%):	98.3
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	13.33	13.05	-	-	16.20	1.06	17.26	24.00	-6.74
6185	12.52	12.05	-	-	15.30	1.87	17.18	24.00	-6.82
6345	13.31	13.32	-	-	16.33	1.03	17.36	24.00	-6.64
6505	12.95	13.00	-	-	15.99	0.97	16.96	24.00	-7.04
6665	13.45	13.13	-	-	16.30	1.13	17.43	24.00	-6.57
6825	13.24	12.70	-	-	15.99	1.13	17.12	24.00	-6.88
6985	14.11	13.99	-	-	17.06	0.23	17.29	24.00	-6.71

Table 277 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 LPI (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	11.16	10.66	-	-	13.93	1.87	15.80	24.00	-8.20
6345 (RU Size 996 + RU Size 484.94)	11.98	12.07	-	-	15.03	1.03	16.06	24.00	-7.94
6505 (RU Size 996 + RU Size 484.94)	12.10	12.12	-	-	15.12	0.97	16.10	24.00	-7.90
6665 (RU Size 996 + RU Size 484.94)	11.87	11.78	-	-	14.83	1.13	15.96	24.00	-8.04
6825 (RU Size 996 + RU Size 484.94)	11.78	11.22	-	-	14.52	1.13	15.65	24.00	-8.35
6985 (RU Size 996 + RU Size 484.94)	12.67	12.59	-	-	15.64	0.23	15.87	24.00	-8.13

Table 278 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 LPI (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484.95)	11.91	11.64	-	-	14.79	1.06	15.84	24.00	-8.16
6185 (RU Size 996 + RU Size 484.94)	11.30	10.82	-	-	14.08	1.87	15.95	24.00	-8.05
6505 (RU Size 996 + RU Size 484.95)	12.11	12.16	-	-	15.15	0.97	16.12	24.00	-7.88
6665 (RU Size 996 + RU Size 484.95)	12.05	11.87	-	-	14.97	1.13	16.10	24.00	-7.90
6825 (RU Size 996 + RU Size 484.95)	11.91	11.41	-	-	14.67	1.13	15.80	24.00	-8.20
6985 (RU Size 996 + RU Size 484.95)	12.64	12.50	-	-	15.58	0.23	15.81	24.00	-8.19

Table 279 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 LPI (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	11.94	11.42	-	-	14.70	1.87	16.57	24.00	-7.43
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	11.93	11.48	-	-	14.72	1.87	16.60	24.00	-7.40
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	11.65	11.21	-	-	14.45	1.87	16.32	24.00	-7.68
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	12.61	12.52	-	-	15.58	1.03	16.60	24.00	-7.40
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	12.60	12.66	-	-	15.64	0.97	16.61	24.00	-7.39
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	12.77	12.59	-	-	15.69	1.13	16.82	24.00	-7.18
6825 (RU Size 996 + RU Size 484 + RU Size 242.96)	12.56	12.08	-	-	15.34	1.13	16.47	24.00	-7.53
6985 (RU Size 996 + RU Size 484 + RU Size 242.96)	13.48	13.29	-	-	16.39	0.23	16.62	24.00	-7.38

Table 280 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 LPI (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.13
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484 + RU Size 242.99)	12.42	12.31	-	-	15.38	1.06	16.43	24.00	-7.57
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	12.69	12.71	-	-	15.71	0.97	16.68	24.00	-7.32
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	12.57	12.37	-	-	15.48	1.13	16.61	24.00	-7.39
6825 (RU Size 996 + RU Size 484 + RU Size 242.99)	12.45	11.89	-	-	15.19	1.13	16.32	24.00	-7.68
6985 (RU Size 996 + RU Size 484 + RU Size 242.99)	13.40	13.20	-	-	16.31	0.23	16.54	24.00	-7.46

Table 281 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	98.3
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	19.07	18.83	-	-	21.96	1.06	23.02	30.00	-6.98
6185	19.31	18.89	-	-	22.12	1.87	23.99	30.00	-6.01
6345	19.03	18.88	-	-	21.97	1.03	22.99	30.00	-7.01
6665	18.74	18.50	-	-	21.63	1.13	22.76	30.00	-7.24

Table 282 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	19.12	18.71	-	-	21.93	1.87	23.80	30.00	-6.20
6345 (RU Size 996 + RU Size 484.94)	19.25	19.16	-	-	22.22	1.03	23.25	30.00	-6.75
6665 (RU Size 996 + RU Size 484.94)	19.07	18.96	-	-	22.03	1.13	23.16	30.00	-6.84

Table 283 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484.95)	19.11	18.79	-	-	21.96	1.06	23.02	30.00	-6.98
6185 (RU Size 996 + RU Size 484.94)	19.21	18.80	-	-	22.02	1.87	23.89	30.00	-6.11
6665 (RU Size 996 + RU Size 484.95)	19.18	19.05	-	-	22.13	1.13	23.26	30.00	-6.74

Table 284 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	19.02	18.60	-	-	21.82	1.87	23.70	30.00	-6.30
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	19.11	18.72	-	-	21.93	1.87	23.80	30.00	-6.20
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	19.13	18.64	-	-	21.90	1.87	23.78	30.00	-6.22
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	19.15	18.95	-	-	22.06	1.03	23.09	30.00	-6.91
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	19.06	18.75	-	-	21.92	1.13	23.05	30.00	-6.95

Table 285 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.13
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484 + RU Size 242.99)	19.18	18.95	-	-	22.07	1.06	23.13	30.00	-6.87
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	19.05	18.85	-	-	21.96	1.13	23.09	30.00	-6.91

Table 286 - Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	98.3
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	0.97
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505	17.12	17.07	-	-	20.10	0.97	21.08	30.00	-8.92

Table 287 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	0.97
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484.94)	19.14	19.01	-	-	22.08	0.97	23.06	30.00	-6.94

Table 288 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	0.97
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484.95)	19.09	19.05	-	-	22.08	0.97	23.05	30.00	-6.95

Table 289 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	0.97
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	19.21	19.19	-	-	22.21	0.97	23.19	30.00	-6.81

Table 290 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	0.97
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	19.23	19.19	-	-	22.22	0.97	23.20	30.00	-6.80

Table 291 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE160 SU VLP	Duty Cycle (%):	98.3
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	7.57	7.08	-	-	10.34	1.87	12.22	14.00	-1.78
6345	8.67	8.79	-	-	11.74	1.03	12.77	14.00	-1.23
6505	8.60	8.61	-	-	11.61	0.97	12.59	14.00	-1.41
6665	8.51	8.30	-	-	11.42	1.13	12.55	14.00	-1.45
6825	8.38	7.81	-	-	11.11	1.13	12.24	14.00	-1.76
6985	9.57	9.49	-	-	12.54	0.23	12.77	14.00	-1.23

Table 292 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 VLP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	1.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	7.14	6.67	-	-	9.92	1.87	11.80	14.00	-2.20
6345 (RU Size 996 + RU Size 484.94)	7.95	7.91	-	-	10.94	1.03	11.97	14.00	-2.03
6505 (RU Size 996 + RU Size 484.94)	8.10	8.02	-	-	11.07	0.97	12.05	14.00	-1.95
6665 (RU Size 996 + RU Size 484.94)	7.93	7.71	-	-	10.83	1.13	11.96	14.00	-2.04
6825 (RU Size 996 + RU Size 484.94)	7.72	7.07	-	-	10.42	1.13	11.55	14.00	-2.45
6985 (RU Size 996 + RU Size 484.94)	8.73	8.64	-	-	11.69	0.23	11.92	14.00	-2.08

Table 293 - Maximum Conducted (average) Output Power Results