



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 SU VLP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115	0.96	-	-	-	0.96	4.20	5.16	14.00	-8.84
6255	0.87	-	-	-	0.87	4.20	5.07	14.00	-8.93
6415	0.19	-	-	-	0.19	4.40	4.59	14.00	-9.41
6435	0.21	-	-	-	0.21	4.70	4.91	14.00	-9.09
6475	0.18	-	-	-	0.18	4.70	4.88	14.00	-9.12
6515	0.10	-	-	-	0.10	4.70	4.80	14.00	-9.20
6535	0.95	-	-	-	0.95	3.80	4.75	14.00	-9.25
6695	1.31	-	-	-	1.31	3.80	5.11	14.00	-8.89
6855	0.92	-	-	-	0.92	3.80	4.72	14.00	-9.28
6875	1.32	-	-	-	1.32	3.80	5.12	14.00	-8.88
6895	1.44	-	-	-	1.44	3.50	4.94	14.00	-9.06
6995	1.37	-	-	-	1.37	3.50	4.87	14.00	-9.13
7095	1.38	-	-	-	1.38	3.50	4.88	14.00	-9.12

Table 337 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE40 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	3.94	-	-	-	3.94	4.20	8.14	14.00	-5.86
6245	3.63	-	-	-	3.63	4.20	7.83	14.00	-6.17
6405	3.31	-	-	-	3.31	4.40	7.71	14.00	-6.29
6445	3.18	-	-	-	3.18	4.70	7.88	14.00	-6.12
6485	3.20	-	-	-	3.20	4.70	7.90	14.00	-6.10
6525	3.46	-	-	-	3.46	4.70	8.16	14.00	-5.84
6565	4.11	-	-	-	4.11	3.80	7.91	14.00	-6.09
6725	4.13	-	-	-	4.13	3.80	7.93	14.00	-6.07
6845	4.03	-	-	-	4.03	3.80	7.83	14.00	-6.17
6885	4.36	-	-	-	4.36	3.80	8.16	14.00	-5.84
6925	4.42	-	-	-	4.42	3.50	7.92	14.00	-6.08
7005	4.29	-	-	-	4.29	3.50	7.79	14.00	-6.21
7085	4.54	-	-	-	4.54	3.50	8.04	14.00	-5.96

Table 338 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	7.08	-	-	-	7.08	4.20	11.28	14.00	-2.72
6225	6.67	-	-	-	6.67	4.20	10.87	14.00	-3.13
6305	6.42	-	-	-	6.42	4.40	10.82	14.00	-3.18
6385	6.19	-	-	-	6.19	4.40	10.59	14.00	-3.41
6465	6.60	-	-	-	6.60	4.70	11.30	14.00	-2.70
6545	6.32	-	-	-	6.32	4.70	11.02	14.00	-2.98
6625	7.09	-	-	-	7.09	3.80	10.89	14.00	-3.11
6705	7.05	-	-	-	7.05	3.80	10.85	14.00	-3.15
6785	7.01	-	-	-	7.01	3.80	10.81	14.00	-3.19
6865	7.22	-	-	-	7.22	3.80	11.02	14.00	-2.98
6945	7.56	-	-	-	7.56	3.50	11.06	14.00	-2.94
7025	7.35	-	-	-	7.35	3.50	10.85	14.00	-3.15

Table 339 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	8.43	-	-	-	8.43	4.20	12.63	14.00	-1.37
6345	8.20	-	-	-	8.20	4.40	12.60	14.00	-1.40
6505	8.00	-	-	-	8.00	4.70	12.70	14.00	-1.30
6665	9.04	-	-	-	9.04	3.80	12.84	14.00	-1.16
6825	8.89	-	-	-	8.89	3.80	12.69	14.00	-1.31
6985	9.18	-	-	-	9.18	3.50	12.68	14.00	-1.32

Table 340 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU26 VLP	Duty Cycle (%):	93.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU26.0)	-8.24	-	-	-	-8.24	4.20	-4.04	14.00	-18.04
6255 (RU26.0)	-8.48	-	-	-	-8.48	4.20	-4.28	14.00	-18.28
6415 (RU26.8)	-8.95	-	-	-	-8.95	4.40	-4.55	14.00	-18.55
6435 (RU26.0)	-9.01	-	-	-	-9.01	4.70	-4.31	14.00	-18.31
6475 (RU26.0)	-9.11	-	-	-	-9.11	4.70	-4.41	14.00	-18.41
6515 (RU26.8)	-9.08	-	-	-	-9.08	4.70	-4.38	14.00	-18.38
6535 (RU26.0)	-8.10	-	-	-	-8.10	3.80	-4.30	14.00	-18.30
6695 (RU26.0)	-8.10	-	-	-	-8.10	3.80	-4.30	14.00	-18.30
6855 (RU26.8)	-8.14	-	-	-	-8.14	3.80	-4.34	14.00	-18.34
6875 (RU26.3)	-7.95	-	-	-	-7.95	3.80	-4.15	14.00	-18.15
6875 (RU26.5)	-7.84	-	-	-	-7.84	3.80	-4.04	14.00	-18.04
6895 (RU26.0)	-8.02	-	-	-	-8.02	3.50	-4.52	14.00	-18.52
6995 (RU26.0)	-8.08	-	-	-	-8.08	3.50	-4.58	14.00	-18.58
7095 (RU26.8)	-7.39	-	-	-	-7.39	3.50	-3.89	14.00	-17.89

Table 341 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU52 VLP	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU52.37)	-5.54	-	-	-	-5.54	4.20	-1.34	14.00	-15.34
6255 (RU52.37)	-5.51	-	-	-	-5.51	4.20	-1.31	14.00	-15.31
6275 (RU52.37)	-5.87	-	-	-	-5.87	4.40	-1.47	14.00	-15.47
6415 (RU52.40)	-6.04	-	-	-	-6.04	4.40	-1.64	14.00	-15.64
6435 (RU52.37)	-6.30	-	-	-	-6.30	4.70	-1.60	14.00	-15.60
6475 (RU52.37)	-6.40	-	-	-	-6.40	4.70	-1.70	14.00	-15.70
6515 (RU52.40)	-6.38	-	-	-	-6.38	4.70	-1.68	14.00	-15.68
6535 (RU52.37)	-5.28	-	-	-	-5.28	3.80	-1.48	14.00	-15.48
6695 (RU52.37)	-5.29	-	-	-	-5.29	3.80	-1.49	14.00	-15.49
6855 (RU52.40)	-5.49	-	-	-	-5.49	3.80	-1.69	14.00	-15.69
6875 (RU52.38)	-5.25	-	-	-	-5.25	3.80	-1.45	14.00	-15.45
6875 (RU52.39)	-5.12	-	-	-	-5.12	3.80	-1.32	14.00	-15.32
6895 (RU52.37)	-5.01	-	-	-	-5.01	3.50	-1.51	14.00	-15.51
6995 (RU52.37)	-5.05	-	-	-	-5.05	3.50	-1.55	14.00	-15.55
7095 (RU52.40)	-4.91	-	-	-	-4.91	3.50	-1.41	14.00	-15.41

Table 342 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU106 VLP	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU106.53)	-2.40	-	-	-	-2.40	4.20	1.80	14.00	-12.20
6255 (RU106.53)	-2.48	-	-	-	-2.48	4.20	1.72	14.00	-12.28
6415 (RU106.54)	-2.91	-	-	-	-2.91	4.40	1.49	14.00	-12.51
6435 (RU106.53)	-3.20	-	-	-	-3.20	4.70	1.50	14.00	-12.50
6475 (RU106.53)	-3.10	-	-	-	-3.10	4.70	1.60	14.00	-12.40
6515 (RU106.54)	-3.22	-	-	-	-3.22	4.70	1.48	14.00	-12.52
6535 (RU106.53)	-2.35	-	-	-	-2.35	3.80	1.45	14.00	-12.55
6695 (RU106.53)	-2.42	-	-	-	-2.42	3.80	1.38	14.00	-12.62
6855 (RU106.54)	-2.26	-	-	-	-2.26	3.80	1.54	14.00	-12.46
6875 (RU106.53)	-1.97	-	-	-	-1.97	3.80	1.83	14.00	-12.17
6875 (RU106.54)	-2.04	-	-	-	-2.04	3.80	1.76	14.00	-12.24
6895 (RU106.53)	-2.09	-	-	-	-2.09	3.50	1.41	14.00	-12.59
6995 (RU106.53)	-2.06	-	-	-	-2.06	3.50	1.44	14.00	-12.56
7095 (RU106.54)	-2.06	-	-	-	-2.06	3.50	1.44	14.00	-12.56

Table 343 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 52 + RU Size 26 VLP	Duty Cycle (%):	97.4
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU Size 52 + RU Size 26.70)	-3.54	-	-	-	-3.54	4.20	0.66	14.00	-13.34
6255 (RU Size 52 + RU Size 26.70)	-3.58	-	-	-	-3.58	4.20	0.62	14.00	-13.38
6415 (RU Size 52 + RU Size 26.72)	-3.98	-	-	-	-3.98	4.40	0.42	14.00	-13.58
6435 (RU Size 52 + RU Size 26.70)	-4.52	-	-	-	-4.52	4.70	0.18	14.00	-13.82
6475 (RU Size 52 + RU Size 26.70)	-4.41	-	-	-	-4.41	4.70	0.29	14.00	-13.71
6515 (RU Size 52 + RU Size 26.72)	-4.52	-	-	-	-4.52	4.70	0.18	14.00	-13.82
6535 (RU Size 52 + RU Size 26.70)	-3.46	-	-	-	-3.46	3.80	0.34	14.00	-13.66
6695 (RU Size 52 + RU Size 26.70)	-3.65	-	-	-	-3.65	3.80	0.15	14.00	-13.85
6855 (RU Size 52 + RU Size 26.72)	-3.70	-	-	-	-3.70	3.80	0.10	14.00	-13.90
6875 (RU Size 52 + RU Size 26.70)	-3.16	-	-	-	-3.16	3.80	0.64	14.00	-13.36
6875 (RU Size 52 + RU Size 26.72)	-3.26	-	-	-	-3.26	3.80	0.54	14.00	-13.46
6895 (RU Size 52 + RU Size 26.70)	-3.32	-	-	-	-3.32	3.50	0.18	14.00	-13.82
6995 (RU Size 52 + RU Size 26.70)	-3.18	-	-	-	-3.18	3.50	0.32	14.00	-13.68
7095 (RU Size 52 + RU Size 26.72)	-2.86	-	-	-	-2.86	3.50	0.64	14.00	-13.36

Table 344 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 106 + RU Size 26 VLP	Duty Cycle (%):	97.3
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU Size 106 + RU Size 26.82)	-1.57	-	-	-	-1.57	4.20	2.63	14.00	-11.37
6255 (RU Size 106 + RU Size 26.82)	-1.59	-	-	-	-1.59	4.20	2.61	14.00	-11.39
6415 (RU Size 106 + RU Size 26.83)	-1.80	-	-	-	-1.80	4.40	2.60	14.00	-11.40
6435 (RU Size 106 + RU Size 26.82)	-2.09	-	-	-	-2.09	4.70	2.61	14.00	-11.39
6475 (RU Size 106 + RU Size 26.82)	-2.25	-	-	-	-2.25	4.70	2.45	14.00	-11.55
6515 (RU Size 106 + RU Size 26.83)	-2.09	-	-	-	-2.09	4.70	2.61	14.00	-11.39
6535 (RU Size 106 + RU Size 26.82)	-1.50	-	-	-	-1.50	3.80	2.30	14.00	-11.70
6695 (RU Size 106 + RU Size 26.82)	-1.30	-	-	-	-1.30	3.80	2.50	14.00	-11.50
6855 (RU Size 106 + RU Size 26.83)	-1.40	-	-	-	-1.40	3.80	2.40	14.00	-11.60
6875 (RU Size 106 + RU Size 26.82)	-1.36	-	-	-	-1.36	3.80	2.44	14.00	-11.56
6875 (RU Size 106 + RU Size 26.83)	-1.23	-	-	-	-1.23	3.80	2.57	14.00	-11.43
6895 (RU Size 106 + RU Size 26.82)	-1.47	-	-	-	-1.47	3.50	2.03	14.00	-11.97
6995 (RU Size 106 + RU Size 26.82)	-1.42	-	-	-	-1.42	3.50	2.08	14.00	-11.92
7095 (RU Size 106 + RU Size 26.83)	-0.89	-	-	-	-0.89	3.50	2.61	14.00	-11.39

Table 345 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 VLP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145 (RU Size 484 + RU Size 242.93)	5.57	-	-	-	5.57	4.20	9.77	14.00	-4.23
6225 (RU Size 484 + RU Size 242.92)	5.57	-	-	-	5.57	4.20	9.77	14.00	-4.23
6385 (RU Size 484 + RU Size 242.90)	5.29	-	-	-	5.29	4.40	9.69	14.00	-4.31
6465 (RU Size 484 + RU Size 242.93)	5.24	-	-	-	5.24	4.70	9.94	14.00	-4.06
6545 (RU Size 484 + RU Size 242.90)	5.09	-	-	-	5.09	4.70	9.79	14.00	-4.21
6545 (RU Size 484 + RU Size 242.93)	4.93	-	-	-	4.93	4.70	9.63	14.00	-4.37
6625 (RU Size 484 + RU Size 242.93)	5.73	-	-	-	5.73	3.80	9.53	14.00	-4.47
6705 (RU Size 484 + RU Size 242.91)	5.64	-	-	-	5.64	3.80	9.44	14.00	-4.56
6785 (RU Size 484 + RU Size 242.90)	5.74	-	-	-	5.74	3.80	9.54	14.00	-4.46
6865 (RU Size 484 + RU Size 242.90)	5.62	-	-	-	5.62	3.80	9.42	14.00	-4.58
6865 (RU Size 484 + RU Size 242.93)	5.93	-	-	-	5.93	3.80	9.73	14.00	-4.27
6945 (RU Size 484 + RU Size 242.93)	6.16	-	-	-	6.16	3.50	9.66	14.00	-4.34
7025 (RU Size 484 + RU Size 242.90)	5.75	-	-	-	5.75	3.50	9.25	14.00	-4.75

Table 346 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 VLP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	8.18	-	-	-	8.18	4.20	12.38	14.00	-1.62
6345 (RU Size 996 + RU Size 484.94)	8.11	-	-	-	8.11	4.40	12.51	14.00	-1.49
6505 (RU Size 996 + RU Size 484.94)	7.92	-	-	-	7.92	4.70	12.62	14.00	-1.38
6665 (RU Size 996 + RU Size 484.94)	8.80	-	-	-	8.80	3.80	12.60	14.00	-1.40
6825 (RU Size 996 + RU Size 484.94)	8.54	-	-	-	8.54	3.80	12.34	14.00	-1.66
6985 (RU Size 996 + RU Size 484.94)	8.63	-	-	-	8.63	3.50	12.13	14.00	-1.87

Table 347 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 VLP (Secondary)	Duty Cycle (%):	97.8
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.94)	8.29	-	-	-	8.29	4.20	12.49	14.00	-1.51
6505 (RU Size 996 + RU Size 484.95)	7.95	-	-	-	7.95	4.70	12.65	14.00	-1.35
6665 (RU Size 996 + RU Size 484.95)	8.77	-	-	-	8.77	3.80	12.57	14.00	-1.43
6825 (RU Size 996 + RU Size 484.95)	8.57	-	-	-	8.57	3.80	12.37	14.00	-1.63
6985 (RU Size 996 + RU Size 484.95)	8.56	-	-	-	8.56	3.50	12.06	14.00	-1.94

Table 348 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 VLP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	8.30	-	-	-	8.30	4.20	12.50	14.00	-1.50
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	8.41	-	-	-	8.41	4.20	12.61	14.00	-1.39
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	8.42	-	-	-	8.42	4.20	12.62	14.00	-1.38
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	8.23	-	-	-	8.23	4.40	12.63	14.00	-1.37
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	7.96	-	-	-	7.96	4.70	12.66	14.00	-1.34
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	9.07	-	-	-	9.07	3.80	12.87	14.00	-1.13
6825 (RU Size 996 + RU Size 484 + RU Size 242.96)	9.15	-	-	-	9.15	3.80	12.95	14.00	-1.05
6985 (RU Size 996 + RU Size 484 + RU Size 242.96)	9.24	-	-	-	9.24	3.50	12.74	14.00	-1.26

Table 349 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 VLP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	4.70
Active Port(s):	A (Core 0)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	8.07	-	-	-	8.07	4.70	12.77	14.00	-1.23
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	9.11	-	-	-	9.11	3.80	12.91	14.00	-1.09
6825 (RU Size 996 + RU Size 484 + RU Size 242.99)	8.98	-	-	-	8.98	3.80	12.78	14.00	-1.22
6985 (RU Size 996 + RU Size 484 + RU Size 242.99)	9.27	-	-	-	9.27	3.50	12.77	14.00	-1.23

Table 350 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a20 LPI	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	-	3.76	-	-	3.76	5.30	9.06	24.00	-14.94
6175	-	5.68	-	-	5.68	3.00	8.68	24.00	-15.32
6415	-	4.05	-	-	4.05	4.60	8.65	24.00	-15.35
6435	-	4.01	-	-	4.01	5.00	9.01	24.00	-14.99
6475	-	3.77	-	-	3.77	5.00	8.77	24.00	-15.23
6515	-	3.89	-	-	3.89	5.00	8.89	24.00	-15.11
6535	-	3.68	-	-	3.68	5.20	8.88	24.00	-15.12
6695	-	3.58	-	-	3.58	5.20	8.78	24.00	-15.22
6855	-	3.74	-	-	3.74	5.20	8.94	24.00	-15.06
6875	-	3.65	-	-	3.65	5.20	8.85	24.00	-15.15
6895	-	4.29	-	-	4.29	4.40	8.69	24.00	-15.31
6995	-	4.44	-	-	4.44	4.40	8.84	24.00	-15.16
7095	-	4.54	-	-	4.54	4.40	8.94	24.00	-15.06
7115	-	1.31	-	-	1.31	4.40	5.71	24.00	-18.29

Table 351 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a40 LPI	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	-	6.72	-	-	6.72	5.30	12.02	24.00	-11.98
6165	-	8.96	-	-	8.96	3.00	11.96	24.00	-12.04
6405	-	7.24	-	-	7.24	4.60	11.84	24.00	-12.16
6445	-	6.97	-	-	6.97	5.00	11.97	24.00	-12.03
6485	-	6.89	-	-	6.89	5.00	11.89	24.00	-12.11
6525	-	6.97	-	-	6.97	5.00	11.97	24.00	-12.03
6565	-	6.72	-	-	6.72	5.20	11.92	24.00	-12.08
6725	-	6.78	-	-	6.78	5.20	11.98	24.00	-12.02
6845	-	6.75	-	-	6.75	5.20	11.95	24.00	-12.05
6885	-	6.69	-	-	6.69	5.20	11.89	24.00	-12.11
6925	-	7.62	-	-	7.62	4.40	12.02	24.00	-11.98
7005	-	7.65	-	-	7.65	4.40	12.05	24.00	-11.95
7085	-	7.66	-	-	7.66	4.40	12.06	24.00	-11.94

Table 352 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 LPI	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	-	9.86	-	-	9.86	5.30	15.16	24.00	-8.84
6145	-	11.94	-	-	11.94	3.00	14.94	24.00	-9.06
6385	-	10.41	-	-	10.41	4.60	15.01	24.00	-8.99
6465	-	10.31	-	-	10.31	5.00	15.31	24.00	-8.69
6545	-	10.02	-	-	10.02	5.20	15.22	24.00	-8.78
6625	-	9.78	-	-	9.78	5.20	14.98	24.00	-9.02
6705	-	10.00	-	-	10.00	5.20	15.20	24.00	-8.80
6785	-	9.91	-	-	9.91	5.20	15.11	24.00	-8.89
6865	-	9.82	-	-	9.82	5.20	15.02	24.00	-8.98
6945	-	10.74	-	-	10.74	4.40	15.14	24.00	-8.86
7025	-	10.44	-	-	10.44	4.40	14.84	24.00	-9.16

Table 353 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 LPI	Duty Cycle (%):	97.4
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	-	12.35	-	-	12.35	5.30	17.65	24.00	-6.35
6185	-	14.65	-	-	14.65	3.00	17.65	24.00	-6.35
6345	-	13.00	-	-	13.00	4.60	17.60	24.00	-6.40
6505	-	12.56	-	-	12.56	5.00	17.56	24.00	-6.44
6665	-	12.43	-	-	12.43	5.20	17.63	24.00	-6.37
6825	-	12.59	-	-	12.59	5.20	17.79	24.00	-6.21
6985	-	13.17	-	-	13.17	4.40	17.57	24.00	-6.43

Table 354 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 SU LPI	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	-	3.98	-	-	3.98	5.30	9.28	24.00	-14.72
6175	-	6.04	-	-	6.04	3.00	9.04	24.00	-14.96
6415	-	4.26	-	-	4.26	4.60	8.86	24.00	-15.14
6435	-	4.05	-	-	4.05	5.00	9.05	24.00	-14.95
6475	-	3.97	-	-	3.97	5.00	8.97	24.00	-15.03
6515	-	3.97	-	-	3.97	5.00	8.97	24.00	-15.03
6535	-	3.67	-	-	3.67	5.20	8.87	24.00	-15.13
6695	-	3.87	-	-	3.87	5.20	9.07	24.00	-14.93
6855	-	3.72	-	-	3.72	5.20	8.92	24.00	-15.08
6875	-	3.76	-	-	3.76	5.20	8.96	24.00	-15.04
6895	-	4.55	-	-	4.55	4.40	8.95	24.00	-15.05
6995	-	4.43	-	-	4.43	4.40	8.83	24.00	-15.17
7095	-	4.61	-	-	4.61	4.40	9.01	24.00	-14.99

Table 355 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE40 SU LPI	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	-	6.74	-	-	6.74	5.30	12.04	24.00	-11.96
6165	-	8.97	-	-	8.97	3.00	11.97	24.00	-12.03
6405	-	7.30	-	-	7.30	4.60	11.90	24.00	-12.10
6445	-	7.07	-	-	7.07	5.00	12.07	24.00	-11.93
6485	-	6.95	-	-	6.95	5.00	11.95	24.00	-12.05
6525	-	7.03	-	-	7.03	5.00	12.03	24.00	-11.97
6565	-	6.80	-	-	6.80	5.20	12.00	24.00	-12.00
6725	-	6.84	-	-	6.84	5.20	12.04	24.00	-11.96
6845	-	6.80	-	-	6.80	5.20	12.00	24.00	-12.00
6885	-	6.80	-	-	6.80	5.20	12.00	24.00	-12.00
6925	-	7.65	-	-	7.65	4.40	12.05	24.00	-11.95
7005	-	7.42	-	-	7.42	4.40	11.82	24.00	-12.18
7085	-	7.45	-	-	7.45	4.40	11.85	24.00	-12.15

Table 356 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU LPI	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	-	9.88	-	-	9.88	5.30	15.18	24.00	-8.82
6145	-	11.81	-	-	11.81	3.00	14.81	24.00	-9.19
6385	-	10.48	-	-	10.48	4.60	15.08	24.00	-8.92
6465	-	10.30	-	-	10.30	5.00	15.30	24.00	-8.70
6545	-	9.99	-	-	9.99	5.20	15.19	24.00	-8.81
6625	-	9.64	-	-	9.64	5.20	14.84	24.00	-9.16
6705	-	9.92	-	-	9.92	5.20	15.12	24.00	-8.88
6785	-	9.86	-	-	9.86	5.20	15.06	24.00	-8.94
6865	-	9.79	-	-	9.79	5.20	14.99	24.00	-9.01
6945	-	10.67	-	-	10.67	4.40	15.07	24.00	-8.93
7025	-	10.41	-	-	10.41	4.40	14.81	24.00	-9.19

Table 357 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU LPI	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	-	12.29	-	-	12.29	5.30	17.59	24.00	-6.41
6185	-	14.62	-	-	14.62	3.00	17.62	24.00	-6.38
6345	-	13.04	-	-	13.04	4.60	17.64	24.00	-6.36
6505	-	12.71	-	-	12.71	5.00	17.71	24.00	-6.29
6665	-	12.59	-	-	12.59	5.20	17.79	24.00	-6.21
6825	-	12.40	-	-	12.40	5.20	17.60	24.00	-6.40
6985	-	13.18	-	-	13.18	4.40	17.58	24.00	-6.42

Table 358 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU26 LPI	Duty Cycle (%):	96.9
Modulation Coding Scheme:	MCS2x1	DCCC (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU26.0)	-	-5.57	-	-	-5.57	5.30	-0.27	24.00	-24.27
6175 (RU26.0)	-	-3.28	-	-	-3.28	3.00	-0.28	24.00	-24.28
6415 (RU26.8)	-	-5.00	-	-	-5.00	4.60	-0.40	24.00	-24.40
6435 (RU26.0)	-	-5.41	-	-	-5.41	5.00	-0.41	24.00	-24.41
6475 (RU26.0)	-	-5.43	-	-	-5.43	5.00	-0.43	24.00	-24.43
6515 (RU26.8)	-	-5.38	-	-	-5.38	5.00	-0.38	24.00	-24.38
6535 (RU26.0)	-	-5.80	-	-	-5.80	5.20	-0.60	24.00	-24.60
6695 (RU26.0)	-	-5.64	-	-	-5.64	5.20	-0.44	24.00	-24.44
6855 (RU26.8)	-	-5.43	-	-	-5.43	5.20	-0.23	24.00	-24.23
6875 (RU26.3)	-	-5.30	-	-	-5.30	5.20	-0.10	24.00	-24.10
6875 (RU26.5)	-	-5.01	-	-	-5.01	5.20	0.19	24.00	-23.81
6895 (RU26.0)	-	-4.54	-	-	-4.54	4.40	-0.14	24.00	-24.14
6995 (RU26.0)	-	-4.80	-	-	-4.80	4.40	-0.40	24.00	-24.40
7095 (RU26.8)	-	-4.36	-	-	-4.36	4.40	0.04	24.00	-23.96

Table 359 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU52 LPI	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCC (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU52.37)	-	-2.63	-	-	-2.63	5.30	2.67	24.00	-21.33
6175 (RU52.37)	-	-0.64	-	-	-0.64	3.00	2.36	24.00	-21.64
6415 (RU52.40)	-	-2.04	-	-	-2.04	4.60	2.56	24.00	-21.44
6435 (RU52.37)	-	-2.48	-	-	-2.48	5.00	2.52	24.00	-21.48
6475 (RU52.37)	-	-2.48	-	-	-2.48	5.00	2.52	24.00	-21.48
6515 (RU52.40)	-	-2.45	-	-	-2.45	5.00	2.55	24.00	-21.45
6535 (RU52.37)	-	-2.84	-	-	-2.84	5.20	2.36	24.00	-21.64
6695 (RU52.37)	-	-2.78	-	-	-2.78	5.20	2.42	24.00	-21.58
6855 (RU52.40)	-	-2.56	-	-	-2.56	5.20	2.64	24.00	-21.36
6875 (RU52.38)	-	-2.53	-	-	-2.53	5.20	2.67	24.00	-21.33
6875 (RU52.39)	-	-2.54	-	-	-2.54	5.20	2.66	24.00	-21.34
6895 (RU52.37)	-	-1.82	-	-	-1.82	4.40	2.58	24.00	-21.42
6995 (RU52.37)	-	-1.74	-	-	-1.74	4.40	2.66	24.00	-21.34
7095 (RU52.40)	-	-1.61	-	-	-1.61	4.40	2.79	24.00	-21.21

Table 360 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU106 LPI	Duty Cycle (%):	98.8
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU106.53)	-	0.24	-	-	0.24	5.30	5.54	24.00	-18.46
6175 (RU106.53)	-	2.48	-	-	2.48	3.00	5.48	24.00	-18.52
6415 (RU106.54)	-	0.90	-	-	0.90	4.60	5.50	24.00	-18.50
6435 (RU106.53)	-	0.40	-	-	0.40	5.00	5.40	24.00	-18.60
6475 (RU106.53)	-	0.44	-	-	0.44	5.00	5.44	24.00	-18.56
6515 (RU106.54)	-	0.41	-	-	0.41	5.00	5.41	24.00	-18.59
6535 (RU106.53)	-	0.21	-	-	0.21	5.20	5.41	24.00	-18.59
6695 (RU106.53)	-	0.25	-	-	0.25	5.20	5.45	24.00	-18.55
6855 (RU106.54)	-	0.48	-	-	0.48	5.20	5.68	24.00	-18.32
6875 (RU106.53)	-	0.89	-	-	0.89	5.20	6.09	24.00	-17.91
6875 (RU106.54)	-	0.86	-	-	0.86	5.20	6.06	24.00	-17.94
6895 (RU106.53)	-	1.34	-	-	1.34	4.40	5.74	24.00	-18.26
6995 (RU106.53)	-	1.23	-	-	1.23	4.40	5.63	24.00	-18.37
7095 (RU106.54)	-	0.96	-	-	0.96	4.40	5.36	24.00	-18.64

Table 361 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 52 + RU Size 26 LPI	Duty Cycle (%):	97.3
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU Size 52 + RU Size 26.70)	-	-0.52	-	-	-0.52	5.30	4.78	24.00	-19.22
6175 (RU Size 52 + RU Size 26.70)	-	1.56	-	-	1.56	3.00	4.56	24.00	-19.44
6415 (RU Size 52 + RU Size 26.72)	-	-0.50	-	-	-0.50	4.60	4.10	24.00	-19.90
6435 (RU Size 52 + RU Size 26.70)	-	-0.41	-	-	-0.41	5.00	4.59	24.00	-19.41
6475 (RU Size 52 + RU Size 26.70)	-	-0.39	-	-	-0.39	5.00	4.61	24.00	-19.39
6515 (RU Size 52 + RU Size 26.72)	-	-0.40	-	-	-0.40	5.00	4.60	24.00	-19.40
6535 (RU Size 52 + RU Size 26.70)	-	-1.05	-	-	-1.05	5.20	4.15	24.00	-19.85
6695 (RU Size 52 + RU Size 26.70)	-	-0.99	-	-	-0.99	5.20	4.21	24.00	-19.79
6855 (RU Size 52 + RU Size 26.72)	-	-1.08	-	-	-1.08	5.20	4.12	24.00	-19.88
6875 (RU Size 52 + RU Size 26.70)	-	-0.60	-	-	-0.60	5.20	4.60	24.00	-19.40
6875 (RU Size 52 + RU Size 26.72)	-	-0.55	-	-	-0.55	5.20	4.65	24.00	-19.35
6895 (RU Size 52 + RU Size 26.70)	-	-0.21	-	-	-0.21	4.40	4.19	24.00	-19.81
6995 (RU Size 52 + RU Size 26.70)	-	-0.16	-	-	-0.16	4.40	4.24	24.00	-19.76
7095 (RU Size 52 + RU Size 26.72)	-	0.42	-	-	0.42	4.40	4.82	24.00	-19.18

Table 362 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 106 + RU Size 26 LPI	Duty Cycle (%):	97.3
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU Size 106 + RU Size 26.82)	-	1.11	-	-	1.11	5.30	6.41	24.00	-17.59
6175 (RU Size 106 + RU Size 26.82)	-	3.73	-	-	3.73	3.00	6.73	24.00	-17.27
6415 (RU Size 106 + RU Size 26.83)	-	2.22	-	-	2.22	4.60	6.82	24.00	-17.18
6435 (RU Size 106 + RU Size 26.82)	-	1.51	-	-	1.51	5.00	6.51	24.00	-17.49
6475 (RU Size 106 + RU Size 26.82)	-	1.48	-	-	1.48	5.00	6.48	24.00	-17.52
6515 (RU Size 106 + RU Size 26.83)	-	1.49	-	-	1.49	5.00	6.49	24.00	-17.51
6535 (RU Size 106 + RU Size 26.82)	-	1.33	-	-	1.33	5.20	6.53	24.00	-17.47
6695 (RU Size 106 + RU Size 26.82)	-	1.41	-	-	1.41	5.20	6.61	24.00	-17.39
6855 (RU Size 106 + RU Size 26.83)	-	1.43	-	-	1.43	5.20	6.63	24.00	-17.37
6875 (RU Size 106 + RU Size 26.82)	-	1.51	-	-	1.51	5.20	6.71	24.00	-17.29
6875 (RU Size 106 + RU Size 26.83)	-	1.49	-	-	1.49	5.20	6.69	24.00	-17.31
6895 (RU Size 106 + RU Size 26.82)	-	2.03	-	-	2.03	4.40	6.43	24.00	-17.57
6995 (RU Size 106 + RU Size 26.82)	-	2.02	-	-	2.02	4.40	6.42	24.00	-17.58
7095 (RU Size 106 + RU Size 26.83)	-	2.36	-	-	2.36	4.40	6.76	24.00	-17.24

Table 363 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 LPI	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985 (RU Size 484 + RU Size 242.93)	-	8.42	-	-	8.42	5.30	13.72	24.00	-10.28
6145 (RU Size 484 + RU Size 242.92)	-	10.87	-	-	10.87	3.00	13.87	24.00	-10.13
6385 (RU Size 484 + RU Size 242.90)	-	9.14	-	-	9.14	4.60	13.74	24.00	-10.26
6465 (RU Size 484 + RU Size 242.93)	-	8.62	-	-	8.62	5.00	13.62	24.00	-10.38
6545 (RU Size 484 + RU Size 242.90)	-	8.46	-	-	8.46	5.20	13.66	24.00	-10.34
6545 (RU Size 484 + RU Size 242.93)	-	8.52	-	-	8.52	5.20	13.72	24.00	-10.28
6625 (RU Size 484 + RU Size 242.93)	-	8.13	-	-	8.13	5.20	13.33	24.00	-10.67
6705 (RU Size 484 + RU Size 242.91)	-	8.07	-	-	8.07	5.20	13.27	24.00	-10.73
6785 (RU Size 484 + RU Size 242.90)	-	8.23	-	-	8.23	5.20	13.43	24.00	-10.57
6865 (RU Size 484 + RU Size 242.90)	-	8.24	-	-	8.24	5.20	13.44	24.00	-10.56
6865 (RU Size 484 + RU Size 242.93)	-	8.50	-	-	8.50	5.20	13.70	24.00	-10.30
6945 (RU Size 484 + RU Size 242.93)	-	9.55	-	-	9.55	4.40	13.95	24.00	-10.05
7025 (RU Size 484 + RU Size 242.90)	-	9.01	-	-	9.01	4.40	13.41	24.00	-10.59

Table 364 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 LPI (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	-	13.66	-	-	13.66	3.00	16.66	24.00	-7.34
6345 (RU Size 996 + RU Size 484.94)	-	11.85	-	-	11.85	4.60	16.45	24.00	-7.55
6505 (RU Size 996 + RU Size 484.94)	-	11.48	-	-	11.48	5.00	16.48	24.00	-7.52
6665 (RU Size 996 + RU Size 484.94)	-	11.39	-	-	11.39	5.20	16.59	24.00	-7.41
6825 (RU Size 996 + RU Size 484.94)	-	11.18	-	-	11.18	5.20	16.38	24.00	-7.62
6985 (RU Size 996 + RU Size 484.94)	-	12.09	-	-	12.09	4.40	16.49	24.00	-7.51

Table 365 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 LPI (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484.95)	-	10.73	-	-	10.73	5.30	16.03	24.00	-7.97
6185 (RU Size 996 + RU Size 484.94)	-	13.71	-	-	13.71	3.00	16.71	24.00	-7.29
6505 (RU Size 996 + RU Size 484.95)	-	11.47	-	-	11.47	5.00	16.47	24.00	-7.53
6665 (RU Size 996 + RU Size 484.95)	-	11.48	-	-	11.48	5.20	16.68	24.00	-7.32
6825 (RU Size 996 + RU Size 484.95)	-	11.34	-	-	11.34	5.20	16.54	24.00	-7.46
6985 (RU Size 996 + RU Size 484.95)	-	11.63	-	-	11.63	4.40	16.03	24.00	-7.97

Table 366 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 LPI (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	-	14.30	-	-	14.30	3.00	17.30	24.00	-6.70
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	-	14.01	-	-	14.01	3.00	17.01	24.00	-6.99
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	14.07	-	-	14.07	3.00	17.07	24.00	-6.93
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	12.44	-	-	12.44	4.60	17.04	24.00	-6.96
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	12.06	-	-	12.06	5.00	17.06	24.00	-6.94
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	12.19	-	-	12.19	5.20	17.39	24.00	-6.61
6825 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	11.96	-	-	11.96	5.20	17.16	24.00	-6.84
6985 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	12.71	-	-	12.71	4.40	17.11	24.00	-6.89

Table 367 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 LPI (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	11.63	-	-	11.63	5.30	16.93	24.00	-7.07
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	12.01	-	-	12.01	5.00	17.01	24.00	-6.99
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	11.88	-	-	11.88	5.20	17.08	24.00	-6.92
6825 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	12.10	-	-	12.10	5.20	17.30	24.00	-6.70
6985 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	12.83	-	-	12.83	4.40	17.23	24.00	-6.77

Table 368 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a20 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	-	19.39	-	-	19.39	5.30	24.69	30.00	-5.31
6175	-	19.10	-	-	19.10	3.00	22.10	30.00	-7.90
6415	-	19.32	-	-	19.32	4.60	23.92	30.00	-6.08
6535	-	19.27	-	-	19.27	5.20	24.47	30.00	-5.53
6695	-	19.22	-	-	19.22	5.20	24.42	30.00	-5.58
6855	-	19.10	-	-	19.10	5.20	24.30	30.00	-5.70

Table 369 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a40 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	-	19.29	-	-	19.29	5.30	24.59	30.00	-5.41
6165	-	19.45	-	-	19.45	3.00	22.45	30.00	-7.55
6405	-	19.19	-	-	19.19	4.60	23.79	30.00	-6.21
6565	-	19.30	-	-	19.30	5.20	24.50	30.00	-5.50
6685	-	19.16	-	-	19.16	5.20	24.36	30.00	-5.64
6845	-	19.47	-	-	19.47	5.20	24.67	30.00	-5.33

Table 370 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	-	19.18	-	-	19.18	5.30	24.48	30.00	-5.52
6145	-	19.03	-	-	19.03	3.00	22.03	30.00	-7.97
6385	-	19.05	-	-	19.05	4.60	23.65	30.00	-6.35
6625	-	19.37	-	-	19.37	5.20	24.57	30.00	-5.43
6705	-	19.08	-	-	19.08	5.20	24.28	30.00	-5.72
6785	-	19.04	-	-	19.04	5.20	24.24	30.00	-5.76

Table 371 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	-	19.26	-	-	19.26	5.30	24.56	30.00	-5.44
6185	-	19.20	-	-	19.20	3.00	22.20	30.00	-7.80
6345	-	19.21	-	-	19.21	4.60	23.81	30.00	-6.19
6665	-	19.03	-	-	19.03	5.20	24.23	30.00	-5.77

Table 372 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	-	19.18	-	-	19.18	5.30	24.48	30.00	-5.52
6175	-	19.21	-	-	19.21	3.00	22.21	30.00	-7.79
6415	-	19.41	-	-	19.41	4.60	24.01	30.00	-5.99
6535	-	19.28	-	-	19.28	5.20	24.48	30.00	-5.52
6695	-	19.29	-	-	19.29	5.20	24.49	30.00	-5.51
6855	-	19.03	-	-	19.03	5.20	24.23	30.00	-5.77

Table 373 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	-	19.34	-	-	19.34	5.30	24.64	30.00	-5.36
6165	-	19.36	-	-	19.36	3.00	22.36	30.00	-7.64
6405	-	19.34	-	-	19.34	4.60	23.94	30.00	-6.06
6565	-	19.19	-	-	19.19	5.20	24.39	30.00	-5.61
6685	-	19.22	-	-	19.22	5.20	24.42	30.00	-5.58
6845	-	19.11	-	-	19.11	5.20	24.31	30.00	-5.69

Table 374 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	-	19.32	-	-	19.32	5.30	24.62	30.00	-5.38
6145	-	19.12	-	-	19.12	3.00	22.12	30.00	-7.88
6385	-	19.17	-	-	19.17	4.60	23.77	30.00	-6.23
6625	-	19.48	-	-	19.48	5.20	24.68	30.00	-5.32
6705	-	19.17	-	-	19.17	5.20	24.37	30.00	-5.63
6785	-	19.09	-	-	19.09	5.20	24.29	30.00	-5.71

Table 375 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	-	19.33	-	-	19.33	5.30	24.63	30.00	-5.37
6185	-	19.33	-	-	19.33	3.00	22.33	30.00	-7.67
6345	-	19.35	-	-	19.35	4.60	23.95	30.00	-6.05
6665	-	19.24	-	-	19.24	5.20	24.44	30.00	-5.56

Table 376 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU26 SP	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU26.0)	-	10.08	-	-	10.08	5.30	15.38	30.00	-14.62
6175 (RU26.0)	-	10.18	-	-	10.18	3.00	13.18	30.00	-16.82
6415 (RU26.8)	-	10.05	-	-	10.05	4.60	14.65	30.00	-15.35
6535 (RU26.0)	-	10.12	-	-	10.12	5.20	15.32	30.00	-14.68
6695 (RU26.0)	-	10.10	-	-	10.10	5.20	15.30	30.00	-14.70
6855 (RU26.8)	-	10.08	-	-	10.08	5.20	15.28	30.00	-14.72

Table 377 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU52 SP	Duty Cycle (%):	98.8
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU52.37)	-	13.29	-	-	13.29	5.30	18.59	30.00	-11.41
6175 (RU52.37)	-	13.20	-	-	13.20	3.00	16.20	30.00	-13.80
6415 (RU52.40)	-	13.18	-	-	13.18	4.60	17.78	30.00	-12.22
6535 (RU52.37)	-	13.23	-	-	13.23	5.20	18.43	30.00	-11.57
6695 (RU52.37)	-	13.26	-	-	13.26	5.20	18.46	30.00	-11.54
6855 (RU52.40)	-	13.06	-	-	13.06	5.20	18.26	30.00	-11.74

Table 378 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU106 SP	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU106.53)	-	16.22	-	-	16.22	5.30	21.52	30.00	-8.48
6175 (RU106.53)	-	16.09	-	-	16.09	3.00	19.09	30.00	-10.91
6415 (RU106.54)	-	16.41	-	-	16.41	4.60	21.01	30.00	-8.99
6535 (RU106.53)	-	16.41	-	-	16.41	5.20	21.61	30.00	-8.39
6695 (RU106.53)	-	16.39	-	-	16.39	5.20	21.59	30.00	-8.41
6855 (RU106.54)	-	16.15	-	-	16.15	5.20	21.35	30.00	-8.65

Table 379 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 52 + RU Size 26 SP	Duty Cycle (%):	97.4
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU Size 52 + RU Size 26.70)	-	14.97	-	-	14.97	5.30	20.27	30.00	-9.73
6175 (RU Size 52 + RU Size 26.70)	-	14.83	-	-	14.83	3.00	17.83	30.00	-12.17
6415 (RU Size 52 + RU Size 26.72)	-	14.88	-	-	14.88	4.60	19.48	30.00	-10.52
6535 (RU Size 52 + RU Size 26.70)	-	14.67	-	-	14.67	5.20	19.87	30.00	-10.13
6695 (RU Size 52 + RU Size 26.70)	-	14.54	-	-	14.54	5.20	19.74	30.00	-10.26
6855 (RU Size 52 + RU Size 26.72)	-	14.91	-	-	14.91	5.20	20.11	30.00	-9.89

Table 380 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 106 + RU Size 26 SP	Duty Cycle (%):	97.3
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU Size 106 + RU Size 26.82)	-	16.85	-	-	16.85	5.30	22.15	30.00	-7.85
6175 (RU Size 106 + RU Size 26.82)	-	16.68	-	-	16.68	3.00	19.68	30.00	-10.32
6415 (RU Size 106 + RU Size 26.83)	-	16.98	-	-	16.98	4.60	21.58	30.00	-8.42
6535 (RU Size 106 + RU Size 26.82)	-	16.75	-	-	16.75	5.20	21.95	30.00	-8.05
6695 (RU Size 106 + RU Size 26.82)	-	16.90	-	-	16.90	5.20	22.10	30.00	-7.90
6855 (RU Size 106 + RU Size 26.83)	-	16.85	-	-	16.85	5.20	22.05	30.00	-7.95

Table 381 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 SP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985 (RU Size 484 + RU Size 242.93)	-	17.92	-	-	17.92	5.30	23.22	30.00	-6.78
6145 (RU Size 484 + RU Size 242.92)	-	17.65	-	-	17.65	3.00	20.65	30.00	-9.35
6385 (RU Size 484 + RU Size 242.90)	-	17.76	-	-	17.76	4.60	22.36	30.00	-7.64
6625 (RU Size 484 + RU Size 242.93)	-	17.77	-	-	17.77	5.20	22.97	30.00	-7.03
6705 (RU Size 484 + RU Size 242.91)	-	17.62	-	-	17.62	5.20	22.82	30.00	-7.18
6785 (RU Size 484 + RU Size 242.90)	-	17.84	-	-	17.84	5.20	23.04	30.00	-6.96

Table 382 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	-	17.87	-	-	17.87	3.00	20.87	30.00	-9.13
6345 (RU Size 996 + RU Size 484.94)	-	17.75	-	-	17.75	4.60	22.35	30.00	-7.65
6665 (RU Size 996 + RU Size 484.94)	-	17.72	-	-	17.72	5.20	22.92	30.00	-7.08

Table 383 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484.95)	-	17.76	-	-	17.76	5.30	23.06	30.00	-6.94
6185 (RU Size 996 + RU Size 484.94)	-	18.00	-	-	18.00	3.00	21.00	30.00	-9.00
6665 (RU Size 996 + RU Size 484.95)	-	17.81	-	-	17.81	5.20	23.01	30.00	-6.99

Table 384 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	-	19.30	-	-	19.30	3.00	22.30	30.00	-7.70
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	-	19.41	-	-	19.41	3.00	22.41	30.00	-7.59
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	19.44	-	-	19.44	3.00	22.44	30.00	-7.56
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	19.25	-	-	19.25	4.60	23.85	30.00	-6.15
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	19.28	-	-	19.28	5.20	24.48	30.00	-5.52

Table 385 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.30
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	19.19	-	-	19.19	5.30	24.49	30.00	-5.51
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	19.36	-	-	19.36	5.20	24.56	30.00	-5.44

Table 386 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a20 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435	-	19.40	-	-	19.40	5.00	24.40	30.00	-5.60
6475	-	19.12	-	-	19.12	5.00	24.12	30.00	-5.88
6515	-	19.10	-	-	19.10	5.00	24.10	30.00	-5.90

Table 387 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a40 SP	Duty Cycle (%):	97.5
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6445	-	19.33	-	-	19.33	5.00	24.33	30.00	-5.67
6485	-	19.20	-	-	19.20	5.00	24.20	30.00	-5.80
6525	-	19.30	-	-	19.30	5.00	24.30	30.00	-5.70

Table 388 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465	-	19.26	-	-	19.26	5.00	24.26	30.00	-5.74
6545	-	19.23	-	-	19.23	5.20	24.43	30.00	-5.57

Table 389 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505	-	19.33	-	-	19.33	5.00	24.33	30.00	-5.67

Table 390 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435	-	19.41	-	-	19.41	5.00	24.41	30.00	-5.59
6475	-	19.11	-	-	19.11	5.00	24.11	30.00	-5.89
6515	-	19.07	-	-	19.07	5.00	24.07	30.00	-5.93

Table 391 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6445	-	19.18	-	-	19.18	5.00	24.18	30.00	-5.82
6485	-	19.39	-	-	19.39	5.00	24.39	30.00	-5.61
6525	-	19.21	-	-	19.21	5.00	24.21	30.00	-5.79

Table 392 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465	-	19.27	-	-	19.27	5.00	24.27	30.00	-5.73
6545	-	19.25	-	-	19.25	5.20	24.45	30.00	-5.55

Table 393 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505	-	19.25	-	-	19.25	5.00	24.25	30.00	-5.75

Table 394 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU26 SP	Duty Cycle (%):	98.8
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435 (RU26.0)	-	10.19	-	-	10.19	5.00	15.19	30.00	-14.81
6475 (RU26.0)	-	10.08	-	-	10.08	5.00	15.08	30.00	-14.92
6515 (RU26.8)	-	10.17	-	-	10.17	5.00	15.17	30.00	-14.83

Table 395 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU52 SP	Duty Cycle (%):	98.8
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435 (RU52.37)	-	13.19	-	-	13.19	5.00	18.19	30.00	-11.81
6475 (RU52.37)	-	13.26	-	-	13.26	5.00	18.26	30.00	-11.74
6515 (RU52.40)	-	13.24	-	-	13.24	5.00	18.24	30.00	-11.76

Table 396 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU106 SP	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435 (RU106.53)	-	16.34	-	-	16.34	5.00	21.34	30.00	-8.66
6475 (RU106.53)	-	16.39	-	-	16.39	5.00	21.39	30.00	-8.61
6515 (RU106.54)	-	16.29	-	-	16.29	5.00	21.29	30.00	-8.71

Table 397 - ISSED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 52 + RU Size 26 SP	Duty Cycle (%):	97.5
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435 (RU Size 52 + RU Size 26.70)	-	14.98	-	-	14.98	5.00	19.98	30.00	-10.02
6475 (RU Size 52 + RU Size 26.70)	-	14.90	-	-	14.90	5.00	19.90	30.00	-10.10
6515 (RU Size 52 + RU Size 26.72)	-	14.99	-	-	14.99	5.00	19.99	30.00	-10.01

Table 398 - ISSED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 106 + RU Size 26 SP	Duty Cycle (%):	97.5
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435 (RU Size 106 + RU Size 26.82)	-	16.84	-	-	16.84	5.00	21.84	30.00	-8.16
6475 (RU Size 106 + RU Size 26.82)	-	16.74	-	-	16.74	5.00	21.74	30.00	-8.26
6515 (RU Size 106 + RU Size 26.83)	-	16.89	-	-	16.89	5.00	21.89	30.00	-8.11

Table 399 - ISSED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 SP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465 (RU Size 484 + RU Size 242.93)	-	17.84	-	-	17.84	5.00	22.84	30.00	-7.16
6545 (RU Size 484 + RU Size 242.90)	-	17.85	-	-	17.85	5.20	23.05	30.00	-6.95
6545 (RU Size 484 + RU Size 242.93)	-	17.71	-	-	17.71	5.20	22.91	30.00	-7.09

Table 400 - ISSED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484.94)	-	17.77	-	-	17.77	5.00	22.77	30.00	-7.23

Table 401 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484.95)	-	17.55	-	-	17.55	5.00	22.55	30.00	-7.45

Table 402 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	19.32	-	-	19.32	5.00	24.32	30.00	-5.68

Table 403 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.00
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	19.33	-	-	19.33	5.00	24.33	30.00	-5.67

Table 404 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a20 VLP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115	-	2.00	-	-	2.00	3.00	5.00	14.00	-9.00
6255	-	1.58	-	-	1.58	3.00	4.58	14.00	-9.42
6415	-	-0.04	-	-	-0.04	4.60	4.56	14.00	-9.44
6435	-	-0.32	-	-	-0.32	5.00	4.68	14.00	-9.32
6475	-	-0.18	-	-	-0.18	5.00	4.82	14.00	-9.18
6515	-	-0.40	-	-	-0.40	5.00	4.60	14.00	-9.40
6535	-	-0.51	-	-	-0.51	5.20	4.69	14.00	-9.31
6695	-	-0.23	-	-	-0.23	5.20	4.97	14.00	-9.03
6855	-	-0.20	-	-	-0.20	5.20	5.00	14.00	-9.00
6875	-	-0.21	-	-	-0.21	5.20	4.99	14.00	-9.01
6895	-	0.41	-	-	0.41	4.40	4.81	14.00	-9.19
6995	-	-0.00	-	-	-0.00	4.40	4.40	14.00	-9.60
7095	-	0.68	-	-	0.68	4.40	5.08	14.00	-8.92
7115	-	0.10	-	-	0.10	4.40	4.50	14.00	-9.50

Table 405 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a40 VLP	Duty Cycle (%):	97.3
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	-	5.12	-	-	5.12	3.00	8.12	14.00	-5.88
6245	-	5.04	-	-	5.04	3.00	8.04	14.00	-5.96
6405	-	3.09	-	-	3.09	4.60	7.69	14.00	-6.31
6445	-	3.08	-	-	3.08	5.00	8.08	14.00	-5.92
6485	-	2.51	-	-	2.51	5.00	7.51	14.00	-6.49
6525	-	2.79	-	-	2.79	5.00	7.79	14.00	-6.21
6565	-	2.83	-	-	2.83	5.20	8.03	14.00	-5.97
6725	-	2.72	-	-	2.72	5.20	7.92	14.00	-6.08
6845	-	2.85	-	-	2.85	5.20	8.05	14.00	-5.95
6885	-	2.93	-	-	2.93	5.20	8.13	14.00	-5.87
6925	-	3.66	-	-	3.66	4.40	8.06	14.00	-5.94
7005	-	3.67	-	-	3.67	4.40	8.07	14.00	-5.93
7085	-	3.61	-	-	3.61	4.40	8.01	14.00	-5.99

Table 406 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a80 VLP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	-	7.82	-	-	7.82	3.00	10.82	14.00	-3.18
6225	-	7.89	-	-	7.89	3.00	10.89	14.00	-3.11
6385	-	6.23	-	-	6.23	4.60	10.83	14.00	-3.17
6465	-	6.34	-	-	6.34	5.00	11.34	14.00	-2.66
6545	-	6.19	-	-	6.19	5.20	11.39	14.00	-2.61
6625	-	5.85	-	-	5.85	5.20	11.05	14.00	-2.95
6705	-	5.94	-	-	5.94	5.20	11.14	14.00	-2.86
6785	-	5.85	-	-	5.85	5.20	11.05	14.00	-2.95
6865	-	5.75	-	-	5.75	5.20	10.95	14.00	-3.05
6945	-	6.65	-	-	6.65	4.40	11.05	14.00	-2.95
7025	-	6.40	-	-	6.40	4.40	10.80	14.00	-3.20

Table 407 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11a160 VLP	Duty Cycle (%):	97.4
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	-	9.74	-	-	9.74	3.00	12.74	14.00	-1.26
6345	-	8.12	-	-	8.12	4.60	12.72	14.00	-1.28
6505	-	7.54	-	-	7.54	5.00	12.54	14.00	-1.46
6665	-	7.30	-	-	7.30	5.20	12.50	14.00	-1.50
6825	-	7.63	-	-	7.63	5.20	12.83	14.00	-1.17
6985	-	8.25	-	-	8.25	4.40	12.65	14.00	-1.35

Table 408 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115	-	2.24	-	-	2.24	3.00	5.24	14.00	-8.76
6255	-	1.85	-	-	1.85	3.00	4.85	14.00	-9.15
6415	-	0.19	-	-	0.19	4.60	4.79	14.00	-9.21
6435	-	-0.12	-	-	-0.12	5.00	4.88	14.00	-9.12
6475	-	-0.02	-	-	-0.02	5.00	4.98	14.00	-9.02
6515	-	-0.20	-	-	-0.20	5.00	4.80	14.00	-9.20
6535	-	-0.57	-	-	-0.57	5.20	4.63	14.00	-9.37
6695	-	-0.29	-	-	-0.29	5.20	4.91	14.00	-9.09
6855	-	-0.18	-	-	-0.18	5.20	5.02	14.00	-8.98
6875	-	-0.03	-	-	-0.03	5.20	5.17	14.00	-8.83
6895	-	0.79	-	-	0.79	4.40	5.19	14.00	-8.81
6995	-	0.63	-	-	0.63	4.40	5.03	14.00	-8.97
7095	-	0.65	-	-	0.65	4.40	5.05	14.00	-8.95

Table 409 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE40 SU VLP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	-	5.20	-	-	5.20	3.00	8.20	14.00	-5.80
6245	-	5.01	-	-	5.01	3.00	8.01	14.00	-5.99
6405	-	3.09	-	-	3.09	4.60	7.69	14.00	-6.31
6445	-	3.09	-	-	3.09	5.00	8.09	14.00	-5.91
6485	-	2.63	-	-	2.63	5.00	7.63	14.00	-6.37
6525	-	2.87	-	-	2.87	5.00	7.87	14.00	-6.13
6565	-	2.46	-	-	2.46	5.20	7.66	14.00	-6.34
6725	-	2.79	-	-	2.79	5.20	7.99	14.00	-6.01
6845	-	2.87	-	-	2.87	5.20	8.07	14.00	-5.93
6885	-	2.96	-	-	2.96	5.20	8.16	14.00	-5.84
6925	-	3.53	-	-	3.53	4.40	7.93	14.00	-6.07
7005	-	3.67	-	-	3.67	4.40	8.07	14.00	-5.93
7085	-	3.63	-	-	3.63	4.40	8.03	14.00	-5.97

Table 410 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE80 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	-	7.83	-	-	7.83	3.00	10.83	14.00	-3.17
6225	-	8.07	-	-	8.07	3.00	11.07	14.00	-2.93
6385	-	6.48	-	-	6.48	4.60	11.08	14.00	-2.92
6465	-	6.40	-	-	6.40	5.00	11.40	14.00	-2.60
6545	-	6.16	-	-	6.16	5.20	11.36	14.00	-2.64
6625	-	5.86	-	-	5.86	5.20	11.06	14.00	-2.94
6705	-	5.94	-	-	5.94	5.20	11.14	14.00	-2.86
6785	-	5.85	-	-	5.85	5.20	11.05	14.00	-2.95
6865	-	5.81	-	-	5.81	5.20	11.01	14.00	-2.99
6945	-	6.74	-	-	6.74	4.40	11.14	14.00	-2.86
7025	-	6.39	-	-	6.39	4.40	10.79	14.00	-3.21

Table 411 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE160 SU VLP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	-	9.79	-	-	9.79	3.00	12.79	14.00	-1.21
6345	-	8.09	-	-	8.09	4.60	12.69	14.00	-1.31
6505	-	7.51	-	-	7.51	5.00	12.51	14.00	-1.49
6665	-	7.45	-	-	7.45	5.20	12.65	14.00	-1.35
6825	-	7.26	-	-	7.26	5.20	12.46	14.00	-1.54
6985	-	8.14	-	-	8.14	4.40	12.54	14.00	-1.46

Table 412 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU26 VLP	Duty Cycle (%):	45.6
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU26.0)	-	-7.17	-	-	-7.17	3.00	-4.17	14.00	-18.17
6255 (RU26.0)	-	-7.35	-	-	-7.35	3.00	-4.35	14.00	-18.35
6415 (RU26.8)	-	-8.77	-	-	-8.77	4.60	-4.17	14.00	-18.17
6435 (RU26.0)	-	-9.09	-	-	-9.09	5.00	-4.09	14.00	-18.09
6475 (RU26.0)	-	-9.01	-	-	-9.01	5.00	-4.01	14.00	-18.01
6515 (RU26.8)	-	-9.39	-	-	-9.39	5.00	-4.39	14.00	-18.39
6875 (RU26.3)	-	-9.21	-	-	-9.21	5.20	-4.01	14.00	-18.01
6875 (RU26.5)	-	-9.40	-	-	-9.40	5.20	-4.20	14.00	-18.20
6895 (RU26.0)	-	-8.51	-	-	-8.51	4.40	-4.11	14.00	-18.11
6995 (RU26.0)	-	-8.58	-	-	-8.58	4.40	-4.18	14.00	-18.18
7095 (RU26.8)	-	-8.21	-	-	-8.21	4.40	-3.81	14.00	-17.81

Table 413 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU52 VLP	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU52.37)	-	-4.50	-	-	-4.50	3.00	-1.50	14.00	-15.50
6255 (RU52.37)	-	-4.59	-	-	-4.59	3.00	-1.59	14.00	-15.59
6415 (RU52.40)	-	-6.23	-	-	-6.23	4.60	-1.63	14.00	-15.63
6435 (RU52.37)	-	-6.35	-	-	-6.35	5.00	-1.35	14.00	-15.35
6475 (RU52.37)	-	-6.41	-	-	-6.41	5.00	-1.41	14.00	-15.41
6515 (RU52.40)	-	-6.58	-	-	-6.58	5.00	-1.58	14.00	-15.58
6535 (RU52.37)	-	-6.80	-	-	-6.80	5.20	-1.60	14.00	-15.60
6695 (RU52.37)	-	-6.80	-	-	-6.80	5.20	-1.60	14.00	-15.60
6855 (RU52.40)	-	-6.47	-	-	-6.47	5.20	-1.27	14.00	-15.27
6875 (RU52.38)	-	-6.41	-	-	-6.41	5.20	-1.21	14.00	-15.21
6875 (RU52.39)	-	-6.39	-	-	-6.39	5.20	-1.19	14.00	-15.19
6895 (RU52.37)	-	-6.00	-	-	-6.00	4.40	-1.60	14.00	-15.60
6995 (RU52.37)	-	-5.67	-	-	-5.67	4.40	-1.27	14.00	-15.27
7095 (RU52.40)	-	-5.58	-	-	-5.58	4.40	-1.18	14.00	-15.18

Table 414 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU106 VLP	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU106.53)	-	-1.36	-	-	-1.36	3.00	1.64	14.00	-12.36
6255 (RU106.53)	-	-1.45	-	-	-1.45	3.00	1.55	14.00	-12.45
6415 (RU106.54)	-	-3.09	-	-	-3.09	4.60	1.51	14.00	-12.49
6435 (RU106.53)	-	-3.52	-	-	-3.52	5.00	1.48	14.00	-12.52
6475 (RU106.53)	-	-3.34	-	-	-3.34	5.00	1.66	14.00	-12.34
6515 (RU106.54)	-	-3.50	-	-	-3.50	5.00	1.50	14.00	-12.50
6535 (RU106.53)	-	-3.71	-	-	-3.71	5.20	1.49	14.00	-12.51
6695 (RU106.53)	-	-3.78	-	-	-3.78	5.20	1.42	14.00	-12.58
6855 (RU106.54)	-	-3.44	-	-	-3.44	5.20	1.76	14.00	-12.24
6875 (RU106.53)	-	-3.16	-	-	-3.16	5.20	2.04	14.00	-11.96
6875 (RU106.54)	-	-3.19	-	-	-3.19	5.20	2.01	14.00	-11.99
6895 (RU106.53)	-	-2.67	-	-	-2.67	4.40	1.73	14.00	-12.27
6995 (RU106.53)	-	-2.84	-	-	-2.84	4.40	1.56	14.00	-12.44
7095 (RU106.54)	-	-2.98	-	-	-2.98	4.40	1.42	14.00	-12.58

Table 415 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 52 + RU Size 26 VLP	Duty Cycle (%):	97.4
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU Size 52 + RU Size 26.70)	-	-2.41	-	-	-2.41	3.00	0.59	14.00	-13.41
6255 (RU Size 52 + RU Size 26.70)	-	-2.51	-	-	-2.51	3.00	0.49	14.00	-13.51
6415 (RU Size 52 + RU Size 26.72)	-	-4.48	-	-	-4.48	4.60	0.12	14.00	-13.88
6435 (RU Size 52 + RU Size 26.70)	-	-4.64	-	-	-4.64	5.00	0.36	14.00	-13.64
6475 (RU Size 52 + RU Size 26.70)	-	-4.44	-	-	-4.44	5.00	0.56	14.00	-13.44
6515 (RU Size 52 + RU Size 26.72)	-	-4.63	-	-	-4.63	5.00	0.37	14.00	-13.63
6535 (RU Size 52 + RU Size 26.70)	-	-5.30	-	-	-5.30	5.20	-0.10	14.00	-14.10
6695 (RU Size 52 + RU Size 26.70)	-	-5.04	-	-	-5.04	5.20	0.16	14.00	-13.84
6855 (RU Size 52 + RU Size 26.72)	-	-4.91	-	-	-4.91	5.20	0.29	14.00	-13.71
6875 (RU Size 52 + RU Size 26.70)	-	-4.59	-	-	-4.59	5.20	0.61	14.00	-13.39
6875 (RU Size 52 + RU Size 26.72)	-	-4.40	-	-	-4.40	5.20	0.80	14.00	-13.20
6895 (RU Size 52 + RU Size 26.70)	-	-4.10	-	-	-4.10	4.40	0.30	14.00	-13.70
6995 (RU Size 52 + RU Size 26.70)	-	-4.03	-	-	-4.03	4.40	0.37	14.00	-13.63
7095 (RU Size 52 + RU Size 26.72)	-	-3.55	-	-	-3.55	4.40	0.85	14.00	-13.15

Table 416 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 106 + RU Size 26 VLP	Duty Cycle (%):	97.3
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU Size 106 + RU Size 26.82)	-	-0.52	-	-	-0.52	3.00	2.48	14.00	-11.52
6255 (RU Size 106 + RU Size 26.82)	-	-0.68	-	-	-0.68	3.00	2.32	14.00	-11.68
6415 (RU Size 106 + RU Size 26.83)	-	-2.01	-	-	-2.01	4.60	2.59	14.00	-11.41
6435 (RU Size 106 + RU Size 26.82)	-	-2.42	-	-	-2.42	5.00	2.58	14.00	-11.42
6475 (RU Size 106 + RU Size 26.82)	-	-2.47	-	-	-2.47	5.00	2.53	14.00	-11.47
6515 (RU Size 106 + RU Size 26.83)	-	-2.40	-	-	-2.40	5.00	2.60	14.00	-11.40
6535 (RU Size 106 + RU Size 26.82)	-	-2.87	-	-	-2.87	5.20	2.33	14.00	-11.67
6695 (RU Size 106 + RU Size 26.82)	-	-2.76	-	-	-2.76	5.20	2.44	14.00	-11.56
6855 (RU Size 106 + RU Size 26.83)	-	-2.55	-	-	-2.55	5.20	2.65	14.00	-11.35
6875 (RU Size 106 + RU Size 26.82)	-	-2.54	-	-	-2.54	5.20	2.66	14.00	-11.34
6875 (RU Size 106 + RU Size 26.83)	-	-2.56	-	-	-2.56	5.20	2.64	14.00	-11.36
6895 (RU Size 106 + RU Size 26.82)	-	-1.98	-	-	-1.98	4.40	2.42	14.00	-11.58
6995 (RU Size 106 + RU Size 26.82)	-	-2.00	-	-	-2.00	4.40	2.40	14.00	-11.60
7095 (RU Size 106 + RU Size 26.83)	-	-1.60	-	-	-1.60	4.40	2.80	14.00	-11.20

Table 417 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 VLP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145 (RU Size 484 + RU Size 242.93)	-	6.76	-	-	6.76	3.00	9.76	14.00	-4.24
6225 (RU Size 484 + RU Size 242.92)	-	6.63	-	-	6.63	3.00	9.63	14.00	-4.37
6385 (RU Size 484 + RU Size 242.90)	-	5.08	-	-	5.08	4.60	9.68	14.00	-4.32
6465 (RU Size 484 + RU Size 242.93)	-	4.84	-	-	4.84	5.00	9.84	14.00	-4.16
6545 (RU Size 484 + RU Size 242.90)	-	4.29	-	-	4.29	5.20	9.49	14.00	-4.51
6545 (RU Size 484 + RU Size 242.93)	-	4.38	-	-	4.38	5.20	9.58	14.00	-4.42
6625 (RU Size 484 + RU Size 242.93)	-	4.34	-	-	4.34	5.20	9.54	14.00	-4.46
6705 (RU Size 484 + RU Size 242.91)	-	4.34	-	-	4.34	5.20	9.54	14.00	-4.46
6785 (RU Size 484 + RU Size 242.90)	-	4.26	-	-	4.26	5.20	9.46	14.00	-4.54
6865 (RU Size 484 + RU Size 242.90)	-	4.42	-	-	4.42	5.20	9.62	14.00	-4.38
6865 (RU Size 484 + RU Size 242.93)	-	4.27	-	-	4.27	5.20	9.47	14.00	-4.53
6945 (RU Size 484 + RU Size 242.93)	-	5.42	-	-	5.42	4.40	9.82	14.00	-4.18
7025 (RU Size 484 + RU Size 242.90)	-	4.84	-	-	4.84	4.40	9.24	14.00	-4.76

Table 418 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 VLP (Primary)	Duty Cycle (%):	97.3
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	-	9.57	-	-	9.57	3.00	12.57	14.00	-1.43
6345 (RU Size 996 + RU Size 484.94)	-	7.72	-	-	7.72	4.60	12.32	14.00	-1.68
6505 (RU Size 996 + RU Size 484.94)	-	7.44	-	-	7.44	5.00	12.44	14.00	-1.56
6665 (RU Size 996 + RU Size 484.94)	-	7.57	-	-	7.57	5.20	12.77	14.00	-1.23
6825 (RU Size 996 + RU Size 484.94)	-	7.18	-	-	7.18	5.20	12.38	14.00	-1.62
6985 (RU Size 996 + RU Size 484.94)	-	7.98	-	-	7.98	4.40	12.38	14.00	-1.62

Table 419 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 VLP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.94)	-	9.69	-	-	9.69	3.00	12.69	14.00	-1.31
6505 (RU Size 996 + RU Size 484.95)	-	7.54	-	-	7.54	5.00	12.54	14.00	-1.46
6665 (RU Size 996 + RU Size 484.95)	-	7.42	-	-	7.42	5.20	12.62	14.00	-1.38
6825 (RU Size 996 + RU Size 484.95)	-	7.31	-	-	7.31	5.20	12.51	14.00	-1.49
6985 (RU Size 996 + RU Size 484.95)	-	7.90	-	-	7.90	4.40	12.30	14.00	-1.70

Table 420 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 VLP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	-	9.99	-	-	9.99	3.00	12.99	14.00	-1.01
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	-	9.86	-	-	9.86	3.00	12.86	14.00	-1.14
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	9.87	-	-	9.87	3.00	12.87	14.00	-1.13
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	8.06	-	-	8.06	4.60	12.66	14.00	-1.34
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	7.70	-	-	7.70	5.00	12.70	14.00	-1.30
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	7.60	-	-	7.60	5.20	12.80	14.00	-1.20
6825 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	7.41	-	-	7.41	5.20	12.61	14.00	-1.39
6985 (RU Size 996 + RU Size 484 + RU Size 242.96)	-	8.28	-	-	8.28	4.40	12.68	14.00	-1.32

Table 421 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 VLP (Secondary)	Duty Cycle (%):	97.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	5.20
Active Port(s):	B (Core 1)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	7.56	-	-	7.56	5.00	12.56	14.00	-1.44
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	7.63	-	-	7.63	5.20	12.83	14.00	-1.17
6825 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	7.43	-	-	7.43	5.20	12.63	14.00	-1.37
6985 (RU Size 996 + RU Size 484 + RU Size 242.99)	-	8.31	-	-	8.31	4.40	12.71	14.00	-1.29

Table 422 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a20 LPI	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	-1.85	-2.14	-	-	1.02	5.30	6.32	24.00	-17.68
6175	-0.82	-1.22	-	-	1.99	4.20	6.19	24.00	-17.81
6415	-2.32	-2.15	-	-	0.77	4.60	5.37	24.00	-18.63
6435	-2.78	-2.20	-	-	0.53	5.00	5.53	24.00	-18.47
6475	-2.94	-2.04	-	-	0.54	5.00	5.54	24.00	-18.46
6515	-3.31	-2.28	-	-	0.24	5.00	5.24	24.00	-18.76
6535	-3.14	-2.00	-	-	0.48	5.20	5.68	24.00	-18.32
6695	-3.89	-2.07	-	-	0.12	5.20	5.32	24.00	-18.68
6855	-3.33	-1.89	-	-	0.46	5.20	5.66	24.00	-18.34
6875	-2.91	-1.59	-	-	0.81	5.20	6.01	24.00	-17.99
6895	-2.46	-1.26	-	-	1.19	4.40	5.59	24.00	-18.41
6995	-1.87	-1.14	-	-	1.52	4.40	5.92	24.00	-18.08
7095	-1.35	-1.07	-	-	1.80	4.40	6.20	24.00	-17.80
7115	-1.81	-1.53	-	-	1.34	4.40	5.74	24.00	-18.26

Table 423 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a40 LPI	Duty Cycle (%):	96.9
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	0.96	1.25	-	-	4.12	5.30	9.42	24.00	-14.58
6165	2.28	2.46	-	-	5.38	4.20	9.58	24.00	-14.42
6405	0.44	1.04	-	-	3.76	4.60	8.36	24.00	-15.64
6445	-0.41	0.71	-	-	3.20	5.00	8.20	24.00	-15.80
6485	-0.19	0.98	-	-	3.44	5.00	8.44	24.00	-15.56
6525	-0.26	1.19	-	-	3.54	5.00	8.54	24.00	-15.46
6565	-0.75	1.35	-	-	3.44	5.20	8.64	24.00	-15.36
6725	-1.12	1.43	-	-	3.35	5.20	8.55	24.00	-15.45
6845	-1.01	1.52	-	-	3.45	5.20	8.65	24.00	-15.35
6885	-0.36	1.67	-	-	3.78	5.20	8.98	24.00	-15.02
6925	0.22	2.01	-	-	4.22	4.40	8.62	24.00	-15.38
7005	0.64	1.92	-	-	4.33	4.40	8.73	24.00	-15.27
7085	0.66	1.80	-	-	4.28	4.40	8.68	24.00	-15.32

Table 424 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a80 LPI	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	4.37	3.85	-	-	7.13	5.30	12.43	24.00	-11.57
6145	5.58	5.16	-	-	8.39	4.20	12.59	24.00	-11.41
6385	3.00	4.25	-	-	6.68	4.60	11.28	24.00	-12.72
6465	2.83	4.37	-	-	6.68	5.00	11.68	24.00	-12.32
6545	2.67	4.09	-	-	6.45	5.20	11.65	24.00	-12.35
6625	2.87	4.47	-	-	6.75	5.20	11.95	24.00	-12.05
6705	3.29	4.56	-	-	6.98	5.20	12.18	24.00	-11.82
6785	3.57	4.48	-	-	7.06	5.20	12.26	24.00	-11.74
6865	3.54	4.54	-	-	7.08	5.20	12.28	24.00	-11.72
6945	4.07	5.26	-	-	7.72	4.40	12.12	24.00	-11.88
7025	3.92	4.65	-	-	7.31	4.40	11.71	24.00	-12.29

Table 425 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a160 LPI	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	6.96	6.45	-	-	9.72	5.30	15.02	24.00	-8.98
6185	7.87	7.35	-	-	10.63	4.20	14.83	24.00	-9.17
6345	5.35	7.15	-	-	9.36	4.60	13.96	24.00	-10.04
6505	4.63	6.66	-	-	8.77	5.00	13.77	24.00	-10.23
6665	5.03	7.17	-	-	9.24	5.20	14.44	24.00	-9.56
6825	5.02	7.29	-	-	9.31	5.20	14.51	24.00	-9.49
6985	5.57	7.73	-	-	9.79	4.40	14.19	24.00	-9.81

Table 426 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 SU LPI	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	-1.65	-1.95	-	-	1.21	5.30	6.51	24.00	-17.49
6175	-0.56	-0.95	-	-	2.26	4.20	6.46	24.00	-17.54
6415	-2.14	-1.93	-	-	0.98	4.60	5.58	24.00	-18.42
6435	-2.58	-2.04	-	-	0.71	5.00	5.71	24.00	-18.29
6475	-3.02	-2.15	-	-	0.45	5.00	5.45	24.00	-18.55
6515	-3.16	-2.13	-	-	0.39	5.00	5.39	24.00	-18.61
6535	-2.74	-1.63	-	-	0.86	5.20	6.06	24.00	-17.94
6695	-3.64	-1.85	-	-	0.35	5.20	5.55	24.00	-18.45
6855	-3.13	-1.57	-	-	0.73	5.20	5.93	24.00	-18.07
6875	-2.69	-1.31	-	-	1.06	5.20	6.26	24.00	-17.74
6895	-1.98	-0.83	-	-	1.64	4.40	6.04	24.00	-17.96
6995	-1.70	-0.97	-	-	1.69	4.40	6.09	24.00	-17.91
7095	-1.36	-1.07	-	-	1.80	4.40	6.20	24.00	-17.80

Table 427 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU LPI	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	0.93	1.22	-	-	4.09	5.30	9.39	24.00	-14.61
6165	2.33	2.50	-	-	5.43	4.20	9.63	24.00	-14.37
6405	0.39	1.00	-	-	3.71	4.60	8.31	24.00	-15.69
6445	-0.13	0.99	-	-	3.48	5.00	8.48	24.00	-15.52
6485	-0.45	0.74	-	-	3.19	5.00	8.19	24.00	-15.81
6525	-0.26	1.19	-	-	3.54	5.00	8.54	24.00	-15.46
6565	-0.78	1.32	-	-	3.40	5.20	8.60	24.00	-15.40
6725	-1.24	1.48	-	-	3.34	5.20	8.54	24.00	-15.46
6845	-0.95	1.59	-	-	3.51	5.20	8.71	24.00	-15.29
6885	-0.36	1.65	-	-	3.77	5.20	8.97	24.00	-15.03
6925	0.24	1.98	-	-	4.21	4.40	8.61	24.00	-15.39
7005	0.65	1.92	-	-	4.34	4.40	8.74	24.00	-15.26
7085	0.67	1.77	-	-	4.26	4.40	8.66	24.00	-15.34

Table 428 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU LPI	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	4.17	3.67	-	-	6.94	5.30	12.24	24.00	-11.76
6145	5.25	4.79	-	-	8.04	4.20	12.24	24.00	-11.76
6385	3.02	4.28	-	-	6.71	4.60	11.31	24.00	-12.69
6465	2.89	4.43	-	-	6.74	5.00	11.74	24.00	-12.26
6545	2.65	4.09	-	-	6.44	5.20	11.64	24.00	-12.36
6625	2.83	4.51	-	-	6.76	5.20	11.96	24.00	-12.04
6705	3.11	4.40	-	-	6.81	5.20	12.01	24.00	-11.99
6785	3.62	4.47	-	-	7.08	5.20	12.28	24.00	-11.72
6865	3.53	4.60	-	-	7.11	5.20	12.31	24.00	-11.69
6945	4.16	5.23	-	-	7.74	4.40	12.14	24.00	-11.86
7025	3.90	4.71	-	-	7.34	4.40	11.74	24.00	-12.26

Table 429 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE160 SU LPI	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	6.93	6.50	-	-	9.73	5.30	15.03	24.00	-8.97
6185	7.54	8.02	-	-	10.80	4.20	15.00	24.00	-9.00
6345	5.66	7.09	-	-	9.45	4.60	14.05	24.00	-9.95
6505	5.23	7.05	-	-	9.24	5.00	14.24	24.00	-9.76
6665	5.21	7.08	-	-	9.26	5.20	14.46	24.00	-9.54
6825	5.20	6.94	-	-	9.16	5.20	14.36	24.00	-9.64
6985	5.93	7.61	-	-	9.86	4.40	14.26	24.00	-9.74

Table 430 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU52 LPI	Duty Cycle (%):	97.8
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU52.37)	-8.06	-8.48	-	-	-5.26	5.30	0.04	24.00	-23.96
6175 (RU52.37)	-7.39	-7.65	-	-	-4.51	4.20	-0.31	24.00	-24.31
6415 (RU52.40)	-8.32	-8.26	-	-	-5.28	4.60	-0.68	24.00	-24.68
6435 (RU52.37)	-8.91	-8.39	-	-	-5.63	5.00	-0.63	24.00	-24.63
6475 (RU52.37)	-9.24	-8.50	-	-	-5.84	5.00	-0.84	24.00	-24.84
6515 (RU52.40)	-9.45	-8.46	-	-	-5.91	5.00	-0.91	24.00	-24.91
6535 (RU52.37)	-9.26	-8.20	-	-	-5.68	5.20	-0.48	24.00	-24.48
6695 (RU52.37)	-10.01	-8.20	-	-	-6.00	5.20	-0.80	24.00	-24.80
6855 (RU52.40)	-9.70	-7.97	-	-	-5.74	5.20	-0.54	24.00	-24.54
6875 (RU52.38)	-9.23	-7.73	-	-	-5.40	5.20	-0.20	24.00	-24.20
6875 (RU52.39)	-8.63	-7.89	-	-	-5.23	5.20	-0.03	24.00	-24.03
6895 (RU52.37)	-8.61	-7.20	-	-	-4.84	4.40	-0.44	24.00	-24.44
6995 (RU52.37)	-8.24	-7.42	-	-	-4.80	4.40	-0.40	24.00	-24.40
7095 (RU52.40)	-7.62	-7.47	-	-	-4.54	4.40	-0.14	24.00	-24.14

Table 431 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU106 LPI	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU106.53)	-5.12	-5.57	-	-	-2.33	5.30	2.97	24.00	-21.03
6175 (RU106.53)	-4.07	-4.33	-	-	-1.19	4.20	3.01	24.00	-20.99
6415 (RU106.54)	-5.11	-5.16	-	-	-2.12	4.60	2.48	24.00	-21.52
6435 (RU106.53)	-5.84	-5.30	-	-	-2.55	5.00	2.45	24.00	-21.55
6475 (RU106.53)	-6.10	-5.38	-	-	-2.71	5.00	2.29	24.00	-21.71
6515 (RU106.54)	-6.26	-5.38	-	-	-2.78	5.00	2.22	24.00	-21.78
6535 (RU106.53)	-6.15	-5.16	-	-	-2.61	5.20	2.59	24.00	-21.41
6695 (RU106.53)	-6.94	-5.09	-	-	-2.90	5.20	2.30	24.00	-21.70
6855 (RU106.54)	-6.64	-5.00	-	-	-2.74	5.20	2.46	24.00	-21.54
6875 (RU106.53)	-6.01	-4.53	-	-	-2.20	5.20	3.00	24.00	-21.00
6875 (RU106.54)	-5.84	-4.58	-	-	-2.15	5.20	3.05	24.00	-20.95
6895 (RU106.53)	-5.56	-4.30	-	-	-1.87	4.40	2.53	24.00	-21.47
6995 (RU106.53)	-4.80	-4.20	-	-	-1.48	4.40	2.92	24.00	-21.08
7095 (RU106.54)	-4.65	-4.60	-	-	-1.61	4.40	2.79	24.00	-21.21

Table 432 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 52 + RU Size 26 LPI	Duty Cycle (%):	97.4
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU Size 52 + RU Size 26.70)	-6.25	-6.24	-	-	-3.23	5.30	2.07	24.00	-21.93
6175 (RU Size 52 + RU Size 26.70)	-5.14	-5.03	-	-	-2.07	4.20	2.13	24.00	-21.87
6415 (RU Size 52 + RU Size 26.72)	-6.63	-6.28	-	-	-3.44	4.60	1.16	24.00	-22.84
6435 (RU Size 52 + RU Size 26.70)	-7.12	-6.35	-	-	-3.71	5.00	1.29	24.00	-22.71
6475 (RU Size 52 + RU Size 26.70)	-7.27	-6.35	-	-	-3.78	5.00	1.22	24.00	-22.78
6515 (RU Size 52 + RU Size 26.72)	-7.64	-6.52	-	-	-4.04	5.00	0.96	24.00	-23.04
6535 (RU Size 52 + RU Size 26.70)	-7.78	-6.37	-	-	-4.00	5.20	1.20	24.00	-22.80
6695 (RU Size 52 + RU Size 26.70)	-8.52	-6.44	-	-	-4.34	5.20	0.86	24.00	-23.14
6855 (RU Size 52 + RU Size 26.72)	-7.99	-6.33	-	-	-4.07	5.20	1.13	24.00	-22.87
6875 (RU Size 52 + RU Size 26.70)	-7.44	-5.82	-	-	-3.55	5.20	1.65	24.00	-22.35
6875 (RU Size 52 + RU Size 26.72)	-7.28	-5.86	-	-	-3.50	5.20	1.70	24.00	-22.30
6895 (RU Size 52 + RU Size 26.70)	-7.40	-5.87	-	-	-3.55	4.40	0.85	24.00	-23.15
6995 (RU Size 52 + RU Size 26.70)	-6.42	-5.61	-	-	-2.99	4.40	1.41	24.00	-22.59
7095 (RU Size 52 + RU Size 26.72)	-5.63	-5.20	-	-	-2.40	4.40	2.00	24.00	-22.00

Table 433 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 106 + RU Size 26 LPI	Duty Cycle (%):	97.3
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU Size 106 + RU Size 26.82)	-4.57	-4.57	-	-	-1.56	5.30	3.74	24.00	-20.26
6175 (RU Size 106 + RU Size 26.82)	-3.25	-2.92	-	-	-0.07	4.20	4.13	24.00	-19.87
6415 (RU Size 106 + RU Size 26.83)	-4.17	-3.89	-	-	-1.02	4.60	3.58	24.00	-20.42
6435 (RU Size 106 + RU Size 26.82)	-4.93	-4.18	-	-	-1.53	5.00	3.47	24.00	-20.53
6475 (RU Size 106 + RU Size 26.82)	-5.09	-4.21	-	-	-1.62	5.00	3.38	24.00	-20.62
6515 (RU Size 106 + RU Size 26.83)	-5.46	-4.35	-	-	-1.86	5.00	3.14	24.00	-20.86
6535 (RU Size 106 + RU Size 26.82)	-5.38	-4.00	-	-	-1.62	5.20	3.58	24.00	-20.42
6695 (RU Size 106 + RU Size 26.82)	-5.88	-3.85	-	-	-1.74	5.20	3.46	24.00	-20.54
6855 (RU Size 106 + RU Size 26.83)	-5.52	-3.99	-	-	-1.68	5.20	3.52	24.00	-20.48
6875 (RU Size 106 + RU Size 26.82)	-5.23	-3.73	-	-	-1.41	5.20	3.79	24.00	-20.21
6875 (RU Size 106 + RU Size 26.83)	-5.11	-3.77	-	-	-1.38	5.20	3.82	24.00	-20.18
6895 (RU Size 106 + RU Size 26.82)	-5.14	-3.69	-	-	-1.34	4.40	3.06	24.00	-20.94
6995 (RU Size 106 + RU Size 26.82)	-4.26	-3.51	-	-	-0.86	4.40	3.54	24.00	-20.46
7095 (RU Size 106 + RU Size 26.83)	-3.69	-3.22	-	-	-0.44	4.40	3.96	24.00	-20.04

Table 434 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 LPI	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985 (RU Size 484 + RU Size 242.93)	2.99	2.79	-	-	5.90	5.30	11.20	24.00	-12.80
6145 (RU Size 484 + RU Size 242.92)	3.95	3.51	-	-	6.74	4.20	10.94	24.00	-13.06
6385 (RU Size 484 + RU Size 242.90)	1.82	3.25	-	-	5.61	4.60	10.21	24.00	-13.79
6465 (RU Size 484 + RU Size 242.93)	1.53	3.02	-	-	5.35	5.00	10.35	24.00	-13.65
6545 (RU Size 484 + RU Size 242.90)	0.81	2.90	-	-	4.99	5.20	10.19	24.00	-13.81
6545 (RU Size 484 + RU Size 242.93)	0.92	2.89	-	-	5.03	5.20	10.23	24.00	-13.77
6625 (RU Size 484 + RU Size 242.93)	1.40	3.18	-	-	5.39	5.20	10.59	24.00	-13.41
6705 (RU Size 484 + RU Size 242.91)	0.85	2.95	-	-	5.04	5.20	10.24	24.00	-13.76
6785 (RU Size 484 + RU Size 242.90)	1.56	2.82	-	-	5.25	5.20	10.45	24.00	-13.55
6865 (RU Size 484 + RU Size 242.90)	1.96	3.05	-	-	5.55	5.20	10.75	24.00	-13.25
6865 (RU Size 484 + RU Size 242.93)	1.90	3.05	-	-	5.52	5.20	10.72	24.00	-13.28
6945 (RU Size 484 + RU Size 242.93)	2.43	3.59	-	-	6.06	4.40	10.46	24.00	-13.54
7025 (RU Size 484 + RU Size 242.90)	2.88	3.25	-	-	6.08	4.40	10.48	24.00	-13.52

Table 435 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 LPI (Primary)	Duty Cycle (%):	97.8
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	6.13	6.61	-	-	9.39	4.20	13.59	24.00	-10.41
6345 (RU Size 996 + RU Size 484.94)	4.44	5.95	-	-	8.27	4.60	12.87	24.00	-11.13
6505 (RU Size 996 + RU Size 484.94)	3.74	5.68	-	-	7.83	5.00	12.83	24.00	-11.17
6665 (RU Size 996 + RU Size 484.94)	4.09	5.95	-	-	8.13	5.20	13.33	24.00	-10.67
6825 (RU Size 996 + RU Size 484.94)	3.86	5.65	-	-	7.86	5.20	13.06	24.00	-10.94
6985 (RU Size 996 + RU Size 484.94)	4.60	6.27	-	-	8.53	4.40	12.93	24.00	-11.07

Table 436 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 LPI (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484.95)	5.03	5.20	-	-	8.12	5.30	13.42	24.00	-10.58
6185 (RU Size 996 + RU Size 484.94)	6.26	6.71	-	-	9.50	4.20	13.70	24.00	-10.30
6505 (RU Size 996 + RU Size 484.95)	3.56	5.49	-	-	7.64	5.00	12.64	24.00	-11.36
6665 (RU Size 996 + RU Size 484.95)	4.11	6.07	-	-	8.21	5.20	13.41	24.00	-10.59
6825 (RU Size 996 + RU Size 484.95)	4.15	5.85	-	-	8.09	5.20	13.29	24.00	-10.71
6985 (RU Size 996 + RU Size 484.95)	4.51	6.23	-	-	8.46	4.40	12.86	24.00	-11.14

Table 437 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 LPI (Primary)	Duty Cycle (%):	97.8
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	7.00	7.49	-	-	10.27	4.20	14.47	24.00	-9.53
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	6.84	7.33	-	-	10.10	4.20	14.30	24.00	-9.70
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	6.88	7.28	-	-	10.10	4.20	14.30	24.00	-9.70
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	5.37	6.81	-	-	9.16	4.60	13.76	24.00	-10.24
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	4.43	6.34	-	-	8.50	5.00	13.50	24.00	-10.50
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	5.03	6.81	-	-	9.02	5.20	14.22	24.00	-9.78
6825 (RU Size 996 + RU Size 484 + RU Size 242.96)	4.80	6.64	-	-	8.82	5.20	14.02	24.00	-9.98
6985 (RU Size 996 + RU Size 484 + RU Size 242.96)	5.35	7.09	-	-	9.32	4.40	13.72	24.00	-10.28

Table 438 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 LPI (Secondary)	Duty Cycle (%):	97.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484 + RU Size 242.99)	5.76	5.92	-	-	8.85	5.30	14.15	24.00	-9.85
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	4.39	6.16	-	-	8.37	5.00	13.37	24.00	-10.63
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	4.84	6.81	-	-	8.94	5.20	14.14	24.00	-9.86
6825 (RU Size 996 + RU Size 484 + RU Size 242.99)	4.78	6.58	-	-	8.78	5.20	13.98	24.00	-10.02
6985 (RU Size 996 + RU Size 484 + RU Size 242.99)	5.41	7.22	-	-	9.42	4.40	13.82	24.00	-10.18

Table 439 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a20 SP	Duty Cycle (%):	97.3
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	15.20	14.70	-	-	17.97	5.30	23.27	30.00	-6.73
6175	16.96	16.76	-	-	19.87	4.20	24.07	30.00	-5.93
6415	14.98	16.12	-	-	18.60	4.60	23.20	30.00	-6.80
6535	14.68	15.94	-	-	18.37	5.20	23.57	30.00	-6.43
6695	14.80	15.99	-	-	18.45	5.20	23.65	30.00	-6.35
6855	14.88	16.05	-	-	18.52	5.20	23.72	30.00	-6.28

Table 440 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a40 SP	Duty Cycle (%):	97.3
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	17.94	18.20	-	-	21.08	5.30	26.38	30.00	-3.62
6165	18.88	19.39	-	-	22.15	4.20	26.35	30.00	-3.65
6405	17.52	19.23	-	-	21.47	4.60	26.07	30.00	-3.93
6565	17.22	19.32	-	-	21.40	5.20	26.60	30.00	-3.40
6685	16.94	19.20	-	-	21.23	5.20	26.43	30.00	-3.57
6845	17.25	19.39	-	-	21.46	5.20	26.66	30.00	-3.34

Table 441 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a80 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	19.36	18.92	-	-	22.16	5.30	27.46	30.00	-2.54
6145	19.14	18.78	-	-	21.97	4.20	26.17	30.00	-3.83
6385	18.34	19.21	-	-	21.81	4.60	26.41	30.00	-3.59
6625	17.70	19.25	-	-	21.55	5.20	26.75	30.00	-3.25
6705	17.79	19.18	-	-	21.55	5.20	26.75	30.00	-3.25
6785	18.08	19.17	-	-	21.67	5.20	26.87	30.00	-3.13

Table 442 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a160 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	18.59	19.14	-	-	21.89	5.30	27.19	30.00	-2.81
6185	18.25	19.05	-	-	21.68	4.20	25.88	30.00	-4.12
6345	17.38	19.27	-	-	21.44	4.60	26.04	30.00	-3.96
6665	16.67	19.12	-	-	21.08	5.20	26.28	30.00	-3.72

Table 443 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 SU SP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	15.41	15.02	-	-	18.23	5.30	23.53	30.00	-6.47
6175	17.21	16.97	-	-	20.11	4.20	24.31	30.00	-5.69
6415	15.14	16.34	-	-	18.79	4.60	23.39	30.00	-6.61
6535	15.01	16.30	-	-	18.71	5.20	23.91	30.00	-6.09
6695	15.05	16.24	-	-	18.69	5.20	23.89	30.00	-6.11
6855	15.40	16.54	-	-	19.02	5.20	24.22	30.00	-5.78

Table 444 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	17.96	18.32	-	-	21.16	5.30	26.46	30.00	-3.54
6165	18.58	19.11	-	-	21.86	4.20	26.06	30.00	-3.94
6405	17.65	19.41	-	-	21.63	4.60	26.23	30.00	-3.77
6565	17.43	19.40	-	-	21.53	5.20	26.73	30.00	-3.27
6685	17.09	19.26	-	-	21.32	5.20	26.52	30.00	-3.48
6845	16.93	19.13	-	-	21.18	5.20	26.38	30.00	-3.62

Table 445 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	19.20	18.69	-	-	21.96	5.30	27.26	30.00	-2.74
6145	19.22	18.80	-	-	22.03	4.20	26.23	30.00	-3.77
6385	18.08	19.03	-	-	21.59	4.60	26.19	30.00	-3.81
6625	17.74	19.37	-	-	21.64	5.20	26.84	30.00	-3.16
6705	17.66	19.01	-	-	21.40	5.20	26.60	30.00	-3.40
6785	18.18	19.19	-	-	21.72	5.20	26.92	30.00	-3.08

Table 446 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	18.99	19.33	-	-	22.18	5.30	27.48	30.00	-2.52
6185	18.72	19.28	-	-	22.02	4.20	26.22	30.00	-3.78
6345	17.85	19.44	-	-	21.73	4.60	26.33	30.00	-3.67
6665	17.18	19.27	-	-	21.36	5.20	26.56	30.00	-3.44

Table 447 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU26 SP	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU26.0)	7.09	6.62	-	-	9.87	5.30	15.17	30.00	-14.83
6175 (RU26.0)	8.08	7.54	-	-	10.83	4.20	15.03	30.00	-14.97
6415 (RU26.8)	6.09	7.07	-	-	9.62	4.60	14.22	30.00	-15.78
6535 (RU26.0)	6.20	7.22	-	-	9.75	5.20	14.95	30.00	-15.05
6695 (RU26.0)	5.68	6.91	-	-	9.35	5.20	14.55	30.00	-15.45
6855 (RU26.8)	5.84	7.27	-	-	9.62	5.20	14.82	30.00	-15.18

Table 448 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU52 SP	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU52.37)	9.72	9.15	-	-	12.45	5.30	17.75	30.00	-12.25
6175 (RU52.37)	10.75	10.35	-	-	13.56	4.20	17.76	30.00	-12.24
6415 (RU52.40)	8.85	9.76	-	-	12.34	4.60	16.94	30.00	-13.06
6535 (RU52.37)	8.58	9.66	-	-	12.16	5.20	17.36	30.00	-12.64
6695 (RU52.37)	8.60	9.72	-	-	12.21	5.20	17.41	30.00	-12.59
6855 (RU52.40)	8.60	10.04	-	-	12.39	5.20	17.59	30.00	-12.41

Table 449 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU106 SP	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU106.53)	13.05	12.44	-	-	15.77	5.30	21.07	30.00	-8.93
6175 (RU106.53)	14.04	13.56	-	-	16.82	4.20	21.02	30.00	-8.98
6415 (RU106.54)	12.31	13.25	-	-	15.82	4.60	20.42	30.00	-9.58
6535 (RU106.53)	11.84	12.77	-	-	15.34	5.20	20.54	30.00	-9.46
6695 (RU106.53)	11.72	12.89	-	-	15.35	5.20	20.55	30.00	-9.45
6855 (RU106.54)	11.25	12.76	-	-	15.08	5.20	20.28	30.00	-9.72

Table 450 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 52 + RU Size 26 SP	Duty Cycle (%):	97.4
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU Size 52 + RU Size 26.70)	11.73	11.11	-	-	14.44	5.30	19.74	30.00	-10.26
6175 (RU Size 52 + RU Size 26.70)	12.97	12.54	-	-	15.77	4.20	19.97	30.00	-10.03
6415 (RU Size 52 + RU Size 26.72)	11.15	12.10	-	-	14.66	4.60	19.26	30.00	-10.74
6535 (RU Size 52 + RU Size 26.70)	10.48	11.53	-	-	14.04	5.20	19.24	30.00	-10.76
6695 (RU Size 52 + RU Size 26.70)	10.61	11.80	-	-	14.26	5.20	19.46	30.00	-10.54
6855 (RU Size 52 + RU Size 26.72)	10.21	11.58	-	-	13.96	5.20	19.16	30.00	-10.84

Table 451 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 106 + RU Size 26 SP	Duty Cycle (%):	97.4
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU Size 106 + RU Size 26.82)	13.66	13.01	-	-	16.36	5.30	21.66	30.00	-8.34
6175 (RU Size 106 + RU Size 26.82)	15.10	14.67	-	-	17.90	4.20	22.10	30.00	-7.90
6415 (RU Size 106 + RU Size 26.83)	13.38	14.36	-	-	16.91	4.60	21.51	30.00	-8.49
6535 (RU Size 106 + RU Size 26.82)	12.84	13.94	-	-	16.44	5.20	21.64	30.00	-8.36
6695 (RU Size 106 + RU Size 26.82)	12.78	13.92	-	-	16.40	5.20	21.60	30.00	-8.40
6855 (RU Size 106 + RU Size 26.83)	12.39	13.75	-	-	16.13	5.20	21.33	30.00	-8.67

Table 452 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 SP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985 (RU Size 484 + RU Size 242.91)	17.86	17.39	-	-	20.64	5.30	25.94	30.00	-4.06
5985 (RU Size 484 + RU Size 242.93)	17.84	17.22	-	-	20.55	5.30	25.85	30.00	-4.15
6145 (RU Size 484 + RU Size 242.92)	17.73	17.44	-	-	20.59	4.20	24.79	30.00	-5.21
6385 (RU Size 484 + RU Size 242.90)	16.68	17.64	-	-	20.20	4.60	24.80	30.00	-5.20
6625 (RU Size 484 + RU Size 242.93)	16.33	17.99	-	-	20.25	5.20	25.45	30.00	-4.55
6705 (RU Size 484 + RU Size 242.91)	16.45	17.77	-	-	20.17	5.20	25.37	30.00	-4.63
6785 (RU Size 484 + RU Size 242.90)	16.69	17.67	-	-	20.22	5.20	25.42	30.00	-4.58

Table 453 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	17.20	17.94	-	-	20.59	4.20	24.79	30.00	-5.21
6345 (RU Size 996 + RU Size 484.94)	16.22	17.80	-	-	20.09	4.60	24.69	30.00	-5.31
6665 (RU Size 996 + RU Size 484.94)	15.80	17.72	-	-	19.87	5.20	25.07	30.00	-4.93

Table 454 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484.94)	17.62	17.94	-	-	20.80	5.30	26.10	30.00	-3.90
6025 (RU Size 996 + RU Size 484.95)	17.80	17.34	-	-	20.59	5.30	25.89	30.00	-4.11
6185 (RU Size 996 + RU Size 484.94)	17.23	17.76	-	-	20.52	4.20	24.72	30.00	-5.28
6665 (RU Size 996 + RU Size 484.95)	15.78	17.86	-	-	19.95	5.20	25.15	30.00	-4.85

Table 455 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	18.74	19.30	-	-	22.04	4.20	26.24	30.00	-3.76
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	18.83	19.40	-	-	22.13	4.20	26.33	30.00	-3.67
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	18.79	19.33	-	-	22.08	4.20	26.28	30.00	-3.72
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	17.70	19.23	-	-	21.54	4.60	26.14	30.00	-3.86
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	17.56	19.49	-	-	21.64	5.20	26.84	30.00	-3.16

Table 456 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.525-6.875 GHz	Band:	U-NII-5 U-NII-7
Limit Clause(s):	15.407(a)(7) RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.30
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025 (RU Size 996 + RU Size 484 + RU Size 242.97)	19.06	19.39	-	-	22.24	5.30	27.54	30.00	-2.46
6025 (RU Size 996 + RU Size 484 + RU Size 242.99)	19.16	18.67	-	-	21.93	5.30	27.23	30.00	-2.77
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	17.29	19.33	-	-	21.44	5.20	26.64	30.00	-3.36

Table 457 - Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a20 SP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435	14.51	16.05	-	-	18.36	5.00	23.36	30.00	-6.64
6475	14.43	15.79	-	-	18.17	5.00	23.17	30.00	-6.83
6515	14.71	15.97	-	-	18.40	5.00	23.40	30.00	-6.60

Table 458 - ISD Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a40 SP	Duty Cycle (%):	97.5
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6445	17.29	19.09	-	-	21.29	5.00	26.29	30.00	-3.71
6485	17.46	19.14	-	-	21.39	5.00	26.39	30.00	-3.61
6525	17.36	19.31	-	-	21.45	5.00	26.45	30.00	-3.55

Table 459 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a80 SP	Duty Cycle (%):	97.4
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465	17.91	19.12	-	-	21.57	5.00	26.57	30.00	-3.43
6545	17.70	19.00	-	-	21.41	5.20	26.61	30.00	-3.39

Table 460 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a160 SP	Duty Cycle (%):	97.4
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505	17.14	19.17	-	-	21.28	5.00	26.28	30.00	-3.72

Table 461 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 SU SP	Duty Cycle (%):	99.2
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435	14.72	16.25	-	-	18.56	5.00	23.56	30.00	-6.44
6475	14.67	16.05	-	-	18.42	5.00	23.42	30.00	-6.58
6515	14.60	15.97	-	-	18.35	5.00	23.35	30.00	-6.65

Table 462 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU SP	Duty Cycle (%):	99.2
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6445	17.09	18.87	-	-	21.08	5.00	26.08	30.00	-3.92
6485	17.54	19.20	-	-	21.46	5.00	26.46	30.00	-3.54
6525	17.29	19.22	-	-	21.37	5.00	26.37	30.00	-3.63

Table 463 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465	17.93	19.12	-	-	21.58	5.00	26.58	30.00	-3.42
6545	18.09	19.28	-	-	21.74	5.20	26.94	30.00	-3.06

Table 464 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE160 SU SP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505	17.59	19.50	-	-	21.66	5.00	26.66	30.00	-3.34

Table 465 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU26 SP	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435 (RU26.0)	5.58	6.75	-	-	9.22	5.00	14.22	30.00	-15.78
6475 (RU26.0)	5.54	6.73	-	-	9.19	5.00	14.19	30.00	-15.81
6515 (RU26.8)	5.80	6.96	-	-	9.43	5.00	14.43	30.00	-15.57

Table 466 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU52 SP	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435 (RU52.37)	8.55	9.70	-	-	12.17	5.00	17.17	30.00	-12.83
6475 (RU52.37)	7.99	9.22	-	-	11.66	5.00	16.66	30.00	-13.34
6515 (RU52.40)	8.61	9.54	-	-	12.11	5.00	17.11	30.00	-12.89

Table 467 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU106 SP	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435 (RU106.53)	11.76	12.78	-	-	15.31	5.00	20.31	30.00	-9.69
6475 (RU106.53)	11.74	12.84	-	-	15.33	5.00	20.33	30.00	-9.67
6515 (RU106.54)	11.82	12.67	-	-	15.28	5.00	20.28	30.00	-9.72

Table 468 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 52 + RU Size 26 SP	Duty Cycle (%):	97.5
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435 (RU Size 52 + RU Size 26.70)	10.33	11.40	-	-	13.91	5.00	18.91	30.00	-11.09
6475 (RU Size 52 + RU Size 26.70)	10.35	11.50	-	-	13.97	5.00	18.97	30.00	-11.03
6515 (RU Size 52 + RU Size 26.72)	10.50	11.37	-	-	13.97	5.00	18.97	30.00	-11.03

Table 469 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 106 + RU Size 26 SP	Duty Cycle (%):	97.4
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6435 (RU Size 106 + RU Size 26.82)	12.79	13.92	-	-	16.40	5.00	21.40	30.00	-8.60
6475 (RU Size 106 + RU Size 26.82)	12.84	13.95	-	-	16.44	5.00	21.44	30.00	-8.56
6515 (RU Size 106 + RU Size 26.83)	12.92	13.82	-	-	16.40	5.00	21.40	30.00	-8.60

Table 470 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz	Band:	U-NII-6 U-NII-7
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 SP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6465 (RU Size 484 + RU Size 242.93)	16.51	17.67	-	-	20.14	5.00	25.14	30.00	-4.86
6545 (RU Size 484 + RU Size 242.90)	16.54	17.57	-	-	20.10	5.20	25.30	30.00	-4.70
6545 (RU Size 484 + RU Size 242.93)	16.46	17.55	-	-	20.05	5.20	25.25	30.00	-4.75

Table 471 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484.94)	15.82	17.73	-	-	19.89	5.00	24.89	30.00	-5.11

Table 472 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484.95)	15.92	17.77	-	-	19.95	5.00	24.95	30.00	-5.05

Table 473 - ISED Maximum Conducted (average) Output Power Results

Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	17.42	19.27	-	-	21.45	5.00	26.45	30.00	-3.55

Table 474 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz	Band:	U-NII-6
Limit Clause(s):	RSS-248 4.5.5	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 SP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.00
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	17.51	19.22	-	-	21.46	5.00	26.46	30.00	-3.54

Table 475 - ISED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a20 VLP	Duty Cycle (%):	97.3
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115	-4.74	-4.75	-	-	-1.74	4.20	2.46	14.00	-11.54
6255	-4.87	-5.42	-	-	-2.13	4.20	2.07	14.00	-11.93
6415	-6.36	-6.13	-	-	-3.23	4.60	1.37	14.00	-12.63
6435	-6.73	-6.20	-	-	-3.45	5.00	1.55	14.00	-12.45
6475	-6.86	-6.06	-	-	-3.43	5.00	1.57	14.00	-12.43
6515	-7.28	-6.29	-	-	-3.74	5.00	1.26	14.00	-12.74
6535	-7.13	-5.97	-	-	-3.50	5.20	1.70	14.00	-12.30
6695	-7.71	-5.83	-	-	-3.66	5.20	1.54	14.00	-12.46
6855	-7.50	-5.88	-	-	-3.61	5.20	1.59	14.00	-12.41
6875	-6.84	-5.40	-	-	-3.05	5.20	2.15	14.00	-11.85
6895	-6.69	-5.22	-	-	-2.88	4.40	1.52	14.00	-12.48
6995	-6.00	-5.15	-	-	-2.55	4.40	1.85	14.00	-12.15
7095	-5.32	-4.99	-	-	-2.14	4.40	2.26	14.00	-11.74
7115	-5.98	-5.54	-	-	-2.74	4.40	1.66	14.00	-12.34

Table 476 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a40 VLP	Duty Cycle (%):	94.5
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	-2.01	-1.50	-	-	1.26	4.20	5.46	14.00	-8.54
6245	-1.87	-1.52	-	-	1.32	4.20	5.52	14.00	-8.48
6405	-3.43	-2.81	-	-	-0.10	4.60	4.50	14.00	-9.50
6445	-4.05	-2.88	-	-	-0.42	5.00	4.58	14.00	-9.42
6485	-4.07	-2.83	-	-	-0.40	5.00	4.60	14.00	-9.40
6525	-4.43	-2.89	-	-	-0.58	5.00	4.42	14.00	-9.58
6565	-4.67	-2.49	-	-	-0.43	5.20	4.77	14.00	-9.23
6725	-5.15	-2.59	-	-	-0.67	5.20	4.53	14.00	-9.47
6845	-5.06	-2.54	-	-	-0.61	5.20	4.59	14.00	-9.41
6885	-4.32	-2.33	-	-	-0.21	5.20	4.99	14.00	-9.01
6925	-3.73	-1.99	-	-	0.24	4.40	4.64	14.00	-9.36
7005	-3.21	-1.97	-	-	0.46	4.40	4.86	14.00	-9.14
7085	-2.99	-1.90	-	-	0.60	4.40	5.00	14.00	-9.00

Table 477 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a80 VLP	Duty Cycle (%):	97.2
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	1.45	1.15	-	-	4.31	4.20	8.51	14.00	-5.49
6225	1.31	0.91	-	-	4.12	4.20	8.32	14.00	-5.68
6385	0.15	0.10	-	-	3.14	4.60	7.74	14.00	-6.26
6465	-0.47	0.33	-	-	2.96	5.00	7.96	14.00	-6.04
6545	-1.41	-0.08	-	-	2.32	5.20	7.52	14.00	-6.48
6625	-1.53	0.39	-	-	2.54	5.20	7.74	14.00	-6.26
6705	-1.61	0.19	-	-	2.39	5.20	7.59	14.00	-6.41
6785	-0.99	0.47	-	-	2.81	5.20	8.01	14.00	-5.99
6865	-0.91	0.59	-	-	2.91	5.20	8.11	14.00	-5.89
6945	0.23	1.28	-	-	3.80	4.40	8.20	14.00	-5.80
7025	0.19	0.78	-	-	3.51	4.40	7.91	14.00	-6.09

Table 478 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11a160 VLP	Duty Cycle (%):	97.4
Data Rate:	12 Mbps	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	4.24	4.02	-	-	7.14	4.20	11.34	14.00	-2.66
6345	1.43	3.19	-	-	5.41	4.60	10.01	14.00	-3.99
6505	0.97	2.69	-	-	4.93	5.00	9.93	14.00	-4.07
6665	0.98	3.18	-	-	5.23	5.20	10.43	14.00	-3.57
6825	1.00	2.95	-	-	5.09	5.20	10.29	14.00	-3.71
6985	1.56	3.56	-	-	5.69	4.40	10.09	14.00	-3.91

Table 479 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115	-4.53	-4.57	-	-	-1.54	4.20	2.66	14.00	-11.34
6255	-4.70	-5.23	-	-	-1.95	4.20	2.25	14.00	-11.75
6415	-6.15	-5.94	-	-	-3.03	4.60	1.57	14.00	-12.43
6435	-6.54	-5.99	-	-	-3.25	5.00	1.75	14.00	-12.25
6475	-6.91	-6.10	-	-	-3.48	5.00	1.52	14.00	-12.48
6515	-7.08	-6.09	-	-	-3.55	5.00	1.45	14.00	-12.55
6535	-7.01	-5.78	-	-	-3.34	5.20	1.86	14.00	-12.14
6695	-7.53	-5.64	-	-	-3.48	5.20	1.72	14.00	-12.28
6855	-7.01	-5.43	-	-	-3.14	5.20	2.06	14.00	-11.94
6875	-7.08	-5.43	-	-	-3.17	5.20	2.03	14.00	-11.97
6895	-5.94	-4.82	-	-	-2.34	4.40	2.06	14.00	-11.94
6995	-5.60	-4.80	-	-	-2.17	4.40	2.23	14.00	-11.77
7095	-5.24	-4.91	-	-	-2.06	4.40	2.34	14.00	-11.66

Table 480 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU VLP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6125	-2.08	-1.56	-	-	1.20	4.20	5.40	14.00	-8.60
6245	-1.94	-1.57	-	-	1.26	4.20	5.46	14.00	-8.54
6405	-3.47	-2.84	-	-	-0.14	4.60	4.46	14.00	-9.54
6445	-4.11	-2.92	-	-	-0.46	5.00	4.54	14.00	-9.46
6485	-4.09	-2.84	-	-	-0.41	5.00	4.59	14.00	-9.41
6525	-4.43	-2.93	-	-	-0.61	5.00	4.39	14.00	-9.61
6565	-4.67	-2.50	-	-	-0.44	5.20	4.76	14.00	-9.24
6725	-5.10	-2.58	-	-	-0.65	5.20	4.55	14.00	-9.45
6845	-5.02	-2.54	-	-	-0.60	5.20	4.60	14.00	-9.40
6885	-4.28	-2.34	-	-	-0.19	5.20	5.01	14.00	-8.99
6925	-3.67	-1.98	-	-	0.27	4.40	4.67	14.00	-9.33
7005	-3.17	-1.96	-	-	0.49	4.40	4.89	14.00	-9.11
7085	-2.98	-1.90	-	-	0.60	4.40	5.00	14.00	-9.00

Table 481 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU VLP	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145	1.45	1.12	-	-	4.30	4.20	8.50	14.00	-5.50
6225	1.31	0.91	-	-	4.12	4.20	8.32	14.00	-5.68
6385	0.16	0.08	-	-	3.13	4.60	7.73	14.00	-6.27
6465	-0.50	0.30	-	-	2.93	5.00	7.93	14.00	-6.07
6545	-1.40	-0.08	-	-	2.32	5.20	7.52	14.00	-6.48
6625	-1.56	0.36	-	-	2.51	5.20	7.71	14.00	-6.29
6705	-1.55	0.20	-	-	2.42	5.20	7.62	14.00	-6.38
6785	-1.09	0.37	-	-	2.71	5.20	7.91	14.00	-6.09
6865	-0.85	0.58	-	-	2.94	5.20	8.14	14.00	-5.86
6945	0.20	1.24	-	-	3.76	4.40	8.16	14.00	-5.84
7025	0.18	0.79	-	-	3.51	4.40	7.91	14.00	-6.09

Table 482 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE160 SU VLP	Duty Cycle (%):	98.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185	3.54	4.10	-	-	6.84	4.20	11.04	14.00	-2.96
6345	1.65	3.23	-	-	5.52	4.60	10.12	14.00	-3.88
6505	1.39	2.96	-	-	5.26	5.00	10.26	14.00	-3.74
6665	1.25	3.28	-	-	5.39	5.20	10.59	14.00	-3.41
6825	1.50	3.34	-	-	5.53	5.20	10.73	14.00	-3.27
6985	2.05	3.86	-	-	6.06	4.40	10.46	14.00	-3.54

Table 483 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU106 VLP	Duty Cycle (%):	98.6
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU106.53)	-8.09	-8.35	-	-	-5.21	4.20	-1.01	14.00	-15.01
6255 (RU106.53)	-8.27	-8.77	-	-	-5.51	4.20	-1.31	14.00	-15.31
6415 (RU106.54)	-9.16	-9.13	-	-	-6.13	4.60	-1.53	14.00	-15.53
6435 (RU106.53)	-10.06	-9.50	-	-	-6.76	5.00	-1.76	14.00	-15.76
6475 (RU106.53)	-10.11	-9.34	-	-	-6.70	5.00	-1.70	14.00	-15.70
6515 (RU106.54)	-10.20	-9.30	-	-	-6.72	5.00	-1.72	14.00	-15.72
6535 (RU106.53)	-10.51	-9.13	-	-	-6.75	5.20	-1.55	14.00	-15.55
6695 (RU106.53)	-11.04	-9.17	-	-	-6.99	5.20	-1.79	14.00	-15.79
6855 (RU106.54)	-10.53	-8.86	-	-	-6.61	5.20	-1.41	14.00	-15.41
6875 (RU106.53)	-10.23	-8.50	-	-	-6.27	5.20	-1.07	14.00	-15.07
6875 (RU106.54)	-10.12	-8.65	-	-	-6.31	5.20	-1.11	14.00	-15.11
6895 (RU106.53)	-10.12	-8.56	-	-	-6.26	4.40	-1.86	14.00	-15.86
6995 (RU106.53)	-9.08	-8.20	-	-	-5.61	4.40	-1.21	14.00	-15.21
7095 (RU106.54)	-8.64	-8.53	-	-	-5.57	4.40	-1.17	14.00	-15.17

Table 484 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 52 + RU Size 26 VLP	Duty Cycle (%):	97.5
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	4.40
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU Size 52 + RU Size 26.70)	-9.09	-9.39	-	-	-6.23	4.20	-2.03	14.00	-16.03
6175 (RU Size 52 + RU Size 26.70)	-9.09	-9.30	-	-	-6.19	4.20	-1.99	14.00	-15.99
6255 (RU Size 52 + RU Size 26.72)	-8.92	-9.47	-	-	-6.18	4.20	-1.98	14.00	-15.98

Table 485 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 106 + RU Size 26 VLP	Duty Cycle (%):	97.3
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6115 (RU Size 106 + RU Size 26.82)	-6.90	-7.26	-	-	-4.07	4.20	0.13	14.00	-13.87
6255 (RU Size 106 + RU Size 26.82)	-7.06	-7.61	-	-	-4.32	4.20	-0.12	14.00	-14.12
6415 (RU Size 106 + RU Size 26.83)	-8.06	-8.01	-	-	-5.03	4.60	-0.43	14.00	-14.43
6435 (RU Size 106 + RU Size 26.82)	-8.98	-8.40	-	-	-5.67	5.00	-0.67	14.00	-14.67
6475 (RU Size 106 + RU Size 26.82)	-8.98	-8.26	-	-	-5.59	5.00	-0.59	14.00	-14.59
6515 (RU Size 106 + RU Size 26.83)	-9.36	-8.45	-	-	-5.87	5.00	-0.87	14.00	-14.87
6535 (RU Size 106 + RU Size 26.82)	-9.30	-8.23	-	-	-5.72	5.20	-0.52	14.00	-14.52
6695 (RU Size 106 + RU Size 26.82)	-9.99	-8.19	-	-	-5.99	5.20	-0.79	14.00	-14.79
6855 (RU Size 106 + RU Size 26.83)	-9.64	-7.93	-	-	-5.69	5.20	-0.49	14.00	-14.49
6875 (RU Size 106 + RU Size 26.82)	-9.40	-7.75	-	-	-5.48	5.20	-0.28	14.00	-14.28
6875 (RU Size 106 + RU Size 26.83)	-9.14	-7.73	-	-	-5.37	5.20	-0.17	14.00	-14.17
6895 (RU Size 106 + RU Size 26.82)	-9.34	-7.77	-	-	-5.48	4.40	-1.08	14.00	-15.08
6995 (RU Size 106 + RU Size 26.82)	-8.45	-7.58	-	-	-4.98	4.40	-0.58	14.00	-14.58
7095 (RU Size 106 + RU Size 26.83)	-7.50	-7.37	-	-	-4.42	4.40	-0.02	14.00	-14.02

Table 486 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT80 RU Size 484 + RU Size 242 VLP	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6145 (RU Size 484 + RU Size 242.93)	0.26	0.15	-	-	3.22	4.20	7.42	14.00	-6.58
6225 (RU Size 484 + RU Size 242.92)	0.06	-0.21	-	-	2.94	4.20	7.14	14.00	-6.86
6385 (RU Size 484 + RU Size 242.90)	-0.92	-0.88	-	-	2.11	4.60	6.71	14.00	-7.29
6465 (RU Size 484 + RU Size 242.90)	-1.79	-1.10	-	-	1.58	5.00	6.58	14.00	-7.42
6545 (RU Size 484 + RU Size 242.90)	-2.86	-1.55	-	-	0.86	5.20	6.06	14.00	-7.94
6545 (RU Size 484 + RU Size 242.93)	-2.51	-1.42	-	-	1.08	5.20	6.28	14.00	-7.72
6625 (RU Size 484 + RU Size 242.93)	-3.00	-0.89	-	-	1.20	5.20	6.40	14.00	-7.60
6705 (RU Size 484 + RU Size 242.91)	-3.14	-1.27	-	-	0.91	5.20	6.11	14.00	-7.89
6785 (RU Size 484 + RU Size 242.90)	-2.44	-0.84	-	-	1.44	5.20	6.64	14.00	-7.36
6865 (RU Size 484 + RU Size 242.90)	-2.39	-0.89	-	-	1.43	5.20	6.63	14.00	-7.37
6865 (RU Size 484 + RU Size 242.93)	-2.59	-0.88	-	-	1.36	5.20	6.56	14.00	-7.44
6945 (RU Size 484 + RU Size 242.93)	-1.21	-0.24	-	-	2.31	4.40	6.71	14.00	-7.29
7025 (RU Size 484 + RU Size 242.90)	-0.99	-0.52	-	-	2.26	4.40	6.66	14.00	-7.34

Table 487 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 VLP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.95)	2.12	2.75	-	-	5.46	4.20	9.66	14.00	-4.34
6345 (RU Size 996 + RU Size 484.94)	1.25	2.06	-	-	4.68	4.60	9.28	14.00	-4.72
6505 (RU Size 996 + RU Size 484.94)	0.15	1.35	-	-	3.80	5.00	8.80	14.00	-5.20
6665 (RU Size 996 + RU Size 484.94)	0.50	1.95	-	-	4.30	5.20	9.50	14.00	-4.50
6825 (RU Size 996 + RU Size 484.94)	-0.37	1.91	-	-	3.93	5.20	9.13	14.00	-4.87
6985 (RU Size 996 + RU Size 484.94)	1.05	2.48	-	-	4.83	4.40	9.23	14.00	-4.77

Table 488 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 VLP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484.94)	2.13	2.62	-	-	5.39	4.20	9.59	14.00	-4.41
6505 (RU Size 996 + RU Size 484.95)	0.02	1.57	-	-	3.88	5.00	8.88	14.00	-5.12
6665 (RU Size 996 + RU Size 484.95)	-0.70	2.08	-	-	3.92	5.20	9.12	14.00	-4.88
6825 (RU Size 996 + RU Size 484.95)	-0.41	1.93	-	-	3.93	5.20	9.13	14.00	-4.87
6985 (RU Size 996 + RU Size 484.95)	1.58	2.13	-	-	4.87	4.40	9.27	14.00	-4.73

Table 489 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 VLP (Primary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6185 (RU Size 996 + RU Size 484 + RU Size 242.97)	2.98	3.60	-	-	6.32	4.20	10.52	14.00	-3.48
6185 (RU Size 996 + RU Size 484 + RU Size 242.98)	3.04	3.67	-	-	6.37	4.20	10.57	14.00	-3.43
6185 (RU Size 996 + RU Size 484 + RU Size 242.99)	3.06	3.59	-	-	6.35	4.20	10.55	14.00	-3.45
6345 (RU Size 996 + RU Size 484 + RU Size 242.96)	1.63	2.44	-	-	5.06	4.60	9.66	14.00	-4.34
6505 (RU Size 996 + RU Size 484 + RU Size 242.96)	0.86	2.25	-	-	4.62	5.00	9.62	14.00	-4.38
6665 (RU Size 996 + RU Size 484 + RU Size 242.96)	0.08	2.65	-	-	4.56	5.20	9.76	14.00	-4.24
6825 (RU Size 996 + RU Size 484 + RU Size 242.96)	0.89	2.73	-	-	4.92	5.20	10.12	14.00	-3.88
6985 (RU Size 996 + RU Size 484 + RU Size 242.96)	1.59	2.93	-	-	5.32	4.40	9.72	14.00	-4.28

Table 490 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(9) RSS-248 RSS-248 4.5.6	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT160 RU Size 996 + RU Size 484 + RU Size 242 VLP (Secondary)	Duty Cycle (%):	97.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	5.20
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6505 (RU Size 996 + RU Size 484 + RU Size 242.99)	1.44	2.05	-	-	4.77	5.00	9.77	14.00	-4.23
6665 (RU Size 996 + RU Size 484 + RU Size 242.99)	0.20	2.75	-	-	4.67	5.20	9.87	14.00	-4.13
6825 (RU Size 996 + RU Size 484 + RU Size 242.99)	0.36	2.59	-	-	4.63	5.20	9.83	14.00	-4.17
6985 (RU Size 996 + RU Size 484 + RU Size 242.99)	1.25	3.17	-	-	5.33	4.40	9.73	14.00	-4.27

Table 491 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 SU LPI	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955	1.46	1.12	-	-	4.31	4.87	9.18	24.00	-14.82
6175	2.24	1.98	-	-	5.12	3.64	8.76	24.00	-15.24
6415	0.82	0.84	-	-	3.84	4.50	8.34	24.00	-15.66
6435	0.28	0.95	-	-	3.63	4.85	8.49	24.00	-15.51
6475	-0.15	0.80	-	-	3.36	4.85	8.21	24.00	-15.79
6515	-0.31	0.81	-	-	3.29	4.85	8.15	24.00	-15.85
6535	-0.15	1.11	-	-	3.54	4.56	8.09	24.00	-15.91
6695	-0.71	1.10	-	-	3.30	4.56	7.85	24.00	-16.15
6855	-0.19	1.23	-	-	3.59	4.56	8.14	24.00	-15.86
6875	0.21	1.48	-	-	3.91	4.56	8.46	24.00	-15.54
6895	0.64	1.77	-	-	4.26	3.97	8.23	24.00	-15.77
6995	1.10	1.94	-	-	4.55	3.97	8.52	24.00	-15.48
7095	0.42	2.05	-	-	4.32	3.97	8.30	24.00	-15.70

Table 492 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE40 SU LPI	Duty Cycle (%):	99.1
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5965	3.58	3.95	-	-	6.78	4.87	11.65	24.00	-12.35
6165	5.04	5.28	-	-	8.17	3.64	11.81	24.00	-12.19
6405	2.25	4.13	-	-	6.30	4.50	10.80	24.00	-13.20
6445	2.16	4.19	-	-	6.30	4.85	11.16	24.00	-12.84
6485	2.17	4.09	-	-	6.24	4.85	11.10	24.00	-12.90
6525	2.18	4.28	-	-	6.37	4.85	11.22	24.00	-12.78
6565	2.33	4.50	-	-	6.56	4.56	11.12	24.00	-12.88
6725	2.61	4.32	-	-	6.56	4.56	11.11	24.00	-12.89
6845	2.29	4.27	-	-	6.40	4.56	10.96	24.00	-13.04
6885	2.61	4.67	-	-	6.77	4.56	11.33	24.00	-12.67
6925	3.28	5.13	-	-	7.32	3.97	11.29	24.00	-12.71
7005	3.18	5.14	-	-	7.28	3.97	11.25	24.00	-12.75
7085	3.44	5.05	-	-	7.33	3.97	11.30	24.00	-12.70

Table 493 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE80 SU LPI	Duty Cycle (%):	99.0
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.96
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5985	7.31	6.78	-	-	10.06	4.87	14.94	24.00	-9.06
6145	8.40	7.95	-	-	11.19	3.64	14.83	24.00	-9.17
6385	6.17	7.32	-	-	9.79	4.50	14.29	24.00	-9.71
6465	6.08	7.44	-	-	9.83	4.85	14.68	24.00	-9.32
6545	5.83	7.15	-	-	9.55	4.96	14.51	24.00	-9.49
6625	6.03	7.50	-	-	9.84	4.56	14.40	24.00	-9.60
6705	6.08	7.18	-	-	9.67	4.56	14.23	24.00	-9.77
6785	6.19	7.10	-	-	9.68	4.56	14.24	24.00	-9.76
6865	6.15	7.29	-	-	9.77	4.56	14.32	24.00	-9.68
6945	6.91	8.06	-	-	10.54	3.97	14.51	24.00	-9.49
7025	6.66	7.53	-	-	10.13	3.97	14.10	24.00	-9.90

Table 494 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE160 SU LPI	Duty Cycle (%):	98.3
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
6025	10.03	9.58	-	-	12.82	4.87	17.70	24.00	-6.30
6185	10.49	11.05	-	-	13.79	3.64	17.43	24.00	-6.57
6345	8.62	10.13	-	-	12.45	4.50	16.95	24.00	-7.05
6505	8.08	9.93	-	-	12.11	4.85	16.96	24.00	-7.04
6665	8.14	10.16	-	-	12.28	4.56	16.83	24.00	-7.17
6825	8.02	9.93	-	-	12.09	4.56	16.65	24.00	-7.35
6985	8.87	10.69	-	-	12.89	3.97	16.86	24.00	-7.14

Table 495 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU26 LPI	Duty Cycle (%):	49.3
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU26.0)	-7.99	-8.34	-	-	-5.15	4.87	-0.28	24.00	-24.28
6175 (RU26.0)	-6.82	-7.10	-	-	-3.95	3.64	-0.31	24.00	-24.31
6415 (RU26.8)	-8.05	-8.01	-	-	-5.02	4.50	-0.52	24.00	-24.52
6435 (RU26.0)	-8.86	-8.37	-	-	-5.60	4.85	-0.74	24.00	-24.74
6475 (RU26.0)	-8.94	-8.24	-	-	-5.56	4.85	-0.71	24.00	-24.71
6515 (RU26.8)	-9.20	-8.21	-	-	-5.67	4.85	-0.81	24.00	-24.81
6535 (RU26.0)	-8.97	-7.95	-	-	-5.42	4.56	-0.86	24.00	-24.86
6695 (RU26.0)	-9.69	-7.93	-	-	-5.71	4.56	-1.16	24.00	-25.16
6855 (RU26.8)	-9.46	-7.76	-	-	-5.52	4.56	-0.96	24.00	-24.96
6875 (RU26.3)	-8.61	-7.83	-	-	-5.19	4.56	-0.63	24.00	-24.63
6875 (RU26.5)	-8.38	-7.56	-	-	-4.94	4.56	-0.38	24.00	-24.38
6895 (RU26.0)	-8.64	-7.31	-	-	-4.91	3.97	-0.94	24.00	-24.94
6995 (RU26.0)	-7.92	-7.22	-	-	-4.54	3.97	-0.57	24.00	-24.57
7095 (RU26.8)	-7.02	-6.92	-	-	-3.96	3.97	0.02	24.00	-23.98

Table 496 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU52 LPI	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU52.37)	-5.07	-5.53	-	-	-2.29	4.87	2.59	24.00	-21.41
6175 (RU52.37)	-4.24	-4.53	-	-	-1.37	3.64	2.27	24.00	-21.73
6415 (RU52.40)	-5.28	-5.35	-	-	-2.30	4.50	2.20	24.00	-21.80
6435 (RU52.37)	-5.94	-5.47	-	-	-2.69	4.85	2.16	24.00	-21.84
6475 (RU52.37)	-6.28	-5.59	-	-	-2.91	4.85	1.94	24.00	-22.06
6515 (RU52.40)	-6.47	-5.55	-	-	-2.97	4.85	1.88	24.00	-22.12
6535 (RU52.37)	-6.30	-5.30	-	-	-2.76	4.56	1.80	24.00	-22.20
6695 (RU52.37)	-7.11	-5.27	-	-	-3.08	4.56	1.48	24.00	-22.52
6855 (RU52.40)	-6.52	-4.95	-	-	-2.65	4.56	1.90	24.00	-22.10
6875 (RU52.38)	-6.41	-4.79	-	-	-2.51	4.56	2.04	24.00	-21.96
6875 (RU52.39)	-6.49	-5.03	-	-	-2.69	4.56	1.87	24.00	-22.13
6895 (RU52.37)	-5.70	-4.43	-	-	-2.01	3.97	1.97	24.00	-22.03
6995 (RU52.37)	-4.98	-4.34	-	-	-1.64	3.97	2.33	24.00	-21.67
7095 (RU52.40)	-4.49	-4.44	-	-	-1.46	3.97	2.52	24.00	-21.48

Table 497 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU106 LPI	Duty Cycle (%):	98.7
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU106.53)	-2.18	-2.64	-	-	0.60	4.87	5.48	24.00	-18.52
6175 (RU106.53)	-1.03	-1.27	-	-	1.86	3.64	5.51	24.00	-18.49
6415 (RU106.54)	-2.17	-2.15	-	-	0.85	4.50	5.35	24.00	-18.65
6435 (RU106.53)	-2.88	-2.36	-	-	0.40	4.85	5.25	24.00	-18.75
6475 (RU106.53)	-3.22	-2.50	-	-	0.17	4.85	5.02	24.00	-18.98
6515 (RU106.54)	-3.33	-2.43	-	-	0.15	4.85	5.00	24.00	-19.00
6535 (RU106.53)	-3.17	-2.14	-	-	0.38	4.56	4.94	24.00	-19.06
6695 (RU106.53)	-3.96	-2.21	-	-	0.02	4.56	4.57	24.00	-19.43
6855 (RU106.54)	-3.43	-1.80	-	-	0.47	4.56	5.03	24.00	-18.97
6875 (RU106.53)	-3.08	-1.56	-	-	0.75	4.56	5.31	24.00	-18.69
6875 (RU106.54)	-2.82	-1.51	-	-	0.90	4.56	5.45	24.00	-18.55
6895 (RU106.53)	-2.52	-1.20	-	-	1.20	3.97	5.17	24.00	-18.83
6995 (RU106.53)	-1.94	-1.27	-	-	1.42	3.97	5.39	24.00	-18.61
7095 (RU106.54)	-1.80	-1.65	-	-	1.28	3.97	5.26	24.00	-18.74

Table 498 - Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	5.925-6.425 GHz 6.425-6.525 GHz 6.525-6.875 GHz 6.875-7.125 GHz	Band:	U-NII-5 U-NII-6 U-NII-7 U-NII-8
Limit Clause(s):	15.407(a)(8) RSS-248 4.5.3	Test Method(s):	C63.10 12.4.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)d)(ii), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11be EHT20 RU Size 52 + RU Size 26 LPI	Duty Cycle (%):	97.5
Modulation Coding Scheme:	MCS2x2	DCCF (dB):	-
Antenna Configuration:	MIMO SDM	Peak Antenna Gain (dBi):	4.87
Active Port(s):	A+B (Core 0 + Core 1)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ				
5955 (RU Size 52 + RU Size 26.70)	-3.29	-3.27	-	-	-0.27	4.87	4.60	24.00	-19.40
6175 (RU Size 52 + RU Size 26.70)	-2.27	-1.95	-	-	0.90	3.64	4.55	24.00	-19.45
6415 (RU Size 52 + RU Size 26.72)	-3.58	-3.31	-	-	-0.43	4.50	4.07	24.00	-19.93
6435 (RU Size 52 + RU Size 26.70)	-4.12	-3.38	-	-	-0.72	4.85	4.13	24.00	-19.87
6475 (RU Size 52 + RU Size 26.70)	-4.28	-3.40	-	-	-0.81	4.85	4.04	24.00	-19.96
6515 (RU Size 52 + RU Size 26.72)	-4.68	-3.55	-	-	-1.07	4.85	3.78	24.00	-20.22
6535 (RU Size 52 + RU Size 26.70)	-4.59	-3.23	-	-	-0.85	4.56	3.71	24.00	-20.29
6695 (RU Size 52 + RU Size 26.70)	-5.34	-3.34	-	-	-1.22	4.56	3.34	24.00	-20.66
6855 (RU Size 52 + RU Size 26.72)	-4.73	-3.23	-	-	-0.90	4.56	3.65	24.00	-20.35
6875 (RU Size 52 + RU Size 26.70)	-4.43	-2.91	-	-	-0.59	4.56	3.96	24.00	-20.04
6875 (RU Size 52 + RU Size 26.72)	-4.08	-2.75	-	-	-0.35	4.56	4.20	24.00	-19.80
6895 (RU Size 52 + RU Size 26.70)	-4.15	-2.65	-	-	-0.33	3.97	3.65	24.00	-20.35
6995 (RU Size 52 + RU Size 26.70)	-3.53	-2.66	-	-	-0.06	3.97	3.91	24.00	-20.09
7095 (RU Size 52 + RU Size 26.72)	-2.92	-2.47	-	-	0.32	3.97	4.29	24.00	-19.71

Table 499 - Maximum Conducted (average) Output Power Results