


Channel Power Plots


Duty_Cycle: 97.83% DCCF: 0.095dB



12:37:44 PM 05/22/2026

Plot 7-750. Channel Power – UNII 5 – 20 MHz

Duty_Cycle: 97.83% DCCF: 0.095dB



12:38:47 PM 05/22/2026


Plot 7-751. Channel Power – UNII 5 – 160 MHz - Low

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 228 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



12:39:27 PM 05/22/2026

Plot 7-752. Channel Power – UNII 5 – 160 MHz – Mid

Duty_Cycle: 97.83% DCCF: 0.095dB



12:40:28 PM 05/22/2026


Plot 7-753. Channel Power – UNII 5 – 160 MHz - High

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 229 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



12:41:15 PM 05/22/2026

Plot 7-754. Channel Power – UNII 6 – 20 MHz

Duty_Cycle: 97.83% DCCF: 0.095dB



12:42:06 PM 05/22/2026


Plot 7-755. Channel Power – UNII 6 – 160 MHz - Low

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 230 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



12:42:51 PM 05/22/2026

Plot 7-756. Channel Power – UNII 6 – 160 MHz – Mid

Duty_Cycle: 97.83% DCCF: 0.095dB



12:44:42 PM 05/22/2026


Plot 7-757. Channel Power – UNII 6 – 160 MHz - High

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 231 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



12:46:53 PM 05/22/2026

Plot 7-758. Channel Power – UNII 7 – 20 MHz

Duty_Cycle: 97.83% DCCF: 0.095dB



12:48:15 PM 05/22/2026


Plot 7-759. Channel Power – UNII 7 – 160 MHz - Low

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 232 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



12:50:07 PM 05/22/2026

Plot 7-760. Channel Power – UNII 7 – 160 MHz – Mid

Duty_Cycle: 97.83% DCCF: 0.095dB



12:51:30 PM 05/22/2026


Plot 7-761. Channel Power – UNII 7 – 160 MHz - High

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 233 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



12:53:48 PM 05/22/2026

Plot 7-762. Channel Power – UNII 8 – 20 MHz

Duty_Cycle: 97.83% DCCF: 0.095dB



12:55:36 PM 05/22/2026


Plot 7-763. Channel Power – UNII 8 – 160 MHz - Low

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 234 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



12:59:11 PM 05/22/2026

Plot 7-764. Channel Power – UNII 8 – 160 MHz – Mid

Duty_Cycle: 97.83% DCCF: 0.095dB



01:00:34 PM 05/22/2026

Plot 7-765. Channel Power – UNII 8 – 160 MHz - High


FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 235 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Contention-Based Protocol Timing Plots


Duty_Cycle: 97.83% DCCF: 0.095dB



03:19:44 PM 05/27/2026

Plot 7-766. Contention Based Protocol Timing Plot – UNII 5 – 20 MHz Channel 53

Duty_Cycle: 97.83% DCCF: 0.095dB



03:49:32 PM 05/27/2026


Plot 7-767. Contention Based Protocol Timing Plot – UNII 5 – 160 MHz Channel 47 – Low

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 236 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



04:29:04 PM 05/28/2026

Plot 7-768. Contention Based Protocol Timing Plot –UNII 5 – 160 MHz Channel 47 – Mid

Duty_Cycle: 97.83% DCCF: 0.095dB



04:28:05 PM 05/28/2026


Plot 7-769. Contention Based Protocol Timing Plot – UNII 5 – 160 MHz Channel 47 – High

FCC ID: BCGA3595 IC: 579C-A3595	element	Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 237 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



03:13:15 PM 05/27/2026

Plot 7-770. Contention Based Protocol Timing Plot – UNII 6 – 20 MHz Channel 101

Duty_Cycle: 97.83% DCCF: 0.095dB



01:47:30 PM 05/28/2026


Plot 7-771. Contention Based Protocol Timing Plot – UNII 6 – 160 MHz Channel 111 – Low

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 238 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



06:21:54 PM 05/27/2026

Plot 7-772. Contention Based Protocol Timing Plot – UNII 6 – 160 MHz Channel 111 – Mid

Duty_Cycle: 97.83% DCCF: 0.095dB



01:44:17 PM 05/28/2026


Plot 7-773. Contention Based Protocol Timing Plot – UNII 6 – 160 MHz Channel 111 – High

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 239 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



03:33:13 PM 05/27/2026

Plot 7-774. Contention Based Protocol Timing Plot – UNII 7 – 20 MHz Channel 149

Duty_Cycle: 97.83% DCCF: 0.095dB



04:19:35 PM 05/28/2026


Plot 7-775. Contention Based Protocol Timing Plot – UNII 7 – 160 MHz Channel 143 – Low

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 240 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



04:20:42 PM 05/28/2026

Plot 7-776. Contention Based Protocol Timing Plot – UNII 7 – 160 MHz Channel 143 – Mid

Duty_Cycle: 97.83% DCCF: 0.095dB



04:23:36 PM 05/28/2026


Plot 7-777. Contention Based Protocol Timing Plot – UNII 7 – 160 MHz Channel 143 – High

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 241 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



03:36:31 PM 05/27/2026

Plot 7-778. Contention Based Protocol Timing Plot – UNII 8 – 20 MHz Channel 197

Duty_Cycle: 97.83% DCCF: 0.095dB



02:29:56 PM 05/28/2026


Plot 7-779. Contention Based Protocol Timing Plot – UNII 8 – 160 MHz Channel 207 – Low

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 242 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Duty_Cycle: 97.83% DCCF: 0.095dB



02:31:45 PM 05/28/2026

Plot 7-780. Contention Based Protocol Timing Plot – UNII 8 – 160 MHz Channel 207 – Mid

Duty_Cycle: 97.83% DCCF: 0.095dB



02:33:09 PM 05/28/2026

Plot 7-781. Contention Based Protocol Timing Plot – UNII 8 – 160 MHz Channel 207 – High

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 243 of 469

V 12.0 03/03/2026


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

CBP Bandwidth Reduction Plots



12:13:00 PM 06/06/2026

Plot 7-782. 160 MHz Bandwidth, AWGN Signal Injected – 6110 MHz




12:04:16 PM 06/06/2026

Plot 7-783. 160 MHz Bandwidth, AWGN Signal Injected – 6185 MHz

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 244 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



12:01:26 PM 06/06/2026

Plot 7-784. 160 MHz Bandwidth, AWGN Signal Injected – 6260 MHz

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 245 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.7 Radiated Spurious Emissions – Above 1 GHz

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 and KDB 789033 D02 v02r01, and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

For transmitters operating in the 5.925-7.125 GHz band: All emissions outside of the 5.925-7.125 GHz band shall not exceed an EIRP of -27 dBm/MHz. Emissions found in a restricted band are subject to the limits of 15.209 and RSS-Gen (7.4.3) as shown in the table below.

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-104. Radiated Limits

Test Procedures Used

ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 – Sections 12.7.7, 12.7.6
KDB 789033 D02 v02r01 – Section G

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1 MHz
3. VBW = 3 MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1 MHz
3. VBW = 3 MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 246 of 469

V 12.0 03/03/2026

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 247 of 469

V 12.0 03/03/2026

Test Notes

1. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 and section 7.5 of RSS-Gen are below the limit shown in Table 7-104.
2. All spurious emissions lying in restricted bands specified in §15.205 and section 7.5 of RSS-Gen are below the limit shown in Table 7-104. All spurious emissions that do not lie in a restricted band are subject to a limit of -27 dBm/MHz. At a distance of 3 meters, the field strength limit in dB μ V/m can be determined by adding a "conversion" factor of 95.2 dB to the EIRP limit of -27 dBm/MHz to obtain the limit for out of band spurious emissions of 68.2 dB μ V/m.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The spectrum is measured from 9 kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1 GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas.
5. D is the measurement test distance and emissions 1-18 GHz were measured at a 3 meters test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
6. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20 dB of the limit are fully investigated and the results are shown in this section.
7. All data rates were investigated and only the worse case is reported
8. The unit was tested with all possible modes and only the highest emission is reported.
9. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
10. All radiated measurements were tested at the highest supported power setting per band.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level [dB μ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB] – Preamplifier Gain [dB]
- Margin [dB] = Field Strength Level [dB μ V/m] – Limit [dB μ V/m]

Radiated Band Edge Measurement Offset


- The amplitude offset shown in the radiated restricted band edge plots in Section 7.7.3 to 7.7.22 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 248 of 469

V 12.0 03/03/2026

7.7.1 SDM Primary Radiated Spurious Emission

RU26/52



Plot 7-785. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 33 – RU52)


Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6115 MHz
Channel: 33

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 12230.00	Average	H	-	-	-84.79	21.38	43.58	53.98	-10.40
* 12230.00	Peak	H	-	-	-73.01	21.38	55.36	73.98	-18.62


Table 7-105. Radiated Spurious Emission Measurements SDM Primary – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 249 of 469

V 12.0 03/03/2026



Plot 7-786. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 61 – RU52)




Plot 7-787. Radiated Spurious Emissions 18-40 GHz SDM Primary (802.11be – Ch. 61 – RU52)

Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6255 MHz
Channel:	61

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 12510.00	Average	H	-	-	-84.75	22.28	0.00	44.53	53.98	-9.45
* 12510.00	Peak	H	-	-	-73.64	22.28	0.00	55.64	73.98	-18.34
* 18765.00	Average	H	-	-	-63.77	-5.84	-9.54	27.85	53.98	-26.13
* 18765.00	Peak	H	-	-	-52.76	-5.84	-9.54	38.86	73.98	-35.12
25020.00	Average	H	-	-	-63.73	-4.38	-9.54	29.35	68.23	-38.88
25020.00	Peak	H	-	-	-51.73	-4.38	-9.54	41.35	88.23	-46.88
* 31275.00	Average	V	-	-	-64.84	-2.61	-9.54	30.01	53.98	-23.97
* 31275.00	Peak	V	-	-	-53.61	-2.61	-9.54	41.24	73.98	-32.74
37530.00	Average	H	-	-	-67.04	-4.28	-9.54	26.14	68.23	-42.09
37530.00	Peak	H	-	-	-56.77	-4.28	-9.54	36.41	88.23	-51.82

Table 7-106. Radiated Spurious Emission Measurements SDM Primary – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 250 of 469



Plot 7-788. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 93 – RU26)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6415 MHz
Channel:	93

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
12830.00	Average	V	-	-	-84.59	22.22	44.62	68.23	-23.61
12830.00	Peak	V	-	-	-73.24	22.22	55.98	88.23	-32.25

Table 7-107. Radiated Spurious Emission Measurements SDM Primary – RU26

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 251 of 469

V 12.0 03/03/2026



Plot 7-789. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 97 – RU52)


Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6435 MHz
Channel: 97

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
12870.00	Average	H	-	-	-84.69	22.49	44.80	68.23	-23.43
12870.00	Peak	H	-	-	-72.68	22.49	56.81	88.23	-31.42


Table 7-108. Radiated Spurious Emission Measurements SDM Primary – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 252 of 469

V 12.0 03/03/2026



Plot 7-790. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 105 – RU52)




Plot 7-791. Radiated Spurious Emissions 18-40 GHz SDM Primary (802.11be – Ch. 105 – RU52)

Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6475 MHz
Channel: 105

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
12950.00	Average	V	-	-	-85.01	22.56	0.00	44.56	68.23	-23.67
12950.00	Peak	V	-	-	-72.75	22.56	0.00	56.82	88.23	-31.41
* 19425.00	Average	V	-	-	-63.02	-5.91	-9.54	28.53	53.98	-25.45
* 19425.00	Peak	V	-	-	-51.48	-5.91	-9.54	40.08	73.98	-33.90
25900.00	Average	V	-	-	-63.78	-4.42	-9.54	29.26	68.23	-38.97
25900.00	Peak	V	-	-	-52.86	-4.42	-9.54	40.19	88.23	-48.04
32375.00	Average	V	-	-	-64.55	-3.19	-9.54	29.73	68.23	-38.50
32375.00	Peak	V	-	-	-53.11	-3.19	-9.54	41.16	88.23	-47.07
* 38850.00	Average	V	-	-	-67.28	-2.32	-9.54	27.86	53.98	-26.12
* 38850.00	Peak	V	-	-	-56.21	-2.32	-9.54	38.93	73.98	-35.05

Table 7-109. Radiated Spurious Emission Measurements SDM Primary – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 253 of 469



Plot 7-792. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 113 – RU52)


Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6515 MHz
Channel: 113

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13030.00	Average	V	-	-	-85.25	22.88	44.63	68.23	-23.60
13030.00	Peak	V	-	-	-73.88	22.88	55.99	88.23	-32.24

Table 7-110. Radiated Spurious Emission Measurements SDM Primary – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 254 of 469

V 12.0 03/03/2026




Plot 7-793. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 117 – RU52)

Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6535 MHz
Channel: 117


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13070.00	Average	H	-	-	-85.68	22.85	44.17	68.23	-24.06
13070.00	Peak	H	-	-	-73.59	22.85	56.26	88.23	-31.97

Table 7-111. Radiated Spurious Emission Measurements SDM Primary – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 255 of 469



Plot 7-794. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 149 – RU52)



Plot 7-795. Radiated Spurious Emissions 18-40 GHz SDM Primary (802.11be – Ch. 149 – RU52)

Mode: 802.11be

Data Rate: MCS0

Distance of Measurements: 3 Meters


Operating Frequency: 6695 MHz

Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 13390.00	Average	H	-	-	-85.12	22.68	0.00	44.56	53.98	-9.42
* 13390.00	Peak	H	-	-	-74.05	22.68	0.00	55.64	73.98	-18.34
* 20085.00	Average	H	-	-	-63.11	-6.21	-9.54	28.14	53.98	-25.84
* 20085.00	Peak	H	-	-	-52.05	-6.22	-9.54	39.19	73.98	-34.79
26780.00	Average	H	-	-	-64.54	-3.89	-9.54	29.04	68.23	-39.19
26780.00	Peak	H	-	-	-52.69	-3.89	-9.54	40.88	88.23	-47.35
33475.00	Average	H	-	-	-63.88	-3.58	-9.54	30.00	68.23	-38.23
33475.00	Peak	H	-	-	-52.31	-3.59	-9.54	41.56	88.23	-46.67

Table 7-112. Radiated Spurious Emission Measurements SDM Primary – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 256 of 469




Plot 7-796. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 185 – RU52)

Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6875 MHz
Channel: 185

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13750.00	Average	V	-	-	-85.65	22.63	43.98	68.23	-24.25
13750.00	Peak	V	-	-	-74.13	22.63	55.50	88.23	-32.73

Table 7-113. Radiated Spurious Emission Measurements SDM Primary – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 257 of 469



Plot 7-797. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 189 – RU52)


Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6895 MHz
Channel: 189

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13790.00	Average	V	-	-	-85.60	23.03	44.43	68.23	-23.80
13790.00	Peak	V	-	-	-74.53	23.03	55.50	88.23	-32.73


Table 7-114. Radiated Spurious Emission Measurements SDM Primary – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 258 of 469

V 12.0 03/03/2026



Plot 7-798. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 209 – RU52)




Plot 7-799. Radiated Spurious Emissions 18-40 GHz SDM Primary (802.11be – Ch. 209 – RU52)

Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6995 MHz
Channel: 209

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13990.00	Average	H	-	-	-85.66	22.86	0.00	44.20	68.23	-24.03
13990.00	Peak	H	-	-	-74.51	22.86	0.00	55.35	88.23	-32.88
* 20985.00	Average	H	-	-	-63.13	-5.84	-9.54	28.49	53.98	-25.49
* 20985.00	Peak	H	-	-	-51.51	-5.85	-9.54	40.11	73.98	-33.87
27980.00	Average	H	-	-	-64.81	-2.86	-9.54	29.79	68.23	-38.44
27980.00	Peak	H	-	-	-53.73	-2.86	-9.54	40.87	88.23	-47.36
34975.00	Average	H	-	-	-62.92	-4.85	-9.54	29.69	68.23	-38.54
34975.00	Peak	H	-	-	-51.86	-4.85	-9.54	40.75	88.23	-47.48

Table 7-115. Radiated Spurious Emission Measurements SDM Primary – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 259 of 469



Plot 7-800. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 229 – RU26)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	7095 MHz
Channel:	229

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
14190.00	Average	V	-	-	-85.84	23.76	44.92	68.23	-23.31
14190.00	Peak	V	-	-	-75.00	23.76	55.76	88.23	-32.47

Table 7-116. Radiated Spurious Emission Measurements SDM Primary – RU26

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 260 of 469

V 12.0 03/03/2026



Plot 7-801. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 33 – RU242)

Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6115 MHz
Channel:	33


	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	12230.00	Average	V	-	-	-83.69	18.09	41.41	53.98	-12.57
*	12230.00	Peak	V	-	-	-72.70	18.09	52.39	73.98	-21.59

Table 7-117. Radiated Spurious Emission Measurements SDM Primary – RU242

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 261 of 469



Plot 7-802. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 61 – RU242)




Plot 7-803. Radiated Spurious Emissions 18-40 GHz SDM Primary (802.11be – Ch. 61 – RU242)

Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6255 MHz
Channel:	61

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 12510.00	Average	H	-	-	-84.28	18.60	0.00	41.33	53.98	-12.65
* 12510.00	Peak	H	-	-	-73.06	18.60	0.00	52.54	73.98	-21.44
* 18765.00	Average	H	-	-	-63.55	-5.83	-9.54	28.08	53.98	-25.90
* 18765.00	Peak	H	-	-	-52.09	-5.83	-9.54	39.54	73.98	-34.44
25020.00	Average	H	-	-	-63.42	-4.40	-9.54	29.64	68.23	-38.59
25020.00	Peak	H	-	-	-52.54	-4.40	-9.54	40.52	88.23	-47.71
* 31275.00	Average	V	-	-	-64.42	-2.61	-9.54	30.43	53.98	-23.55
* 31275.00	Peak	V	-	-	-53.43	-2.61	-9.54	41.42	73.98	-32.56
37530.00	Average	H	-	-	-66.41	-4.28	-9.54	26.77	68.23	-41.46
37530.00	Peak	H	-	-	-55.12	-4.28	-9.54	38.06	88.23	-50.17

Table 7-118. Radiated Spurious Emission Measurements SDM Primary – RU242

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 262 of 469



Plot 7-804. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 93 – RU242)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6415 MHz
Channel:	93

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
12830.00	Average	H	-	-	-84.01	19.01	42.00	68.23	-26.23
12830.00	Peak	H	-	-	-72.85	19.01	53.16	88.23	-35.07

Table 7-119. Radiated Spurious Emission Measurements SDM Primary – RU242

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 263 of 469

V 12.0 03/03/2026



Plot 7-805. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 97 – RU242)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6435 MHz
Channel:	97

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
12870.00	Average	H	-	-	-83.97	18.96	41.99	68.23	-26.24
12870.00	Peak	H	-	-	-72.75	18.96	53.21	88.23	-35.02


Table 7-120. Radiated Spurious Emission Measurements SDM Primary – RU242

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 264 of 469

V 12.0 03/03/2026



Plot 7-806. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 105 – RU242)




Plot 7-807. Radiated Spurious Emissions 18-40 GHz SDM Primary (802.11be – Ch. 105 – RU242)

Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6475 MHz
Channel:	105

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
12950.00	Average	V	-	-	-84.51	19.33	0.00	41.82	68.23	-26.41
12950.00	Peak	V	-	-	-73.09	19.33	0.00	53.24	88.23	-34.99
* 19425.00	Average	V	-	-	-62.83	-5.95	-9.54	28.68	53.98	-25.30
* 19425.00	Peak	V	-	-	-51.88	-5.95	-9.54	39.62	73.98	-34.36
25900.00	Average	V	-	-	-63.62	-4.45	-9.54	29.39	68.23	-38.84
25900.00	Peak	V	-	-	-52.86	-4.45	-9.54	40.14	88.23	-48.09
32375.00	Average	V	-	-	-64.29	-3.19	-9.54	29.98	68.23	-38.25
32375.00	Peak	V	-	-	-53.14	-3.19	-9.54	41.13	88.23	-47.10
* 38850.00	Average	V	-	-	-65.64	-2.32	-9.54	29.50	53.98	-24.48
* 38850.00	Peak	V	-	-	-54.52	-2.32	-9.54	40.62	73.98	-33.36

Table 7-121. Radiated Spurious Emission Measurements SDM Primary – RU242

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 265 of 469



Plot 7-808. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 113 – RU242)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6515 MHz
Channel:	113

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13030.00	Average	V	-	-	-84.35	19.29	41.95	68.23	-26.28
13030.00	Peak	V	-	-	-72.88	19.29	53.42	88.23	-34.81

Table 7-122. Radiated Spurious Emission Measurements SDM Primary – RU242

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 266 of 469

V 12.0 03/03/2026



Plot 7-809. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 117 – RU242)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6535 MHz
Channel:	117

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13070.00	Average	V	-	-	-84.42	19.42	41.99	68.23	-26.24
13070.00	Peak	V	-	-	-72.71	19.42	53.70	88.23	-34.53


Table 7-123. Radiated Spurious Emission Measurements SDM Primary – RU242

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 267 of 469

V 12.0 03/03/2026



Plot 7-810. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 149 – RU242)




Plot 7-811. Radiated Spurious Emissions 18-40 GHz SDM Primary (802.11be – Ch. 149 – RU242)

Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6695 MHz
Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 13390.00	Average	V	-	-	-83.99	19.39	0.00	42.40	53.98	-11.58
* 13390.00	Peak	V	-	-	-72.13	19.39	0.00	54.26	73.98	-19.72
* 20085.00	Average	V	-	-	-62.91	-6.22	-9.54	28.33	53.98	-25.65
* 20085.00	Peak	V	-	-	-52.15	-6.22	-9.54	39.09	73.98	-34.89
26780.00	Average	V	-	-	-64.32	-3.81	-9.54	29.33	68.23	-38.90
26780.00	Peak	V	-	-	-52.79	-3.81	-9.54	40.86	88.23	-47.37
33475.00	Average	V	-	-	-63.21	-3.59	-9.54	30.66	68.23	-37.57
33475.00	Peak	V	-	-	-52.54	-3.59	-9.54	41.33	88.23	-46.90

Table 7-124. Radiated Spurious Emission Measurements SDM Primary – RU242

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 268 of 469



Plot 7-812. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 185 – RU242)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6875 MHz
Channel:	185

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13750.00	Average	H	-	-	-83.89	19.22	42.33	68.23	-25.90
13750.00	Peak	H	-	-	-72.74	19.22	53.48	88.23	-34.75

Table 7-125. Radiated Spurious Emission Measurements SDM Primary – RU242

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 269 of 469

V 12.0 03/03/2026



Plot 7-813. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 189 – RU242)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6895 MHz
Channel:	189

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13790.00	Average	V	-	-	-84.20	19.02	41.81	68.23	-26.42
13790.00	Peak	V	-	-	-72.46	19.02	53.55	88.23	-34.68


Table 7-126. Radiated Spurious Emission Measurements SDM Primary – RU242

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 270 of 469

V 12.0 03/03/2026



Plot 7-814. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 209 – RU242)




Plot 7-815. Radiated Spurious Emissions 18-40 GHz SDM Primary (802.11be – Ch. 209 – RU242)

Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6995 MHz
Channel:	209

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
13990.00	Average	H	-	-	-84.38	19.53	0.00	42.15	68.23	-26.08
13990.00	Peak	H	-	-	-71.94	19.53	0.00	54.60	88.23	-33.63
* 20985.00	Average	H	-	-	-62.72	-5.87	-9.54	28.88	53.98	-25.10
* 20985.00	Peak	H	-	-	-50.57	-5.87	-9.54	41.03	73.98	-32.95
27980.00	Average	H	-	-	-64.55	-2.86	-9.54	30.04	68.23	-38.19
27980.00	Peak	H	-	-	-53.25	-2.86	-9.54	41.35	88.23	-46.88
34975.00	Average	H	-	-	-62.78	-4.82	-9.54	29.86	68.23	-38.37
34975.00	Peak	H	-	-	-51.50	-4.82	-9.54	41.14	88.23	-47.09

Table 7-127. Radiated Spurious Emission Measurements SDM Primary – RU242

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 271 of 469



Plot 7-816. Radiated Spurious Emissions above 1 GHz SDM Primary (802.11be – Ch. 233 – RU242)

Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	7115 MHz
Channel:	233


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
14230.00	Average	V	-	-	-84.31	19.58	42.27	68.23	-25.96
14230.00	Peak	V	-	-	-72.99	19.58	53.59	88.23	-34.64

Table 7-128. Radiated Spurious Emission Measurements SDM Primary – RU242

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 272 of 469

7.7.2 SDM Diversity Radiated Spurious Emission

RU26/52



Plot 7-817. Radiated Spurious Emissions above 1 GHz SDM Diversity (802.11be – Ch. 33 – RU52)


Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6115 MHz
Channel:	33

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 12230.00	Average	V	-	-	-84.98	21.16	43.18	53.98	-10.80
* 12230.00	Peak	V	-	-	-73.34	21.16	54.82	73.98	-19.16


Table 7-129. Radiated Spurious Emission Measurements SDM Diversity – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 273 of 469

V 12.0 03/03/2026



Plot 7-818. Radiated Spurious Emissions above 1 GHz SDM Diversity (802.11be – Ch. 61 – RU52)




Plot 7-819. Radiated Spurious Emissions 18-40 GHz SDM Diversity (802.11be – Ch. 61 – RU52)

Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6255 MHz
Channel: 61

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 12510.00	Average	H	-	-	-84.60	22.28	0.00	44.69	53.98	-9.29
* 12510.00	Peak	H	-	-	-72.89	22.28	0.00	56.40	73.98	-17.58
* 18765.00	Average	H	-	-	-63.79	-5.84	-9.54	27.83	53.98	-26.15
* 18765.00	Peak	H	-	-	-52.10	-5.84	-9.54	39.52	73.98	-34.46
* 25020.00	Average	H	-	-	-63.67	-4.40	-9.54	29.39	68.23	-38.84
* 25020.00	Peak	H	-	-	-52.16	-4.40	-9.54	40.90	88.23	-47.33
* 31275.00	Average	V	-	-	-64.86	-2.61	-9.54	29.99	53.98	-23.99
* 31275.00	Peak	V	-	-	-53.09	-2.61	-9.54	41.76	73.98	-32.22
* 37530.00	Average	V	-	-	-67.37	-4.28	-9.54	25.81	68.23	-42.42
* 37530.00	Peak	V	-	-	-56.75	-4.28	-9.54	36.43	88.23	-51.80

Table 7-130. Radiated Spurious Emission Measurements SDM Diversity – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		
				Page 274 of 469




Plot 7-820. Radiated Spurious Emissions above 1 GHz SDM Diversity (802.11be – Ch. 93 – RU26)

Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6415 MHz
Channel:	93

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
12830.00	Average	H	-	-	-84.60	22.48	44.88	68.23	-23.35
12830.00	Peak	H	-	-	-73.06	22.48	56.42	88.23	-31.81

Table 7-131. Radiated Spurious Emission Measurements SDM Diversity – RU26

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 275 of 469



Plot 7-821. Radiated Spurious Emissions above 1 GHz SDM Diversity (802.11be – Ch. 97 – RU52)


Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6435 MHz
Channel: 97

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
12870.00	Average	H	-	-	-84.50	22.61	45.11	68.23	-23.12
12870.00	Peak	H	-	-	-73.73	22.61	55.88	88.23	-32.35


Table 7-132. Radiated Spurious Emission Measurements SDM Diversity – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 276 of 469

V 12.0 03/03/2026



Plot 7-822. Radiated Spurious Emissions above 1 GHz SDM Diversity (802.11be – Ch. 105 – RU52)




Plot 7-823. Radiated Spurious Emissions 18-40 GHz SDM Diversity (802.11be – Ch. 105 – RU52)

Mode:	802.11be
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6475 MHz
Channel:	105

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
12950.00	Average	H	-	-	-84.57	22.58	0.00	45.01	68.23	-23.22
12950.00	Peak	H	-	-	-73.31	22.58	0.00	56.28	88.23	-31.95
* 19425.00	Average	H	-	-	-62.92	-5.91	-9.54	28.63	53.98	-25.35
* 19425.00	Peak	H	-	-	-51.67	-5.95	-9.54	39.84	73.98	-34.14
25900.00	Average	H	-	-	-64.19	-4.39	-9.54	28.89	68.23	-39.34
25900.00	Peak	H	-	-	-52.53	-4.45	-9.54	40.48	88.23	-47.75
32375.00	Average	H	-	-	-64.40	-3.25	-9.54	29.81	68.23	-38.42
32375.00	Peak	H	-	-	-52.97	-3.19	-9.54	41.30	88.23	-46.93
* 38850.00	Average	H	-	-	-67.10	-2.32	-9.54	28.04	53.98	-25.94
* 38850.00	Peak	H	-	-	-56.29	-2.32	-9.54	38.85	73.98	-35.13

Table 7-133. Radiated Spurious Emission Measurements SDM Diversity – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 277 of 469



Plot 7-824. Radiated Spurious Emissions above 1 GHz SDM Diversity (802.11be – Ch. 113 – RU52)

Mode: 802.11be
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6515 MHz
Channel: 113

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13030.00	Average	H	-	-	-84.89	22.88	44.99	68.23	-23.24
13030.00	Peak	H	-	-	-73.33	22.88	56.54	88.23	-31.69

Table 7-134. Radiated Spurious Emission Measurements SDM Diversity – RU52

FCC ID: BCGA3595 IC: 579C-A3595		Test Dates: 5/12/2026 - 7/15/2026	EUT Type: Tablet Device	Approved by: Technical Manager
Test Report S/N: 1C2604030025-14-R2.BCG		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 278 of 469

V 12.0 03/03/2026