

# FCC MPE REPORT

## FCC Certification

**Applicant Name:**  
LG Electronics USA**Address:**  
1000 Sylvan Avenue Englewood Cliffs, NJ 07632  
  
United States**Date of Issue:**

July 7, 2016

**Test Site/Location:**

HCT CO., LTD., 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

**Report No.:** HCT-R-1607-E004**HCT FRN:** 0005866421**IC Recognition No.:** 5944A-5**FCC ID:** BEJ-ISC61-V1**APPLICANT:** LG Electronics USA**Model(s):** ISC61G-ZB**EUT Type:** Smart ThinQ Sensor**Frequency Range:** 2405 MHz -2480 MHz (Zigbee Mode)

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)



**Report prepared by**  
: Seoul Ki Lee  
**Test engineer of RF Team**



**Approved by**  
: Jong Seok Lee  
**Manager of RF Team**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## Version

| TEST REPORT NO. | DATE         | DESCRIPTION             |
|-----------------|--------------|-------------------------|
| HCT-R-1607-E004 | July 7, 2016 | - First Approval Report |
|                 |              |                         |
|                 |              |                         |
|                 |              |                         |
|                 |              |                         |

## RF Exposure Statement

### 1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

#### (B) Limits for General Population/Uncontrolled Exposures

| Frequency range<br>(MHz) | Electric field<br>Strength (V/m) | Magnetic field<br>Strength (A/m) | Power density<br>(mW/cm <sup>2</sup> ) | Averaging time<br>(minutes) |
|--------------------------|----------------------------------|----------------------------------|----------------------------------------|-----------------------------|
| 0.3 - 1.34.....          | 614                              | 1.63                             | *(100)                                 | 30                          |
| 1.34 - 30.....           | 824/f                            | 2.19/f                           | *(180/ f <sup>2</sup> )                | 30                          |
| 30 - 300.....            | 27.5                             | 0.073                            | 0.2                                    | 30                          |
| 300 - 1500.....          | .....                            | .....                            | f/1500                                 | 30                          |
| 1500 - 100.000.....      | .....                            | .....                            | 1.0                                    | 30                          |

F = frequency in MHz

\* = Plane-wave equivalent power density

### 2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

### 3. RESULTS

#### **\*. Zigbee Mode**

|                                                             |            |                    |
|-------------------------------------------------------------|------------|--------------------|
| Max Peak output Power at antenna input terminal             | 17.016     | dBm                |
| Max Peak output Power at antenna input terminal             | 50.304     | mW                 |
| Prediction distance                                         | 20.00000   | cm                 |
| Prediction frequency                                        | 2405.00000 | MHz                |
| Antenna Gain(Peak)                                          | 2.76000    | dBi                |
| Antenna Gain(numeric)                                       | 1.88799    | -                  |
| Power density at prediction frequency (S)                   | 0.018894   | mW/cm <sup>2</sup> |
| MPE limit for uncontrolled exposure at prediction frequency | 1.00000    | mW/cm <sup>2</sup> |