

RF TEST REPORT

Test item : DIGITAL CAR AVN SYSTEM
Model No. : LNN2010IWUM
Order No. : DTNC1507-03656
Date of receipt : 2015-07-22
Test duration : 2015-07-24 ~ 2015-07-30
Date of issue : 2015-08-13
Use of report : FCC Original Grant

Applicant : LG Electronics USA
1000 Sylvan Avenue Englewood Cliffs, New Jersey, 07632, United States

Test laboratory : DT&C Co., Ltd.
42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 449-935

Test specification : FCC Part 15 Subpart C.247
RSS-247 Issue 1 (2015-05)
RSS-GEN Issue 4 (2014-11)
Test environment : See appended test report
Test result : ☒ Pass ☐ Fail

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DT&C Co., Ltd.

Tested by :



Engineer
Jaejin Lee

Reviewed by :



Technical Manager
GeunKi Son

Test Report Version

Test Report No.	Date	Description
DRTFCC1508-0180	Aug. 13, 2015	Initial issue

Table of Contents

1. General Information	4
1.1 Testing Laboratory	4
1.2 Details of Applicant	4
1.3 Description of EUT	4
1.4 Declaration by the applicant / manufacturer	5
1.5 Information about the FHSS characteristics	5
1.6 Test conditions	5
1.7 Test Equipment List.....	6
1.8 Summary of Test Results	7
1.9 Conclusion of worst-case and operation mode	8
2. Maximum Peak Output Power Measurement	9
2.1 Test Setup.....	9
2.2 Limit	9
2.3 Test Procedure.....	9
2.4 Test Results.....	10
3. 20 dB BW.....	16
3.1 Test Setup.....	16
3.2 Limit	16
3.3 Test Procedure.....	16
3.4 Test Results.....	16
4. Carrier Frequency Separation.....	22
4.1 Test Setup.....	22
4.2 Limit	22
4.3 Procedure.....	22
4.4 Test Results.....	22
5. Number of Hopping Frequencies	27
5.1 Test Setup.....	27
5.2 Limit	27
5.3 Procedure.....	27
5.4 Test Results.....	27
6. Time of Occupancy (Dwell Time).....	33
6.1 Test Setup.....	33
6.2 Limit	33
6.3 Test Procedure.....	33
6.4 Test Results.....	33
7. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission	38
7.1 Test Setup.....	38
7.2 Limit	38
7.3. Test Procedures	39
7.3.1. Test Procedures for Radiated Spurious Emissions	39
7.3.2. Test Procedures for Conducted Spurious Emissions	39
7.4. Test Results.....	40
7.4.1. Radiated Emissions.....	40
7.4.2. Conducted Spurious Emissions.....	44
8. Transmitter AC Power Line Conducted Emission	68
8.1 Test Setup.....	68
8.2 Limit	68
8.3 Test Procedures	68
8.4 Test Results.....	68
9. Antenna Requirement	69
10. Occupied Bandwidth (99 %).....	70
10.1 Test Setup.....	70
10.2 Limit	70
10.3 Test Procedure	70
10.4 Test Results.....	70
APPENDIX I	71

1. General Information

1.1 Testing Laboratory

DT&C Co., Ltd.			
Standard		Site number	Address
FCC	☒	165783	42, Yurim-ro 154 beon-gil, Cheoin -gu, Yongin-si, Gyeonggi -do, South Korea 449-935
	☐	804488	42, Yurim-ro 154 beon-gil, Cheoin -gu, Yongin-si, Gyeonggi -do, South Korea 449-935
	☐	596748	42, Yurim-ro 154 beon-gil, Cheoin -gu, Yongin-si, Gyeonggi -do, South Korea 449-935
	☐	678747	683-3, Yubang-dong, Cheoin-gu, Yongin-si, Kyeonggi-do, Korea, 449-080
IC	☐	5740A-3	42, Yurim-ro 154 beon-gil, Cheoin -gu, Yongin-si, Gyeonggi -do, South Korea 449-935
	☐	5740A-2	683-3, Yubang-dong, Cheoin-gu, Yongin-si, Kyeonggi-do, Korea, 449-080
www.dtnc.net			
Telephone	:	+ 82-31-321-2664	
FAX	:	+ 82-31-321-1664	

1.2 Details of Applicant

Applicant : LG Electronics USA
 Address : 1000 Sylvan Avenue Englewood Cliffs, New Jersey, 07632, United States
 Contact person : Jongchul Lee

1.3 Description of EUT

EUT	DIGITAL CAR AVN SYSTEM
Model Name	LNN2010IWUM
Serial Number	Identical prototype
Hardware version	1.0
Software version	506121
Power Supply	DC 14.4 V
Battery type	NA
Frequency Range	2402 MHz ~ 2480 MHz
Modulation Technique	GFSK, $\pi/4$ -DQPSK, 8DPSK
Number of Channels	79
Antenna Type	Internal Antenna
Antenna Gain	PK : 3.50 dBi

1.4 Declaration by the applicant / manufacturer

- NA

1.5 Information about the FHSS characteristics

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following :
 - A) The hopping sequence is pseudorandom
 - B) All channels are used equally on average
 - C) The receiver input bandwidth equals the transmit bandwidth
 - D) The receiver hops in sequence with the transmit signal
- 15.247(g) : In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h) : In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection / hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h) : The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

1.6 Test conditions

Ambient Condition	
▪ Temperature	+21 °C ~ +24 °C
▪ Relative Humidity	34 % ~ 42 %

1.7 Test Equipment List

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	14/09/15	15/09/15	MY50200867
BlueTooth Tester	TESCOM	TC-3000C	15/02/26	16/02/26	3000C000396
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2495A	14/10/07	15/10/07	1435003
		MA2490A			1409034
Digital Multimeter	FLUKE	17B	15/04/27	16/04/27	26030065WS
Thermohygrometer	BODYCOM	BJ5478	15/02/26	16/02/26	1209
Dynamic Measurement DC Source	Agilent Technologies	66332A	15/01/22	16/01/22	US37471368
Signal Generator	Rohde Schwarz	SMF100A	15/06/29	16/06/29	102341
Vector Signal Generator	Rohde Schwarz	SMBV100A	15/01/06	16/01/06	255571
3dB Attenuator	SMAJK	SMAJK-2-3	14/10/21	15/10/21	3
High-pass filter	Wainwright	WHKX12-2580- 3000-18000-80SS	14/09/11	15/09/11	3
High-pass filter	Wainwright	WHNX8.5	14/09/11	15/09/11	1
Low Noise Pre Amplifier	TSJ	MLA-010K01-B01- 27	15/04/09	16/04/09	1844538
Amplifier	Agilent Technologies	8449B	14/11/06	15/11/06	3008A02108
PreAmplifier	A.H. SYSTEMS	PAM-1840VH	14/12/12	15/12/12	163
Loop Antenna	Rohde Schwarz	FMZB1513	14/04/29	16/04/29	1513-128
TRILOG Broadband Test-Antenna	Schwarzbeck	VULB 9160	14/04/04	16/04/04	3357
HORN ANT	ETS	3115	15/02/09	17/02/09	21097
HORN ANT	A.H.Systems	SAS-574	15/04/30	17/04/30	154
EMI TEST RECEIVER	Rohde Schwarz	ESR7	14/10/21	15/10/21	101109

1.8 Summary of Test Results

FCC Part RSS Std.	Parameter	Limit (Using in 2400~ 2483.5 MHz)	Test Condition	Status Note 1
15.247(a) RSS-247(5.1)	Carrier Frequency Separation	>= 20 dB BW or >= Two thirds of the 20 dB BW, whichever is greater.	Conducted	C
	Number of Hopping Frequencies	>= 15 hops		C
	20 dB Bandwidth	None		C
	Dwell Time	=< 0.4 seconds		C
15.247(b) RSS-247(5.4)	Transmitter Output Power	For FCC =< 1 Watt , if CHs >= 75 Others =< 0.125 W For IC if CHs >= 75 =< 1 Watt For Conducted Power =< 4 Watt For e.i.r.p, Others =< 0.125 W For Conducted Power. =< 0.5 Watt For e.i.r.p		C
15.247(d) RSS-247(5.5)	Conducted Spurious Emissions	The radiated emission to any 100 kHz of out-band shall be at least 20 dB below the highest in-band spectral density.	Radiated	C
RSS Gen(6.6)	Occupied Bandwidth (99 %)	RSS-Gen		NA
15.205 & 209 RSS-247(5.5) RSS-Gen (8.9 & 8.10)	Radiated Spurious Emissions	FCC 15.209 Limits RSS-Gen 8.9		C <i>Note2</i>
15.207 RSS-Gen(8.8)	AC Conducted Emissions	FCC 15.207 Limits	AC Line Conducted	NA <i>Note3</i>
15.203 RSS-Gen(6.7)	Antenna Requirements	FCC 15.203	-	C
Note 1 : C = Comply NC = Not Comply NT = Not Tested NA = Not Applicable Note 2 : This test item was performed in each axis and the worst case data was reported. Note 3: This device is installed in a car. Therefore the power source is a battery of car. Note 4 : The sample was tested according to the following specifications : - ANSI C63.10-2013				

1.9 Conclusion of worst-case and operation mode

The EUT has three type of modulation (GFSK, $\pi/4$ DQPSK and 8DPSK).

Therefore all applicable requirements were tested with all the modulations.

The field strength of spurious emission was measured in three orthogonal EUT positions (X-axis, Y-axis and Z-axis).

Tested frequency information,

- Hopping Function : Enable

	TX Frequency (MHz)	RX Frequency (MHz)
Hopping Band	2402 ~ 2480	2402 ~ 2480

- Hopping Function : Disable

	TX Frequency (MHz)	RX Frequency (MHz)
Lowest Channel	2402	2402
Middle Channel	2441	2441
Highest Channel	2480	2480

2. Maximum Peak Output Power Measurement

2.1 Test Setup

Refer to the APPENDIX I.

2.2 Limit

■ FCC Requirements

The maximum peak output power of the intentional radiator shall not exceed the following :

1. §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
2. §15.247(b)(1), For frequency hopping systems operating in the 2400 – 2483.5 MHz employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725 – 5805 MHz band : 1 Watt.

■ IC Requirements

1. RSS-247(5.4), For FHSs operating in the band 2400 - 2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels the maximum peak conducted output power shall not exceed 0.125 W and the e.i.r.p. shall not exceed 0.5 W if the hopset uses less than 75 hopping channels

2.3 Test Procedure

1. The RF output power was measured with a spectrum analyzer connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency, A spectrum analyzer was used to record the shape of the transmit signal.
2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using ;
Span = approximately 5 times of the 20 dB bandwidth, centered on a hopping channel
RBW $\geq$ 20 dB BW
VBW $\geq$ RBW
Sweep = auto
Detector function = peak
Trace = max hold


2.4 Test Results

Modulation	Tested Channel	Frame Average Output Power		Peak Output Power	
		dBm	mW	dBm	mW
<u>GFSK</u>	Lowest	-2.53	0.558	-1.03	0.789
	Middle	-2.04	0.625	-0.37	0.917
	Highest	-2.14	0.611	-0.68	0.855
<u>$\pi/4$DQPSK</u>	Lowest	-5.54	0.279	-1.42	0.721
	Middle	-4.65	0.343	-0.75	0.841
	Highest	-4.89	0.324	-1.05	0.786
<u>8DPSK</u>	Lowest	-5.51	0.281	-0.89	0.815
	Middle	-4.62	0.345	-0.21	0.953
	Highest	-4.88	0.325	-0.52	0.887


Note 1 : Average output power was using the average power meter for reference only.

Note 2 : See next pages for actual measured spectrum plots.


Peak Output Power

Lowest Channel & Modulation : GFSK


Peak Output Power

Middle Channel & Modulation : GFSK

Peak Output Power

Highest Channel & Modulation : GFSK


Peak Output Power

Lowest Channel & Modulation : $\pi/4$ DQPSK


Middle Channel & Modulation : $\pi/4$ DQPSK

Highest Channel & Modulation : $\pi/4$ DQPSK


Peak Output Power

Lowest Channel & Modulation : 8DPSK

Peak Output Power

Middle Channel & Modulation : 8DPSK

Peak Output Power

Highest Channel & Modulation : 8DPSK

3. 20 dB BW

3.1 Test Setup

Refer to the APPENDIX I.

3.2 Limit

Limit : Not Applicable

3.3 Test Procedure

1. The 20 dB bandwidth were measured with a spectrum analyzer connected to RF antenna Connector (conducted measurement) while EUT was operating in transmit mode. The analyzer center frequency was set to the EUT carrier frequency, using the analyzer.
2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using $RBW \geq 1\%$ of the 20 dB bandwidth, $VBW \geq RBW$, Span = 3 MHz.

3.4 Test Results

Modulation	Tested Channel	20 dB BW (MHz)
<u>GFSK</u>	Lowest	0.930
	Middle	0.930
	Highest	0.930
<u>$\pi/4$DQPSK</u>	Lowest	1.320
	Middle	1.317
	Highest	1.323
<u>8DPSK</u>	Lowest	1.302
	Middle	1.302
	Highest	1.296

Note 1 : See next pages for actual measured spectrum plots.

20 dB Bandwidth

Lowest Channel & Modulation : GFSK

20 dB Bandwidth

Middle Channel & Modulation : GFSK

20 dB Bandwidth

Highest Channel & Modulation : GFSK

20 dB Bandwidth

Lowest Channel & Modulation : $\pi/4$ DQPSK

20 dB Bandwidth

Middle Channel & Modulation : $\pi/4$ DQPSK

20 dB Bandwidth

Highest Channel & Modulation : $\pi/4$ DQPSK

20 dB Bandwidth

Lowest Channel & Modulation : 8DPSK

20 dB Bandwidth

Middle Channel & Modulation : 8DPSK

20 dB Bandwidth

Highest Channel & Modulation : 8DPSK

4. Carrier Frequency Separation

4.1 Test Setup

Refer to the APPENDIX I.

4.2 Limit

Limit : ≥ 20 dB BW or $\geq$ Two-Thirds of the 20 dB BW

4.3 Procedure

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to :

Span = wide enough to capture the peaks of two adjacent channels

RBW = 1 % of the span

Sweep = auto

VBW = $\geq$ RBW

Detector function = peak

Trace = max hold

4.4 Test Results

FH mode

Hopping Mode	Test Mode	Peak of center channel (MHz)	Peak of adjacent Channel (MHz)	Test Result (MHz)
Enable	GFSK	2440.958	2441.961	1.003
	$\pi/4$ -DQPSK	2440.964	2441.970	1.006
	8DPSK	2439.956	2440.962	1.006

AFH mode

Hopping Mode	Test Mode	Peak of center channel (MHz)	Peak of adjacent Channel (MHz)	Test Result (MHz)
Enable	GFSK	2410.958	2411.961	1.003
	$\pi/4$ -DQPSK	2410.952	2411.955	1.003
	8DPSK	2410.949	2411.955	1.006


Note 1 : See next pages for actual measured spectrum plots.

- Minimum Standard :


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400 - 2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


Carrier Frequency Separation (FH)

Hopping mode : Enable & GFSK

Carrier Frequency Separation (FH)

Hopping mode : Enable & $\pi/4$ -DQPSK


Hopping mode : Enable & 8DPSK




Carrier Frequency Separation (AFH)

Hopping mode : Enable & GFSK

Carrier Frequency Separation (AFH)

Hopping mode : Enable & $\pi/4$ -DQPSK

Hopping mode : Enable & 8DPSK



5. Number of Hopping Frequencies

5.1 Test Setup

Refer to the APPENDIX I.

5.2 Limit

Limit : ≥ 15 hops

5.3 Procedure

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, two frequency ranges for FH mode within the 2400 ~ 2483.5 MHz were examined.

The spectrum analyzer is set to :

Span for FH mode = 50 MHz	Start Frequency = 2391.5 MHz,	Stop Frequency = 2441.5 MHz
	Start Frequency = 2441.5 MHz,	Stop Frequency = 2491.5 MHz
Span for AFH mode = 30 MHz	Start Frequency = 2396.0 MHz,	Stop Frequency = 2426.0 MHz
RBW = 1 % of the span or more	Sweep = auto	
VBW = $\geq$ RBW	Detector function = peak	
Trace = max hold		

5.4 Test Results

FH mode

Hopping mode	Test mode	Test Result (Total Hops)
Enable	GFSK	79
	$\pi/4$ -DQPSK	79
	8DPSK	79

AFH mode


Hopping mode	Test mode	Test Result (Total Hops)
Enable	GFSK	20
	$\pi/4$ -DQPSK	20
	8DPSK	20

Note 1 : See next pages for actual measured spectrum plots.


- Minimum Standard :

At least 15 hops


Number of Hopping Frequencies 1(FH)

Hopping mode : Enable & GFSK


Number of Hopping Frequencies 2(FH)

Hopping mode : Enable & GFSK

Number of Hopping Frequencies 1(FH)

Hopping mode : Enable & $\pi/4$ -DQPSK


Number of Hopping Frequencies 2(FH)

Hopping mode : Enable & $\pi/4$ -DQPSK


Number of Hopping Frequencies 1(FH)

Hopping mode : Enable & 8DPSK

Number of Hopping Frequencies 2(FH)

Hopping mode : Enable & 8DPSK


Number of Hopping Frequencies 1(AFH)

Hopping mode : Enable & GFSK


Number of Hopping Frequencies 1(AFH)

Hopping mode : Enable & $\pi/4$ -DQPSK

9



Hopping mode : Enable & 8DPSK



6. Time of Occupancy (Dwell Time)

6.1 Test Setup

Refer to the APPENDIX I.

6.2 Limit

The maximum permissible time of occupancy is 400 ms within a period of 400 ms multiplied by the number of hopping channels employed.

6.3 Test Procedure

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to :

Center frequency = 2441 MHz

RBW = 1 MHz

Trace = max hold

Span = zero

VBW = $\geq$ RBW

Detector function = peak

6.4 Test Results

FH mode

Hopping mode	Packet Type	Number of hopping Channels	Burst On Time (ms)	Period (ms)	Test Result (sec)
Enable	DH 5	79	2.880	3.750	0.307
	2 DH 5	79	2.880	3.750	0.307
	3 DH 5	79	2.880	3.750	0.307

AFH mode


Hopping mode	Packet Type	Number of hopping Channels	Burst On Time (ms)	Period (ms)	Test Result (sec)
Enable	DH 5	20	2.880	3.750	0.154
	2 DH 5	20	2.880	3.750	0.154
	3 DH 5	20	2.880	3.750	0.154

Note 1 : Dwell Time = $0.4 \times \text{Hopping channel} \times \text{Burst ON time} \times ((\text{Hopping rate} \div \text{Time slots}) \div \text{Hopping channel})$


- Time slots for DH5 = 6 slots (TX = 5 slot / RX = 1 slot)
- Hopping Rate = 1600 for FH mode & 800 for AFH mode

Note 2 : See next pages for actual measured spectrum plots.

Time of Occupancy (FH)



Hopping mode : Enable & GFSK

Time of Occupancy (FH)


Hopping mode : Enable & $\pi/4$ -DQPSK

Time of Occupancy (FH)

Hopping mode : Enable & 8DPSK

Time of Occupancy (AFH)***Hopping mode : Enable & GFSK*****Time of Occupancy (AFH)*****Hopping mode : Enable & $\pi/4$ -DQPSK***

Time of Occupancy (AFH)

Hopping mode : Enable & 8DPSK

7. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission

7.1 Test Setup

Refer to the APPENDIX I.

7.2 Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section §15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section §15.205(a), must also comply the radiated emission limits specified in section §15.209(a) (see section §15.205(c))

According to § 15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Limit (uV/m)	Measurement Distance (meter)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1705	24000/F (kHz)	30
1705 ~ 30.0	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 - 72 MHz, 76 - 88 MHz, 174 - 216 MHz or 470 - 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

According to § 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~ 12.52025	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.57675 ~ 12.57725	156.52475 ~ 156.52525	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	13.36 ~ 13.41	156.7 ~ 156.9	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	16.42 ~ 16.423	162.0125 ~ 167.17	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.69475 ~ 16.69525	167.72 ~ 173.2	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.80425 ~ 16.80475	240 ~ 285	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	25.5 ~ 25.67	322 ~ 335.4	2655 ~ 2900		
8.291 ~ 8.294	37.5 ~ 38.25	399.90 ~ 410	3260 ~ 3267		
8.362 ~ 8.366	73 ~ 74.6	608 ~ 614	3332 ~ 3339		
8.37625 ~ 8.38675	74.8 ~ 75.2	960 ~ 1240	3345.8 ~ 3358		
			3600 ~ 4400		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

7.3. Test Procedures

7.3.1. Test Procedures for Radiated Spurious Emissions

1. The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m.
The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 1 or 3 meter away from the interference-receiving antenna.
3. For measurements above 1GHz absorbers are placed on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1 GHz, the absorbers are removed.
4. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
5. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
6. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.

NOTE 2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz.

NOTE 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1 kHz for Average detection (AV) at frequency above 1 GHz.

7.3.2. Test Procedures for Conducted Spurious Emissions

1. The transmitter output was connected to the spectrum analyzer.
2. The **reference level** of the fundamental frequency was measured with the spectrum analyzer using RBW = 100 kHz, VBW = 300 kHz.
3. The conducted spurious emission was tested each ranges were set as below.

Frequency range : 9 kHz ~ 30 MHz

RBW = 100 kHz, VBW = 300 kHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD, SWEEP POINT : 40001

Frequency range : 30 MHz ~ 10 GHz, 10 GHz ~ 25 GHz

RBW = 1 MHz, VBW = 3 MHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD, SWEEP POINT : 40001

LIMIT LINE = 20 dB below of the reference level of above measurement procedure Step 2. (RBW = 100 kHz, VBW = 300 kHz)

If the emission level with above setting was close to the limit (ie, less than 3 dB margin) then zoom scan is required using RBW = 100 kHz, VBW = 300 kHz, SPAN = 100 MHz and BINS = 2001 to get accurate emission level within 100 kHz BW.

Also the path loss for conducted measurement setup was used as described on the Appendix I of this test report.

7.4. Test Results

7.4.1. Radiated Emissions

9 kHz ~ 25 GHz Data (Modulation : GFSK)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2389.940	V	X	PK	47.06	2.88	N/A	N/A	49.94	74.00	24.06
2389.610	V	X	AV	33.58	2.88	N/A	N/A	36.46	54.00	17.54
4803.994	V	X	PK	44.21	3.16	N/A	N/A	47.37	74.00	26.63
4804.015	V	X	AV	32.77	3.16	N/A	N/A	35.93	54.00	18.07

▪ Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4881.925	V	X	PK	44.40	3.39	N/A	N/A	47.79	74.00	26.21
4881.898	V	X	AV	32.34	3.39	N/A	N/A	35.73	54.00	18.27

▪ Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.615	V	X	PK	47.93	3.36	N/A	N/A	51.29	74.00	22.71
2483.764	V	X	AV	33.43	3.36	N/A	N/A	36.79	54.00	17.21
4960.202	V	X	PK	44.62	3.70	N/A	N/A	48.32	74.00	25.68
4960.180	V	X	AV	32.73	3.70	N/A	N/A	36.43	54.00	17.57

▪ Note.

1. No other spurious and harmonic emissions were found greater than listed emissions on above table.

2. Information of Distance Factor

For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.

- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = \underline{-9.54 \text{ dB}}$

When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)

- Time to cycle through all channels = $\Delta t = T [\text{ms}] \times 20$ minimum hopping channels, where T = pulse width

- $100 \text{ ms} / \Delta t [\text{ms}] = H \rightarrow$ Round up to next highest integer, to account for worst case, H'

- The Worst Case Dwell Time = $T [\text{ms}] \times H'$

- D.C.F = $20 \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB}$

4. Sample Calculation.

Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Modulation : $\pi/4$ DQPSK)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2389.490	V	X	PK	47.29	2.88	N/A	N/A	50.17	74.00	23.83
2389.250	V	X	AV	33.41	2.88	N/A	N/A	36.29	54.00	17.71
4803.984	V	X	PK	44.38	3.16	N/A	N/A	47.54	74.00	26.46
4803.994	V	X	AV	33.17	3.16	N/A	N/A	36.33	54.00	17.67

▪ Middle Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4881.936	V	X	PK	44.73	3.39	N/A	N/A	48.12	74.00	25.88
4881.914	V	X	AV	32.49	3.39	N/A	N/A	35.88	54.00	18.12

▪ Highest Channel

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.747	V	X	PK	46.61	3.36	N/A	N/A	49.97	74.00	24.03
2483.512	V	X	AV	33.72	3.36	N/A	N/A	37.08	54.00	16.92
4960.122	V	X	PK	44.56	3.70	N/A	N/A	48.26	74.00	25.74
4960.154	V	X	AV	33.68	3.70	N/A	N/A	37.38	54.00	16.62

▪ **Note.**

1. No other spurious and harmonic emissions were found greater than listed emissions on above table.
2. Information of Distance Factor

For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.

- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = -9.54 \text{ dB}$

When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)

- Time to cycle through all channels = $\Delta t = T [\text{ms}] \times 20$ minimum hopping channels, where T = pulse width
- $100 \text{ ms} / \Delta t [\text{ms}] = H \rightarrow$ Round up to next highest integer, to account for worst case, H'
- The Worst Case Dwell Time = $T [\text{ms}] \times H'$
- D.C.F = $20 \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB}$

4. Sample Calculation.

Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Modulation : 8DPSK)▪ **Lowest Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2389.370	V	X	PK	46.45	2.88	N/A	N/A	49.33	74.00	24.67
2389.220	V	X	AV	33.36	2.88	N/A	N/A	36.24	54.00	17.76
4803.989	V	X	PK	44.20	3.16	N/A	N/A	47.36	74.00	26.64
4803.968	V	X	AV	32.82	3.16	N/A	N/A	35.98	54.00	18.02

▪ **Middle Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4881.994	V	X	PK	44.51	3.39	N/A	N/A	47.90	74.00	26.10
4881.973	V	X	AV	32.32	3.39	N/A	N/A	35.71	54.00	18.29

▪ **Highest Channel**

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2483.665	V	X	PK	48.45	3.36	N/A	N/A	51.81	74.00	22.19
2483.714	V	X	AV	33.75	3.36	N/A	N/A	37.11	54.00	16.89
4960.074	V	X	PK	45.02	3.70	N/A	N/A	48.72	74.00	25.28
4960.069	V	X	AV	32.87	3.70	N/A	N/A	36.57	54.00	17.43

▪ **Note.**

1. No other spurious and harmonic emissions were found greater than listed emissions on above table.
2. Information of Distance Factor

For finding emissions, the test distance might be reduced from 3m to 1m. In this case, the distance factor(-9.54dB) is applied to the result.

- Calculation of distance factor = $20 \log(\text{applied distance} / \text{required distance}) = 20 \log(1 \text{ m} / 3 \text{ m}) = \underline{\underline{-9.54 \text{ dB}}}$

When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

3. D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)

- Time to cycle through all channels = $\Delta t = T [\text{ms}] \times 20$ minimum hopping channels, where T = pulse width
- $100 \text{ ms} / \Delta t [\text{ms}] = H \rightarrow$ Round up to next highest integer, to account for worst case, H'
- The Worst Case Dwell Time = $T [\text{ms}] \times H'$
- D.C.F = $20 \log(\text{The Worst Case Dwell Time} / 100 \text{ ms}) \text{ dB}$

4. Sample Calculation.

Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

9 kHz ~ 25 GHz Data (Hopping mode)

▪ Modulation : GFSK

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBUV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)
2389.889	V	X	PK	47.21	2.88	N/A	N/A	50.09	74.00	23.91
2389.740	V	X	AV	31.58	2.88	N/A	N/A	34.46	54.00	19.54
2483.556	V	X	PK	47.88	3.36	N/A	N/A	51.24	74.00	22.76
2483.694	V	X	AV	32.84	3.36	N/A	N/A	36.20	54.00	17.80

▪ Modulation : $\pi/4$ DQPSK

Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBUV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)
2389.520	V	X	PK	46.69	2.88	N/A	N/A	49.57	74.00	24.43
2389.310	V	X	AV	31.94	2.88	N/A	N/A	34.82	54.00	19.18
2483.644	V	X	PK	46.51	3.36	N/A	N/A	49.87	74.00	24.13
2483.487	V	X	AV	32.08	3.36	N/A	N/A	35.44	54.00	18.56

▪ Modulation : 8DPSK


Frequency (MHz)	ANT Pol	The worst case EUT Position (Axis)	Detector Mode	Reading (dBUV)	T.F (dB/m)	D.C.F (dB)	Distance Factor (dB)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)
2389.412	V	X	PK	46.32	2.88	N/A	N/A	49.20	74.00	24.80
2389.180	V	X	AV	32.18	2.88	N/A	N/A	35.06	54.00	18.94
2483.559	V	X	PK	47.85	3.36	N/A	N/A	51.21	74.00	22.79
2483.662	V	X	AV	32.16	3.36	N/A	N/A	35.52	54.00	18.48

▪ **Note.**

- No other spurious and harmonic emissions were found greater than listed emissions on above table.
- D.C.F Calculation. (D.C.F = Duty Cycle Correction Factor)
 - Time to cycle through all channels = $\Delta t = T$ [ms] X 20 minimum hopping channels, where T = pulse width
 - 100 ms / Δt [ms] = H -> Round up to next highest integer, to account for worst case, H'
 - The Worst Case Dwell Time = T [ms] x H'
 - D.C.F = 20 Log(The Worst Case Dwell Time / 100 ms) dB
- Sample Calculation.
 Margin = Limit – Result / Result = Reading + T.F + D.C.F / T.F = AF + CL – AG
 Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain.

7.4.2. Conducted Spurious Emissions


Low Band-edge

Lowest Channel & Modulation : GFSK

Low Band-edge

Hopping mode & Modulation : GFSK

Lowest Channel & Modulation : GFSK



Conducted Spurious Emissions

Lowest Channel & Modulation : GFSK




Reference for limit

Middle Channel & Modulation : GFSK




Conducted Spurious Emissions


Middle Channel & Modulation : GFSK




Middle Channel & Modulation : GFSK




High Band-edge

Highest Channel & Modulation : GFSK


High Band-edge

Hopping mode & Modulation : GFSK


Highest Channel & Modulation : GFSK




Conducted Spurious Emissions

Highest Channel & Modulation : GFSK



Low Band-edge

Lowest Channel & Modulation : $\pi/4$ DQPSK

Low Band-edge

Hopping mode & Modulation : $\pi/4$ DQPSK


Conducted Spurious Emissions

Lowest Channel & Modulation : $\pi/4$ DQPSK


Conducted Spurious Emissions

Lowest Channel & Modulation : $\pi/4$ DQPSK


Reference for limit

Middle Channel & Modulation : $\pi/4$ DQPSK

Conducted Spurious Emissions



Middle Channel & Modulation : $\pi/4$ DQPSK

Conducted Spurious Emissions

Middle Channel & Modulation : $\pi/4$ DQPSK

High Band-edge***Highest Channel & Modulation : $\pi/4$ DQPSK*****High Band-edge*****Hopping mode & Modulation : $\pi/4$ DQPSK***


Conducted Spurious Emissions

Highest Channel & Modulation : $\pi/4$ DQPSK


Conducted Spurious Emissions

Highest Channel & Modulation : $\pi/4$ DQPSK



Low Band-edge

Lowest Channel & Modulation : 8DPSK

Low Band-edge


Hopping mode & Modulation : 8DPSK

Conducted Spurious Emissions


Lowest Channel & Modulation : 8DPSK

Conducted Spurious Emissions

Lowest Channel & Modulation : 8DPSK




Middle Channel & Modulation : 8DPSK




Conducted Spurious Emissions

Middle Channel & Modulation : 8DPSK



Conducted Spurious Emissions


Middle Channel & Modulation : 8DPSK




High Band-edge

Highest Channel & Modulation : 8DPSK


High Band-edge

Hopping mode & Modulation : 8DPSK

Highest Channel & Modulation : 8DPSK



Conducted Spurious Emissions

Highest Channel & Modulation : 8DPSK

8. Transmitter AC Power Line Conducted Emission

8.1 Test Setup

Refer to test setup photo.

8.2 Limit

According to §15.207(a) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohm line impedance stabilization network (LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

8.3 Test Procedures

Conducted emissions from the EUT were measured according to the ANSI C63.10.

1. The test procedure is performed in a 6.5 m $\times$ 3.5 m $\times$ 3.5 m (L $\times$ W $\times$ H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) $\times$ 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

8.4 Test Results

NA

9. Antenna Requirement

Describe how the EUT complies with the requirement that either its antenna is permanently attached, or that it employs a unique antenna connector, for every antenna proposed for use with the EUT.

Conclusion: **Comply**

The antenna is permanently attached. (Refer to Internal photo file.)

- Minimum Standard :

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions.

10. Occupied Bandwidth (99 %)

10.1 Test Setup

Refer to the APPENDIX I.

10.2 Limit

Limit : Not Applicable

10.3 Test Procedure

The 99 % power bandwidth was measured with a calibrated spectrum analyzer.

The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately $3 \times \text{RBW}$.

Spectrum analyzer plots are included on the following pages.


10.4 Test Results

NA


APPENDIX I

Test set up diagrams

▪ Radiated Measurement



▪ Conducted Measurement



Path loss information

Frequency (GHz)	Path Loss (dB)	Frequency (GHz)	Path Loss (dB)
0.03	6.82	15	11.15
1	7.87	20	12.46
2402 & 2440 & 2480	8.35	25	13.70
5	10.27	-	-
10	10.87	-	-

Note 1 : The path loss from EUT to Spectrum analyzer were measured and used for test.

Path loss (S/A's Correction factor) = Cable A + Power splitter