

RADIO PERFORMANCE TEST REPORT

Test Report No. : OT-241-RWD-030
Reception No. : 2311004036
Applicant : LG Electronics USA
Address : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, 07632, United States
Manufacturer : LG Electronics Inc.
Address : 128, Yeoui-daero, Yeongdeungpo-gu, Seoul, Republic of Korea
Type of Equipment : Car Navigation
FCC ID. : BEJ-MIB3CLASSIC
Model Name : MIB3CLASSIC
Multiple Model Name : N/A
Serial number : N/A
Total page of Report : 79 pages (including this page)
Date of Incoming : December 04, 2023
Date of issue : January 24, 2024

SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART E Section 15.407**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

This report is not correlated with the "KS Q ISO/IEC 17025 and KOLAS accreditation" of Korean Laboratory Accreditation Scheme.



Tested by
 Si-eon Lee / Sr. Engineer
 ONETECH Corp.



Reviewed by
 Tae-Ho, Kim / Chief Engineer
 ONETECH Corp.



Approved by
 Jae-Ho, Lee / Chief Engineer
 ONETECH Corp.

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	7
2. TEST SUMMARY	8
2.1 TEST ITEMS AND RESULTS	8
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS.....	8
2.3 RELATED SUBMITTAL(S) / GRANT(S)	8
2.4 PURPOSE OF THE TEST	8
2.5 TEST METHODOLOGY.....	8
2.6 TEST FACILITY.....	8
3. GENERAL INFORMATION.....	9
3.1 PRODUCT DESCRIPTION.....	9
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	11
4. EUT MODIFICATIONS.....	11
5. SYSTEM TEST CONFIGURATION	12
5.1 JUSTIFICATION.....	12
5.2 PERIPHERAL EQUIPMENT	12
5.3 MODE OF OPERATION DURING THE TEST	13
5.4 CONFIGURATION OF TEST SYSTEM.....	17
5.5 ANTENNA REQUIREMENT	17
6. PRELIMINARY TEST	17
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....	17
6.2 GENERAL RADIATED EMISSIONS TESTS	17
7. 99 % OCCUPIED BANDWIDTH & MINIMUM 26 DB BANDWIDTH	18
7.1 OPERATING ENVIRONMENT	18
7.2 TEST SET-UP	18
7.3 TEST DATE	18
7.4 TEST DATA FOR 802.11A RLAN MODE.....	19
7.4.1 Test data for Antenna 0	19
7.4.2 Test data for Antenna 1	20
7.5 TEST DATA FOR 802.11N_HT20 RLAN MODE	21
7.5.1 Test data for Antenna 0	21
7.5.2 Test data for Antenna 1	22
7.6 TEST DATA FOR 802.11N_HT40 RLAN MODE.....	23
7.6.1 Test data for Antenna 0	23
7.6.2 Test data for Antenna 1	24

7.7 TEST DATA FOR 802.11AC_VHT80 RLAN MODE.....	25
7.7.1 Test data for Antenna 0	25
7.7.2 Test data for Antenna 1	25
8. 6 DB BANDWIDTH	26
8.1 OPERATING ENVIRONMENT	26
8.2 TEST SET-UP	26
8.3 TEST DATE	26
8.4 TEST DATA FOR 802.11A RLAN MODE.....	27
8.4.1 Test data for Antenna 0	27
8.4.2 Test data for Antenna 1	27
8.5 TEST DATA FOR 802.11N_HT20 RLAN MODE.....	28
8.5.1 Test data for Antenna 0	28
8.5.2 Test data for Antenna 1	28
8.6 TEST DATA FOR 802.11N_HT40 RLAN MODE.....	29
8.6.1 Test data for Antenna 0	29
8.6.2 Test data for Antenna 1	29
8.7 TEST DATA FOR 802.11AC_VHT80 RLAN MODE.....	29
8.7.1 Test data for Antenna 0	29
8.7.2 Test data for Antenna 1	29
9. MAXIMUM CONDUCTED(AVERAGE) OUTPUT POWER	30
9.1 OPERATING ENVIRONMENT	30
9.2 TEST SET-UP	30
9.3 TEST DATE	30
9.4 TEST DATA FOR 802.11A RLAN MODE.....	31
9.4.1 Test data for Antenna 0	31
9.4.2 Test data for Antenna 1	31
9.4.3 Test data for Multiple Transmit	32
9.5 TEST DATA FOR 802.11N_HT20 RLAN MODE.....	33
9.5.1 Test data for Antenna 0	33
9.5.2 Test data for Antenna 1	33
9.5.3 Test data for Multiple Transmit	34
9.6 TEST DATA FOR 802.11N_HT40 RLAN MODE.....	35
9.6.1 Test data for Antenna 0	35
9.6.2 Test data for Antenna 1	35
9.6.3 Test data for Multiple Transmit	36
9.7 TEST DATA FOR 802.11AC_HT80 RLAN MODE.....	37
9.7.1 Test data for Antenna 0	37

9.7.2 Test data for Antenna 1	37
9.7.3 Test data for Multiple Transmit	37
10. POWER SPECTRAL DENSITY	38
10.1 OPERATING ENVIRONMENT	38
10.2 TEST SET-UP	38
10.3 TEST DATE	38
10.4 TEST DATA FOR 802.11A RLAN MODE.....	39
10.4.1 Test data for Antenna 0	39
10.4.2 Test data for Antenna 1	39
10.4.3 Test data for Multiple Transmit	40
10.5 TEST DATA FOR 802.11N_HT20 RLAN MODE.....	41
10.5.1 Test data for Antenna 0	41
10.5.2 Test data for Antenna 1	41
10.5.3 Test data for Multiple Transmit	42
10.6 TEST DATA FOR 802.11N_HT40 RLAN MODE.....	43
10.6.1 Test data for Antenna 0	43
10.6.2 Test data for Antenna 1	43
10.7 TEST DATA FOR 802.11AC_HT80 RLAN MODE.....	45
10.7.1 Test data for Antenna 0	45
10.7.2 Test data for Antenna 1	45
10.7.3 Test data for Multiple Transmit	46
11. FREQUENCY STABILITY WITH TEMPERATURE VARIATION.....	47
11.1 OPERATING ENVIRONMENT	47
11.2 TEST SET-UP	47
11.3 TEST DATE	47
11.4 TEST DATA FOR U-NII-1	48
11.5 TEST DATA FOR U-NII-3	49
12. FREQUENCY STABILITY WITH VOLTAGE VARIATION.....	50
12.1 OPERATING ENVIRONMENT	50
12.2 TEST SET-UP	50
12.3 TEST DATE	50
12.4 TEST DATA FOR U-NII-1	51
12.5 TEST DATA FOR U-NII-3	51
13. RADIATED SPURIOUS EMISSIONS.....	52
13.1 OPERATING ENVIRONMENT	52
13.2 TEST SET-UP FOR CONDUCTED MEASUREMENT	52
13.3 TEST DATE	53

13.4 TEST DATA FOR BELOW 30 MHz	54
13.5 TEST DATA FOR 30 MHz ~ 1 000 MHz	55
13.5.1 Test data for WLAN 5 GHz	55
13.5.2 Test data for Intermodulation Mode(Bluetooth + WLAN 5 GHz)	56
13.5.3 Test data for Intermodulation Mode(WLAN 2 GHz + WLAN 5 GHz)	57
13.6 TEST DATA FOR ABOVE 1 GHz.....	58
13.6.1 Test data for Frequency UNII I	58
13.6.2 Test data for Frequency UNII 3.....	62
14. RADIATED RESTRICTED BAND EDGE MEASUREMENTS	66
14.1 OPERATING ENVIRONMENT	66
14.2 TEST SET-UP FOR CONDUCTED MEASUREMENT	66
14.3 TEST DATE	66
14.4 TEST DATA FOR FREQUENCY UNII I.....	67
14.4.1 Test data for 802.11a RLAN Mode	67
14.4.2 Test data for 802.11n_HT20 RLAN Mode.....	68
14.4.3 Test data for 802.11n_HT40 RLAN Mode.....	69
14.4.4 Test data for 802.11ac_VHT80 RLAN Mode.....	70
14.5 TEST DATA FOR FREQUENCY U-NII-3.....	71
14.5.1 Test data for 802.11a RLAN Mode	71
14.5.2 Test data for 802.11n_HT20 RLAN Mode.....	73
14.5.3 Test data for 802.11n_HT40 RLAN Mode.....	75
14.5.4 Test data for 802.11ac_VHT80 RLAN Mode.....	77
14.5.5 U-NII-3 Emission Limits	78
15. LIST OF TEST EQUIPMENT	79

※ Please refer to the Annex section for All test plots

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-241-RWD-030	January 24, 2024	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : LG Electronics USA

Address : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, 07632, United States

Contact Person : Heejae, Cho / Director, Regulatory and Environmental Affairs

Telephone No. : +201-266-2215

FCC ID : BEJ-MIB3CLASSIC

Model Name : MIB3CLASSIC

Brand Name : LG

Serial Number : N/A

Date : January 24, 2024

EQUIPMENT CLASS	Unlicensed National Information infrastructure(UNII)
E.U.T. DESCRIPTION	Car Navigation
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART E Section 15.407 789033 D02 General UNII Test Procedures New Rules v02r01
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.407(a)	26 dB Bandwidth	PASS
15.407(a)	Maximum Conducted Output Power	Met the Limit / PASS
15.407(a)	Power Spectral Density	Met the Limit / PASS
15.407(e)	6 dB Bandwidth	Met the Limit / PASS
15.407(g)	Frequency Stability	Met the Limit / PASS
15.407(b)	Undesirable Emissions	Met the Limit / PASS
15.205, 15.407(b)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Met the Limit / PASS
15.207	Conducted Limits	N/A (See Note)

Note: This test is not performed because the EUT is operated by only using DC Power.

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART E Section 15.407

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea.

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-20122/ C-14617/ G-10666/ T-11842

ISED (Innovation, Science and Economic Development Canada) – Registration No. Site# 3736A-3

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

3. GENERAL INFORMATION

3.1 Product Description

The LG Electronics USA, Model MIB3CLASSIC (referred to as the EUT in this report) is a Car Navigation. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Car Navigation	
OPERATING FREQUENCY	Bluetooth	2 402 MHz ~ 2 480 MHz
	WLAN 2.4 GHz	2 412 MHz ~ 2 462 MHz (802.11b/g/n(HT20))
	WLAN	5 180 MHz ~ 5 240 MHz (802.11a/n(HT20))
	5 150 MHz ~	5 190 MHz ~ 5 230 MHz (802.11n(HT40))
	5 250 MHz Band	5 210 MHz (802.11ac(VHT80))
	WLAN	5 745 MHz ~ 5 825 MHz (802.11a/n(HT20))
	5 725 MHz ~	5 755 MHz ~ 5 795 MHz (802.11n(HT40))
	5 850 MHz Band	5 775 MHz (802.11ac(VHT80))
MODULATION TYPE	Bluetooth	GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps, 8-DPSK for 3Mbps
	WLAN 2.4 GHz	802.11b: DSSS Modulation (DBPSK/DQPSK/CCK) 802.11g/n(HT20): OFDM Modulation (BPSK/QPSK/16QAM/64QAM)
	WLAN 5 GHz	802.11a/n(HT20)/n(HT40)/ac(VHT80): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)

RF OUTPUT POWER	Bluetooth	2.53 dBm (1 Mbps) 1.64 dBm (2 Mbps) 1.92 dBm (3 Mbps)	
	WLAN 2.4 GHz	8.09 dBm (802.11b) 7.83 dBm (802.11g) 7.99 dBm (802.11n_HT20)	
	WLAN 5 150 MHz ~ 5 250 MHz Band	Antenna 0	9.44 dBm(802.11a) 9.45 dBm(802.11n_HT20) 9.43 dBm(802.11n_HT40) 9.57 dBm(802.11ac_VHT80)
		Antenna 1	9.29 dBm(802.11a) 9.17 dBm(802.11n_HT20) 9.13 dBm(802.11n_HT40) 9.25 dBm(802.11ac_VHT80)
		Multiple Antenna	12.38 dBm(802.11a) 12.32 dBm(802.11n_HT20) 12.29 dBm(802.11n_HT40) 12.42 dBm(802.11ac_VHT80)
		Antenna 0	12.14 dBm(802.11a) 12.30 dBm(802.11n_HT20) 11.95 dBm(802.11n_HT40) 12.04 dBm(802.11ac_VHT80)
		Antenna 1	11.72 dBm(802.11a) 11.88 dBm(802.11n_HT20) 11.63 dBm(802.11n_HT40) 11.59 dBm(802.11ac_VHT80)
		Multiple Antenna	14.93 dBm(802.11a) 15.11 dBm(802.11n_HT20) 14.80 dBm(802.11n_HT40) 14.83 dBm(802.11ac_VHT80)
	WLAN 5 725 MHz ~ 5 850 MHz Band	Antenna 0	12.14 dBm(802.11a) 12.30 dBm(802.11n_HT20) 11.95 dBm(802.11n_HT40) 12.04 dBm(802.11ac_VHT80)
		Antenna 1	11.72 dBm(802.11a) 11.88 dBm(802.11n_HT20) 11.63 dBm(802.11n_HT40) 11.59 dBm(802.11ac_VHT80)
		Multiple Antenna	14.93 dBm(802.11a) 15.11 dBm(802.11n_HT20) 14.80 dBm(802.11n_HT40) 14.83 dBm(802.11ac_VHT80)

ANTENNA TYPE	Bluetooth	PCB Antenna	
	WLAN 2.4 GHz	PCB Antenna	
	WLAN 5 GHz	PCB Antenna	
ANTENNA GAIN	Bluetooth & WLAN 2.4 GHz	Antenna 0	3.28 dBi
		Antenna 1	4.87 dBi
	5 150 MHz ~ 5 250 MHz Band	Antenna 0	3.76 dBi
		Antenna 1	5.04 dBi
	5 725 MHz ~ 5 850 MHz Band	Antenna 0	5.28 dBi
		Antenna 1	6.70 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)		2.17 MHz, 2.2 MHz, 3 MHz, 19.2 MHz, 25 MHz, 26 MHz, 27 MHz, 28.636 36 MHz, 38.4 MHz, 40 MHz, 55.466 67 MHz	
RATED SUPPLY VOLTAGE		DC 14.0 V	

3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

4. EUT MODIFICATIONS

-. None

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	N/A	N/A	N/A

5.2 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested:

Model	Manufacturer	Description	Connected to
MIB3CLASSIC	LG Electronics Inc.	Car Navigation (EUT)	-
RTL8852BE	HP	Notebook PC	EUT

5.3 Mode of operation during the test

-. Duty Cycle (Antenna 0)

Band	TEST Mode	Data Rate	On Time (ms)	Total Time (ms)	Duty Cycle (%)	Duty Cycle Factor (dB)
UNII 1	802.11 a (5 220 MHz)	6	1.432	1.447	98.95	0.05
		9	0.960	0.975	98.43	0.07
		12	0.728	0.743	97.94	0.09
		18	0.492	0.507	96.98	0.13
		24	0.376	0.391	96.09	0.17
		36	0.256	0.271	94.36	0.25
		48	0.200	0.215	92.89	0.32
		54	0.180	0.195	92.24	0.35
	802.11 n(HT20) (5 220 MHz)	MCS0	1.340	1.355	98.88	0.05
		MCS1	0.688	0.703	97.82	0.10
		MCS2	0.472	0.487	96.86	0.14
		MCS3	0.364	0.379	95.96	0.18
		MCS4	0.256	0.271	94.36	0.25
		MCS5	0.200	0.215	92.89	0.32
		MCS6	0.184	0.199	92.32	0.35
		MCS7	0.168	0.183	91.65	0.38
	802.11 n(HT40) (5 230 MHz)	MCS0	0.664	0.680	97.71	0.10
		MCS1	0.352	0.368	95.77	0.19
		MCS2	0.248	0.264	94.06	0.27
		MCS3	0.196	0.212	92.65	0.33
		MCS4	0.144	0.160	90.25	0.45
		MCS5	0.116	0.132	88.11	0.55
		MCS6	0.108	0.124	87.34	0.59
		MCS7	0.100	0.116	86.47	0.63
	802.11 ac(VHT80) (5 210 MHz)	MCS0	0.192	0.208	92.34	0.35
		MCS1	0.120	0.136	88.28	0.54
		MCS2	0.100	0.116	86.26	0.64
		MCS3	0.084	0.100	84.06	0.75
		MCS4	0.072	0.088	81.83	0.87
		MCS5	0.064	0.080	80.01	0.97
		MCS6	0.064	0.080	80.08	0.96
		MCS7	0.060	0.076	79.04	1.02
		MCS8	0.060	0.076	79.03	1.02
		MCS9	0.056	0.072	77.86	1.09

-. Duty Cycle (Antenna 1)

Band	TEST Mode	Data Rate	On Time (ms)	Total Time (ms)	Duty Cycle (%)	Duty Cycle Factor (dB)
UNII 1	802.11 a (5 220 MHz)	6	1.432	1.447	98.95	0.05
		9	0.960	0.975	98.43	0.07
		12	0.728	0.743	97.94	0.09
		18	0.492	0.507	96.98	0.13
		24	0.376	0.391	96.09	0.17
		36	0.256	0.271	94.36	0.25
		48	0.200	0.215	92.89	0.32
		54	0.180	0.195	92.16	0.35
	802.11 n(HT20) (5 220 MHz)	MCS0	1.340	1.355	98.88	0.05
		MCS1	0.688	0.703	97.82	0.10
		MCS2	0.472	0.487	96.86	0.14
		MCS3	0.364	0.379	96.00	0.18
		MCS4	0.256	0.271	94.36	0.25
		MCS5	0.200	0.215	92.89	0.32
		MCS6	0.184	0.199	92.32	0.35
		MCS7	0.168	0.183	91.73	0.37
	802.11 n(HT40) (5 230 MHz)	MCS0	0.664	0.680	97.71	0.10
		MCS1	0.352	0.368	95.77	0.19
		MCS2	0.248	0.264	94.06	0.27
		MCS3	0.196	0.212	92.60	0.33
		MCS4	0.144	0.160	90.25	0.45
		MCS5	0.116	0.132	88.18	0.55
		MCS6	0.108	0.124	87.41	0.58
		MCS7	0.100	0.116	86.46	0.63
	802.11 ac(VHT80) (5 210 MHz)	MCS0	0.192	0.208	92.32	0.35
		MCS1	0.120	0.136	88.25	0.54
		MCS2	0.100	0.116	86.26	0.64
		MCS3	0.084	0.100	84.01	0.76
		MCS4	0.072	0.088	81.87	0.87
		MCS5	0.064	0.080	80.02	0.97
		MCS6	0.064	0.080	80.02	0.97
		MCS7	0.060	0.076	78.96	1.03
		MCS8	0.060	0.076	78.96	1.03
		MCS9	0.056	0.072	77.86	1.09

Note – Duty Cycle : (Tx On Time / (Tx On Time + Tx Off Time)) * 100

Correction Factor : $10 * \log(1 / (\text{Duty Cycle} / 100))$

-. Duty Cycle (Antenna 0)

Band	TEST Mode	Data Rate	On Time (ms)	Total Time (ms)	Duty Cycle (%)	Duty Cycle Factor (dB)
UNII 3	802.11 a (5 785 MHz)	6	1.432	1.447	98.95	0.05
		9	0.960	0.975	98.45	0.07
		12	0.728	0.743	97.96	0.09
		18	0.492	0.507	96.98	0.13
		24	0.492	0.507	97.01	0.13
		36	0.492	0.507	97.01	0.13
		48	0.200	0.215	93.03	0.31
		54	0.180	0.195	92.24	0.35
	802.11 n(HT20) (5 785 MHz)	MCS0	1.340	1.355	98.87	0.05
		MCS1	0.688	0.703	97.82	0.10
		MCS2	0.472	0.487	96.89	0.14
		MCS3	0.364	0.379	96.00	0.18
		MCS4	0.256	0.271	94.47	0.25
		MCS5	0.200	0.215	92.89	0.32
		MCS6	0.184	0.199	92.40	0.34
		MCS7	0.168	0.183	91.72	0.38
	802.11 n(HT40) (5 795 MHz)	MCS0	0.664	0.680	97.71	0.10
		MCS1	0.352	0.368	95.77	0.19
		MCS2	0.248	0.264	94.09	0.26
		MCS3	0.196	0.212	92.65	0.33
		MCS4	0.144	0.160	90.25	0.45
		MCS5	0.116	0.132	88.18	0.55
		MCS6	0.108	0.124	87.41	0.58
		MCS7	0.100	0.116	86.47	0.63
	802.11 ac(VHT80) (5 775 MHz)	MCS0	0.192	0.208	92.34	0.35
		MCS1	0.120	0.136	88.28	0.54
		MCS2	0.100	0.116	86.26	0.64
		MCS3	0.084	0.100	84.01	0.76
		MCS4	0.072	0.088	81.83	0.87
		MCS5	0.064	0.080	80.08	0.96
		MCS6	0.064	0.080	80.07	0.97
		MCS7	0.060	0.076	79.03	1.02
		MCS8	0.060	0.076	78.96	1.03
		MCS9	0.056	0.072	77.85	1.09

-. Duty Cycle (Antenna 1)

Band	TEST Mode	Data Rate	On Time (ms)	Total Time (ms)	Duty Cycle (%)	Duty Cycle Factor (dB)
UNII 3	802.11 a (5 785 MHz)	6	1.432	1.447	98.94	0.05
		9	0.960	0.975	98.43	0.07
		12	0.728	0.743	97.96	0.09
		18	0.492	0.507	97.01	0.13
		24	0.492	0.507	96.98	0.13
		36	0.492	0.507	97.01	0.13
		48	0.200	0.215	92.96	0.32
		54	0.180	0.195	92.24	0.35
	802.11 n(HT20) (5 785 MHz)	MCS0	1.340	1.355	98.88	0.05
		MCS1	0.688	0.703	97.84	0.09
		MCS2	0.472	0.487	96.89	0.14
		MCS3	0.364	0.379	95.96	0.18
		MCS4	0.256	0.271	94.41	0.25
		MCS5	0.200	0.215	92.96	0.32
		MCS6	0.184	0.199	92.40	0.34
		MCS7	0.168	0.183	91.65	0.38
	802.11 n(HT40) (5 795 MHz)	MCS0	0.664	0.680	97.71	0.10
		MCS1	0.352	0.368	95.79	0.19
		MCS2	0.248	0.264	94.10	0.26
		MCS3	0.196	0.212	92.69	0.33
		MCS4	0.144	0.159	90.30	0.44
		MCS5	0.116	0.132	88.18	0.55
		MCS6	0.108	0.124	87.41	0.58
		MCS7	0.100	0.116	86.54	0.63
	802.11 ac(VHT80) (5 775 MHz)	MCS0	0.192	0.208	92.32	0.35
		MCS1	0.120	0.136	88.28	0.54
		MCS2	0.100	0.116	86.22	0.64
		MCS3	0.084	0.100	84.02	0.76
		MCS4	0.072	0.088	81.89	0.87
		MCS5	0.064	0.080	80.08	0.96
		MCS6	0.064	0.080	80.00	0.97
		MCS7	0.060	0.076	78.98	1.03
		MCS8	0.060	0.076	78.98	1.03
		MCS9	0.056	0.072	77.86	1.09

Note – Duty Cycle : (Tx On Time / (Tx On Time + Tx Off Time)) * 100

Correction Factor : $10 * \log(1 / (\text{Duty Cycle} / 100))$

5.4 Configuration of Test System

Line Conducted Test: It is not need to test this requirement, because the EUT shall be operated by only using DC Battery.

Radiated Emission Test: Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meter Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The antenna of the EUT is a PCB Antenna on the main board in the EUT, so no consideration of replacement by the user.

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
It is not need to test this requirement, because the power of the EUT is supplied by DC Battery.	

6.2 General Radiated Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X

7. 99 % OCCUPIED BANDWIDTH & MIMIMUM 26 dB BANDWIDTH

7.1 Operating environment

Temperature : 22 °C

Relative humidity : 48 % R.H.

7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 1%-5% OBW for 99% bandwidth, and peak detection was used. The 99 % bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission.

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to approximately 1% of the emission bandwidth, and peak detection was used. The 26 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 26 dB.



7.3 Test Date

December 15, 2023 ~ January 12, 2024

7.4 Test data for 802.11a RLAN Mode

7.4.1 Test data for Antenna 0

7.4.1.1 99 % OCCUPIED BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	16.43
	Middle	5 220.00	16.48
	High	5 240.00	16.43
5 725 ~ 5 850	Low	5 745.00	16.48
	Middle	5 785.00	16.53
	High	5 825.00	16.48

7.4.1.2 MINIMUM 26 dB BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	19.68
	Middle	5 220.00	19.48
	High	5 240.00	19.73
5 725 ~ 5 850	Low	5 745.00	19.63
	Middle	5 785.00	19.58
	High	5 825.00	19.38

7.4.2 Test data for Antenna 1

7.4.2.1 99 % OCCUPIED BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	16.48
	Middle	5 220.00	16.43
	High	5 240.00	16.48
5 725 ~ 5 850	Low	5 745.00	16.43
	Middle	5 785.00	16.48
	High	5 825.00	16.48

7.4.2.2 MINIMUM 26 dB BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	19.58
	Middle	5 220.00	19.38
	High	5 240.00	19.28
5 725 ~ 5 850	Low	5 745.00	19.83
	Middle	5 785.00	19.43
	High	5 825.00	19.33

7.5 Test data for 802.11n_HT20 RLAN Mode

7.5.1 Test data for Antenna 0

7.5.1.1 99 % OCCUPIED BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	17.53
	Middle	5 220.00	17.58
	High	5 240.00	17.53
5 725 ~ 5 850	Low	5 745.00	17.58
	Middle	5 785.00	17.58
	High	5 825.00	17.53

7.5.1.2 MINIMUM 26 dB BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	19.83
	Middle	5 220.00	19.93
	High	5 240.00	19.83
5 725 ~ 5 850	Low	5 745.00	19.73
	Middle	5 785.00	19.73
	High	5 825.00	19.93

7.5.2 Test data for Antenna 1

7.5.2.1 99 % OCCUPIED BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	17.63
	Middle	5 220.00	17.58
	High	5 240.00	17.63
5 725 ~ 5 850	Low	5 745.00	17.58
	Middle	5 785.00	17.58
	High	5 825.00	17.63

7.5.2.2 MINIMUM 26 dB BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Low	5 180.00	19.68
	Middle	5 220.00	19.88
	High	5 240.00	19.63
5 725 ~ 5 850	Low	5 745.00	19.88
	Middle	5 785.00	19.83
	High	5 825.00	19.73

7.6 Test data for 802.11n_HT40 RLAN Mode

7.6.1 Test data for Antenna 0

7.6.1.1 99 % OCCUPIED BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Low	5 190.00	36.26
	High	5 230.00	36.16
5 725 ~ 5 850	Low	5 755.00	36.16
	High	5 795.00	36.16

7.6.1.2 MINIMUM 26 dB BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Low	5 190.00	40.66
	High	5 230.00	41.06
5 725 ~ 5 850	Low	5 755.00	40.56
	High	5 795.00	40.26

7.6.2 Test data for Antenna 1

7.6.2.1 99 % OCCUPIED BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Low	5 190.00	36.36
	High	5 230.00	36.26
5 725 ~ 5 850	Low	5 755.00	36.06
	High	5 795.00	36.26

7.6.2.2 MINIMUM 26 dB BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Low	5 190.00	39.76
	High	5 230.00	39.86
5 725 ~ 5 850	Low	5 755.00	39.96
	High	5 795.00	39.96

7.7 Test data for 802.11ac_VHT80 RLAN Mode

7.7.1 Test data for Antenna 0

7.7.1.1 99 % OCCUPIED BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Middle	5 210.00	76.32
5 725 ~ 5 850	Middle	5 775.00	75.92

7.7.1.2 MINIMUM 26 dB BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Middle	5 210.00	81.72
5 725 ~ 5 850	Middle	5 775.00	81.72

7.7.2 Test data for Antenna 1

7.7.2.1 99 % OCCUPIED BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	99 % Bandwidth (MHz)
5 150 ~ 5 250	Middle	5 210.00	75.92
5 725 ~ 5 850	Middle	5 775.00	76.12

7.7.2.2 MINIMUM 26 dB BANDWIDTH

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	26 dB Bandwidth (MHz)
5 150 ~ 5 250	Middle	5 210.00	81.52
5 725 ~ 5 850	Middle	5 775.00	81.52

8. 6 dB BANDWIDTH


8.1 Operating environment

Temperature : 22 °C

Relative humidity : 48 % R.H.

8.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz, and peak detection was used. The 6 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 6 dB.



8.3 Test Date

December 15, 2023 ~ January 12, 2024

8.4 Test data for 802.11a RLAN Mode

8.4.1 Test data for Antenna 0

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
5 725 ~ 5 850	Low	5 745.00	16.33	0.50	15.83
	Middle	5 785.00	16.33	0.50	15.83
	High	5 825.00	16.33	0.50	15.83

8.4.2 Test data for Antenna 1

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
5 725 ~ 5 850	Low	5 745.00	16.33	0.50	15.83
	Middle	5 785.00	16.33	0.50	15.83
	High	5 825.00	16.38	0.50	15.88

8.5 Test data for 802.11n_HT20 RLAN Mode

8.5.1 Test data for Antenna 0

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
5 725 ~ 5 850	Low	5 745.00	16.53	0.50	16.03
	Middle	5 785.00	16.93	0.50	16.43
	High	5 825.00	17.18	0.50	16.68

8.5.2 Test data for Antenna 1

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
5 725 ~ 5 850	Low	5 745.00	17.13	0.50	16.63
	Middle	5 785.00	17.13	0.50	16.63
	High	5 825.00	17.33	0.50	16.83

8.6 Test data for 802.11n_HT40 RLAN Mode

8.6.1 Test data for Antenna 0

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
5 725 ~ 5 850	Low	5 755.00	35.56	0.50	35.06
	High	5 795.00	35.76	0.50	35.26

8.6.2 Test data for Antenna 1

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
5 725 ~ 5 850	Low	5 755.00	35.46	0.50	34.96
	High	5 795.00	35.56	0.50	35.06

8.7 Test data for 802.11ac_VHT80 RLAN Mode

8.7.1 Test data for Antenna 0

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
5 725 ~ 5 850	Middle	5 775.00	76.32	0.50	75.82

8.7.2 Test data for Antenna 1

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
5 725 ~ 5 850	Middle	5 775.00	76.32	0.50	75.82

9. MAXIMUM CONDUCTED(AVERAGE) OUTPUT POWER

9.1 Operating environment


Temperature : 22 °C

Relative humidity : 48 % R.H.

9.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer.

The resolution bandwidth is set to 1 MHz, the video bandwidth is set to 3 times the resolution bandwidth.



9.3 Test Date

December 15, 2023 ~ January 12, 2024

9.4 Test data for 802.11a RLAN Mode

9.4.1 Test data for Antenna 0

-. Test Result : Pass

-. Duty Cycle : 98.95 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	9.05	0.05	9.10	23.98	14.88
	Middle	5 220.00	9.20	0.05	9.25	23.98	14.73
	High	5 240.00	9.39	0.05	9.44	23.98	14.54
5 725 ~ 5 850	Low	5 745.00	11.87	0.05	11.92	30.00	18.08
	Middle	5 785.00	11.39	0.05	11.44	30.00	18.56
	High	5 825.00	12.09	0.05	12.14	30.00	17.86

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

9.4.2 Test data for Antenna 1

-. Test Result : Pass

-. Duty Cycle : 98.95 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	8.96	0.05	9.01	23.98	14.97
	Middle	5 220.00	8.99	0.05	9.04	23.98	14.94
	High	5 240.00	9.24	0.05	9.29	23.98	14.69
5 725 ~ 5 850	Low	5 745.00	11.67	0.05	11.72	29.30	17.58
	Middle	5 785.00	10.88	0.05	10.93	29.30	18.37
	High	5 825.00	11.64	0.05	11.69	29.30	17.61

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

9.4.3 Test data for Multiple Transmit

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	12.07	22.52	10.45
	Middle	5 220.00	12.16	22.52	10.36
	High	5 240.00	12.38	22.52	10.14
5 725 ~ 5 850	Low	5 745.00	14.83	26.94	12.11
	Middle	5 785.00	14.20	26.94	12.74
	High	5 825.00	14.93	26.94	12.01

Remark 1: Margin = Limit – Total Value

Remark 2: Calculated Output Power= $10\log (10^{(\text{Antenna0 Output Power}/10)} + 10^{(\text{Antenna1 Output Power}/10)})$

Remark 3: Calculated Antenna Gain = $10\log (10^{(\text{Antenna0 Gain}/10)} + 10^{(\text{Antenna1 Gain}/10)})$

Remark 4: Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

9.5 Test data for 802.11n_HT20 RLAN Mode

9.5.1 Test data for Antenna 0

-. Test Result : Pass

-. Duty Cycle : 98.88 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	9.05	0.05	9.1	23.98	14.88
	Middle	5 220.00	9.18	0.05	9.23	23.98	14.75
	High	5 240.00	9.40	0.05	9.45	23.98	14.53
5 725 ~ 5 850	Low	5 745.00	12.02	0.05	12.07	30.00	17.93
	Middle	5 785.00	11.53	0.05	11.58	30.00	18.42
	High	5 825.00	12.25	0.05	12.30	30.00	17.70

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

9.5.2 Test data for Antenna 1

-. Test Result : Pass

-. Duty Cycle : 98.88 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	8.90	0.05	8.95	23.98	15.03
	Middle	5 220.00	8.97	0.05	9.02	23.98	14.96
	High	5 240.00	9.12	0.05	9.17	23.98	14.81
5 725 ~ 5 850	Low	5 745.00	11.79	0.05	11.84	29.30	17.46
	Middle	5 785.00	11.00	0.05	11.05	29.30	18.25
	High	5 825.00	11.83	0.05	11.88	29.30	17.42

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

9.5.3 Test data for Multiple Transmit

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	12.04	22.52	10.48
	Middle	5 220.00	12.14	22.52	10.38
	High	5 240.00	12.32	22.52	10.20
5 725 ~ 5 850	Low	5 745.00	14.97	26.94	11.97
	Middle	5 785.00	14.33	26.94	12.61
	High	5 825.00	15.11	26.94	11.83

Remark 1: Margin = Limit – Total Value

Remark 2: Calculated Output Power= $10\log (10^{(\text{Antenna0 Output Power}/10)} + 10^{(\text{Antenna1 Output Power}/10)})$

Remark 3: Calculated Antenna Gain = $10\log (10^{(\text{Antenna0 Gain}/10)} + 10^{(\text{Antenna1 Gain}/10)})$

Remark 4: Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

9.6 Test data for 802.11n_HT40 RLAN Mode

9.6.1 Test data for Antenna 0

-. Test Result : Pass

-. Duty Cycle : 97.71 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 190.00	9.13	0.10	9.23	23.98	14.75
	High	5 230.00	9.33	0.10	9.43	23.98	14.55
5 725 ~ 5 850	Low	5 755.00	11.85	0.10	11.95	30.00	18.05
	High	5 795.00	11.57	0.10	11.67	30.00	18.33

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

9.6.2 Test data for Antenna 1

-. Test Result : Pass

-. Duty Cycle : 97.71 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 190.00	8.78	0.10	8.88	23.98	15.10
	High	5 230.00	9.03	0.10	9.13	23.98	14.85
5 725 ~ 5 850	Low	5 755.00	11.53	0.10	11.63	29.30	17.67
	High	5 795.00	11.07	0.10	11.17	29.30	18.13

Remark : Margin = Limit –Total Value (=Measured Value +Duty Factor)

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

9.6.3 Test data for Multiple Transmit

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Low	5 190.00	12.07	22.52	10.45
	High	5 230.00	12.29	22.52	10.23
5 725 ~ 5 850	Low	5 755.00	14.80	26.94	12.14
	High	5 795.00	14.44	26.94	12.50

Remark 1: Margin = Limit – Total Value

Remark 2: Calculated Output Power= $10\log (10^{(\text{Antenna0 Output Power}/10)} + 10^{(\text{Antenna1 Output Power}/10)})$

Remark 3: Calculated Antenna Gain = $10\log (10^{(\text{Antenna0 Gain}/10)} + 10^{(\text{Antenna1 Gain}/10)})$

Remark 4: Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

9.7 Test data for 802.11ac_HT80 RLAN Mode

9.7.1 Test data for Antenna 0

-. Test Result : Pass

-. Duty Cycle : 92.34 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Middle	5 210.00	9.22	0.35	9.57	23.98	14.41
5 725 ~ 5 850	Middle	5 775.00	11.69	0.35	12.04	30.00	17.96

Remark : Margin = Limit – Total Value (=Measured Value +Duty Factor)

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

9.7.2 Test data for Antenna 1

-. Test Result : Pass

-. Duty Cycle : 92.34 %

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Total Value (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Middle	5 210.00	8.90	0.35	9.25	23.98	14.73
5 725 ~ 5 850	Middle	5 775.00	11.24	0.35	11.59	29.30	17.71

Remark : Margin = Limit – Total Value (=Measured Value +Duty Factor)

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

9.7.3 Test data for Multiple Transmit

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
5 150 ~ 5 250	Middle	5 210.00	12.42	22.52	10.10
5 725 ~ 5 850	Middle	5 775.00	14.83	26.94	12.11

Remark 1: Margin = Limit – Total Value

Remark 2: Calculated Output Power= $10\log(10^{(\text{Antenna0 Output Power}/10)} + 10^{(\text{Antenna1 Output Power}/10)})$

Remark 3: Calculated Antenna Gain = $10\log(10^{(\text{Antenna0 Gain}/10)} + 10^{(\text{Antenna1 Gain}/10)})$

Remark 4: Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

10. POWER SPECTRAL DENSITY


10.1 Operating environment

Temperature : 22 °C

Relative humidity : 48 % R.H.

10.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 1 MHz(UNII 1) and 500 kHz(UNII 3), the video bandwidth is set to 3 times the resolution bandwidth. The maximum level for the EUT in 1 MHz bandwidth was measured with above condition



10.3 Test Date

December 15, 2023 ~ January 12, 2024

10.4 Test data for 802.11a RLAN Mode

10.4.1 Test data for Antenna 0

-. Operating condition : Highest Output Power Transmitting Mode

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	-1.96	0.05	-1.91	11.00	12.91
	Middle	5 220.00	-1.77	0.05	-1.72	11.00	12.72
	High	5 240.00	-1.47	0.05	-1.42	11.00	12.42

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value (dBm)	LIMIT (dBm / 500 kHz)	MARGIN (dB)
5 725 ~ 5 850	Low	5 745.00	-1.89	0.05	-1.84	30.00	31.84
	Middle	5 785.00	-2.19	0.05	-2.14	30.00	32.14
	High	5 825.00	-1.33	0.05	-1.28	30.00	31.28

Remark.1: Peak Power Spectral Density = Measured Value + Duty Cycle Factor

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

10.4.2 Test data for Antenna 1

-. Operating condition : Highest Output Power Transmitting Mode

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	-1.60	0.05	-1.55	11.00	12.55
	Middle	5 220.00	-1.90	0.05	-1.85	11.00	12.85
	High	5 240.00	-1.97	0.05	-1.92	11.00	12.92

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value (dBm)	LIMIT (dBm / 500 kHz)	MARGIN (dB)
5 725 ~ 5 850	Low	5 745.00	-2.28	0.05	-2.23	29.30	31.53
	Middle	5 785.00	-3.13	0.05	-3.08	29.30	32.38
	High	5 825.00	-2.16	0.05	-2.11	29.30	31.41

Remark.1: Peak Power Spectral Density = Measured Value + Duty Cycle Factor

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

10.4.3 Test data for Multiple Transmit

-. Operating condition : Highest Output Power Transmitting Mode

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	1.28	9.54	8.26
	Middle	5 220.00	1.23	9.54	8.31
	High	5 240.00	1.35	9.54	8.19

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / 500 kHz)	MARGIN (dB)
5 725 ~ 5 850	Low	5 745.00	0.98	26.94	25.96
	Middle	5 785.00	0.43	26.94	26.51
	High	5 825.00	1.34	26.94	25.60

Remark 1: Margin = Limit – Total Value

Remark 2: Calculated Output Power = $10\log (10^{(\text{Antenna0 Output Power}/10)} + 10^{(\text{Antenna1 Output Power}/10)})$

Remark 3: Calculated Antenna Gain = $10\log (10^{(\text{Antenna0 Gain}/10)} + 10^{(\text{Antenna1 Gain}/10)})$

Remark 4: Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

10.5 Test data for 802.11n_HT20 RLAN Mode

10.5.1 Test data for Antenna 0

-. Operating condition : Highest Output Power Transmitting Mode

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value' (dBm)	LIMIT (dBm) / MHz	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	-1.89	0.05	-1.84	11.00	12.84
	Middle	5 220.00	-1.86	0.05	-1.81	11.00	12.81
	High	5 240.00	-1.76	0.05	-1.71	11.00	12.71

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value (dBm)	LIMIT (dBm) / 500 kHz	MARGIN (dB)
5 725 ~ 5 850	Low	5 745.00	-2.07	0.05	-2.02	30.00	32.02
	Middle	5 785.00	-2.53	0.05	-2.48	30.00	32.48
	High	5 825.00	-2.17	0.05	-2.12	30.00	32.12

Remark.1: Peak Power Spectral Density = Measured Value + Duty Cycle Factor

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

10.5.2 Test data for Antenna 1

-. Operating condition : Highest Output Power Transmitting Mode

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value' (dBm)	LIMIT (dBm) / MHz	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	-2.27	0.05	-2.22	11.00	13.22
	Middle	5 220.00	-2.39	0.05	-2.34	11.00	13.34
	High	5 240.00	-2.15	0.05	-2.10	11.00	13.10

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value (dBm)	LIMIT (dBm) / 500 kHz	MARGIN (dB)
5 725 ~ 5 850	Low	5 745.00	-2.16	0.05	-2.11	29.30	31.41
	Middle	5 785.00	-2.55	0.05	-2.50	29.30	31.80
	High	5 825.00	-2.05	0.05	-2.00	29.30	31.30

Remark.1: Peak Power Spectral Density = Measured Value + Duty Cycle Factor

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

10.5.3 Test data for Multiple Transmit

-. Operating condition : Highest Output Power Transmitting Mode

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 180.00	0.98	9.54	8.56
	Middle	5 220.00	0.94	9.54	8.60
	High	5 240.00	1.11	9.54	8.43

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / 500 kHz)	MARGIN (dB)
5 725 ~ 5 850	Low	5 745.00	0.95	26.94	25.99
	Middle	5 785.00	0.52	26.94	26.42
	High	5 825.00	0.95	26.94	25.99

Remark 1: Margin = Limit – Total Value

Remark 2: Calculated Output Power = $10\log (10^{(\text{Antenna0 Output Power}/10)} + 10^{(\text{Antenna1 Output Power}/10)})$

Remark 3: Calculated Antenna Gain = $10\log (10^{(\text{Antenna0 Gain}/10)} + 10^{(\text{Antenna1 Gain}/10)})$

Remark 4: Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

10.6 Test data for 802.11n_HT40 RLAN Mode

10.6.1 Test data for Antenna 0

-. Operating condition : Highest Output Power Transmitting Mode

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result Value (dBm)	LIMIT (dBm) / MHz	MARGIN (dB)
5 150 ~ 5 250	Low	5 190.00	-4.95	0.10	-4.85	11.00	15.85
	High	5 230.00	-4.69	0.10	-4.59	11.00	15.59

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value (dBm)	LIMIT (dBm) / 500 kHz	MARGIN (dB)
5 725 ~ 5 850	Low	5 755.00	-4.92	0.10	-4.82	30.00	34.82
	High	5 795.00	-5.52	0.10	-5.42	30.00	35.42

Remark.1: Peak Power Spectral Density = Measured Value + Duty Cycle Factor

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

10.6.2 Test data for Antenna 1

-. Operating condition : Highest Output Power Transmitting Mode

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result VALUE (dBm)	LIMIT (dBm) / MHz	MARGIN (dB)
5 150 ~ 5 250	Low	5 190.00	-5.45	0.10	-5.35	11.00	16.35
	High	5 230.00	-5.07	0.10	-4.97	11.00	15.97

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value (dBm)	LIMIT (dBm) / 500 kHz	MARGIN (dB)
5 725 ~ 5 850	Low	5 755.00	-5.01	0.10	-4.91	29.30	34.21
	High	5 795.00	-6.11	0.10	-6.01	29.30	35.31

Remark.1: Peak Power Spectral Density = Measured Value + Duty Cycle Factor

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

10.6.3 Test data for Multiple Transmit

-. Operating condition : Highest Output Power Transmitting Mode

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 190.00	-2.08	9.54	11.62
	High	5 230.00	-1.77	9.54	11.31

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / 500 kHz)	MARGIN (dB)
5 725 ~ 5 850	Low	5 755.00	-1.85	26.94	28.79
	High	5 795.00	-2.69	26.94	29.63

Remark 1: Margin = Limit – Total Value

Remark 2: Calculated Output Power = $10\log(10^{(\text{Antenna0 Output Power}/10)} + 10^{(\text{Antenna1 Output Power}/10)})$

Remark 3: Calculated Antenna Gain = $10\log(10^{(\text{Antenna0 Gain}/10)} + 10^{(\text{Antenna1 Gain}/10)})$

Remark 4: Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

10.7 Test data for 802.11ac_HT80 RLAN Mode

10.7.1 Test data for Antenna 0

-. Operating condition : Highest Output Power Transmitting Mode

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 210.00	-8.42	0.35	-8.07	11.00	19.07

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value (dBm)	LIMIT (dBm / 500 kHz)	MARGIN (dB)
5 725 ~ 5 850	Low	5 775.00	-8.32	0.35	-7.97	30.00	37.97

Remark.1: Peak Power Spectral Density = Measured Value + Duty Cycle Factor

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

10.7.2 Test data for Antenna 1

-. Operating condition : Highest Output Power Transmitting Mode

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Low	5 210.00	-8.59	0.35	-8.24	11.00	19.24

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor (dB)	Result value (dBm)	LIMIT (dBm / 500 kHz)	MARGIN (dB)
5 725 ~ 5 850	Low	5 775.00	-8.72	0.35	-8.37	29.30	37.67

Remark.1: Peak Power Spectral Density = Measured Value + Duty Cycle Factor

Remark : Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

10.7.3 Test data for Multiple Transmit

-. Operating condition : Highest Output Power Transmitting Mode

-. Test Result : Pass

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / MHz)	MARGIN (dB)
5 150 ~ 5 250	Middle	5 210.00	-5.14	9.54	14.68

FREQUENCY RANGE (MHz)	CHANNEL	FREQUENCY (MHz)	ANT0 + ANT1 TOTAL VALUE (dBm)	LIMIT (dBm / 500 kHz)	MARGIN (dB)
5 725 ~ 5 850	Middle	5 775.00	-5.16	26.94	32.10

Remark 1: Margin = Limit – Total Value

Remark 2: Calculated Output Power = $10\log (10^{(\text{Antenna0 Output Power}/10)} + 10^{(\text{Antenna1 Output Power}/10)})$

Remark 3: Calculated Antenna Gain = $10\log (10^{(\text{Antenna0 Gain}/10)} + 10^{(\text{Antenna1 Gain}/10)})$

Remark 4: Limit = If the antenna's directional gain exceeds 6 dBi, the limit is reduced by the amount exceeded.

11. FREQUENCY STABILITY WITH TEMPERATURE VARIATION


11.1 Operating environment

Temperature : 22 °C

Relative humidity : 48 % R.H.

11.2 Test set-up

Turn EUT off and set chamber temperature to -20 °C and then allow sufficient time (approximately 20 min to 30 min after chamber reach the assigned temperature) for EUT to stabilize. Turn on the EUT and measure the EUT operating frequency and then turn off the EUT after the measurement. The temperature in the chamber was raised 10 °C step from -20 °C to +50 °C. Repeat above method for frequency measurements every 10 °C step and then record all measured frequencies on each temperature step.



11.3 Test Date

December 15, 2023 ~ January 12, 2024

11.4 Test Data for U-NII-1

-. Result : Pass

Temperature (°C)	Carrier Freq. (Hz)	Measured Freq. (Hz)	Frequency Error (Hz)
-20	5 180 000 000	5 180 077 500	77 500
-10		5 180 060 000	60 000
0		5 180 040 000	40 000
10		5 180 025 000	25 000
20		5 179 997 500	- 2 500
30		5 179 992 500	- 7 500
40		5 179 975 000	- 25 000
50		5 179 981 500	- 18 500
-20	5 220 000 000	5 220 055 000	55 000
-10		5 220 047 500	47 500
0		5 220 022 500	22 500
10		5 220 020 000	20 000
20		5 219 995 000	- 5 000
30		5 219 987 500	- 12 500
40		5 219 980 000	- 20 000
50		5 219 983 500	- 16 500
-20	5 240 000 000	5 240 062 500	62 500
-10		5 240 057 500	57 500
0		5 240 042 500	42 500
10		5 240 027 500	27 500
20		5 239 992 500	- 7 500
30		5 239 985 000	- 15 000
40		5 239 975 000	- 25 000
50		5 239 977 500	- 22 500

Note : While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.

Four measurements in total are made.(ANSI C63.10-2013)

11.5 Test Data for U-NII-3

-. Result : Pass

Temperature (°C)	Carrier Freq. (Hz)	Measured Freq. (Hz)	Frequency Error (Hz)
-20	5 745 000 000	5 745 072 500	72 500
-10		5 745 052 500	52 500
0		5 745 045 000	45 000
10		5 745 027 500	27 500
20		5 744 995 000	- 5 000
30		5 744 987 500	- 12 500
40		5 744 976 000	- 24 000
50		5 744 987 500	- 12 500
-20	5 785 000 000	5 785 057 500	57 500
-10		5 785 042 500	42 500
0		5 785 037 500	37 500
10		5 785 021 000	21 000
20		5 785 007 500	7 500
30		5 784 990 000	- 10 000
40		5 784 981 000	- 19 000
50		5 784 982 500	- 17 500
-20	5 825 000 000	5 825 065 000	65 000
-10		5 825 042 500	42 500
0		5 825 033 000	33 000
10		5 825 017 500	17 500
20		5 824 999 000	- 1 000
30		5 824 985 000	- 15 000
40		5 824 980 500	- 19 500
50		5 824 982 500	- 17 500

Note : While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.

Four measurements in total are made.(ANSI C63.10-2013)

12. FREQUENCY STABILITY WITH VOLTAGE VARIATION


12.1 Operating environment

Temperature : 22 °C

Relative humidity : 48 % R.H.

12.2 Test set-up

An external DC power supply was connected to the input of the EUT. The voltage of EUT set to 115.0 % of the nominal value and then was reduced to 85.0 % of nominal voltage. The output frequency was recorded at each step.



12.3 Test Date

December 15, 2023 ~ January 12, 2024

12.4 Test Data for U-NII-1

-. Result : Pass

Voltage (VDC)	Carrier Freq. (Hz)	Measured Freq. (Hz)	Frequency Error (Hz)
14.00	5 180 000 000	5 179 996 500	- 3 500
11.90		5 179 997 000	- 3 000
16.10		5 179 995 000	- 5 000
14.00	5 220 000 000	5 219 995 500	- 4 500
11.90		5 219 995 000	- 5 000
16.10		5 219 993 500	- 6 500
14.00	5 240 000 000	5 239 993 500	- 6 500
11.90		5 239 993 000	- 7 000
16.10		5 239 992 000	- 8 000

12.5 Test Data for U-NII-3

-. Result : Pass

Voltage (VDC)	Carrier Freq. (Hz)	Measured Freq. (Hz)	Frequency Error (Hz)
14.00	5 745 000 000	5 744 995 000	- 5 000
11.90		5 744 995 500	- 4 500
16.10		5 744 994 000	- 6 000
14.00	5 785 000 000	5 785 007 500	7 500
11.90		5 785 002 500	2 500
16.10		5 785 003 500	3 500
14.00	5 825 000 000	5 824 998 500	- 1 500
11.90		5 824 999 000	- 1 000
16.10		5 824 998 000	- 2 000

13. RADIATED SPURIOUS EMISSIONS

13.1 Operating environment

Temperature : 22 °C


Relative humidity : 48 % R.H.

13.2 Test set-up for conducted measurement


The radiated emissions measurements were on the 3 m semi anechoic chamber. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.

The frequency spectrum from 30 MHz to 40 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.


1. Below 30 MHz



2. 30 MHz - 1 GHz



3. Above 1 GHz



13.3 Test Date

December 15, 2023 ~ January 12, 2024

13.4 Test data for Below 30 MHz

- . Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)
- . Frequency range : 9 kHz ~ 30 MHz
- . Measurement distance : 3 m
- . Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dBμV/m)	Limits (dBμV/m)	Margin (dB)
Emission from the EUT more than 20 dB below the limit in each frequency range.									

13.5 Test data for 30 MHz ~ 1 000 MHz

13.5.1 Test data for WLAN 5 GHz


Limits apply to : FCC CFR 47, PART 15, SUBPART E, SECTION 15.407

Result : PASSED

EUT : Car Navigation

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)

-. Antenna 0, Antenna 1 and Multiple transmit tested, but the worst data were recorded.



No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	QP	FACTOR	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	77.530	31.0	13.2	1.3	32.0	13.5	40.0	26.5	400	359
2	145.430	28.9	18.8	1.8	32.1	17.4	43.5	26.1	100	102
3	562.529	29.6	23.7	3.7	32.3	24.7	46.0	21.3	300	0
----- Vertical -----										
4	40.670	38.0	16.7	0.9	32.1	23.5	40.0	16.5	100	359
5	77.530	35.1	13.2	1.3	32.0	17.6	40.0	22.4	100	359
6	102.750	33.2	15.8	1.4	32.1	18.3	43.5	25.2	400	334


13.5.2 Test data for Intermodulation Mode(Bluetooth + WLAN 5 GHz)

Limits apply to : FCC CFR 47, PART 15, SUBPART E, SECTION 15.407

Result : PASSED

EUT : Car Navigation

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	[dBuV]	FACTOR	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	140.580	29.0	19.2	1.8	32.1	17.9	43.5	25.6	400	0
2	181.320	30.2	16.4	2.0	32.1	16.5	43.5	27.0	200	0
3	830.241	29.8	27.2	4.4	32.2	29.2	46.0	16.8	400	263
----- Vertical -----										
4	41.640	38.7	16.3	0.9	32.1	23.8	40.0	16.2	100	188
5	76.560	34.6	13.2	1.3	32.0	17.1	40.0	22.9	100	0
6	832.181	30.1	27.2	4.4	32.2	29.5	46.0	16.5	200	359


13.5.3 Test data for Intermodulation Mode(WLAN 2 GHz + WLAN 5 GHz)

Limits apply to : FCC CFR 47, PART 15, SUBPART E, SECTION 15.407

Result : PASSED

EUT : Car Navigation

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ [MHz]	READING [dBuV]	ANT PEAK FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	139.610	29.8	19.2	1.8	32.1	18.7	43.5	24.8	400	314
2	562.529	30.4	23.7	3.7	32.3	25.5	46.0	20.5	300	359
3	844.791	30.6	27.2	4.5	32.2	30.1	46.0	15.9	200	0
----- Vertical -----										
4	40.670	39.0	16.7	0.9	32.1	24.5	40.0	15.5	100	86
5	77.530	36.2	13.2	1.3	32.0	18.7	40.0	21.3	100	0
6	242.430	38.3	17.3	2.3	32.1	25.8	46.0	20.2	400	359

13.6 Test data for Above 1 GHz

13.6.1 Test data for Frequency UNII I

13.6.1.1 Test data for 802.11a RLAN Mode

13.6.1.1.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
1 MHz and Peak Detector for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : 98.95 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit										
10 373.84	50.44	Peak	H	39.50	10.01	42.10	-	57.85	68.20	10.35
10 383.18	50.53	Peak	V	39.53	10.01	42.10	-	57.97	68.20	10.23
10 424.82	50.68	Peak	H	39.75	10.01	42.10	-	58.34	68.20	9.86
10 430.01	50.46	Peak	V	39.78	10.01	42.10	-	58.15	68.20	10.05
10 489.59	50.21	Peak	H	39.98	9.80	42.10	-	57.89	68.20	10.31
10 498.53	50.36	Peak	V	40.00	9.80	42.10	-	58.06	68.20	10.14

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

13.6.1.2 Test data for 802.11n_HT20 RLAN Mode

13.6.1.2.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
1 MHz and Peak Detector for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : 98.88 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit										
10 362.50	50.71	Peak	H	39.45	10.01	42.10	-	58.07	68.20	10.13
10 380.68	50.22	Peak	V	39.52	10.01	42.10	-	57.65	68.20	10.55
10 432.06	50.70	Peak	H	39.79	10.01	42.10	-	58.40	68.20	9.80
10 436.90	50.75	Peak	V	39.82	10.01	42.10	-	58.48	68.20	9.72
10 489.99	50.38	Peak	H	39.98	9.80	42.10	-	58.06	68.20	10.14
10 496.53	50.95	Peak	V	39.99	9.80	42.10	-	58.64	68.20	9.56

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

13.6.1.3 Test data for 802.11n_HT40 RLAN Mode

13.6.1.3.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
1 MHz and Peak Detector for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : 97.71 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit										
10 386.79	50.28	Peak	H	39.55	10.01	42.10	-	57.74	68.20	10.46
10 397.98	50.17	Peak	V	39.59	10.01	42.10	-	57.67	68.20	10.53
10 420.84	50.48	Peak	H	39.73	10.01	42.10	-	58.12	68.20	10.08
10 420.44	50.20	Peak	V	39.72	10.01	42.10	-	57.83	68.20	10.37

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

13.6.1.4 Test data for 802.11ac_HT80 RLAN Mode

13.6.1.4.1 Test data for Multiple Transmit

- . Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
1 MHz and Peak Detector for the emissions outside restricted band
- . Video bandwidth : 3 MHz for Peak and Average Mode
- . Frequency range : 1 GHz ~ 40 GHz
- . Measurement distance : 3 m
- . Duty Cycle : 92.34 %
- . Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit										
10 413.21	49.68	Peak	H	39.68	10.01	42.10	-	57.27	68.20	10.93
10 417.60	49.46	Peak	V	39.71	10.01	42.10	-	57.08	68.20	11.12

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

13.6.2 Test data for Frequency UNII 3

13.6.2.1 Test data for 802.11a RLAN Mode

13.6.2.1.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
1 MHz and Peak Detector for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : 98.95 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit										
11 488.90	49.66	Peak	H	40.16	10.12	42.00	-	57.94	74.00	16.06
11 483.06	37.14	Average	H	40.13	10.12	42.00	0.05	45.44	54.00	8.56
11 479.86	49.14	Peak	V	40.12	10.12	42.00	-	57.38	74.00	16.62
11 485.90	37.01	Average	V	40.14	10.12	42.00	0.05	45.32	54.00	8.68
11 558.16	49.55	Peak	H	40.08	10.14	41.99	-	57.78	74.00	16.22
11 548.52	36.96	Average	H	40.10	10.12	41.99	0.05	45.24	54.00	8.76
11 562.46	49.53	Peak	V	40.08	10.14	41.99	-	57.76	74.00	16.24
11 545.57	36.99	Average	V	40.11	10.12	41.99	0.05	45.28	54.00	8.72
11 633.02	48.78	Peak	H	39.74	10.14	41.97	-	56.69	74.00	17.31
11 630.77	36.42	Average	H	39.75	10.14	41.97	0.05	44.39	54.00	9.61
11 639.86	49.13	Peak	V	39.68	10.14	41.97	-	56.98	74.00	17.02
11 630.92	36.56	Average	V	39.75	10.14	41.97	0.05	44.53	54.00	9.47

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

13.6.2.2 Test data for 802.11n_HT20 RLAN Mode

13.6.2.2.1 Test data for Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
1 MHz and Peak Detector for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : 98.88 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit										
11 483.36	49.29	Peak	H	40.13	10.12	42.00	-	57.54	74.00	16.46
11 493.65	37.10	Average	H	40.17	10.12	42.00	0.05	45.44	54.00	8.56
11 471.62	49.74	Peak	V	40.09	10.12	42.01	-	57.94	74.00	16.06
11 471.02	36.90	Average	V	40.08	10.12	42.01	0.05	45.14	54.00	8.86
11 547.07	48.91	Peak	H	40.11	10.12	41.99	-	57.15	74.00	16.85
11 549.32	36.98	Average	H	40.10	10.12	41.99	0.05	45.26	54.00	8.74
11 547.62	49.41	Peak	V	40.10	10.12	41.99	-	57.64	74.00	16.36
11 565.70	36.92	Average	V	40.07	10.14	41.99	0.05	45.19	54.00	8.81
11 628.07	49.01	Peak	H	39.78	10.14	41.97	-	56.96	74.00	17.04
11 629.92	36.37	Average	H	39.76	10.14	41.97	0.05	44.35	54.00	9.65
11 626.82	49.33	Peak	V	39.79	10.14	41.97	-	57.29	74.00	16.71
11 625.52	36.43	Average	V	39.80	10.14	41.97	0.05	44.45	54.00	9.55

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

13.6.2.3 Test data for 802.11n_HT40 RLAN Mode

13.6.2.3.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
1 MHz and Peak Detector for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 40 GHz
- Measurement distance : 3 m
- Duty Cycle : 97.71 %
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit										
11 462.65	49.17	Peak	H	40.05	10.12	42.01	-	57.33	74.00	16.67
11 498.51	37.02	Average	H	40.19	10.12	42.00	0.10	45.43	54.00	8.57
11 529.28	49.72	Peak	V	40.14	10.12	41.99	-	57.99	74.00	16.01
11 482.33	36.90	Average	V	40.13	10.12	42.00	0.10	45.25	54.00	8.75
11 553.44	49.23	Peak	H	40.09	10.14	41.99	-	57.47	74.00	16.53
11 557.03	37.00	Average	H	40.09	10.14	41.99	0.10	45.34	54.00	8.66
11 541.15	49.11	Peak	V	40.12	10.12	41.99	-	57.36	74.00	16.64
11 554.34	36.85	Average	V	40.09	10.14	41.99	0.10	45.19	54.00	8.81

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

13.6.2.4 Test data for 802.11ac_VHT80 RLAN Mode

13.6.2.4.1 Test data for Multiple Transmit

- . Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
1 MHz and Peak Detector for the emissions outside restricted band
- . Video bandwidth : 3 MHz for Peak and Average Mode
- . Frequency range : 1 GHz ~ 40 GHz
- . Measurement distance : 3 m
- . Duty Cycle : 92.34 %
- . Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit										
11 556.69	49.02	Peak	H	40.09	10.14	41.99	-	57.26	74.00	16.74
11 520.83	36.94	Average	H	40.16	10.12	42.00	0.35	45.57	54.00	8.43
11 536.21	49.45	Peak	V	40.13	10.12	41.99	-	57.71	74.00	16.29
11 522.13	36.92	Average	V	40.16	10.12	42.00	0.35	45.55	54.00	8.45

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

14.4 Test data for Frequency UNII I

14.4.1 Test data for 802.11a RLAN Mode

14.4.1.1 Test data for Multiple Transmit

- . Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- . Video bandwidth : 3 MHz for Peak and Average Mode
- . Measurement distance : 3 m
- . Duty Cycle : 98.95 %
- . Result : Pass

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	ATT (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit											
5 148.41	53.37	Peak	H	31.91	6.51	41.77	6.13	-	56.15	74.00	17.85
5 145.01	42.74	Average	H	31.92	6.51	41.77	6.13	0.05	45.58	54.00	8.42
5 139.58	53.69	Peak	V	31.94	6.51	41.77	6.13	-	56.50	74.00	17.50
5 128.71	42.34	Average	V	31.99	6.51	41.77	6.13	0.05	45.25	54.00	8.75

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

14.4.2 Test data for 802.11n_HT20 RLAN Mode

14.4.2.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : 98.88 %
- Result : Pass

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	ATT (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit											
5 149.09	53.89	Peak	H	31.90	6.51	41.77	6.13	-	56.66	74.00	17.34
5 149.77	42.84	Average	H	31.90	6.51	41.77	6.13	0.05	45.66	54.00	8.34
5 132.79	53.52	Peak	V	31.97	6.51	41.77	6.13	-	56.36	74.00	17.64
5 134.83	42.26	Average	V	31.96	6.51	41.77	6.13	0.05	45.14	54.00	8.86

Tabulated test data for Restricted Band

Remark - “H”: Horizontal, “V”: Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

14.4.3 Test data for 802.11n_HT40 RLAN Mode

14.4.3.1 Test data for Multiple Transmit

- . Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- . Video bandwidth : 3 MHz for Peak and Average Mode
- . Measurement distance : 3 m
- . Duty Cycle : 97.71 %
- . Result : Pass

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	ATT (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit											
5 148.99	54.42	Peak	H	31.90	6.51	41.77	6.13	-	57.19	74.00	16.81
5 148.30	42.87	Average	H	31.91	6.51	41.77	6.13	0.10	45.75	54.00	8.25
5 108.32	53.12	Peak	V	32.07	6.50	41.78	6.13	-	56.04	74.00	17.96
5 147.61	42.41	Average	V	31.91	6.51	41.77	6.13	0.10	45.29	54.00	8.71

Tabulated test data for Restricted Band

Remark - “H”: Horizontal, “V”: Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

14.4.4 Test data for 802.11ac_VHT80 RLAN Mode

14.4.4.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : 92.34 %
- Result : Pass

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	ATT (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit											
5 144.39	56.18	Peak	H	31.92	6.51	41.77	6.13	-	58.97	74.00	15.03
5 145.10	43.49	Average	H	31.92	6.51	41.77	6.13	0.35	46.63	54.00	7.37
4 986.93	53.17	Peak	V	31.27	6.38	41.80	6.15	-	55.17	74.00	18.83
5 145.81	42.28	Average	V	31.92	6.51	41.77	6.13	0.35	45.42	54.00	8.58

Tabulated test data for Restricted Band

Remark - “H”: Horizontal, “V”: Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

14.5 Test data for Frequency U-NII-3

14.5.1 Test data for 802.11a RLAN Mode

14.5.1.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : 98.95 %
- Result : Pass

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	ATT (dB)	Duty (dB)	Total (dBuV/m)	Limits (dBuV/m)	Margin (dB)
Multiple Transmit											
5 650.27	53.01	Peak	H	31.90	6.79	41.70	6.13	-	56.13	68.40	12.27
5 714.20	65.32	Peak	H	31.90	6.77	41.70	6.12	-	68.41	109.18	40.77
5 720.24	64.87	Peak	H	31.90	6.77	41.70	6.12	-	67.96	111.35	43.39
5 854.98	54.07	Peak	H	32.41	6.74	41.70	6.12	-	57.64	110.85	53.21
5 870.71	55.51	Peak	H	32.44	6.74	41.70	6.12	-	59.11	106.40	47.29
5 924.83	53.54	Peak	H	32.50	6.83	41.70	6.13	-	57.30	68.33	11.03
5 650.08	52.32	Peak	V	31.90	6.79	41.70	6.13	-	55.44	68.26	12.82
5 719.99	62.99	Peak	V	31.90	6.77	41.70	6.12	-	66.08	110.80	44.72
5 720.30	61.64	Peak	V	31.90	6.77	41.70	6.12	-	64.73	111.48	46.75
5 854.78	54.36	Peak	V	32.41	6.74	41.70	6.12	-	57.93	111.30	53.37
5 874.87	54.91	Peak	V	32.45	6.74	41.70	6.12	-	58.52	105.24	46.72
5 924.98	54.13	Peak	V	32.50	6.83	41.70	6.13	-	57.89	68.21	10.32

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	ATT (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit											
5 651.07	53.23	Peak	H	31.90	6.79	41.70	6.13	-	56.35	68.99	12.64
5 701.57	53.46	Peak	H	31.90	6.77	41.70	6.12	-	56.55	105.64	49.09
5 720.36	54.09	Peak	H	31.90	6.77	41.70	6.12	-	57.18	111.62	54.44
5 854.14	60.50	Peak	H	32.41	6.74	41.70	6.12	-	64.07	112.76	48.69
5 873.91	54.89	Peak	H	32.45	6.74	41.70	6.12	-	58.50	105.51	47.01
5 924.63	54.05	Peak	H	32.50	6.83	41.70	6.13	-	57.81	68.47	10.66
5 650.32	52.56	Peak	V	31.90	6.79	41.70	6.13	-	55.68	68.44	12.76
5 704.13	54.05	Peak	V	31.90	6.77	41.70	6.12	-	57.14	106.36	49.22
5 720.02	53.32	Peak	V	31.90	6.77	41.70	6.12	-	56.41	110.85	54.44
5 854.83	58.00	Peak	V	32.41	6.74	41.70	6.12	-	61.57	111.19	49.62
5 874.99	54.21	Peak	V	32.45	6.74	41.70	6.12	-	57.82	105.20	47.38
5 923.28	55.48	Peak	V	32.50	6.83	41.70	6.13	-	59.24	69.47	10.23

Tabulated test data for Restricted Band

Remark - “H”: Horizontal, “V”: Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

14.5.2 Test data for 802.11n_HT20 RLAN Mode

14.5.2.1 Test data for Multiple Transmit

- . Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- . Video bandwidth : 3 MHz for Peak and Average Mode
- . Measurement distance : 3 m
- . Duty Cycle : 98.88 %
- . Result : Pass

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	ATT (dB)	Duty (dB)	Total (dBuV/m)	Limits (dBuV/m)	Margin (dB)
Multiple Transmit											
5 650.27	53.04	Peak	H	31.90	6.79	41.70	6.13	-	56.16	68.40	12.24
5 719.21	63.58	Peak	H	31.90	6.77	41.70	6.12	-	66.67	110.58	43.91
5 720.06	63.43	Peak	H	31.90	6.77	41.70	6.12	-	66.52	110.94	44.42
5 854.93	54.79	Peak	H	32.41	6.74	41.70	6.12	-	58.36	110.96	52.60
5 874.89	53.93	Peak	H	32.45	6.74	41.70	6.12	-	57.54	105.23	47.69
5 924.53	54.06	Peak	H	32.50	6.83	41.70	6.13	-	57.82	68.55	10.73
5 650.22	52.05	Peak	V	31.90	6.79	41.70	6.13	-	55.17	68.36	13.19
5 718.33	60.95	Peak	V	31.90	6.77	41.70	6.12	-	64.04	110.33	46.29
5 720.07	58.82	Peak	V	31.90	6.77	41.70	6.12	-	61.91	110.96	49.05
5 854.87	54.95	Peak	V	32.41	6.74	41.70	6.12	-	58.52	111.10	52.58
5 874.49	54.63	Peak	V	32.45	6.74	41.70	6.12	-	58.24	105.34	47.10
5 924.98	53.24	Peak	V	32.50	6.83	41.70	6.13	-	57.00	68.21	11.21

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	ATT (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit											
5 650.52	53.08	Peak	H	31.90	6.79	41.70	6.13	-	56.20	68.58	12.38
5 700.91	53.80	Peak	H	31.90	6.77	41.70	6.12	-	56.89	105.45	48.56
5 720.03	54.53	Peak	H	31.90	6.77	41.70	6.12	-	57.62	110.87	53.25
5 854.75	60.39	Peak	H	32.41	6.74	41.70	6.12	-	63.96	111.37	47.41
5 855.91	60.77	Peak	H	32.41	6.74	41.70	6.12	-	64.34	110.55	46.21
5 924.68	53.57	Peak	H	32.50	6.83	41.70	6.13	-	57.33	68.44	11.11
5 650.42	52.66	Peak	V	31.90	6.79	41.70	6.13	-	55.78	68.51	12.73
5 700.43	53.39	Peak	V	31.90	6.77	41.70	6.12	-	56.48	105.32	48.84
5 720.06	53.94	Peak	V	31.90	6.77	41.70	6.12	-	57.03	110.94	53.91
5 854.90	57.89	Peak	V	32.41	6.74	41.70	6.12	-	61.46	111.03	49.57
5 874.87	54.16	Peak	V	32.45	6.74	41.70	6.12	-	57.77	105.24	47.47
5 924.73	53.77	Peak	V	32.50	6.83	41.70	6.13	-	57.53	68.40	10.87

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

14.5.3 Test data for 802.11n_HT40 RLAN Mode

14.5.3.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : 97.71 %
- Result : Pass

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	ATT (dB)	Duty (dB)	Total (dBuV/m)	Limits (dBuV/m)	Margin (dB)
Multiple Transmit											
5650.67	53.03	Peak	H	31.90	6.79	41.70	6.13	-	56.15	68.70	12.55
5714.02	66.31	Peak	H	31.90	6.77	41.70	6.12	-	69.40	109.13	39.73
5720.08	64.57	Peak	H	31.90	6.77	41.70	6.12	-	67.66	110.98	43.32
5854.91	53.85	Peak	H	32.41	6.74	41.70	6.12	-	57.42	111.01	53.59
5874.03	54.38	Peak	H	32.45	6.74	41.70	6.12	-	57.99	105.47	47.48
5924.98	53.24	Peak	H	32.50	6.83	41.70	6.13	-	57.00	68.21	11.21
5650.17	53.02	Peak	V	31.90	6.79	41.70	6.13	-	56.14	68.33	12.19
5714.92	61.86	Peak	V	31.90	6.77	41.70	6.12	-	64.95	109.38	44.43
5720.32	62.65	Peak	V	31.90	6.77	41.70	6.12	-	65.74	111.53	45.79
5854.93	54.78	Peak	V	32.41	6.74	41.70	6.12	-	58.35	110.96	52.61
5872.37	54.94	Peak	V	32.44	6.74	41.70	6.12	-	58.54	105.94	47.40
5924.48	54.31	Peak	V	32.50	6.83	41.70	6.13	-	58.07	68.58	10.51

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	ATT (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit											
5650.27	52.53	Peak	H	31.90	6.79	41.70	6.13	-	55.65	68.40	12.75
5700.63	54.20	Peak	H	31.90	6.77	41.70	6.12	-	57.29	105.38	48.09
5720.31	56.33	Peak	H	31.90	6.77	41.70	6.12	-	59.42	111.51	52.09
5854.86	56.10	Peak	H	32.41	6.74	41.70	6.12	-	59.67	111.12	51.45
5872.57	55.17	Peak	H	32.45	6.74	41.70	6.12	-	58.78	105.88	47.10
5924.43	53.84	Peak	H	32.50	6.83	41.70	6.13	-	57.60	68.62	11.02
5650.42	53.04	Peak	V	31.90	6.79	41.70	6.13	-	56.16	68.51	12.35
5700.35	53.66	Peak	V	31.90	6.77	41.70	6.12	-	56.75	105.30	48.55
5720.41	54.90	Peak	V	31.90	6.77	41.70	6.12	-	57.99	111.73	53.74
5854.74	54.94	Peak	V	32.41	6.74	41.70	6.12	-	58.51	111.39	52.88
5874.71	54.49	Peak	V	32.45	6.74	41.70	6.12	-	58.10	105.28	47.18
5923.98	54.61	Peak	V	32.50	6.83	41.70	6.13	-	58.37	68.95	10.58

Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

14.5.4 Test data for 802.11ac_VHT80 RLAN Mode

14.5.4.1 Test data for Multiple Transmit

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : 92.34 %
- Result : Pass

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Gain (dB)	ATT (dB)	Duty (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Multiple Transmit											
5 650.67	53.15	Peak	H	31.90	6.79	41.70	6.13	-	56.27	68.70	12.43
5 709.78	64.65	Peak	H	31.90	6.77	41.70	6.12	-	67.74	107.94	40.20
5 720.12	64.11	Peak	H	31.90	6.77	41.70	6.12	-	67.20	111.07	43.87
5 854.93	56.65	Peak	H	32.41	6.74	41.70	6.12	-	60.22	110.96	50.74
5 869.06	58.06	Peak	H	32.44	6.74	41.70	6.12	-	61.66	106.86	45.20
5 924.83	54.22	Peak	H	32.50	6.83	41.70	6.13	-	57.98	68.33	10.35
5 650.17	53.71	Peak	V	31.90	6.79	41.70	6.13	-	56.83	68.33	11.50
5 707.32	62.60	Peak	V	31.90	6.77	41.70	6.12	-	65.69	107.25	41.56
5 720.88	61.75	Peak	V	31.90	6.77	41.70	6.12	-	64.84	112.81	47.97
5 854.62	55.47	Peak	V	32.41	6.74	41.70	6.12	-	59.04	111.67	52.63
5 871.59	55.57	Peak	V	32.44	6.74	41.70	6.12	-	59.17	106.15	46.98
5 923.23	54.95	Peak	V	32.50	6.83	41.70	6.13	-	58.71	69.51	10.80


Tabulated test data for Restricted Band

Remark - "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Emission Level (dBμV/m)

14.5.5 U-NII-3 Emission Limits

14.5.5.1 Emission Mask Plots



Remark.

-. Title 47 → Part 15 → Subpart E—UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE DEVICES

§ 15.407 General technical requirements.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

15. LIST OF TEST EQUIPMENT

Model Number	Manufacturer	Description	Serial Number	Last Cal.(Interval)
FSV40-N	Rohde & Schwarz	Signal Analyzer	102165	Jul. 15, 2024 (1Y)
FSV40-N	Rohde & Schwarz	Signal Analyzer	101651	Jul. 15, 2024 (1Y)
FSVA40	Rohde & Schwarz	Signal Analyzer	101593	Jul. 15, 2024 (1Y)
ESU	Rohde & Schwarz	EMI Test Receiver	100261	Mar. 06, 2023 (1Y)
310N	Sonoma Instrument	Pre-Amplifier	392756	Oct. 16, 2023 (1Y)
SCU18	Rohde & Schwarz	Signal Conditioning unit	102266	Jul. 11, 2023 (1Y)
SCU40A	Rohde & Schwarz	Signal Conditioning unit	100436	Jan. 18, 2024 (1Y)
SH-241	ESPEC	Temperature&Humidity Chamber	92009049	Jan. 16, 2024 (1Y)
F-40-10.0-RF	RLC Electronis	High Pass Filter	0427	Jan. 15, 2024 (1Y)
FMZB 1513	Schwarzbeck	Loop Antenna	1513-235	Mar. 24, 2022 (2Y)
HLP-2008	TDK	Hybrid Antenna	131316	Mar. 07, 2022 (2Y)
BBHA9120D	Schwarzbeck	Horn Antenna	9120D-1366	Jun. 22, 2023 (1Y)
BBHA9170	Schwarzbeck	Horn Antenna	BBHA9170179	Jan. 25, 2024 (1Y)
DT2000-2t	Innco System	Turn Table	N/A	N/A
MA-4640-XPET	Innco System	Antenna Master	MA4640/652/43100318/P	N/A
CO3000	Innco System	Controller	1026/40960617/P	N/A

All test equipment used is calibrated on a regular basis.