

RADIO PERFORMANCE TEST REPORT

Test Report No. : OT-22D-RWD-050

Reception No. : 2204001282

Applicant : LG Electronics USA

Address : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, 07632, United States

Manufacturer : LG Electronics Inc.

Address : 222 LG-ro, Jinwi-Myeon, Pyeongtaek -Si, Gyeonggi-Do, 451-713, Korea

Type of Equipment : Car Navigation

FCC ID. : BEJ-MIB3GP

Model Name : MIB3GP

Multiple Model Name : N/A

Serial number : N/A

Total page of Report : 32 pages (including this page)

Date of Incoming : November 28, 2022

Date of issue : December 29, 2022

SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.


This report is not correlated with the "KS Q ISO/IEC 17025 and KOLAS accreditation" of Korean Laboratory Accreditation Scheme.



Tested by
Myeong-Hwa, Jang / Manager
ONETECH Corp.



Reviewed by
Tae-Ho, Kim / General Manager
ONETECH Corp.



Approved by
Ki-Hong, Nam / General Manager
ONETECH Corp.

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	5
2. TEST SUMMARY	6
2.1 TEST ITEMS AND RESULTS	6
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS.....	6
2.3 RELATED SUBMITTAL(S) / GRANT(S)	6
2.4 PURPOSE OF THE TEST	6
2.5 TEST METHODOLOGY.....	6
2.6 TEST FACILITY.....	6
3. GENERAL INFORMATION.....	7
3.1 PRODUCT DESCRIPTION.....	7
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	9
4. EUT MODIFICATIONS.....	9
5. SYSTEM TEST CONFIGURATION	10
5.1 JUSTIFICATION.....	10
5.2 PERIPHERAL EQUIPMENT	10
5.3 MODE OF OPERATION DURING THE TEST	10
5.4 CONFIGURATION OF TEST SYSTEM.....	12
5.5 ANTENNA REQUIREMENT	12
6. PRELIMINARY TEST	12
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....	12
6.2 GENERAL RADIATED EMISSIONS TESTS	12
7. MIMIMUM 6 DB BANDWIDTH	13
7.1 OPERATING ENVIRONMENT	13
7.2 TEST SET-UP	13
7.3 TEST DATE	13
7.4 TEST DATA FOR 802.11B WLAN MODE.....	14
7.5 TEST DATA FOR 802.11G WLAN MODE	14
7.6 TEST DATA FOR 802.11N_HT20 WLAN MODE.....	14
8. MAXIMUM CONDUCTED(AVERAGE) OUTPUT POWER	15
8.1 OPERATING ENVIRONMENT	15
8.2 TEST SET-UP	15
8.3 TEST DATE	15

8.4 TEST DATA FOR 802.11B WLAN MODE.....	16
8.5 TEST DATA FOR 802.11G WLAN MODE	16
8.6 TEST DATA FOR 802.11N_HT20 WLAN MODE.....	16
9. 100 KHZ BANDWIDTH OUTSIDE THE FREQUENCY BAND.....	17
9.1 OPERATING ENVIRONMENT	17
9.2 TEST SET-UP FOR CONDUCTED MEASUREMENT	17
9.3 TEST SET-UP FOR RADIATED MEASUREMENT.....	17
9.4 TEST DATE	17
9.5 TEST DATA FOR CONDUCTED EMISSION	17
9.6 TEST DATA FOR RADIATED EMISSION.....	18
9.6.1 Radiated Emission which fall in the Restricted Band.....	18
9.6.2 Spurious & Harmonic Radiated Emission.....	21
10. POWER SPECTRAL DENSITY	24
10.1 OPERATING ENVIRONMENT	24
10.2 TEST SET-UP	24
10.3 TEST DATE	24
10.4 TEST DATA FOR 802.11B WLAN MODE.....	25
10.5 TEST DATA FOR 802.11G WLAN MODE	25
10.6 TEST DATA FOR 802.11N_HT20 WLAN MODE.....	25
11. RADIATED EMISSION TEST	26
11.1 OPERATING ENVIRONMENT	26
11.2 TEST SET-UP	26
11.3 TEST DATE	27
11.4 TEST DATA FOR 30 MHz ~ 1 000 MHz	28
11.4.1 Test data for WLAN 2.4 GHz	28
11.4.2 Test data for Intermodulation Mode(Bluetooth + WLAN 2.4 GHz)	29
11.4.3 Test data for Intermodulation Mode(WLAN 2.4 GHz + WLAN 5 GHz)	30
11.5 TEST DATA FOR BELOW 30 MHz	31
11.6 TEST DATA FOR ABOVE 1 GHz	31
12. LIST OF TEST EQUIPMENT	32

※ Please refer to the Annex section for All test plots

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-22D-RWD-050	December 29, 2022	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : LG Electronics USA

Address : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, 07632, United States

Contact Person : Sung Soo, Kim / Director, Regulatory and Environmental Affairs

Telephone No. : +201-266-2215

FCC ID : BEJ-MIB3GP

Model Name : MIB3GP

Brand Name : LG, Volkswagen, Seat, Skoda, Ford

Serial Number : N/A

Date : December 29, 2022

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Car Navigation
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.247 (a) (2)	Minimum 6 dB Bandwidth	Met the Limit / PASS
15.247 (b) (3)	Maximum Conducted Output Power	Met the Limit / PASS
15.247 (d)	100 kHz Bandwidth Outside the Frequency Band	Met the Limit / PASS
15.247 (d)	Radiated Emission which fall in the Restricted Band	Met the Limit / PASS
15.247 (e)	Power Spectral Density	Met the Limit / PASS
15.209	Radiated Emission Limits	Met the Limit / PASS
15.207	Conducted Limits	N/A (See Note)
15.203	Antenna Requirement	Met requirement / PASS

Note: This test is not performed because the EUT is operated by only using DC Power.

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART C Section 15.247.

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea.

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-20122/ C-14617/ G-10666/ T-11842

ISED (Innovation, Science and Economic Development Canada) – Registration No. Site# 3736A-3

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

3. GENERAL INFORMATION

3.1 Product Description

The LG Electronics USA, Model MIB3GP (referred to as the EUT in this report) is a Car Navigation. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Car Navigation	
OPERATING FREQUENCY	Bluetooth	2 402 MHz ~ 2 480 MHz
	WLAN 2.4 GHz	2 412 MHz ~ 2 462 MHz (802.11b/g/n(HT20))
	WLAN	5 180 MHz ~ 5 240 MHz (802.11a/n(HT20))
	5 150 MHz ~	5 190 MHz ~ 5 230 MHz (802.11n(HT40))
	5 250 MHz Band	5 210 MHz (802.11ac(VHT80))
	WLAN	5 745 MHz ~ 5 825 MHz (802.11a/n(HT20))
	5 725 MHz ~	5 755 MHz ~ 5 795 MHz (802.11n(HT40))
	5 850 MHz Band	5 775 MHz (802.11ac(VHT80))
MODULATION TYPE	Bluetooth	GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps, 8-DPSK for 3Mbps
	WLAN 2.4 GHz	802.11b: DSSS Modulation (DBPSK/DQPSK/CCK) 802.11g/n(HT20): OFDM Modulation (BPSK/QPSK/16QAM/64QAM)
	WLAN 5 GHz	802.11a/n(HT20)/n(HT40)/ac(VHT80): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)

RF OUTPUT POWER	Bluetooth	2.51 dBm (1 Mbps) 1.77 dBm (2 Mbps) 2.02 dBm (3 Mbps)	
	WLAN 2.4 GHz	8.51 dBm (802.11b) 8.63 dBm (802.11g) 8.83 dBm (802.11n_HT20)	
	WLAN 5 150 MHz ~ 5 250 MHz Band	Antenna 0	9.62 dBm(802.11a) 9.59 dBm(802.11n_HT20) 9.69 dBm(802.11n_HT40) 9.79 dBm(802.11ac_VHT80)
		Antenna 1	9.34 dBm(802.11a) 9.32 dBm(802.11n_HT20) 9.39 dBm(802.11n_HT40) 9.53 dBm(802.11ac_VHT80)
		Multiple Antenna	12.48 dBm(802.11a) 12.46 dBm(802.11n_HT20) 12.55 dBm(802.11n_HT40) 12.67 dBm(802.11ac_VHT80)
		Antenna 0	13.04 dBm(802.11a) 13.00 dBm(802.11n_HT20) 12.90 dBm(802.11n_HT40) 12.93 dBm(802.11ac_VHT80)
		Antenna 1	12.11 dBm(802.11a) 12.11 dBm(802.11n_HT20) 11.97 dBm(802.11n_HT40) 11.99 dBm(802.11ac_VHT80)
		Multiple Antenna	15.61 dBm(802.11a) 15.59 dBm(802.11n_HT20) 15.47 dBm(802.11n_HT40) 15.50 dBm(802.11ac_VHT80)
	WLAN 5 725 MHz ~ 5 850 MHz Band		

ANTENNA TYPE	Bluetooth	PCB Antenna	
	WLAN 2.4 GHz	Chip Antenna	
	WLAN 5 GHz	Antenna 0	Chip Antenna
		Antenna 1	PCB Antenna
ANTENNA GAIN	Bluetooth	2.76 dBi	
	WLAN 2.4 GHz	4.18 dBi	
	5 150 MHz ~ 5 250 MHz Band	Antenna 0	2.49 dBi
		Antenna 1	3.44 dBi
		Multiple Antenna	6.00 dBi
	5 725 MHz ~ 5 850 MHz Band	Antenna 0	6.55 dBi
		Antenna 1	6.63 dBi
		Multiple Antenna	9.60 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)		32.786 kHz, 2.17 MHz, 2.2 MHz, 3 MHz, 19.2 MHz, 25 MHz, 26 MHz, 27 MHz, 38.4 MHz, 40 MHz, 55.466 67 MHz	
RATED SUPPLY VOLTAGE		DC 14.0 V	

3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

4. EUT MODIFICATIONS

-. None

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	N/A	N/A	N/A

5.2 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested:

Model	Manufacturer	Description	Connected to
MIB3GP	LG Electronics Inc.	Car Navigation (EUT)	-
GP-4303D	LG Precision Co.,Ltd	DC Power Supply	EUT
Ideapad L340	Lenovo	Notebook PC	EUT

5.3 Mode of operation during the test

-. Channel List (WLAN 2.4 GHz)

Channel	Frequency[MHz]	Channel	Frequency[MHz]	Channel	Frequency[MHz]
1	2 412.00	6	2 437.00	11	2 462.00
2	2 417.00	7	2 442.00		
3	2 422.00	8	2 447.00		
4	2 427.00	9	2 452.00		
5	2 432.00	10	2 457.00		

-. Duty Cycle

Band	TEST Mode	Data Rate	On Time (ms)	Total Time (ms)	Duty Cycle (%)	Duty Cycle Factor (dB)
WLAN 2.4 GHz	802.11 b	1	8.624	8.636	99.87	0.01
		2	4.408	4.419	99.75	0.01
		5.5	1.726	1.737	99.35	0.03
		11	0.958	0.969	98.84	0.05
	802.11 g	6	1.432	1.449	98.81	0.05
		9	0.960	0.977	98.24	0.08
		12	0.728	0.745	97.69	0.10
		18	0.492	0.509	96.62	0.15
		24	0.376	0.393	95.63	0.19
		36	0.256	0.273	93.71	0.28
		48	0.200	0.217	92.09	0.36
		54	0.180	0.197	91.28	0.40
	802.11 n(HT20)	MCS0	1.340	1.357	98.73	0.06
		MCS1	0.688	0.705	97.58	0.11
		MCS2	0.472	0.489	96.49	0.16
		MCS3	0.364	0.381	95.49	0.20
		MCS4	0.256	0.273	93.71	0.28
		MCS5	0.200	0.217	92.15	0.35
		MCS6	0.184	0.201	91.45	0.39
		MCS7	0.168	0.185	90.72	0.42

Note – Duty Cycle : (Tx On Time / (Tx On Time + Tx Off Time)) * 100

Correction Factor : 10 * Log(1 / (Duty Cycle / 100))

5.4 Configuration of Test System

Line Conducted Test: It is not need to test this requirement, because the EUT shall be operated by only using DC Power.

Radiated Emission Test: Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meter Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The antenna of the EUT is a PCB Antenna and Chip Antenna on the main board in the EUT, so no consideration of replacement by the user.

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
It is not need to test this requirement, because the power of the EUT is supplied by DC Power.	

6.2 General Radiated Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X

7. MINIMUM 6 dB BANDWIDTH


7.1 Operating environment

Temperature : 24 °C

Relative humidity : 52 % R.H.

7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz, and peak detection was used. The 6 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 6 dB.



7.3 Test Date

November 28, 2022 ~ December 08, 2022

7.4 Test data for 802.11b WLAN Mode

-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
Low	2 412.00	10.09	0.50	9.59
Middle	2 437.00	10.09	0.50	9.59
High	2 462.00	10.09	0.50	9.59

Remark. Margin = Measured Value – Limit

7.5 Test data for 802.11g WLAN Mode

-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
Low	2 412.00	16.28	0.50	15.78
Middle	2 437.00	16.33	0.50	15.83
High	2 462.00	16.28	0.50	15.78

Remark. Margin = Measured Value – Limit

7.6 Test data for 802.11n_HT20 WLAN Mode

-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
Low	2 412.00	17.53	0.50	17.03
Middle	2 437.00	17.53	0.50	17.03
High	2 462.00	17.13	0.50	16.63

Remark. Margin = Measured Value – Limit

8. MAXIMUM CONDUCTED(AVERAGE) OUTPUT POWER

8.1 Operating environment


Temperature : 24 °C

Relative humidity : 52 % R.H.

8.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer.

The resolution bandwidth is set to 1 MHz, the video bandwidth is set to 3 times the resolution bandwidth.



8.3 Test Date

November 28, 2022 ~ December 08, 2022

8.4 Test data for 802.11b WLAN Mode

-. Test Result : Pass

-. Duty Cycle : 99.87 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor(dB)	Total Value(dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412.00	7.91	0.01	7.92	30.00	22.08
MIDDLE	2 437.00	8.50	0.01	8.51	30.00	21.49
HIGH(11)	2 462.00	8.33	0.01	8.34	30.00	21.66

Remark. Margin = Limit – Result (=Measured Value + Duty Factor)

8.5 Test data for 802.11g WLAN Mode

-. Test Result : Pass

-. Duty Cycle : 98.81 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor(dB)	Total Value(dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412.00	8.14	0.05	8.19	30.00	21.80
MIDDLE	2 437.00	8.58	0.05	8.63	30.00	21.36
HIGH(11)	2 462.00	8.53	0.05	8.58	30.00	21.41

Remark. Margin = Limit – Result (=Measured Value + Duty Factor)

8.6 Test data for 802.11n_HT20 WLAN Mode

-. Test Result : Pass

-. Duty Cycle : 98.73 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor(dB)	Total Value(dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412.00	8.31	0.06	8.37	30.00	21.63
MIDDLE	2 437.00	8.77	0.06	8.83	30.00	21.17
HIGH(11)	2 462.00	8.72	0.06	8.78	30.00	21.22

Remark. Margin = Limit – Result (=Measured Value + Duty Factor)

9. 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND


9.1 Operating environment

Temperature : 24 °C

Relative humidity : 52 % R.H.

9.2 Test set-up for conducted measurement

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz and video bandwidth is set to 300 kHz, and peak detection was used.



9.3 Test set-up for radiated measurement

The radiated emissions measurements were performed on the 3 m semi anechoic chamber. The EUT was placed on turntable approximately 1.5 m above the ground plane.

The frequency spectrum from 30 MHz to 26.5 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.

9.4 Test Date

November 28, 2022 ~ December 08, 2022

9.5 Test data for conducted emission

Please refer to the Annex

9.6 Test data for radiated emission

9.6.1 Radiated Emission which fall in the Restricted Band

9.6.1.1 Test data for 802.11b WLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : 99.87 %
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	ATT (dB)	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel											
2 389.120	52.56	Peak	H	27.38	7.99	44.94	6.01	-	49.00	74.00	25.00
2 389.740	41.01	Average	H	27.38	7.99	44.94	6.01	0.01	37.46	54.00	16.54
2 318.710	52.80	Peak	V	27.68	7.69	44.97	6.02	-	49.22	74.00	24.78
2 390.040	40.49	Average	V	27.38	7.99	44.94	6.01	0.01	36.94	54.00	17.06
Test Data for High Channel											
2 494.100	52.66	Peak	H	27.41	8.07	44.90	5.99	-	49.23	74.00	24.77
2 483.920	41.64	Average	H	27.43	8.07	44.91	5.99	0.01	38.23	54.00	15.77
2 497.590	52.51	Peak	V	27.4	8.07	44.90	5.99	-	49.07	74.00	24.93
2 485.100	40.88	Average	V	27.43	8.07	44.91	5.99	0.01	37.47	54.00	16.53

Remark: "H": Horizontal, "V": Vertical

Margin (dB) = Limits (dBμV/m) - Total Level (dBμV/m)

Total Level = Reading + Antenna Factor + Cable Loss + ATT + Duty Factor - AMP Gain

9.6.1.2 Test data for 802.11g WLAN Mode

- . Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- . Video bandwidth : 3 MHz for Peak and Average Mode
- . Measurement distance : 3 m
- . Duty Cycle : 98.81 %
- . Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	ATT (dB)	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel											
2 389.630	62.49	Peak	H	27.38	7.99	44.94	6.01	-	58.93	74.00	15.07
2 390.040	43.36	Average	H	27.38	7.99	44.94	6.01	0.05	39.85	54.00	14.15
2 389.230	61.30	Peak	V	27.38	7.99	44.94	6.01	-	57.74	74.00	16.26
2 389.840	42.71	Average	V	27.38	7.99	44.94	6.01	0.05	39.20	54.00	14.80
Test Data for High Channel											
2 483.580	64.65	Peak	H	27.43	8.07	44.91	5.99	-	61.23	74.00	12.77
2 483.700	45.99	Average	H	27.43	8.07	44.91	5.99	0.05	42.62	54.00	11.38
2 484.230	62.87	Peak	V	27.43	8.07	44.91	5.99	-	59.45	74.00	14.55
2 483.700	44.99	Average	V	27.43	8.07	44.91	5.99	0.05	41.62	54.00	12.38

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{ATT} + \text{Duty Factor} - \text{AMP Gain}$$

9.6.1.3 Test data for 802.11n_HT20 WLAN Mode

- . Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- . Video bandwidth : 3 MHz for Peak and Average Mode
- . Measurement distance : 3 m
- . Duty Cycle : 98.73 %
- . Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	ATT (dB)	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel											
2 389.630	62.25	Peak	H	27.38	7.99	44.94	6.01	-	58.69	74.00	15.31
2 389.940	43.53	Average	H	27.38	7.99	44.94	6.01	0.06	40.03	54.00	13.97
2 390.040	61.64	Peak	V	27.38	7.99	44.94	6.01	-	58.08	74.00	15.92
2 389.940	42.07	Average	V	27.38	7.99	44.94	6.01	0.06	38.57	54.00	15.43
Test Data for High Channel											
2 483.810	66.93	Peak	H	27.43	8.07	44.91	5.99	-	63.51	74.00	10.49
2 483.510	49.97	Average	H	27.43	8.07	44.91	5.99	0.06	46.61	54.00	7.39
2 483.771	65.26	Peak	V	27.43	8.07	44.91	5.99	-	61.84	74.00	12.16
2 483.505	46.51	Average	V	27.43	8.07	44.91	5.99	0.06	43.15	54.00	10.85

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{ATT} + \text{Duty Factor} - \text{AMP Gain}$$

9.6.2 Spurious & Harmonic Radiated Emission

9.6.2.1 Test data for 802.11b WLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Duty Cycle : 99.87 %
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel										
4 810.410	49.85	Peak	H	31.28	11.37	44.66	-	47.84	74.00	26.16
4 811.310	38.02	Average	H	31.28	11.37	44.66	0.01	36.02	54.00	17.98
4 836.390	49.08	Peak	V	31.23	11.37	44.67	-	47.01	74.00	26.99
4 845.680	37.22	Average	V	31.21	11.37	44.67	0.01	35.14	54.00	18.86
Test Data for Middle Channel										
4 890.030	49.85	Peak	H	31.28	11.37	44.68	-	47.82	74.00	26.18
4 896.530	38.10	Average	H	31.29	11.37	44.68	0.01	36.09	54.00	17.91
4 860.010	49.12	Peak	V	31.22	11.37	44.67	-	47.04	74.00	26.96
4 861.610	37.30	Average	V	31.22	11.37	44.67	0.01	35.23	54.00	18.77
Test Data for High Channel										
4 912.110	50.09	Peak	H	31.32	11.37	44.68	-	48.10	74.00	25.90
4 946.380	37.53	Average	H	31.39	11.37	44.69	0.01	35.61	54.00	18.39
4 937.440	49.02	Peak	V	31.37	11.37	44.69	-	47.07	74.00	26.93
4 909.860	37.12	Average	V	31.32	11.37	44.68	0.01	35.14	54.00	18.86

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{Duty Factor} - \text{AMP Factor}$$

9.6.2.2 Test data for 802.11g WLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Duty Cycle : 98.81 %
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel										
4 840.380	50.86	Peak	H	31.22	11.37	44.67	-	48.78	74.00	25.22
4 806.920	37.41	Average	H	31.29	11.37	44.66	0.05	35.46	54.00	18.54
4 807.220	49.44	Peak	V	31.29	11.37	44.66	-	47.44	74.00	26.56
4 846.230	37.35	Average	V	31.21	11.37	44.67	0.05	35.31	54.00	18.69
Test Data for Middle Channel										
4 888.980	50.05	Peak	H	31.28	11.37	44.68	-	48.02	74.00	25.98
4 853.320	38.00	Average	H	31.21	11.37	44.67	0.05	35.96	54.00	18.04
4 886.840	49.46	Peak	V	31.27	11.37	44.68	-	47.42	74.00	26.58
4 850.570	37.33	Average	V	31.20	11.37	44.67	0.05	35.28	54.00	18.72
Test Data for High Channel										
4 944.630	50.41	Peak	H	31.39	11.37	44.69	-	48.48	74.00	25.52
4 899.380	38.65	Average	H	31.30	11.37	44.68	0.05	36.69	54.00	17.31
4 909.420	49.09	Peak	V	31.32	11.37	44.68	-	47.10	74.00	26.90
4 948.580	37.34	Average	V	31.40	11.37	44.69	0.05	35.47	54.00	18.53

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{Duty Factor} - \text{AMP Factor}$$

9.6.2.3 Test data for 802.11n_HT20 WLAN Mode

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode for the emissions fall in restricted band,
1 MHz and RMS Detector for Average Mode for the emissions fall in restricted band
100 kHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Duty Cycle : 98.73 %
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	Duty Factor (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel										
4 801.420	50.68	Peak	H	31.30	11.37	44.66	-	48.69	74.00	25.31
4 799.720	38.99	Average	H	31.30	11.37	44.66	0.06	37.06	54.00	16.94
4 814.360	49.20	Peak	V	31.27	11.21	44.66	-	47.02	74.00	26.98
4 846.677	37.38	Average	V	31.21	11.24	44.67	0.06	35.22	54.00	18.78
Test Data for Middle Channel										
4 884.690	49.72	Peak	H	31.27	11.37	44.68	-	47.68	74.00	26.32
4 850.020	37.98	Average	H	31.20	11.37	44.67	0.06	35.94	54.00	18.06
4 890.783	49.13	Peak	V	31.28	11.27	44.68	-	47.00	74.00	27.00
4 856.967	37.41	Average	V	31.21	11.25	44.67	0.06	35.26	54.00	18.74
Test Data for High Channel										
4 936.088	49.63	Peak	H	31.37	11.31	44.69	-	47.62	74.00	26.38
4 947.826	37.44	Average	H	31.40	11.33	44.63	0.06	35.60	54.00	18.40
4 908.565	49.31	Peak	V	31.32	11.29	44.68	-	47.24	74.00	26.76
4 946.328	37.47	Average	V	31.39	11.33	44.69	0.06	35.56	54.00	18.44

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{Duty Factor} - \text{AMP Factor}$$

10. POWER SPECTRAL DENSITY

10.1 Operating environment

Temperature : 24 °C

Relative humidity : 52 % R.H.

10.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer.

The resolution bandwidth is set to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$, the video bandwidth is set to 3 times the resolution bandwidth.



10.3 Test Date

November 28, 2022 ~ December 08, 2022

10.4 Test data for 802.11b WLAN Mode

-. Test Result : Pass

-. Duty Cycle : 99.87 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor(dB)	Total Value(dBm)	LIMIT (dBm / 3 kHz)	MARGIN (dB)
LOW	2 412.00	-25.41	0.01	-25.40	8.00	33.40
MIDDLE	2 437.00	-24.71	0.01	-24.70	8.00	32.70
HIGH(11)	2 462.00	-24.88	0.01	-24.87	8.00	32.87

Remark. Margin = Limit – Result (=Measured Value + Duty Factor)

10.5 Test data for 802.11g WLAN Mode

-. Test Result : Pass

-. Duty Cycle : 98.81 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor(dB)	Total Value(dBm)	LIMIT (dBm / 3 kHz)	MARGIN (dB)
LOW	2 412.00	-26.17	0.05	-26.12	8.00	34.12
MIDDLE	2 437.00	-25.76	0.05	-25.71	8.00	33.71
HIGH(11)	2 462.00	-25.93	0.05	-25.88	8.00	33.88

Remark. Margin = Limit – Result (=Measured Value + Duty Factor)

10.6 Test data for 802.11n_HT20 WLAN Mode

-. Test Result : Pass

-. Duty Cycle : 98.73 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	Duty Factor(dB)	Total Value(dBm)	LIMIT (dBm / 3 kHz)	MARGIN (dB)
LOW	2 412.00	-26.31	0.06	-26.25	8.00	34.25
MIDDLE	2 437.00	-25.90	0.06	-25.84	8.00	33.84
HIGH(11)	2 462.00	-26.00	0.06	-25.94	8.00	33.94

Remark. Margin = Limit – Result (=Measured Value + Duty Factor)

11. RADIATED EMISSION TEST

11.1 Operating environment

Temperature : 24 °C

Relative humidity : 52 % R.H.


11.2 Test set-up

The radiated emissions measurements were on the 3 m semi anechoic chamber. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.


The frequency spectrum from 30 MHz to 26.5 GHz was scanned and emission levels maximized at each frequency recorded. The system was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

- Test Configuration


1. Below 30 MHz



2. 30 MHz - 1 GHz



3. Above 1 GHz



11.3 Test Date

November 28, 2022 ~ December 08, 2022

11.4 Test data for 30 MHz ~ 1 000 MHz

11.4.1 Test data for WLAN 2.4 GHz

Humidity Level : 52 % R.H.


Temperature: 24 °C

Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247

Result : PASSED

EUT : Car Navigation

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	QP	FACTOR	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	71.710	37.4	13.1	1.1	32.0	19.6	40.0	20.4	300	33
2	107.600	32.9	16.6	1.3	32.0	18.8	43.5	24.7	400	0
3	288.020	31.6	18.8	2.2	32.0	20.6	46.0	25.4	100	274
----- Vertical -----										
4	208.480	31.2	15.8	1.8	32.0	16.8	43.5	26.7	100	0
5	687.655	30.9	25.2	3.4	32.3	27.2	46.0	18.8	100	0
6	859.340	27.9	27.3	3.8	32.2	26.8	46.0	19.2	200	260

11.4.2 Test data for Intermodulation Mode(Bluetooth + WLAN 2.4 GHz)

Humidity Level : 52 % R.H.


Temperature: 24 °C

Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247

Result : PASSED

EUT : Car Navigation

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	QP	FACTOR	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	107.600	35.0	16.6	1.3	32.0	20.9	43.5	22.6	300	359
2	143.490	30.9	18.9	1.5	32.0	19.3	43.5	24.2	300	359
3	288.020	33.1	18.8	2.2	32.0	22.1	46.0	23.9	100	256
----- Vertical -----										
4	35.820	45.2	18.8	0.8	32.2	32.6	40.0	7.4	100	0
5	64.920	47.3	12.6	1.0	32.0	28.9	40.0	11.1	100	0
6	831.211	34.5	27.2	3.8	32.3	33.2	46.0	12.8	100	0

11.4.3 Test data for Intermodulation Mode(WLAN 2.4 GHz + WLAN 5 GHz)

Humidity Level : 52 % R.H.


Temperature: 24 °C

Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247

Result : PASSED

EUT : Car Navigation

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	QP	FACTOR	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	71.710	38.7	13.1	1.1	32.0	20.9	40.0	19.1	300	0
2	107.600	36.4	16.6	1.3	32.0	22.3	43.5	21.2	400	252
3	143.490	31.1	18.9	1.5	32.0	19.5	43.5	24.0	300	122
4	687.655	31.8	25.2	3.4	32.3	28.1	46.0	17.9	300	190
----- Vertical -----										
5	562.529	28.5	23.7	3.1	32.2	23.1	46.0	22.9	100	82
6	859.340	28.4	27.3	3.8	32.2	27.3	46.0	18.7	100	269

11.5 Test data for Below 30 MHz

- . Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)
- . Frequency range : 9 kHz ~ 30 MHz
- . Measurement distance : 3 m
- . Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dBμV/m)	Limits (dBμV/m)	Margin (dB)
Emission from the EUT more than 20 dB below the limit in each frequency range.									

11.6 Test data for above 1 GHz

- . Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode
1 MHz and RMS Detector for Average Mode
- . Video bandwidth : 3 MHz for Peak and Average Mode
- . Frequency range : 1 GHz ~ 26.5 GHz
- . Measurement distance : 3 m
- . Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dBμV/m)	Limits (dBμV/m)	Margin (dB)
Emission from the EUT more than 20 dB below the limit in each frequency range.									

12. LIST OF TEST EQUIPMENT

Model Number	Manufacturer	Description	Serial Number	Last Cal.(Interval)
FSV30	Rohde & Schwarz	Signal Analyzer	101372	Jul. 14, 2022 (1Y)
FSVA40	Rohde & Schwarz	Signal Analyzer	101586	Apr. 21, 2022 (1Y)
ESU	Rohde & Schwarz	EMI Test Receiver	100261	Mar. 07, 2022 (1Y)
310N	Sonoma Instrument	Pre-Amplifier	392756	Oct. 13, 2022 (1Y)
SCU18	Rohde & Schwarz	Signal Conditioning unit	102266	Jul. 12, 2022 (1Y)
SCU40A	Rohde & Schwarz	Signal Conditioning unit	100436	Jan. 18, 2022 (1Y)
GP-4303D	LG Precision Co.,Ltd	DC Power Supply	5071069	Jan. 03, 2022 (1Y)
HPF 3GHz	Rohde & Schwarz	High Pass Filter	N/A	Jan. 18, 2022 (1Y)
FMZB 1513	Schwarzbeck	Loop Antenna	1513-235	Mar. 24, 2022 (2Y)
HLP-2008	TDK	Hybrid Antenna	131316	Mar. 07, 2022 (2Y)
BBHA9120D	Schwarzbeck	Horn Antenna	9120D-1366	Jul. 05, 2022 (1Y)
BBHA9170	Schwarzbeck	Horn Antenna	BBHA9170179	Jan. 21, 2022 (1Y)
DT2000-2t	Innco System	Turn Table	N/A	N/A
MA-4640-XPET	Innco System	Antenna Master	MA4640/652/43100318/P	N/A
CO3000	Innco System	Controller	1026/40960617/P	N/A