PCTEST Engineering Laboratory, Inc.

6660-B Dobbin Road · Columbia, MD 21045 · U.S.A.
TEL (410) 290-6652 · FAX (410) 290-6654
http://www.pctestlab.com

CERTIFICATE OF COMPLIANCE
FCC Part 24 & 22 Certification

LG ELECTRONICS, INC.
Communication Terminal Research Lab
459-9, Kasan-dong, Keumchun-Ku
Seoul, KOREA 153-023

Dates of Tests: August 18-22, 2003
Test Report S/N: 22/24.230818400.BEJ
Test Site: PCTEST Lab, Columbia MD

FCC ID	**BEJ4600**
APPLICANT	**LG ELECTRONICS, INC.**

Classification:	**Licensed Portable Transmitter Held to Ear (PCE)**
FCC Rule Part(s):	**§24(E), §22(H), §22.901(d); §2**
EUT Type:	**Tri-Mode Dual-Band Analog/PCS Phone (AMPS/CDMA)**
Model:	***LG-4600***
Tx Frequency Range:	**824.04MHz – 848.97MHz (AMPS) / 824.70 – 848.31MHz (CDMA)** **1851.25MHz – 1908.75MHz (PCS CDMA)**
Rx Frequency Range:	**869.04MHz – 893.97MHz (AMPS) / 869.70 – 893.31MHz (CDMA)** **1931.25MHz – 1988.75MHz (PCS CDMA)**
Max. RF Output Power:	**0.405 W ERP AMPS (26.073 dBm) / 0.226 W ERP CDMA (23.533 dBm)** **0.289 W EIRP PCS CDMA (24.601 dBm)**
Max. SAR Measurement:	**0.937 W/kg AMPS Head SAR; 0.324 W/kg AMPS Body SAR;** **0.575 W/kg CDMA Head SAR; 0.189 W/kg CDMA Body SAR;** **0.855 W/kg PCS CDMA Head SAR; 0.341 W/kg PCS CDMA Body SAR**
Emission Designator(s):	**40K0F8W / 40K0F1D (AMPS), 1M25F9W (CDMA)**
Test Device Serial No.	**Identical Prototype [S/N: #3]**

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant conditions: Power output listed is ERP for Part 22 and EIRP for Part 24. SAR compliance for body-worn operating configuration is limited to the specific belt-clip/holster tested for this filing. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Alfred Cirwithian
Vice President Engineering

2 3 0 8 1 8 4 0 0 . B E J

© 2003 PCTEST ENGINEERING LABORATORY, INC.

TABLE OF CONTENTS

ATTACHMENT A: COVER LETTER(S)

ATTACHMENT B: ATTESTATION STATEMENT(S)

ATTACHMENT C: TEST REPORT

1.1 SCOPE	3
2.1 INTRODUCTION	4
3.1 INSERTS	5
4.1 DESCRIPTION OF TESTS	6-10
5.1 EFFECTIVE RADIATED POWER OUTPUT	11-12
6.1 EQUIVALENT ISOTROPIC RADIATED POWER	13
7.1 RADIATED MEASUREMENTS	14-22
8.1 FREQUENCY STABILITY	23-28
9.1 PLOTS OF EMISSIONS	29
10.1 LIST OF TEST EQUIPMENT	30
11.1 SAMPLE CALCULATIONS	31
12.1 CONCLUSION	32

ATTACHMENT D: TEST PLOTS

ATTACHMENT E: FCC ID LABEL / LOCATION

ATTACHMENT F: TEST SETUP PHOTOGRAPHS

ATTACHMENT G: EXTERNAL PHOTOGRAPHS

ATTACHMENT H: INTERNAL PHOTOGRAPHS

ATTACHMENT I: BLOCK DIAGRAM(S)

ATTACHMENT J: SCHEMATIC DIAGRAM(S)

ATTACHMENT K: OPERATIONAL / CIRCUIT DESCRIPTION

ATTACHMENT L: PARTS LIST/TUNE UP PROCEDURE

ATTACHMENT M: USER'S MANUAL

ATTACHMENT N: SAR MEASUREMENT REPORT

ATTACHMENT O: SAR TEST DATA

ATTACHMENT P: SAR TEST SETUP PHOTOGRAPHS

ATTACHMENT Q: DIPOLE VALIDATION

ATTACHMENT R: PROBE CALIBRATION

© 2003 PCTEST ENGINEERING LABORATORY, INC.

MEASUREMENT REPORT

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

§2.1033 General Information

Applicant Name: **LG ELECTRONICS, INC.**
Address: **Communication Terminal Research Lab**
459-9, Kasan-dong, Keumchun-Ku
Seoul, KOREA 153-023

- FCC ID: **BEJ4600**
- Quantity: Quantity production is planned
- Emission Designators: 40K0F8W / 40K0F1D (AMPS), 1M25F9W (CDMA)
- Tx Freq. Range: 824.04 – 848.97 MHz (AMPS)
  824.70 – 848.31 MHz (CDMA)
  1851.25 – 1908.75 MHz (PCS CDMA)
- Rx Freq. Range: 869.04 – 893.97 MHz (AMPS)
  869.70 – 893.31 MHz (CDMA)
  1931.25 – 1988.75 MHz (PCS CDMA)
- Max. Power Rating: 0.405 W ERP AMPS (26.073 dBm) / 0.226 W ERP CDMA (23.533 dBm)
  0.289 W EIRP PCS CDMA (24.601 dBm)
- FCC Classification(s): Licensed Portable Tx Held to Ear (PCE)
- Equipment (EUT) Type: Tri-Mode Dual-Band Analog/PCS Phone
- Modulation(s): AMPS / CDMA
- Frequency Tolerance: ± 0.00025% (2.5 ppm)
- FCC Rule Part(s): § 24(E), §22(H), §22.901(d)
- Dates of Tests: August 18-22, 2003
- Place of Tests: PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N: 22/24.230818400.BEJ

© 2003 PCTEST ENGINEERING LABORATORY, INC.

2.1 INTRODUCTION



Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.

These measurement tests were conducted at ***PCTEST Engineering Laboratory, Inc.*** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

Measurement Procedure

The radiated and spurious measurements were made outdoors at a 3-meter test range (see Figure2). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.



Figure 2. Diagram of 3-meter outdoor test range

© 2003 PCTEST ENGINEERING LABORATORY, INC.

3.1 INSERTS

Function of Active Devices (Confidential)

The Function of active devices are shown in Attachment K.

Block & Schematic Diagrams (Confidential)

The block diagrams are shown in Attachment I, and the schematic diagrams are shown in Attachment J.

Operating Instructions

The instruction manual is shown in Attachment M.

Parts List & Tune-Up Procedure (Confidential)

The parts list & tune-up procedure is shown in Attachment L.

Description of Freq. Stabilization Circuit (Confidential)

The description of frequency stabilization circuit is shown in Attachment K.

Description for Suppression of Spurious Radiation, for Limiting Modulation, and Harmonic Suppresion Circuits (Confidential)

The description of suppression stabilization circuits is shown in Attachment K.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

4.1 DESCRIPTION OF TESTS

4.2 Transmitter Audio Frequency Response

The frequency response of the audio modulating circuit over the frequency range 100 – 5000 Hz is measured. The audio signal generator is connected to the audio input circuit/microphone of the EUT. The audio signal input is adjusted to obtain 50% modulation at 1kHz and this point is taken as the 0dB reference. With the input held constant and below the limit at all frequencies, the audio signal generator is varied from 100 to 50 kHz.

4.3 Audio Low Pass Filter Frequency Response

The response in dB relative to 1kHz is measured using the HP8901 a Modulation Analyzer. For the frequency response of the audio low-pass filter, the audio input is connected at the input to the modulation limiter and the modulated stage. The audio output is connected at the output of the modulated stage. The corresponding plots are shown herein.

4.4 Modulation Limiting

The audio signal generator is connected to the audio input circuit/microphone of the EUT. The modulation response is measured for each of the three modulating frequencies (300Hz, 1000 Hz, and 3000Hz), and the input voltage is varied from 30% modulation (±3.6kHz deviation) to at least 20dB higher than the saturation point. Measurements of modulation and the plots are attached herein. Measurements were performed for ST, SAT, and wide-band data modulations. The corresponding results are shown herein.

Note: ST, SAT, & Wide-Band data were internally generated by the EUT.



Fig. 3. Transmitter Audio Frequency & Tone Modulation Test Setup.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

4.5 Occupied Bandwidth Emission Limits

(a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB.

(b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

(c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.

(d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

4.6 Cellular - Base Frequency Blocks



BLOCK 1: 869 – 880 MHz (A* Low + A)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 4: 891.5 – 894 MHz (B*)

4.7 Cellular - Mobile Frequency Blocks



BLOCK 1: 824 – 835 MHz (A* Low + A)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 4: 846.5 – 849 MHz (B*)

© 2003 PCTEST ENGINEERING LABORATORY, INC.

4.1 DESCRIPTION OF TESTS (CONTINUED)

4.8 PCS - Base Frequency Blocks



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 5: 1970 – 1975 MHz (F)

BLOCK 6: 1975 – 1990 MHz (C)

4.9 PCS - Mobile Frequency Blocks



BLOCK 1: 1850 – 1865 MHz (A)

BLOCK 2: 1865 – 1870 MHz (D)

BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 4: 1885 – 1890 MHz (E)

BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 6: 1895 – 1910 MHz (C)

© 2003 PCTEST ENGINEERING LABORATORY, INC.

4.10 Occupied Bandwidth

The audio signal generator is adjusted to 1kHz. The output level is set to ±6kHz deviation. With the level constant, the frequency is set to 2500Hz. Then the audio signal level is increased by 16dB. The occupied bandwidth data is obtained for the SAT (Supervisory Audio Tone), ST (Signaling Tone), WBD (Wideband data), and DTMF (Dual Tone Multi Frequencies). The results are shown on the attached graphs.

Specified Limits:

a. On any frequency removed from the assigned carrier frequency by more than 20 kHz, up to and including 45kHz, the sideband is at least 26dB below the carrier.

b. On any frequency removed from the assigned carrier frequency by more than 45 kHz, up to and including 90kHz, the sideband is at least 45dB below the carrier.

c. On any frequency removed from the assigned carrier frequency by more than 90 kHz, up to the first multiple of the carrier frequency, the sideband is at least 60dB below the carrier or 40 + $\log_{10}$ (mean power output in Watts) dB, whichever is the smaller attenuation.

4.11 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to 10 GHz. The transmitter is modulated with a 2500Hz tone at a level of 16dB greater than that required to provided 50% modulation.

At the input terminals of the spectrum analyzer, an isolator (RF circulator with on port terminated with 50 ohms) and an 870 MHz to 890 MHz bandpass filter is connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The rejection of the bandpass filter to signals in the 825 – 845 MHz range is adequate to limit the transmit energy from the test transceiver which appears to a level which will allow the analyzer to measure signals less than –90dBm. Calibration of the test receiver is performed in the 870 – 890 MHz range to insure accuracy to allow variation in the bandpass filter insertion loss to be calibrated.

4.12 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and an high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 1.6 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

4.13 Radiation Spurious and Harmonic Emissions

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

5.0 Frequency Stability/Temperature Variation.

The frequency stability of the transmitter is measured by:

a.) **Temperature:** The temperature is varied from -30°C to +60°C using an environmental chamber.

b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025 (±2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (22°C to 25°C to provide a reference).
2. The equipment is subjected to an overnight "soak" at -30°C without any power applied.
3. After the overnight "soak" at -30°C (usually 14-16 hours), the equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

NOTE: The EUT is tested down to the battery endpoint.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

5.1 Test Data

5.2 Effective Radiated Power Output

A. POWER: **Low (Analog Mode)**

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)
824.04	-35.200	H	0.004	6.073
836.49	-35.380	H	0.004	6.049
848.97	-35.580	H	0.004	6.005

B. POWER: **High (Analog Mode)**

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)	BATTERY
824.04	-15.200	H	0.405	26.073	Standard
836.49	-15.380	H	0.403	26.049	Standard
848.97	-15.580	H	0.399	26.005	Standard
824.04	-15.250	H	0.400	26.023	Extended

Note: Standard & Extended batteries are options for this phone

NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

5.1 Test Data

5.3 Effective Radiated Power Output

A. POWER: **High (CDMA Mode)**

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)	BATTERY
824.70	-17.820	H	0.221	23.453	Standard
836.52	-17.900	H	0.226	23.533	Standard
848.31	-18.070	H	0.225	23.513	Standard
836.52	-18.000	H	0.220	23.433	Extended

Note: Standard & Extended batteries are options for this phone

NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

6.1 Test Data

6.2 Equivalent Isotropic Radiated Power (E.I.R.P.)

Radiated measurements at 3 meters

Supply Voltage: 3.7 VDC

Modulation: PCS

FREQ. (MHz)	REF. LEVEL (dBm)	POL (H/V)	Azimuth (o angle)	EIRP (dBm)	EIRP (W)	Battery
1851.25	-18.500	H	240	24.581	0.288	Standard
1880.00	-18.650	H	240	24.601	0.289	Standard
1908.75	-18.850	H	240	24.571	0.287	Standard
1880.00	-18.720	H	240	24.531	0.285	Extended

Note: Standard & Extended batteries are options for this phone

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data

7.2 AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.04 MHz
CHANNEL: 0991 (Low)
MEASURED OUTPUT POWER: 26.073 dBm = 0.405 W
MODULATION SIGNAL: FM (Internal)
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 39.07 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1648.08	-25.58	6.10	-19.48	V	45.6
2472.12	-43.78	6.70	-37.08	V	63.2
3296.16	-49.38	6.80	-42.58	V	68.7
4120.20	-55.48	6.50	-48.98	V	75.1
4944.24	-60.58	7.00	-53.58	V	79.7

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data (Continued)

7.3 AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.49 MHz
CHANNEL: 383
MEASURED OUTPUT POWER: 26.073 dBm = 0.405 W
MODULATION SIGNAL: FM (Internal)
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 39.07 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1672.98	-25.78	6.10	-19.68	V	45.8
2509.47	-42.18	6.70	-35.48	V	61.6
3345.96	-45.28	6.80	-38.48	V	64.6
4182.45	-52.48	6.50	-45.98	V	72.1
5018.94	-61.68	7.00	-54.68	V	80.8

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data (Continued)

7.4 AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.97 MHz
CHANNEL: 0799 (High)
MEASURED OUTPUT POWER: 26.073 dBm = 0.405 W
MODULATION SIGNAL: FM (Internal)
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 39.07 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1697.94	-40.18	6.10	-34.08	V	60.2
2546.91	-42.08	6.70	-35.38	V	61.5
3395.88	-52.58	6.80	-45.78	V	71.9
4244.85	-63.48	6.50	-56.98	V	83.1
5093.82	-69.68	7.00	-62.68	V	88.8

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data (Continued)

7.5 CELLULAR CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.70 MHz
CHANNEL: 1013 (Low)
MEASURED OUTPUT POWER: 23.533 dBm = 0.226 W
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 36.54 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1649.40	-32.78	6.10	-26.68	V	50.2
2474.10	-57.08	6.70	-50.38	V	73.9
3298.80	-61.58	6.80	-54.78	V	78.3
4123.50	-63.38	6.50	-56.88	V	80.4

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data (Continued)

7.6 CELLULAR CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.52 MHz
CHANNEL: 384
MEASURED OUTPUT POWER: 23.533 dBm = 0.226 W
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 36.54 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1673.04	-27.58	6.10	-21.48	V	45.0
2509.56	-51.98	6.70	-45.28	V	68.8
3346.08	-60.18	6.80	-53.38	V	76.9
4182.60	-72.78	6.50	-66.28	V	89.8

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data (Continued)

7.7 CELLULAR CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.31 MHz
CHANNEL: 0777 (High)
MEASURED OUTPUT POWER: 23.533 dBm = 0.226 W
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 36.54 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1696.62	-38.58	6.10	-32.48	V	56.0
2544.93	-50.88	6.70	-44.18	V	67.7
3393.24	-56.28	6.80	-49.48	V	73.0
4241.55	-58.98	6.50	-52.48	V	76.0
5089.86	-61.68	7.00	-54.68	V	78.2

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data (Continued)

7.8 PCS CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1851.25 MHz
CHANNEL: 0025 (Low)
MEASURED OUTPUT POWER: 24.601 dBm = 0.289 W
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 37.61 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3702.50	-26.83	8.70	-18.13	V	42.7
5553.75	-50.53	9.70	-40.83	V	65.4
7405.00	-51.33	9.90	-41.43	V	66.0

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data (Continued)

7.9 PCS CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz
CHANNEL: 0600 (Mid)
MEASURED OUTPUT POWER: 24.601 dBm = 0.289 W
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 37.61 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-31.13	8.70	-22.43	V	47.0
5640.00	-57.33	9.70	-47.63	V	72.2
7520.00	-66.13	9.90	-56.23	V	80.8

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data (Continued)

7.10 PCS CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1908.75 MHz
CHANNEL: 1175 (High)
MEASURED OUTPUT POWER: 24.601 dBm = 0.289 W
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 37.61 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3817.50	-32.93	8.70	-24.23	V	48.8
5726.25	-53.63	9.70	-43.93	V	68.5
7635.00	-51.83	9.90	-41.93	V	66.5
9543.75	-63.93	11.40	-52.53	V	77.1

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

8.1 Test Data

8.2 FREQUENCY STABILITY (AMPS)

OPERATING FREQUENCY: 836,490,002 Hz

CHANNEL: 383

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (ºC)	FREQ. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	836,490,002	0.000000
100 %		- 30	836,489,751	0.000030
100 %		- 20	836,489,701	0.000036
100 %		- 10	836,489,768	0.000028
100 %		0	836,489,692	0.000037
100 %		+ 10	836,489,659	0.000041
100 %		+ 20	836,490,002	0.000000
100 %		+ 25	836,489,843	0.000019
100 %		+ 30	836,489,776	0.000027
100 %		+ 40	836,489,709	0.000035
100 %		+ 50	836,489,768	0.000028
100 %		+ 60	836,489,600	0.000048
85 %	3.15	+ 20	836,490,002	0.000000
115 %	4.26	+ 20	836,490,002	0.000000
BATT. ENDPOINT	2.95	+ 20	836,490,002	0.000000

© 2003 PCTEST ENGINEERING LABORATORY, INC.

8.1 Test Data (Continued)

8.3 FREQUENCY STABILITY (AMPS)



© 2003 PCTEST ENGINEERING LABORATORY, INC.

8.1 Test Data (Continued)

8.4 FREQUENCY STABILITY (CDMA 800 MHz)

OPERATING FREQUENCY: 836,520,003 Hz

CHANNEL: 384

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (ºC)	FREQ. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	836,520,003	0.000000
100 %		- 30	836,519,852	0.000018
100 %		- 20	836,519,786	0.000026
100 %		- 10	836,519,760	0.000029
100 %		0	836,519,777	0.000027
100 %		+ 10	836,519,735	0.000032
100 %		+ 20	836,520,003	0.000000
100 %		+ 25	836,519,852	0.000018
100 %		+ 30	836,519,802	0.000024
100 %		+ 40	836,519,786	0.000026
100 %		+ 50	836,519,702	0.000036
100 %		+ 60	836,519,677	0.000039
85 %	3.15	+ 20	836,520,003	0.000000
115 %	4.26	+ 20	836,520,003	0.000000
BATT. ENDPOINT	2.98	+ 20	836,520,003	0.000000

© 2003 PCTEST ENGINEERING LABORATORY, INC.

8.1 Test Data (Continued)

8.5 FREQUENCY STABILITY (CDMA 800 MHz)



© 2003 PCTEST ENGINEERING LABORATORY, INC.

8.1 Test Data (Continued)

8.6 FREQUENCY STABILITY (PCS CDMA)

OPERATING FREQUENCY: 1,880,000,002 Hz

CHANNEL: 600

REFERENCE VOLTAGE: 3.7 VAC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (ºC)	FREQ. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	1,880,000,002	0.000000
100 %		- 30	1,879,999,833	0.000009
100 %		- 20	1,879,999,701	0.000016
100 %		- 10	1,879,999,476	0.000028
100 %		0	1,879,999,701	0.000016
100 %		+ 10	1,879,999,626	0.000020
100 %		+ 20	1,880,000,002	0.000000
100 %		+ 25	1,879,999,852	0.000008
100 %		+ 30	1,879,999,626	0.000020
100 %		+ 40	1,879,999,457	0.000029
100 %		+ 50	1,879,999,344	0.000035
100 %		+ 60	1,879,999,269	0.000039
85 %	3.15	+ 20	1,880,000,002	0.000000
115 %	4.26	+ 20	1,880,000,002	0.000000
BATT. ENDPOINT	3.01	+ 20	1,880,000,002	0.000000

© 2003 PCTEST ENGINEERING LABORATORY, INC.

8.1 Test Data (Continued)

8.7 FREQUENCY STABILITY (PCS CDMA)



© 2003 PCTEST ENGINEERING LABORATORY, INC.

9.1 PLOT(S) OF EMISSIONS

(SEE ATTACHMENT D)

© 2003 PCTEST ENGINEERING LABORATORY, INC.

10.1 TEST EQUIPMENT

Type	Model	Cal. Due Date	S/N
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	08/15/04	3638A08713
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	04/17/04	2542A11898
Spectrum Analyzer/Tracking Gen.	HP 8591A (100Hz-1.8GHz)	08/10/04	3144A02458
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/04	2232A19558
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/04	1851A09816
Signal Generator*	Rohde & Schwarz (0.1-1000MHz)	09/12/04	894215/012
Ailtech/Eaton Receiver	NM 37/57A-SL (30-1000MHz)	04/12/04	0792-03271
Ailtech/Eaton Receiver	NM 37/57A (30-1000MHz)	03/11/04	0805-03334
Ailtech/Eaton Receiver	NM 17/27A (0.1-32MHz)	09/17/04	0608-03241
Quasi-Peak Adapter	HP 85650A	08/15/04	2043A00301
Ailtech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	03/11/04	0194-04082
Gigatronics Universal Power Meter	8657A		1835256
Gigatronics Power Sensor	80701A (0.05-18GHz)		1833460
Signal Generator	HP 8648D (9kHz-4GHz)		3613A00315
Amplifier Research	5S1G4 (5W, 800MHz-4.2GHz)		22322
Network Analyzer	HP 8753E (30kHz-3GHz)		JP38020182
Audio Analyzer	HP 8903B		3011A09025
Modulation Analyzer	HP 8901A		2432A03467
Power Meter	HP 437B		3125U24437
Power Sensor	HP 8482H (30µW-3W)		2237A02084
Harmonic/Flicker Test System	HP 6841A (IEC 555-2/3)		3531A00115
Broadband Amplifier (2)	HP 8447D		1145A00470, 1937A03348
Broadband Amplifier	HP 8447F		2443A03784
Horn Antenna	EMCO Model 3115 (1-18GHz)		9704-5182
Horn Antenna	EMCO Model 3115 (1-18GHz)		9205-3874
Horn Antenna	EMCO Model 3116 (18-40GHz)		9203-2178
Biconical Antenna (4)	Eaton 94455/Eaton 94455-1/Singer 94455-1/Compliance Design		1295, 1332, 0355
Log-Spiral Antenna (3)	Ailtech/Eaton 93490-1		0608, 1103, 1104
Roberts Dipoles	Compliance Design (1 set)		
Ailtech Dipoles	DM-105A (1 set)		33448-111
EMCO LISN (6)	3816/2		1079
Microwave Preamplifier 40dB Gain	HP 83017A (0.5-26.5GHz)		3123A00181
Microwave Cables	MicroCoax (1.0-26.5GHz)		
Ailtech/Eaton Receiver	NM37/57A-SL		0792-03271
Spectrum Analyzer	HP 8594A		3051A00187
Spectrum Analyzer (2)	HP 8591A		3034A01395, 3108A02053
Microwave Survey Meter	Holaday Model 1501 (2.450GHz)		80931
Digital Thermometer	Extech Instruments 421305		426966
Attenuator	HP 8495A (0-70dB) DC-4GHz		
Bi-Directional Coax Coupler	Narda 3020A (50-1000MHz)		
Shielded Screen Room	RF Lindgren Model 26-2/2-0		6710 (PCT270)
Shielded Semi-Anechoic Chamber	Ray Proof Model S81		R2437 (PCT278)
Enviromental Chamber	Associated Systems Model 1025 (Temperature/Humidity)		PCT285

* Calibration traceable to the National Institute of Standards and Technology (NIST).

© 2003 PCTEST ENGINEERING LABORATORY, INC.

11.1 SAMPLE CALCULATIONS

A. Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination (Audio/Data)
(Measured at the 99.75% power bandwidth)

Emission Designator = 40K0F8W

Calculation: Voice + SAT
Modulation: Voice is 2.5 kHz and SAT is 6 kHz – Maximum modulation is M = 6 kHz
Deviation: Voice is 12 kHz and SAT is 2 kHz – Maximum deviation is D = 12 + 2 = 14 kHz
Bn = 2xM + 2xDK with K = 1
Bn = 40 kHz

Calculation: Signaling Tone (ST) + SAT
Modulation: ST is 10 kHz and SAT is 6 kHz – Maximum modulation is M = 10 kHz
Deviation: ST is 8 kHz and SAT is 2 kHz – Maximum deviation is D = 8 + 2 = 10 kHz
Bn = 2xM + 2xDK with K = 1
Bn = 40 kHz

Emission Designator = 40K0F1D

Calculation: Voice + SAT
Modulation: Wideband Data is 10 kHz and SAT is 6 kHz – Maximum modulation is M = 10 kHz
Deviation: Wideband Data is 8 kHz and SAT is 2 kHz – Maximum deviation is D = 8 + 2 = 10 kHz
Bn = 2xM + 2xDK with K = 1
Bn = 40 kHz

B. Spurious Radiated Emission - PCS Band

Example: Channel 25 PCS Mode 2nd Harmonic (3702.50 MHz)

The receive analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3702.50 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80) = 50.3 dBc

© 2003 PCTEST ENGINEERING LABORATORY, INC.

12.1 CONCLUSION

The data collected shows that the **LG ELECTRONICS, INC. Tri-Mode Dual-Band Analog/PCS Phone (AMPS/CDMA) FCC ID: BEJ4600** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules.

© 2003 PCTEST ENGINEERING LABORATORY, INC.

PCTEST Engineering Lab.

SPECTRUM ANALYZER PRESENTATION

FCC ID:BEJ4600
LG Electronics
Tri-Mode Phone
FM Channel 383
Operating Frequency: 836.490 MHz
Output Power : 26.0 dBm

Test Mode:Unmodulated Signal



PCTEST Engineering Lab.

SPECTRUM ANALYZER PRESENTATION

FCC ID:BEJ4600
LG Electronics
Tri-Mode Phone
FM Channel 383
Operating Frequency: 836.490 MHz
Output Power : 26.0 dBm

Test Mode:Voice



PCTEST Engineering Lab.

SPECTRUM ANALYZER PRESENTATION

FCC ID:BEJ4600
LG Electronics
Tri-Mode Phone
FM Channel 383
Operating Frequency: 836.490 MHz
Output Power : 26.0 dBm

Test Mode:Wide Band Data



PCTEST Engineering Lab.

SPECTRUM ANALYZER PRESENTATION

FCC ID:BEJ4600
LG Electronics
Tri-Mode Phone
FM Channel 383
Operating Frequency: 836.490 MHz
Output Power : 26.0 dBm

Test Mode:SAT




FCC ID: BEJ4600 FM MODE
MKR 891.00 MHz
REF -60.0 dBm ATTEN 10 dB PG 25.0 dB
-97.79 dBm
PEAK
LOG
5
dB/
OFFST
6.0
dB
DL
-80.0
dBm
VA SB
SC FC
CORR
START 869.00 MHz
STOP 894.00 MHz
#RES BW 100 kHz
#VBW 100 kHz
SWP 20 msec


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs FM Ch. 0991
Mkr1 1.649 GHz
Ref 26 dBm
Atten 40 dB
-15.08 dBm
Peak
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs FM Ch. 0991
Mkr1 7.975 GHz
Ref 26 dBm
Atten 40 dB
-34.60 dBm
Peak
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Start 2.500 GHz
Stop 10.000 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 12.52 ms (601 pts)
Center Freq
6.25000000 GHz
Start Freq
2.50000000 GHz
Stop Freq
10.0000000 GHz
CF Step
750.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs FM Ch. 0383
Mkr1 1.674 GHz
Ref 26 dBm
Atten 40 dB
-15.00 dBm
Peak
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs FM Ch. 0383
Mkr1 7.050 GHz
Ref 26 dBm
Atten 40 dB
-34.84 dBm
Peak
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Start 2.500 GHz
Stop 10.000 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 12.52 ms (601 pts)
Center Freq
6.25000000 GHz
Start Freq
2.50000000 GHz
Stop Freq
10.0000000 GHz
CF Step
750.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs FM Ch. 0799
Mkr1 1.699 GHz
Ref 26 dBm
Atten 40 dB
-17.95 dBm
Peak
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs FM Ch. 0799
Mkr1 7.712 GHz
Ref 26 dBm
Atten 40 dB
-34.99 dBm
Peak
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Start 2.500 GHz
Stop 10.000 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 12.52 ms (601 pts)
Center Freq
6.25000000 GHz
Start Freq
2.50000000 GHz
Stop Freq
10.0000000 GHz
CF Step
750.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


FCC ID: BEJ4600 CDMA MODE
MKR 881.62 MHz
REF -60.0 dBm ATTEN 10 dB PG 25.0 dB
-97.47 dBm
PEAK
LOG
5
dB/
OFFST
6.0
dB
DL
-80.0
dBm
VA SB
SC FC
CORR
START 869.00 MHz
#RES BW 100 kHz
#VBW 100 kHz
STOP 894.00 MHz
SWP 20 msec


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs CDMA Ch. 1013
Mkr1 1.649 GHz
Ref 23.5 dBm
Atten 40 dB
-15.06 dBm
Peak
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs CDMA Ch. 1013
Mkr1 7.025 GHz
Ref 23.5 dBm
Atten 40 dB
-34.83 dBm
Peak
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Center Freq
6.25000000 GHz
Start Freq
2.50000000 GHz
Stop Freq
10.0000000 GHz
CF Step
750.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Start 2.500 GHz
Stop 10.000 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 12.52 ms (601 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs CDMA Ch. 0384
Mkr1 1.649 GHz
Ref 23.5 dBm
Atten 40 dB
-15.48 dBm
Peak
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs CDMA Ch. 0384
Mkr1 7.700 GHz
Ref 23.5 dBm
Atten 40 dB
-34.06 dBm
Peak
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Center Freq
6.25000000 GHz
Start Freq
2.50000000 GHz
Stop Freq
10.0000000 GHz
CF Step
750.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 2.500 GHz
Stop 10.000 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 12.52 ms (601 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs CDMA Ch. 0777
Mkr1 1.649 GHz
Ref 23.5 dBm
Atten 40 dB
-15.05 dBm
Peak
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs CDMA Ch. 0777
Mkr1 7.950 GHz
Ref 23.5 dBm
Atten 40 dB
-34.88 dBm
Peak
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Center Freq
6.25000000 GHz
Start Freq
2.50000000 GHz
Stop Freq
10.0000000 GHz
CF Step
750.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 2.500 GHz
Stop 10.000 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 12.52 ms (601 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Power Out CDMA Ch. 1013
Ref 23.5 dBm
Atten 40 dB
Samp
Log
10
dB/
Offst
0.7
dB
LgAv
100
V1 S2
S3 FS
¤(f):
FTun
Swp
Center 824.70 MHz
Span 10 MHz
#Res BW 3 MHz
#VBW 3 MHz
Sweep 1.038 ms (600 pts)
Center Freq
824.700000 MHz
Start Freq
819.700000 MHz
Stop Freq
829.700000 MHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Power Out CDMA Ch. 0384
Ref 23.5 dBm
Atten 40 dB
Samp
Log
10
dB/
Offst
0.7
dB
LgAv
100
V1 S2
S3 FS
¤(f):
FTun
Swp
Center 836.52 MHz
Span 10 MHz
#Res BW 3 MHz
#VBW 3 MHz
Sweep 1.038 ms (600 pts)
Center Freq
836.520000 MHz
Start Freq
831.520000 MHz
Stop Freq
841.520000 MHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Power Out CDMA Ch. 0384
Ref 23.5 dBm
Atten 40 dB
Samp
Log
10
dB/
Offst
0.7
dB
LgAv
100
V1 S2
S3 FS
¤(f):
FTun
Swp
Center 836.52 MHz
Span 10 MHz
#Res BW 3 MHz
#VBW 3 MHz
Sweep 1.038 ms (600 pts)
Center Freq
836.520000 MHz
Start Freq
831.520000 MHz
Stop Freq
841.520000 MHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Power Out CDMA Ch. 0777
Ref 23.5 dBm
Atten 40 dB
Samp
Log
10
dB/
Offst
0.7
dB
LgAv
100
V1 S2
S3 FS
¤(f):
FTun
Swp
Center 848.31 MHz
Span 10 MHz
#Res BW 3 MHz
#VBW 3 MHz
Sweep 1.038 ms (600 pts)
Center Freq
848.310000 MHz
Start Freq
843.310000 MHz
Stop Freq
853.310000 MHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Band Edge CDMA Ch. 1013
Mkr1 824.000 MHz
Ref 23.5 dBm
Atten 40 dB
-20.979 dBm
Samp
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
824.000000 MHz
Start Freq
821.500000 MHz
Stop Freq
826.500000 MHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 824.000 MHz
Span 5 MHz
#Res BW 13 kHz
#VBW 13 kHz
Sweep 112.8 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Band Edge CDMA Ch. 0777
Mkr1 849.000 MHz
Ref 23.5 dBm
Atten 40 dB
-18.561 dBm
Samp
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
849.000000 MHz
Start Freq
846.500000 MHz
Stop Freq
851.500000 MHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 849.000 MHz
Span 5 MHz
#Res BW 13 kHz
#VBW 13 kHz
Sweep 112.8 ms (600 pts)
Copyright 2000-2002 Agilent Technologies

Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Band Edge CDMA Ch. 1013
Mkr1 824.000 MHz
Ref 23.5 dBm
Atten 40 dB
-21.157 dBm
Samp
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
824.000000 MHz
Start Freq
823.000000 MHz
Stop Freq
825.000000 MHz
CF Step
200.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 824.000 MHz
Span 2 MHz
#Res BW 13 kHz
#VBW 13 kHz
Sweep 45.12 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Band Edge CDMA Ch. 0777
Mkr1 849.000 MHz
Ref 23.5 dBm
Atten 40 dB
-17.123 dBm
Samp
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
849.000000 MHz
Start Freq
848.000000 MHz
Stop Freq
850.000000 MHz
CF Step
200.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 849.000 MHz
Span 2 MHz
#Res BW 13 kHz
#VBW 13 kHz
Sweep 45.12 ms (600 pts)
Copyright 2000-2002 Agilent Technologies

Agilent
R L
Freq/Channel
FCC ID: BEJ4600 4 MHz. Span CDMA Ch. 1013
Mkr1 822.927 MHz
Ref 23.5 dBm
Atten 40 dB
-34.961 dBm
Samp
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
100
V1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
821.000000 MHz
Start Freq
819.000000 MHz
Stop Freq
823.000000 MHz
CF Step
400.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 821.000 MHz
Span 4 MHz
#Res BW 100 kHz
#VBW 100 kHz
Sweep 1.557 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 4 MHz. Span CDMA Ch. 0777
Mkr1 850.073 MHz
Ref 23.5 dBm
Atten 40 dB
-34.109 dBm
Samp
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
100
V1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
852.000000 MHz
Start Freq
850.000000 MHz
Stop Freq
854.000000 MHz
CF Step
400.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 852.000 MHz
Span 4 MHz
#Res BW 100 kHz
#VBW 100 kHz
Sweep 1.557 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 836.52 MHz
Trig Free
Channel Power
Averages: 10
FCC ID: BEJ4600 Ch. Power CDMA Ch. 0384
Ref 23.5 dBm
Atten 40 dB
#Avg
Log
10
dB/
Offst
0.7
dB
Center 836.520 MHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
Sweep 9.744 ms (600 pts)
Channel Power
Power Spectral Density
23.52 dBm /2.0000 MHz
-39.49 dBm/Hz
Center Freq
836.520000 MHz
Start Freq
835.020000 MHz
Stop Freq
838.020000 MHz
CF Step
300.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 836.52 MHz
Trig Free
Occupied Bandwidth
FCC ID: BEJ4600 Occpd BW CDMA Ch. 0384
Ref 23.5 dBm
Atten 40 dB
#Samp
Log
10
dB/
Offst
0.7
dB
Center 836.520 MHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
Sweep 9.744 ms (600 pts)
Occupied Bandwidth
1.2510 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB
Transmit Freq Error -6.414 kHz
x dB Bandwidth 1.379 MHz*
Center Freq
836.520000 MHz
Start Freq
835.020000 MHz
Stop Freq
838.020000 MHz
CF Step
300.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Block Edge CDMA Ch. 310
Mkr1 834.996 MHz
Ref 23.5 dBm
Atten 40 dB
-18.581 dBm
Samp
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center 835.000 MHz
Span 5 MHz
#Res BW 13 kHz
#VBW 13 kHz
Sweep 112.8 ms (600 pts)
Center Freq
835.000000 MHz
Start Freq
832.500000 MHz
Stop Freq
837.500000 MHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Block Edge CDMA Ch. 357
Mkr1 835.000 MHz
Ref 23.5 dBm
Atten 40 dB
-23.100 dBm
Samp
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center 835.000 MHz
Span 5 MHz
#Res BW 13 kHz
#VBW 13 kHz
Sweep 112.8 ms (600 pts)
Center Freq
835.000000 MHz
Start Freq
832.500000 MHz
Stop Freq
837.500000 MHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge CDMA Ch. 643
Mkr1 845.000 MHz
Ref 23.5 dBm
Atten 40 dB
-21.183 dBm
Samp
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
845.000000 MHz
Start Freq
842.500000 MHz
Stop Freq
847.500000 MHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 845.000 MHz
Span 5 MHz
#Res BW 13 kHz
#VBW 13 kHz
Sweep 112.8 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge CDMA Ch. 690
Mkr1 845.000 MHz
Ref 23.5 dBm
Atten 40 dB
-16.369 dBm
Samp
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
845.000000 MHz
Start Freq
842.500000 MHz
Stop Freq
847.500000 MHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 845.000 MHz
Span 5 MHz
#Res BW 13 kHz
#VBW 13 kHz
Sweep 112.8 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge CDMA Ch. 693
Mkr1 846.500 MHz
Ref 23.5 dBm
Atten 40 dB
-22.434 dBm
Samp
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center 846.500 MHz
Span 5 MHz
#Res BW 13 kHz
#VBW 13 kHz
Sweep 112.8 ms (600 pts)
Center Freq
846.500000 MHz
Start Freq
844.000000 MHz
Stop Freq
849.000000 MHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge CDMA Ch. 740
Mkr1 846.500 MHz
Ref 23.5 dBm
Atten 40 dB
-17.318 dBm
Samp
Log
10
dB/
Offst
0.7
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center 846.500 MHz
Span 5 MHz
#Res BW 13 kHz
#VBW 13 kHz
Sweep 112.8 ms (600 pts)
Center Freq
846.500000 MHz
Start Freq
844.000000 MHz
Stop Freq
849.000000 MHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R T
Freq/Channel
FCC ID: BEJ4600 Cond Spurs PCS Ch. 0025
Mkr1 2.442 GHz
Ref 24 dBm
Atten 40 dB
-38.70 dBm
Peak
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Center 1.255 GHz
Span 2.49 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.153 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs PCS Ch. 0025
Mkr1 3.70 GHz
Ref 24 dBm
Atten 40 dB
-22.51 dBm
Peak
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Center Freq
11.2500000 GHz
Start Freq
2.50000000 GHz
Stop Freq
20.0000000 GHz
CF Step
1.75000000 GHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Center 11.25 GHz
Span 17.5 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 43.77 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs PCS Ch. 0600
Mkr1 2.346 GHz
Ref 24 dBm
Atten 40 dB
-39.38 dBm
Peak
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 1.255 GHz
Span 2.49 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.153 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs PCS Ch. 0600
Mkr1 3.76 GHz
Ref 24 dBm
Atten 40 dB
-27.29 dBm
Peak
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Center Freq
11.2500000 GHz
Start Freq
2.50000000 GHz
Stop Freq
20.0000000 GHz
CF Step
1.75000000 GHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 11.25 GHz
Span 17.5 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 43.77 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs PCS Ch. 1175
Mkr1 2.280 GHz
Ref 24 dBm
Atten 40 dB
-39.10 dBm
Peak
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 1.255 GHz
Span 2.49 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.153 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Cond Spurs PCS Ch. 1175
Mkr1 3.81 GHz
Ref 24 dBm
Atten 40 dB
-29.25 dBm
Peak
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
¤(f):
FTun
Swp
Center Freq
11.2500000 GHz
Start Freq
2.50000000 GHz
Stop Freq
20.0000000 GHz
CF Step
1.75000000 GHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 11.25 GHz
Span 17.5 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 43.77 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Power Out PCS Ch. 0025
Ref 24 dBm
Atten 40 dB
Samp
Log
10
dB/
Offst
1
dB
LgAv
100
V1 S2
S3 FS
¤(f):
FTun
Swp
Center 1.851 25 GHz
Span 10 MHz
#Res BW 3 MHz
#VBW 3 MHz
Sweep 1.038 ms (600 pts)
Center Freq
1.85125000 GHz
Start Freq
1.84625000 GHz
Stop Freq
1.85625000 GHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Power Out PCS Ch. 0600
Ref 24 dBm
Atten 40 dB
Samp
Log
10
dB/
Offst
1
dB
LgAv
100
V1 S2
S3 FS
¤(f):
FTun
Swp
Center 1.880 00 GHz
Span 10 MHz
#Res BW 3 MHz
#VBW 3 MHz
Sweep 1.038 ms (600 pts)
Center Freq
1.88000000 GHz
Start Freq
1.87500000 GHz
Stop Freq
1.88500000 GHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Band Edge PCS Ch. 0025
Mkr1 1.850 000 GHz
Ref 24 dBm
Atten 40 dB
-31.517 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center 1.850 000 GHz
Span 5 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 21.2 ms (600 pts)
Center Freq
1.85000000 GHz
Start Freq
1.84750000 GHz
Stop Freq
1.85250000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: BEJ4600 Band Edge PCS Ch. 1175
Mkr1 1.910 000 GHz
Ref 24 dBm
Atten 40 dB
-25.500 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center 1.910 000 GHz
Span 5 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 21.2 ms (600 pts)
Center Freq
1.91000000 GHz
Start Freq
1.90750000 GHz
Stop Freq
1.91250000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Band Edge PCS Ch. 0025
Mkr1 1.850 000 GHz
Ref 24 dBm
Atten 40 dB
-30.469 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
1.85000000 GHz
Start Freq
1.84900000 GHz
Stop Freq
1.85100000 GHz
CF Step
200.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 1.850 000 GHz
Span 2 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 8.506 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Band Edge PCS Ch. 1175
Mkr1 1.910 000 GHz
Ref 24 dBm
Atten 40 dB
-25.103 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
1.91000000 GHz
Start Freq
1.90900000 GHz
Stop Freq
1.91100000 GHz
CF Step
200.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 1.910 000 GHz
Span 2 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 8.506 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 4 MHz. Span PCS Ch. 0025
Mkr1 1.848 993 GHz
Ref 24 dBm
Atten 40 dB
-28.189 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
V1 S2
S3 FS
¤(f):
FTun
Swp
Center 1.847 000 GHz
Span 4 MHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 1.038 ms (600 pts)
Center Freq
1.84700000 GHz
Start Freq
1.84500000 GHz
Stop Freq
1.84900000 GHz
CF Step
400.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 4 MHz. Span PCS Ch. 1175
Mkr1 1.911 000 GHz
Ref 24 dBm
Atten 40 dB
-23.824 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
V1 S2
S3 FS
¤(f):
FTun
Swp
Center 1.913 000 GHz
Span 4 MHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 1.038 ms (600 pts)
Center Freq
1.91300000 GHz
Start Freq
1.91100000 GHz
Stop Freq
1.91500000 GHz
CF Step
400.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 1.88 GHz
Trig Free
Channel Power
Averages: 10
FCC ID: BEJ4600 Ch. Power PCS Ch. 0600
Ref 24 dBm
Atten 40 dB
#Avg
Log
10
dB/
Offst
1
dB
Center 1.880 000 GHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
Sweep 9.744 ms (600 pts)
Channel Power
24.04 dBm /2.0000 MHz
Power Spectral Density
-38.98 dBm/Hz
Center Freq
1.88000000 GHz
Start Freq
1.87850000 GHz
Stop Freq
1.88150000 GHz
CF Step
300.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 1.88 GHz
Trig Free
Occupied Bandwidth
Averages: 10
FCC ID: BEJ4600 Occpd BW PCS Ch. 0600
Ref 24 dBm
Atten 40 dB
#Samp
Log
10
dB/
Offst
1
dB
Center 1.880 000 GHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
Sweep 9.744 ms (600 pts)
Occupied Bandwidth
1.2514 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB
Transmit Freq Error 195.802 Hz
x dB Bandwidth 1.392 MHz*
Center Freq
1.88000000 GHz
Start Freq
1.87850000 GHz
Stop Freq
1.88150000 GHz
CF Step
300.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge PCS Ch. 275
Mkr1 1.865 000 GHz
Ref 24 dBm
Atten 40 dB
-32.789 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
1.86500000 GHz
Start Freq
1.86250000 GHz
Stop Freq
1.86750000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 1.865 000 GHz
Span 5 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 21.2 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge PCS Ch. 325
Mkr1 1.865 000 GHz
Ref 24 dBm
Atten 40 dB
-31.986 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
1.86500000 GHz
Start Freq
1.86250000 GHz
Stop Freq
1.86750000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 1.865 000 GHz
Span 5 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 21.2 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge PCS Ch. 375
Mkr1 1.870 000 GHz
Ref 24 dBm
Atten 40 dB
-30.347 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center 1.870 000 GHz
Span 5 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 21.2 ms (600 pts)
Center Freq
1.87000000 GHz
Start Freq
1.86750000 GHz
Stop Freq
1.87250000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge PCS Ch. 425
Mkr1 1.870 000 GHz
Ref 24 dBm
Atten 40 dB
-30.080 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center 1.870 000 GHz
Span 5 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 21.2 ms (600 pts)
Center Freq
1.87000000 GHz
Start Freq
1.86750000 GHz
Stop Freq
1.87250000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge PCS Ch. 675
Mkr1 1.885 000 GHz
Ref 24 dBm
Atten 40 dB
-30.166 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center 1.885 000 GHz
Span 5 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 21.2 ms (600 pts)
Center Freq
1.88500000 GHz
Start Freq
1.88250000 GHz
Stop Freq
1.88750000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge PCS Ch. 425
Mkr1 1.870 000 GHz
Ref 24 dBm
Atten 40 dB
-30.080 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center 1.870 000 GHz
Span 5 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 21.2 ms (600 pts)
Center Freq
1.87000000 GHz
Start Freq
1.86750000 GHz
Stop Freq
1.87250000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge PCS Ch. 775
Mkr1 1.890 000 GHz
Ref 24 dBm
Atten 40 dB
-32.074 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
1.89000000 GHz
Start Freq
1.88750000 GHz
Stop Freq
1.89250000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 1.890 000 GHz
Span 5 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 21.2 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge PCS Ch. 825
Mkr1 1.890 000 GHz
Ref 24 dBm
Atten 40 dB
-35.962 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
1.89000000 GHz
Start Freq
1.88750000 GHz
Stop Freq
1.89250000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 1.890 000 GHz
Span 5 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 21.2 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge PCS Ch. 875
Mkr1 1.895 000 GHz
Ref 24 dBm
Atten 40 dB
-37.641 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
1.89500000 GHz
Start Freq
1.89250000 GHz
Stop Freq
1.89750000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 1.895 000 GHz
Span 5 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 21.2 ms (600 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: BEJ4600 Block Edge PCS Ch. 925
Mkr1 1.895 000 GHz
Ref 24 dBm
Atten 40 dB
-39.215 dBm
Samp
Log
10
dB/
Offst
1
dB
Dl
-13.0
dBm
LgAv
100
W1 S2
S3 FS
¤(f):
f>50k
Swp
Center Freq
1.89500000 GHz
Start Freq
1.89250000 GHz
Stop Freq
1.89750000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 1.895 000 GHz
Span 5 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 21.2 ms (600 pts)
Copyright 2000-2002 Agilent Technologies

SUBJECT: Modulation Characteristics
FCC Part 24/22

Test Report No.: 22/24.230818400.BEJ
Test Date: 08.18.2003

EUT: Tri-Mode Dual-Band Analog/PCS Phone (AMPS/CDMA)
Model: *LG-4600*
FCC ID: **BEJ4600**

REFERENCE: 1 kHz = 0 dB



SUBJECT: Modulation Characteristics
FCC Part 24/22

Test Report No.: 22/24.230818400.BEJ
Test Date: 08.18.2003

EUT: Tri-Mode Dual-Band Analog/PCS Phone (AMPS/CDMA)
Model: *LG-4600*
FCC ID: **BEJ4600**

REFERENCE: 1 kHz = 0 dB



SUBJECT: Modulation Characteristics
FCC Part 24/22

Test Report No.: 22/24.230818400.BEJ
Test Date: 08.18.2003

EUT: Tri-Mode Dual-Band Analog/PCS Phone (AMPS/CDMA)
Model: *LG-4600*
FCC ID: **BEJ4600**

REFERENCE: 1 kHz = 0 dB