

Test Report for FCC

FCC ID:BEJ52LG50DCUG

Report Number		ESTF150811-006			
Applicant	Company name	LG Electronics USA			
	Address	1000 Sylvan Avenue Englewood Cliffs, NJ 07632			
	Telephone	847-941-8373			
Product	Product name	LCD TV/MONITOR			
	Model name	52LG50DC-UG	Manufacturer	LG Electronics Inc.	
	Serial number	NONE	Country of origin	KOREA	
Test date	11-Nov-08		Date of issue	13-Nov-08	
Testing location	ESTECH. Co., Ltd. 97-1 Hoiuk-Ri Majang-Myon, Icheon-city, KyungKi-Do, Korea				
Standard	FCC PART 15 2007 , ANSI C 63.4 2003 , ICES-003				
Test item	☒ Conducted Emission	☐ Class A	☒ Class B	Test result	OK
	☒ Radiated Emission	☐ Class A	☒ Class B	Test result	OK
Measurement facility registration number		94696			
Tested by	Senior Engineer J.H.Kim (Signature)				
Reviewed by	Engineering Manager J.M.Yang (Signature)				
Abbreviation	OK, Pass = Passed, Fail = Failed, N/A = not applicable				
* Note - This test report is not permitted to copy partly without our permission - This test result is dependent on only equipment to be used - This test result based on a single evaluation of one sample of the above mentioned					

Contents

1. Laboratory Information	3
2. Description of EUT	4
3. Test Standards	5
4. Measurement condition	6
5. Measurement of radiated emission	8
5.1 Measurement equipment	8
5.2 Environmental conditions	8
5.3 Test data	9
5.4 Test data	10
6. Measurement of conducted emission	11
6.1 Measurement equipment	11
6.2 Environmental conditions	11
6.3 Test data	12
7. Photographs of test setup	13
8. Photographs of EUT	15

Appendix 1. Spectral diagram

2. Description of EUT

2.1 Summary of Equipment Under Test

Product Name : LCD TV/MONITOR
 Model Number : 52LG50DC-UG
 Serial Number : NONE
 Manufacturer : LG Electronics Inc.
 Country of origin : KOREA
 Rating : INPUT:AC100-240V ~ 50 /60Hz
 Receipt Date : 2008-11-06
 X-tal lists : 4MHz, 12MHz, 25MHz

2.2 General descriptions of EUT

MODELS		47LG50 (47LG50-UG) 47LG50DC (47LG50DC-UG) 47LG55 (47LG55-UE)	52LG50 (52LG50-UG) 52LG50DC (52LG50DC-UG)	Resolution	Horizontal Frequency(KHz)	Vertical Frequency(Hz)
Dimensions (Width x Height x Depth)	With stand	45.5 x 32.0 x 13.5 inches 1156.2 x 813.1 x 342.9 mm	50.8 x 35.1 x 13.5 inches 1291.7 x 892.2 x 342.9 mm	640x350	31.468	70.09
	Without stand	45.5 x 29.1 x 4.0 inches 1156.2 x 739.2 x 103.0 mm	50.8 x 32.1 x 4.5 inches 1291.7 x 817.0 x 115.3 mm	720x400	31.469	70.08
		640x480	31.469	59.94		
		Weight	With stand	64.3 pounds / 29.2 kg	87.0 pounds / 39.5 kg	800x600
Without stand	54.2 pounds / 24.6 kg		76.9 pounds / 34.9 kg	37.879	60.31	
Power requirement		AC100-240V ~ 50/60Hz		1024x768	48.363	60.00
Television System		NTSC-M, ATSC, 64 & 256 QAM			56.476	70.06
Program Coverage		VHF 2-13, UHF 14-69, CATV 1-135, DTV 2-69, CADTV 1-135		1280x768	47.776	59.87
External Antenna Impedance		75 ohm				
Environment condition	Operating Temperature	32 ~ 104°F (0 ~ 40°C)		1280x1024	63.981	60.02
	Operating Humidity	Less than 80%		1360x768	47.712	60.015
	Storage Temperature	-4 ~ 140°F (-20 ~ 60°C)				
	Storage Humidity	Less than 85%		1600x1200	75.00	60.00
				1920x1080 RGB-PC	66.587	59.934
				1920x1080 HDMI-PC	67.5	60.00

3. Test Standards

Test Standard : FCC PART 15 (2007) & ICES-003

This Standard sets out the regulations under which an intentional, unintentional, or incidental radiator may be operated without an individual license. It also contains the technical specifications, administrative requirements and other conditions relating to the marketing of Part 15 devices.

Test Method : ANSI C 63.4 (2003)


This standard sets forth uniform methods of measurement of radio-frequency (RF) signals and noise emitted from both unintentional and intentional emitters of RF energy in the frequency range 9 kHz to 40 GHz. Methods for the measurement of radiated and AC power-line conducted radio noise are covered and may be applied to any such equipment unless otherwise specified by individual equipment requirements. These methods cover measurement of certain devices that deliberately radiate energy, such as intentional emitters, but does not cover licensed transmitters. This standard is not intended for certification/approval of avionic equipment or for industrial, scientific, and medical (ISM) equipment. These methods apply to the measurement of individual units or systems comprised of multiple units.

4. Measurement Condition

4.1 EUT Operation.

- * The EUT was in the following operation mode during all testing
- * The operational conditions of the EUT was determined by the manufacturer according to the typical use of the EUT with respect to the expected highest level of emission
- * After setting as test arrangment diagram, we tested the EUT under continuous displaying "H" character and playing Audio out /Video

4.2 Configuration and Peripherals



4.3 EUT and Support equipment

Equipment Name	Model	S/N	Manufacturer	Remark (FCC ID)
LCD TV/MONITOR	52LG50DC -UG	NONE	LG Electronics Inc.	EUT
Personal Computer	DCMF	6RKPHBX	Dell Inc.	-
iPod	A1136	9C6453A6V9K	Apple Computer Inc.	-
Keyboard	L100	CN0RH6596589085H0EYE	Dell Inc.	-
Mouse	MO56UOA	G0U00X18	Dell Inc.	-
Printer	MJC - 5750	NA34BFFP313402V	SAMSUNG ELECTRONICS(SHANDONG)DIGIT AL PRINTING CO.,LTD.	-
Adapter	PA8040WB	0703016326	Bestec Electronics (DongGuan)Co.,Ltd.	-

4.4 Cable Connecting

Start Equipment		End Equipment		Cable Standard		Remark
Name	I/O port	Name	I/O port	Length	Shielded	
LCD TV/MONITOR	DVI/HDMI	Personal Computer	DVI	2	Y	
LCD TV/MONITOR	RGB	Personal Computer	RGB	2	Y	
LCD TV/MONITOR	LINE IN	Personal Computer	Line out	2	N	
LCD TV/MONITOR	S-VIDEO	-	-	2	N	
LCD TV/MONITOR	AV IN1 x3port	-	-	2	N	
LCD TV/MONITOR	AV IN2 x3port	-	-	2	N	
LCD TV/MONITOR	AV OUT x2port	-	-	2	N	
LCD TV/MONITOR	ANTENNA	-	-	2	N	
LCD TV/MONITOR	Component x 10port	-	-	2	N	
Personal Computer	USB	iPod	USB	0.5	Y	
Personal Computer	USB	Keyboard	USB	2	Y	
Personal Computer	USB	Mouse	USB	2	Y	
Personal Computer	USB	Printer	USB	2	Y	
Printer	Power	Adapter	-	2	N	

5. Measurement of radiated disturbance

Above 30 MHz Electric Field strength was measured in accordance with FCC Part 15 (2007) & ICES-003. The test setup was made according to ANSI C 63.4 (2003) on an open test site, which allows a 3m distance measurement. The EUT was placed in the center of wooden turntable. The height of this table was 0.8m. The measurement was conducted with both horizontal and vertical antenna polarization. The turntable has fully rotated. For further description of the configuration refer to the picture of the test setup.

5.1 Measurement equipments

Equipment Name	Type	Manufacturer	Serial No.	Next Calibration date
Test Receiver	ESVS10	Rohde & Schwarz	838562/002	2009. 1. 24
Spectrum Analyzer	R3261C	ADVANTEST	61720116	2009. 4. 22
LogBicon Antenna	VULB 9160	Schwarzbeck	3142	2009. 5. 15
Amplifier	8447F	HP	2805A02972	2009. 6. 26
Turn Table	2087	EMCO	2129	-
Antenna Mast	2070-01	EMCO	9702-203	-
ANT Mast Controller	2090	EMCO	1535	-
Turn Table Controller	2090	EMCO	1535	-

5.2 Environmental Condition

Test Place : Open site(3m)
 Temperature (°C) : 17 °C
 Humidity (%) : 40 %

5.3 Test data

Test Date : 11-Nov-08

Measurement Distance : 3 m

Frequency (MHz)	Reading (dBμV)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dBμV/m)	Result (dBμV/m)	Margin (dB)
54.61	16.20	V	1.0	12.11	1.1	40.0	29.44	-10.56
74.85	16.70	V	1.0	8.98	1.3	40.0	27.01	-12.99
82.51	26.40	V	1.0	8.09	1.4	40.0	35.88	-4.12
110.58	20.00	V	1.0	10.29	1.6	43.5	31.90	-11.60
143.32	21.90	H	1.0	12.76	2.0	43.5	36.66	-6.84
167.33	19.60	H	1.6	12.13	2.2	43.5	33.89	-9.61
177.51	20.20	H	1.3	11.29	2.2	43.5	33.68	-9.82
221.04	20.10	H	1.4	10.40	2.5	46.0	33.04	-12.96
247.53	18.80	H	1.0	11.31	2.8	46.0	32.88	-13.12
264.00	20.40	H	1.0	11.83	2.9	46.0	35.14	-10.86
346.53	21.00	H	1.0	13.93	3.6	46.0	38.56	-7.44
363.03	12.20	H	1.0	14.30	3.7	46.0	30.21	-15.79
440.08	12.80	V	1.0	16.25	4.4	46.0	33.47	-12.53
495.00	11.70	H	1.0	17.04	4.7	46.0	33.45	-12.55
524.86	17.10	H	1.0	17.65	5.0	46.0	39.73	-6.27
908.79	5.80	H	1.0	23.31	7.4	46.0	36.56	-9.44

Remark	H : Horizontal, V : Vertical TEST MODE ; Resolution 1920*1080(60Hz) at RGB mode (Worse Case) *CL = Cable Loss-Amplifier Gain(In case of above 1000Mhz) *CL = Cable Loss(In case of below 1000Mhz) *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120KHz for Quasi-peak detection at frequency below 1GHz. *After connect with ferrite cores to RGB cable, tested radiated emission.
--------	--

5.4 Test data

Test Date : 11-Nov-08

Measurement Distance : 3 m

Frequency (MHz)	Reading (dBμV)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dBμV/m)	Result (dBμV/m)	Margin (dB)
48.62	19.10	H	4.0	12.41	1.1	40.0	32.58	-7.42
53.50	16.40	V	1.0	12.21	1.1	40.0	29.72	-10.28
74.86	17.30	V	1.0	8.98	1.3	40.0	27.61	-12.39
82.51	24.00	V	1.0	8.09	1.4	40.0	33.48	-6.52
110.62	22.60	V	1.0	10.29	1.6	43.5	34.51	-8.99
140.13	20.30	H	1.8	12.77	2.0	43.5	35.07	-8.43
170.72	19.20	H	1.3	11.85	2.2	43.5	33.26	-10.24
179.07	21.00	H	1.2	11.17	2.2	43.5	34.35	-9.15
219.99	21.50	H	1.0	10.36	2.5	46.0	34.39	-11.61
247.54	16.50	H	1.0	11.31	2.8	46.0	30.58	-15.42
264.02	18.90	H	1.0	11.83	2.9	46.0	33.64	-12.36
346.52	21.10	H	1.0	13.93	3.6	46.0	38.66	-7.34
363.01	11.60	H	1.0	14.30	3.7	46.0	29.61	-16.39
440.06	13.00	V	1.0	16.25	4.4	46.0	33.67	-12.33
495.01	11.60	H	1.0	17.04	4.7	46.0	33.35	-12.65
524.87	13.20	H	1.0	17.65	5.0	46.0	35.83	-10.17
910.76	4.20	V	1.0	23.34	7.4	46.0	34.91	-11.09
Remark	H : Horizontal, V : Vertical TEST MODE ; Resolution 1920*1080(60Hz) at DVI mode (Worse Case) *CL = Cable Loss-Amplifier Gain(In case of above1000Mhz) *CL = Cable Loss(In case of below1000Mhz) *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120KHz for Quasi-peak detection at frequency below 1GHz. *After connect with ferrite cores to RGB cable, tested radiated emission.							

6. Measurement of conducted disturbance

The continuous disturbance voltage of AC Mains in the frequency from 0.15 to 30 MHz was measured in accordance to FCC Part 15 (2007) & ICES-003. The test setup was made according to ANSI C 63.4 (2003) in a shielded. The EUT was placed on a non-conductive table at least 80 above the ground plan. A grounded vertical reference plane was positioned in a distance of 40cm from the EUT. The distance from the EUT to other metal surfaces was at least 0.8m. The EUT was only earthen by its power cord through the line impedance stabilizing network. The power cord has been bundled to a length of 1.0m.. The test receiver with Quasi Peak detector complies with CISPR 16.

6.1 Measurement equipments

Equipment Name	Type	Manufacturer	Serial No.	Next Calibration date
LISN	NNLA8120A	Schwarzbeck	8120161	2009. 2. 28
LISN	ESH3-Z5	Schwarzbeck	838979/010	2009. 2. 28
TEST Receive	ESPI7	Rohde & Schwarz	100185	2009. 8. 27
Pulse Limiter	ESH3Z2	Rohde & Schwarz	NONE	-

6.2 Environmental Condition

Test Place : Shield Room
 Temperature (°C) : 23 °C
 Humidity (%) : 42 %

6.3 Test data

Test Date : 11-Nov-08

Frequency (MHz)	Correction Factor		Line (H/N)	Quasi-peak Value			Average Value		
	Lisn (dB)	Cable (dB)		Limit (dBμV)	Reading (dBμV)	Result (dBμV)	Limit (dBμV)	Reading (dBμV)	Result (dB)
0.21	0.17	0.2	H	63.24	45.19	45.59	53.24	26.57	26.97
0.22	0.18	0.2	N	62.93	48.11	48.52	52.93	37.82	38.23
0.25	0.19	0.2	H	61.63	44.56	44.98	51.63	27.19	27.61
0.28	0.20	0.2	H	60.73	47.40	47.83	50.73	34.12	34.55
0.29	0.21	0.2	N	60.58	47.69	48.13	50.58	33.67	34.11
0.32	0.21	0.2	H	59.71	48.88	49.33	49.71	35.36	35.81
0.54	0.20	0.4	H	56.00	25.34	25.91	46.00	21.38	21.95
0.65	0.20	0.4	H	56.00	24.00	24.58	46.00	18.64	19.22
0.78	0.20	0.4	N	56.00	25.12	25.72	46.00	20.93	21.53
1.22	0.19	0.5	H	56.00	23.07	23.75	46.00	17.80	18.48
1.27	0.19	0.5	N	56.00	23.44	24.12	46.00	19.02	19.70
1.29	0.19	0.5	H	56.00	23.53	24.21	46.00	18.64	19.32
12.75	0.63	0.9	H	60.00	22.02	23.58	50.00	15.81	17.37
20.57	0.85	1.1	H	60.00	22.43	24.43	50.00	14.77	16.77
Remark	H : Hot Line, N : Neutral Line *After connect with ferrite cores to RGB cable, tested conducted emission.								

7. Photographs of test setup

7.1 Setup for Radiated Test : 30 ~ 1000 MHz

[Front]



[Rear]



7.2 Setup for Conducted Test : 0.15 ~ 30 MHz

[Front]



[Rear]



8. Photographs of EUT

[Front]



[Rear]




Appendix 1. Spectral diagram

*HOT



RBW 9 kHz
MT 1 s

Att 10 dB AUTO PREAMP OFF



Comment: 52LG50DC-UG_H0T

Date: 11.NOV.2008 10:57:01


*NEUTRAL



RBW 9 kHz

MT 1 s

Att 10 dB AUTO PREAMP OFF



Comment: 52LG50DC-UG_NEUTRAL

Date: 11.NOV.2008 11:03:04