

FCC 15.247
2.4 GHz Report

for

LG Electronics Inc.

**1, Gwanak-ro, Gwanak-gu, Seoul, 151-919,
Rep. of Korea**

Brand : LG
Product Name : Scene Gateway
Model Name : 9GW97185D3
FCC ID : BEJ9GW97185D3-1

TABLE OF CONTENTS

Description	Page
TEST REPORT CERTIFICATION	4
1. REPORT HISTORY.....	5
2. SUMMARY OF TEST RESULTS	6
3. GENERAL INFORMATION	7
3.1. Description of EUT	7
3.2. EUT Specifications Assessed in Current Report	8
3.3. Antenna Information	8
3.4. Test Configuration	9
3.5. Tested Supporting System List	10
3.6. Setup Configuration	10
3.7. Operating Condition of EUT	11
3.8. Description of Test Facility	11
3.9. Measurement Uncertainty	12
4. MEASUREMENT EQUIPMENT LIST	13
4.1. Conducted Emission Measurement	13
4.2. Radiated Emission Measurement	13
4.3. RF Conducted Measurement	13
5. CONDUCTED EMISSION MEASUREMENT	14
5.1. Block Diagram of Test Setup	14
5.2. Power Line Conducted Emission Limit	14
5.3. Test Procedure	14
5.4. Conducted Emission Measurement Results	15
6. RADIATED EMISSION MEASUREMENT	17
6.1. Block Diagram of Test Setup	17
6.2. Radiated Emission Limits	18
6.3. Test Procedure	18
6.4. Measurement Result Explanation	19
6.5. Test Results	19
7. 6dB BANDWIDTH MEASUREMENT	31
7.1. Block Diagram of Test Setup	31
7.2. Specification Limits	31
7.3. Test Procedure	31
7.4. Test Results	31
8. MAXIMUM PEAK OUTPUT POWER MEASUREMENT	33
8.1. Block Diagram of Test Setup	33
8.2. Specification Limits	33
8.3. Test Procedure	33
8.4. Test Results	34
9. EMISSION LIMITATIONS MEASUREMENT	37
9.1. Block Diagram of Test Setup	37
9.2. Specification Limits	37
9.3. Test Procedure	37
9.4. Test Results	38

AUDIX Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

10. POWER SPECTRAL DENSITY	41
10.1. Block Diagram of Test Setup	41
10.2. Specification Limits	41
10.3. Test Procedure	41
10.4. Test Results	42
11. DEVIATION TO TEST SPECIFICATIONS.....	43

APPENDIX A TEST PHOTOGRAPHS

TEST REPORT CERTIFICATION

Applicant : LG Electronics Inc.
Manufacture : LG Electronics Inc.
Factory : TIANJIN BLUECOM CO., LTD
Product Name : Scene Gateway
Model No. : 9GW97185D3
Serial No. : N/A
Brand : LG
Power Supply : DC 5V (via power adaptor)


Applicable Standards:

FCC Rules and Regulations Part 15 Subpart C, Oct. 2014
ANSI C63.4:2009
KDB 558074 D01 DTS Meas Guidance v03r02

AUDIX Technology Corp. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report. **AUDIX Technology Corp.** does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens and samples.

Date of Test: 2015. 05. 29 ~ 06. 10

Date of Report: 2015. 06. 11

Producer: 
(Tina Huang/Administrator)

Signatory: 
(Ben Cheng/Manager)

1. REPORT HISTORY

Revision	Date	Revision Summary	Report Number
0	2015. 06. 11	Original Report.	EM-F150298

2. SUMMARY OF TEST RESULTS

Rule	Description	Results
15.207	Conducted Emission	PASS
15.247(d)/ 15.205	Radiated Band Edge and Radiated Spurious Emission	PASS
15.247(a)	6dB Bandwidth	PASS
15.247(b)	Maximum Peak Output	PASS
15.247(d)	Conducted Band Edges and Conducted Spurious Emission	PASS
15.247 (e)	Power Spectral Density	PASS
15.203	Antenna Requirement	PASS

3. GENERAL INFORMATION

3.1. Description of EUT

Product	Scene Gateway
Model Number	9GW97185D3
Serial Number	N/A
Brand Name	LG
Applicant	LG Electronics Inc. 1, Gwanak-ro, Gwanak-gu, Seoul, 151-919, Rep. of Korea
Manufacture	LG Electronics Inc. 1, Gwanak-ro, Gwanak-gu, Seoul, 151-919, Rep. of Korea
Factory	TIANJIN BLUECOM CO., LTD. Quanxing road, Wu-Qing, Development Area, Hi-tech industry Park, Tianjin, China
RF Features	ZigBee (IEEE 802.15.4)
Transmit Type	1T1R
Adapter	LG, M/N: MCS-02KR Input: AC 100-240V, 50/60Hz, Max. 0.2A Output: DC 5V, 0.85A
USB DC Cable	Unshielded, Detachable, 1.2m
Interface Ports	DC Port *1 LAN Port*1
Date of Receipt of Sample	2015. 04. 30

3.2. EUT Specifications Assessed in Current Report


Mode	Fundamental Range (MHz)	Channel Number	Modulation	Data Rate (Mbps)
ZigBee (IEEE 802.15.4)	2405-2480	16	DSSS (O-QPSK)	0.25

Channel List			
ZigBee (IEEE 802.15.4)			
Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)
11	2405	19	2445
12	2410	20	2450
13	2415	21	2455
14	2420	22	2460
15	2425	23	2465
16	2430	24	2470
17	2435	25	2475
18	2440	26	2480

3.3. Antenna Information

Antenna Part Number	Manufacture	Antenna Type	Frequency	Max Gain (dBi)
---	BLUECOM	PIFA	2.4GHz	1.74

3.4. Test Configuration



Note: When duty cycle is less than 98% (0.98) that duty cycle factor $10\log(1/x)$ is needed to add in conducted test items measured in average detector.

AC Conduction	
Test Case	Normal operation

Item		Mode	Data Rate	Test Channel
Radiated Test Case	Radiated Band Edge ^{Note1}	ZigBee	0.25 Mbps	11/12/25/26
	Radiated Spurious Emission (30MHz-1GHz) ^{Note1}	ZigBee	0.25 Mbps	18
	Radiated Spurious Emission (Above 1GHz) ^{Note1}	ZigBee	0.25 Mbps	11/18/26
Conducted Test Case	6dB Bandwidth	ZigBee	0.25 Mbps	11/18/26
	Peak Power Spectral Density	ZigBee	0.25 Mbps	11/18/26
	Peak Output Power	ZigBee	0.25 Mbps	11/12/18/25/26
	Band Edge	ZigBee	0.25 Mbps	11/18/26
	Spurious Emission	ZigBee	0.25 Mbps	11/18/26

Note 1:

☒ Mobile Device

☐ Portable Device, and 3 axis were assessed. The worst scenario for Radiated Spurious Emission as follow:

- ☐ Lie
- ☐ Side
- ☐ Stand

3.5. Tested Supporting System List

3.5.1. Support Peripheral Unit


No.	Product	Brand	Model No.	Serial No.	FCC ID
1.	Notebook PC	acer	MS2362	N/A	PPD-AAR5B225
2.	Test Jig	N/A	N/A	N/A	N/A
3.	Power Socket	N/A	N/A	N/A	N/A

3.5.2. Cable Lists


No.	Cable Description Of The Above Support Units
1.	LAN Cable: Shielded, Detachable, 1.0m Adapter: Chicony, M/N CPA09-A065N1, DC Cord: Shielded, Undetachable, 1.8m, Bonded a ferrite core AC Power Cord: Unshielded, Detachable, 1.8m
2.	BUS Cable: Unshielded, Detachable, 0.1m USB Cable: Shielded, Detachable, 1.8m
3.	Power Cord: Unshielded, Detachable, 1.8m

3.6. Setup Configuration

3.6.1. EUT Configuration for Power Line and Radiated Emission



3.6.2. EUT Configuration for Conducted Test Items



3.7. Operating Condition of EUT

Test program “ember.desktop” is used for enabling EUT RF function under continues transmitting and choosing data rate/ channel. The EUT was transmit in a pulse transmission

3.8. Description of Test Facility

Test Firm Name	:	AUDIX Technology Corporation EMC Department No. 53-11, Dingfu, Linkou Dist., New Taipei City 244, Taiwan
Test Location & Facility	:	No. 8 Shielded Room No. 53-11, Dingfu, Linkou Dist., New Taipei City 244, Taiwan Semi-Anechoic Chamber No. 53-11, Dingfu, Linkou Dist., New Taipei City 244, Taiwan May 11, 2012 File on Federal Communication Commission Registration Number: 90993
NVLAP Lab. Code	:	200077-0
TAF Accreditation No	:	1724

3.9. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty
Conduction Test	150kHz~30MHz	± 3.5dB
Radiation Test (Distance: 3m)	30MHz~300MHz	± 3.64dB
	300MHz~1000MHz	± 4.07dB
	Above 1GHz	± 2.94dB

Remark : Uncertainty = $k_{uc}(y)$

Test Item	Uncertainty
6dB Bandwidth	± 0.05kHz
Maximum peak output power	± 0.33dB
Power spectral density	± 0.13dB
Conducted Emission Limitations	± 0.13dB

4. MEASUREMENT EQUIPMENT LIST

4.1. Conducted Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Test Receiver	R&S	ESR3	101774	2015. 02. 06	1 Year
2.	A.M.N.	R&S	ENV4200	100169	2015. 05. 08	1 Year
3.	L.I.S.N.	Kyoritsu	KNW-407	8-855-9	2014. 12. 26	1 Year
4.	Pulse Limiter	R&S	ESH3-Z2	100354	2015. 01. 17	1 Year

4.2. Radiated Emission Measurement

4.2.1. Frequency Range 30MHz~1000MHz

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A-526	MY53400071	2014. 09. 15	1 Year
2.	Test Receiver	R & S	ESCS30	100338	2014. 06. 24	1 Year
3.	Amplifier	HP	8447D	2944A06305	2015. 02. 12	1 Year
4.	Bilog Antenna	TESEQ	CBL6112D	33821	2014. 08. 02	1 Year

4.2.2. Frequency Range 30MHz~1000MHz

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A-526	MY53400071	2014. 09. 15	1 Year
2.	Test Receiver	R & S	ESCS30	100338	2014. 06. 24	1 Year
3.	Amplifier	Agilent	8449B	3008A02676	2015. 02. 11	1 Year
4.	2.4GHz Notch Filter	K&L	7NSL10-244 1.5E130.5-0 0	1	2014. 06. 12	1 Year
5.	3G High Pass Filter	Microwave Circuits	H3G018G1	484796	2014. 06. 12	1 Year
6.	Double-Ridged Waveguide Horn	ETS-Lindgren	3115	00114104	2015. 04. 07	1 Year
7.	Horn Antenna	EMCO	3116	2653	2014. 10. 10	1 Year


4.3. RF Conducted Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A-544	US51350140	2014. 07. 24	1 Year
2.	Power Meter	Anritsu	ML2495A	1145008	2014. 10. 17	1 Year
3.	Power Sensor	Anritsu	MA2411B	1126096	2014. 10. 17	1 Year

5. CONDUCTED EMISSION MEASUREMENT

5.1. Block Diagram of Test Setup

Shielded Room Setup Diagram



5.2. Power Line Conducted Emission Limit

Frequency	Conducted Limit	
	Quasi-Peak Level	Average Level
150kHz ~ 500kHz	66 ~ 56 dB μ V	56 ~ 46 dB μ V
500kHz ~ 5MHz	56 dB μ V	46 dB μ V
5MHz ~ 30MHz	60 dB μ V	50 dB μ V

Remark 1.: If the average limit is met when using a Quasi-Peak detector, the measurement using the average detector is not required.

2.: The lower limit applies to the band edges.


5.3. Test Procedure

- 5.3.1. To set up the EUT as indicated in ANSI C 63.4. The EUT was placed on the table which has 80 cm height to the ground and 40 cm distance to the conducting wall.
- 5.3.2. Power supplier of the EUT was connected to the AC mains through an Artificial Mains Network (A.M.N.).
- 5.3.3. The AC power supplies to all peripheral devices must be provided through line impedance stabilization network (L.I.S.N.)
- 5.3.4. Checking frequency range from 150 kHz to 30 MHz and record the emission which does not have 20 dB below limit.

5.4. Conducted Emission Measurement Results

PASSED.


Test Date	2015/06/02	Temp./Hum.	26°C/56%
Test Voltage	DC 5V (via power adaptor)		



Site no. : No.8 Shielded Room Data no. : 2
Condition : ENV4200 100169 Phase : NEUTRAL
Limit : FCC PART 15C
Env. / Ins. : 26°C / 56% ESR3 (1774) Engineer : Tim
EUT : 9GW97185D3
Power Rating : DC 5V (via power adaptor)
Test Mode : Operating

	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.377	11.02	0.03	9.87	20.28	41.20	48.34	7.14	Average
2	0.377	11.02	0.03	9.87	31.67	52.59	58.34	5.75	QP
3	0.466	10.99	0.03	9.88	17.21	38.11	46.58	8.47	Average
4	0.466	10.99	0.03	9.88	25.34	46.24	56.58	10.34	QP
5	0.720	10.97	0.04	9.88	10.26	31.15	46.00	14.85	Average
6	0.720	10.97	0.04	9.88	23.65	44.54	56.00	11.46	QP
7	1.442	10.98	0.05	9.87	14.26	35.16	46.00	10.84	Average
8	1.442	10.98	0.05	9.87	24.14	45.04	56.00	10.96	QP
9	7.379	11.77	0.12	9.90	14.04	35.83	50.00	14.17	Average
10	7.379	11.77	0.12	9.90	23.46	45.25	60.00	14.75	QP
11	17.450	13.81	0.19	9.93	7.47	31.40	50.00	18.60	Average
12	17.450	13.81	0.19	9.93	16.23	40.16	60.00	19.84	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.



Site no. : No.8 Shielded Room Data no. : 1
Condition : ENV4200 100169 Phase : LINE
Limit : FCC PART 15C
Env. / Ins. : 26°C / 56% ESR3 (1774) Engineer : Tim
EUT : 96W97185D3
Power Rating : DC 5V (via power adaptor)
Test Mode : Operating

	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.174	10.72	0.03	9.87	15.88	36.50	54.77	18.27	Average
2	0.174	10.72	0.03	9.87	24.11	44.73	64.77	20.04	QP
3	0.363	10.57	0.03	9.87	15.45	35.92	48.65	12.73	Average
4	0.363	10.57	0.03	9.87	23.73	44.20	58.65	14.45	QP
5	0.709	10.54	0.04	9.88	12.07	32.53	46.00	13.47	Average
6	0.709	10.54	0.04	9.88	19.34	39.80	56.00	16.20	QP
7	1.480	10.56	0.05	9.87	13.57	34.05	46.00	11.95	Average
8	1.480	10.56	0.05	9.87	20.50	40.98	56.00	15.02	QP
9	3.055	10.62	0.07	9.88	10.33	30.90	46.00	15.10	Average
10	3.055	10.62	0.07	9.88	16.60	37.17	56.00	18.83	QP
11	7.348	11.03	0.12	9.90	15.93	36.98	50.00	13.02	Average
12	7.348	11.03	0.12	9.90	23.15	44.20	60.00	15.80	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.


6. RADIATED EMISSION MEASUREMENT

6.1. Block Diagram of Test Setup


6.1.1. Block Diagram of EUT

Indicated as section 3.6

6.1.2. Setup Diagram for 30-1000 MHz



6.1.3. Semi-Anechoic Chamber (3m) Setup Diagram for above 1GHz



6.2. Radiated Emission Limits

In any 100kHz bandwidth outside the frequency band, the radio frequency power produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205, must also comply with the radiated emission limits specified as below.

Frequency (MHz)	Distance (m)	Field Strengths Limits	
		$\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
Above 960	3	500	54.0
Above 1000	3	74.0 $\text{dB}\mu\text{V/m}$ (Peak) 54.0 $\text{dB}\mu\text{V/m}$ (Average)	

Remark : (1) $\text{dB}\mu\text{V/m} = 20 \log (\mu\text{V/m})$

- (2) The tighter limit applies to the edge between two frequency bands.
- (3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- (4) Fundamental and emission fall within operation band are exempted from this section.
- (5) Pursuant to ANSI 63.4: 8.3.2.2, if the maximized peak measured value complies with the average limit, then it is unnecessary to perform an average measurement.

6.3. Test Procedure

The EUT setup on the turn table which has 0.8 m height to the ground. The turn table rotated 360 degrees and antenna varied from 1 m to 4 m to find the maximum emission level. Both horizontal and vertical polarization are required. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4-2009 regulation.

Frequency below 1 GHz:

Spectrum Analyzer is used for pre-testing with following setting:

- (1) RBW = 120KHz
- (2) VBW $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.
- (7) When peak-detected value is lower than limit that the measurement using the Q.P. detector is not required. Otherwise using Q.P. for finally measurement.

Frequency above 1GHz to 10th harmonic:

Peak Detector:

- (1) RBW = 1MHz
- (2) VBW $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.
- (7) When peak-detected value is lower than limit that the measurement using the average detector is not required. Otherwise using average for finally measurement.

Average Measurement:

☒ **Option 1:**

- (1) RBW = 1 MHz
- (2) VBW = 1/T
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.

☐ **Option 2:**

Average Emission Level = Peak Emission Level + D.C.C.F.

6.4. Measurement Result Explanation

☒ Peak Emission Level = Antenna Factor + Cable Loss + Meter Reading

☒ Average Emission Level = Antenna Factor + Cable Loss + Meter Reading

☐ Average Emission Level = Peak Emission Level + DCCF

Duty Cycle Correction Factor (DCCF) = $20\log(TX_{on}/TX_{on+off})$ presented in section 3.4

6.5. Test Results

PASSED.

Test Date	2015/05/29~06/10	Temp./Hum.	20~24°C/46%
Test Voltage	DC 5V (via power adaptor)		

6.5.1. Emissions within Restricted Frequency Bands

6.5.1.1. Frequency Below 1 GHz

Mode	ZigBee	Frequency	TX 2440MHz
------	--------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
275.41	12.78	4.50	24.95	42.23	46.00	3.77	Peak
324.88	13.78	4.93	24.12	42.83	46.00	3.17	Peak
499.48	16.95	6.44	18.79	42.18	46.00	3.82	Peak
990.30	21.04	8.05	20.05	49.14	54.00	4.86	Peak


Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
40.67	12.98	2.52	20.84	36.34	40.00	3.66	Peak
125.06	12.01	3.41	23.82	39.24	43.50	4.26	Peak
299.66	13.12	4.65	23.83	41.60	46.00	4.40	Peak
450.01	16.29	6.07	19.56	41.92	46.00	4.08	Peak
831.22	20.20	7.28	14.57	42.05	46.00	3.95	Peak

6.5.1.2. Frequency Above 1 GHz to 10th harmonics


Band Edge:

Mode	ZigBee	Frequency	TX 2405MHz
------	--------	-----------	------------



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2370.36	32.13	6.05	27.60	65.78	74.00	8.22	Peak
2390.00	32.16	6.08	25.65	63.89	74.00	10.11	Peak
2404.32	32.18	6.10	79.95	118.23	---	---	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.80	32.16	6.08	12.71	50.95	54.00	3.05	Average
2390.00	32.16	6.08	12.58	50.82	54.00	3.18	Average
2405.16	32.18	6.10	77.42	115.70	---	---	Average

Mode	ZigBee	Frequency	TX 2405MHz
------	--------	-----------	------------



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2362.20	32.11	6.04	18.02	56.17	74.00	17.83	Peak
2390.00	32.16	6.08	14.71	52.95	74.00	21.05	Peak
2404.56	32.18	6.10	69.13	107.41	---	---	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.80	32.16	6.08	4.17	42.41	54.00	11.59	Average
2390.00	32.16	6.08	3.92	42.16	54.00	11.84	Average
2404.92	32.18	6.10	66.82	105.10	---	---	Average

Mode	ZigBee	Frequency	TX 2410MHz
------	--------	-----------	------------



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2378.40	32.13	6.06	28.87	67.06	74.00	6.94	Peak
2390.00	32.16	6.08	25.35	63.59	74.00	10.41	Peak
2409.60	32.18	6.10	79.93	118.21	---	---	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.80	32.16	6.08	12.19	50.43	54.00	3.57	Average
2390.00	32.16	6.08	12.50	50.74	54.00	3.26	Average
2410.20	32.18	6.10	77.59	115.87	---	---	Average

Mode	ZigBee	Frequency	TX 2410MHz
------	--------	-----------	------------



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2380.80	32.13	6.07	21.57	59.77	74.00	14.23	Peak
2390.00	32.16	6.08	20.31	58.55	74.00	15.45	Peak
2409.36	32.18	6.10	69.52	107.80	---	---	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.56	32.16	6.08	8.96	47.20	54.00	6.80	Average
2390.00	32.16	6.08	8.97	47.21	54.00	6.79	Average
2410.20	32.18	6.10	67.11	105.39	---	---	Average

Mode	ZigBee	Frequency	TX 2475MHz
------	--------	-----------	------------



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2474.48	32.28	6.17	64.64	103.09	---	---	Peak
2483.52	32.28	6.19	23.03	61.50	74.00	12.50	Peak
2484.80	32.28	6.19	23.60	62.07	74.00	11.93	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2475.04	32.28	6.18	62.53	100.99	---	---	Average
2483.52	32.28	6.19	12.10	50.57	54.00	3.43	Average
2483.60	32.28	6.19	12.06	50.53	54.00	3.47	Average

Mode	ZigBee	Frequency	TX 2475MHz
------	--------	-----------	------------



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2474.48	32.28	6.17	53.37	91.82	---	---	Peak
2483.52	32.28	6.19	12.86	51.33	74.00	22.67	Peak
2483.60	32.28	6.19	13.54	52.01	74.00	21.99	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2475.04	32.28	6.18	51.30	89.76	---	---	Average
2483.52	32.28	6.19	1.83	40.30	54.00	13.70	Average
2483.60	32.28	6.19	1.79	40.26	54.00	13.74	Average

Mode	ZigBee	Frequency	TX 2480MHz
------	--------	-----------	------------



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2479.44	32.28	6.18	54.71	93.17	---	---	Peak
2483.50	32.28	6.19	29.19	67.66	74.00	6.34	Peak
2483.60	32.28	6.19	29.56	68.03	74.00	5.97	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2480.08	32.28	6.18	52.43	90.89	---	---	Average
2483.50	32.28	6.19	13.23	51.70	54.00	2.30	Average
2483.60	32.28	6.19	12.74	51.21	54.00	2.79	Average

Mode	ZigBee	Frequency	TX 2480MHz
------	--------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2479.44	32.28	6.18	43.13	81.59	---	---	Peak
2483.50	32.28	6.19	16.97	55.44	74.00	18.56	Peak
2483.68	32.28	6.19	17.39	55.86	74.00	18.14	Peak



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2480.00	32.28	6.18	40.79	79.25	---	---	Average
2483.50	32.28	6.19	2.60	41.07	54.00	12.93	Average
2483.60	32.28	6.19	2.09	40.56	54.00	13.44	Average

6.5.2. Emissions outside the frequency band:

The emissions (up to 25GHz) not reported for there is no emission be found.

Mode	ZigBee	Frequency	TX 2405MHz
------	--------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4810.00	34.22	8.87	15.07	58.16	74.00	15.84	Peak
4810.00	34.22	8.87	6.58	49.67	54.00	4.33	Average

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4810.00	34.22	8.87	15.99	59.08	74.00	14.92	Peak
4810.00	34.22	8.87	7.68	50.77	54.00	3.23	Average

Mode	ZigBee	Frequency	TX 2440MHz
------	--------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4879.00	34.25	9.14	20.90	64.29	74.00	9.71	Peak
4879.00	34.25	9.14	8.45	51.84	54.00	2.16	Average

Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4879.00	34.25	9.14	13.02	56.41	74.00	17.59	Peak
4879.00	34.25	9.14	5.32	48.71	54.00	5.29	Average

6.5.3. Emissions in Non-restricted Frequency Bands

Pursuant to KDB 558074 D01 v03r02 that emission levels below the 15.209 general radiated emissions limits is not required.

7. 6dB BANDWIDTH MEASUREMENT

7.1. Block Diagram of Test Setup



7.2. Specification Limits

The minimum 6dB bandwidth shall be at least 500kHz.

7.3. Test Procedure

Following measurement procedure is reference to KDB 558074 D01 DTS Meas Guidance v03r02:

■ Option 2

- (1) Set RBW = 100 kHz.
- (2) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Trace mode = max hold.
- (5) Sweep = auto couple.
- (6) Allow the trace to stabilize.
- (7) Setting channel bandwidth function x dB to -6 dB to record the final bandwidth.


7.4. Test Results

Test Date	2015/06/01	Temp./Hum.	24°C/34%
Cable Loss	0.5dB	Test Voltage	DC 5V (via power adaptor)

7.4.1. 6dB Bandwidth Result


Modulation Type	Centre Frequency (MHz)	6 dB Bandwidth (MHz)
ZigBee	2405	1.550
	2440	1.549
	2480	1.633

7.4.2. Measurement Plots



8. MAXIMUM PEAK OUTPUT POWER MEASUREMENT

8.1. Block Diagram of Test Setup



8.2. Specification Limits

The Limits of maximum Peak Output Power for digital modulation in 2400-2483.5MHz is : 1Watt. (30dBm)

8.3. Test Procedure

Following measurement procedure is reference to KDB 558074 D01 DTS Meas Guidance v03r02:

☐ **PKPM1 Peak power meter method:**

EUT is connected to power sensor and record the maximum output power.

☐ **Method AVGPM (Measurement using an RF average power meter):**

EUT is connected to power sensor and record the maximum average output power and duty cycle factor is added when duty cycle presented in section 3.5.1 is < 98%.

☒ **RBW ≥ DTS bandwidth**

- (1) Set span to at least 3 times the OBW
- (2) Set $RBW \geq OBW$
- (3) Set the video bandwidth (VBW) $\geq 3 \times RBW$.
- (4) Detector = Peak
- (5) Trace mode = max hold
- (6) Sweep = auto couple.
- (7) To find the peak amplitude level.

8.4. Test Results


Test Date	2015/05/29~2015/06/10	Temp./Hum.	20~25°C/46~50%
Cable Loss	1.1dB/2.06 dB	Test Voltage	DC 5V (via power adaptor)


8.4.1. Peak Output Power

Modulation Type	Centre Frequency (MHz)	Peak Output Power		Limit
		(dBm)	(W)	
ZigBee	2405	16.411	0.043762	< 30 dBm (1 W)
	2410	22.019	0.159184	
	2440	19.875	0.097163	
	2475	7.589	0.005740	
	2480	-1.782	0.000663	

Note: The results have been included cable loss.


8.4.2. Peak Measurement Plots





9. EMISSION LIMITATIONS MEASUREMENT

9.1. Block Diagram of Test Setup



9.2. Specification Limits

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (See Section 15.205(c)).

9.3. Test Procedure

■Reference Level


- (1) Set analyzer center frequency to DTS channel center frequency.
- (2) Set the span to 1.5 times the DTS bandwidth.
- (3) Set the RBW to: 100 kHz.
- (4) Set the VBW $\geq 3 \times$ RBW.
- (5) Detector = peak.
- (6) Sweep time = auto couple.
- (7) Trace mode = max hold.
- (8) Allow trace to fully stabilize to find the max PSD as reference level.

■Emission Level Measurement

- (1) Set analyzer center frequency to DTS channel center frequency.
- (2) Set the span to 1.5 times the DTS bandwidth.
- (3) Set the RBW to: 100 kHz.
- (4) Set the VBW $\geq 3 \times$ RBW.
- (5) Detector = peak.
- (6) Sweep time = auto couple.
- (7) Trace mode = max hold.
- (8) Allow trace to fully stabilize to find the max level.

9.4. Test Results


Test Date	2015/06/01	Temp./Hum.	24°C/34%
Mode	ZigBee	Frequency	TX 2405MHz
Cable Loss	0.5dB	Test Voltage	DC 5V (via power adaptor)



AUDIX Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303


Test Date	2015/06/01	Temp./Hum.	24°C/34%
Mode	ZigBee	Frequency	TX 2440MHz
Cable Loss	0.5dB	Test Voltage	DC 5V



AUDIX Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Test Date	2015/06/01	Temp./Hum.	24°C/34%
Mode	ZigBee	Frequency	TX 2480MHz
Cable Loss	0.5dB	Test Voltage	DC 5V




File Number: C1M1505271

Report Number: EM-F150298

This test report may be reproduced in full only. The document may only be updated by AUDIX Technology Corp. personnel Any changes will be noted in the Document History section of the report.

10. POWER SPECTRAL DENSITY

10.1. Block Diagram of Test Setup



10.2. Specification Limits

The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band.

10.3. Test Procedure

Following measurement procedure is reference to KDB 558074 D01 DTS Meas Guidance v03r02:

☐ Method PKPSD (peak PSD)


- (1) Set analyzer center frequency to DTS channel center frequency.
- (2) Set the span to 1.5 times the DTS bandwidth.
- (3) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- (4) Set the VBW $\geq 3 \times \text{RBW}$.
- (5) Detector = peak.
- (6) Sweep time = auto couple.
- (7) Trace mode = max hold.
- (8) Allow trace to fully stabilize.
- (9) Use the peak marker function to determine the maximum amplitude level.
- (10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

☒ Method AVGPSD-2

- (1) Using peak PSD procedure step 1 to step 4.
- (2) Detector = RMS detector
- (3) Sweep time = auto couple
- (4) Trace mode = trace averaging over a minimum of 100 traces
- (5) Use the peak marker function to determine the maximum amplitude level.
- (6) Duty cycle factor is added when duty cycle presented in section 3.5.1. < 98%.
- (7) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

10.4. Test Results

Test Date	2014/06/02	Temp./Hum.	24°C/35%
Cable Loss	4.61dB	Test Voltage	DC 5V (via power adaptor)



11.DEVIATION TO TEST SPECIFICATIONS

【NONE】