

Maximum Permissive Exposure

FCC ID: BEJ9SMB2B2B5C2

Product Name: Scheduling Switch

Model No: (1)9SMB2B2B5C2 (2)9SMB2B1B5C2

1. According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 Limits for Maximum Permissible Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

2. MPE Calculation

LG Electronics Inc. declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

RF Exposure Calculations:

$$S = (P * G) / (4 * \pi * r^2) \text{ or } r = \sqrt{(P * G) / (4 * \pi * S)}$$

Where :

Based on safety distance (r)=	20	cm		
Highest Power Output (P)=	8.250	dBm =	6.683	mW
Antenna Gain (G)=	0.072	dBi =	1.017	Numerical
MPE (S) = (P*G) / (4*π*r ²) =	= (6.683*1.017)/(4*π*20 ²)=		0.001352	mW/cm ²

Based on safety distance (r) **20cm**, the antenna gain (G) is **1.017 Numerical**, and the highest power output (P) is **6.683mW**, the power density (S) is **0.001352mW/cm²**.

Sincerely Yours,



Mr. Ben Cheng
Manager
AUDIX Technology Corporation