


ATTACHMENT D – TEST PLOT(S)

LGE FCC ID: BEJCN772C Packard Bell
1280 x 1024 64KHz./60Hz. LINE A


PCTEST Engineering Lab.



No.	Freq. [MHz]	Quasi-Pk [dBuV]	Limit [dBuV]	Margin [dB]	Average [dBuV]	Limit [dBuV]	Margin [dB]
1	1.737	42.25	56.00	-13.75	35.09	46.00	-10.91
2	3.865	39.79	56.00	-16.21	34.36	46.00	-11.64
3	4.190	40.48	56.00	-15.52	33.51	46.00	-12.49
4	4.835	42.03	56.00	-13.97	34.56	46.00	-11.44
5	6.836	44.99	60.00	-15.01	27.74	50.00	-22.26
6	4.963	42.92	56.00	-13.08	35.52	46.00	-10.48
7	6.707	44.55	60.00	-15.45	35.99	50.00	-14.01
8	2.193	41.96	56.00	-14.04	37.86	46.00	-8.14
9	2.513	41.55	56.00	-14.45	37.58	46.00	-8.42
10	2.063	40.74	56.00	-15.26	35.25	46.00	-10.75

LGE FCC ID: BEJCN772C Packard Bell
1280 x 1024 64KHz./60Hz. LINE B


PCTEST Engineering Lab.



No.	Freq. [MHz]	Quasi-Pk [dBuV]	Limit [dBuV]	Margin [dB]	Average [dBuV]	Limit [dBuV]	Margin [dB]
1	1.866	42.71	56.00	-13.29	38.13	46.00	-7.87
2	1.674	41.13	56.00	-14.87	35.85	46.00	-10.15
3	1.932	40.80	56.00	-15.20	35.94	46.00	-10.06
4	2.000	40.84	56.00	-15.16	35.29	46.00	-10.71
5	1.802	41.54	56.00	-14.46	35.12	46.00	-10.88
6	2.193	41.67	56.00	-14.33	36.61	46.00	-9.39
7	.771	41.27	56.00	-14.73	36.88	46.00	-9.12
8	1.739	41.08	56.00	-14.92	35.05	46.00	-10.95
9	2.515	40.87	56.00	-15.13	36.13	46.00	-9.87
10	2.901	39.79	56.00	-16.21	33.81	46.00	-12.19

LGE FCC ID: BEJCN772C Packard Bell
1024 x 768 69KHz./85Hz. LINE A


PCTEST Engineering Lab.



No.	Freq. [MHz]	Quasi-Pk [dBuV]	Limit [dBuV]	Margin [dB]	Average [dBuV]	Limit [dBuV]	Margin [dB]
1	4.848	43.55	56.00	-12.45	36.83	46.00	-9.17
2	4.779	43.31	56.00	-12.69	37.10	46.00	-8.90
3	1.798	42.93	56.00	-13.07	37.76	46.00	-8.24
4	4.364	41.72	56.00	-14.28	35.78	46.00	-10.22
5	4.571	42.71	56.00	-13.29	36.41	46.00	-9.59
6	.898	43.03	56.00	-12.97	37.35	46.00	-8.65
7	6.718	46.56	60.00	-13.44	38.22	50.00	-11.78
8	1.937	42.32	56.00	-13.68	36.63	46.00	-9.37
9	2.910	42.75	56.00	-13.25	38.53	46.00	-7.47
10	1.867	42.65	56.00	-13.35	39.43	46.00	-6.57

LGE FCC ID: BEJCN772C Packard Bell
1024 x 768 69KHz./85Hz. LINE B


PCTEST Engineering Lab.



No.	Freq. [MHz]	Quasi-Pk [dBuV]	Limit [dBuV]	Margin [dB]	Average [dBuV]	Limit [dBuV]	Margin [dB]
1	2.979	41.77	56.00	-14.23	38.02	46.00	-7.98
2	1.936	40.96	56.00	-15.04	35.18	46.00	-10.82
3	2.425	41.16	56.00	-14.84	34.13	46.00	-11.87
4	2.772	40.92	56.00	-15.08	36.37	46.00	-9.63
5	1.867	42.39	56.00	-13.61	38.52	46.00	-7.48
6	1.798	41.73	56.00	-14.27	35.63	46.00	-10.37
7	2.633	41.64	56.00	-14.36	36.36	46.00	-9.64
8	.759	41.54	56.00	-14.46	38.20	46.00	-7.80
9	.898	40.87	56.00	-15.13	35.26	46.00	-10.74
10	1.733	40.05	56.00	-15.95	33.56	46.00	-12.44

LGE FCC ID: BEJCN772C Packard Bell
800 x 600 54KHz./85Hz. LINE A


PCTEST Engineering Lab.



No.	Freq. [MHz]	Quasi-Pk [dBuV]	Limit [dBuV]	Margin [dB]	Average [dBuV]	Limit [dBuV]	Margin [dB]
1	4.000	41.09	56.00	-14.91	34.14	46.00	-11.86
2	4.865	41.87	56.00	-14.13	34.04	46.00	-11.96
3	.862	41.36	56.00	-14.64	37.29	46.00	-8.71
4	4.811	41.20	56.00	-14.80	33.92	46.00	-12.08
5	2.002	40.49	56.00	-15.51	37.24	46.00	-8.76
6	3.783	40.08	56.00	-15.92	33.68	46.00	-12.32
7	1.835	40.74	56.00	-15.26	35.31	46.00	-10.69
8	2.326	41.67	56.00	-14.33	37.40	46.00	-8.60
9	.754	40.63	56.00	-15.37	36.69	46.00	-9.31
10	1.889	39.45	56.00	-16.55	32.83	46.00	-13.17

LGE FCC ID: BEJCN772C Packard Bell
800 x 600 54KHz./85Hz. LINE B


PCTEST Engineering Lab.



No.	Freq. [MHz]	Quasi-Pk [dBuV]	Limit [dBuV]	Margin [dB]	Average [dBuV]	Limit [dBuV]	Margin [dB]
1	2.326	41.77	56.00	-14.23	36.06	46.00	-9.94
2	.754	40.52	56.00	-15.48	35.79	46.00	-10.21
3	.862	40.30	56.00	-15.70	34.72	46.00	-11.28
4	1.835	39.75	56.00	-16.25	34.39	46.00	-11.61
5	1.943	38.96	56.00	-17.04	33.93	46.00	-12.07
6	2.054	38.33	56.00	-17.67	34.72	46.00	-11.28
7	.813	38.46	56.00	-17.54	34.73	46.00	-11.27
8	1.241	38.24	56.00	-17.76	35.02	46.00	-10.98
9	1.781	38.69	56.00	-17.31	34.63	46.00	-11.37
10	1.349	38.13	56.00	-17.87	33.30	46.00	-12.70

LGE FCC ID: BEJCN772C Packard Bell
640 x 480 43KHz./85Hz. LINE A


PCTEST Engineering Lab.



No.	Freq. [MHz]	Quasi-Pk [dBuV]	Limit [dBuV]	Margin [dB]	Average [dBuV]	Limit [dBuV]	Margin [dB]
1	4.188	40.45	56.00	-15.55	34.93	46.00	-11.07
2	.826	40.19	56.00	-15.81	36.36	46.00	-9.64
3	1.306	37.31	56.00	-18.69	34.16	46.00	-11.84
4	2.401	37.70	56.00	-18.30	35.48	46.00	-10.52
5	1.263	37.77	56.00	-18.23	35.24	46.00	-10.76
6	1.960	37.77	56.00	-18.23	34.50	46.00	-11.50
7	1.437	39.10	56.00	-16.90	36.46	46.00	-9.54
8	.739	38.60	56.00	-17.40	34.13	46.00	-11.87
9	2.096	38.57	56.00	-17.43	35.78	46.00	-10.22
10	1.393	38.24	56.00	-17.76	35.08	46.00	-10.92

LGE FCC ID: BEJCN772C Packard Bell
640 x 480 43KHz./85Hz. LINE B

PCTEST Engineering Lab.



No.	Freq. [MHz]	Quasi-Pk [dBuV]	Limit [dBuV]	Margin [dB]	Average [dBuV]	Limit [dBuV]	Margin [dB]
1	2.357	37.99	56.00	-18.01	31.38	46.00	-14.62
2	1.742	38.52	56.00	-17.48	32.70	46.00	-13.30
3	1.917	39.18	56.00	-16.82	35.04	46.00	-10.96
4	1.873	39.35	56.00	-16.65	35.49	46.00	-10.51
5	.826	39.07	56.00	-16.93	33.83	46.00	-12.17
6	1.829	37.59	56.00	-18.41	32.38	46.00	-13.62
7	.783	38.32	56.00	-17.68	34.43	46.00	-11.57
8	1.960	36.71	56.00	-19.29	32.06	46.00	-13.94
9	3.970	36.81	56.00	-19.19	31.82	46.00	-14.18
10	1.786	37.03	56.00	-18.97	31.51	46.00	-14.49