

LG Electronics USA, Inc.

MPE ASSESSMENT REPORT

Report Type:

FCC Part §2.1091, §2.1093 and §1.1307(b) assessment report

Model:

MZBK1729#, SKSLV3100#

REPORT NUMBER:

231100516SHA-002

ISSUE DATE:

December 7, 2023

DOCUMENT CONTROL NUMBER:

TTRFFCCMPE-01_V1 © 2018 Intertek



TEST REPORT

Applicant: LG Electronics USA, Inc.
111 Sylvan Avenue North Building, Englewood Cliffs, New Jersey, United States

Manufacturing Site: LG Electronics Tianjin Appliances Co., Ltd.
No.9 Jinwei Road, Bei Chen Dist., Tianjin 300402, People's Republic of China

Product Name: Microwave oven

Type/Model: MZBK1729#, SKSLV3100#
("#" on model/type reference represents A to Z or blank, according to exterior design, color, cooking utensil or market)

FCC ID: BEJD1722NAF

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 18 (2018)
FCC/OET MP-5 (1986)
KDB447498 D01 General RF Exposure Guidance v06
FCC Part2.1093 FCC Part1.1307(b), 1.1310, 2.1091

PREPARED BY:



Project Engineer
Dylan Tang

REVIEWED BY:



Reviewer
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No.	Version	Description	Issued Date
231100516SHA-002	Rev. 01	Initial issue of report	December 7, 2023

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Microwave oven
Type/Model:	MZBK1729#, SKSLV3100# (#- Represent any alphanumeric code for color of Control panel/door panel.)
Brand Name:	LG
Description of EUT:	The EUT is a Microwave oven which have series models, and they are electric identical. The model SKSLV3100S were chosen to testing.
Rating:	AC 120V 60Hz Output: 975W
Frequency:	2450MHz
EUT type:	☒ Table top ☐ Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	November 15, 2023
Date of test:	November 15, 2023 ~ December 5, 2023

1.2 Technical Specification

Contains FCC ID: BEJ-LCW009

Frequency Band:	2400MHz ~ 2483.5MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n(HT20), IEEE 802.11n(HT40)
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n(HT20): OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n(HT40): OFDM (64-QAM, 16-QAM, QPSK, BPSK)
Operating Frequency:	2412MHz to 2462MHz for IEEE 802.11b/g/n(HT20) 2422MHz to 2452MHz for IEEE 802.11n(HT40)
Channel Number:	11 Channels for 802.11b, 802.11g, 802.11n(HT20) 7 Channels for 802.11n(HT40)
Channel Separation:	5 MHz
Antenna Information:	PCB antenna: 1.58dBi

TEST REPORT

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

2 Radiation Hazard Measurement

Test result: Pass

2.1 Limit

A maximum of 1.0mW/cm² is allowed in accordance with the applicable FCC standards. Hence, microwave leakage in the as-received condition with the oven door closed was below the maximum allowed.

2.2 Radiation Hazard (Health) Requirement

For ISM equipment operating on higher frequencies (above 900 MHz), in particular microwave ovens and medical diathermy equipment, radiation leakage should be measured in accordance with the current Bureau of Radiological Health standard, employing an electromagnetic radiation monitor. This test is made primarily to assure that personnel will not be exposed to radiation hazard in testing the equipment. Equipment submitted to the FCC which have radiation leakage apparently in excess of BRH limit will be reported to BRH for their evaluation. See FCC Bulletin OST 56, "Questions and Answers about Biological Effects and Potential Hazards of Radiofrequency Radiation".

2.3 Measurement Procedure

The EUT was set-up according to the FCC MP-5 and FCC Part 18 for Radiation Hazard Measurement. The measurement was using a microwave leakage meter to measure the Radiation leakage in the as-received condition with the oven door closed. A 1000ml water load in a beaker was located in the center of the oven and the Microwave Oven was set to maximum power. While the oven operating, the microwave meter will check the leakage and then record the maximum leakage.

2.4 MPE Assessment Limit

Mobile device exposure for standalone operations:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
Limits For General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=Frequency in MHz; *Plane-wave equivalent power density

A maximum of 1.0mW/cm² is allowed in accordance with the applicable FCC standards. Hence, microwave leakage in the as-received condition with the oven door closed was below the maximum allowed.

2.3 Test Results

For WIFI module :

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm²

P = Radiated transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Working Mode	Frequency band	Power		Antenna Gain		R	S	Limits
	(MHz)	dBm	mW	dBi	(Numeric)	(cm)	(mW/cm ²)	(mW/cm ²)
2.4G WIFI	2412-2462	20	100	1.58	1.44	20	0.028624	1

Note: 1 mW/cm² from 1.310 Table 1.

TEST REPORT

For microwave oven

There was no microwave leakage exceeding a power level of 0.15mW/cm² observed at any point 5cm or more from the external surface of the oven.

WIF module and microwave oven can simultaneous transmitting, so the maximum rate of MPE is,
 $0.15/1+0.028624/1=0.178624<1.0$.

*****END*****