

LG Electronics USA, Inc.

EMC TEST REPORT

Report Type:
FCC Part 18 EMC report

Model:
MZBZ1727#

REPORT NUMBER:
2507B1688SHA-001

ISSUE DATE:
September 8, 2025

DOCUMENT CONTROL NUMBER:
TTRF18_V1 © 2018 Intertek



TEST REPORT

Applicant: LG Electronics USA, Inc.
111 Sylvan Avenue North Building, Englewood Cliffs, New Jersey, United States

Manufacturing Site: LG Electronics Tianjin Appliances Co., Ltd.
No.9 Jinwei Road, Bei Chen Dist., Tianjin 300402, People's Republic of China

Product Name: Microwave oven

Type/Model: MZBZ1727#
(#- Represent any alphanumeric code for color of Control panel/door panel.)

FCC ID: BEJD1792NAD


SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 18 (2018): Industrial, Scientific, and Medical Equipment

FCC/OET MP-5 (1986): FCC methods of Measurements of Radio Noise Emissions From Industrial, Scientific, and Medical Equipment

PREPARED BY:



Project Engineer
Dylan Tang

REVIEWED BY:



Reviewer
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Content

REVISION HISTORY.....	4
MEASUREMENT RESULT SUMMARY	5
1 GENERAL INFORMATION	6
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST FACILITY	7
2 TEST SPECIFICATIONS.....	8
2.1 STANDARDS OR SPECIFICATION	8
2.2 MODE OF OPERATION DURING THE TEST	8
2.3 TEST SOFTWARE LIST	8
2.4 TEST PERIPHERALS LIST.....	8
2.5 TEST LOAD DESCRIPTION.....	8
2.6 TEST ENVIRONMENT CONDITION:.....	9
2.7 INSTRUMENT LIST	10
2.8 MEASUREMENT UNCERTAINTY.....	11
3 OPERATING FREQUENCY.....	12
3.1 LIMIT	12
3.2 MEASUREMENT PROCEDURE	12
3.3 TEST RESULTS	12
4 RF OUTPUT POWER MEASUREMENT	13
4.1 LIMIT	13
4.2 MEASUREMENT PROCEDURE	13
4.3 TEST RESULTS	13
5 RADIATION HAZARD MEASUREMENT	14
5.1 LIMIT	14
5.2 MEASUREMENT PROCEDURE	14
5.3 TEST RESULTS	14
6 RADIATED EMISSIONS	15
6.1 LIMIT	15
6.2 MEASUREMENT PROCEDURE	15
6.3 TEST CONFIGURATION	17
6.4 TEST RESULTS OF RADIATED EMISSIONS	19
7 CONDUCTED EMISSION	24
7.1 LIMIT	24
7.2 TEST CONFIGURATION	24
7.3 MEASUREMENT PROCEDURE	25
7.4 TEST RESULTS OF POWER LINE CONDUCTED EMISSION.....	26
APPENDIX I: PHOTOGRAPH OF TEST SETUP	28
APPENDIX II: PHOTOGRAPH OF EQUIPMENT UNDER TEST	28

Revision History

Report No.	Version	Description	Issued Date
2507B1688SHA-001	Rev. 01	Initial issue of report	September 8, 2025

Measurement result summary

TEST ITEM	FCC REFERENCE	RESULT
Conducted Emission (150 kHz to 30 MHz)	18.307(b)	Pass
Radiated Emission (9 kHz to 30 MHz)	18.305(b)	Pass
Radiated Emission (30 MHz to 1 GHz)	18.305(b)	Pass
Radiated Emission (1 GHz to 25 GHz)	18.305(b)	Pass
Operating Frequency	Clause 4.5	Pass
RF Output Power Measurement	Clause 4.3	Pass

Notes: 1: NA =Not Applicable

2. Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

TEST REPORT

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Microwave oven
Type/Model:	MZBZ1727# (#- Represent any alphanumeric code for color of Control panel/door panel.)
Brand Name:	LG
Description of EUT:	The EUT is Microwave oven incorporated certified wireless module (FCC ID: BEJ-LCWB008), that has series models, and all the electrical and mechanical characteristics are the same as basic models except color of Control panel and door panel. The model MZB1727X was chosen to testing.
Rating:	AC 120V 60Hz Output: 975W
Frequency:	2450MHz
EUT type:	☒ Table top ☐ Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	June 30, 2025
Date of test:	June 30, 2025 ~ August 20, 2025

1.2 Description of Test Facility

Name:	Intertek Testing Services (Shanghai FTZ) Co., Ltd.
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 18 (2018)
FCC/OET MP-5 (1986)

2.2 Mode of operation during the test

Within this test report, EUT was tested under all available operation modes and tested under its rating voltage and frequency. Other voltage and frequency are specified if used.

Worst test mode: Working mode with full power.

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No.	Name	Band and Model	Description
1	Beaker	NA	1000/700/300mL

2.5 Test Load Description

Load for power output measurement, frequency measurement, radiation hazard test: 1000 milliliters of water in the beaker located in the center of the oven;

Load for measurement of radiation on second and third harmonic: Two loads, one of 700 and the other of 300 milliliters, of water are used. Each load is tested both with the beaker located in the center of the oven and with it in the right front corner.

Load for all other measurements: 700 milliliters of water, with the beaker located in the center of the oven.

2.6 Test environment condition:

Test items	Temperature	Humidity
Radiated Emissions	22°C	55% RH
Conducted Emission	21°C	52% RH

2.7 Instrument list

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESR7	EC 6194	2026-02-17
☒	A.M.N.	R&S	ESH2-Z5	EC 3119	2026-07-23
☐	A.M.N.	R&S	ENV4200	EC 3558	2025-12-06
☒	Attenuator	Hua Xiang	Ts5-10db-6g	EC 6194-1	2025-12-06
☒	Shielded room	Zhongyu	-	EC 2838	2026-01-09
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESIB 26	EC 3045	2026-08-18
☒	Test Receiver	R&S	ESR	EC6501	2025-09-10
☒	Bilog Antenna	TESEQ	CBL 6112B	EC 6411	2025-09-11
☒	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2026-08-09
☒	Horn antenna	Tonscend	bha9120d	EC 6432-2	2026-04-10
☒	Pre-amplifier	Tonscend	tap01018050	EC 6432-1	2025-12-03
☐	Horn antenna	ETS	3117	EC 4792-1	2025-09-13
☒	Horn antenna	ETS	3116C	EC 5955	2026-08-14
☒	Semi-anechoic chamber	Albatross project	-	EC 3048	2026-07-11
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Therom-Hygrograph	Testo	175h1	EC 6640	2025-08-29
☒	Pressure meter	YM3	Shanghai Mengde	EC 3320	2025-08-16

2.8 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Radiated Emissions in restricted frequency bands below 1GHz	$\pm 4.90\text{dB}$
Radiated Emissions in restricted frequency bands above 1GHz	$\pm 5.02\text{dB}$
Power line conducted emission	$\pm 3.19\text{dB}$

3 Operating Frequency

Test result: Pass

3.1 Limit

ISM equipment may be operated on any frequency above 9 kHz. And the frequency band 2400-2500MHz is allocated for use by ISM equipment. (§18.301)

ISM frequency	Tolerance
6.78 MHz	±15.0 kHz
13.56 MHz	±7.0 kHz
27.12 MHz	±163.0 kHz
40.68 MHz	±20.0 kHz
915 MHz	±13.0 MHz
2,450 MHz	±50.0 MHz
5,800 MHz	±75.0 MHz
24,125 MHz	±125.0 MHz
61.25 GHz	±250.0 MHz
122.50 GHz	±500.0 MHz
245.00 GHz	±1.0 GHz

3.2 Measurement Procedure

a) Frequency for Normal Voltage

The operating frequency was measured using a spectrum analyzer. Starting with the EUT at room temperature, a 1000mL water load was placed in the center of the oven and the oven was operated at maximum output power. The fundamental operating frequency was monitored until the water load was reduced to 20 percent of the original load.

b) Frequency for Line Voltage

The EUT was operated / warmed by at least 10 minutes of use with a 1000 mL water load at room temperature at the beginning of the test. Then the operating frequency was monitored as the input voltage was varied between 80 and 125 percent of the nominal rating.

3.3 Test Results

Item	START Frequency (MHz)	STOP Frequency (MHz)
Frequency for Normal Voltage	2401.70	2479.86
Frequency for Line Voltage	2401.65	2473.45

4 RF Output Power Measurement

Test result: Pass

4.1 Limit

NA

4.2 Measurement Procedure

The EUT in microwave mode with full power.

Formula:

$$P = \frac{4,187 \cdot m_w(T_2 - T_1) + 0,55 \cdot m_c(T_2 - T_0)}{t}$$

NOTE:

P is the microwave power output (W)

mw is the mass of the water (ml)

mc is the mass of the container (g)

T0 is the ambient temperature (°C)

T₁ is the initial temperature of the water (°C)

T₂ is the final temperature of the water (°C)

t is the heating time (s), excluding the magnetron filament heating-up time (s).

4.3 Test Results

Quantity of Water [ml]	Mass of the container [g]	Ambient temperature [°C]	Initial temperature [°C]	Final temperature [°C]	Heating time [s]	Power output [W]
1 000	450	21.6	24.9	42.5	120	657.20

5 Radiation Hazard Measurement

Test result: Pass

5.1 Limit

A maximum of $1.0\text{mW}/\text{cm}^2$ is allowed in accordance with the applicable FCC standards. Hence, microwave leakage in the as-received condition with the oven door closed was below the maximum allowed.

5.2 Measurement Procedure

The EUT was set-up according to the FCC MP-5 and FCC Part 18 for Radiation Hazard Measurement. The measurement was using a microwave leakage meter to measure the Radiation leakage in the as-received condition with the oven door closed. A 1000ml water load in a beaker was located in the center of the oven and the Microwave Oven was set to maximum power. While the oven operating, the microwave meter will check the leakage and then record the maximum leakage.

5.3 Test Results

There was no microwave leakage exceeding a power level of $0.32\text{mW}/\text{cm}^2$ observed at any point 5cm or more from the external surface of the oven.

6 Radiated Emissions

Test result: Pass

6.1 Limit

- (a) ISM equipment operation on a frequency specified in §18.301 is permitted unlimited radiated energy in the band specified for that frequency.
(b) The field strength levels of emissions which lie outside the bands specified in §18.301, unless otherwise indicated, shall not exceed the following:

Equipment	Operating frequency	RF Power generated by equipment (watts)	Field strength limit (uV/m)	Distance (meters)
Any type unless otherwise specified (miscellaneous)	Any ISM frequency	Below 500	25	300
		500 or more	$25 \times \text{SQRT}(\text{power}/500)$	300

RF Power = 657.20W according to clause 4.3

Limit = $20\lg(25 \times \text{SQRT}(\text{power}/500)) + 20\lg(300/3) = 29.15 + 40 = 69.15\text{dBuV/m}$ @ 3m distance.

6.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on the top of a rotating table 1 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

TEST REPORT**For Radiated emission above 30MHz:**


- a) The EUT was placed on the top of a rotating table 1.0 meters above the ground at 3-meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or $3 \times \text{RBW}$ (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported

6.3 Test Configuration


For Radiated emission below 30MHz:



For Radiated emission 30MHz to 1GHz:





For Radiated emission above 1GHz:



6.4 Test Results of Radiated Emissions

Test plots of 9KHz ~ 30MHz:



TEST REPORT


Test data of 9KHz ~ 30MHz:

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
X	0.009987	57.2	69.15	11.95	AV
X	0.013230	48.1	69.15	21.05	AV
X	0.044532	46.4	69.15	22.75	AV
X	0.508200	58.4	69.15	10.75	AV
X	0.836550	46.6	69.15	22.55	AV
X	4.866	34.3	69.15	34.85	AV
Y	0.009987	62.5	69.15	6.65	AV
Y	0.017883	51.6	69.15	17.55	AV
Y	0.448500	57.8	69.15	11.35	AV
Y	0.866400	47.2	69.15	21.95	AV
Y	4.896	43.0	69.15	26.15	AV
Y	9.881	36.6	69.15	32.55	AV


TEST REPORT

Test plots of 30MHz ~ 1GHz:

Horizontal



Vertical



TEST REPORT

Test data of 30MHz ~ 1GHz:

Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Limits (dBuV/m)	Margin (dBuV/m)	Detector
Horizontal	64.435	18.6	69.15	50.55	AV
	112.935	32.2	69.15	36.95	AV
	184.424	27.9	69.15	41.25	AV
	327.693	24.4	69.15	44.75	AV
	460.292	28.9	69.15	40.25	AV
	970.512	34.2	69.15	34.95	AV
Vertical	61.137	35.4	69.15	33.75	AV
	98.288	42.3	69.15	26.85	AV
	132.044	30.6	69.15	38.55	AV
	170.844	27.4	69.15	41.75	AV
	456.703	33.1	69.15	36.05	AV
	970.415	41.1	69.15	28.05	AV

TEST REPORT

Test data of 1GHz ~ 25GHz:

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	1204	32.82	69.15	36.33	AV
H	4918	53.60	69.15	15.55	AV
H	7269	66.17	69.15	2.98	AV
H	9892	47.95	69.15	21.20	AV
H	12345	56.01	69.15	13.14	AV
H	14661	46.99	69.15	22.16	AV
V	1204	42.64	69.15	26.51	AV
V	4918	55.42	69.15	13.73	AV
V	7337	60.50	69.15	8.65	AV
V	9892	48.60	69.15	20.55	AV
V	12174	60.92	69.15	8.23	AV
V	14798	42.90	69.15	26.25	AV
H	19815	61.10	69.15	8.05	AV
H	20312	62.20	69.15	6.95	AV
H	22306	64.50	69.15	4.65	AV
V	19786	59.60	69.15	9.55	AV
V	20221	60.90	69.15	8.25	AV
V	22254	63.10	69.15	6.05	AV

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.

2. Corrected Reading = Original Receiver Reading + Correct Factor

3. Margin = Limit - Corrected Reading

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
Limit = 40.00dBuV/m.
Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;
Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;
Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

7 Conducted Emission


Test result: Pass

7.1 Limit

Frequency range (MHz)	Limits dB(μV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 ~ 56 *	56 ~ 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

Note: 1. * Means the limit decreasing linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz
 2. If the limit for the measurement with the average detector is met when using a receiver with a quasi-peak detector, the equipment under test shall be deemed to meet both limits and the measurement using the receiver with an average detector need not be carried out.

7.2 Test Configuration



7.3 Measurement Procedure



Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

7.4 Test Results of Power line conducted emission

Test Curve:



TEST REPORT

Test Data:

No.	Frequency	Limit dBuV	Level dBuV	Margin dB	Reading dBuV	Factor dB	Detector	Phase
1	163.500kHz	65.28	41.62	23.66	31.42	10.20	QP	L1
2	190.500kHz	64.01	44.03	19.98	33.83	10.20	QP	L1
3	213.000kHz	63.09	50.24	12.85	40.04	10.20	QP	L1
4	249.000kHz	61.79	39.73	22.06	29.53	10.20	QP	L1
5	294.000kHz	60.41	33.96	26.45	23.76	10.20	QP	L1
6	343.500kHz	59.12	28.73	30.39	18.53	10.20	QP	L1
7	1.932MHz	56.00	25.85	30.15	15.45	10.40	QP	L1
8	26.115MHz	60.00	19.67	40.33	7.77	11.90	QP	L1
9	150.000kHz	66.00	44.15	21.85	34.05	10.10	QP	N
10	172.500kHz	64.84	45.21	19.63	35.11	10.10	QP	N
11	213.000kHz	63.09	51.01	12.08	40.91	10.10	QP	N
12	303.000kHz	60.16	30.71	29.45	20.61	10.10	QP	N
13	384.000kHz	58.19	25.68	32.51	15.48	10.20	QP	N
14	424.500kHz	57.36	19.59	37.77	9.39	10.20	QP	N
15	1.946MHz	56.00	19.09	36.91	8.59	10.50	QP	N
16	10.617MHz	60.00	21.87	38.13	11.07	10.80	QP	N
17	199.500kHz	53.63	36.41	17.22	26.21	10.20	AV	L1
18	226.500kHz	52.58	39.82	12.76	29.62	10.20	AV	L1
19	271.500kHz	51.07	27.27	23.80	17.07	10.20	AV	L1
20	316.500kHz	49.80	21.44	28.36	11.24	10.20	AV	L1
21	10.716MHz	50.00	20.83	29.17	10.03	10.80	AV	L1
22	12.453MHz	50.00	20.93	29.07	9.93	11.00	AV	L1
23	181.500kHz	54.42	36.20	18.22	26.10	10.10	AV	N
24	213.000kHz	53.09	41.32	11.77	31.22	10.10	AV	N
25	244.500kHz	51.94	31.58	20.36	21.48	10.10	AV	N
26	325.500kHz	49.57	19.49	30.08	9.39	10.10	AV	N
27	10.716MHz	50.00	21.69	28.31	10.89	10.80	AV	N
28	12.350MHz	50.00	21.86	28.14	10.86	11.00	AV	N

Remark: 1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Corrected Reading = Original Receiver Reading + Correct Factor

3. Margin = Limit - Corrected Reading

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

5. The emissions of number 6, 13, 19 and 26 are the product's RF signal.

Appendix I: Photograph of test setup

Refer to Test set up photos.

Appendix II: Photograph of equipment under test

Refer to EUT External photos and Internal photos.

***** END *****