

MPE Calculation : WLAN(2.4GHz)

Frequency range :	2412.00 MHz ~ 2462.00 MHz
Max Target power :	15.50 dBm (802.11b)
Measured Conducted power :	14.87 dBm (802.11b)
Maximum antenna gain(PK) :	2.18 dBi
Maximum EIRP :	17.68 dBm(58.614)mW

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE calculation for this exposure is shown below.

▪ Calculation of power density at the specific separation

▪ $S = \text{EIRP} / (4 R^2 \pi)$ $= \frac{58.614}{(4 \times 20^2 \times \pi)}$ $= \frac{0.01166}{\text{mW/cm}^2}$	- Note S = Maximum power density(mW/cm²) EIRP = Equivalent Isotropic Radiated Power(mW) R = Distance to the center of the radiation of the antenna(20cm)
--	--

▪ Requirement = **1** mW/cm²

(FCC Part 1.1310 Table 1 Limits for maximum permissible exposure(MPE))

Conclusion : **The exposure condition of this device is compliant with FCC rules.**

MPE Calculation : WLAN(5GHz)

Frequency range :	5745.00 MHz ~ 5825.00 MHz
Max Target power :	16.50 dBm (802.11n HT20)
Measured Conducted power :	15.62 dBm (802.11n HT20)
Maximum antenna gain(PK) :	2.36 dBi
Maximum EIRP :	18.86 dBm(76.913)mW

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE calculation for this exposure is shown below.

▪ Calculation of power density at the specific separation

▪ $S = \text{EIRP} / (4 R^2 \pi)$ $= \frac{76.913}{(4 \times 20^2 \times \pi)}$ $= \frac{0.01530}{\text{mW/cm}^2}$	- Note S = Maximum power density(mW/cm²) EIRP = Equivalent Isotropic Radiated Power(mW) R = Distance to the center of the radiation of the antenna(20cm)
--	---

▪ Requirement = **1** mW/cm²

(FCC Part 1.1310 Table 1 Limits for maximum permissible exposure(MPE))

Conclusion : The exposure condition of this device is compliant with FCC rules.

MPE Calculation : BT(2.4GHz)

Frequency range :	2402.00 MHz ~ 2480.00 MHz
Max Target power :	5.50 dBm (1Mbps)
Measured Conducted power :	4.77 dBm (1Mbps)
Maximum antenna gain(PK) :	-0.22 dBi
Maximum EIRP :	5.28 dBm(3.373)mW

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE calculation for this exposure is shown below.

▪ Calculation of power density at the specific separation

▪ $S = \text{EIRP} / (4 R^2 \pi)$ $= \frac{3.373}{(4 \times 20^2 \times \pi)}$ $= \frac{0.00067}{\text{mW/cm}^2}$	- Note S = Maximum power density(mW/cm²) EIRP = Equivalent Isotropic Radiated Power(mW) R = Distance to the center of the radiation of the antenna(20cm)
---	---

▪ Requirement = 1 mW/cm²

(FCC Part 1.1310 Table 1 Limits for maximum permissible exposure(MPE))

Conclusion : The exposure condition of this device is compliant with FCC rules.

RF Exposure Compliance for simultaneous operations

▪ Configurations for simultaneous operations

- **Configuration 1:** WLAN 2.4GHz 802.11b/g/n + Bluetooth 2.4GHz
- **Configuration 2:** WLAN 5GHz 802.11a/n/ac + Bluetooth 2.4GHz
- **Configuration 3:** N/A

Note: Above configuration was declared from applicant.

▪ Configurations for simultaneous operations

RF function	WLAN		BT		N/A		Σ of MPE ratios
Band	2.4GHz	5GHz	2.4GHz	N/A	N/A	N/A	
Power Density (mW/cm ²)	0.01166	0.01530	0.00067				
Requirement (mW/cm ²)	1.000	1.000	1.000				
MPE ratio (Power Density/Requirement)	0.012	0.015	0.001				
Configuration 1 (MPE ratio)	0.012		0.001				0.013
Configuration 2 (MPE ratio)		0.015	0.001				0.016
Configuration 3 (MPE ratio)							

Note: The maximum power density in each RF function was used for above table.

- Requirement = **Σ of MPE ratios ≤ 1**

Conclusion : **The exposure condition of this device is compliant with FCC rules.**