

FIGURE 1
LCD MONITOR (M/N: E2342TA)
GENERAL APPEARANCE (FRONT VIEW)



FIGURE 2
LCD MONITOR (M/N: E2342TA)
GENERAL APPEARANCE (BACK VIEW)



FIGURE 3
LCD MONITOR (M/N: E2342TA)
PORTS



FIGURE 4
LCD MONITOR (M/N: E2342TA)
D-SUB CABLE



FIGURE 5
LCD MONITOR (M/N: E2342TA)
DVI CABLE



FIGURE 6
LCD MONITOR (M/N: E2342TA)
ADAPTER #1 (GENERAL APPEARANCE)



FIGURE 7
LCD MONITOR (M/N: E2342TA)
ADAPTER #1 (GENERAL APPEARANCE – AC PORT)



FIGURE 8
LCD MONITOR (M/N: E2342TA)
ADAPTER #1 (GENERAL APPEARANCE – LABEL)



FIGURE 9
LCD MONITOR (M/N: E2342TA)
ADAPTER #2 (GENERAL APPEARANCE)



FIGURE 10
LCD MONITOR (M/N: E2342TA)
ADAPTER #2 (GENERAL APPEARANCE – AC PORT)



SWITCHING ADAPTER
源适配器/電源供應器
P/N: EAY62549301
4-40SG-19-3 19032G
140 V-50/60 Hz 1.0 A (1.0 A)
V $\approx$ 1.7 A (1.7 A) $\oplus$ $\ominus$

This device complies with part 15 of the FCC Rules.
Operation is subject to the following two conditions:
1) This device may not cause harmful interference.
2) This device must accept any interference received,
including interference that may cause undesired operation.

型號	40SG-19-3 19032G
輸入電壓	100-240 V~50/60 Hz 1.0 A
輸出電壓	19 V $\approx$ 1.7 A
製造商	Shenzhen Hase Electronics Co., Ltd.
總代理	廣電(China)
地址	2451, 10
電話	1544-7777
傳真	KTC HU10450-11018A

 中國製造
中國製造

 

 

中國製造
中國製造

140 V-
50/60 Hz 1.0 A
 $\approx$ 1.7 A
Electronics
源适配器

ENERGY
PERFORMANCE
VERIFIED
RECOGNIZED
ENERGY-STAR
VERIFIED

Intertek
EP 4001528

MADE IN CHINA



do not open

001

uo jamaadoituskoskeftimilla
iaan"
sa jordet stikkontakt"
lutats till jordat uttag"

內有危險電壓，請勿開
用

TIEMPO EN OPERACIÓN (Hrs) 0.030
TIEMPO EN MODO DE ESPERA (Hrs) 0.0001

ELECTRONIC CO., LTD. 4111
司/深圳哈陸通電子有限公司

