

FCC / ISCED LTE REPORT

Certification

Applicant Name:
 LG Electronics Inc.

Address:
 2621, Nambusunhwan-ro, Gangnam-gu, Seoul,
 Republic of Korea

Date of Issue:
 February 13, 2017

Location:
 HCT CO., LTD.,
 74, Seoicheon-ro 578beon-gil, Majang-myeon,
 Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA
Report No.: HCT-R-1702-F013
HCT FRN: 0005866421

FCC ID:	BEJGEN21CA
IC:	2703H-GEN21CA
APPLICANT:	LG Electronics Inc.

FCC/ IC Model(s): TM03LNCAHK0
EUT Type: AVN Modem Module
FCC Classification: PCS Licensed Transmitter (PCB)
FCC Rule Part(s): §27, §2
IC Rule: RSS-Gen (Issue 4), RSS-130 (Issue 1), RSS-139 (Issue 3)

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	Conducted output power		EIRP	
				Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)
LTE – Band4 (5)	1712.5 – 1752.5	4M50G7D	QPSK	0.207	23.17	0.075	18.76
		4M50W7D	16QAM	0.163	22.11	0.055	17.40
LTE – Band4 (10)	1715.0 – 1750.0	8M96G7D	QPSK	0.230	23.62	0.081	19.10
		8M93W7D	16QAM	0.162	22.10	0.060	17.75
LTE – Band4 (15)	1717.5 – 1747.5	13M5G7D	QPSK	0.215	23.33	0.085	19.32
		13M4W7D	16QAM	0.157	21.95	0.064	18.06
LTE – Band4 (20)	1720.0 – 1745.0	17M9G7D	QPSK	0.217	23.37	0.085	19.29
		17M9W7D	16QAM	0.158	21.99	0.063	18.00


Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	Conducted output power		ERP	
				Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)
LTE – Band17 (5)	706.5 – 713.5	4M50G7D	QPSK	0.223	23.48	0.116	20.63
		4M50W7D	16QAM	0.156	21.93	0.084	19.24
LTE – Band17 (10)	709.0 – 711.0	8M95G7D	QPSK	0.224	23.50	0.108	20.34
		8M94W7D	16QAM	0.153	21.84	0.082	19.12

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C. 853(a)



Report prepared by
: Jeong Ho Kim
Test engineer of RF Team



Approved by
: Jong Seok Lee
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1702-F013	February 13, 2017	- First Approval Report

Table of Contents

1. GENERAL INFORMATION	6
2. INTRODUCTION	8
2.1. EUT DESCRIPTION.....	8
2.2. MEASURING INSTRUMENT CALIBRATION.....	8
2.3. TEST FACILITY	8
3. DESCRIPTION OF TESTS	9
3.1 CONDUCTED OUTPUT POWER.....	9
3.2 ERP/EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS.....	10
3.3 AWS – MOBILE FREQUENCY BLOCKS (1710 – 1755 MHz)	11
3.4 BLOCK B FREQUENCY RANGE (704 – 710 and 734 – 740 MHz, 777 – 792 MHz)	11
3.5 PEAK-AVERAGE RATIO.	12
3.6 OCCUPIED BANDWIDTH.	14
3.7 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	15
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	16
4. LIST OF TEST EQUIPMENT	17
5. MEASUREMENT UNCERTAINTY	18
6. SUMMARY OF TEST RESULTS	19
7. SAMPLE CALCULATION.....	20
8. TEST DATA	21
8.1 CONDUCTED OUTPUT POWER.....	21
8.2 EQUIVALENT ISOTROPIC RADIATED POWER (Band 4)	28
8.3 EFFECTIVE RADIATED POWER (Band 17).....	31
8.4 RADIATED SPURIOUS EMISSIONS.....	33
8.4.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 4 LTE)	33
8.4.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 4 LTE)	34
8.4.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 4 LTE)	35
8.4.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 4 LTE)	36
8.4.5 RADIATED SPURIOUS EMISSIONS (5 MHz Band 17 LTE).....	37
8.4.6 RADIATED SPURIOUS EMISSIONS (10 MHz Band 17 LTE).....	38
8.5 PEAK-TO-AVERAGE RATIO	39
8.6 OCCUPIED BANDWIDTH	40
8.7 CONDUCTED SPURIOUS EMISSIONS	41
8.7.1 BAND EDGE.....	42
8.8 RECEIVER SPURIOUS EMISSIONS	43
8.9 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	44

8.9.1 FREQUENCY STABILITY (5 MHz Band 4 LTE)	44
8.9.2 FREQUENCY STABILITY (10 MHz Band 4 LTE)	45
8.9.3 FREQUENCY STABILITY (15 MHz Band 4 LTE)	46
8.9.4 FREQUENCY STABILITY (20 MHz Band 4 LTE)	47
8.9.5 FREQUENCY STABILITY (5 MHz Band 17 LTE)	48
8.9.6 FREQUENCY STABILITY (10 MHz Band 17 LTE)	49
9. TEST PLOTS.....	50

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name: LG Electronics Inc.

Address: 2621, Nambusunhwan-ro, Gangnam-gu, Seoul, Republic of Korea

FCC ID: BEJGEN21CA

IC: 2703H-GEN21CA

Application Type: Certification

FCC Classification: PCS Licensed Transmitter (PCB)

FCC Rule Part(s): §27, §2

EUT Type: AVN Modem Module

FCC / IC Model(s): TM03LNCAHK0

Tx Frequency: 1712.5 MHz – 1752.5 MHz (LTE – Band 4 (5 MHz))
1715.0 MHz – 1750.0 MHz (LTE – Band 4 (10 MHz))
1717.5 MHz – 1747.5 MHz (LTE – Band 4 (15 MHz))
1720.0 MHz – 1745.0 MHz (LTE – Band 4 (20 MHz))

706.5 MHz – 713.5 MHz (LTE – Band 17 (5 MHz))
709.0 MHz – 711.0 MHz (LTE – Band 17 (10 MHz))

Conducted Output Power:

Band 4 (5 MHz):	0.207 W (QPSK) (23.17 dBm) 0.163 W (16-QAM) (22.11 dBm)
Band 4 (10 MHz):	0.230 W (QPSK) (23.62 dBm) 0.162 W (16-QAM) (22.10 dBm)
Band 4 (15 MHz):	0.215 W (QPSK) (23.33 dBm) 0.157 W (16-QAM) (21.95 dBm)
Band 4 (20 MHz):	0.217 W (QPSK) (23.37 dBm) 0.158 W (16-QAM) (21.99 dBm)
Band 17 (5 MHz) :	0.223 W (QPSK) (23.48 dBm) 0.156 W (16-QAM) (21.93 dBm)
Band 17 (10 MHz) :	0.224 W (QPSK) (23.50 dBm) 0.153 W (16-QAM) (21.84 dBm)

Max. RF Output Power:	Band 4 (5 MHz):	0.075 W (QPSK) (18.76 dBm) 0.055 W (16-QAM) (17.40 dBm)
	Band 4 (10 MHz):	0.081 W (QPSK) (19.10 dBm) 0.060 W (16-QAM) (17.75 dBm)
	Band 4 (15 MHz):	0.085 W (QPSK) (19.32 dBm) 0.064 W (16-QAM) (18.06 dBm)
	Band 4 (20 MHz):	0.085 W (QPSK) (19.29 dBm) 0.063 W (16-QAM) (18.00 dBm)
	Band 17 (5 MHz) :	0.116 W (QPSK) (20.63 dBm) 0.084 W (16-QAM) (19.24 dBm)
	Band 17 (10 MHz) :	0.108 W (QPSK) (20.34 dBm) 0.082 W (16-QAM) (19.12 dBm)
Emission Designator(s):	Band 4 (5 MHz):	4M50G7D (QPSK) / 4M50W7D (16-QAM)
	Band 4 (10 MHz):	8M96G7D (QPSK) / 8M93W7D (16-QAM)
	Band 4 (15 MHz):	13M5G7D (QPSK) / 13M4W7D (16-QAM)
	Band 4 (20 MHz):	17M9G7D (QPSK) / 17M9W7D (16-QAM)
	Band 17 (5 MHz) :	4M50G7D (QPSK) / 4M50W7D (16-QAM)
Date(s) of Tests:	Band 17 (10 MHz) :	8M95G7D (QPSK) / 8M94W7D (16-QAM)
Antenna Specification:	Manufacturer:	INFAC Elecs co.,. Ltd.
	Antenna type:	PCB antenna
	Peak Gain:	Band 4: 2.41 dBi
		Band 17: -1.44 dBi

2. INTRODUCTION

2.1. EUT DESCRIPTION

The LG Electronics Inc. TM03LNCAHK0 AVN Modem Module consists of LTE 4 and 17.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 CONDUCTED OUTPUT POWER

Test Procedure

Conducted Output Power is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 5.2 and RSS-Gen, November 2014, Issue4, Section 6.12

5.2.1 Procedure for use with a spectrum/signal analyzer when EUT can be configured to transmit continuously or when sweep triggering/signal gating can be properly implemented

The EUT is considered to transmit continuously if it can be configured to transmit at a burst duty cycle of greater than or equal to 98% throughout the duration of the measurement. If this condition can be achieved, then the following procedure can be used to measure the average output power of the EUT.

This procedure can also be used when the EUT cannot be configured to transmit continuously, provided that the measurement instrument can be configured to trigger a sweep at the beginning of each full-power transmission burst, and the sweep time is less than or equal to the minimum transmission time during each burst (*i.e.*, no burst off-time is to be included in the measurement).

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Set number of points in sweep $\geq 2 \times$ span / RBW.
- e) Sweep time = auto-couple.
- f) Detector = RMS (power averaging).
- g) If the EUT can be configured to transmit continuously (*i.e.*, burst duty cycle $\geq 98\%$), then set the trigger to free run.
- h) If the EUT cannot be configured to transmit continuously (*i.e.*, burst duty cycle $< 98\%$), then use a sweep trigger with the level set to enable triggering only on full power bursts and configure the EUT to transmit at full power for the entire duration of each sweep. Ensure that the sweep time is less than or equal to the transmission burst duration.
- i) Trace average at least 100 traces in power averaging (*i.e.*, RMS) mode.
- j) Compute the power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with the band limits set equal to the OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

3.2 ERP/EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS

Note: ERP(Effective Radiated Power), EIRP(Effective Isotropic Radiated Power)

Test Procedure RSS-Gen, November 2014, Issue4, Section 6.12 & 6.13

Radiated emission measurements are performed in the Fully-anechoic chamber. The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-D-2010 Clause 2.2.17. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission. The level and position of the maximized emission is recorded with the spectrum analyzer using a RMS detector.

A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(dBm)} = P_{g(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

The maximum EIRP is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration


The maximum EIRP is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

Radiated spurious emissions

: Frequency Range : 9 kHz ~ 10th Harmonics of highest channel fundamental frequency.

3.3 AWS – MOBILE FREQUENCY BLOCKS (1710 – 1755 MHz)

§27.5(h) & SRSP-513(4)



3.4 BLOCK B FREQUENCY RANGE (704 – 710 and 734 – 740 MHz, 777 – 792 MHz)

§27.5(c)

698-746 MHz Band. The following frequencies are available for licensing pursuant to this part in the 698–746 MHz band: (1) Three paired channel blocks of 12 MHz each are available for assignment as follows :

Block A : 698 – 704 MHz and 728 – 734 MHz ;

Block B : 704 – 710 MHz and 734 – 740 MHz ; and

Block C : 710 – 716 MHz and 740 – 746 MHz.

The EUT is only being authorized for operation in Blocks B and C.

3.5 PEAK-AVERAGE RATIO.

Test Procedure

Peak to Average Power Ratio is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 5.7.

- Section 5.7.1 CCDF Procedure

- a) Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
- b) Set the number of counts to a value that stabilizes the measured CCDF curve;
- c) Set the measurement interval as follows:
 - 1) for continuous transmissions, set to 1 ms,
 - 2) for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
- d) Record the maximum PAPR level associated with a probability of 0.1%.

- Section 5.7.2 Alternate Procedure

Use one of the procedures presented in 5.1 to measure the total peak power and record as P_{Pk} . Use one of the applicable procedures presented 5.2 to measure the total average power and record as P_{Avg} . Determine the P.A.R. from: $P.A.R_{(dB)} = P_{Pk (dBm)} - P_{Avg (dBm)}$ (P_{Avg} = Average Power + Duty cycle Factor)

5.1.1 Peak power measurements with a spectrum/signal analyzer or EMI receiver

The following procedure can be used to determine the total peak output power.

- a) Set the RBW $\geq$ OBW.
- b) Set VBW $\geq 3 \times$ RBW.
- c) Set span $\geq 2 \times$ RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Ensure that the number of measurement points $\geq$ span/RBW.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the peak amplitude level.

5.2.2 Procedures for use with a spectrum/signal analyzer when EUT cannot be configured to transmit continuously and sweep triggering/signal gating cannot be properly implemented

If the EUT cannot be configured to transmit continuously (burst duty cycle < 98%), then one of the following procedures can be used. The selection of the applicable procedure will depend on the characteristics of the measured burst duty cycle.

Measure the burst duty cycle with a spectrum/signal analyzer or EMC receiver can be used in zero-span mode if the response time and spacing between bins on the sweep are sufficient to permit accurate measurement of the burst on/off time of the transmitted signal.

5.2.2.2 Constant burst duty cycle


If the measured burst duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then:

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (power averaging).
- g) Set sweep trigger to "free run".
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
- j) Add $10 \log (1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission).

For example, add $10 \log (1/0.25) = 6$ dB if the duty cycle is a constant 25%.

3.6 OCCUPIED BANDWIDTH.

Test set-up



(Configuration of conducted Emission measurement)

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

Test Procedure

OBW is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 4.2 and RSS-Gen, November 2014, Issue4, Section 6.6

The EUT makes a call to the communication simulator. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels(low, middle and high operational range.)

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

3.7 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.

Test Procedure

Spurious and harmonic emissions at antenna terminal is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 6.0 and RSS-Gen, November 2014, Issue4, Section 6.13

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.


The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30kHz bandwidth may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency

NOTES: The analyzer plot offsets were determined by below conditions.

- For LTE Band 4, total offset 27.4 dB = 20 dB attenuator + 6 dB Divider + 1.4 dB RF cables.
- For LTE Band 17 total offset 27.4 dB = 20 dB attenuator + 6 dB Divider + 1.4 dB RF cables.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

Test Set-up



* Nominal Operating Voltage

Test Procedure

Frequency stability is tested in accordance with ANSI/TIA-603-D-2010 section 2.2.2 and RSS-Gen, November 2014, Issue4, Section 6.11

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from the end point to 100 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block

Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

1. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

NOTE: The EUT is tested down to the battery endpoint.

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibration Interval	Calibration Due
REOHDE&SCHWARZ	SCU 18 / AMPLIFIER	10094	09/07/2016	Annual	09/07/2017
Wainwright	WHK1.2/15G-10EF/H.P.F	4	04/11/2016	Annual	04/11/2017
Wainwright	WHK3.3/18G-10EF/H.P.F	2	04/11/2016	Annual	04/11/2017
Hewlett Packard	11667B / Power Splitter	10545	02/15/2016	Annual	02/15/2017
Hewlett Packard	11667B / Power Splitter	11275	04/29/2016	Annual	04/29/2017
Agilent	E3632A/DC Power Supply	KR75303243	07/12/2016	Annual	07/12/2017
Schwarzbeck	UHAP/ Dipole Antenna	557	03/23/2015	Biennial	03/23/2017
Schwarzbeck	UHAP/ Dipole Antenna	558	03/23/2015	Biennial	03/23/2017
EXP	EX-TH400/ Chamber	None	05/31/2016	Annual	05/31/2017
Schwarzbeck	BBHA 9120D/ Horn Antenna	147	09/09/2016	Biennial	09/09/2018
Schwarzbeck	BBHA 9120D/ Horn Antenna	1299	05/15/2015	Biennial	05/15/2017
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/30/2015	Biennial	04/30/2017
Schwarzbeck	BBHA 9170/ Horn Antenna(15~35GHz)	BBHA9170124	04/30/2015	Biennial	04/30/2017
Agilent	N9020A/Signal Analyzer	MY52090906	05/13/2016	Annual	05/13/2017
Hewlett Packard	8493C/ATTENUATOR	17280	06/22/2016	Annual	06/22/2017
REOHDE&SCHWARZ	FSV40/Spectrum Analyzer	1307.9002K40-100931-NK	06/15/2016	Annual	06/15/2017
Agilent	8960 (E5515C)/ Base Station(Now)	MY48360800	10/19/2016	Annual	10/19/2017
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	02/23/2016	Biennial	02/23/2018
Schwarzbeck	VULB9160/ Bilog Antenna	3150	09/30/2016	Biennial	09/30/2018
Schwarzbeck	VULB9160/ Bilog Antenna	3368	10/14/2016	Biennial	10/14/2018
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6200863156	02/26/2016	Annual	02/26/2017
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	02/16/2016	Annual	02/16/2017
CERNEX	CBLU1183540B-01/ POWER AMP	25539	05/17/2017	Annual	05/17/2018
REOHDE & SCHWARZ	ESU / EMI TEST RECEIVER	100346	08/11/2017	Annual	08/11/2018

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	6.07

6. SUMMARY OF TEST RESULTS

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result
2.1049	RSS-Gen(6.6)	Occupied Bandwidth	N/A	CONDUCTED	PASS
2.1051, 27.53(g), 27.53(h)	RSS-130(4.6) RSS-139(6.6)	Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	$< 43 + 10 \log_{10}(P[\text{Watts}])$ at Band Edge and for all-of-band emissions		PASS
27.50(d)(5)	RSS-130(4.4) RSS-139(6.5)	Peak-Average Ratio	$< 13 \text{ dB}$		PASS
2.1046	RSS-130(4.4) RSS-139(4.1)	Conducted Output Power	N/A		PASS
2.1055, 27.54	RSS-130(4.3) RSS-139(6.4)	Frequency stability / variation of ambient temperature	Emission must remain in band		PASS
27.50(c)(10)	RSS-130(4.4) SRSP-503(5.1.2)	Equivalent Isotropic Radiated Power Effective Radiated Power (Band 17)	IC $< 5 \text{ Watts max. EIRP}$ FCC $< 3 \text{ Watts max. ERP}$	RADIATED	PASS
27.50(d)(4)	RSS-139(6.5)	Equivalent Isotropic Radiated Power (Band 4)	$< 1 \text{ Watts max. EIRP}$		PASS
2.1053, 27.53(g), 27.53(h)	RSS-130(4.6) RSS-139(6.6)	Undesirable Out-of-Band Emissions	$< 43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions		PASS
	RSS-GEN(7)	Receiver Spurious Emissions	RSS-GEN section 7.1.2 table 2		PASS

7. SAMPLE CALCULATION

A. EIRP Sample Calculation

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL(dBm)	Ant. Gain (dBi)	C.L	Pol.	Limit	EIRP	
	channel	Freq.(MHz)						W	W	dBm
LTE Band4	20175	1,732.50	-15.75	18.45	9.90	1.76	H	< 1.00	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a wooden tripod is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated and the antenna height is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of Equivalent Isotropic Radiated Power (**EIRP**).

B. Emission Designator

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

16QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = main carrier modulated in a combination of two

or more of the following modes;

amplitude, angle, pulse

7 = Quantized/Digital Info


D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 CONDUCTED OUTPUT POWER

Conducted Output Power was tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 5.2 and RSS-Gen, November 2014, Issue4, Section 6.12

A base station simulator was used to establish communication with the EUT, and Spectrum analyzer was used for test results. This device was tested under all configurations and the highest power is reported. Conducted Output Powers of EUT are reported below.



Test Result

Band	Band Width (MHz)	Frequency (MHz)	Channel	Resource Block Size	Resource Block Offset	Average Power [dBm]	
						QPSK	16-QAM
Band 4	5	1712.5	19975	1	0	23.07	21.96
				1	12	23.08	21.94
				1	24	22.92	21.95
				12	0	22.08	21.10
				12	6	22.07	21.09
				12	11	22.06	21.00
				25	0	21.91	21.01
		1732.5	20175	1	0	23.04	21.97
				1	12	23.09	21.93
				1	24	23.00	21.82
				12	0	22.00	21.07
				12	6	22.04	20.97
				12	11	21.99	20.83
				25	0	21.94	20.94
		1752.5	20375	1	0	23.17	22.01
				1	12	23.16	22.11
				1	24	23.17	22.11
				12	0	22.06	20.80
				12	6	22.11	20.85
				12	11	22.09	20.95
				25	0	22.08	21.28

LTE Conducted Average Output Powers (5 MHz Band 4 LTE)

Band	Band Width (MHz)	Frequency (MHz)	Channel	Resource Block Size	Resource Block Offset	Average Power [dBm]	
						QPSK	16-QAM
Band 4	10	1715.0	20000	1	0	23.32	22.10
				1	24	23.37	21.99
				1	49	23.11	21.81
				25	0	22.22	21.22
				25	12	22.20	21.21
				25	24	21.91	21.03
				50	0	22.04	21.17
		1732.5	20175	1	0	23.15	21.87
				1	24	23.06	21.96
				1	49	23.23	21.90
				25	0	22.16	21.21
				25	12	21.97	21.20
				25	24	21.91	21.04
				50	0	21.90	21.06
		1750.0	20350	1	0	23.25	22.00
				1	24	23.62	22.03
				1	49	23.38	22.02
				25	0	22.24	21.27
				25	12	22.26	21.29
				25	24	22.07	21.18
				50	0	22.13	21.26

LTE Conducted Average Output Powers (10 MHz Band 4 LTE)

Band	Band Width (MHz)	Frequency (MHz)	Channel	Resource Block Size	Resource Block Offset	Average Power [dBm]	
						QPSK	16-QAM
Band 4	15	1717.5	20025	1	0	23.19	21.95
				1	36	23.20	21.85
				1	74	23.14	21.77
				36	0	22.05	21.07
				36	18	21.99	20.94
				36	39	21.85	20.90
				75	0	21.92	21.01
		1732.5	20175	1	0	23.18	21.77
				1	36	23.25	21.76
				1	74	23.01	21.50
				36	0	22.13	21.08
				36	18	22.00	20.82
				36	39	21.82	20.79
				75	0	21.99	20.99
		1747.5	20325	1	0	23.33	21.80
				1	36	23.06	21.76
				1	74	23.13	21.91
				36	0	21.97	21.11
				36	18	22.12	21.16
				36	39	21.98	20.92
				75	0	22.00	21.07

LTE Conducted Average Output Powers (15 MHz Band 4 LTE)

Band	Band Width (MHz)	Frequency (MHz)	Channel	Resource Block Size	Resource Block Offset	Average Power [dBm]	
						QPSK	16-QAM
Band 4	20	1720.0	20050	1	0	23.11	21.99
				1	49	23.13	21.83
				1	99	23.10	21.76
				50	0	22.01	21.06
				50	25	22.07	21.01
				50	49	21.95	21.00
				100	0	21.98	20.97
		1732.5	20175	1	0	23.15	21.66
				1	49	23.29	21.60
				1	99	22.96	21.50
				50	0	22.06	21.01
				50	25	21.96	20.79
				50	49	21.87	20.92
				100	0	21.91	21.09
		1745.0	20300	1	0	23.29	21.70
				1	49	23.37	21.62
				1	99	23.08	21.67
				50	0	22.16	21.20
				50	25	22.10	21.14
				50	49	22.03	21.07
				100	0	21.96	21.12

LTE Conducted Average Output Powers (20 MHz Band 4 LTE)

Band	Band Width (MHz)	Frequency (MHz)	Channel	Resource Block Size	Resource Block Offset	Average Power [dBm]	
						QPSK	16-QAM
Band 17	5	706.5	23755	1	0	23.07	21.76
				1	12	23.20	21.84
				1	24	23.08	21.78
				12	0	22.08	20.90
				12	6	22.08	20.91
				12	11	21.99	20.80
				25	0	22.01	20.92
		710.0	23790	1	0	23.19	21.93
				1	12	23.08	21.84
				1	24	22.68	21.55
				12	0	22.06	20.99
				12	6	22.09	20.92
				12	11	22.01	20.93
				25	0	22.03	20.96
		713.5	23825	1	0	23.01	21.82
				1	12	23.48	21.52
				1	24	23.03	21.34
				12	0	21.98	20.71
				12	6	22.09	20.80
				12	11	22.11	20.85
				25	0	21.93	20.86

LTE Conducted Average Output Powers (5 MHz Band 17 LTE)

Band	Band Width (MHz)	Frequency (MHz)	Channel	Resource Block Size	Resource Block Offset	Average Power [dBm]	
						QPSK	16-QAM
Band 17	10	709.0	23780	1	0	23.00	21.73
				1	24	23.48	21.71
				1	49	23.12	21.75
				25	0	21.98	21.01
				25	12	22.11	21.03
				25	24	22.05	20.86
				50	0	22.04	20.96
		710.0	23790	1	D0	23.15	21.68
				1	24	23.50	21.53
				1	49	23.27	21.84
				25	0	22.13	21.04
				25	12	22.15	21.05
				25	24	22.12	21.02
				50	0	22.15	21.00
		711.0	23800	1	0	22.97	21.55
				1	24	23.17	21.78
				1	49	23.13	21.65
				25	0	22.02	20.85
				25	12	22.07	20.99
				25	24	21.97	21.01
				50	0	21.92	20.85

LTE Conducted Average Output Powers (10 MHz Band 17 LTE)

Note : Detecting mode is average.

8.2 EQUIVALENT ISOTROPIC RADIATED POWER (Band 4)

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1712.5	5 MHz	QPSK	-22.98	10.36	9.37	2.45	V	< 1.00	0.053	17.28
		16-QAM	-23.92	9.42	9.37	2.45	V		0.043	16.34
1732.5		QPSK	-21.53	11.79	9.44	2.47	V		0.075	18.76
		16-QAM	-22.89	10.43	9.44	2.47	V		0.055	17.40
1752.5		QPSK	-22.15	11.17	9.51	2.47	V		0.066	18.21
		16-QAM	-23.56	9.76	9.51	2.47	V		0.048	16.80

Equivalent Isotropic Radiated Power Data (5 MHz Band4 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

This device uses 4.9 m cables interchangeably.

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1715.0	10 MHz	QPSK	-22.68	10.66	9.39	2.46	V	< 1.00	0.057	17.59
		16-QAM	-24.01	9.33	9.39	2.46	V		0.042	16.26
1732.5		QPSK	-21.19	12.13	9.44	2.47	V		0.081	19.10
		16-QAM	-22.54	10.78	9.44	2.47	V		0.060	17.75
1750.0		QPSK	-22.34	10.98	9.51	2.47	V		0.063	18.02
		16-QAM	-23.78	9.54	9.51	2.47	V		0.046	16.58

Equivalent Isotropic Radiated Power Data (10 MHz Band4 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

This device uses 4.9 m cables interchangeably.

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1717.5	15 MHz	QPSK	-22.77	10.57	9.40	2.47	V	< 1.00	0.056	17.50
		16-QAM	-23.94	9.40	9.40	2.47	V		0.043	16.33
1732.5		QPSK	-20.97	12.35	9.44	2.47	V		0.085	19.32
		16-QAM	-22.23	11.09	9.44	2.47	V		0.064	18.06
1747.5		QPSK	-22.56	10.76	9.51	2.47	V		0.060	17.80
		16-QAM	-23.87	9.45	9.51	2.47	V		0.045	16.49

Equivalent Isotropic Radiated Power Data (15 MHz Band4 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

This device uses 4.9 m cables interchangeably.

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1720.0	20 MHz	QPSK	-22.68	10.66	9.40	2.47	V	< 1.00	0.057	17.59
		16-QAM	-24.00	9.34	9.40	2.47	V		0.042	16.27
1732.5		QPSK	-21.00	12.32	9.44	2.47	V		0.085	19.29
		16-QAM	-22.29	11.03	9.44	2.47	V		0.063	18.00
1745.0		QPSK	-22.33	11.03	9.49	2.47	V		0.064	18.05
		16-QAM	-23.59	9.77	9.49	2.47	V		0.048	16.79

Equivalent Isotropic Radiated Power Data (20 MHz Band4 LTE)

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

This device uses 4.9 m cables interchangeably.

NOTES:Equivalent Isotropic Radiated Power Measurements by Substitution Methodaccording to ANSI/TIA/EIA-603-D-2010 June 24, 2010:

The EUT was placed on a non-conductive styrofoam resin table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For LTE signals, RBW = 1-5% of the OBW, not to exceed 1MHz, VBW $\geq 3 \times$ RBW, Detector = RMS. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is y plane in LTE mode. Also worst case of detecting Antenna is vertical polarization in LTE mode.

8.3 EFFECTIVE RADIATED POWER (Band 17)

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
706.5	5 MHz	QPSK	-29.45	32.37	-10.20	1.54	H	< 3.00	0.116	20.63
		16-QAM	-30.84	30.98	-10.20	1.54	H		0.084	19.24
710.0		QPSK	-29.92	31.68	-10.22	1.55	H		0.098	19.91
		16-QAM	-31.28	30.32	-10.22	1.55	H		0.072	18.55
713.5		QPSK	-30.23	31.21	-10.24	1.55	H		0.087	19.42
		16-QAM	-31.52	29.92	-10.24	1.55	H		0.065	18.13

Effective Radiated Power Data (5 MHz Band 17 LTE)

Note: All of RB size has been tested for emissions and ERP, with the 1RB configuration observed as the worst case

This device uses 4.9 m cables interchangeably.

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
709.0	10 MHz	QPSK	-29.58	32.10	-10.22	1.54	H	< 3.00	0.108	20.34
		16-QAM	-30.80	30.88	-10.22	1.54	H		0.082	19.12
710.0		QPSK	-29.59	32.01	-10.22	1.55	H		0.106	20.24
		16-QAM	-31.10	30.50	-10.22	1.55	H		0.075	18.73
711.0		QPSK	-29.84	31.65	-10.23	1.55	H		0.097	19.87
		16-QAM	-31.24	30.25	-10.23	1.55	H		0.070	18.47

Effective Radiated Power Data Data (10 MHz Band 17 LTE)

Note: All of RB size has been tested for emissions and ERP, with the 1RB configuration observed as the worst case

This device uses 4.9 m cables interchangeably.

NOTES:Effective Radiated Power Output Measurements by Substitution Methodaccording to ANSI/TIA/EIA-603-D-2010 June 24, 2010:

The EUT was placed on a non-conductive styrofoam resin table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For LTE signals, RBW = 1-5% of the OBW, not to exceed 1MHz, VBW $\geq 3 \times$ RBW, Detector = RMS. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is y plane in LTE mode. Also worst case of detecting Antenna is horizontal polarization in LTE mode.

8.4 RADIATED SPURIOUS EMISSIONS

8.4.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 4 LTE)

- ▣ OPERATING FREQUENCY: 1732.50 MHz
- ▣ MEASURED OUTPUT POWER: 18.76 dBm = 0.075 W
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $43 + 10 \log_{10} (W) =$ 31.76 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
19975 (1712.5)	3,425.00	-47.11	12.20	-54.40	1.50	H	-43.69	62.45
	5,137.50	-37.48	12.77	-38.31	2.50	V	-28.04	46.80
	6,850.00	-54.52	12.04	-50.49	3.49	H	-41.94	60.70
20175 (1732.5)	3,465.00	-42.86	12.28	-49.75	1.49	H	-38.96	57.72
	5,197.50	-44.27	12.86	-45.38	2.57	V	-35.09	53.85
	6,930.00	-52.06	11.87	-47.46	3.53	H	-39.12	57.88
20375 (1752.5)	3,505.00	-42.24	12.36	-48.79	1.54	H	-37.97	56.73
	5,257.50	-40.20	12.95	-41.99	2.63	V	-31.67	50.43
	7,010.00	-54.09	11.73	-51.31	3.64	H	-43.22	61.98

- NOTES:**
1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.
 6. This device uses 4.9 m cables interchangeably.
 7. The cable provided by the manufacturer was used for the radiation test.

8.4.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 4 LTE)

- OPERATING FREQUENCY: 1732.50 MHz
- MEASURED OUTPUT POWER: 19.10 dBm = 0.081 W
- MODULATION SIGNAL: 10 MHz QPSK
- DISTANCE: 3 meters
- LIMIT: $43 + 10 \log_{10}(W) =$ 32.10 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
20000 (1715.0)	3,430.00	-47.15	12.21	-54.55	1.50	H	-43.84	62.94
	5,145.00	-38.87	12.78	-39.63	2.51	V	-29.36	48.46
	6,860.00	-53.34	12.01	-49.26	3.49	H	-40.74	59.84
20175 (1732.5)	3,465.00	-42.32	12.28	-49.21	1.49	H	-38.42	57.52
	5,197.50	-46.03	12.86	-47.14	2.57	V	-36.85	55.95
	6,930.00	-53.04	11.87	-48.44	3.53	H	-40.10	59.20
20350 (1750.0)	3,500.00	-40.05	12.35	-46.70	1.55	H	-35.90	55.00
	5,250.00	-44.87	12.93	-46.68	2.63	V	-36.38	55.48
	7,000.00	-52.13	11.73	-50.00	3.63	H	-41.90	61.00

- NOTES:**
1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.
 6. This device uses 4.9 m cables interchangeably.
 7. The cable provided by the manufacturer was used for the radiation test.

8.4.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 4 LTE)

- OPERATING FREQUENCY: 1732.50 MHz
- MEASURED OUTPUT POWER: 19.32 dBm = 0.085 W
- MODULATION SIGNAL: 15 MHz QPSK
- DISTANCE: 3 meters
- LIMIT: $43 + 10 \log_{10}(W) =$ 32.32 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
20025 (1717.5)	3,435.00	-46.17	12.22	-53.42	1.51	H	-42.71	62.03
	5,152.50	-40.93	12.79	-41.62	2.52	H	-31.35	50.67
	6,870.00	-55.19	11.99	-51.43	3.44	H	-42.88	62.20
20175 (1732.5)	3,465.00	-43.64	12.28	-50.53	1.49	H	-39.74	59.06
	5,197.50	-46.99	12.86	-48.10	2.57	H	-37.81	57.13
	6,930.00	-53.52	11.87	-48.92	3.53	V	-40.58	59.90
20325 (1747.5)	3,495.00	-43.40	12.34	-50.01	1.54	H	-39.21	58.53
	5,242.50	-46.47	12.92	-47.93	2.60	H	-37.61	56.93
	6,990.00	-55.23	11.75	-50.29	3.52	H	-42.06	61.38

- NOTES:**
1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.
 6. This device uses 4.9 m cables interchangeably.
 7. The cable provided by the manufacturer was used for the radiation test.

8.4.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 4 LTE)

- OPERATING FREQUENCY: 1732.50 MHz
- MEASURED OUTPUT POWER: 19.29 dBm = 0.085 W
- MODULATION SIGNAL: 20 MHz QPSK
- DISTANCE: 3 meters
- LIMIT: $43 + 10 \log_{10}(W) =$ 32.29 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
20050 (1720.0)	3,440.00	-47.32	12.23	-54.43	1.52	H	-43.72	63.01
	5,160.00	-39.84	12.80	-40.87	2.53	V	-30.60	49.89
	6,880.00	-54.42	11.97	-50.49	3.46	H	-41.98	61.27
20175 (1732.5)	3,465.00	-44.23	12.28	-51.12	1.49	H	-40.33	59.62
	5,197.50	-41.96	12.86	-43.07	2.57	V	-32.78	52.07
	6,930.00	-53.59	11.87	-48.99	3.53	H	-40.65	59.94
20300 (1745.0)	3,490.00	-45.33	12.33	-51.90	1.53	H	-41.10	60.39
	5,235.00	-41.31	12.91	-42.84	2.59	V	-32.52	51.81
	6,980.00	-54.15	11.77	-49.08	3.50	V	-40.81	60.10

- NOTES:**
1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.
 6. This device uses 4.9 m cables interchangeably.
 7. The cable provided by the manufacturer was used for the radiation test.

8.4.5 RADIATED SPURIOUS EMISSIONS (5 MHz Band 17 LTE)

- OPERATING FREQUENCY: 706.50 MHz
- MEASURED OUTPUT POWER: 20.63 dBm = 0.116 W
- MODULATION SIGNAL: 5 MHz QPSK
- DISTANCE: 3 meters
- LIMIT: $43 + 10 \log_{10}(W) =$ 33.63 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	ERP (dBm)	dBc
23755 (706.50)	1,413.00	-54.96	8.05	-63.03	1.19	V	-56.17	76.80
	2,119.50	-56.26	10.46	-63.83	1.18	H	-54.55	75.18
	2,826.00	-56.34	11.18	-62.59	1.23	H	-52.64	73.27
23790 (710.00)	1,420.00	-51.58	8.09	-59.92	1.18	V	-53.01	73.64
	2,130.00	-56.15	10.47	-63.40	1.17	H	-54.10	74.73
	2,840.00	-56.92	11.19	-63.06	1.26	H	-53.13	73.76
23825 (713.50)	1,427.00	-55.51	8.11	-64.04	1.18	V	-57.11	77.74
	2,140.50	-56.47	10.49	-63.37	1.17	H	-54.05	74.68
	2,854.00	-56.55	11.20	-62.74	1.27	H	-52.81	73.44

- NOTES:**
1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and ERP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.
 6. This device uses 4.9 m cables interchangeably.
 7. The cable provided by the manufacturer was used for the radiation test.

8.4.6 RADIATED SPURIOUS EMISSIONS (10 MHz Band 17 LTE)

- OPERATING FREQUENCY: 709.00 MHz
- MEASURED OUTPUT POWER: 20.34 dBm = 0.108 W
- MODULATION SIGNAL: 10 MHz QPSK
- DISTANCE: 3 meters
- LIMIT: $43 + 10 \log_{10}(W) =$ 33.34 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	ERP (dBm)	dBc
23780 (709.00)	1,418.00	-55.32	8.08	-63.59	1.18	V	-56.69	77.03
	2,127.00	-55.50	10.47	-62.85	1.17	H	-53.55	73.89
	2,836.00	-56.42	11.19	-62.58	1.25	H	-52.64	72.98
23790 (710.00)	1,420.00	-54.53	8.09	-62.87	1.18	V	-55.96	76.30
	2,130.00	-56.05	10.47	-63.30	1.17	H	-54.00	74.34
	2,840.00	-56.12	11.19	-62.26	1.26	H	-52.33	72.67
23800 (711.00)	1,422.00	-55.84	8.10	-64.24	1.18	V	-57.32	77.66
	2,133.00	-55.71	10.47	-62.85	1.17	H	-53.55	73.89
	2,844.00	-55.52	11.19	-61.71	1.26	H	-51.78	72.12

- NOTES:**
1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and ERP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.
 6. This device uses 4.9 m cables interchangeably.
 7. The cable provided by the manufacturer was used for the radiation test.

8.5 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
4	5 MHz	1732.5	QPSK	25	0	5.15
			16-QAM	25		5.87
	10 MHz		QPSK	50		5.16
			16-QAM	50		5.88
	15 MHz		QPSK	75		5.07
			16-QAM	75		5.81
	20 MHz		QPSK	100		5.06
			16-QAM	100		5.84

- Plots of the EUT's Peak- to- Average Ratio are shown Page 57~ 60.

8.6 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
4	5 MHz	1732.5	QPSK	25	0	4.5033
			16-QAM	25		4.4997
	10 MHz		QPSK	50		8.9567
			16-QAM	50		8.9265
	15 MHz		QPSK	75		13.460
			16-QAM	75		13.414
	20 MHz		QPSK	100		17.856
			16-QAM	100		17.883

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
17	5 MHz	710.0	QPSK	25	0	4.5023
			16-QAM	25	0	4.4953
	10 MHz		QPSK	50	0	8.9465
			16-QAM	50	0	8.9362

- Plots of the EUT's Occupied Bandwidth are shown Page 51 ~ 56.

8.7 CONDUCTED SPURIOUS EMISSIONS

■FACTORS FOR FREQUENCY

Frequency Range (GHz)	Factor [dB]
0.03 – 1	27.145
1 – 5	26.960
5 – 10	27.542
10 – 15	28.439
15 – 20	29.144
Above 20	30.148

NOTES:

Factor(dB) = Cable Loss + Attenuator +Power Splitter

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
4	5	1712.5	18.8750	29.144	-62.86	-33.716	-13.00
		1732.5	16.4585	29.144	-62.68	-33.536	
		1752.5	18.9160	29.144	-62.72	-33.576	
	10	1715.0	18.9035	29.144	-62.77	-33.626	
		1732.5	18.5865	29.144	-62.73	-33.586	
		1750.0	18.9285	29.144	-62.56	-33.416	
	15	1717.5	18.8725	29.144	-62.85	-33.706	
		1732.5	18.9130	29.144	-62.45	-33.306	
		1747.5	18.8975	29.144	-62.80	-33.656	
	20	1720.0	18.9235	29.144	-62.85	-33.706	
		1732.5	18.9200	29.144	-62.53	-33.386	
		1745.0	18.8820	29.144	-62.69	-33.546	

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
17	5	706.5	3.71923	26.960	-66.770	-39.810	-13.00
		710.0	3.67599	26.960	-66.950	-39.990	
		713.5	3.69065	26.960	-67.351	-40.391	
	10	709.0	3.68618	26.960	-67.100	-40.140	
		710.0	3.69786	26.960	-66.830	-39.870	
		711.0	3.70681	26.960	-67.250	-40.290	

NOTES:

1. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
2. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)

- Plots of the EUT's Conducted Spurious Emissions are shown Page 78 ~ 95.

8.7.1 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 61 ~ 77.

8.8 RECEIVER SPURIOUS EMISSIONS

IC Rule(s) RSS-Gen 7.1.2

Test Requirements: Below the table

Operating conditions: Under normal test conditions

Method of testing: Radiated

S/A. Settings: F < 1 GHz: RBW: 120 kHz, VBW: 300 kHz (Quasi-Peak)
F > 1 GHz: RBW: 1 MHz, VBW: 1 MHz (Average)

Mode of operation: Receive

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$ at 3 meters)
30 – 88	100
88 - 216	150
216 – 960	200
Above 960	500

Operation Mode: Receive:

30 MHz ~ 1 GHz

Frequency	Reading	Ant. factor+Cable loss- Amp Gain	Ant. POL	Total	Limit	Margin
MHz	$\text{dB } \mu\text{V}$	dB/m	(H/V)	$\text{dB } \mu\text{V}/\text{m}$	$\text{dB } \mu\text{V}/\text{m}$	dB
No Peak Found						

Above 1 GHz


Frequency	Reading	Ant. factor+Cable loss- Amp Gain	Ant. POL	Total	Limit	Margin
MHz	$\text{dB } \mu\text{V}$	dB/m	(H/V)	$\text{dB } \mu\text{V}/\text{m}$	$\text{dB } \mu\text{V}/\text{m}$	dB
No Peak Found						

8.9 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

8.9.1 FREQUENCY STABILITY (5 MHz Band 4 LTE)

- OPERATING FREQUENCY: 1732,500,000 Hz
- CHANNEL: 20175 (5 MHz)
- REFERENCE VOLTAGE: 12.0 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (℃)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	12.0	+20(Ref)	1732 500 004	0.0	0.000 000	0.000
100%		-30	1732 500 009	5.2	0.000 000	0.003
100%		-20	1732 500 008	4.0	0.000 000	0.002
100%		-10	1732 500 000	-3.9	0.000 000	-0.002
100%		0	1732 500 010	5.8	0.000 000	0.003
100%		+10	1732 500 009	4.7	0.000 000	0.003
100%		+30	1732 500 009	4.6	0.000 000	0.003
100%		+40	1732 500 000	-4.4	0.000 000	-0.003
100%		+50	1732 500 009	5.2	0.000 000	0.003
Batt. Endpoint	10.2	+20	1732 500 007	3.2	0.000 000	0.002



8.9.2 FREQUENCY STABILITY (10 MHz Band 4 LTE)

- OPERATING FREQUENCY: 1732,500,000 Hz
- CHANNEL: 20175 (10 MHz)
- REFERENCE VOLTAGE: 12.0 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	12.0	+20(Ref)	1732 500 006	0.0	0.000 000	0.000
100%		-30	1732 500 011	4.5	0.000 000	0.003
100%		-20	1732 500 001	-5.2	0.000 000	-0.003
100%		-10	1732 500 002	-4.6	0.000 000	-0.003
100%		0	1732 500 010	4.3	0.000 000	0.002
100%		+10	1732 500 011	5.0	0.000 000	0.003
100%		+30	1732 500 012	6.1	0.000 000	0.004
100%		+40	1732 500 010	3.9	0.000 000	0.002
100%		+50	1732 500 009	3.0	0.000 000	0.002
Batt. Endpoint	10.2	+20	1732 500 011	4.8	0.000 000	0.003



8.9.3 FREQUENCY STABILITY (15 MHz Band 4 LTE)

- OPERATING FREQUENCY: 1732,500,000 Hz
- CHANNEL: 20175 (15 MHz)
- REFERENCE VOLTAGE: 12.0 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (℃)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	12.0	+20(Ref)	1732 500 005	0.0	0.000 000	0.000
100%		-30	1732 500 009	4.0	0.000 000	0.002
100%		-20	1732 500 010	5.5	0.000 000	0.003
100%		-10	1732 500 000	-4.8	0.000 000	-0.003
100%		0	1732 500 001	-3.6	0.000 000	-0.002
100%		+10	1732 499 998	-6.2	0.000 000	-0.004
100%		+30	1732 500 008	3.7	0.000 000	0.002
100%		+40	1732 499 999	-5.8	0.000 000	-0.003
100%		+50	1732 499 999	-5.7	0.000 000	-0.003
Batt. Endpoint	10.2	+20	1732 499 998	-6.7	0.000 000	-0.004



8.9.4 FREQUENCY STABILITY (20 MHz Band 4 LTE)

- OPERATING FREQUENCY: 1732,500,000 Hz
- CHANNEL: 20175 (20 MHz)
- REFERENCE VOLTAGE: 12.0 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	12.0	+20(Ref)	1732 500 005	0.0	0.000 000	0.000
100%		-30	1732 500 008	3.5	0.000 000	0.002
100%		-20	1732 500 012	7.0	0.000 000	0.004
100%		-10	1732 500 002	-3.4	0.000 000	-0.002
100%		0	1732 500 001	-3.9	0.000 000	-0.002
100%		+10	1732 500 013	7.7	0.000 000	0.004
100%		+30	1732 500 010	5.1	0.000 000	0.003
100%		+40	1732 500 002	-3.4	0.000 000	-0.002
100%		+50	1732 500 009	3.8	0.000 000	0.002
Batt. Endpoint	10.2	+20	1732 499 999	-5.6	0.000 000	-0.003



8.9.5 FREQUENCY STABILITY (5 MHz Band 17 LTE)

- OPERATING FREQUENCY: 710,000,000 Hz
- CHANNEL: 23790 (5 MHz)
- REFERENCE VOLTAGE: 12.0 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (℃)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	12.0	+20(Ref)	709 999 998	0.0	0.000 000	0.0000
100%		-30	710 000 000	2.4	0.000 000	0.0034
100%		-20	709 999 995	-2.6	0.000 000	-0.0037
100%		-10	709 999 996	-1.6	0.000 000	-0.0023
100%		0	709 999 995	-3.0	0.000 000	-0.0042
100%		+10	709 999 994	-3.2	0.000 000	-0.0045
100%		+30	710 000 000	2.0	0.000 000	0.0028
100%		+40	709 999 994	-3.7	-0.000 001	-0.0052
100%		+50	709 999 996	-2.0	0.000 000	-0.0028
Batt. Endpoint	10.2	+20	710 000 000	2.5	0.000 000	0.0035



8.9.6 FREQUENCY STABILITY (10 MHz Band 17 LTE)


- OPERATING FREQUENCY: 710,000,000 Hz
- CHANNEL: 23790 (10 MHz)
- REFERENCE VOLTAGE: 12.0 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	12.0	+20(Ref)	710 000 003	0.0	0.000 000	0.0000
100%		-30	710 000 005	1.6	0.000 000	0.0023
100%		-20	710 000 002	-1.8	0.000 000	-0.0025
100%		-10	710 000 001	-2.7	0.000 000	-0.0038
100%		0	710 000 006	2.9	0.000 000	0.0041
100%		+10	710 000 000	-3.5	0.000 000	-0.0049
100%		+30	710 000 000	-3.2	0.000 000	-0.0045
100%		+40	710 000 006	2.3	0.000 000	0.0032
100%		+50	710 000 007	3.1	0.000 000	0.0044
Batt. Endpoint	10.2	+20	710 000 006	2.5	0.000 000	0.0035




9. TEST PLOTS


BAND 4. Occupied Bandwidth Plot (5M BW Ch.20175 QPSK RB 25)




BAND 4. Occupied Bandwidth Plot (5M BW Ch.20175 16QAM RB 25)




BAND 4. Occupied Bandwidth Plot (10M BW Ch.20175 QPSK RB 50)




BAND 4. Occupied Bandwidth Plot (10M BW Ch.20175 16QAM RB 50)




BAND 4. Occupied Bandwidth Plot (15M BW Ch.20175 QPSK RB 75)




BAND 4. Occupied Bandwidth Plot (15M BW Ch.20175 16QAM RB 75)




BAND 4. Occupied Bandwidth Plot (20M BW Ch.20175 QPSK RB 100)




BAND 4. Occupied Bandwidth Plot (20M BW Ch.20175 16QAM RB 100)




BAND 17. Occupied Bandwidth Plot (5M BW Ch.23790 QPSK RB 25)




BAND 17. Occupied Bandwidth Plot (5M BW Ch.23790 16QAM RB 25)




BAND 17. Occupied Bandwidth Plot (10M BW Ch.23790 QPSK RB 50)




BAND 17. Occupied Bandwidth Plot (10M BW Ch.23790 16QAMRB 50)




BAND 4. PAR Plot (5M BW_Ch.20175_QPSK_RB25_0)




BAND 4. PAR Plot (5M BW_Ch.20175_16QAM_RB25_0)




BAND 4. PAR Plot (10M BW_Ch.20175_QPSK_RB50_0)




BAND 4. PAR Plot (10M BW_Ch.20175_16QAM_RB50_0)




BAND 4. PAR Plot (15M BW_Ch.20175_QPSK_RB75_0)




BAND 4. PAR Plot (15M BW_Ch.20175_16QAM_RB75_0)




BAND 4. PAR Plot (20M BW_Ch.20175_QPSK_RB100_0)




BAND 4. PAR Plot (20M BW_Ch.20175_16QAM_RB100_0)




BAND 4. Lower Band Edge Plot (5M BW Ch.19975 QPSK RB 1, Offset 0) -1




BAND 4. Lower Band Edge Plot (5M BW Ch.19975 QPSK RB 25) -2



BAND 4. Lower Extended Band Edge Plot (5M BW Ch.19975 QPSK_RB25_0) -3




BAND 4. Lower Band Edge Plot (10M BW Ch.20000 QPSK RB 1, Offset 0) -1




BAND 4. Lower Band Edge Plot (10M BW Ch.20000 QPSK RB 50) -2



BAND 4. Lower Extended Band Edge Plot (10M BW Ch.20000 QPSK_RB50_0) -3




BAND 4. Lower Band Edge Plot (15M BW Ch.20025 QPSK RB 1, Offset 0) -1




BAND 4. Lower Band Edge Plot (15M BW Ch.20025 QPSK RB 75) -2



BAND 4. Lower Extended Band Edge Plot (15M BW Ch.20025 QPSK_RB75_0) -3




BAND 4. Lower Band Edge Plot (20M BW Ch.20050 QPSK RB 1, Offset 0) -1




BAND 4. Lower Band Edge Plot (20M BW Ch.20050 QPSK RB 100) -2



BAND 4. Lower Extended Band Edge Plot (20M BW Ch.20050 QPSK_RB100_0) -3




BAND 4. Upper Band Edge Plot (5M BW Ch.20375 QPSK_RB1_Offset 24) -1




BAND 4. Upper Band Edge Plot (5M BW Ch.20375 QPSK_RB25) -2



BAND 4. Upper Extended Band Edge Plot (5M BW Ch.20375 QPSK_RB25) -3




BAND 4. Upper Band Edge Plot (10M BW Ch.20350 QPSK_RB1_Offset 49) -1




BAND 4. Upper Band Edge Plot (10M BW Ch.20350 QPSK_RB50) -2



BAND 4. Upper Extended Band Edge Plot (10M BW Ch.20350 QPSK_RB50) -3




BAND 4. Upper Band Edge Plot (15M BW Ch.20325 QPSK_RB1_Offset 74) -1




BAND 4. Upper Band Edge Plot (15M BW Ch.20325 QPSK_RB75) -2



BAND 4. Upper Extended Band Edge Plot (15M BW Ch.20325 QPSK_RB75) -3




BAND 4. Upper Band Edge Plot (20M BW Ch.20300 QPSK_RB1_Offset 99) -1




BAND 4. Upper Band Edge Plot (20M BW Ch.20300 QPSK_RB100) -2



BAND 4. Upper Extended Band Edge Plot (20M BW Ch.20300 QPSK_RB100) -3




Band 17 Lower Band Edge Plot (5M BW Ch.23755 QPSK_RB1 OFFSET0)




Band 17 Lower Band Edge Plot (5M BW Ch.23755 QPSK_RB25)




Band 17 Lower Band Edge Plot (10M BW Ch.23780 QPSK_RB1 OFFSET0)



Band 17 Lower Band Edge Plot (10M BW Ch.23780 QPSK_RB50_0)



Band 17 Upper Band Edge Plot (5M BW Ch.23825 QPSK_RB1_Offset 24)




Band 17 Upper Band Edge Plot (5M BW Ch.23825 QPSK_RB25)



Band 17 Upper Extended Band Edge Plot (5M BW Ch.23825 QPSK_RB25_0)



Band 17 Upper Band Edge Plot (10M BW Ch.23800 QPSK_RB1_Offset 49)




Band 17 Upper Band Edge Plot (10M BW Ch.23800 QPSK_RB50)




Band 17 Upper Extended Band Edge Plot (10M BW Ch.23800 QPSK_RB50_0)




BAND 4. Conducted Spurious Plot_1 (19975ch_5MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_2 (19975ch_5MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_1 (20175ch_5MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_2 (20175ch_5MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_1 (20375ch_5MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_2 (20375ch_5MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_1 (20000ch_10MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_2 (20000ch_10MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_1 (20175ch_10MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_2 (20175ch_10MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_1 (20350ch_10MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_2 (20350ch_10MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_1 (20025ch_15MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_2 (20025ch_15MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_1 (20175ch_15MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_2 (20175ch_15MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_1 (20325ch_15MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_2 (20325ch_15MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_1 (20050ch_20MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_2 (20050ch_20MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_1 (20175ch_20MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_2 (20175ch_20MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_1 (20300ch_20MHz_QPSK_RB 1_0)




BAND 4. Conducted Spurious Plot_2 (20300ch_20MHz_QPSK_RB 1_0)




BAND 17. Conducted Spurious Plot_ (23755ch_5MHz_QPSK_RB 1_0)-1




BAND 17. Conducted Spurious Plot_ (23755ch_5MHz_QPSK_RB 1_0)-2




BAND 17. Conducted Spurious Plot_ (23790ch_5MHz_QPSK_RB 1_0)-1




BAND 17. Conducted Spurious Plot_ (23790ch_5MHz_QPSK_RB 1_0)-2




BAND 17. Conducted Spurious Plot_ (23825ch_5MHz_QPSK_ RB 1_0)-1




BAND 17. Conducted Spurious Plot_ (23825ch_5MHz_QPSK_ RB 1_0)-2




BAND 17. Conducted Spurious Plot_ (23780ch_10MHz_QPSK_RB 1_0)-1




BAND 17. Conducted Spurious Plot_ (23780ch_10MHz_QPSK_RB 1_0)-2



BAND 17. Conducted Spurious Plot_ (23790ch_10MHz_QPSK_RB 1_0)-1



BAND 17. Conducted Spurious Plot_ (23790ch_10MHz_QPSK_RB 1_0)-2



BAND 17. Conducted Spurious Plot_ (23800ch_10MHz_QPSK_RB 1_0)-1



BAND 17. Conducted Spurious Plot_ (23800ch_10MHz_QPSK_RB 1_0)-2

