



FCC EVALUATION REPORT FOR CERTIFICATION

FCC Class B (Class II Permissive Change)

Applicant : LG Electronics Inc.

19-1, Cheongho-ri, Jinwi-myeon,

Pyeongteak-si, Gyeonggi-do, Korea.

Attn: Mr. Myoung-Kyu Lee, Chief research engineer

Date of Issue : April 27, 2010

Order Number: GETEC-C1-10-103

Test Report Number: GETEC-E3-10-049

Test Site: Gumi College EMC Center

FCC Registration Number: (100749, 443957)

FCC ID.: BEJGX2MP

Applicant: LG Electronics Inc.

Rule Part(s)	: FCC Part 15 Subpart B
Equipment Class	: Class B computing device peripheral (JBP)
EUT Type	: LCD Monitor
Type of Authority	: Certification
Model Name	: GX2MP
Trade Name	: NDS
Class II Change(s)	: With alternate LCD panel

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003 / Canadian standard ICES-003

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,

Reviewed by,

Soon-Hoon Jeong, Engineer
GUMI College EMC center

Jae-Hoon Jeong, Senior Engineer
GUMI College EMC center



CONTENTS

1. GENERAL INFORMATION	3
2. INTRODUCTION	4
3. PRODUCT INFORMATION	5
3.1 DESCRIPTION OF EUT.....	5
3.2 SUPPORT EQUIPMENT / CABLES USED	6
3.3 MODIFICATION ITEM(S)	6
4. DESCRIPTION OF TESTS.....	7
4.1 TEST CONDITION.....	7
4.2 CONDUCTED EMISSION	8
4.3 RADIATED EMISSION.....	9
5. CONDUCTED EMISSION.....	10
5.1 OPERATING ENVIRONMENT	10
5.2 TEST SET-UP	10
5.3 MEASUREMENT UNCERTAINTY.....	10
5.4 LIMIT	11
5.5 TEST EQUIPMENT USED.....	11
5.6 TEST DATA FOR CONDUCTED EMISSION	11
6. RADIATED EMISSION	14
6.1 OPERATING ENVIRONMENT	14
6.2 TEST SET-UP	14
6.3 MEASUREMENT UNCERTAINTY.....	14
6.4 LIMIT	15
6.5 TEST EQUIPMENT USED.....	15
6.6 TEST DATA FOR RADIATED EMISSION.....	15
7. SAMPLE CALCULATIONS.....	18
7.1 EXAMPLE 1 :	18
7.2 EXAMPLE 2 :	18
8. RECOMMENDATION & CONCLUSION.....	19

APPENDIX A – INFORMATION OF CLASS II PERMISSIVE CHANGE

APPENDIX B – TEST SET-UP PHOTOGRAPHS



Scope: Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.

1. General Information

Applicant: LG Electronics Inc.

Applicant Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Manufacturer: LG Electronics Inc.

Manufacturer Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Contact Person: Mr. Myoung-Kyu Lee, Chief research engineer

Tel Number: +82-31-610-9623

- **FCC ID.** BEJGX2MP
- **EUT Type** LCD Monitor
- **Model Name** GX2MP
- **Trade Name** NDS
- **Serial Number** Prototype
- **Rule Part(s)** FCC Part 15 Subpart B
- **Type of Authority** Certification
- **Test Procedure(s)** ANSI C63.4 (2003) / Canadian standard ICES-003
- **Dates of Test** April 16 ~ 21, 2010
- **Place of Test** **Gumi College EMC Center** (FCC Registration Number: 100749, 443957)
407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.
- **Test Report Number** GETEC-E3-10-049
- **Dates of Issue** April 27, 2010
- **Class II Change(s)** With alternate LCD panel

EUT Type: LCD Monitor

FCC ID.: BEJGX2MP




2. Introduction

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ASNI C63.4-2003) was used in determining radiated and conducted emissions emanating from **LG Electronics Inc. LCD Monitor (Model Name: GX2MP)**

These measurement tests were conducted at **Gumi College EMC Center**.

The site address is 407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.

This test site is one of the highest point of Gumi 1 college at about 200 km away from Seoul city and 40 km away from Daegu city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 (2003)



GUMI COLLEGE EMC CENTER
407, Bugok-dong, Gumi-si,
Gyeongbuk 730-711, Korea.
Tel: +82-54-440-1195
Fax: +82-54-440-1199

Fig 1. The map above shows the Gumi College in vicinity area.



3. Product Information

3.1 Description of EUT

The Equipment under Test (EUT) is the **LG Electronics Inc. LCD Monitor (Model Name: GX2MP) FCC ID.: BEJGX2MP**

- . Equipment	: LCD Monitor
- . Model Name	: GX2MP
- . Serial Number	: Prototype
- . Maximum Frequency Range	: 162 MHz

Display	20.1 inches (51.0cm) Flat Panel Active matrix-TFT LCD Anti-Glare coating Visible diagonal size: 51.0cm 0.255mm pixel pitch	
Sync Input	Horizontal Freq.	28 - 83kHz (Automatic)
	Vertical Freq.	56 - 85Hz (Automatic)
	Input Form	Separate Sync Composite Sync SOG (Sync On Green) , Digital
Video Input	Signal Input	15 pin D-Sub Connector DVI - D connector (Digital)
	Input Form	RGB Analog (0.7Vp-p / 75ohm) , Digital
Resolution	Max	VESA 1600 x 1200@60Hz
	Recommend	VESA 1600 x 1200@60Hz
Plug&Play	DDC 2B	
Power Consumption	On Mode	: 58W
	Sleep Mode	≤ 1W
	Off Mode	≤ 1W
Dimensions &Weight (with tilt/ swivel stand)	Width	44.60 cm / 17.56 inches
	Height	44.78 cm / 17.62 inches (Min) 52.78 cm / 20.76 inches (Max)
	Depth	24.26 cm / 9.55 inches
	Net	7.6 kg
Range	Tilt	-3°~30°
	Swivel	90°
	Height	80mm / 3.15 inches
	Rotate	90°clockwise
Power Input	AC 100-240V- 50/60Hz 1.2A	
Environmental Conditions	Operating Conditions	
	Temperature	10°C to 35 °C
	Humidity	10 % to 80 % non-Condensing
	Storage Conditions	
	Temperature	-20°C to 60 °C
	Humidity	5 % to 90 % non-Condensing
Tilt/Swivel Stand	Attached(●), Detached (○)	
Power cord	Wall-outlet type .	

EUT Type: LCD Monitor

FCC ID.: BEJGX2MP



3.2 Support Equipment / Cables used

3.2.1 Used Support Equipment

Description	Manufacturer	Model Name	S/N & FCC ID.
PC	Hewlett Packard	D530	S/N: CNG34800PY FCC ID.: DoC
Video card	ATI	ATI RV360(9600)	S/N: SN0402017176 FCC ID.: DoC
Keyboard	COMPAQ	166516-AD6	S/N: B13BBOR391006D FCC ID.: AQ6-23K15
PS2 mouse	LOGITECH	M-S69	S/N: 334684-108 FCC ID.: JNZ211443
Joystick	MICROSOFT	X05-92626	S/N: 9262600296169 FCC ID.: DoC
Printer	Hewlett Packard	970CXI	S/N: MY9B01F1FG FCC ID.: DoC
USB memory stick	LG Electronics Inc.	UM5 2GB	S/N: 003RLRZN37758 FCC ID.: DoC

See “Appendix B – Test Setup Photographs” for actual system test set-up

3.2.2 System configuration

Description	Manufacturer	Model Name	S/N & FCC ID.
None	-	-	-

3.2.3 Used Cable(s)

Cable Name	Condition	Description
Power cable	Connected to the EUT	1.80 m unshielded
D-Sub(Analog) in cable	Connected to the EUT and PC	1.80 m shielded with two ferrite cores
DVI-D(Digital) in cable	Connected to the EUT and PC	2.00 m shielded with two ferrite cores
USB(Upstream) in cable	Connected to the EUT and PC	1.80 m shielded

3.3 Modification Item(s)

- None



4. Description of tests

4.1 Test Condition

The EUT was installed, arranged and operated in a manner that is most representative of equipment as typically used. The measurements were carried out while varying operating modes and cable positions within typically arrangement to determine maximum emission level.

The representative and worst test mode(s) were noted in the test report.

- Test Voltage / Frequency : AC 120 V / 60 Hz

- Test Mode(s)

-. Monitor mode

Radiated emission: **1 600 × 1 200 / 60 Hz (RGB: Analog): Worst-case**

1 600 × 1 200 / 60 Hz (DVI-D: Digital)

Conducted emission: **1 600 × 1 200 / 60 Hz (RGB: Analog): Worst-case**

1 600 × 1 200 / 60 Hz (DVI-D: Digital)

1 024 × 768 / 60 Hz (RGB: Analog), 640 × 480 / 60 Hz (Analog)

- ◆ Operating test pattern: -. “H” character scrolling mode (Font size: 10)
 - . Black background white character
 - . Brightness and contrast was adjusted as maximum level
 - . Continuous reading and writing mode via USB memory stick with software



4.2 Conducted Emission

The Line conducted emission test facility is inside a 4 m × 8 m × 2.5 m shielded enclosure. (FCC Registration No.: 100749)

The EUT was placed on a non-conducting 1.0 m by 1.5 m table, which is 0.8 m in height and 0.4 m away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ESH2-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH3-Z5). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCS30).

The EMI test receiver was scanned from 150 kHz to 30 MHz with 20 ms sweep time to determine the frequency producing the maximum EME from the EUT. The frequency producing the maximum level was re-examined using Quasi-Peak mode of the EMI test receiver.

The bandwidth of Quasi-peak mode was set to 9 kHz. Each emission was maximized consistent with typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum diagram emission. Excess cable lengths were bundled at center with 30 cm ~ 40 cm.

Each EME reported was calibrated using the R/S signal generator




Fig 2. Impedance of LISN



4.3 Radiated Emission

Preliminary measurements were conducted 3 m semi anechoic chamber using broadband antennas to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The technology configuration, mode of operation and turntable azimuth with respect to antenna was note for each frequency found.

Final measurements were made 3 m chamber (FCC registration No.: 443957) and/or 10 m OATS (FCC registration No.: 100749).

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was re-examined and investigated using EMI test receiver. The detector function was set to CISPR quasi-peak mode average mode and the bandwidth of the receiver was set to 120 kHz or 1 MHz depending on the frequency or type of signal.

The EUT, support equipment and interconnecting cables were reconfigured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8 m high non-metallic 1.0 m × 1.5 m table.

The turntable containing the test sample was rotated; the antenna height was varied 1 to 4 meter and stopped at the azimuth or height producing the maximum emission.

Each EME reported was calibrated using the R/S signal generator




Fig 3. Dimensions of test site.



5. Conducted Emission

5.1 Operating Environment

Temperature : 24 °C
Relative Humidity : 35 % R.H.

5.2 Test Set-up

The conducted emission measurements were performed in the shielded room.

The EUT was placed on wooden table, 0.8 m heights above the floor, 0.4 m from the reference ground plane (GRP) wall and 0.8 m from AMN.

AMN is bonded on horizontal reference ground plane.

The ground plane, which was electrically bonded to the shield room, ground system and all power lines entering the shield room, were filtered.

5.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO "Guide to the expression of uncertainty in measurement."

The measurement uncertainty was given with a confidence of 95 %.

Test Items	Uncertainty	Remark
Conducted emission (9 kHz ~ 150 kHz)	± 2.69 dB	Confidence levels of 95 % ($k = 2$)
Conducted emission (150 kHz ~ 30 MHz)	± 4.16 dB	Confidence levels of 95 % ($k = 2$)



5.4 Limit

RFI Conducted	FCC Limit(dB μ V/m) Class B	
Freq. Range	Quasi-Peak	Average
150 kHz ~ 0.5 MHz	66 ~ 56*	56 ~ 46*
0.5 MHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50
*Limits decreases linearly with the logarithm of frequency.		

5.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESCS30	Rohde & Schwarz	EMI test receiver	839809/003	12. 10. 2010
■ - ESH3-Z5	Rohde & Schwarz	LISN	838979/020	12. 10. 2010
■ - ESH2-Z5	Rohde & Schwarz	LISN	829991/009	12. 10. 2010
□ - ISN T8	TESEQ. GmbH	ISN	24568	10. 16. 2010


5.6 Test data for Conducted Emission

-. Test Date : April 16, 2010
-. Resolution Bandwidth : 9 kHz
-. Frequency Range : 0.15 MHz ~ 30 MHz



◆ Operating condition: 1 920 × 1 080 / 60 Hz (RGB: Analog)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	44.1	1000.000	9.000	GND	L1	10.0	21.9	66.0	
0.195000	45.7	1000.000	9.000	GND	L1	10.0	18.0	63.7	
0.270000	37.0	1000.000	9.000	GND	L1	10.0	23.9	60.9	
0.345000	30.6	1000.000	9.000	GND	L1	10.0	28.3	58.9	
0.540000	33.0	1000.000	9.000	GND	L1	10.0	23.0	56.0	
0.615000	30.1	1000.000	9.000	GND	L1	10.0	25.9	56.0	
1.605000	18.3	1000.000	9.000	GND	L1	10.1	37.7	56.0	
2.880000	19.0	1000.000	9.000	GND	L1	10.1	37.0	56.0	
3.480000	23.3	1000.000	9.000	GND	L1	10.1	32.7	56.0	
4.680000	21.5	1000.000	9.000	GND	L1	10.2	34.5	56.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.210000	33.6	1000.000	9.000	GND	L1	10.0	19.4	53.0	
0.270000	26.2	1000.000	9.000	GND	L1	10.0	24.7	50.9	
0.420000	20.1	1000.000	9.000	GND	L1	10.0	27.2	47.3	
0.540000	23.0	1000.000	9.000	GND	L1	10.0	23.0	46.0	
0.615000	20.1	1000.000	9.000	GND	L1	10.0	25.9	46.0	
0.900000	18.3	1000.000	9.000	GND	L1	10.0	27.7	46.0	
1.200000	17.1	1000.000	9.000	GND	L1	10.1	28.9	46.0	
4.800000	16.6	1000.000	9.000	GND	L1	10.2	29.4	46.0	
14.475000	20.0	1000.000	9.000	GND	L1	10.7	30.0	50.0	
28.890000	24.7	1000.000	9.000	GND	L1	11.4	25.3	50.0	

< Fig 4. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	44.0	1000.000	9.000	GND	N	10.0	22.0	66.0	
0.210000	43.9	1000.000	9.000	GND	N	10.0	19.2	63.0	
0.240000	34.6	1000.000	9.000	GND	N	10.0	27.3	61.9	
0.495000	27.3	1000.000	9.000	GND	N	10.0	28.8	56.1	
0.555000	30.7	1000.000	9.000	GND	N	10.0	25.3	56.0	
2.235000	19.3	1000.000	9.000	GND	N	10.1	36.7	56.0	
3.585000	23.0	1000.000	9.000	GND	N	10.2	33.0	56.0	
4.755000	21.7	1000.000	9.000	GND	N	10.2	34.3	56.0	
7.665000	23.3	1000.000	9.000	GND	N	10.3	36.7	60.0	
11.250000	21.2	1000.000	9.000	GND	N	10.4	38.8	60.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.210000	32.3	1000.000	9.000	GND	N	10.0	20.7	53.0	
0.270000	23.7	1000.000	9.000	GND	N	10.0	27.2	50.9	
0.480000	18.6	1000.000	9.000	GND	N	10.0	27.7	46.3	
0.540000	21.5	1000.000	9.000	GND	N	10.0	24.5	46.0	
14.475000	20.6	1000.000	9.000	GND	N	10.6	29.4	50.0	
28.890000	24.5	1000.000	9.000	GND	N	10.8	25.5	50.0	

< Fig 5. Conducted emission result (Neutral line)>



6. Radiated Emission

6.1 Operating Environment

Temperature : 24 °C
Relative Humidity : 43 % R.H.

6.2 Test Set-up

A preliminary and final measurement was at 3 m anechoic chamber.

The EUT was placed on a non-conductive turntable approximately 0.8 m above the ground plane.

The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels.

This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

6.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95 %.

Test Items(Chamber)	Uncertainty	Remark
Radiated emission (30 MHz ~ 300 MHz, 3 m, Vertical)	± 4.32 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (30 MHz ~ 300 MHz, 3 m, Horizontal)	± 4.21 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Vertical)	± 3.96 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Horizontal)	± 3.97 dB	Confidence levels of 95 % ($k = 2$)



6.4 Limit

Frequency (MHz)	FCC Limit @ 3 m. dB μ V/m	CISPR Limit @ 10 m. dB μ V/m
30 ~ 88	40.0	30.0
88 ~ 216	43.5	30.0
216 ~ 230	46.0	30.0
230 ~ 960	46.0	37.0
960 ~ 1 000	54.0	37.0
> 1 000	54.0	No Specified limit

6.5 Test Equipment used


Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESI	Rohde & Schwarz	EMI test receiver	830482/010	12. 11. 2010
■ - VULB9160	Schwarzbeck	Broadband Test Antenna	3193	03. 11. 2012
■ - BBHA9120D	Schwarzbeck	Horn ANT	207	12. 22. 2011
■ - MCU066	matur GmbH	Position Controller	1390306	N/A
■ - TT2.5SI	matur GmbH	Turntable	1390307	N/A
■ - AM 4.0	matur GmbH	Antenna Mast	1390308	N/A
■ - AFS 44 00101800-25-10P-44	MITEQ	Preamplifier	1258943	11. 12. 2010

6.6 Test data for Radiated Emission

- Test Date : April 21, 2010
- Resolution Bandwidth : 120 kHz/1 MHz
- Frequency Range : 30 MHz ~ 2 000 MHz
- Measurement Distance : 3 m
- Note : The highest frequency of the internal source of the EUT is between 108 MHz and 500 MHz (162 MHz). The measurement was made up to 2 000 MHz.



- ◆ Operating Condition: 1 600 × 1 200 / 60 Hz (RGB: Analog)
Red trace: Vertical polarization, Blue trace: Horizontal polarization




Final Result [1]

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
32.646250	30.2	1000.0	120.000	100.0	V	217.0	11.4	9.83	40.00
43.476250	30.2	1000.0	120.000	100.0	V	149.0	12.5	9.82	40.00
68.052500	26.7	1000.0	120.000	100.0	V	309.0	11.7	13.30	40.00
122.280000	25.6	1000.0	120.000	111.0	V	90.0	13.8	17.86	43.50
124.100000	26.0	1000.0	120.000	100.0	V	102.0	13.8	17.50	43.50
228.385000	28.2	1000.0	120.000	142.0	H	78.0	13.3	17.81	46.00
339.441250	27.3	1000.0	120.000	100.0	H	209.0	17.4	18.66	46.00
407.947500	36.9	1000.0	120.000	109.0	V	0.0	18.0	9.09	46.00
475.652500	32.9	1000.0	120.000	111.0	V	11.0	20.2	13.08	46.00
702.028750	41.7	1000.0	120.000	100.0	H	139.0	23.5	4.30	46.00
962.442500	34.7	1000.0	120.000	100.0	H	221.0	30.2	11.35	46.00

< Fig 6. Radiated emission result (30 MHz ~ 1 000 MHz)>



- ◆ Operating Condition: 1 920 × 1 080 / 60 Hz (RGB: Analog)
Green trace: Average detector, Blue trace: Peak detector



Final Result 1

Frequency (MHz)	MaxPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1951.903808	53.2	100.0	1000.000	162.0	H	275.0	-12.9	20.8	74.0

Final Result 2

Frequency (MHz)	Average (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1000.000000	31.0	100.0	1000.000	187.0	V	342.0	-15.9	23.0	54.0
1099.596393	30.6	100.0	1000.000	197.0	V	176.0	-15.4	23.4	54.0
1184.168738	29.2	100.0	1000.000	155.0	H	98.0	-15.1	24.8	54.0
1500.006012	32.0	100.0	1000.000	121.0	V	126.0	-14.3	22.0	54.0
1560.522245	36.0	100.0	1000.000	100.0	H	144.0	-13.9	18.0	54.0
1660.310621	29.4	100.0	1000.000	130.0	V	166.0	-13.6	24.6	54.0
1690.782766	39.3	100.0	1000.000	100.0	V	206.0	-13.6	14.7	54.0
1820.643287	33.3	100.0	1000.000	147.0	V	228.0	-13.1	20.7	54.0
1950.903808	42.5	100.0	1000.000	144.0	H	184.0	-12.9	11.5	54.0

< Fig 7. Radiated emission result (1 000 MHz ~ 2 000 MHz)>



7. Sample Calculations

$$\begin{aligned} \text{dB}\mu\text{V} &= 20 \text{ Log}_{10}(\mu\text{V}/\text{m}) \\ \text{dB}\mu\text{V} &= \text{dBm} + 107 \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)} \end{aligned}$$

7.1 Example 1 :

■ 20.3 MHz

Class B Limit	= 250 μV = 48 dB μV
Reading	= 39.2 dB μV
$10^{(39.2\text{dB}\mu\text{V}/20)}$	= 91.2 μV
Margin	= 48 dB μV - 39.2 dB μV = 8.8 dB

7.2 Example 2 :

■ 66.7 MHz

Class B Limit	= 100 $\mu\text{V}/\text{m}$ = 40.0 dB $\mu\text{V}/\text{m}$
Reading	= 31.0 dB μV
Antenna Factor + Cable Loss = 5.8 dB	
Total	= 36.8 dB $\mu\text{V}/\text{m}$
Margin	= 40.0 dB $\mu\text{V}/\text{m}$ - 36.8 dB $\mu\text{V}/\text{m}$ = 3.2 dB



8. Recommendation & Conclusion

The data collected shows that the **LG Electronics Inc. LCD Monitor (Model Name: GX2MP)** was complies with §15.107 and 15.109 of the FCC Rules.