

LG Electronics
BLUETOOTH HEADSET
HBM-300
User's Guide

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES.
OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS :

- (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE AND
- (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION

IMPORTANT NOTE :

TO COMPLY WITH THE FCC RF EXPOSURE COMPLIANCE REQUIREMENTS, NO CHANGE TO THE ANTENNA OR THE DEVICE IS PERMITTED. ANY CHANGE TO THE ANTENNA OR THE DEVICE COULD RESULT IN THE DEVICE EXCEEDING THE RF EXPOSURE REQUIREMENTS AND VOID USER'S AUTHORITY TO OPERATE THE DEVICE.

Information to user :

CHANGES OR MODIFICATIONS NOT EXPRESSLY APPROVED BY THE PARTY RESPONSIBLE FOR COMPLIANCE COULD VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT

This manual was published by LG Electronics, Inc. in order to provide useful information in using the HBM-300 Bluetooth Headset in different situations. Any improvements or changes to this manual as a result of typographical errors, inaccuracies, or software/equipment upgrades, may be made by LG Electronics, Inc. at any time and without advanced notice. However, such changes will be incorporated into future editions of this manual. All rights reserved. LG Electronics, Inc., 2005 The Bluetooth official mark and logos are owned by the Bluetooth SIG, Inc. and any use of this mark by LG Electronics is under license.

Introduction

The LG HBM-300 Bluetooth Headset is a lightweight wireless Headset utilizing Bluetooth technology. This product can be used as an audio accessory for devices supporting either the Headset or Handsfree Bluetooth Profiles.

Included package

Bluetooth Headset
User's Guide
Additional Information
A/C Adapter
Carry case

Part description

Configuration

Choose Right or Left Ear Wearing Style

The LG Bluetooth Headset HBM-300 can be worn on either ear.

1. Rotate the earpiece to select your left or right ear.
2. Place the Headset on your ear
3. Place the ear-speaker into your ear.
4. Extend the ear ring then slip it over the top of your ear, manoeuvre the speaker gently into your ear, squeeze the ear ring closed until the Headset is held securely on your ear.

Charging

Before you can use your Headset, you need to charge it fully.

1. Open the DC jack cover on the bottom side of the Headset first.
2. Plug the charger into the DC jack outlet.
3. While charging, the blue LED indicator light on the Headset is lit, and will remain lit, until the Headset is fully charged.
4. Charge the Headset for approximately 2 hours or until the indicator lights go out.

Tip) Low Battery Warning

The Headset needs to be recharged when you hear a short beeping sound through the Headset's speaker at 7 second intervals and when you see the blue LED indicator flash quickly 5 times at 7 second intervals. You have 5 to 7 minutes of talktime remaining once the low battery warning indicators start.

Power On

Press in and hold the CALL Control button for more than 1 second to turn the Headset on.

Power Off

Press in and hold the CALL Control button for more than 4 seconds to turn the Headset off.

How to use

Pairing the Bluetooth Headset with the Handset

Before using your Headset for the first time, you must pair it with another Bluetooth device, such as a mobile phone. Follow the steps below for most devices.

1. **Turn the LG Bluetooth Headset HBM-300 on.**

Turn on the Headset by pressing and holding the CALL Control button for at least 1 second.

2. **Place the LG Bluetooth Headset HBM-300 in pairing mode.**

Press and hold the CALL Control button for at least 5 second while listening for a beeping sound. You should hear a series of beeps followed by a connection signal. The blue LED indicator light begins to flash once every second.

3. **Set your LG Bluetooth Headset HBM-300 to “discover”**

Follow the instruction guide for your phone. This usually involves going to a “setup”, “connect”, or “Bluetooth” menu on your phone and then selecting the option to “discover” or “add” a Bluetooth device.

4. **Your phone will find “HBM-300”**

You will be prompted to accept the pairing by pressing “Yes” or “Ok” on the Handset and to confirm with the passkey or PIN⁴ = 0000 (4 zeros). You will receive confirmation when pairing is complete. If pairing is unsuccessful, repeat steps 1-4.

If pairing is successful, the blue LED indicator light will flash in standby mode every 5 seconds. If pairing fails, the blue LED indicator light will flash once every second. Please repeat these steps.

NOTE) Pairing can be done with up to 3 Handsets maximum

- 1 The LG Bluetooth Headset HBM-300 stores up to 3 different Handset registrations in memory.
- 2 If you add a 4th Handset, the LG Bluetooth Headset HBM-300 will automatically remove the registration information of the least used Handset.
- 3 Priority is given to the Handset most recently paired.
- 4 When you want to change the Handset priority, try to connect manually from the Handset.

Tip)

Once a Handset is registered to the LG Bluetooth Headset HBM-300 , it will be stayed in paired status until deleted.

Basic usage of your LG Bluetooth HBM-300 Headset

1. **To answer a call**

Press the CALL Control button to capture and transfer the call to the headset.

2. **To reject a call**

Press the CALL Control button for at least 2 seconds.

3. **To end a call**

Press the CALL Control button for at least 2 seconds.

4. To make a call

When you are going to make a call with your HBM-300, simply press the CALL Control button and then the handset will dial the number you have dialed latest.

In case you make a call from the Handset, the call will (subject to phone settings) be automatically transferred to the Headset. If not automatically transferred, you can transfer the call manually by pressing the CALL Control button.

5. Last number redialing

Activate last number redial by pressing the CALL Control button on the Headset. (This will initiate voice dialing with some Handsets.)

6. Volume Control

Press the VOLUME UP or DOWN Button to increase or decrease the speaker volume.

- The Speaker volume is programmed for volume levels 0, 3, 6, 9, 12, and 15.

Transferring a call

To transfer a call from the Handset to the Headset, briefly press the Call Control button. You can transfer a call to the Headset without ending the call. In the other case where you want to transfer the call from Headset to Handset, all you do is just pressing the Call Control button shortly.

Holding Key function

To place a call on hold, press the CALL Control button and the VOLUME UP & DOWN button simultaneously for at least 1 second.

To turn Hold off, press the CALL Control button and the VOLUME UP & DOWN button simultaneously again.

Summary of Button Functions

Function	Current status	Action
Power On	Power off	Press CALL Control button for at least 1 second
Power Off	Power on	Press CALL Control button for at least 4 seconds
Speaker Volume Up	-	Press VOLUME UP button
Speaker Volume Down	-	Press VOLUME DOWN button briefly
Transferring a call (Handset -> Headset)	Talking	Press CALL Control button briefly
Pairing Mode	Power off	Press CALL Control button for at least 5 seconds when powered on
Answering a call	Ringing	Press CALL Control button briefly
Rejecting a call	Ringing	Press CALL Control button for at least 2 seconds.
Ending a call	Talking	Press CALL Control button for at least 2 seconds.
Last Number called	Ready	Press CALL Control button briefly

Hold On	Hold off	Press both Volume Up + Volume Down buttons briefly
Hold Off	Hold on	Press Volume Up + Volume Down simultaneously briefly

LED Indication

Function	HBM-300 status	LED Status
Operating (Blue LED)	Power off	Blue LED light remains on until the Call Control button is released
	Booting	Blue LED light remains on until initialization completes
	Idle	Blue LED light flashes once every 7 seconds
	Discoverable	Blue LED light flashes every 0.5 second
	Ringing	Blue LED light flashes 3 times per every 3 seconds until the call is answered or rejected, or dismissed.
	SCO Connection	Blue LED light flashes two times every 7 seconds
	Low Battery	Blue LED light flashes quickly 5 times at 7 second intervals
Charging (Blue LED)	No Charging	Blue LED light remains off
	Charging	Blue LED light remains on
	Charging Completed	Blue LED light remains off

Troubleshooting

1. Does not turn on	Check if the battery of the HBM-300 is fully discharged.	Charge the battery.
	Check whether the HOLD mode on the HBM-300 is on.	Release the Hold Mode button
2. Unable to communicate with the LG Bluetooth Headset HBM-300	Check whether the Handset supports the Headset or Handsfree Bluetooth Profiles.	Determine whether your Handset supports the Headset or Handsfree Bluetooth Profiles
	Check whether the battery of the HBM-300 is low.	Charge the battery
3. Unable to pair the HBM-300 with the Bluetooth device.	Check whether the Headset is on.	Press the Call Control button for at least 1 second to turn on the Headset.
	Check whether the Handset is on.	Turn on the power.
4. Low sound from the speaker	Check the speaker volume.	Increase the volume level.

Precautions (VISOR Image를 헤드셋으로 바꾸기)

Specification

ITEM	DESCRIPTION
Bluetooth Specification	V1.2
Supported Profile	Handsfree / Headset profile
Rx. Sensitivity	Typ. -88 dBm
Battery	3.7V, 125mAh Li-ion
Speaker	32Ω / 11Ø
MIC	-44dB / Omnidirectional
Standby Current	1mA (Avr.)
Talking Current	23mA (Avr.)
Standby Time	Over 120 Hr
Talking Time	Over 5 Hr
Operating Temperature	-20℃ ~ 60℃
Dimension	20.5mm (W) x 69mm (L) x 12mm (H)