

TEST REPORT

of

FCC Part 15 Subpart E §15.407

FCC ID: BEJIGCJ2PHE

Equipment Under Test : Car AVN
Model Name : IGCJ1PHE
Variant Model Name : IGCJ2PHE
Applicant : LG Electronics USA
Manufacturer : LG Electronics Inc.
Date of Receipt : 2022.12.07
Date of Test(s) : 2022.12.23 ~ 2023.02.16
Date of Issue : 2023.02.23

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.
- 3) This test report cannot be reproduced, except in full, without prior written permission of the Company.
- 4) The data marked ※ in this report was provided by the customer and may affect the validity of the test results.
We are responsible for all the information of this test report except for the data(※) provided by the customer.

Tested by:



Teo Kim

Technical
Manager:



Jinhyoung Cho

SGS Korea Co., Ltd. Gunpo Laboratory

INDEX

Table of contents

1. General Information -----	3
2. Transmitter Radiated Spurious Emissions -----	17
3. 26 dB Bandwidth & 99 % Bandwidth -----	36
4. 6 dB Bandwidth -----	96
5. Maximum Conducted Output Power -----	111
6. Peak Power Spectral Density -----	122
7. Antenna Requirement -----	160

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

1.2. Details of Applicant

Applicant : LG Electronics USA

Address : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, United States, 07632

Contact Person : Cho, Hee-jae

Phone No. : +1 201 470 2696

1.3. Details of Manufacturer

Company : LG Electronics Inc.

Address : 10, Magokjungang 10-ro, Gangseo-gu, Seoul, Korea, 07796

1.4. Description of EUT

Kind of Product	Car AVN
Brand Name	JAGUAR LAND ROVER
Model Name	IGCJ1PHE
Variant Model Name	IGCJ2PHE
Serial Number	211VIYKC97034
Power Supply	DC 12 V
Frequency Range	5 180 MHz ~ 5 240 MHz (Band 1: 11a/n_HT20, 11ac_VHT20) 5 190 MHz ~ 5 230 MHz (Band 1: 11n_HT40, 11ac_VHT40) 5 210 MHz (Band 1: 11ac_VHT80) 5 745 MHz ~ 5 825 MHz (Band 3: 11a/n_HT20, 11ac_VHT20) 5 755 MHz ~ 5 795 MHz (Band 3: 11n_HT40, 11ac_VHT40) 5 775 MHz (Band 3: 11ac_VHT80)
Modulation Technique	OFDM
Number of Channels	4 channels (Band 1: 11a/n_HT20, 11ac_VHT20) 2 channels (Band 1: 11n_HT40, 11ac_VHT40) 1 channel (Band 1: 11ac_VHT80) 5 channels (Band 3: 11a/n_HT20, 11ac_VHT20) 2 channels (Band 3: 11n_HT40, 11ac_VHT40) 1 channel (Band 3: 11ac_VHT80)
Antenna Type	External Antenna
Antenna Gain ※	Port 1 5 150 MHz ~ 5 250 MHz: 5 dB i 5 725 MHz ~ 5 850 MHz: 5 dB i
	Port 2 5 150 MHz ~ 5 250 MHz: 5 dB i 5 725 MHz ~ 5 850 MHz: 5 dB i
H/W Version	V9.0
S/W Version	IP36

1.5. Declaration by the Manufacturer

- The EUT is a slave without radar detection.
- The EUT Supports Transmit Power Control (TPC).
- WLAN 5G transmits on both Port 1 and Port 2.
- The EUT Only Supports UNII-1 Band and UNII-3 Band.

1.6. Automatically Discontinue Transmission

1.6.1. Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operating failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

1.6.2. Test Result of Automatically Discontinue Transmission

The device complies with this requirement, by automatically discontinue transmission when there's no more information to transmit and any case of operational failure occurs.

1.7. Test Equipment List

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Interval	Cal. Due
Signal Generator	R&S	SMA100B	106887	Oct. 13, 2022	Annual	Oct. 13, 2023
Signal Generator	R&S	SMBV100A	255834	May 25, 2022	Annual	May 25, 2023
Spectrum Analyzer	R&S	FSV30	103210	Dec. 07, 2022	Annual	Dec. 07, 2023
Spectrum Analyzer	Agilent	N9020A	MY53421758	Aug. 26, 2022	Annual	Aug. 26, 2023
Spectrum Analyzer	Agilent	N9030A	US51350132	Nov. 11, 2022	Annual	Nov. 11, 2023
Power Meter	Anritsu	ML2495A	1223004	Nov. 29, 2022	Annual	Nov. 29, 2023
Power Sensor	Anritsu	MA2411B	1207272	May 27, 2022	Annual	May 27, 2023
Power Sensor	R&S	NRP-Z81	100669	May 06, 2022	Annual	May 06, 2023
Attenuator	AEROFLEX / INMET	40AH2W-10	40G-1	Jun. 08, 2022	Annual	Jun. 08, 2023
Low Pass Filter	Mini-Circuits	NLP-1200+	V 8979400903-2	Feb. 09, 2023	Annual	Feb. 09, 2024
Low Pass Filter	WT MICROWAVE INC	WT-A1700-LS	WT151207001	Apr. 05, 2022	Annual	Apr. 05, 2023
High Pass Filter	Wainwright Instrument GmbH	WHKX6.0/18G-10SS	51	Jun. 15, 2022	Annual	Jun. 15, 2023
High Pass Filter	Wainwright Instrument GmbH	WHNX7.5/26.5G-6SS	15	May 31, 2022	Annual	May 31, 2023
DC Power Supply	R&S	HMP2020	020089489	May 17, 2022	Annual	May 17, 2023
Preamplifier	H.P.	8447F	2944A03909	Aug. 04, 2022	Annual	Aug. 04, 2023
Signal Conditioning Unit	R&S	SCU-18	10117	Jun. 13, 2022	Annual	Jun. 13, 2023
Preamplifier	TESTEK	TK-PA1840H	130016	Jan. 11, 2023	Annual	Jan. 11, 2024
Loop Antenna	Schwarzbeck Mess-Elektronik	FMZB 1519	1519-039	Aug. 23, 2021	Biennial	Aug. 23, 2023
Bilog Antenna	Schwarzbeck Mess-Elektronik	VULB 9163	390	Feb. 21, 2022	Annual	Feb. 21, 2023
Bilog Antenna	Schwarzbeck Mess-Elektronik	VULB 9163	01126	Feb. 09, 2023	Annual	Feb. 09, 2024
Horn Antenna	R&S	HF906	100326	Feb. 18, 2022	Annual	Feb. 18, 2023
Horn Antenna	R&S	HF907	102270	Mar. 03, 2022	Annual	Mar. 03, 2023
Horn Antenna	Schwarzbeck Mess-Elektronik	BBHA 9170	9170-540	Nov. 30, 2022	Annual	Nov. 30, 2023
EMI Test Receiver	R&S	ESU26	100109	Jan. 18, 2023	Annual	Jan. 18, 2024
Turn Table	Innco systems GmbH	DS 1200 S	N/A	N.C.R.	N/A	N.C.R.
Controller	Innco systems GmbH	CONTROLLER CO3000-4P	CO3000/963/3 8330516/L	N.C.R.	N/A	N.C.R.
Antenna Mast	Innco systems GmbH	MA4640-XP-ET	MA4640/536/3 8330516/L	N.C.R.	N/A	N.C.R.
Anechoic Chamber	SY Corporation	L x W x H (9.6 m x 6.4 m x 6.6 m)	N/A	N.C.R.	N/A	N.C.R.
Coaxial Cable	RFONE	MWX221-NMSNMS (4 m)	J1023142	Oct. 04, 2022	Semi-Annual	Apr. 04, 2023
Coaxial Cable	Qualwave Inc.	QA500-18-NN-10 (10 m)	22200114	Oct. 04, 2022	Semi-Annual	Apr. 04, 2023
Coaxial Cable	RFONE	PL360P-292M292M-1.5M-A	20200324002	Feb. 18, 2023	Semi-Annual	Aug. 18, 2023

Note;

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date

1.8. Summary of Test Result

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15 Subpart E		
Section	Test Item(s)	Result
15.205(a) 15.209(a) 15.407(b)(1) 15.407(b)(4)	Transmitter Radiated Spurious Emissions	Complied
15.407(a)	26 dB Bandwidth & 99 % Bandwidth	Complied
15.407(e)	6 dB Bandwidth	Complied
15.407(a)(1) 15.407(a)(3)	Maximum Conducted Output Power	Complied
15.407(a)(1) 15.407(a)(3)	Peak Power Spectral Density	Complied
15.207	AC Power Line Conducted Emission	N/A ¹⁾

Note;

- 1) The AC power line test was not performed because the EUT use battery power for operation and which do not operate from the AC power lines.

1.9. Test Procedure(s)

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 789033 D02 General UNII Test Procedures New Rules v02r01 were used in the measurement of the DUT.

1.10. Sample Calculation

Where relevant, the following sample calculation is provided:

1.10.1. Conducted Test

Offset value (dB) = Attenuator (dB) + Cable loss (dB)

1.10.2. Radiation Test

Field strength level (dB μ V/m) = Measured level (dB μ V) + Antenna factor (dB) + Cable loss (dB) - Amplifier gain (dB) + Duty factor (dB)

1.11. Information of software for test

- Using the software of PuTTY (Version 0.78) to testing of EUT.

1.12. Test Report Revision

Revision	Report Number	Date of Issue	Description
0	F690501-RF-RTL003846	2023.02.23	Initial

1.13. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty	
RF Output Power	0.32 dB	
Occupied Bandwidth	3.90 kHz	
Power Spectral Density	0.62 dB	
Radiated Emission, 9 kHz to 30 MHz	H	3.40 dB
	V	3.40 dB
Radiated Emission, below 1 GHz	H	4.50 dB
	V	5.10 dB
Radiated Emission, above 1 GHz	H	3.70 dB
	V	3.90 dB

All measurement uncertainty values are shown with a coverage factor $k = 2$ to indicate a 95 % level of confidence

1.14. Device Capabilities

Mode	SISO		MIMO	
	Ant.1	Ant.2	Ant.1	Ant.2
BT	O	X	X	X
WLAN2	X	O	X	X
WLAN5	O	O	O	O

1.15. Worst-Case Configuration and Test Mode

Radiated emission below 1GHz was performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit Low/Middle/High Channels for each mode.

Conducted tests were performed with the EUT set to transmit Low/Middle/High channels with highest output power.

Modulation	Bandwidth	Antenna	Frequency	Mode	Average Power (dBm)
OFDM	20 MHz	Ant.1	5 220	11n_HT20	0.77
				11ac_VHT20	<u>0.79</u>
		Ant.2		11n_HT20	2.34
				11ac_VHT20	<u>2.36</u>
		MIMO		11n_HT20	1.09
				11ac_VHT20	<u>1.12</u>
	40 MHz	Ant.1	5 190	11n_HT40	0.14
				11ac_VHT40	<u>0.15</u>
		Ant.2		11n_HT40	1.04
				11ac_VHT40	<u>1.59</u>
		MIMO		11n_HT40	0.07
				11ac_VHT40	<u>0.13</u>

Note ;

All radiated emission tests were performed with MIMO Mode as the worst case based on output power.

For duplicate test items among 802.11n_HT20, HT40, 802.11ac_VHT20 and VHT40 mode, the test mode with the highest power level was tested.

SISO

802.11a mode:

We found out the test mode with the highest power level after we analyze all the data rates. 6 Mbps data rate among 6 Mbps, 9 Mbps, 12 Mbps, 18 Mbps, 24 Mbps, 36 Mbps, 48 Mbps and 54 Mbps is chosen as worst case.

802.11ac_VHT20 mode:

We found out the test mode with the highest power level after we analyze all the data rates. MCS0 data rate among MCS0, MCS1, MCS2, MCS3, MCS4, MCS5, MCS6, MCS7 and MCS8 is chosen as worst case.

802.11ac_VHT40 mode:

We found out the test mode with the highest power level after we analyze all the data rates. MCS0 data rate among MCS0, MCS1, MCS2, MCS3, MCS4, MCS5, MCS6, MCS7, MCS8 and MCS9 is chosen as worst case.

802.11ac_VHT80 mode:

We found out the test mode with the highest power level after we analyze all the data rates. MCS0 data rate among MCS0, MCS1, MCS2, MCS3, MCS4, MCS5, MCS6, MCS7, MCS8 and MCS9 is chosen as worst case.

MIMO

802.11a mode:

We found out the test mode with the highest power level after we analyze all the data rates. 6 Mbps data rate among 6 Mbps, 9 Mbps, 12 Mbps, 18 Mbps, 24 Mbps, 36 Mbps, 48 Mbps and 54 Mbps is chosen as worst case.

802.11ac_VHT20 mode:

We found out the test mode with the highest power level after we analyze all the data rates. MCS0 data rate among MCS0, MCS1, MCS2, MCS3, MCS4, MCS5, MCS6, MCS7 and MCS8 is chosen as worst case.

802.11ac_VHT40 mode:

We found out the test mode with the highest power level after we analyze all the data rates. MCS0 data rate among MCS0, MCS1, MCS2, MCS3, MCS4, MCS5, MCS6, MCS7, MCS8 and MCS9 is chosen as worst case.

802.11ac_VHT80 mode:

We found out the test mode with the highest power level after we analyze all the data rates. MCS0 data rate among MCS0, MCS1, MCS2, MCS3, MCS4, MCS5, MCS6, MCS7, MCS8 and MCS9 is chosen as worst case.

1.16. Information of Variant Model

Model Names	Description
IGCJ1PHE	- Basic Model
IGCJ2PHE	- Same as basic model, - The only difference is the model name for Costa Rica, Thailand

Note;

All the test was performed with Basic model.

1.17. Duty Cycle of EUT

Regarding to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, II.B, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below.

Set RBW $\geq$ EBW if possible; otherwise, set RBW to the largest available value, Set VBW $\geq$ RBW.

Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100.

- SISO

Mode	Data Rate (Mbps)	Duty Cycle (%)	Correction Factor (dB)
802.11a	6	93.46	0.29
11ac_VHT20	MCS0	93.06	0.31
11ac_VHT40	MCS0	86.75	0.62
11ac_VHT80	MCS0	76.50	1.16

- MIMO

Mode	Data Rate (Mbps)	Duty Cycle (%)	Correction Factor (dB)
11a	6	93.46	0.29
11ac_VHT20	MCS0	93.06	0.31
11ac_VHT40	MCS0	87.01	0.60
11ac_VHT80	MCS0	76.50	1.16


Remark;

1. As measured duty cycles of EUT, all of mode and data rate keep constant period and are converted to log scale (power averaging) to compensate correction factor to result of average test items.
2. Duty Cycle (%) = (Tx on time / Tx on + off time) x 100
3. Correction Factor (dB) = 10 log (1 / Duty Cycle)


- Test plots

SISO


802.11a




802.11ac_VHT20



802.11ac_VHT40




802.11ac_VHT80




MIMO


802.11a




802.11ac_VHT20



802.11ac_VHT40



802.11ac_VHT80




2. Transmitter Radiated Spurious Emissions


2.1. Test Setup

2.1.1. Transmitter radiated spurious emissions


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated from 1 GHz to the 10th harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



2.2. Limit

According to § 15.407(b)

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dB m/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dB m/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dB m/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dB m/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dB m/MHz at the band edge.

According to § 15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (Meters)
0.009-0.490	2 400/F(kHz)	300
0.490-1.705	24 000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

2.3. Test Procedures

Radiated spurious emissions from the EUT were measured according to the dictates in section G of KDB 789033 D02 General UNII Test Procedures New Rules v02r01 and ANSI C63.10-2013.

2.3.1. Test Procedures for emission below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

2.3.2. Test Procedures for emission from above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 GHz and 1.5 meter above the ground at a 3 meter anechoic chamber test site above 1 GHz. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. For measurements below 1 GHz resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.
6. For measurements Above 1 GHz resolution bandwidth is set to 1 MHz, the video bandwidth is set to 3 MHz for peak measurements and as applicable for average measurements.

- II.G.4. Unwanted emissions measurements below 1 GHz.

Compliance shall be demonstrated using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.

- II.G.5. Unwanted maximum emissions measurements above 1 GHz.

Peak emission levels are measured by setting the analyzer as follows:

Set to RBW = 1 MHz, VBW ≥ 3 MHz, Detector = Peak, Sweep time = auto, Trace mode = Max hold.

- II.G.6. Average unwanted emissions measurements above 1 GHz.

Set to RBW = 1 MHz, VBW ≥ 3 MHz, Detector = power averaging (rms), Averaging type = power averaging (rms), Sweep time = auto, Perform a trace average of at least 100 traces. If the transmission is continuous, If the transmission is not continuous, the number of traces shall be increased by a factor of 1/x, where x is the duty cycle. For example, with 50 % duty cycle, at least 200 traces shall be averaged.

If tests are performed with the EUT transmitting at a duty cycle less than 98 %, a correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 % duty cycle. The correction factor is computed as follows:

- If power averaging (rms) mode was used in II.G.6.c)(iv), the correction factor is $10 \log (1 / x)$, where x is the duty cycle. For example, if the transmit duty cycle was 50 %, then 3 dB must be added to the measured emission levels.

- The test orthogonal plan of EUT was investigated with three axis described in the test setup photo.

The Z-axis was worst-case, all radiated testing of EUT was performed with **Z-axis**.

2.4. Test Result

Ambient temperature : (23 ± 1) °C
Relative humidity : 47 % R.H.

2.4.1. Radiated Spurious Emission below 1 000 MHz

The frequency spectrum from 9 MHz to 1 000 MHz was investigated. All reading values are peak values.



- Ant.1 + Ant.2

Radiated Emissions			Ant.	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
30.68	39.70	Quasi Peak	V	20.43	-27.78	32.35	40.00	7.65
72.32	39.60	Peak	H	18.67	-27.20	31.07	40.00	8.93
101.90	42.80	Peak	H	21.79	-27.08	37.51	43.50	5.99
375.08	40.30	Peak	H	24.80	-25.47	39.63	46.00	6.37
625.10	36.30	Peak	H	29.20	-26.21	39.29	46.00	6.71
900.09	34.80	Peak	H	32.10	-25.37	41.53	46.00	4.47

Remark;

1. Spurious emissions for all channels and modes were investigated and almost the same below 1 GHz.
2. Reported spurious emissions are in **11ac VHT20 (Band 3) / MCS0 / Low channel** as worst case among other modes.
3. Radiated spurious emission measurement as below.
(Actual = Reading + AF + AMP + CL)
4. According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.

- Test plots



2.4.2. Radiated Spurious Emission above 1 000 MHz

- MIMO

OFDM: 802.11a (Band 1)_Ant.1+Ant.2

A. Low Channel (5 180 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*4 500.00	41.60	Peak	V	31.90	-35.69	-	37.81	74.00	36.19
*4 500.00	32.05	Average	V	31.90	-35.69	0.29	28.55	54.00	25.45
*5 031.25	50.26	Peak	V	33.00	-35.25	-	48.01	74.00	25.99
*5 030.65	41.36	Average	V	33.00	-35.26	0.29	39.39	54.00	14.61
*5 150.00	43.25	Peak	V	33.30	-35.49	-	41.06	74.00	32.94
*5 150.00	35.35	Average	V	33.30	-35.49	0.29	33.45	54.00	20.55

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 220 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 240 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

OFDM: 802.11a (Band 3)_Ant.1+Ant.2

A. Low Channel (5 745 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 601.95	42.99	Peak	V	33.90	-33.80		43.09	68.23	25.14
5 699.22	45.86	Peak	V	33.90	-33.55		46.21	104.65	58.44
5 711.10	46.65	Peak	V	33.92	-33.55		47.02	108.34	61.32
5 723.80	45.22	Peak	V	33.95	-33.54		45.63	119.49	73.86

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 785 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 825 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 853.57	46.33	Peak	V	34.21	-33.58		46.96	114.09	67.13
5 867.81	47.75	Peak	V	34.24	-33.40		48.59	107.24	58.65
5 882.98	44.75	Peak	V	34.27	-33.23		45.79	99.32	53.53
5 973.05	44.65	Peak	V	34.55	-33.26		45.94	68.49	22.55

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

OFDM: 802.11ac_VHT20 (Band 1)_Ant.1+Ant.2

A. Low Channel (5 180 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 500.00	41.19	Peak	V	31.90	-35.69	-	37.40	74.00	36.60
*4 500.00	31.84	Average	V	31.90	-35.69	0.31	28.36	54.00	25.64
*5 031.25	49.76	Peak	V	33.00	-35.25	-	47.51	74.00	26.49
*5 028.28	40.85	Average	V	33.00	-35.27	0.31	38.89	54.00	15.11
*5 150.00	42.89	Peak	V	33.30	-35.49	-	40.70	74.00	33.30
*5 150.00	35.13	Average	V	33.30	-35.49	0.31	33.25	54.00	20.75

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 220 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 240 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

OFDM: 802.11ac_VHT20 (Band 3)_Ant.1+Ant.2

A. Low Channel (5 745 MHz)

Radiated Emissions			Ant.	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 601.33	42.10	Peak	V	33.90	-33.81	42.19	68.23	26.04
5 699.43	44.97	Peak	V	33.90	-33.55	45.32	104.81	59.49
5 716.22	47.42	Peak	V	33.93	-33.54	47.81	109.77	61.96
5 723.39	46.05	Peak	V	33.95	-33.54	46.46	118.56	72.10

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. Middle Channel (5 785 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

C. High Channel (5 825 MHz)

Radiated Emissions			Ant.	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 855.00	44.65	Peak	V	34.21	-33.56	45.30	110.83	65.53
5 860.46	45.77	Peak	V	34.22	-33.50	46.49	109.30	62.81
5 875.39	45.07	Peak	V	34.25	-33.31	46.01	104.94	58.93
5 971.21	46.02	Peak	V	34.54	-33.27	47.29	68.47	21.18

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

OFDM: 802.11ac_VHT40 (Band 1)_Ant.1+Ant.2

A. Low Channel (5 190 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 500.00	40.76	Peak	V	31.90	-35.69	-	36.97	74.00	37.03
*4 500.00	32.21	Average	V	31.90	-35.69	0.60	29.02	54.00	24.98
*5 101.49	47.21	Peak	V	33.20	-35.42	-	44.99	74.00	29.01
*5 037.76	37.69	Average	V	33.00	-35.22	0.60	36.07	54.00	17.93
*5 150.00	44.78	Peak	V	33.30	-35.49	-	42.59	74.00	31.41
*5 150.00	35.55	Average	V	33.30	-35.49	0.60	33.96	54.00	20.04

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. High Channel (5 230 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

OFDM: 802.11ac_VHT40 (Band 3)_Ant.1+Ant.2

A. Low Channel (5 755 MHz)

Radiated Emissions			Ant.	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 622.43	44.28	Peak	V	33.90	-33.56	44.62	68.23	23.61
5 697.79	45.22	Peak	V	33.90	-33.54	45.58	103.59	58.01
5 720.00	47.53	Peak	V	33.94	-33.54	47.93	110.83	62.90
5 721.34	48.25	Peak	V	33.94	-33.54	48.65	113.88	65.23

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

B. High Channel (5 795 MHz)

Radiated Emissions			Ant.	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 853.57	44.83	Peak	V	34.21	-33.58	45.46	114.09	68.63
5 871.72	45.34	Peak	V	34.24	-33.35	46.23	106.15	59.92
5 877.92	44.01	Peak	V	34.26	-33.28	44.99	103.07	58.08
5 942.72	44.27	Peak	V	34.47	-33.36	45.38	68.23	22.85

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

OFDM: 802.11ac_VHT80 (Band 1)_Ant.1+Ant.2

A. Middle Channel (5 210 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*4 500.00	40.88	Peak	V	31.90	-35.69	-	37.09	74.00	36.91
*4 500.00	31.96	Average	V	31.90	-35.69	1.16	29.33	54.00	24.67
*5 088.32	49.82	Peak	V	33.15	-35.38	-	47.59	74.00	26.41
*5 147.57	36.94	Average	V	33.30	-35.49	1.16	35.91	54.00	18.09
*5 150.00	49.46	Peak	V	33.30	-35.49	-	47.27	74.00	26.73
*5 150.00	37.16	Average	V	33.30	-35.49	1.16	36.13	54.00	17.87

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

OFDM: 802.11ac_VHT80 (Band 3)_Ant.1+Ant.2

A. Middle Channel (5 775 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 613.21	45.60	Peak	V	33.90	-33.66		45.84	68.23	22.39
5 662.56	44.31	Peak	V	33.90	-33.35		44.86	77.52	32.66
5 707.42	43.91	Peak	V	33.91	-33.56		44.26	107.31	63.05
5 722.77	42.75	Peak	V	33.95	-33.54		43.16	117.14	73.98
5 851.04	42.39	Peak	V	34.20	-33.61		42.98	119.86	76.88
5 869.88	42.79	Peak	V	34.24	-33.37		43.66	106.66	63.00
5 918.36	42.71	Peak	V	34.37	-33.17		43.91	73.14	29.23
5 958.57	43.23	Peak	V	34.52	-33.37		44.38	68.33	23.95

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

Remark;


1. “*” means the restricted band.
2. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using Peak / average detector mode if frequency was in restricted band. Otherwise the frequency was out of restricted band, only peak detector should be used.
3. Actual = Reading + AF + AMP + CL + (DF).
4. If frequency was out of restricted band, the calculation method for peak limit is same as below.

$$68.23 \text{ dB}_{\mu\text{V}}/\text{m} = \text{EIRP} - 20 \log (d) + 104.77 = -27 - 20 \log (3) + 104.77$$
5. In case of the emissions within $\pm 75 \text{ MHz}$ from band edge of band 3, limit should be adjusted to emission mask of 15.407(4)(i).
6. According to § 15.31(o), emission levels are not reported much lower than the limits by over 20 dB.
7. The maximized peak measured value complies with the average limit, to perform an average measurement is unnecessary.


- Test plots

802.11a_Ant.1 + Ant.2


Low channel Band edge (Peak) - Band 1




Low channel Band edge (Average) - Band 1



Low channel Band edge (Peak) - Band 3




High channel Band edge (Peak) - Band 3




802.11ac_VHT20_Ant.1 + Ant.2


Low channel Band edge (Peak) - Band 1




Low channel Band edge (Average) - Band 1



Low channel Band edge (Peak) - Band 3




High channel Band edge (Peak) - Band 3




802.11ac_VHT40_Ant.1 + Ant.2


Low channel Band edge (Peak) - Band 1



Low channel Band edge (Average) - Band 1



Low channel Band edge (Peak) - Band 3




High channel Band edge (Peak) - Band 3




802.11ac_VHT80_Ant.1 + Ant.2


Middle channel Band edge (Peak) - Band 1




Middle channel Band edge (Average) - Band 1



Middle channel Band edge (Peak) - Band 3




Middle channel Band edge (Peak) - Band 3



3. 26 dB Bandwidth & 99 % Bandwidth

3.1. Test Setup



3.2. Limit

None; for reporting purpose only.

3.3. Test Procedure

3.3.1. 26 dB Bandwidth

1. This measurement settings are specified in section II.C.1 of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set RBW = approximately 1 % of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

3.3.2. 99 % Bandwidth

1. This measurement settings are specified in section II.D of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set center frequency to the nominal EUT channel center frequency.
3. Set span = 1.5 times to 5.0 times the OBW.
4. Set RBW = 1 % to 5 % of the OBW.
5. Set VBW $\geq 3 \times$ RBW.
6. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
7. Use the 99 % power bandwidth function of the instrument (if available).
8. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99 % occupied bandwidth is the difference between these two frequencies.

In the result,

- DFS requirements are not applicable in the 5 150 MHz ~ 5 250 MHz.

3.4. Test Result

Ambient temperature : (23 ± 1) °C
Relative humidity : 47 % R.H.

- SISO_Ant.1

Test mode: 11a

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
U-NII 1	5 180	36	6	20.899	17.077
	5 220	44		20.859	17.077
	5 240	48		20.939	17.077
U-NII 3	5 745	149		21.019	17.019
	5 785	157		20.979	17.077
	5 825	165		21.219	17.135

Test mode: 11ac_VHT20

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
U-NII 1	5 180	36	MCS0	21.339	18.119
	5 220	44		21.339	18.119
	5 240	48		21.379	18.119
U-NII 3	5 745	149		21.499	18.119
	5 785	157		21.219	18.119
	5 825	165		21.339	18.119

Test mode: 11ac_VHT40

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
U-NII 1	5 190	38	MCS0	39.880	36.237
	5 230	46		39.960	36.353
U-NII 3	5 755	151		40.200	36.353
	5 795	159		40.200	36.353

Test mode: 11ac_VHT80

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
U-NII 1	5 210	42	MCS0	81.678	75.716
U-NII 3	5 775	155		82.158	75.716

- SISO_Ant.2

Test mode: 11a

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
U-NII 1	5 180	36	6	20.819	16.903
	5 220	44		20.779	16.961
	5 240	48		20.899	16.961
U-NII 3	5 745	149		20.819	17.019
	5 785	157		20.859	16.961
	5 825	165		20.779	16.961

Test mode: 11ac_VHT20

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
U-NII 1	5 180	36	MCS0	21.499	18.119
	5 220	44		21.379	18.061
	5 240	48		21.219	18.119
U-NII 3	5 745	149		21.419	18.119
	5 785	157		21.578	18.061
	5 825	165		21.459	18.177

Test mode: 11ac_VHT40

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
U-NII 1	5 190	38	MCS0	39.960	36.237
	5 230	46		40.280	36.237
U-NII 3	5 755	151		40.280	36.237
	5 795	159		40.200	36.353

Test mode: 11ac_VHT80

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
U-NII 1	5 210	42	MCS0	81.838	75.716
U-NII 3	5 775	155		81.518	75.716

- MIMO

Test mode: 11a

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)		99 % Bandwidth (MHz)	
				ANT 1	ANT 2	ANT 1	ANT 2
U-NII 1	5 180	36	6	21.019	21.339	17.019	16.961
	5 220	44		21.179	21.419	17.019	16.961
	5 240	48		20.939	21.219	17.077	17.019
U-NII 3	5 745	149		20.859	21.179	17.077	17.019
	5 785	157		21.099	21.379	17.077	16.961
	5 825	165		21.099	21.259	17.077	16.961

Test mode: 11ac_VHT20

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)		99 % Bandwidth (MHz)	
				ANT 1	ANT 2	ANT 1	ANT 2
U-NII 1	5 180	36	MCS0	21.499	21.379	18.119	17.829
	5 220	44		21.299	21.219	18.061	17.829
	5 240	48		21.499	21.259	18.119	17.887
U-NII 3	5 745	149		21.419	21.219	18.119	17.887
	5 785	157		21.379	21.459	18.177	17.829
	5 825	165		21.499	21.219	18.061	17.829

Test mode: 11ac_VHT40

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)		99 % Bandwidth (MHz)	
				ANT 1	ANT 2	ANT 1	ANT 2
U-NII 1	5 190	38	MCS0	40.200	39.720	36.237	36.237
	5 230	46		40.280	39.880	36.237	36.237
U-NII 3	5 755	151		40.120	39.640	36.353	36.237
	5 795	159		40.040	39.800	36.353	36.122

Test mode: 11ac_VHT80

Band	Frequency (MHz)	Ch.	Data Rate (Mbps)	26 dB Bandwidth (MHz)		99 % Bandwidth (MHz)	
				ANT 1	ANT 2	ANT 1	ANT 2
U-NII 1	5 210	42	MCS0	81.678	81.359	75.716	75.716
U-NII 3	5 775	155		81.998	81.838	75.716	75.716


- Test plots

- SISO_Ant.1


26 dB Bandwidth

802.11a (Band 1)


Low Channel
(5 180 MHz)



Middle Channel
(5 220 MHz)




High Channel
(5 240 MHz)




802.11a (Band 3)


Low Channel
(5 745 MHz)



Middle Channel
(5 785 MHz)




High Channel
(5 825 MHz)




802.11ac_VHT20 (Band 1)

Low Channel
(5 180 MHz)



Middle Channel
(5 220 MHz)



High Channel
(5 240 MHz)

