



Test Plots (GFSK)

Dwell Time (CH.0)




Test Plots (GFSK)

Dwell Time (CH.39)




Test Plots (GFSK)

Dwell Time (CH.78)




Test Plots (8DPSK)

Dwell Time (CH.0)




Test Plots (8DPSK)

Dwell Time (CH.39)




Test Plots (8DPSK)

Dwell Time (CH.78)




Test Plots ($\pi/4$ DQPSK)

Dwell Time (CH.0)




Test Plots ($\pi/4$ DQPSK)

Dwell Time (CH.39)



Test Plots ($\pi/4$ DQPSK)

Dwell Time (CH.78)



10.6 SPURIOUS EMISSIONS


10.6.1 CONDUCTED SPURIOUS EMISSIONS

Test Result : please refer to the plot below.

In order to simplify the report, attached plots were only the worst case channel and data rate.


Test Plots (8DPSK)- 30 MHz - 1 GHz

Spurious Emission (CH.39)




Test Plots (8DPSK)- 1 GHz – 3 GHz

Spurious Emission (CH.39)




Test Plots(8DPSK)- 3 GHz - 5 GHz

Spurious Emission (CH.39)




Test Plots (8DPSK)- 5 GHz - 7 GHz


Spurious Emission (CH.39)



Test Plots(8DPSK)- 7 GHz - 9 GHz
Spurious Emission (CH.39)




Test Plots(8DPSK)- 9 GHz - 11 GHz
Spurious Emission (CH.39)




Test Plots(8DPSK) 11 GHz - 13 GHz

Spurious Emission (CH.39)




Test Plots (8DPSK)- 13 GHz – 15 GHz

Spurious Emission (CH.39)




Test Plots(8DPSK)– 15 GHz - 17 GHz

Spurious Emission (CH.39)




Test Plots(8DPSK)- 17 GHz - 19 GHz

Spurious Emission (CH.39)




Test Plots (8DPSK)- 19 GHz - 21 GHz

Spurious Emission (CH.39)




Test Plots (8DPSK)- 21 GHz - 23 GHz

Spurious Emission (CH.39)



Test Plots (8DPSK)- 23 GHz - 25 GHz

Spurious Emission (CH.39)



10.6.2 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30MHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = $40 \cdot \log(\text{specific distance} / \text{test distance})$ (dB)
3. Limit line = specific Limits (dBuV) + Distance extrapolation factor
4. Radiated test is performed with hopping off.
5. The test results for below 30 MHz is correlated to an open site.
The result on OATS is about 2 dB higher than semi-anechoic chamber(10 m chamber)

Frequency Range : Below 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
2. Radiated test is performed with hopping off.

Frequency Range : Above 1 GHz

Operation Mode: CH Low(GFSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	51.06	-0.42	V	50.64	73.98	23.34	PK
4804	36.99	-0.42	V	36.57	53.98	17.41	AV
7206	50.42	5.40	V	55.815	73.98	18.17	PK
7206	37.11	5.40	V	42.505	53.98	11.48	AV
4804	51.64	-0.42	H	51.22	73.98	22.76	PK
4804	37.94	-0.42	H	37.52	53.98	16.46	AV
7206	50.98	5.40	H	56.375	73.98	17.61	PK
7206	37.43	5.40	H	42.825	53.98	11.16	AV

Operation Mode: CH Low($\pi/4$ DQPSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	50.89	-0.42	V	50.47	73.98	23.51	PK
4804	37.05	-0.42	V	36.63	53.98	17.35	AV
7206	50.45	5.40	V	55.845	73.98	18.14	PK
7206	37.42	5.40	V	42.815	53.98	11.17	AV
4804	51.90	-0.42	H	51.48	73.98	22.50	PK
4804	37.94	-0.42	H	37.52	53.98	16.46	AV
7206	50.88	5.40	H	56.275	73.98	17.71	PK
7206	37.59	5.40	H	42.985	53.98	11.00	AV

Operation Mode: CH Low(8DPSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	51.17	-0.42	V	50.75	73.98	23.23	PK
4804	37.83	-0.42	V	37.41	53.98	16.57	AV
7206	50.51	5.40	V	55.905	73.98	18.08	PK
7206	37.68	5.40	V	43.075	53.98	10.91	AV
4804	51.46	-0.42	H	51.04	73.98	22.94	PK
4804	37.94	-0.42	H	37.52	53.98	16.46	AV
7206	51.90	5.40	H	57.295	73.98	16.69	PK
7206	37.76	5.40	H	43.155	53.98	10.83	AV

Operation Mode: CH Mid(GFSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	53.20	-0.27	V	52.935	73.98	21.05	PK
4882	37.98	-0.27	V	37.715	53.98	16.27	AV
7323	50.02	5.42	V	55.44	73.98	18.54	PK
7323	36.95	5.42	V	42.37	53.98	11.61	AV
4882	53.41	-0.27	H	53.145	73.98	20.84	PK
4882	40.42	-0.27	H	40.155	53.98	13.83	AV
7323	50.23	5.42	H	55.65	73.98	18.33	PK
7323	37.23	5.42	H	42.65	53.98	11.33	AV

Operation Mode: CH Mid($\pi/4$ DQPSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	51.47	-0.27	V	51.205	73.98	22.78	PK
4882	37.14	-0.27	V	36.875	53.98	17.11	AV
7323	50.11	5.42	V	55.53	73.98	18.45	PK
7323	37.68	5.42	V	43.1	53.98	10.88	AV
4882	51.80	-0.27	H	51.535	73.98	22.45	PK
4882	38.10	-0.27	H	37.835	53.98	16.15	AV
7323	50.43	5.42	H	55.85	73.98	18.13	PK
7323	37.09	5.42	H	42.51	53.98	11.47	AV

Operation Mode: CH Mid(8DPSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	50.89	-0.27	V	50.625	73.98	23.36	PK
4882	37.59	-0.27	V	37.325	53.98	16.66	AV
7323	50.12	5.42	V	55.54	73.98	18.44	PK
7323	36.25	5.42	V	41.67	53.98	12.31	AV
4882	51.37	-0.27	H	51.105	73.98	22.88	PK
4882	38.16	-0.27	H	37.895	53.98	16.09	AV
7323	50.74	5.42	H	56.16	73.98	17.82	PK
7323	37.22	5.42	H	42.64	53.98	11.34	AV

Operation Mode: CH High(GFSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	50.84	-0.67	V	50.17	73.98	23.81	PK
4960	37.68	-0.67	V	37.01	53.98	16.97	AV
7440	49.38	5.70	V	55.08	73.98	18.90	PK
7440	36.30	5.70	V	42.00	53.98	11.98	AV
4960	52.40	-0.67	H	51.73	73.98	22.25	PK
4960	37.74	-0.67	H	37.07	53.98	16.91	AV
7440	49.75	5.70	H	55.45	73.98	18.53	PK
7440	36.42	5.70	H	42.12	53.98	11.86	AV

Operation Mode: CH High($\pi/4$ DQPSK)


Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	51.05	-0.67	V	50.38	73.98	23.60	PK
4960	37.52	-0.67	V	36.85	53.98	17.13	AV
7440	49.87	5.70	V	55.57	73.98	18.41	PK
7440	36.39	5.70	V	42.09	53.98	11.89	AV
4960	51.21	-0.67	H	50.54	73.98	23.44	PK
4960	37.70	-0.67	H	37.03	53.98	16.95	AV
7440	50.17	5.70	H	55.87	73.98	18.11	PK
7440	36.40	5.70	H	42.10	53.98	11.88	AV

Operation Mode: CH High (8DPSK)

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	50.89	-0.67	V	50.22	73.98	23.76	PK
4960	37.66	-0.67	V	36.99	53.98	16.99	AV
7440	50.22	5.70	V	55.92	73.98	18.06	PK
7440	36.27	5.70	V	41.97	53.98	12.01	AV
4960	51.04	-0.67	H	50.37	73.98	23.61	PK
4960	37.73	-0.67	H	37.06	53.98	16.92	AV
7440	50.50	5.70	H	56.20	73.98	17.78	PK
7440	36.36	5.70	H	42.06	53.98	11.92	AV


RESULT PLOTS (Worst case : X-H)

Radiated Spurious Emissions plot – Average Reading (GFSK, Ch.0 2nd Harmonic)



Date: 20.SEP.2018 08:03:01

Radiated Spurious Emissions plot – Peak Reading (GFSK, Ch.0 2nd Harmonic)



Date: 20.SEP.2018 08:04:24

Note:

Plot of worst case are only reported.

10.6.3 RADIATED RESTRICTED BAND EDGES

Operation Mode	Normal(GFSK)
Operating Frequency	2402 MHz, 2480 MHz
Channel No	CH 0, CH 78

Frequency [MHz]	Reading [dBuV]	A.F + C.L + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	19.31	34.42	H	53.73	73.98	20.25	PK
2390.0	10.28	34.42	H	44.70	53.98	9.28	AV
2390.0	22.17	34.42	V	56.59	73.98	17.39	PK
2390.0	11.72	34.42	V	46.14	53.98	7.84	AV
2483.5	32.24	33.59	H	65.83	73.98	8.15	PK
2483.5	12.45	33.59	H	46.04	53.98	7.94	AV
2483.5	29.33	33.59	V	62.92	73.98	11.06	PK
2483.5	12.30	33.59	V	45.89	53.98	8.09	AV

Operation Mode	EDR(8DPSK)
Operating Frequency	2402 MHz, 2480 MHz
Channel No	CH 0, CH 78


Frequency [MHz]	Reading [dBuV]	A.F + C.L + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	19.45	34.42	H	53.87	73.98	20.11	PK
2390.0	10.59	34.42	H	45.01	53.98	8.97	AV
2390.0	21.61	34.42	V	56.03	73.98	17.95	PK
2390.0	11.58	34.42	V	46.00	53.98	7.98	AV
2483.5	31.96	33.59	H	65.55	73.98	8.43	PK
2483.5	12.39	33.59	H	45.98	53.98	8.01	AV
2483.5	29.14	33.59	V	62.73	73.98	11.25	PK
2483.5	12.92	33.59	V	46.51	53.98	7.47	AV

Operation Mode	EDR(π /4DQPSK)
Operating Frequency	2402 MHz, 2480 MHz
Channel No	CH 0, CH 78


Frequency [MHz]	Reading [dBuV]	A.F + C.L + D.F [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	19.04	34.42	H	53.46	73.98	20.52	PK
2390.0	10.95	34.42	H	45.37	53.98	8.61	AV
2390.0	22.33	34.42	V	56.75	73.98	17.23	PK
2390.0	11.70	34.42	V	46.12	53.98	7.86	AV
2483.5	33.10	33.59	H	66.69	73.98	7.30	PK
2483.5	12.47	33.59	H	46.06	53.98	7.92	AV
2483.5	29.12	33.59	V	62.71	73.98	11.27	PK
2483.5	13.15	33.59	V	46.74	53.98	7.24	AV

RESULT PLOTS (Worst case : X-V)


Radiated Restricted Band Edges plot – Average Reading (GFSK, Ch.78)




Radiated Restricted Band Edges plot – Peak Reading (GFSK, Ch.78)





Radiated Restricted Band Edges plot – Average Reading (8DPSK, Ch.78)



Radiated Restricted Band Edges plot – Peak Reading (8DPSK, Ch.78)



Radiated Restricted Band Edges plot – Average Reading ($\pi/4$ DQPSK, Ch.78)

Radiated Restricted Band Edges plot – Peak Reading ($\pi/4$ DQPSK, Ch.78)

Note:

Plot of worst case are only reported.

10.6.4 RECEIVER SPURIOUS EMISSIONS

Frequency Range : Below 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Frequency Range : Above 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

11 LIST OF TEST EQUIPMENT

Conducted Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216 / LISN	12/20/2017	Annual	102245
Rohde & Schwarz	ESCI / Test Receiver	06/27/2018	Annual	100033
ESPAC	SU-642 / Temperature Chamber	03/30/2018	Annual	0093008124
Agilent	N9020A / Signal Analyzer	06/08/2018	Annual	MY51110085
Agilent	N9030A / Signal Analyzer	11/22/2017	Annual	MY49431210
Agilent	N1911A / Power Meter	04/16/2018	Annual	MY45100523
Agilent	N1921A / Power Sensor	04/16/2018	Annual	MY52260025
Agilent	87300B / Directional Coupler	11/20/2017	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	06/07/2018	Annual	05001
Hewlett Packard	E3632A / DC Power Supply	06/26/2018	Annual	KR75303960
Agilent	8493C / Attenuator(10 dB)	07/10/2018	Annual	07560
Rohde & Schwarz	EMC32 / Software	N/A	N/A	N/A
HCT CO., LTD.	FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	N/A	N/A
Rohde & Schwarz	CBT / Bluetooth Tester	05/17/2018	Annual	100422

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Radiated Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Innco system	CO3000 / Controller(Antenna mast)	N/A	N/A	CO3000-4p
Innco system	MA4640/800-XP-EP / Antenna Position Tower	N/A	N/A	N/A
Audix	EM1000 / Controller	N/A	N/A	060520
Audix	Turn Table	N/A	N/A	N/A
Rohde & Schwarz	Loop Antenna	04/19/2017	Biennial	1513-175
Schwarzbeck	VULB 9160 / Hybrid Antenna	08/09/2018	Annual	3368
Schwarzbeck	BBHA 9120D / Horn Antenna	05/02/2017	Biennial	9120D-937
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	12/04/2017	Biennial	BBHA9170541
Rohde & Schwarz	FSP(9 kHz ~ 30 GHz) / Spectrum Analyzer	09/03/2018	Annual	100688
Rohde & Schwarz	FSV40-N / Spectrum Analyzer	09/28/2018	Annual	101068-SZ
Wainwright Instruments	WHK3.0/18G-10EF / High Pass Filter	06/07/2018	Annual	8
Wainwright Instruments	WHFX7.0/18G-8SS / High Pass Filter	05/09/2018	Annual	29
Wainwright Instruments	WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter	06/29/2018	Annual	2
Wainwright Instruments	WRCJV5100/5850-40/50-8EEK / Band Reject Filter	01/03/2018	Annual	2
Api tech.	18B-03 / Attenuator (3 dB)	06/07/2018	Annual	1
Agilent	8493C-10 / Attenuator(10 dB)	07/17/2018	Annual	08285
CERNEX	CBLU1183540 / Power Amplifier	07/10/2018	Annual	22964
CERNEX	CBL06185030 / Power Amplifier	07/10/2018	Annual	22965
CERNEX	CBL18265035 / Power Amplifier	01/10/2018	Annual	22966
CERNEX	CBL26405040 / Power Amplifier	06/29/2018	Annual	25956
TESCOM	TC-3000C / Bluetooth Tester	03/27/2018	Annual	3000C000276

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

12 ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-1810-FC001-P
2	HCT-RF-1810-FC002-P
3	HCT-RF-1810-FC003-P
4	HCT-RF-1810-FC004-P