


|                                                                                   |                                                                                                                          |                                                                                                                                                                                                                                                                                                                                            |                                                         |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|
|  | <b>ESTECH Co., Ltd.</b><br>Rm. 1015, World Venture Center II,<br>426-5 Gasan-dong, Guncheon-gu,<br>Seoul, 158-803, Korea |     | <b>Electromagnetic<br/>Interference<br/>Test Report</b> |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|

## Test Report for FCC

|                                                                                                                                                                                                                                                                                                               |                                                                                                                               |                                                      |                                             |                     |    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|---------------------------------------------|---------------------|----|
| Report Number                                                                                                                                                                                                                                                                                                 |                                                                                                                               | ESTF150603-012                                       |                                             |                     |    |
| Applicant                                                                                                                                                                                                                                                                                                     | Company name                                                                                                                  | LG Electronics Inc.                                  |                                             |                     |    |
|                                                                                                                                                                                                                                                                                                               | Address                                                                                                                       | 459-9, Kasan-dong, Keumchun-ku, Seoul 153-023, Korea |                                             |                     |    |
|                                                                                                                                                                                                                                                                                                               | Telephone                                                                                                                     | 82-2-850-3860                                        |                                             |                     |    |
| Product                                                                                                                                                                                                                                                                                                       | Product name                                                                                                                  | GSM Phone with Bluetooth                             |                                             |                     |    |
|                                                                                                                                                                                                                                                                                                               | Model No.                                                                                                                     | KG920                                                | Manufacturer                                | LG Electronics Inc. |    |
|                                                                                                                                                                                                                                                                                                               | Serial No.                                                                                                                    | NONE                                                 | Country of origin                           | KOREA               |    |
| Test date                                                                                                                                                                                                                                                                                                     | 2006-01-20 ~2006-03-27                                                                                                        |                                                      | Date of issue                               | 27-Mar-06           |    |
| Testing location                                                                                                                                                                                                                                                                                              | ESTECH. Co., Ltd.<br>97-1 Hoiuk-Ri Majang-Myon, Icheon-city, KyungKi-Do, Korea                                                |                                                      |                                             |                     |    |
| Standard                                                                                                                                                                                                                                                                                                      | FCC PART 15 2005 , ANSI C 63.4 2003                                                                                           |                                                      |                                             |                     |    |
| Test item                                                                                                                                                                                                                                                                                                     | <input checked="" type="checkbox"/> Conducted Emission                                                                        | <input type="checkbox"/> Class A                     | <input checked="" type="checkbox"/> Class B | Test result         | OK |
|                                                                                                                                                                                                                                                                                                               | <input checked="" type="checkbox"/> Radiated Emission                                                                         | <input type="checkbox"/> Class A                     | <input checked="" type="checkbox"/> Class B | Test result         | OK |
| Measurement facility registration number                                                                                                                                                                                                                                                                      |                                                                                                                               | 94696                                                |                                             |                     |    |
| Tested by                                                                                                                                                                                                                                                                                                     | Engineer J.H.Kim  (signature)             |                                                      |                                             |                     |    |
| Reviewed by                                                                                                                                                                                                                                                                                                   | Engineering Manager J.M.Yang  (signature) |                                                      |                                             |                     |    |
| Abbreviation                                                                                                                                                                                                                                                                                                  | OK, Pass = Passed, Fail = Failed, N/A = not applicable                                                                        |                                                      |                                             |                     |    |
| <p>* Note</p> <ul style="list-style-type: none"> <li>- This test report is not permitted to copy partly without our permission</li> <li>- This test result is dependent on only equipment to be used</li> <li>- This test result based on a single evaluation of one sample of the above mentioned</li> </ul> |                                                                                                                               |                                                      |                                             |                     |    |

## Contents

|                                                      |    |
|------------------------------------------------------|----|
| 1. Laboratory Information .....                      | 4  |
| 2. Description of EUT .....                          | 5  |
| 3. Test Standards .....                              | 6  |
| 4. Measurement condition .....                       | 7  |
| 5. Carrier Frequency Separation .....                | 10 |
| 5.1 Test procedure .....                             | 10 |
| 5.2 Test instruments and measurement setup .....     | 10 |
| 5.3 Measurement results .....                        | 10 |
| 5.4 Trace data .....                                 | 11 |
| 6. Maximum Peak Output Power .....                   | 12 |
| 7. Number of Hopping Frequency .....                 | 13 |
| 7.1 Test procedure .....                             | 13 |
| 7.2 Measurement results .....                        | 13 |
| 8. Time of Occupancy (Dwell Time) .....              | 15 |
| 8.1 Test procedure .....                             | 15 |
| 8.2 Test instruments and measurement setup .....     | 15 |
| 8.3 Measurement results .....                        | 15 |
| 8.4 Trace data .....                                 | 15 |
| 9. Band-Edge and Out of Band Emissions .....         | 17 |
| 9.1 Test procedure .....                             | 17 |
| 9.2 Test instruments and measurement setup .....     | 17 |
| 9.3 Measurement results .....                        | 17 |
| 9.4 Trace data of band-edge & out of emissioin ..... | 18 |

10. Measurement of radiated emission ..... 20

10.1 Measurement equipment ..... 20

10.2 Environmental conditions ..... 20

10.3 Test data ..... 21

11. Measurement of conducted emission ..... 25

11.1 Measurement equipment ..... 25

11.2 Environmental conditions ..... 25

11.3 Test data ..... 26

12. Antenna Requirement ..... 27

12.1 Standard Applicable ..... 27

12.2 Anetenna connected construction ..... 27

Appendix 1. Spectral diagram

## 1. Laboratory Information

### 1.1 General

This EUT (Equipment Under Test) has been shown to be capable of compliance with the applicable technical standards and is tested in accordance with the measurement procedures as indicated in this report.

ESTECH Lab attests to accuracy of test data. All measurement reported herein were performed by ESTECH Co., Ltd.

ESTECH Lab assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

### 1.2 Test Lab.

Corporation Name : ESTECH Co. Ltd

Head Office : Rm 1015, World Venture Center II, 426-5, Gasan-dong, Geumcheon-gu, Seoul, Korea  
(Safety & Telecom. Test Lab)

EMC Test Lab : 58-1 Osan-Ri, GaNam-Myon, YeoJoo-Gun, KyungKi-Do, Korea  
97-1 Hoiuk-Ri Majang-Myon, Icheon-city, KyungKi-Do, Korea

### 1.3 Official Qualification(s)

MIC : Granted Accreditation from Ministry of Information & Communication for EMC, Safety and Telecommunication

KOLAS : Accredited Lab By Korea Laboratory Accreditation Schema base on CENELEC requirements

FCC : Filed Laboratory at Federal Communications Commission

VCCI : Granted Accreditation from Voluntary Control Council for Interference from ITE

## 2. Description of EUT

### 2.1 Summary of Equipment Under Test (Bluetooth)

Product Name : GSM Phone with Bluetooth  
 Model Number : KG920  
 Modulation Type : FHSS, GFSK  
 Transfer Rate : 1Mbps  
 Number of Channels : 79 ch  
 Serial Number : NONE  
 Manufacturer : LG Electronics Inc.  
 Country of origin : KOREA  
 Rating : 100-240V 50/60Hz 150-100mA / DC 5.2V 800mA  
 Receipt Date : 2006-01-20

### 2.2 General descriptions of EUT

The LG GSM Phone with Bluetooth offers Bluetooth as a feature. The Bluetooth frequency hopping transceiver is designed to operate between 2400 and 2483.5MHz.

### 3. Test Standards

#### Test Standard : FCC PART 15 (2005)

This Standard sets out the regulations under which an intentional, unintentional, or incidental radiator may be operated without an individual license. It also contains the technical specifications, administrative requirements and other conditions relating to the marketing of Part 15 devices.

#### Test Method : ANSI C 63.4 (2003)

This standard sets forth uniform methods of measurement of radio-frequency (RF) signals and noise emitted from both unintentional and intentional emitters of RF energy in the frequency range 9 kHz to 40 GHz. Methods for the measurement of radiated and AC power-line conducted radio noise are covered and may be applied to any such equipment unless otherwise specified by individual equipment requirements. These methods cover measurement of certain devices that deliberately radiate energy, such as intentional emitters, but does not cover licensed transmitters. This standard is not intended for certification/approval of avionic equipment or for industrial, scientific, and medical (ISM) equipment. These methods apply to the measurement of individual units or systems comprised of multiple units.

#### Summary of Test Results

| Applied Standard : 47 CFR Part 15, Subpart C |                                             |        |                      |           |
|----------------------------------------------|---------------------------------------------|--------|----------------------|-----------|
| Standard                                     | Test Type                                   | Result | Remark               | Limit     |
| 15.207                                       | AC Power Conducted Emission                 | Pass   | Meet the requirement |           |
| 15.247(a)(1)                                 | Carrier Frequency Separation & 20 Bandwidth | Pass   | Meet the requirement | >25kHz    |
| 15.247(b)                                    | Maximum Peak output power                   | Pass   | Meet the requirement | 30dBm(1W) |
| 15.247(a)(1)(ii)                             | Number of Hopping Frequency                 | Pass   | Meet the requirement | >75       |
| 15.247(c)                                    | Transmitter Radiated Emission               | Pass   | Meet the requirement |           |
| 15.247(a)(1)(iii)                            | Time of Occupancy (Dwell Time)              | Pass   | Meet the requirement | <400ms    |
| 15.247(c)                                    | Band Edge Measurement                       | Pass   | Meet the requirement |           |

## 4. Measurement Condition

### 4.1 EUT Operation.

#### a. Channel

| Ch. | Frequency | Ch. | Frequency |
|-----|-----------|-----|-----------|
| 0   | 2402 MHz  | 40  | 2442 MHz  |
| 1   | 2403 MHz  | 41  | 2443 MHz  |
| 2   | 2404 MHz  | 42  | 2444 MHz  |
| 3   | 2405 MHz  | 43  | 2445 MHz  |
| 4   | 2406 MHz  | ... | ...       |
| ... | ...       | 78  | 2480 MHz  |
| 39  | 2441 MHz  |     |           |

b. Measurement Channel : Low(2402MHz), Middle(2441MHz),High(2480MHz)


c. Test Mode : FHSS, GFSK

d. Test rate : 1Mbps

## 4.2 EUT Operation.

- \* The EUT was in the following operation mode during all testing
- \* The operational conditions of the EUT was determined by the manufacturer according to the typical use of the EUT with respect to the expected highest level of emission

## 4.3 Configuration and Peripherals



#### 4.4 EUT and Support equipment

| Equipment Name           | Model Name   | S/N           | Manufacturer        | Remark (FCC ID) |
|--------------------------|--------------|---------------|---------------------|-----------------|
| GSM Phone with Bluetooth | KG920        | NONE          | LG Electronics Inc. | EUT             |
| Travel Adapter           | TA-22GR2     | 051114BE00866 | LG Electronics Inc. | —               |
| Bluetooth Tester         | TC-3000A     | 3000A570224   | TESCOM Co., Ltd.    |                 |
| Antenna                  | MBMMC-2600-2 | 4104186       | GAMANU              |                 |
| Headset                  | NONE         | NONE          | LG Electronics Inc. |                 |
|                          |              |               |                     |                 |
|                          |              |               |                     |                 |

#### 4.5 Cable Connecting

| Start Equipment          |          | End Equipment |          | Cable Standard |          | Remark |
|--------------------------|----------|---------------|----------|----------------|----------|--------|
| Name                     | I/O port | Name          | I/O port | Length         | Shielded |        |
| GSM Phone with Bluetooth | Power    | Adapter       | —        | 1              | Y        | —      |
| GSM Phone with Bluetooth | Headset  | Headset       | —        | 1              | Y        | —      |
|                          |          |               |          |                |          |        |
|                          |          |               |          |                |          |        |
|                          |          |               |          |                |          |        |
|                          |          |               |          |                |          |        |

## 5. Carrier Frequency Separation

### 5.1 Test procedure

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

### 5.2 Test instruments and measurement setup

The spectrum analyzer is set to as following.

- . RBW= 300KHz
- . VBW= 300KHz
- . Span= 3MHz
- . Sweep= suitable duration based on the EUT specification.

#### 6dB Bandwidth Test Instruments

| Description                | Model        | Serial Number |
|----------------------------|--------------|---------------|
| Spectrum Analyzer          | E4407B       | US42041281    |
| Bluetooth Tester           | TC-3000A     | 3000A570224   |
| Dual Directional Coupler   | 778D         | 16502         |
| -Spectrum Analyzer <=> EUT | Loss: 21.3dB | -             |

### 5.3 Measurement results

|             |              |                            |            |
|-------------|--------------|----------------------------|------------|
| EUT         | Bluetooth    | MODEL                      | KG920      |
| MODE        | FHSS         | ENVIRONMENTAL<br>CONDITION | 24℃, 40%RH |
| INPUT POWER | 120Vac, 60Hz |                            |            |

| CHANNEL | Channel Frequency<br>(MHz) | Bandwidth at<br>20dB below(kHz) | Channel<br>Separation<br>(MHz) | Limit<br>(kHz) | PASS<br>/FAIL |
|---------|----------------------------|---------------------------------|--------------------------------|----------------|---------------|
| 39      | 2441                       | 921.7                           | 1.0                            | >25            | PASS          |



**ESTECH Co., Ltd.**


Rm 1015, World Venture Center II,  
426-5 Gasan-dong, Guncheon-gu,  
Seoul, 158-803, Korea




**Electromagnetic  
Interference  
Test Report**

## 5.4 Trace data

### Channel Separation



### 20dB bandwidth



## 6. MAXIMUM PEAK OUTPUT POWER

### 6.1 Test procedure

The transmitter antenna terminal is connected to the input of a Spectrum Analyzer. Measurement is made while EUT is operating in transmission mode at the appropriate center frequency. The maximum peak output power measurement is 30dBm.

#### Maximum Peak Output Power Test Instruments

| Description                | Model        | Serial Number |
|----------------------------|--------------|---------------|
| Spectrum Analyzer          | E4407B       | US42041281    |
| Bluetooth Tester           | TC-3000A     | 3000A570224   |
| Dual Directional Coupler   | 778D         | 16502         |
| -Spectrum Analyzer <=> EUT | Loss: 21.3dB | -             |

### 6.2 Measurement results

|             |              |                            |            |
|-------------|--------------|----------------------------|------------|
| EUT         | Bluetooth    | MODEL                      | KG920      |
| MODE        | GFSK, DH5    | ENVIRONMENTAL<br>CONDITION | 23℃, 40%RH |
| INPUT POWER | 120Vac, 60Hz |                            |            |

| CHANNEL | Channel<br>Frequency<br>(MHz) | Peak Power Output(dBm) |        | Limit[1W]<br>(dBm) | PASS/<br>FAIL |
|---------|-------------------------------|------------------------|--------|--------------------|---------------|
|         |                               | (dBm)                  | (W)    |                    |               |
| 0       | 2402                          | -0.86                  | 0.0008 | 30.0               | PASS          |
| 39      | 2441                          | 0.68                   | 0.0012 | 30.0               | PASS          |
| 78      | 2480                          | 0.77                   | 0.0012 | 30.0               | PASS          |

## 7. Number of Hopping Frequency

### 7.1 Test procedure

According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz–2483.5MHz bands shall use at least 75 hopping frequencies.

### 7.2 Test instruments and measurement setup

The spectrum analyzer is set to as following.

- . RBW= 300KHz
- . VBW= 300KHz
- . Span= the frequency band of operation
- . Sweep= suitable duration based on the EUT specification.

#### The Number of Hopping Frequency Test Instruments

| Description                | Model        | Serial Number |
|----------------------------|--------------|---------------|
| Spectrum Analyzer          | E4407B       | US42041281    |
| Bluetooth Tester           | TC-3000A     | 3000A570224   |
| Dual Directional Coupler   | 778D         | 16502         |
| –Spectrum Analyzer <=> EUT | Loss: 21.3dB |               |

### 7.3 Measurement results

|              |                      |                            |            |
|--------------|----------------------|----------------------------|------------|
| EUT          | Bluetooth            | MODEL                      | KG920      |
| MODE         | FHSS                 | ENVIRONMENTAL<br>CONDITION | 23℃, 40%RH |
| INPUT POWER  | 120Vac, 60Hz         |                            |            |
| Number of CH | Limit (Number of CH) | PASS/FAIL                  |            |
| 79           | >75                  | PASS                       |            |





**ESTECH Co., Ltd.**

Rm 1015, World Venture Center II,  
426-5 Gasan-dong, Guncheon-gu,  
Seoul, 158-803, Korea



**Electromagnetic  
Interference  
Test Report**

## 7.4 Trace data



## 8. Time of Occupancy (Dwell Time)

### 8.1 Test procedure

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz–2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

### 8.2 Test instruments and measurement setup

The spectrum analyzer is set to as following.

- . RBW= 1MHz
- . VBW= 1MHz
- . Span= zero
- . Sweep= suitable duration based on the EUT specification.

#### The Time of Occupancy Test Instruments


| Description                | Model        | Serial Number |
|----------------------------|--------------|---------------|
| Spectrum Analyzer          | E4407B       | US42041281    |
| Bluetooth Tester           | TC-3000A     | 3000A570224   |
| Dual Directional Coupler   | 778D         | 16502         |
| -Spectrum Analyzer <=> EUT | Loss: 21.3dB |               |

### 8.3 Measurement results


| EUT         | Bluetooth                   | MODEL                      | KG920      |
|-------------|-----------------------------|----------------------------|------------|
| MODE        | FHSS                        | ENVIRONMENTAL<br>CONDITION | 23℃, 40%RH |
| INPUT POWER | 120Vac, 60Hz                |                            |            |
| Channel     | Pulse Time(ms)<br>(DH1/DH5) | Limit<br>(ms)              | PASS/FAIL  |
| 39          | 0.45/2.95                   | 400.0                      | PASS       |

## 8.4 Trace data

### DH1



### DH5



## 9. band-edge and out of band emissions.

### 9.1 Test procedure

The radio frequency power at 20dB down from the highest inband power level is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency. The band edge&out of band emission shall be at least 20dB below of the highest inband power level.

### 9.2 Test instruments and measurement setup

The spectrum analyzer is set to as following.

- . RBW= 100KHz
- . VBW= 100KHz
- . Span= suitable frequency span
- . Sweep= suitable duration based on the EUT specification.

#### Band Edge&Out of Emission Test Instruments

| Description                | Model        | Serial Number |
|----------------------------|--------------|---------------|
| Spectrum Analyzer          | E4407B       | US42041281    |
| Bluetooth Tester           | TC-3000A     | 3000A570224   |
| Dual Directional Coupler   | 778D         | 16502         |
| -Spectrum Analyzer <=> EUT | Loss: 21.3dB | -             |


### 9.3 Measurement results of band-edge & out of emission

|             |              |                            |            |
|-------------|--------------|----------------------------|------------|
| EUT         | Bluetooth    | MODEL                      | KG920      |
| MODE        | GFSK         | ENVIRONMENTAL<br>CONDITION | 23℃, 40%RH |
| INPUT POWER | 120Vac, 60Hz |                            |            |


\* Refer to attach spectrum analyzer data chart.

## 9.4 Trace data of band-edge & Out of Emission

### CH 0



### CH78






**ESTECH Co., Ltd.**

Rm. 1015, World Venture Center II,  
426-5 Gasan-dong, Guncheon-gu,  
Seoul, 158-803, Korea




**Electromagnetic  
Interference  
Test Report**

## CH 0



## CH78



## 10. Measurement of radiated disturbance

Above 30 MHz Electric Field strength was measured in accordance with FCC Part 15 (2005) & ANSI C 63.4 (2003). The test setup was made according to FCC Part 15 (2005) & ANSI C 63.4 (2003) on an open test site, which allows a 3m distance measurement. The EUT was placed in the center of wooden turntable. The height of this table was 0.8m. The measurement was conducted with both horizontal and vertical antenna polarization. The turntable has fully rotated. For further description of the configuration refer to the picture of the test set-up.

### 10.1 Measurement equipments

| Equipment Name        | Type        | Manufacturer    | Serial No.  | Next Calibration date |
|-----------------------|-------------|-----------------|-------------|-----------------------|
| TEST Receiver         | ESVS10      | Rohde & Schwarz | 838562/002  | 2007. 1. 23           |
| TEST Receiver         | ESPI7       | Rohde & Schwarz | 100185      | 2006. 8. 22           |
| Spectrum Analyzer     | R3261C      | ADVANTEST       | 61720116    | 2006. 4. 10           |
| LogBicon Antenna      | VULB 9160   | S/B             | 3142        | 2006. 7. 04           |
| Horn Antenna          | BBHA 9120 D | SCHWARZBECK     | 352         | 2006. 4. 06           |
| Spectrum Analyzer     | 8563E       | HP              | 3623A05297  | 2007. 3. 6            |
| PREAMPLIFIER          | 8449B       | HP              | 3008A00581  | 2007. 3. 9            |
| BLUETOOTH TESTER      | TC-3000A    | TESCOM          | 3000A570224 | 2007. 1. 10           |
| Turn Table            | 2087        | EMCO            | 2129        | —                     |
| Antenna Mast          | 2070-01     | EMCO            | 9702-203    | —                     |
| ANT Mast Controller   | 2090        | EMCO            | 1535        | —                     |
| Turn Table Controller | 2090        | EMCO            | 1535        | —                     |

### 10.2 Environmental Condition

Test Place : Open site(3m)  
 Temperature (°C) : 11 °C  
 Humidity (%) : 49 %

### 10.3 Test data

Measurement Distance : 3 m

| Frequency<br>(MHz) | Reading<br>(dB $\mu$ V)                                                                                                               | Position<br>(V/H) | Height<br>(m) | Correction Factor  |               | Result Value            |                          |                |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------|-------------------|---------------|--------------------|---------------|-------------------------|--------------------------|----------------|
|                    |                                                                                                                                       |                   |               | Ant Factor<br>(dB) | Cable<br>(dB) | Limit<br>(dB $\mu$ V/m) | Result<br>(dB $\mu$ V/m) | Margin<br>(dB) |
| 34.45              | 11.70                                                                                                                                 | V                 | 1.0           | 12.28              | 0.9           | 40.0                    | 24.89                    | -15.11         |
| 62.31              | 7.90                                                                                                                                  | V                 | 1.0           | 12.69              | 1.2           | 40.0                    | 21.75                    | -18.25         |
| 79.34              | 9.10                                                                                                                                  | V                 | 1.0           | 9.95               | 1.3           | 40.0                    | 20.35                    | -19.65         |
| 110.41             | 6.50                                                                                                                                  | H                 | 1.8           | 11.08              | 1.6           | 43.5                    | 19.18                    | -24.32         |
| 130.19             | 5.80                                                                                                                                  | H                 | 1.7           | 12.63              | 1.7           | 43.5                    | 20.13                    | -23.37         |
| 168.01             | 5.50                                                                                                                                  | H                 | 1.5           | 13.95              | 2.0           | 43.5                    | 21.46                    | -22.04         |
| 201.11             | 4.90                                                                                                                                  | H                 | 1.3           | 10.41              | 2.2           | 43.5                    | 17.49                    | -26.01         |
| 242.91             | 6.80                                                                                                                                  | H                 | 1.1           | 11.78              | 2.4           | 46.0                    | 20.99                    | -25.01         |
| 277.70             | 5.40                                                                                                                                  | H                 | 1.0           | 12.64              | 2.5           | 46.0                    | 20.57                    | -25.43         |
| 400.00             | 4.30                                                                                                                                  | H                 | 1.0           | 15.32              | 3.2           | 46.0                    | 22.77                    | -23.23         |
|                    |                                                                                                                                       |                   |               |                    |               |                         |                          |                |
|                    |                                                                                                                                       |                   |               |                    |               |                         |                          |                |
|                    |                                                                                                                                       |                   |               |                    |               |                         |                          |                |
|                    |                                                                                                                                       |                   |               |                    |               |                         |                          |                |
| Remark             | H : Horizontal, V : Vertical<br>*CL = Cable Loss-Amplifier Gain(In case of above1000Mhz)<br>*CL = Cable Loss(In case of below1000Mhz) |                   |               |                    |               |                         |                          |                |

### 10.3-1 Test data(CH0)

Measurement Distance : 3 m

| Frequency<br>(MHz) | Reading<br>(dBμV)                                                                                                                                                                                                                         | Position<br>(V/H) | Height<br>(m) | Correction Factor  |               | Result Value      |                    |                |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|---------------|--------------------|---------------|-------------------|--------------------|----------------|
|                    |                                                                                                                                                                                                                                           |                   |               | Ant Factor<br>(dB) | Cable<br>(dB) | Limit<br>(dBμV/m) | Result<br>(dBμV/m) | Margin<br>(dB) |
| PEAK               |                                                                                                                                                                                                                                           |                   |               |                    |               |                   |                    |                |
| 2342.53            | 45.67                                                                                                                                                                                                                                     | H                 | 1.5           | 27.72              | -33.0         | 74.0              | 40.39              | -33.61         |
| 2402.00            | 53.67                                                                                                                                                                                                                                     | H                 | 2.0           | 27.62              | -33.0         | *OB               | 48.29              | -              |
| 4804.00            | 51.67                                                                                                                                                                                                                                     | H                 | 1.1           | 31.27              | -32.3         | 74.0              | 50.64              | -23.36         |
| 2342.53            | 48.33                                                                                                                                                                                                                                     | V                 | 1.5           | 27.72              | -33.0         | 74.0              | 43.05              | -30.95         |
| 2402.00            | 54.50                                                                                                                                                                                                                                     | V                 | 1.3           | 27.62              | -33.0         | *OB               | 49.12              | -              |
| 4804.00            | 48.33                                                                                                                                                                                                                                     | V                 | 1.0           | 31.27              | -32.3         | 74.0              | 47.30              | -26.70         |
| AV(VBW 3KHz)       |                                                                                                                                                                                                                                           |                   |               |                    |               |                   |                    |                |
| 2342.53            | 36.33                                                                                                                                                                                                                                     | H                 | 1.5           | 27.72              | -33.0         | 54.0              | 31.05              | -22.95         |
| 2402.00            | 51.00                                                                                                                                                                                                                                     | H                 | 2.0           | 27.62              | -33.0         | *OB               | 45.62              | -              |
| 4804.00            | 46.33                                                                                                                                                                                                                                     | H                 | 1.1           | 31.27              | -32.3         | 54.0              | 45.30              | -8.70          |
| 2342.53            | 36.33                                                                                                                                                                                                                                     | V                 | 1.5           | 27.72              | -33.0         | 54.0              | 31.05              | -22.95         |
| 2402.00            | 52.83                                                                                                                                                                                                                                     | V                 | 1.3           | 27.62              | -33.0         | *OB               | 47.45              | -              |
| 4804.00            | 43.50                                                                                                                                                                                                                                     | V                 | 1.0           | 31.27              | -32.3         | 54.0              | 42.47              | -11.53         |
| Remark             | H : Horizontal, V : Vertical TEST MODE : CH 0(2402MHz)<br>*The TX signal isn't detected from 2th harmonics. *OB = Operating band<br>*CL = Cable Loss-Amplifier Gain(In case of above1000Mhz)<br>*CL = Cable Loss(In case of below1000Mhz) |                   |               |                    |               |                   |                    |                |

### 10.3-2 Test data(CH39)

Measurement Distance : 3 m

| Frequency<br>(MHz) | Reading<br>(dB $\mu$ V)                                                                                                                                                                                                                         | Position<br>(V/H) | Height<br>(m) | Correction Factor  |               | Result Value            |                          |                |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|---------------|--------------------|---------------|-------------------------|--------------------------|----------------|
|                    |                                                                                                                                                                                                                                                 |                   |               | Ant Factor<br>(dB) | Cable<br>(dB) | Limit<br>(dB $\mu$ V/m) | Result<br>(dB $\mu$ V/m) | Margin<br>(dB) |
| PEAK               |                                                                                                                                                                                                                                                 |                   |               |                    |               |                         |                          |                |
| 2441.00            | 52.67                                                                                                                                                                                                                                           | H                 | 1.3           | 27.60              | -33.0         | *OB                     | 47.27                    | -              |
| 4882.00            | 48.50                                                                                                                                                                                                                                           | H                 | 2.0           | 31.38              | -32.3         | 74.0                    | 47.58                    | -26.42         |
| 2441.00            | 54.67                                                                                                                                                                                                                                           | V                 | 1.0           | 27.60              | -33.0         | *OB                     | 49.27                    | -              |
| 4882.00            | 48.33                                                                                                                                                                                                                                           | V                 | 1.0           | 31.38              | -32.3         | 74.0                    | 47.41                    | -26.59         |
| AV(VBW 3KHz)       |                                                                                                                                                                                                                                                 |                   |               |                    |               |                         |                          |                |
| 2441.00            | 49.50                                                                                                                                                                                                                                           | H                 | 1.3           | 27.60              | -33.0         | *OB                     | 44.10                    | -              |
| 4882.00            | 43.17                                                                                                                                                                                                                                           | H                 | 2.0           | 31.38              | -32.3         | 54.0                    | 42.25                    | -11.75         |
| 2441.00            | 52.30                                                                                                                                                                                                                                           | V                 | 1.0           | 27.60              | -33.0         | *OB                     | 46.90                    | -              |
| 4882.00            | 43.50                                                                                                                                                                                                                                           | V                 | 1.0           | 31.38              | -32.3         | 54.0                    | 42.58                    | -11.42         |
|                    |                                                                                                                                                                                                                                                 |                   |               |                    |               |                         |                          |                |
| Remark             | H : Horizontal,   V : Vertical   TEST MODE : CH 39 (2441MHz)<br>*The TX signal isn't detected from 2th harmonics. *OB = Operating band<br>*CL = Cable Loss-Amplifier Gain(In case of above1000Mhz)<br>*CL = Cable Loss(In case of below1000Mhz) |                   |               |                    |               |                         |                          |                |

### 10.3-3 Test data(CH78)

Measurement Distance : 3 m

| Frequency<br>(MHz) | Reading<br>(dB $\mu V$ )                                                                                                                                                                                                                          | Position<br>(V/H) | Height<br>(m) | Correction Factor  |               | Result Value             |                           |                |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|---------------|--------------------|---------------|--------------------------|---------------------------|----------------|
|                    |                                                                                                                                                                                                                                                   |                   |               | Ant Factor<br>(dB) | Cable<br>(dB) | Limit<br>(dB $\mu V$ /m) | Result<br>(dB $\mu V$ /m) | Margin<br>(dB) |
| PEAK               |                                                                                                                                                                                                                                                   |                   |               |                    |               |                          |                           |                |
| 2480.00            | 54.83                                                                                                                                                                                                                                             | H                 | 1.9           | 27.59              | -33.0         | *OB                      | 49.42                     | -              |
| 2497.20            | 47.67                                                                                                                                                                                                                                             | H                 | 1.5           | 27.59              | -33.0         | 74.0                     | 42.26                     | -31.74         |
| 4960.00            | 47.67                                                                                                                                                                                                                                             | H                 | 1.2           | 31.49              | -32.3         | 74.0                     | 46.86                     | -27.14         |
| 2480.00            | 54.83                                                                                                                                                                                                                                             | V                 | 1.4           | 27.59              | -33.0         | *OB                      | 49.42                     | -              |
| 2497.20            | 46.17                                                                                                                                                                                                                                             | V                 | 1.5           | 27.59              | -33.0         | 74.0                     | 40.76                     | -33.24         |
| 4960.00            | 45.83                                                                                                                                                                                                                                             | V                 | 1.5           | 31.49              | -32.3         | 74.0                     | 45.02                     | -28.98         |
| AV(VBW 3KHz)       |                                                                                                                                                                                                                                                   |                   |               |                    |               |                          |                           |                |
| 2480.00            | 52.33                                                                                                                                                                                                                                             | H                 | 1.9           | 27.59              | -33.0         | *OB                      | 46.92                     | -              |
| 2497.20            | 36.00                                                                                                                                                                                                                                             | H                 | 1.5           | 27.59              | -33.0         | 54.0                     | 30.59                     | -23.41         |
| 4960.00            | 40.83                                                                                                                                                                                                                                             | H                 | 1.2           | 31.49              | -32.3         | 54.0                     | 40.02                     | -13.98         |
| 2480.00            | 52.83                                                                                                                                                                                                                                             | V                 | 1.4           | 27.59              | -33.0         | *OB                      | 47.42                     | -              |
| 2497.20            | 36.00                                                                                                                                                                                                                                             | V                 | 1.5           | 27.59              | -33.0         | 54.0                     | 30.59                     | -23.41         |
| 4960.00            | 38.67                                                                                                                                                                                                                                             | V                 | 1.5           | 31.49              | -32.3         | 54.0                     | 37.86                     | -16.14         |
| Remark             | H : Horizontal,    V : Vertical    TEST MODE : CH 78 (2480MHz)<br>*The TX signal isn't detected from 2th harmonics. *OB = Operating band<br>*CL = Cable Loss-Amplifier Gain(In case of above1000Mhz)<br>*CL = Cable Loss(In case of below1000Mhz) |                   |               |                    |               |                          |                           |                |

## 11. Measurement of conducted disturbance

The continuous disturbance voltage of AC Mains in the frequency from 0.15 to 30 MHz was measured in accordance to FCC Part 15 (2005) & ANSI C 63.4 (2003). The test setup was made according to FCC Part 15 (2005) & ANSI C 63.4 (2003) in a shielded. The EUT was placed on a non-conductive table at least 80 above the ground plane. A grounded vertical reference plane was positioned in a distance of 40cm from the EUT. The distance from the EUT to other metal surfaces was at least 0.8m. The EUT was only earthen by its power cord through the line impedance stabilizing network. The power cord has been bundled to a length of 1.0m.. The test receiver with Quasi Peak detector complies with CISPR 16.

### 11.1 Measurement equipments

| Equipment Name   | Type      | Manufacturer    | Serial No.  | Next Calibration date |
|------------------|-----------|-----------------|-------------|-----------------------|
| LISN             | ESH3-Z5   | Rohde & Schwarz | 838979/010  | 2007. 2. 27           |
| LISN             | NNLA8120A | Schwarzbeck     | NONE        | 2007. 2. 27           |
| TEST Receive     | ESPI7     | Rohde & Schwarz | 100185      | 2006. 8. 22           |
| Pulse Limiter    | ESH3Z2    | Rohde & Schwarz | NONE        | 2006. 6. 15           |
| BLUETOOTH TESTER | TC-3000A  | TESCOM          | 3000A570224 | 2007. 1. 10           |

### 11.2 Environmental Condition

Test Place : Shield Room

Temperature (°C) : 20 °C

Humidity (%) : 51 %

### 11.3 Test data(CH39)

| Frequency<br>(MHz) | Correction Factor                                             |               | Line<br>(H/N) | Quasi-peak Value      |                         |                        | Average Value         |                         |                |
|--------------------|---------------------------------------------------------------|---------------|---------------|-----------------------|-------------------------|------------------------|-----------------------|-------------------------|----------------|
|                    | Lisn<br>(dB)                                                  | Cable<br>(dB) |               | Limit<br>(dB $\mu$ V) | Reading<br>(dB $\mu$ V) | Result<br>(dB $\mu$ V) | Limit<br>(dB $\mu$ V) | Reading<br>(dB $\mu$ V) | Result<br>(dB) |
| 0.15               | 0.10                                                          | 0.0           | N             | 66.00                 | 32.65                   | 32.75                  | 56.00                 | 33.52                   | 33.62          |
| 0.19               | 0.10                                                          | 0.0           | N             | 63.91                 | 36.87                   | 37.00                  | 53.91                 | 35.92                   | 36.05          |
| 0.24               | 0.10                                                          | 0.1           | N             | 61.99                 | 35.17                   | 35.33                  | 51.99                 | 33.66                   | 33.82          |
| 0.34               | 0.10                                                          | 0.1           | N             | 59.25                 | 26.89                   | 27.11                  | 49.25                 | 22.79                   | 23.01          |
| 17.08              | 0.52                                                          | 0.8           | N             | 60.00                 | 25.05                   | 26.37                  | 50.00                 | —                       | —              |
| 25.06              | 0.95                                                          | 0.9           | N             | 60.00                 | 23.89                   | 25.74                  | 50.00                 | 20.26                   | 22.11          |
| 28.44              | 1.12                                                          | 0.9           | N             | 60.00                 | 15.73                   | 17.75                  | 50.00                 | 6.76                    | 8.78           |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
|                    |                                                               |               |               |                       |                         |                        |                       |                         |                |
| Remark             | H : Hot Line, N : Neutral Line    TEST MODE : CH 39 (2441MHz) |               |               |                       |                         |                        |                       |                         |                |

## 12. Antenna Requirement

### 12.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


And according to FCC 47 CFR Section 15.24

### 12.2 Antenna Connected Construction

The antenna types used in this product are Multilayer Chip Antenna. The maximum Gain of this antenna is 4.20dBi.


# Appendix 1. Spectral diagram

\*HOT(CH39)



Comment: KG920 HOT  
Date: 18.MAR.2006 11:13:46

\*NEUTRAL(CH39)



Comment: KG920 NEUTRAL  
Date: 18.MAR.2006 11:22:27