

RF Exposure Statement

1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3. RESULTS

3-1. GSM 850 BAND

Average Peak output Power at antenna input terminal	33.500	dBm
Average Peak output Power at antenna input terminal	2238.721	mW
Prediction distance	20.000	cm
Prediction frequency	824.200	MHz
Antenna Gain(typical)	-3.250	dBi
Antenna Gain(numeric)	0.473	-
Power density at prediction frequency(S)	0.211	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.549	mW/cm ²

3-2. GSM 1900 BAND

Average Peak output Power at antenna input terminal	30.500	dBm
Average Peak output Power at antenna input terminal	1122.018	mW
Prediction distance	20.000	cm
Prediction frequency	1850.200	MHz
Antenna Gain(typical)	1.260	dBi
Antenna Gain(numeric)	1.337	-
Power density at prediction frequency(S)	0.298	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

3-3. WCDMA 850 BAND

Average Peak output Power at antenna input terminal	24.200	dBm
Average Peak output Power at antenna input terminal	263.027	mW
Prediction distance	20.000	cm
Prediction frequency	826.400	MHz
Antenna Gain(typical)	-3.250	dBi
Antenna Gain(numeric)	0.473	-
Power density at prediction frequency(S)	0.025	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.551	mW/cm ²

3-4. WCDMA 1900 BAND

Average Peak output Power at antenna input terminal	24.200	dBm
Average Peak output Power at antenna input terminal	263.027	mW
Prediction distance	20.000	cm
Prediction frequency	1852.400	MHz
Antenna Gain(typical)	1.260	dBi
Antenna Gain(numeric)	1.337	-
Power density at prediction frequency(S)	0.070	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

3-5. WCDMA 1700 BAND

Average Peak output Power at antenna input terminal	24.200	dBm
Average Peak output Power at antenna input terminal	263.027	mW
Prediction distance	20.000	cm
Prediction frequency	1712.400	MHz
Antenna Gain(typical)	-0.130	dBi
Antenna Gain(numeric)	0.971	-
Power density at prediction frequency(S)	0.051	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

3-6. LTE BAND 2

Average Peak output Power at antenna input terminal	26.200	dBm
Average Peak output Power at antenna input terminal	416.869	mW
Prediction distance	20.000	cm
Prediction frequency	1850.700	MHz
Antenna Gain(typical)	1.260	dBi
Antenna Gain(numeric)	1.337	-
Power density at prediction frequency(S)	0.111	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

3-7. LTE BAND 5

Average Peak output Power at antenna input terminal	26.200	dBm
Average Peak output Power at antenna input terminal	416.869	mW
Prediction distance	20.000	cm
Prediction frequency	824.700	MHz
Antenna Gain(typical)	-3.250	dBi
Antenna Gain(numeric)	0.473	-
Power density at prediction frequency(S)	0.039	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.550	mW/cm ²

3-8. LTE BAND 4

Average Peak output Power at antenna input terminal	26.200	dBm
Average Peak output Power at antenna input terminal	416.869	mW
Prediction distance	20.000	cm
Prediction frequency	1710.700	MHz
Antenna Gain(typical)	-0.130	dBi
Antenna Gain(numeric)	0.971	-
Power density at prediction frequency(S)	0.080	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

3-9. LTE BAND 17

Average Peak output Power at antenna input terminal	26.200	dBm
Average Peak output Power at antenna input terminal	416.869	mW
Prediction distance	20.000	cm
Prediction frequency	706.500	MHz
Antenna Gain(typical)	-3.030	dBi
Antenna Gain(numeric)	0.498	-
Power density at prediction frequency(S)	0.041	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.471	mW/cm ²

3-10. LTE BAND 7

Average Peak output Power at antenna input terminal	26.200	dBm
Average Peak output Power at antenna input terminal	416.869	mW
Prediction distance	20.000	cm
Prediction frequency	2502.500	MHz
Antenna Gain(typical)	-0.220	dBi
Antenna Gain(numeric)	0.951	-
Power density at prediction frequency(S)	0.079	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²