TEST REPORT

FCC BT LE Test for LGSBWAC24
Certification

APPLICANT
LG Electronics Inc.

REPORT NO.
HCT-RF-2408-FC003

DATE OF ISSUE
August 9, 2024

Tested by
Kyung Jun Woo

Technical Manager
Jong Seok Lee

Accredited by KOLAS, Republic of KOREA

HCT CO., LTD.
BongJai Huh / CEO

The report shall not be (partly) reproduced except in full without approval of the laboratory.
HCT CO., LTD. 2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA Tel. +82 31 645 6300 Fax. +82 31 645 6401

HCT CO.,LTD.
2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.
HCT-RF-2408-FC003

DATE OF ISSUE
August 09, 2024

Applicant	**LG Electronics Inc.** 222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do 17709, Republic of Korea
Product Name Model Name	RF Module LGSBWAC24
FCC ID	BEJLGSBWAC24
Max. RF Output Power	8.483 dBm (7.05 mW)
Date of Test	July 16, 2024 ~ August 09, 2024
FCC Classification	Digital Transmission System(DTS)
Test Standard Used	FCC Rule Part(s): Part 15.247
Test Results	PASS
Location of Test	■ Permanent Testing Lab ☐ On Site Testing Lab (Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)
Brand	LG

The report shall not be (partly) reproduced except in full without approval of the laboratory.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	August 09, 2024	Initial Release

Notice

Content
Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance. The laboratory is not accredited for the test results marked *. Information provided by the applicant is marked **. Test results provided by external providers are marked ***. The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated. The test results have only been applied with the test methods required by the standard(s). When confirmation of authenticity of this test report is required, please contact www.hct.co.kr This test report provides test result(s) under the scope accredited by the Korea Laboratory Accreditation Scheme (KOLAS), which signed the ILAC-MRA. (KOLAS (KS Q ISO/IEC 17025) Accreditation No. KT197)

The report shall not be (partly) reproduced except in full without approval of the laboratory.

CONTENTS

1. EUT DESCRIPTION 5
2. TEST METHODOLOGY 6
   EUT CONFIGURATION 6
   EUT EXERCISE 6
   GENERAL TEST PROCEDURES 6
   DESCRIPTION OF TEST MODES 7
3. INSTRUMENT CALIBRATION 7
4. FACILITIES AND ACCREDITATIONS 7
   FACILITIES 7
   EQUIPMENT 7
5. ANTENNA REQUIREMENTS 8
6. MEASUREMENT UNCERTAINTY 8
7. DESCRIPTION OF TESTS 9
8. SUMMARY TEST OF RESULTS 24
9. TEST RESULT 25
   9.1 DUTY CYCLE 25
   9.2 6 dB BANDWIDTH 28
   9.3 OUTPUT POWER 31
   9.4 POWER SPECTRAL DENSITY 33
   9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS 35
   9.6 RADIATED SPURIOUS EMISSIONS 38
   9.7 RADIATED RESTRICTED BAND EDGES 44
   9.8 POWERLINE CONDUCTED EMISSIONS 46
10. LIST OF TEST EQUIPMENT 47
11. ANNEX A_ TEST SETUP PHOTO 49

The report shall not be (partly) reproduced except in full without approval of the laboratory.

1. EUT DESCRIPTION

Model	LGSBWAC24		
Additional Model	-		
EUT Type	RF Module		
Power Supply	DC 3.30 V		
Frequency Range	2 402 MHz – 2 480 MHz		
Number of Channels	40 Channels		
Max. RF Output Power (Normal)	Peak	1 M Bit/s: 2 M Bit/s: 125 k Bit/s : 500 k Bit/s :	8.483 dBm (7.05 mW) 8.460 dBm (7.01 mW) 8.218 dBm (6.63 mW) 8.183 dBm (6.58 mW)
	Average	1 M Bit/s: 2 M Bit/s: 125 k Bit/s : 500 k Bit/s :	8.07 dBm (6.41 mW) 8.01 dBm (6.32 mW) 7.97 dBm (6.27 mW) 7.99 dBm (6.30 mW)
Modulation Type	GFSK		
Bluetooth Version	5.0		
Antenna Specification	Type: Metal press Ant Peak Gain: -1.01 dBi		
Serial number	Conducted : D07602C7ACA6 Radiated : D07602C7ACAE		

The report shall not be (partly) reproduced except in full without approval of the laboratory.

2. TEST METHODOLOGY

FCC KDB 558074 D01 15.247 Meas Guidance v05r02 dated April 02, 2019 entitled "guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices and the measurement procedure described in ANSI C63.10(Version : 2013) 'the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices'.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1 GHz. Above 1 GHz with 1.5 m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013)

The report shall not be (partly) reproduced except in full without approval of the laboratory.

DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards.
Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

4. FACILITIES AND ACCREDITATIONS

FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.
The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.
Detailed description of test facility was submitted to the Commission and accepted dated March 11, 2024 (Registration Number: KR0032).

EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.
All receiving equipment conforms to CISPR Publication 16-1, “Radio Interference Measuring Apparatus and Measurement Methods.”

The report shall not be (partly) reproduced except in full without approval of the laboratory.

5. ANTENNA REQUIREMENTS

According to FCC 47 CFR § 15.203

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

(1) The antennas of this E.U.T are permanently attached.

(2) The E.U.T Complies with the requirement of § 15.203

6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.98 (Confidence level about 95 %, k=2)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.36 (Confidence level about 95 %, k=2)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.70 (Confidence level about 95 %, k=2)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.52 (Confidence level about 95 %, k=2)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.66 (Confidence level about 95 %, k=2)
Radiated Disturbance (Above 40 GHz)	5.58 (Confidence level about 95 %, k=2)

The report shall not be (partly) reproduced except in full without approval of the laboratory.

7. DESCRIPTION OF TESTS

7.1. Duty Cycle

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to the zero-span measurement method, 6.0)b) in KDB 558074 v05r02.

The largest available value of RBW is 8 MHz and VBW is 8 MHz.

The zero-span method of measuring duty cycle shall not be used if T ≤ 6.25 microseconds. (50/6.25 = 8)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are > 50/ *T*.

1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz (≥ RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = T_{on}/ T_{total} and Duty Cycle Factor = 10log(1/Duty Cycle)

The report shall not be (partly) reproduced except in full without approval of the laboratory.

7.2. 6 dB Bandwidth

Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Procedure 8.2 in KDB 558074 v05r02, Procedure 11.8.1 in ANSI 63.10-2013)

1) RBW = 100 kHz
2) VBW ≥ 3 x RBW
3) Detector = Peak
4) Trace mode = Max hold
5) Sweep = auto couple
6) Allow the trace to stabilize
7) We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.

Note : We tested OBW using the automatic bandwidth measurement capability of a spectrum analyzer.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

7.3. Output Power

Limit

The maximum permissible conducted output power is 1 Watt.

Test Configuration



Test Procedure

The transmitter output is connected to the Power Meter.

▪ Peak Power (Procedure 11.9.1.3 in ANSI 63.10-2013)
: Measure the peak power of the transmitter.

▪ Average Power (Procedure 8.3.2.3 in KDB 558074 v05r02, Procedure 11.9.2.3 in ANSI 63.10-2013)

1) Measure the duty cycle.
2) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
3) Add 10 log (1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

Sample Calculation

▪ Conducted Output Power(Peak) = Measured Value + ATT loss + Cable loss
▪ Conducted Output Power(Average) = Measured Value + ATT loss + Cable loss + Duty Cycle Factor

The report shall not be (partly) reproduced except in full without approval of the laboratory.

7.4. Power Spectral Density

Limit

The transmitter power density average over 1-second interval shall not be greater than 8 dBm in any 3 kHz BW.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to Procedure 8.4 in KDB 558074 v05r02, Procedure 11.10 in ANSI 63.10-2013.

The spectrum analyzer is set to :

1) Set analyzer center frequency to DTS channel center frequency.
2) Set span to at least 1.5 times the DTS bandwidth.
3) RBW = 3 kHz ≤ RBW ≤ 100 kHz.
4) VBW ≥ 3 x RBW.
5) Sweep = auto couple.
6) Detector = Peak.
7) Trace mode = max hold.
8) Allow trace to fully stabilize.
9) Use the peak marker function to determine the maximum amplitude level within the RBW.
10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Sample Calculation

- Power Spectral Density = Measured Value + ATT loss + Cable loss + Duty Cycle Factor

The report shall not be (partly) reproduced except in full without approval of the laboratory.

7.5. Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions

Limit

The maximum conducted (Average) output power was used to demonstrate compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

[Conducted > 20 dBc]

Test Configuration



Test Procedure

The transmitter output is connected to the spectrum analyzer.

(Procedure 8.5 in KDB 558074 v05r02, Procedure 11.11 in ANSI 63.10-2013)

1) RBW = 100 kHz
2) VBW ≥ 3 x RBW
3) Set span to encompass the spectrum to be examined
4) Detector = Peak
5) Trace Mode = Max hold
6) Sweep time = auto couple
7) Ensure that the number of measurement points ≥ 2 x Span/VBW
8) Allow trace to fully stabilize.
9) Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Factors for frequency

Freq(MHz)	Factor(dB)
30	10.13
100	10.25
200	10.35
300	10.41
400	10.44
500	10.46
600	10.48
700	10.50
800	10.53
900	10.58
1 000	10.62
2 000	10.71
2 400	10.74
2 500	10.74
3 000	10.93
4 000	11.22
5 000	11.73
5 150	11.82
5 850	11.82
6 000	11.93
7 000	12.33
8 000	12.52
9 000	12.59
10 000	12.64
11 000	12.78
12 000	12.83
13 000	12.89
14 000	13.06
15 000	13.36
16 000	13.52
17 000	13.55
18 000	13.45
19 000	13.48
20 000	13.37
21 000	13.63
22 000	14.07
23 000	13.89
24 000	14.02
25 000	14.00

Note : 1. 2400 ~ 2500 MHz is fundamental frequency range.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

7.6. Radiated Test

Limit

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration

Below 30 MHz



The report shall not be (partly) reproduced except in full without approval of the laboratory.

30 MHz - 1 GHz



Above 1 GHz



The report shall not be (partly) reproduced except in full without approval of the laboratory.

Test Procedure of Radiated spurious emissions(Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the gro und plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) = 40log(3 m/300 m) = - 80 dB
   Measurement Distance : 3 m
7. Distance Correction Factor(0.490 MHz – 30 MHz) = 40log(3 m/30 m) = - 40 dB
   Measurement Distance : 3 m
8. Spectrum Setting
   - Frequency Range = 9 kHz ~ 30 MHz
   - Detector = Peak
   - Trace = Maxhold
   - RBW = 9 kHz
   - VBW ≥ 3 x RBW
9. Total = Measured Level + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

KDB 414788 OFS and Chamber Correlation Justification

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Test Procedure of Radiated spurious emissions(Below 1GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. The Hybrid antenna was placed at a location 3m from the EUT, which is varied from 1m to 4m to find out the highest emissions.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Spectrum Setting
   (1) Measurement Type(Peak):
   - Measured Frequency Range : 30 MHz – 1 GHz
   - Detector = Peak
   - Trace = Maxhold
   - RBW = 100 kHz
   - VBW ≥ 3 x RBW

   (2) Measurement Type(Quasi-peak):
   - Measured Frequency Range : 30 MHz – 1 GHz
   - Detector = Quasi-Peak
   - RBW = 120 kHz

   ※In general, (1) is used mainly
7. Total = Measured Value + Antenna Factor(A.F) + Cable Loss(C.L)
8. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3 m away from the receiving antenna, which is varied from 1 m to 4 m to find out the highest emissions.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting (Method 8.6 in KDB 558074 v05r02, Procedure 11.12 in ANSI 63.10-2013)
   (1) Measurement Type(Peak):
   - Measured Frequency Range : 1 GHz – 25 GHz
   - Detector = Peak
   - Trace = Max hold
   - RBW = 1 MHz
   - VBW ≥ 3 x RBW

   (2) Measurement Type(Average):
   - Duty cycle < 98 %, duty cycle variations are less than ±2 %
   - Measured Frequency Range : 1 GHz – 25 GHz
   - Detector = RMS
   - Averaging type = power (*i.e.*, RMS)
   - RBW = 1 MHz
   - VBW ≥ 3 x RBW
   - Sweep time = auto.
   - Trace mode = average (at least 100 traces).
   - Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.

- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1

9. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
10. Distance extrapolation factor = 20log (test distance / specific distance) (dB)
11. Total(Measurement Type : Peak)
    = Measured value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(A.G) + Distance Factor(D.F)

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Total(Measurement Type : Average, Duty cycle ≥ 98 %)

= Measured value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(A.G) + Distance Factor(D.F)

#Note : Used Average measurement method according to KDB 558074 Section11 Q3

Test Procedure of Radiated Restricted Band Edge

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3 m away from the receiving antenna, which is varied from 1 m to 4 m to find out the highest emissions.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting
   (1) Measurement Type(Peak):
   - Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
   - Detector = Peak
   - Trace = Max hold
   - RBW = 1 MHz
   - VBW ≥ 3 x RBW

   (2) Measurement Type(Average):
   - Duty cycle < 98 %, duty cycle variations are less than ±2 %
   - Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
   - Detector = RMS
   - Averaging type = power (*i.e.*, RMS)
   - RBW = 1 MHz
   - VBW ≥ 3 x RBW
   - Sweep time = auto.
   - Trace mode = average (at least 100 traces).
   - Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
   - Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.
9. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered

The report shall not be (partly) reproduced except in full without approval of the laboratory.

that's already beyond the background noise floor.

10. Distance extrapolation factor = 20log (test distance / specific distance) (dB)

11.Total

(1)Measurement(Peak)

= Measured Value(Peak)

(2)Measurement(Avg)

= Measured Value(Avg)

- We apply to the offset in range 1 GHz - 18 GHz
- The offset = Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

#Note : Used Average measurement method according to KDB 558074 Section11 Q3

The report shall not be (partly) reproduced except in full without approval of the laboratory.

7.7. AC Power line Conducted Emissions

Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56[(a)]	56 to 46[(a)]
0.50 to 5	56	46
5 to 30	60	50

[(a)]Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Measured Value + Correction Factor

The report shall not be (partly) reproduced except in full without approval of the laboratory.

7.8. Worst case configuration and mode

Radiated Test

1. All modes of operation were investigated and the worst case configuration results are reported.
   - Mode : Stand alone
   - Worstcase : Stand alone
2. EUT Axis
   - Radiated Spurious Emissions : Z
   - Radiated Restricted Band Edge : Y
3. All packet length of operation were investigated and the test results are worst case in lowest packet length.
   (Worst case :1M Bit/s 37 Byte)
   (125k, 500k, 1M Bit/s all have the same 1 MHz Band width and only Worst result is attached.)
4. All datarate of operation were investigated and the worst case configuration results are reported.
   - Worst case : 1 M, 2 M
5. All position of loop antenna were investigated and the test result is a no critical peak found at all positions.
   - Position : Horizontal, Vertical, Parallel to the ground plane

AC Power line Conducted Emissions

1. All modes of operation were investigated and the worst case configuration results are reported.
   - Mode : Stand alone
   - Worstcase : Stand alone

Conducted test

1. The EUT was configured with packet length of highest power.
   - ALL supported mode tested.
   - Worst Results refer to Notes for each test item

The report shall not be (partly) reproduced except in full without approval of the laboratory.

8. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§ 15.247(a)(2)	> 500 kHz	Conducted	PASS
Conducted Maximum Output Power	§ 15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§ 15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge (Out of Band Emissions)	§ 15.247(d)	Conducted > 30 dBc		PASS
AC Power line Conducted Emissions	§ 15.207	cf. Section 7.7		PASS
Radiated Spurious Emissions	§ 15.247(d), 15.205, 15.209	cf. Section 7.6	Radiated	PASS
Radiated Restricted Band Edge	§ 15.247(d), 15.205, 15.209	cf. Section 7.6		PASS

The report shall not be (partly) reproduced except in full without approval of the laboratory.

9. TEST RESULT

9.1 DUTY CYCLE

Data rate (Bit/s)	Packet length (Byte)	T_{on} (ms)	T_{total} (ms)	Duty Cycle	Duty Cycle Factor (dB)
1M	37	0.394	0.626	0.630	2.007
	255	2.139	2.501	0.855	0.679
2M	37	0.208	0.626	0.332	4.785
	255	1.080	1.875	0.576	2.396
125k	37	3.104	3.744	0.829	0.814
	255	17.050	17.500	0.974	0.113
500k	37	1.071	1.875	0.571	2.432
	255	4.550	5.000	0.910	0.410

The report shall not be (partly) reproduced except in full without approval of the laboratory.

1 M Bit/s (37 Byte)



1 M Bit/s (255 Byte)



2 M Bit/s (37 Byte)



2 M Bit/s (255 Byte)



125 k Bit/s(37 Byte)

125 k Bit/s(255 Byte)

The report shall not be (partly) reproduced except in full without approval of the laboratory.

500 k Bit/s(37 Byte)	500 k Bit/s(255 Byte)
	

The report shall not be (partly) reproduced except in full without approval of the laboratory.

9.2 6 dB BANDWIDTH

Mode (Bit/s)	Channel	6 dB Bandwidth (kHz)	Limit (kHz)
1M(37)	0	661.9	> 500
	19	655.0	
	39	663.1	
1M(255)	0	662.6	> 500
	19	660.6	
	39	662.7	
2M(37)	0	1090	> 500
	19	1110	
	39	956.6	
2M(255)	0	1122	> 500
	19	1120	
	39	1126	
125k(37)	0	596.2	> 500
	19	598.2	
	39	600.1	
125k(255)	0	597.5	> 500
	19	598.8	
	39	600.3	
500k(37)	0	650.2	> 500
	19	664.0	
	39	660.6	
500k(255)	0	660.6	> 500
	19	663.5	
	39	661.2	

Note:

In order to simplify the report, attached plots were only the narrowest 6 dB BW Channel.

1M Bit/s: 37 Byte

2M Bit/s: 37 Byte

125k Bit/s: 37 Byte

500k Bit/s: 37 Byte

The report shall not be (partly) reproduced except in full without approval of the laboratory.

1 MBit/s (37 Byte) Test Plots	2 MBit/s (37 Byte) Test Plots
6 dB Bandwidth plot (Low-CH 0)	6 dB Bandwidth plot (Low-CH 0)
6 dB Bandwidth plot (Mid-CH 19)	6 dB Bandwidth plot (Mid-CH 19)
6 dB Bandwidth plot (High-CH 39)	6 dB Bandwidth plot (High-CH 39)

The report shall not be (partly) reproduced except in full without approval of the laboratory.

125k Bit/s(37 Byte) Test Plots	500k Bit/s(37 Byte) Test Plots
6 dB Bandwidth plot (Low-CH 0)	6 dB Bandwidth plot (Low-CH 0)
	
6 dB Bandwidth plot (Mid-CH 19)	6 dB Bandwidth plot (Mid-CH 19)
6 dB Bandwidth plot (High-CH 39)	6 dB Bandwidth plot (High-CH 39)

The report shall not be (partly) reproduced except in full without approval of the laboratory.

9.3 OUTPUT POWER

Peak Power

Data rate	Packet length	LE Mode		Peak Power (dBm)	Limit (dBm)
(Bit/s)	(Byte)	Frequency [MHz]	Channel		
1M	37	2402	0	8.088	30
		2440	19	8.072	
		2480	39	8.483	
	255	2402	0	8.050	
		2440	19	7.982	
		2480	39	8.363	
2M	37	2402	0	8.064	
		2440	19	8.062	
		2480	39	8.460	
	255	2402	0	7.970	
		2440	19	7.966	
		2480	39	8.341	
125k	37	2402	0	8.026	
		2440	19	8.037	
		2480	39	8.191	
	255	2402	0	7.897	
		2440	19	7.955	
		2480	39	8.218	
500k	37	2402	0	8.061	
		2440	19	7.710	
		2480	39	8.133	
	255	2402	0	7.919	
		2440	19	8.069	
		2480	39	8.183	

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Average Power

Note :

1. Total Power [dBm] = Measured Power [dBm] + Duty Cycle Factor [dB]

Data rate	Packet length	LE Mode		Average Power			Limit (dBm)
(Bit/s)	(Byte)	Frequency [MHz]	Channel	Measured Power (dBm)	Duty Cycle Factor (dB)	Result (dBm)	
1M	37	2402	0	5.73	2.01	7.74	30
		2440	19	5.72	2.01	7.73	
		2480	39	6.06	2.01	8.07	
	255	2402	0	7.03	0.68	7.71	
		2440	19	7.02	0.68	7.70	
		2480	39	7.35	0.68	8.03	
2M	37	2402	0	2.88	4.79	7.67	
		2440	19	2.86	4.79	7.65	
		2480	39	3.22	4.79	8.01	
	255	2402	0	5.25	2.40	7.65	
		2440	19	5.19	2.40	7.59	
		2480	39	5.57	2.40	7.97	
125k	37	2402	0	6.81	0.81	7.62	
		2440	19	6.82	0.81	7.63	
		2480	39	7.16	0.81	7.97	
	255	2402	0	7.51	0.11	7.62	
		2440	19	7.47	0.11	7.58	
		2480	39	7.79	0.11	7.90	
500k	37	2402	0	5.12	2.43	7.55	
		2440	19	5.14	2.43	7.57	
		2480	39	5.56	2.43	7.99	
	255	2402	0	7.13	0.41	7.54	
		2440	19	7.10	0.41	7.51	
		2480	39	7.55	0.41	7.96	

The report shall not be (partly) reproduced except in full without approval of the laboratory.

9.4 POWER SPECTRAL DENSITY

Frequency (MHz)	Channel No.	Mode	Test Result	
			Power Spectral Density (dBm)	Limit
2402	0	1 MBit/s 37 Byte	5.463	8 dBm / 3 kHz
2440	19		5.520	
2480	39		5.899	
2402	0	1 MBit/s 255 Byte	5.430	
2440	19		5.426	
2480	39		5.748	
2402	0	2 MBit/s 37 Byte	4.439	
2440	19		4.516	
2480	39		4.852	
2402	0	2 MBit/s 255 Byte	4.307	
2440	19		4.382	
2480	39		4.783	
2402	0	125k 37 Byte	4.670	
2440	19		4.788	
2480	39		5.070	
2402	0	125k 255 Byte	4.541	
2440	19		4.645	
2480	39		4.960	
2402	0	500k 37 Byte	4.999	
2440	19		5.150	
2480	39		5.463	
2402	0	500k 255 Byte	5.451	
2440	19		5.282	
2480	39		5.766	

Note :

1. In order to simplify the report, The plots were attached with the highest PSD Mode.
   Worst case : 1M Bit/s (37 Byte)

The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ Test Plots

Mode : 1 MBit/s (37 Byte)

Power Spectral Density (Low-CH 0)

Power Spectral Density (Mid-CH 19)

Power Spectral Density (High-CH 39)

The report shall not be (partly) reproduced except in full without approval of the laboratory.

9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

[BAND EDGE]

Frequency (MHz)	Mode	Channel No.	Position	Test Result	
				Band Edge (dB)	Limit (dBc)
2402	1M Bit/s 37 Byte	0	Lowest BandEdge	59.148	30
2480		39	Highest BandEdge	59.355	30
2402	1M Bit/s 255 Byte	0	Lowest BandEdge	57.785	30
2480		39	Highest BandEdge	58.246	30
2402	2M Bit/s 37 Byte	0	Lowest BandEdge	33.194	30
2480		39	Highest BandEdge	59.895	30
2402	2M Bit/s 255 Byte	0	Lowest BandEdge	33.247	30
2480		39	Highest BandEdge	59.294	30
2402	125k Bit/s 37 Byte	0	Lowest BandEdge	59.271	30
2480		39	Highest BandEdge	58.419	30
2402	125k Bit/s 255 Byte	0	Lowest BandEdge	61.783	30
2480		39	Highest BandEdge	61.526	30
2402	500k Bit/s 37 Byte	0	Lowest BandEdge	59.666	30
2480		39	Highest BandEdge	60.171	30
2402	500k Bit/s 255 Byte	0	Lowest BandEdge	57.860	30
2480		39	Highest BandEdge	58.995	30

Note :

In order to simplify the report, attached plots were only the worst case channel and data rate.

- Lowest Band Edge: 2M Bit/s (37 Byte)
- Highest Band Edge: 1M Bit/s (255 Byte)

The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ Test Plot(Band Edge)

2M Bit/s (37 Byte) Low-CH 0



1M Bit/s (255 Byte) High-CH 39



The report shall not be (partly) reproduced except in full without approval of the laboratory.

[CONDUCTED SPURIOUS EMISSIONS]

In order to simplify the report, attached plots were only the worst case channel and data rate.
- Worst case : 1M Bit/s 37 Byte Ch. 39(2 480 MHz)

▣ Test Plots(Conducted Spurious Emission (30 MHz – 26.5 GHz))

Conducted Spurious Emission



Limit (dBm): -13.855

The report shall not be (partly) reproduced except in full without approval of the laboratory.

9.6 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30 MHz

Frequency	Measured Value	A.F+C.L+D.F	POL	Total	Limit	Margin
[MHz]	[dBμV]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]
No Critical peaks found						

Note:

1. The Measured of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = 40log (specific distance / test distance) (dB)
3. Limit line = specific Limits (dBμV) + Distance extrapolation factor

Frequency Range : Below 1 GHz

Frequency	Measured Value	A.F+C.L	POL	Total	Limit	Margin
[MHz]	[dBμV]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]
No Critical peaks found						

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Frequency Range : Above 1 GHz

Operation Mode	1 M Bit/s (37 Bytes)
Operating Frequency	2402 MHz
Channel No	CH 0

Frequency	Measured Value	AF+CL-AG	Pol.	Total	Limit	Margin	Measurement Type
[MHz]	[dBμV]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]	
4804	48.97	2.94	V	51.91	73.98	22.07	PK
4804	41.14	2.94	V	44.08	53.98	9.90	AV
7206	41.24	9.79	V	51.03	73.98	22.95	PK
7206	29.10	9.79	V	38.89	53.98	15.09	AV
4804	48.55	2.94	H	51.49	73.98	22.49	PK
4804	40.92	2.94	H	43.86	53.98	10.12	AV
7206	41.06	9.79	H	50.85	73.98	23.13	PK
7206	29.08	9.79	H	38.87	53.98	15.11	AV

Operation Mode	1 M Bit/s (37 Bytes)
Operating Frequency	2440 MHz
Channel No	CH 19

Frequency	Measured Value	AF+CL-AG	Pol.	Total	Limit	Margin	Measurement Type
[MHz]	[dBμV]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]	
4880	45.75	3.59	V	49.34	73.98	24.64	PK
4880	36.67	3.59	V	40.26	53.98	13.72	AV
7320	42.43	10.28	V	52.71	73.98	21.27	PK
7320	29.63	10.28	V	39.91	53.98	14.07	AV
4880	44.81	3.59	H	48.40	73.98	25.58	PK
4880	36.21	3.59	H	39.80	53.98	14.18	AV
7320	42.26	10.28	H	52.54	73.98	21.44	PK
7320	29.63	10.28	H	39.91	53.98	14.07	AV

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Operation Mode	1 M Bit/s (37 Bytes)
Operating Frequency	2480 MHz
Channel No	CH 39

Frequency	Measured Value	AF+CL-AG	Pol.	Total	Limit	Margin	Measurement Type
[MHz]	[dBμV]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]	
4960	43.91	2.96	V	46.87	73.98	27.11	PK
4960	32.93	2.96	V	35.89	53.98	18.09	AV
7440	42.46	10.60	V	53.06	73.98	20.92	PK
7440	29.58	10.60	V	40.18	53.98	13.80	AV
4960	43.06	2.96	H	46.02	73.98	27.96	PK
4960	32.58	2.96	H	35.54	53.98	18.44	AV
7440	42.15	10.60	H	52.75	73.98	21.23	PK
7440	29.00	10.60	H	39.60	53.98	14.38	AV

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Operation Mode	2 M Bit/s (37 Bytes)
Operating Frequency	2402 MHz
Channel No	CH 0

Frequency	Measured Value	AF+CL-AG	Pol.	Total	Limit	Margin	Measurement Type
[MHz]	[dBμV]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]	
4804	48.72	2.94	V	51.66	73.98	22.32	PK
4804	37.59	2.94	V	40.53	53.98	13.45	AV
7206	40.66	9.79	V	50.45	73.98	23.53	PK
7206	29.06	9.79	V	38.85	53.98	15.13	AV
4804	47.51	2.94	H	50.45	73.98	23.53	PK
4804	37.26	2.94	H	40.20	53.98	13.78	AV
7206	40.14	9.79	H	49.93	73.98	24.05	PK
7206	28.88	9.79	H	38.67	53.98	15.31	AV

Operation Mode	2 M Bit/s (37 Bytes)
Operating Frequency	2440 MHz
Channel No	CH 19

Frequency	Measured Value	AF+CL-AG	Pol.	Total	Limit	Margin	Measurement Type
[MHz]	[dBμV]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]	
4880	44.88	3.59	V	48.47	73.98	25.51	PK
4880	33.34	3.59	V	36.93	53.98	17.05	AV
7320	41.28	10.28	V	51.56	73.98	22.42	PK
7320	29.53	10.28	V	39.81	53.98	14.17	AV
4880	43.91	3.59	H	47.50	73.98	26.48	PK
4880	33.05	3.59	H	36.64	53.98	17.34	AV
7320	41.15	10.28	H	51.43	73.98	22.55	PK
7320	29.44	10.28	H	39.72	53.98	14.26	AV

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Operation Mode	2 M Bit/s (37 Bytes)
Operating Frequency	2480 MHz
Channel No	CH 39

Frequency	Measured Value	AF+CL-AG	Pol.	Total	Limit	Margin	Measurement Type
[MHz]	[dBμV]	[dB/m]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]	
4960	42.55	2.96	V	45.51	73.98	28.47	PK
4960	30.93	2.96	V	33.89	53.98	20.09	AV
7440	41.20	10.60	V	51.80	73.98	22.18	PK
7440	29.53	10.60	V	40.13	53.98	13.85	AV
4960	42.16	2.96	H	45.12	73.98	28.86	PK
4960	30.08	2.96	H	33.04	53.98	20.94	AV
7440	40.76	10.60	H	51.36	73.98	22.62	PK
7440	29.49	10.60	H	40.09	53.98	13.89	AV

The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ 1 M Bit/s 37 Bytes Test Plots (Worst case : Z-V)

Radiated Spurious Emissions plot – Average Result (Ch.0 2nd Harmonic)



Date: 1.AUG.2024 14:47:54

Radiated Spurious Emissions plot – Peak Result (Ch.0 2nd Harmonic)



Date: 1.AUG.2024 14:48:19

Note:

Plots of worst case are only reported.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

9.7 RADIATED RESTRICTED BAND EDGES

Operation Mode	1 M Bit/s (37 Bytes)
Operating Frequency	2402 MHz, 2480 MHz
Channel No.	0 CH, 39 CH

Frequency	Measured Value	Ant. Pol.	Total	Limit	Margin	Measurement Type
[MHz]	[dBμV]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]	
2390.0	54.76	H	54.76	73.98	19.22	PK
2390.0	42.75	H	42.75	53.98	11.23	AV
2390.0	54.83	V	54.83	73.98	19.15	PK
2390.0	43.04	V	43.04	53.98	10.94	AV
2483.5	54.82	H	54.82	73.98	19.16	PK
2483.5	42.22	H	42.22	53.98	11.76	AV
2483.5	55.40	V	55.40	73.98	18.58	PK
2483.5	42.56	V	42.56	53.98	11.42	AV

Operation Mode	2 M Bit/s (37 Bytes)
Operating Frequency	2402 MHz, 2480 MHz
Channel No.	0 CH, 39 CH

Frequency	Measured Value	Ant. Pol.	Total	Limit	Margin	Measurement Type
[MHz]	[dBμV]	[H/V]	[dBμV/m]	[dBμV/m]	[dB]	
2390.0	54.89	H	54.89	73.98	19.09	PK
2390.0	42.86	H	42.86	53.98	11.12	AV
2390.0	55.11	V	55.11	73.98	18.87	PK
2390.0	43.05	V	43.05	53.98	10.93	AV
2483.5	54.16	H	54.16	73.98	19.82	PK
2483.5	43.06	H	43.06	53.98	10.92	AV
2483.5	55.14	V	55.14	73.98	18.84	PK
2483.5	43.15	V	43.15	53.98	10.83	AV

The report shall not be (partly) reproduced except in full without approval of the laboratory.

▣ Mode : 2 M Bit/s (37 Bytes) Test Plots

Radiated Restricted Band Edges plot – Average Result (Ch.39, Y-V)



Date: 1.AUG.2024 14:04:25

Radiated Restricted Band Edges plot – Peak Result (Ch.39, Y-V)



Date: 1.AUG.2024 14:04:54

Note:

In order to simplify the report, Plot of worst case are only reported.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

9.8 POWERLINE CONDUCTED EMISSIONS

Conducted Emissions

Test 1 / 1

Test Report

Common Information

EUT : LGSBWAC24
Operating Conditions : BLE Mode
Comment :

Full Spectrum



Final_Result_QPK

Frequency (MHz)	QuasiPeak (dBµV)	Limit (dBµV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.1500	50.30	66.00	15.70	9.000	L1	9.6
0.1660	48.05	65.16	17.11	9.000	L1	9.6
0.1740	45.00	64.77	19.76	9.000	L1	9.6
3.2800	40.04	56.00	15.96	9.000	N	9.7
3.3760	41.05	56.00	14.95	9.000	L1	9.7
3.3880	41.33	56.00	14.67	9.000	L1	9.7
25.8480	39.63	60.00	20.37	9.000	N	9.9
26.5920	38.81	60.00	21.19	9.000	N	9.9
29.0880	39.14	60.00	20.86	9.000	L1	9.9

Final_Result_CAV

Frequency (MHz)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.1700	27.60	54.96	27.36	9.000	L1	9.6
0.1860	25.21	54.21	29.00	9.000	N	9.5
2.8440	30.06	46.00	15.94	9.000	N	9.6
3.3200	32.18	46.00	13.82	9.000	N	9.7
3.4360	31.56	46.00	14.44	9.000	L1	9.7
25.8480	26.61	50.00	23.39	9.000	N	9.9
25.8720	27.34	50.00	22.66	9.000	N	9.9
29.0920	32.26	50.00	17.74	9.000	L1	9.9
29.1000	32.17	50.00	17.83	9.000	L1	9.9

2024-08-06 오후 2:51:15

The report shall not be (partly) reproduced except in full without approval of the laboratory.

10. LIST OF TEST EQUIPMENT

Conducted Test

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
LISN	ENV216	Rohde & Schwarz	102245	07/17/2025	Annual
EMI Test Receiver	ESR	Rohde & Schwarz	101910	07/02/2025	Annual
Temperature Chamber	SU-642	ESPEC	93008124	02/19/2025	Annual
Signal Analyzer	N9030A	Keysight	MY55410508	09/04/2024	Annual
Power Meter	N1911A	Agilent	MY45100523	02/28/2025	Annual
Power Sensor	N1921A	Agilent	MY57820067	02/22/2025	Annual
Directional Coupler	87300B	Agilent	3116A03621	10/30/2024	Annual
Power Splitter	11667B	Hewlett Packard	10545	02/06/2025	Annual
DC Power Supply	E3632A	Agilent	KR75305528	01/02/2025	Annual
Attenuator(10 dB)(DC-26.5 GHz)	8493C-010	Agilent	08285	05/28/2025	Annual
Attenuator(20 dB)	18N-20dB	Rohde & Schwarz	8	02/20/2025	Annual
Software	EMC32	Rohde & Schwarz	N/A	N/A	N/A
FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	HCT CO., LTD.	N/A	N/A	N/A
Bluetooth Tester	CBT	Rohde & Schwarz	100808	02/15/2025	Annual

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

The report shall not be (partly) reproduced except in full without approval of the laboratory.

Radiated Test

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
Controller(Antenna mast)	CO3000	Innco system	CO3000-4p	N/A	N/A
Antenna Position Tower	MA4640/800-XP-EP	Innco system	S3AM	07/30/2025	Annual
Controller	EM2090	Emco	060520	N/A	N/A
Turn Table	N/A	Ets	N/A	N/A	N/A
Amp & Filter Bank Switch Controller	FBSM-01A	TNM system	0	N/A	N/A
Loop Antenna	FMZB 1513	Rohde & Schwarz	1513-333	03/07/2026	Biennial
Hybrid Antenna	VULB 9168	Schwarzbeck	9168-0895	08/16/2024	Biennial
Horn Antenna	BBHA 9120D	Schwarzbeck	9120D-1191	11/07/2025	Biennial
Horn Antenna(15 GHz ~ 40 GHz)	BBHA9170	Schwarzbeck	BBHA9170124	03/28/2025	Biennial
Band Reject Filter	WRCJV2400/2483.5-2370/2520-60/12SS	Wainwright Instruments	2	01/02/2025	Annual
Band Reject Filter	WRCJV12-4900-5100-5900-6100-50SS	Wainwright Instruments	5	06/04/2025	Annual
Band Reject Filter	WRCJV12-4900-5100-5900-6100-50SS	Wainwright Instruments	6	06/04/2025	Annual
Band Reject Filter	WRCJV5100/5850-40/50-8EEK	Wainwright Instruments	1	02/14/2025	Annual
RF Switching System	FBSR-03A (3G HPF+LNA)	T&M SYSTEM	S3L1	11/17/2024	Annual
RF Switching System	FBSR-03A (10dB ATT+LNA)	T&M SYSTEM	S3L2	11/17/2024	Annual
RF Switching System	FBSR-03A (7G HPF+LNA)	T&M SYSTEM	S3L3	11/17/2024	Annual
RF Switching System	FBSR-03A (3dB ATT+LNA)	T&M SYSTEM	S3L4	11/17/2024	Annual
Power Amplifier	CBL18265035	CERNEX	22966	11/17/2024	Annual
Power Amplifier	CBL26405040	CERNEX	25956	02/26/2025	Annual
Bluetooth Tester	TC-3000C	TESCOM	3000C000175	03/19/2025	Annual
Spectrum Analyzer	FSV40 (9 kHz ~ 40 GHz)	Rohde & Schwarz	100900	12/06/2024	Annual

Note:
1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
3. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5(Version : 2017).

The report shall not be (partly) reproduced except in full without approval of the laboratory.

11. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2408-FC003-P

The report shall not be (partly) reproduced except in full without approval of the laboratory.