

# TEST REPORT

FCC/IC BT Test for LGSBWAC94

Class II Permissive Change

**APPLICANT**

LG Electronics Inc.

**REPORT NO.**

HCT-RF-1908-FI037

**DATE OF ISSUE**

August 29, 2019

**HCT Co., Ltd.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA

Tel. +82 31 634 6300 F ax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 Fax. +82 31 645 6401



# TEST REPORT

FCC/IC BT Test for  
LGSBWAC94

REPORT NO.  
HCT-RF-1908-FI037

DATE OF ISSUE  
August 29, 2019

FCC ID/IC  
BEJLGSBWAC94/ 2703H-LGSBWAC94

Applicant **LG Electronics Inc.**  
222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea

|                        |                                                                |
|------------------------|----------------------------------------------------------------|
| Eut Type<br>Model Name | RF Module<br>LGSBWAC94                                         |
| Max. RF Output Power   | 9.414 dBm (8.74 mW)                                            |
| Modulation type        | GFSK(Normal), $\pi/4$ DQPSK and 8DPSK(EDR)                     |
| FCC Classification     | FCC Part 15 Spread Spectrum Transmitter                        |
| FCC Rule Part(s)       | Part 15 subpart C 15.247                                       |
| IC Rule Part(s)        | RSS-247 Issue 2 (February 2017)<br>RSS-Gen Issue 5(April 2018) |

This test results were applied only to the test methods required by the standard.

Tested by  
Se Wook Park

(signature)

Technical Manager  
Jong Seok Lee

(signature)

HCT CO., LTD.

*Soo Chan Lee*

SooChan Lee / CEO  
Accredited by KOLAS, Republic of KOREA

## REVISION HISTORY

The revision history for this test report is shown in table.

| Revision No. | Date of Issue   | Description     |
|--------------|-----------------|-----------------|
| 0            | August 29, 2019 | Initial Release |

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

### Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC / IC Rules under normal use and maintenance.

This laboratory is not accredited for the test results marked \*.

The above Test Report is the accredited test result by KOLAS(Korea Laboratory Accreditation Scheme) / A2LA(American Association for Laboratory Accreditation), which signed the ILAC-MRA.

## CONTENTS

|                                                   |    |
|---------------------------------------------------|----|
| 1. EUT DESCRIPTION                                | 5  |
| 2. Requirements for Bluetooth transmitter(15.247) | 6  |
| 3. TEST METHODOLOGY                               | 7  |
| EUT CONFIGURATION                                 | 7  |
| EUT EXERCISE                                      | 7  |
| GENERAL TEST PROCEDURES                           | 7  |
| DESCRIPTION OF TEST MODES                         | 8  |
| 4. INSTRUMENT CALIBRATION                         | 8  |
| 5. FACILITIES AND ACCREDITATIONS                  | 9  |
| FACILITIES                                        | 9  |
| EQUIPMENT                                         | 9  |
| 6. ANTENNA REQUIREMENTS                           | 10 |
| 7. MEASUREMENT UNCERTAINTY                        | 11 |
| 8. DESCRIPTION OF TESTS                           | 12 |
| 9. SUMMARY OF TEST RESULTS                        | 25 |
| 10. TEST RESULT                                   | 26 |
| 11. TEST PLOT                                     | 27 |
| 12. LIST OF TEST EQUIPMENT                        | 31 |

## 1. EUT DESCRIPTION

|                                                     |                                            |
|-----------------------------------------------------|--------------------------------------------|
| Model                                               | LGSBWAC94                                  |
| Additional Model                                    | -                                          |
| EUT Type                                            | RF Module                                  |
| Power Supply                                        | DC 3.30 V                                  |
| Frequency Range                                     | 2402 MHz - 2480 MHz                        |
| Max. RF Output Power                                | 9.414 dBm (8.74 mW)                        |
| BT Operating Mode                                   | Normal, EDR, AFH                           |
| Modulation Type                                     | GFSK(Normal), $\pi/4$ DQPSK and 8DPSK(EDR) |
| Modulation Technique                                | FHSS                                       |
| Number of Channels                                  | 79Channels, Minimum 20 Channels(AFH)       |
| Antenna type                                        | Metal press Ant                            |
| Antenna Peak Gain                                   | 0.71 dBi                                   |
| Date(s) of Tests                                    | August 27, 2019 ~ August 29, 2019          |
| PMN<br>(Product Marketing Number)                   | LGSBWAC94                                  |
| HVIN<br>(Hardware Version<br>Identification Number) | ETWCFLBC01                                 |
| FVIN<br>(Firmware Version<br>Identification Number) | MT7668_V1.0                                |
| HMN<br>(Host Marketing Name)                        | N/A                                        |

## 2. Requirements for Bluetooth transmitter(15.247)

This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:

- 1) This system is hopping pseudo-randomly.
- 2) Each frequency is used equally on the average by each transmitter.
- 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
- 4) The receiver shifts frequencies in synchronization with the transmitted signals.

- 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.

- 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

- RSS-247 5.1 (a): The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

### 3. TEST METHODOLOGY

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Device (ANSI C63.10-2013, KDB 558074) is used in the measurement of the test device.

#### EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C. / RSS-GEN issue 5, RSS-247 issue 2.

#### GENERAL TEST PROCEDURES

##### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

##### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3.75 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013). To record the final measurements, the analyzer detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 120 kHz for frequencies below 1 GHz or 1 MHz for frequencies above 1GHz. For average measurements above 1 GHz, the analyzer was set to peak detector with a reduced VBW setting(RBW = 1 MHz, VBW = 1/T Hz, where T =

Pulse width).

#### **DESCRIPTION OF TEST MODES**

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

#### **4. INSTRUMENT CALIBRATION**

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

## 5. FACILITIES AND ACCREDITATIONS

### FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil,

Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032 ).

For ISED, test facility was accepted dated February 14, 2019 (CAB identifier: KR0032).

### EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

## 6. ANTENNA REQUIREMENTS

### According to FCC 47 CFR § 15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

\* The antennas of this E.U.T are permanently attached.

\* The E.U.T Complies with the requirement of § 15.203

### According to RSS-GEN(Issue 5) Section 6.8:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested..

## 7. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of

ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicate a 95 % level of confidence.

The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Parameter                                | Expanded Uncertainty ( $\pm$ dB) |
|------------------------------------------|----------------------------------|
| Conducted Disturbance (150 kHz ~ 30 MHz) | 1.82                             |
| Radiated Disturbance (9 kHz ~ 30 MHz)    | 3.40                             |
| Radiated Disturbance (30 MHz ~ 1 GHz)    | 4.80                             |
| Radiated Disturbance (1 GHz ~ 18 GHz)    | 5.70                             |
| Radiated Disturbance (18 GHz ~ 40 GHz)   | 5.05                             |

## 8. DESCRIPTION OF TESTS

### 8.1. Radiated Test

#### Limit

#### FCC

| Frequency (MHz) | Field Strength (uV/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 0.009 – 0.490   | $2400/F(\text{kHz})$  | 300                      |
| 0.490 – 1.705   | $24000/F(\text{kHz})$ | 30                       |
| 1.705 – 30      | 30                    | 30                       |

#### IC


| Frequency (MHz) | Field Strength (uA/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 0.009 – 0.490   | $6.37/F(\text{kHz})$  | 300                      |
| 0.490 – 1.705   | $63.7/F(\text{kHz})$  | 30                       |
| 1.705 – 30      | 0.08                  | 30                       |

#### FCC&IC


| Frequency (MHz) | Field Strength (uV/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 30-88           | 100                   | 3                        |
| 88-216          | 150                   | 3                        |
| 216-960         | 200                   | 3                        |
| Above 960       | 500                   | 3                        |

## Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



## Test Procedure of Radiated spurious emissions(Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) =  $40 \cdot \log(3 \text{ m}/300 \text{ m}) = - 80 \text{ dB}$   
Measurement Distance : 3 m
7. Distance Correction Factor(0.490 MHz – 30 MHz) =  $40 \cdot \log(3 \text{ m}/30 \text{ m}) = - 40 \text{ dB}$   
Measurement Distance : 3 m
8. Spectrum Setting
  - Frequency Range = 9 kHz ~ 30 MHz
  - Detector = Peak
  - Trace = Maxhold
  - RBW = 9 kHz
  - VBW  $\geq 3 \cdot \text{RBW}$
9. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

**KDB 414788 OFS and Chamber Correlation Justification**

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

**Test Procedure of Radiated spurious emissions(Below 1GHz)**

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

**5. Spectrum Setting****(1) Measurement Type(Peak):**

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 100 kHz
- VBW  $\geq 3 \times$  RBW

**(2) Measurement Type(Quasi-peak):**

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

\*In general, (1) is used mainly

6. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)
7. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

**Test Procedure of Radiated spurious emissions (Above 1 GHz)**

1. Radiated test is performed with hopping off.
2. The EUT is placed on a turntable, which is 1.5 m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
6. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).  
\*Distance extrapolation factor =  $20 \cdot \log (\text{test distance} / \text{specific distance})$  (dB)
7. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
8. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
9. The unit was tested with its standard battery.
10. Spectrum Setting
  - (1) Measurement Type(Peak):
    - Measured Frequency Range : 1 GHz – 25 GHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 1 MHz
    - VBW  $\geq 3 \cdot \text{RBW}$
  - (2) Measurement Type(Average):
    - We performed using a reduced video BW method was done with the analyzer in linear mode
    - Measured Frequency Range : 1 GHz – 25 GHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 1 MHz
    - VBW  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds

The actual setting value of VBW = 1 kHz
11. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
12. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

### **Test Procedure of Radiated Restricted Band Edge**

1. Radiated test is performed with hopping off.
2. The EUT is placed on a turntable, which is 1.5 m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
6. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).  
\*Distance extrapolation factor =  $20 \cdot \log (\text{test distance} / \text{specific distance})$  (dB)
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.

### **9. Spectrum Setting**

#### **(1) Measurement Type(Peak):**

- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW  $\geq 3 \cdot \text{RBW}$

#### **(2) Measurement Type(Average):**

We performed using a reduced video BW method was done with the analyzer in linear mode

- Detector = Peak
  - Trace = Maxhold
  - RBW = 1 MHz
  - VBW  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds
- The actual setting value of VBW = 1 kHz

### **10. Total**

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

## 8.2. AC Power line Conducted Emissions

### Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN).

| Frequency Range (MHz) | Limits (dB $\mu$ V) |           |
|-----------------------|---------------------|-----------|
|                       | Quasi-peak          | Average   |
| 0.15 to 0.50          | 66 to 56*           | 56 to 46* |
| 0.50 to 5             | 56                  | 46        |
| 5 to 30               | 60                  | 50        |

\*Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

**Test Procedure**

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.
5. The EUT is the device operating below 30 MHz.
  - For unterminated the Antenna, the AC line conducted tests are performed with the antenna connected
  - For terminated the Antenna, the AC line conducted tests are performed with a dummy load connected to the EUT antenna output terminal.

**Sample Calculation**

Quasi-peak(Final Result) = Reading Value + Correction Factor

### 8.3. Receiver Spurious Emissions

#### Limit


| Frequency (MHz) | Field Strength (uV/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 30-88           | 100                   | 3                        |
| 88-216          | 150                   | 3                        |
| 216-960         | 200                   | 3                        |
| Above 960       | 500                   | 3                        |

Note:


Measurements for compliance with the limits in table may be performed at distances other than 3 metres.

#### Test Configuration

30 MHz - 1 GHz



Above 1 GHz



## Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).  
 $\text{*Distance extrapolation factor} = 20 \cdot \log(\text{test distance} / \text{specific distance}) \text{ (dB)}$
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting
  - (1) Measurement Type(Peak):
    - Measured Frequency Range : 1 GHz – 25 GHz

- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW  $\geq 3 \times$  RBW

(2) Measurement Type(Average):

- We performed using a reduced video BW method was done with the analyzer in linear mode
- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds

The actual setting value of VBW = 1 kHz

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

11. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

#### **8.4. Worst case configuration and mode**

##### **Radiated test**

1. All modes of operation were investigated and the worst case configuration results are reported.
  - Mode : Stand alone
  - Worstcase : Stand alone
2. EUT Axis
  - Radiated Spurious Emissions : X
  - Radiated Restricted Band Edge : X
3. All data rate of operation were investigated and the test results are worst case in highest datarate of each mode.
  - GFSK : DH5
  - $\pi/4$ DQPSK : 2-DH5
  - 8DPSK : 3-DH5
4. All position of loop antenna were investigated and the test result is a no critical peak found at all positions.
  - Position : Horizontal, Vertical, Parallel to the ground plane

##### **AC Power line Conducted Emissions**

1. All modes of operation were investigated and the worst case configuration results are reported.
  - Mode : Stand alone + External accessories (Notebook)

##### **Conducted test**

1. The EUT was configured with data rate of highest power.
  - GFSK : DH5
  - $\pi/4$ DQPSK : 2-DH5
  - 8DPSK : 3-DH5
2. AFH & Non-AFH were tested and the worst case results are reported.  
(Worst case : Non-AFH)

## 9. SUMMARY OF TEST RESULTS

| Test Description                  | FCC Part Section(s)               | Test Limit           | Test Condition | Test Result | Status              |
|-----------------------------------|-----------------------------------|----------------------|----------------|-------------|---------------------|
| 6 dB Bandwidth                    | § 15.247(a)(2)                    | > 500 kHz            | Conducted      | PASS        | NT <sup>Note2</sup> |
| Conducted Maximum Output Power    | § 15.247(b)(3)                    | < 1 Watt             |                | PASS        | C <sup>Note4</sup>  |
| Power Spectral Density            | § 15.247(e)                       | < 8 dBm / 3 kHz Band |                | PASS        | NT <sup>Note2</sup> |
| Band Edge (Out of Band Emissions) | § 15.247(d)                       | Conducted > 30 dBc   |                | PASS        | NT <sup>Note2</sup> |
| AC Power line Conducted Emissions | § 15.207                          | cf. Section 7.7      |                | PASS        | NT <sup>Note2</sup> |
| Radiated Spurious Emissions       | § 15.247(d),<br>15.205,<br>15.209 | cf. Section 7.6      | Radiated       | PASS        | C <sup>Note3</sup>  |
| Radiated Restricted Band Edge     | § 15.247(d),<br>15.205,<br>15.209 | cf. Section 7.6      |                | PASS        | C <sup>Note3</sup>  |

### Note:

1. C = Comply, NT = Not Tested, NA = Not Applicable, NC = Not Comply
2. C2PC model is electrically identical to the Original model.  
The Product Equality Declaration includes detailed information about the changes between the devices.
3. The data from that application has been verified through appropriate spot checks to demonstrate compliance for this device as shown in the test result of section 9
4. Output power was verified to be within the expected tune up tolerances prior to performing the spot checks for radiated spurious emissions and band edge to confirm that the proposed changes to the digital circuitry had not adversely affected the previously reported values in the original filing.


## 10. TEST RESULT

| Test Item | Data Rate | Channel | Measured Frequency (MHz) | Original Result [dBuV/m] |       | C2PC Result [dBuV/m] |       | Deviation (dB) |      |
|-----------|-----------|---------|--------------------------|--------------------------|-------|----------------------|-------|----------------|------|
|           |           |         |                          | Average                  | Peak  | Average              | Peak  | Average        | Peak |
| Band Edge | DH5       | Ch.78   | 2483.5 MHz<br>~2500 MHz  | 67.47                    | 70.51 | 65.17                | 68.81 | 2.30           | 1.70 |
| RSE       | DH5       | Ch.0    | 7206 MHz                 | 48.82                    | 57.65 | 47.68                | 56.74 | 1.14           | 0.91 |


## 11. TEST PLOT

### Bandedge

| Frequency<br>[MHz] | Reading<br>[dBuV] | A.F.+CL<br>[dB] | Pol.<br>[H/V] | Duty Cycle<br>Correction<br>[dB] | Total<br>[dBuV/m] | Limit<br>[dBuV/m] | Margin<br>[dB] | Measurement<br>Type |
|--------------------|-------------------|-----------------|---------------|----------------------------------|-------------------|-------------------|----------------|---------------------|
| 2483.5             | 33.45             | 35.36           | V             | 0                                | 68.81             | 73.98             | 5.17           | PK                  |
| 2483.5             | 29.81             | 35.36           | V             | -24.73                           | 40.44             | 53.98             | 13.54          | AV                  |




Date: 28.AUG.2019 10:13:15




Date: 28.AUG.2019 10:12:25

## RSE

| Frequency<br>[MHz] | Reading<br>[dBuV] | AN.+CL-AMP G<br>[dB] | Pol.<br>[H/V] | Total<br>[dBuV/m] | Limit<br>[dBuV/m] | Margin<br>[dB] | Measurement<br>Type |
|--------------------|-------------------|----------------------|---------------|-------------------|-------------------|----------------|---------------------|
| 7206               | 47.77             | 8.97                 | H             | 56.74             | 73.98             | 17.24          | PK                  |
| 7206               | 38.71             | 8.97                 | H             | 47.68             | 53.98             | 6.30           | AV                  |



Date: 28.AUG.2019 10:31:55



Date: 28.AUG.2019 10:32:46

## 12. LIST OF TEST EQUIPMENT

### Radiated Test

| Manufacturer           | Model / Equipment                                       | Calibration Date | Calibration Interval | Serial No.  |
|------------------------|---------------------------------------------------------|------------------|----------------------|-------------|
| Innco system           | CO3000 / Controller(Antenna mast)                       | N/A              | N/A                  | CO3000-4p   |
| Innco system           | MA4640/800-XP-EP / Antenna Position Tower               | N/A              | N/A                  | N/A         |
| Emco                   | 2090 / Controller                                       | N/A              | N/A                  | 060520      |
| Ets                    | Turn Table                                              | N/A              | N/A                  | N/A         |
| Rohde & Schwarz        | Loop Antenna                                            | 08/23/2018       | Biennial             | 1513-175    |
| Schwarzbeck            | VULB 9160 / Hybrid Antenna                              | 08/09/2018       | Biennial             | 3368        |
| Schwarzbeck            | BBHA 9120D / Horn Antenna                               | 11/21/2017       | Biennial             | 9120D-1191  |
| Schwarzbeck            | BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)                | 12/04/2017       | Biennial             | BBHA9170541 |
| Rohde & Schwarz        | FSP(9 kHz ~ 30 GHz) / Spectrum Analyzer                 | 09/19/2018       | Annual               | 836650/016  |
| Rohde & Schwarz        | FSV40-N / Spectrum Analyzer                             | 09/19/2018       | Annual               | 101068-SZ   |
| Wainwright Instruments | WHKX10-2700-3000-18000-40SS / High Pass Filter          | 01/03/2019       | Annual               | 4           |
| Wainwright Instruments | WHKX8-6090-7000-18000-40SS / High Pass Filter           | 01/03/2019       | Annual               | 5           |
| Wainwright Instruments | WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter | 06/19/2019       | Annual               | 2           |
| Wainwright Instruments | WRCJV5100/5850-40/50-8EEK / Band Reject Filter          | 01/03/2019       | Annual               | 2           |
| Api tech.              | 18B-03 / Attenuator (3 dB)                              | 06/04/2019       | Annual               | 1           |
| WEINSCHL               | 56-10 / Attenuator(10 dB)                               | 10/10/2018       | Annual               | 72316       |
| CERNEX                 | CBLU1183540B-01/Broadband Bench Top LNA                 | 01/03/2019       | Annual               | 28549       |
| CERNEX                 | CBL06185030 / Broadband Low Noise Amplifier             | 01/03/2019       | Annual               | 24615       |
| CERNEX                 | CBL18265035 / Power Amplifier                           | 01/03/2019       | Annual               | 22966       |
| CERNEX                 | CBL26405040 / Power Amplifier                           | 06/18/2019       | Annual               | 25956       |
| TESCOM                 | TC-3000C / Bluetooth Tester                             | 03/26/2019       | Annual               | 3000C000276 |

### **Note:**

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.