




PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA
Tel. 410.290.6652 / Fax 410.290.6554
<http://www.pctestlab.com>



RF EXPOSURE EVALUATION (MAXIMUM PERMISSIBLE EXPOSURE)

Applicant Name:

LG Electronics USA
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:

March 22, 2011

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0Y1103230620.BEJ

FCC ID: BEJLTGEN97L

APPLICANT: LG Electronics USA

EUT Type: Cellular/PCS CDMA/EvDO Transceiver with Bluetooth

FCC Rule Part(s): FCC Part 1 (§1.1310) and Part 2 (§2.1091)

FCC Classification: PCS Licensed Transmitter (PCB)

Test Procedure: OET Bulletin 65

The device bearing the FCC Identifier specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in FCC OET Bulletin 65 (See Test Report). These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti -Drug Abuse Act of 1988, 21 U.S.C. 862.


Randy Ortanez
President



FCC ID: BEJLTGEN97L		 MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT			Reviewed by: Quality Manager
Test Report S/N: 0Y1103230620.BEJ	Test Dates: March 22, 2011	EUT Type: Cellular/PCS CDMA/EvDO Transceiver with Bluetooth			Page 1 of 8

TABLE OF CONTENTS

1.0	RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	3
1.1	INTRODUCTION.....	3
1.2	EUT DESCRIPTION	3
1.3	MPE REQUIREMENTS OVERVIEW	4
1.4	TRANSMITTER CONDUCTED OUTPUT POWER	5
1.5	PROCEDURE.....	6
1.6	SUMMARY OF RESULTS.....	7
2.0	CONCLUSION	8

FCC ID: BEJLTGEN97L		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1103230620.BEJ	Test Dates: March 22, 2011	EUT Type: Cellular/PCS CDMA/EvDO Transceiver with Bluetooth		Page 2 of 8

1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 Introduction

This document is prepared on behalf of LG Electronics USA to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations and RSS-102 of Industry Canada.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310 and RSS-102: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

Table 1-1. Limits for Maximum Permissible Exposure (MPE)

1.2 EUT Description

The LG Model: GEN97L is a Cellular/PCS CDMA/EvDO Transceiver with Bluetooth. For this MPE evaluation the maximum permissible antenna gain is calculated based on the power density limit in the cellular band and the EIRP limit in the PCS band as the limiting factors.

EUT:

Model: GEN97L
 Grantee: LG Electronics USA
 FCC ID: BEJLTGEN97L
 EUT Type: Cellular/PCS CDMA/EvDO Transceiver with Bluetooth
 Conducted Powers: Cellular: 26.05 dBm
 PCS: 23.83 dBm

FCC ID: BEJLTGEN97L		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1103230620.BEJ	Test Dates: March 22, 2011	EUT Type: Cellular/PCS CDMA/EvDO Transceiver with Bluetooth		Page 3 of 8

1.3 MPE Requirements Overview

Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile, and portable and are defined as follows:

- o **Fixed Installations:** fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- o **Mobile Devices:** a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.
- o **Portable Devices:** a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

- o **Occupational/Controlled Exposure:** In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
- o **General Population/Uncontrolled Exposure:** The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

The LG Cellular/PCS CDMA/EvDO Transceiver with Bluetooth FCC ID: BEJLTGEN97L is evaluated to the Mobile Device requirements and is considered a device to be used by the General Population/Uncontrolled Exposure.

FCC ID: BEJLTGEN97L		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1103230620.BEJ	Test Dates: March 22, 2011	EUT Type: Cellular/PCS CDMA/EvDO Transceiver with Bluetooth		Page 4 of 8

1.4 Transmitter Conducted Output Power

		Loopback							Data			
Band	Channel	SO2 [dBm]	SO2 [dBm]	SO2 [dBm]	SO55 [dBm]	SO55 [dBm]	SO9 [dBm]	SO9 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]	1x EvDO Rev. A [dBm]
	F-RC	RC1	RC3	RC4	RC1	RC3	RC2	RC5	(FTAP)	(RTAP)	(FETAP)	(RETAP)
	Vocoder Rate	Full	Full	Full	Full	Full	Full	Full	N/A	N/A	N/A	N/A
Cellular	1013	25.97	25.92	25.93	26.05	26.02	26.04	26.02	25.32	25.24	25.35	25.28
	384	24.78	24.74	24.72	24.95	24.71	24.72	24.71	24.04	24.00	24.06	24.09
	777	24.72	24.81	24.80	24.92	24.79	24.81	24.89	23.93	24.01	24.10	24.05
PCS	25	23.71	23.68	23.67	23.70	23.57	23.67	23.63	23.03	23.08	23.04	23.15
	600	23.78	23.65	23.72	23.75	23.83	23.70	23.75	23.66	23.70	23.72	23.65
	1175	23.63	23.51	23.53	23.54	23.52	23.59	23.49	23.62	23.53	23.53	23.51

Table 1-2. Conducted Output Powers




Figure 1-1. Test Setup and Instrumentation

1.5 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by the transmitter used in this product was initially measured by the call box and the powers were recorded. Through use of the Friis transmission formula, the maximum antenna gain is calculated based on one of two limiting factors: (1) power density limit at a distance of 20cm in the cellular band and (2) the EIRP limit in the PCS band.

Friis Transmission Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4\pi r^2)$

Where,

P_d = Power Density (mW/cm²)

$p = 3.1416$

P_{out} = output power to antenna (mW)

r = distance between observation point and center of the radiator (cm)

G = gain of antenna in linear scale

Calculated MPE

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the information in Table 1-1. The following power densities are calculated for each of the transmitters' bands of operation at 20cm spacing:

Frequency	824.7 MHz	
Limit	0.550 mW/cm ²	
Distance (cm), R =	20 cm	
Power (dBm), P =	26.05 dBm	402.72 mW
TX Ant Gain (dBi), G =	8.35 dBi	
Power Density (S) =	0.548 mW/cm ²	(at 20cm)
Minimum Distance =	20.0 cm	

Table 1-3. Calculated MPE Data for Cellular Band

Frequency:	1880 MHz	
Limit:	1.000 mW/cm ²	
Distance (cm), R =	20 cm	
Power (dBm), P =	23.83 dBm	241.55 mW
TX Ant Gain (dBi), G =	9.17 dBi	
Power Density (S) =	0.3969 mW/cm ²	(at 20cm)
Minimum Distance =	12.6 cm	

Table 1-4. Calculated MPE Data for PCS Band

FCC ID: BEJLTGEN97L		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1103230620.BEJ	Test Dates: March 22, 2011	EUT Type: Cellular/PCS CDMA/EvDO Transceiver with Bluetooth		Page 6 of 8

1.6 Summary of Results

Frequency Band [MHz]	Maximum Antenna Gain [dBi]	MPE @ 20cm (mW/cm ²)	Test Result
824.7 – 848.31	8.35	0.548	PASS
1851.25 – 1908.75	9.17	0.3969	PASS

Table 1-5. Maximum Permissible Exposure Summary Table

FCC ID: BEJLTGEN97L		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1103230620.BEJ	Test Dates: March 22, 2011	EUT Type: Cellular/PCS CDMA/EvDO Transceiver with Bluetooth		Page 7 of 8

2.0 CONCLUSION

The device meets the mobile RF exposure limit at a 20cm separation distance as specified in §2.1091 of the FCC Rules and Regulations and Health Canada Safety Code 6. An appropriate RF exposure compliance statement will be placed in the user's manual.

FCC ID: BEJLTGEN97L		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1103230620.BEJ	Test Dates: March 22, 2011	EUT Type: Cellular/PCS CDMA/EvDO Transceiver with Bluetooth		Page 8 of 8