HCT CO., LTD.
Product Compliance Division
TEL : +82 31 639 8518 FAX : +82 31 639 8535

CERTIFICATE OF COMPLIANCE

FCC Certification

Applicant Name:
LG Electronics, Inc.

Address:
60-39, Gasan-dong, Gumchon-gu, Seoul 153-023, Korea

Date of Issue:
December 28, 2009

Location:
HCT.CO., LTD., San 136-1 Ami-ri, Bubal-eup, Icheon-si, Kyoungki-do, Korea

Test Report No.: HCTR0912FR10

HCT FRN: 0005866421

IC Recognition No.: IC 5944A-1

FCC ID:	**BEJLUU2110TI**
APPLICANT:	**LG Electronics, Inc.**

Model(s):	LUU-2110TI
EUT Type:	Cellular/ PCS GSM/ WCDMA/ EDGE USB Dongle
Tx Frequency:	824.20 - 848.80 MHz (GSM850) 1 850.20 - 1 909.80 MHz (GSM1900) 1 852.4 – 1 907.6 MHz (WCDMA1900)
Rx Frequency:	869.20 - 893.80 MHz (GSM850) 1 930.20 - 1 989.80 MHz (GSM1900) 1 932.4 – 1 987.6 MHz (WCDMA1900)
Max. RF Output Power:	1.297 W ERP GSM850 (31.13 dBm) / 0.525 W EIRP GSM1900 (27.20 dBm) 0.635 W ERP EDGE850 (28.03 dBm) / 0.396 W EIRP EDGE1900 (25.98 dBm) 0.254 W EIRP WCDMA1900(24.04 dBm)
Emission Designator(s):	251KGXW (GSM850) 246KGXW (GSM1900) 250KG7W (GSM850 EDGE) 248KG7W (GSM1900 EDGE) 4M14F9W (WCDMA1900)
FCC Classification:	PCS Licensed Transmitter (PCB)
FCC Rule Part(s):	§22, §24, §2

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT.CO., LTD. Certifies that no party to this application has been denied FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

Jong Seok Lee

Report prepared by
: Jong Seok Lee
Test engineer of RF Team

Sang Jun Lee

Approved by
: Sang Jun Lee
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Table of Contents

1. GENERAL INFORMATION 3
2. INTRODUCTION 4
    2.1. EUT DESCRIPTION 4
    2.2. MEASURING INSTRUMENT CALIBRATION 4
    2.3. TEST FACILITY 4
3. DESCRIPTION OF TESTS 5
    3.1 Effective Radiated Power/Equivalent Isotropic Radiated Power 5
    3.2 Peak- to- Average Ratio 6
    3.3 Occupied bandwidth. 7
    3.4 Spurious and Harmonic Emissions at Antenna Terminal. 8
    3.5 Radiated Spurious and Harmonic Emissions 9
    3.6 Frequency stability / variation of ambient temperature 10
4. LIST OF TEST EQUIPMENT 11
5. SUMMARY OF TEST RESULTS 12
6. SAMPLE CALCULATION 13
7. TEST DATA 14
    7.1 Conducted Output Power 14
    7.2 Peak-to-Average Ratio 15
    7.3 Occupied Bandwidth 16
    7.4 Conducted Spurious Emissions 17
        7.4.1 Band Edge 17
    7.5 Effective Radiated Power Output (GSM) 18
    7.6 Equivalent Isotropic Radiated Power (GSM / WCDMA) 19
    7.7 Radiated Spurious Emissions 20
        7.7.1 Radiated Spurious Emissions (GSM850) 20
        7.7.2 Radiated Spurious Emissions (GSM1900) 21
        7.7.3 Radiated Spurious Emissions (WCDMA1900) 22
    7.8 Frequency stability / variation of ambient temperature 23
        7.8.1 FREQUENCY STABILITY (GSM850) 23
        7.8.2 FREQUENCY STABILITY (GSM1900) 24
        7.8.3 FREQUENCY STABILITY (WCDMA1900) 25
8. TEST PLOTS 26

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	LG Electronics, Inc.
Address:	60-39, Gasan-dong, Gumchon-gu, Seoul 153-023, Korea
FCC ID:	BEJLUU2110TI
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter (PCB)
FCC Rule Part(s):	§22, §24, §2
EUT Type:	Cellular/ PCS GSM/ WCDMA/ EDGE USB Dongle
Model(s):	LUU-2110TI
Tx Frequency:	824.20 - 848.80 MHz (GSM850) 1 850.20 - 1 909.80 MHz (GSM1900) 1 852.4 – 1 907.6 MHz (WCDMA1900)
Rx Frequency:	869.20 - 893.80 MHz (GSM850) 1 930.20 - 1 989.80 MHz (GSM1900) 1 932.4 – 1 987.6 MHz (WCDMA1900)
Max. RF Output Power:	1.297 W ERP GSM850 (31.13 dBm) / 0.525 W EIRP GSM1900 (27.20 dBm) 0.635 W ERP EDGE850 (28.03 dBm) / 0.396 W EIRP EDGE1900 (25.98 dBm) 0.254 W EIRP WCDMA1900(24.04 dBm)
Emission Designator(s):	251KGXW (GSM850) 246KGXW (GSM1900) 250KG7W (GSM850 EDGE) 248KG7W (GSM1900 EDGE) 4M14F9W (WCDMA1900)
Antenna Specification	Manufacturer: KOMATECH Co., Ltd. Antenna type: Internal Antenna Peak Gain: 1.457 dBi
Date(s) of Tests:	October 24, 2009 ~ December 16, 2009

2. INTRODUCTION

2.1. EUT DESCRIPTION

The LG Electronics, Inc. LUU-2110TI Cellular/ PCS GSM/ WCDMA/ EDGE USB Dongle consists of GSM850, GSM1900, GPRS12 and GPRS mode Class B(GPRS and GSM, but not simultaneously), EDGE, WCDMA1900, HSDPA and HSUPA.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, Maekok-Ri, Hobup-Myun, Ichon-Si, Kyoungki-Do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated June 10, 2009(Registration Number: 90661)

3. DESCRIPTION OF TESTS

3.1 Effective Radiated Power/Equivalent Isotropic Radiated Power

Test Set-up



Test Procedure

Radiated emission measurements were performed at an open Site.

The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

A wooden turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.

The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

3.2 Peak- to- Average Ratio

A peak to average ratio measurement is performed at the conducted port of the EUT. For CDMA and WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. Plots of the EUT's Peak- to- Average Ratio are shown herein.

3.3 Occupied bandwidth.

Test set-up



(Configuration of conducted Emission measurement)
Test Procedure

The EUT was setup to maximum output power at its lowest channel. The occupied bandwidth was measured using a spectrum analyzer. The measurements are repeated for the highest and a middle channel. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Plots of the EUT's occupied bandwidth are shown herein.

3.4 Spurious and Harmonic Emissions at Antenna Terminal.

Test Procedure

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.

The EUT was setup to maximum output power at its lowest channel. The Resolution BW of the analyzer is set to 1 % of the emission bandwidth to show compliance with the – 13 dBm limit, in the 1 MHz bands immediately outside and adjacent to the edge of the frequency block. The 1 MHz RBW was used to scan from 10 MHz to 10 GHz. (GSM1900 Mode: 10 MHz to 20 GHz). A display line was placed at – 13 dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.

- Band Edge Requirement : In the 1MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions. Limit, -13dBm.

3.5 Radiated Spurious and Harmonic Emissions

Test Set-up



The measurement facilities used for this test have been documented in previous filings with the commission pursuant to section § 2.948. The open field test site is situated in open field with ground screen whose site attenuation characteristics meet ANSI C63.4 –2003. A mast capable of lifting the receiving antenna from a height of one to four meters is used together with a rotatable wooden platform mounted at three from the antenna mast.

1) The unit mounted on a wooden table 1.5 m × 1.0 m × 0.80 m is 0.8 meter above test site ground level.
2) During the emission test, the turntable is rotated and the EUT is manipulated to find the configuration resulting in maximum emission under normal condition of installation and operation.
3) The antenna height and polarization are also varied from 1 to 4 meters until the maximum signal is found.
4) The spectrum shall be scanned up to the 10th harmonic of the fundamental frequency.

Test Procedure

The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

A wooden turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.

The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

3.6 Frequency stability / variation of ambient temperature

Test Set-up



* Nominal Operating Voltage

Test Procedure

The frequency stability of the transmitter is measured by:
a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.

b.) **Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 115 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 0.000 25 %(± 2.5 ppm) of the center frequency.

Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
1. The equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.

2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.
NOTE: The EUT is tested down to the battery endpoint.

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Interval	Calibration Due
R&S	ESI40/ Spectrum Analyzer	831564/003	Annual	10/30/2010
Agilent	E4416A/ Power Meter	GB41291412	Annual	01/21/2010
Agilent	E9327A/ Power Sensor	MY4442009	Annual	07/28/2010
Agilent	8960 (E5515C)/ Base Station	GB44400269	Annual	02/10/2010
MITEQ	AMF-60-0010 1800-35-20P / AMP	1200937	Annual	05/20/2010
Wainwright	WHK1.2/15G-10EF/H.P.F	2	Annual	06/29/2010
Wainwright	WHK3.3/18G-10EF/H.P.F	1	Annual	06/29/2010
Agilent	775D/ Dual Directional Coupler	12922	Annual	12/24/2010
Agilent	11636B/ Power Divider	11377	Annual	12/24/2010
Digital	EP-3010/ Power Supply	3110117	Annual	01/07/2010
Schwarzbeck	UHAP/ Dipole Antenna	585	Biennial	02/13/2011
Schwarzbeck	UHAP/ Dipole Antenna	558	Biennial	02/13/2011
Korea Engineering	KR-1005L / Chamber	KRAB07063-2CH	Annual	12/31/2009
Schwarzbeck	BBHA 9120D/ Horn Antenna	147	Biennial	03/26/2010
Agilent	E4440A/Spectrum Analyzer	US45303008	Annual	12/23/2010

5. SUMMARY OF TEST RESULTS

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result
2.1049, 22.917(a), 24.238(a)	Occupied Bandwidth	N/A	CONDUCTED	PASS
2.1051, 22.917(a), 24.238(a)	Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	< 43 + 10log$_{10}$ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS
2.1046	Conducted Output Power	N/A		PASS
24.232(d)	Peak- to- Average Ratio	< 13 dB		
2.1055, 22.355, 24.235	Frequency stability / variation of ambient temperature	< 2.5 ppm		PASS
22.913(a)(2) 24.232(c)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS
	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS
2.1053, 22.917(a), 24.238(a)	Radiated Spurious and Harmonic Emissions	< 43 + 10log$_{10}$ (P[Watts]) for all out-of band emissions		PASS

6. SAMPLE CALCULATION

A. ERP Sample Calculation

Mode	Ch./ Freq.		Measured Level(dBm)	Substitude LEVEL(dBm)	Ant. Gain	C.L	Pol.	ERP	
	channel	Freq.(MHz)						W	dBm
GSM850	128	824.20	-11.56	34.28	-8.32	1.17	H	0.30	24.79

ERP = SubstitudeLEVEL(dBm) + Ant. Gain – CL(Cable Loss)

1) The EUT mounted on a wooden tripod is 0.8 meter above test site ground level.
2) During the test , the turn table is rotated and the antenna height is also varied from 1 to 4 meters until the maximum signal is found.
3) Record the field strength meter's level.
4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power (**ERP**).

B. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

7. TEST DATA

This Module is not supported a voice mode. So the worst case of the EUT is GPRS mode during the test at GSM850, 1900.

7.1 Conducted Output Power

A base station simulator was used to establish communication with the EUT. The base station simulator parameters were set to produce the maximum power from the EUT. This device was tested under all configurations and the highest power is reported. Conducted Output Powers of EUT are reported below.



Test Result

Band	Channel	GPRS Data			
		GPRS 1 TX Slot (dBm)	GPRS 2 TX Slot (dBm)	GPRS 3 TX Slot (dBm)	GPRS 4 TX Slot (dBm)
GSM 850	128	32.27	30.14	28.31	27.15
	190	32.28	30.15	28.34	27.17
	251	32.25	30.17	28.35	27.19
GSM 1900	512	29.74	27.08	25.30	24.07
	661	29.83	27.11	25.30	24.10
	810	29.82	27.31	25.44	24.23

(GSM Conducted Maximum Output Powers)

Band	Channel	EDGE Data			
		EDGE 1 TX Slot (dBm)	EDGE 2 TX Slot (dBm)	EDGE 3 TX Slot (dBm)	EDGE 4 TX Slot (dBm)
GSM 850	128	26.17	22.98	20.95	20.04
	190	26.26	22.78	20.85	19.75
	251	26.19	22.99	21.08	19.59
GSM 1900	512	25.65	22.42	20.32	18.99
	661	25.70	22.40	20.28	18.96
	810	25.67	22.20	20.17	18.91

(GSM EDGE Conducted Output Powers)

3GPP Release Version	Mode	3GPP 34.121 Subtest	PCS Band [dBm]			MPR
			9262	9400	9538	
99	WCDMA	12.2 kbps RMC	22.12	22.35	21.85	-
5	HSDPA	Subtest 1	22.30	22.57	22.58	0.0
5		Subtest 2	22.16	22.41	22.27	0.0
5		Subtest 3	21.71	22.08	21.68	-0.5
5		Subtest 4	21.60	21.90	21.62	-0.5
6	HSUPA	Subtest 1	20.55	20.63	20.08	-1.5
6		Subtest 2	20.25	20.15	19.82	-2.0
6		Subtest 3	20.94	21.25	20.83	-1.0
6		Subtest 4	20.02	20.08	19.56	-2.0
6		Subtest 5	20.63	20.53	20.65	-1.5

(WCDMA Conducted Output Powers)

Note : Detecting mode is average.

7.2 Peak-to-Average Ratio

- Plots of the EUT's Peak- to- Average Ratio are shown Page 31, 33.

7.3 Occupied Bandwidth

Band	Channel	Frequency(MHz)	Data (GSM: kHz / WCDMA : MHz)
GSM850	128	824.20	250.6587
	190	836.60	244.7131
	251	848.80	245.2428
GSM850 EDGE	128	824.20	249.8401
GSM1900	512	1850.20	246.0831
	661	1880.00	245.5856
	810	1909.80	244.0766
GSM1900 EDGE	512	1850.20	247.7808
WCDMA1900	9262	1852.40	4.1403
	9400	1880.00	4.1306
	9538	1907.60	4.1400

- Plots of the EUT's Occupied Bandwidth are shown Page 27 ~ 30, 32 ~ 33.

7.4 Conducted Spurious Emissions

Band	Channel	Frequency of Maximum Harmonic (GHz)	Maximum Data (dBm)
GSM850	128	6.9500	-30.82
	190	7.1125	-30.13
	251	7.0000	-31.00
GSM1900	512	14.8800	-27.84
	661	13.8670	-27.40
	810	13.7870	-26.91
WCDMA1900	9262	14.1600	-37.46
	9400	13.2800	-37.55
	9538	13.9200	-37.88

- Plots of the EUT's Conducted Spurious Emissions are shown Page 40 ~ 48.

7.4.1 Band Edge

- Plots of the EUT's Band Edge are shown Page 34 ~ 39.

7.5 Effective Radiated Power Output (GSM)

(GSM850 Mode)

Ch./ Freq.		Measured	Substitude	Ant. Gain	C.L	Pol.	ERP	
channel	Freq.(MHz)	Level(dBm)	LEVEL (dBm)	(dBd)			**W**	**dBm**
128	824.20	-6.42	39.42	-8.32	1.17	H	0.98	29.93
190	836.60	-6.15	40.34	-8.22	1.19	H	1.24	30.93
251	848.80	-6.67	40.45	-8.12	1.20	H	1.30	31.13
EDGE 251	848.80	-9.77	37.35	-8.12	1.20	H	0.64	28.03

Note: This unit was tested with a notebook computer.

NOTES:

Effective Radiated Power Output Measurements by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to “1” and in GSM mode and using a Power Control Level of “0” in the PCS Band and “5” in the Cellular Band. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is in x plane in GSM850 mode. Also worst case of detecting Antenna is in horizontal polarization in GSM850 mode.

The EDGE mode testing were performed using 1Tx because 1Tx is highest power in EDGE mode.

7.6 Equivalent Isotropic Radiated Power (GSM / WCDMA)

(GSM1900 Mode)

Ch./ Freq.		Measured	Substitude	Ant. Gain	C.L	Pol.	EIRP	
channel	Freq.(MHz)	Level(dBm)	LEVEL (dBm)	(dBi)			**W**	**dBm**
512	1,850.20	−12.95	18.66	10.05	1.91	V	0.48	26.79
661	1,880.00	−12.95	18.87	10.05	1.95	V	0.50	26.97
810	1,909.80	−12.79	19.11	10.06	1.97	V	0.52	27.20
EDGE 810	1,909.80	−14.01	17.89	10.06	1.97	V	0.40	25.98

(WCDMA1900 Mode)

Ch./ Freq.		Measured	Substitude	Ant. Gain	C.L	Pol.	EIRP	
channel	Freq.(MHz)	Level(dBm)	LEVEL (dBm)	(dBi)			**W**	**dBm**
9262	1,852.40	−16.46	15.15	10.05	1.91	V	0.21	23.29
9400	1,880.00	−16.89	14.93	10.05	1.95	V	0.20	23.03
9538	1,907.60	−15.97	15.95	10.06	1.97	V	0.25	24.04

Note: This unit was tested with a notebook computer.

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to “1” and in GSM mode and using a Power Control Level of “0” in the PCS Band and “5” in the Cellular Band. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is in y plane in GSM1900 and WCDMA1900 mode. Also worst case of detecting Antenna is in vertical polarization in GSM1900 and WCDMA1900 mode.

The EDGE mode testing were performed using 1Tx because 1Tx is highest power in EDGE mode.

7.7 Radiated Spurious Emissions

7.7.1 Radiated Spurious Emissions (GSM850)

▣ MEASURED OUTPUT POWER: 31.13 dBm = 1.297 W

▣ MODULATION SIGNAL: GSM850

▣ DISTANCE: 3 meters

▣ LIMIT: - (43 + 10 $\log_{10}$ (W)) = - 44.13 dBc

Ch.	Freq.(MHz)	Measured Level [dBm]	Ant. Gain (dBd)	Substitute Level [dBm]	C.L	Pol.	ERP (dBm)	dBc
128 (824.2)	1,648.40	-49.50	7.09	-60.03	1.73	H	-54.67	-84.47
	2,472.60	-40.09	8.12	-47.20	2.28	H	-41.36	-71.16
	3,296.80	-57.91	9.72	-65.49	2.57	H	-58.34	-88.14
190 (836.6)	1,673.20	-40.61	7.23	-51.37	1.79	H	-45.93	-75.73
	2,509.80	-40.81	8.14	-47.94	2.33	H	-42.13	-71.93
	3,346.40	-57.55	9.99	-65.58	2.66	H	-58.25	-88.05
251 (848.8)	1,697.60	-44.57	7.41	-55.18	1.83	H	-49.60	-79.40
	2,546.40	-41.32	8.21	-48.60	2.34	H	-42.73	-72.53
	3,395.20	-47.19	9.91	-54.82	2.85	H	-47.76	-77.56

NOTES: 1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for all channel.

3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

7.7.2 Radiated Spurious Emissions (GSM1900)

▣ MEASURED OUTPUT POWER: 27.20 dBm = 0.525 W

▣ MODULATION SIGNAL: GSM1900

▣ DISTANCE: 3 meters

▣ LIMIT: - (43 + 10 $\log_{10}$ (W)) = - 40.20 dBc

Ch.	Freq.(MHz)	Measured Level [dBm]	Ant. Gain (dBi)	Substitute Level [dBm]	C.L	Pol.	EIRP (dBm)	dBc
512 (1850.2)	3,700.40	-40.22	12.46	-46.49	2.73	H	-36.76	-63.96
	5,550.60	-47.04	12.70	-48.62	3.60	V	-39.52	-66.72
	7,400.80	-52.04	11.36	-43.16	3.88	H	-35.68	-62.88
661 (1880.0)	3,760.00	-37.61	12.47	-43.58	2.73	V	-33.84	-61.04
	5,640.00	-46.92	10.60	-46.42	3.60	V	-39.42	-66.62
	7,520.00	-48.71	11.33	-39.61	3.88	V	-32.16	-59.36
810 (1909.8)	3,819.60	-40.02	12.49	-45.90	2.73	V	-36.14	-63.34
	5,729.40	-38.18	12.80	-39.49	3.60	V	-30.29	-57.49
	7,639.20	-51.40	11.30	-42.07	3.88	V	-34.65	-61.85

NOTES: 1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for all channel.

3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

7.7.3 Radiated Spurious Emissions (WCDMA1900)

- ▣ MEASURED OUTPUT POWER: 24.04 dBm = 0.254 W
- ▣ MODULATION SIGNAL: WCDMA 1900
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: - (43 + 10 $\log_{10}$ (W)) = - 37.04 dBc

Ch.	Freq.(MHz)	Measured Level [dBm]	Ant. Gain (dBi)	Substitute Level [dBm]	C.L	Pol.	EIRP (dBm)	dBc
9262	3,704.80	-54.11	12.46	-60.35	2.73	H	-50.62	-74.66
	5,557.20	-57.60	12.71	-59.21	3.60	H	-50.10	-74.14
	7,409.60	-56.55	11.36	-47.66	3.88	V	-40.18	-64.22
9400	3,760.00	-53.71	12.47	-59.68	2.73	H	-49.94	-73.98
	5,640.00	-58.11	12.75	-59.76	3.60	H	-50.61	-74.65
	7,520.00	-58.30	11.33	-49.20	3.88	H	-41.75	-65.79
9538	3,815.20	-52.78	12.46	-58.65	2.73	H	-48.92	-72.96
	5,722.80	-58.00	12.79	-59.33	3.60	V	-50.14	-74.18
	7,630.40	-57.41	11.30	-48.09	3.88	V	-40.67	-64.71

NOTES: 1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for all channel.

3. we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

7.8 Frequency stability / variation of ambient temperature

7.8.1 FREQUENCY STABILITY (GSM850)

OPERATING FREQUENCY: 836,600,000 Hz

CHANNEL: 190

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIM IT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (℃)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.700	+20(Ref)	836 600 005	4.61	0.000 001	0.006
100%		−30	836 600 006	6.47	0.000 001	0.008
100%		−20	836 600 007	7.34	0.000 001	0.009
100%		−10	836 600 002	1.50	0.000 000	0.002
100%		0	836 600 003	3.04	0.000 000	0.004
100%		+10	836 599 999	−0.94	0.000 000	−0.001
100%		+20	836 600 003	3.47	0.000 000	0.004
100%		+30	836 599 998	−1.71	0.000 000	−0.002
100%		+40	836 600 003	2.75	0.000 000	0.003
100%		+50	836 599 998	−2.22	0.000 000	−0.003
115%	4.255	+20	836 600 007	7.26	0.000 001	0.009
Batt. Endpoint	3.400	+20	836 600 009	8.73	0.000 001	0.010



7.8.2 FREQUENCY STABILITY (GSM1900)

OPERATING FREQUENCY: 1880,000,000 Hz

CHANNEL: 661

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIM IT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (℃)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.700	+20(Ref)	1879 999 995	−5.36	0.000 000	−0.003
100%		−30	1880 000 009	9.10	0.000 000	0.005
100%		−20	1880 000 005	5.01	0.000 000	0.003
100%		−10	1880 000 010	9.97	0.000 001	0.005
100%		0	1880 000 012	12.04	0.000 001	0.006
100%		+10	1880 000 008	8.41	0.000 000	0.004
100%		+20	1879 999 995	−5.05	0.000 000	−0.003
100%		+30	1880 000 006	6.12	0.000 000	0.003
100%		+40	1880 000 014	13.84	0.000 001	0.007
100%		+50	1880 000 014	14.29	0.000 001	0.008
115%	4.255	+20	1880 000 011	10.84	0.000 001	0.006
Batt. Endpoint	3.400	+20	1880 000 012	12.44	0.000 001	0.007



7.8.3 FREQUENCY STABILITY (WCDMA1900)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 9400

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIM IT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (℃)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.700	+20(Ref)	1,879,999,989	-10.52	-0.000001	-0.006
100%		-30	1,879,999,993	-7.01	0.000000	-0.004
100%		-20	1,879,999,987	-13.32	-0.000001	-0.007
100%		-10	1,880,000,008	8.48	0.000000	0.005
100%		0	1,879,999,990	-10.16	-0.000001	-0.005
100%		+10	1,880,000,004	3.52	0.000000	0.002
100%		+20	1,879,999,990	-9.94	-0.000001	-0.005
100%		+30	1,879,999,985	-15.30	-0.000001	-0.008
100%		+40	1,880,000,007	6.71	0.000000	0.004
100%		+50	1,879,999,990	-9.81	-0.000001	-0.005
115%	4.255	+20	1,880,000,010	9.62	0.000001	0.005
Batt. Endpoint	3.400	+20	1,879,999,991	-9.33	0.000000	-0.005



8. TEST PLOTS

■ GSM850 MODE (128 CH.) Occupied Bandwidth



■ GSM850 MODE (190 CH.) Occupied Bandwidth



■ GSM850 MODE (251 CH.) Occupied Bandwidth



■ GSM850 EDGE (128 CH.) Occupied Bandwidth



■ GSM1900 MODE (512 CH.) Occupied Bandwidth



■ GSM1900 MODE (661 CH.) Occupied Bandwidth



■ GSM1900 MODE (810 CH.) Occupied Bandwidth



■ GSM1900 EDGE (512 CH.) Occupied Bandwidth



■ PCS MODE (661 CH.) Peak-to-Average Ratio



■ PCS EDGE MODE (661 CH.) Peak-to-Average Ratio



■ WCDMA1900 MODE (9262 CH.) Occupied Bandwidth



■ WCDMA1900 MODE (9400 CH.) Occupied Bandwidth



■ WCDMA1900 MODE (9538 CH.) Occupied Bandwidth



■ WCDMA1900 MODE (9400 CH.) Peak-to-Average Ratio



■ GSM850 MODE (128 CH.) Block Edge



■ GSM850 MODE (251 CH.) Block Edge



■ EDGE MODE (128 CH.) Block Edge



■ EDGE MODE (251 CH.) Block Edge



■ GSM1900 MODE (512 CH.) Block Edge



■ GSM1900 MODE (810 CH.) Block Edge



■ EDGE MODE (512 CH.) Block Edge



■ EDGE MODE (810 CH.) Block Edge



■ WCDMA1900 MODE (9262 CH.) Block Edge



■ WCDMA1900 MODE (9538 CH.) Block Edge



■ WCDMA1900 MODE (9262 CH.) – 4 MHz Span



■ WCDMA1900 MODE (9538 CH.) – 4 MHz Span



■ GSM850 MODE (128 CH.) Conducted Spurious Emissions1



■ GSM850 MODE (128 CH.) Conducted Spurious Emissions2



■ GSM850 MODE (190 CH.) Conducted Spurious Emissions1



■ GSM850 MODE (190 CH.) Conducted Spurious Emissions2



■ GSM850 MODE (251 CH.) Conducted Spurious Emissions1



■ GSM850 MODE (251 CH.) Conducted Spurious Emissions2



■ GSM1900 MODE (512 CH.) Conducted Spurious Emissions1



■ GSM1900 MODE (512 CH.) Conducted Spurious Emissions2



■ GSM1900 MODE (661 CH.) Conducted Spurious Emissions1



■ GSM1900 MODE (661 CH.) Conducted Spurious Emissions2



■ GSM1900 MODE (810 CH.) Conducted Spurious Emissions1



■ GSM1900 MODE (810 CH.) Conducted Spurious Emissions2



■ WCDMA1900 MODE (9262 CH.) Conducted Spurious Emissions1



■ WCDMA1900 MODE (9262 CH.) Conducted Spurious Emissions2



■ WCDMA1900 MODE (9400 CH.) Conducted Spurious Emissions1



■ WCDMA1900 MODE (9400 CH.) Conducted Spurious Emissions2



■ WCDMA1900 MODE (9538 CH.) Conducted Spurious Emissions1



■ WCDMA1900 MODE (9538 CH.) Conducted Spurious Emissions2