



HCT CO., LTD.

PRODUCT COMPLIANCE DIVISION
SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI, KYOUNGKI-DO, 467-701, KOREA
TEL : +82 31 639 8539 FAX : +82 31 639 8525 www.hct.co.kr

EMI CERTIFICATION REPORT

LG Electronics Inc.

**60-39, Gasan-dong, Gumchon-gu,
Seoul, 153-023, Korea**

Date of Issue: January 14, 2010

Test Report No.: HCTE1001FE09

Test Site: HCT CO., LTD.

HCT FRN: 0005-8664-21

FCC ID:

BEJLW510

Rule Part(s) / Standard(s) : FCC PART 15 Subpart B / CISPR 22 Class B

Equipment (EUT) Type : Cellular/AWS/PCS CDMA Phone with Bluetooth

Trade Name / Model(s) : LG Electronics Inc. / LW510

Additional Model(s) : MN510, UN510

Port / Connector(s) : USB Data Port / Headset Port

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862.


Report prepared by

: Gyeong Seon Kim

Test Engineer of EMC Tech. Part


Approved by

: Nam Wook Kang

Manager of EMC Tech. Part

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	
1.1 Product description	3
1.2 Related submittal(s)/Grant(s)	3
1.3 Tested system details	4
1.4 Cable description	4
1.5 Noise suppression parts on cable. (I/O cable)	4
1.6 Test methodology	5
1.7 Test facility	5
2. SYSTEM TEST CONFIGURATION	
2.1 Configuration of tested system	6
3. PRELIMINARY TEST	
3.1 Conducted Emission test	7
3.2 Radiated Emission test	7
4. CONDUCTED AND RADIATED EMISSION TESTS SUMMARY	
4.1 Conducted Emission test	8
4.2 Radiated Emission test	13
5. FIELD STRENGTH CALCULATION	14
6. TEST EQUIPMENT	15
7. CONCLUSION	16

ATTACHMENT : TEST SETUP PHOTOGRAPHS

1. GENERAL INFORMATION

1.1 Product Description

The **LG Electronics Inc. Model: LW510, Cellular/AWS/PCS CDMA Phone with Bluetooth.**

Its basic purpose is used for communications. It transmits from CDMA 850 (824.70 MHz to 848.31 MHz), CDMA 1 900 (1 850.00 MHz to 1 910. 20 MHz) AWS CDMA (1 711.25 MHz to 1 753.75 MHz) and receives from CDMA 850 (869.70 MHz to 893.31 MHz) CDMA 1 900 (1 930.00 MHz to 1 990.00 MHz), AWS CDMA (2 111.25 MHz to 2 153.75 MHz).

Model	LW510
Additional Model	MN510, UN510
FCC ID	BEJLW510
E.U.T Type	Cellular/AWS/PCS CDMA Phone with Bluetooth
TX Frequency	824.70 MHz to 848.31 MHz (CDMA 850) 1 850.00 MHz to 1 910. 20 MHz (CDMA 1 900) 1 711.25 MHz to 1 753.75 MHz (AWS CDMA)
RX Frequency	869.70 MHz to 893.31 MHz (CDMA 850) 1 930.00 MHz to 1 990.00 MHz (CDMA 1 900) 2 111.25 MHz to 2 153.75 MHz (AWS CDMA)

1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Manufacturer	Model Number/ Part Number	FCC ID / DoC	Connected To
Cellular/AWS/PCS CDMA Phone with Bluetooth	LG	LW510	BEJLW510	Notebook PC
Notebook PC	Sam-Sung	NT-R519	DoC	E.U.T
Notebook PC adaptor	DELTA	ADP-60ZH D AD-6019R	-	Notebook PC
Mouse	Microsoft	Intellimouse optical USB and PS/2 compatible	DoC	Notebook PC
USB cable	-	-	-	E.U.T Notebook PC
Headset	-	-	-	E.U.T

1.4 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (M)
Cellular/AWS/PCS CDMA Phone with Bluetooth	Headset jack	-	-	(D)1.2
	USB data	Y	Y	(P,D)1.2
Notebook PC	USB (Mouse)	-	Y	(D)1.8

* The marked "(D)" means the data cable and "(P)" means the power cable.

1.5 Noise Suppression Parts on Cable. (I/O cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
Cellular/AWS/PCS CDMA Phone with Bluetooth	Headset jack	N	-	Y	E.U.T End
	USB data	N	-	Y	Both End
Notebook PC	USB (Mouse)	Y	Notebook PC End	Y	Notebook PC End

1.6 Test Methodology

Both Conducted and Radiated testing was performed according to the procedures in ANSI C63.4/2003. Radiated testing was performed at an antenna to E.U.T distance of 3 m

1.7 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, Maekok-ri, Hobup-myun, Ichon-si, Kyoungki-do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated June 10, 2009. (Registration Number: 90661)

1.8 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower


2. SYSTEM TEST CONFIGURATION

2.1 Configuration of Test System

Power Line Conducted test : E.U.T was connected to LISN, all other peripheral equipment were connected to another LISN. Preliminary Power Line Conducted Emission tests were performed by using the procedure in ANSI C63.4/2003 7.2.3 to determine the worst operating conditions.

Radiated Emission test : Preliminary Radiated Emission tests were performed by using the procedure in ANSI C63.4/2003 8.3.1.1 to determine the worst operating condition. Final Radiated Emission tests were performed at 3 m open area test site.

[Configuration of Tested System]



Power Line: 110 VAC

3. PRELIMINARY TEST

3.1 Conducted Emission Test

During preliminary tests, the following operating mode was investigated:

Operation Mode	The Worst Operating Condition
Data Communication	○

3. 2 Radiated Emission Test

During preliminary tests, the following operating mode was investigated:

Operation Mode	The Worst Operating Condition
Data Communication	○

4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The following table shows the highest levels of conducted emissions on both polarization of hot and neutral line.

Limit apply to	: CISPR 22 Class B
Result	: Passed by 7.1 dB
Operating condition	: Data Communication mode
Detector	: Quasi-Peak, Average (6 dB Bandwidth: 9 kHz)
Temperature	: 20.8 °C
Humidity level	: 38.7 %
Test date	: January 13, 2010

Power Line Conducted Emissions			CISPR 22 Class B		
Frequency (MHz)	Amplitude (dB μ V)	Conductor	Result	Limit (dB μ V)	Margin (dB)
0.5400	32.7	NEUTRAL	Average	46.0	13.3
0.5400	47.3	NEUTRAL	Quasi-Peak	56.0	8.7
0.6520	38.9	HOT	Average	46.0	7.1
0.6520	48.5	HOT	Quasi-Peak	56.0	7.5

※ **NOTE:** Refer to page 9 to page 12 for details.

1. All modes of operation were investigated, and the worst-case emissions are reported.
2. Line H = Hot, Line N = Neutral


HCT

EMC TEST LAB.

EUT : LW510
Manufacturer : LG
Operating Condition : DATA COMMUNICATION MODE
Test Site : SHIELD ROOM
Operator : GS KIM
Test Specification : CISPR 22 CLASS B
Comment : H

SCAN TABLE: "EN 55022 CLASS B"

Short Description: EN 55022 Voltage
Start Stop Step Detector Meas. IF Transducer
Frequency Frequency Width Time Bandw.
150.0 kHz 500.0 kHz 5.0 kHz MaxPeak 10.0 ms 9 kHz None
Average
500.0 kHz 30.0 MHz 3.0 kHz MaxPeak 10.0 ms 9 kHz None
Average



MEASUREMENT RESULT: "PHONE_fin_QP"

2010-01-13 7:41

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150001	52.10	10.1	66	13.9	---	---
0.492501	43.60	10.2	56	12.6	---	---
0.500000	45.30	10.2	56	10.7	---	---
0.632000	47.50	10.2	56	8.5	---	---
0.652000	48.50	10.2	56	7.5	---	---
0.676000	41.20	10.2	56	14.8	---	---
19.120001	23.70	12.4	60	36.3	---	---
19.136001	23.60	12.4	60	36.4	---	---
19.148001	23.80	12.4	60	36.2	---	---

2010-01-13 7:42 HCT EMC LAB

MEASUREMENT RESULT: "PHONE_fin AV"

2010-01-13 7:41

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150001	37.70	10.1	56	18.3	---	---
0.485001	25.40	10.2	46	20.9	---	---
0.495001	31.80	10.2	46	14.3	---	---
0.624000	35.10	10.2	46	10.9	---	---
0.640000	35.40	10.2	46	10.6	---	---
0.652000	38.90	10.2	46	7.1	---	---
19.120001	15.40	12.4	50	34.6	---	---
19.136001	15.30	12.4	50	34.7	---	---
19.144001	15.30	12.4	50	34.7	---	---

2010-01-13 7:42 HCT EMC LAB


HCT

EMC TEST LAB.

EUT : LW510
Manufacturer : LG
Operating Condition : DATA COMMUNICATION MODE
Test Site : SHIELD ROOM
Operator : GS KIM
Test Specification : CISPR 22 CLASS B
Comment : N

SCAN TABLE: "EN 55022 CLASS B"

Short Description: EN 55022 Voltage
Start Stop Step Detector Meas. IF Transducer
Frequency Frequency Width Time Bandw.
150.0 kHz 500.0 kHz 5.0 kHz MaxPeak 10.0 ms 9 kHz None
Average
500.0 kHz 30.0 MHz 3.0 kHz MaxPeak 10.0 ms 9 kHz None
Average



MEASUREMENT RESULT: "PHONE_fin QP"

2010-01-13 7:36

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150001	54.40	10.1	66	11.6	---	---
0.472501	41.60	10.2	57	14.9	---	---
0.495001	39.50	10.2	56	16.6	---	---
0.540000	47.30	10.2	56	8.7	---	---
0.636000	45.60	10.2	56	10.4	---	---
0.680000	44.40	10.2	56	11.6	---	---
9.336001	33.90	11.1	60	26.1	---	---
9.564001	34.50	11.2	60	25.5	---	---
9.764001	34.20	11.2	60	25.8	---	---

2010-01-13 7:37 HCT EMC LAB

MEASUREMENT RESULT: "PHONE_fin AV"

2010-01-13 7:36

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150001	40.30	10.1	56	15.7	---	---
0.445001	28.80	10.1	47	18.1	---	---
0.462501	30.90	10.2	47	15.8	---	---
0.540000	32.70	10.2	46	13.3	---	---
0.580000	29.70	10.2	46	16.3	---	---
0.596000	32.70	10.2	46	13.3	---	---
9.568001	23.50	11.2	50	26.5	---	---
9.752001	23.80	11.2	50	26.2	---	---
9.824001	23.60	11.2	50	26.4	---	---

2010-01-13 7:37 HCT EMC LAB

4.2 Radiated Emission Test

The following table shows the highest levels of Radiated Emissions on both polarization of horizontal and vertical.

Limit apply to	: FCC PART 15 Subpart B
Result	: Passed by 8.8 dB
Operating condition	: Data Communication mode
Detector	: Quasi-Peak (6 dB Bandwidth: 120 kHz)
Temperature	: 10.0 °C
Humidity level	: 60.5 %
Test date	: January 13, 2010

Frequency	Reading	Ant. Factor	Cable Loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB/m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
220.1	18.0	10.5	1.6	H	30.1	46.0	15.9
233.1	16.7	10.9	1.6	H	29.2	46.0	16.8
474.2	15.9	16.9	2.4	H	35.2	46.0	10.8
485.9	17.7	17.1	2.4	H	37.2	46.0	8.8
497.5	14.6	17.2	2.4	H	34.2	46.0	11.8
507.1	12.3	17.4	2.5	V	32.2	46.0	13.8

5. FIELD STRENGTH CALCULATION

The field strength is calculated by adding the antenna factor and cable factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

Assume a receiver reading of 21.5 dB μ V is obtained. The antenna factor of 7.4 dB/m and a cable factor of 1.1 dB are added. The 30 dB μ V/m value is mathematically converted to its corresponding level in μ V/m.

$$FS = 21.5 + 7.4 + 1.1 = 30 \text{ dB}\mu\text{V/m}$$

[Radiated Emission Limits]

Frequency of Emission (MHz)	Field Strength	
	μ V/m	dB μ V/m
30 to 88	100	40.0
88 to 216	150	43.5
216 to 960	200	46.0
Above 960	500	54.0

6. TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Number</u>	<u>Next CAL Date</u>
<u>Conducted Emission</u>			
☒ EMI Test Receiver	Rohde & Schwarz	ESCI	2010.06.02
☒ LISN	Rohde & Schwarz	ESH3-Z5	2010.02.06
☐ LISN	Rohde & Schwarz	ENV216	2010.04.01
☒ Attenuator	Rohde & Schwarz	ESH3-Z2	2010.10.30
<u>Radiated Emission</u>			
☒ EMI Test Receiver	Rohde & Schwarz	ESI40	2010.10.30
☒ Trilog Antenna	Schwarzbeck	VULB9160	2010.12.18
☒ Antenna Master	HD	MA240	-
☒ Turn Table	EMCO	1060	-
☐ Communication Antenna	TDK	LPDA-0802	-
☐ Antenna Position Tower	HD	240/520/00	-
☐ Base Station	Rohde & Schwarz	CMU 200	2010.02.17
☒ Horn Antenna	Schwarzbeck	BBHA 9120D	2010.03.26
☒ RF-Amplifier	MITEQ	AMF-6D-00101800-35. 20P.PS	2010.04.25
☐ Bluetooth Base Station	TESCOM	TC-3000A	2011.01.07

7. CONCLUSION

The data collected shows that the **LG Electronics Inc. Model: LW510. Cellular/AWS/PCS CDMA Phone with Bluetooth. FCC ID: BEJLW510** complies with §15.107 and §15.109 of the FCC rules.